



Center for  
Internet Security®

# CIS Google Chrome Benchmark

v1.1.0 - 03-15-2016

This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International Public License. The link to the license terms can be found at <https://creativecommons.org/licenses/by-nc-sa/4.0/legalcode>

To further clarify the Creative Commons license related to CIS Benchmark content, you are authorized to copy and redistribute the content for use by you, within your organization and outside your organization for non-commercial purposes only, provided that (i) appropriate credit is given to CIS, (ii) a link to the license is provided. Additionally, if you remix, transform or build upon the CIS Benchmark(s), you may only distribute the modified materials if they are subject to the same license terms as the original Benchmark license and your derivative will no longer be a CIS Benchmark. Commercial use of CIS Benchmarks is subject to the prior approval of the Center for Internet Security.

DRAFT

# Table of Contents

Overview .....	4
Intended Audience .....	4
Consensus Guidance.....	4
Typographical Conventions .....	5
Scoring Information .....	5
Profile Definitions .....	6
Acknowledgements .....	7
Recommendations .....	8
1 Computer Configuration .....	8
1.1 Google Chrome .....	8
1.1.1 (L1) Ensure 'Allow invocation of file selection dialog' is set to 'Enabled' (Scored) .....	8
1.1.2 (L1) Ensure 'Enable alternate error pages' is set to 'Disabled' (Scored) .....	10
1.1.3 (L1) Ensure 'Enable AutoFill' is set to 'Disabled' (Scored) .....	11
1.1.4 (L1) Ensure 'Continue running background apps when Google Chrome is closed' is set to 'Disabled' (Scored) .....	12
1.1.5 (L1) Ensure 'Block third party cookies' is set to 'Enabled' (Scored) .....	13
1.1.6 (L1) Ensure 'Allow running plugins that are outdated' is set to 'Disabled' (Scored) .....	14
1.1.7 (L1) Ensure 'Always runs plugins that require authorization' is set to 'Disabled' (Scored) .....	15
1.1.8 (L1) Ensure 'Specify whether the plugin finder should be disabled' is set to 'Enabled' (Scored) .....	16
1.1.9 (L1) Ensure 'Enable Google Cloud Print Proxy' is set to 'Disabled' (Scored) ....	17
1.1.10 (L1) Ensure 'Enable submission of documents to Google Cloud print' is set to 'Disabled' (Scored) .....	18
1.1.11 (L1) Ensure 'Specify a list of Disabled Plugins' is set to 'Enabled' (Scored) ...	19
1.1.12 (L1) Ensure 'Import saved passwords from default browser on first run' is set to 'Disabled' (Scored) .....	21
1.1.13 (L1) Ensure 'Enable reporting of usage and crash-related data' is set to 'Disabled' (Scored) .....	23

1.2 Allow Google Chrome Frame to Handle the Following Content Types .....	24
1.3 Configure Remote Access Options.....	25
1.3.1 (L1) Ensure 'Enable firewall traversal from remote access host' is set to 'Disabled' (Scored) .....	25
1.3.2 (L1) Ensure 'Configure the required domain name for remote access hosts' is set to 'Enabled' (Scored) .....	27
1.3.3 (L1) Ensure 'Enable or disable PIN-less authentication' is set to 'Disabled' (Scored) .....	28
1.3.4 (L1) Ensure 'Enable curtaining of remote access hosts' is set to 'Enabled' (Scored) .....	29
1.4 Content Settings.....	30
1.4.1 (L2) Ensure 'Default cookies setting' is set to 'Enabled (Keep cookies for the duration of the session)' (Scored).....	30
1.4.2 (L1) Ensure 'Default Plugin Setting' is set to 'Enabled' (Scored).....	31
1.5 Default HTML Renderer for Google Chrome Frame .....	32
1.6 Default Search Provider.....	32
1.7 Extensions.....	33
1.7.1 (L1) Ensure 'Configure Extension Installation Blacklist' is set to 'Enabled ("*" for all extensions)' (Scored) .....	33
1.8 Home Page .....	35
1.9 Locally Managed Users Settings .....	35
1.10 Native Messaging.....	35
1.11 Password Manager.....	36
1.11.1 (L1) Ensure 'Enable the password manager' is set to 'Disabled' (Scored).....	36
1.11.2 (L1) Ensure 'Allow users to show passwords in Password Manager' is set to 'Disabled' (Scored) .....	38
1.12 Policies for HTTP Authentication.....	39
1.13 Proxy Server .....	39
1.14 Startup Pages.....	39
Appendix: Change History .....	42

# Overview

This document provides prescriptive guidance for establishing a secure configuration posture for Google Chrome Browser. This guide was tested against Google Chrome v49.0.2623.87m. To obtain the latest version of this guide, please visit <http://benchmarks.cisecurity.org>. If you have questions, comments, or have identified ways to improve this guide, please write us at [feedback@cisecurity.org](mailto:feedback@cisecurity.org).

## Intended Audience

This document is intended for system and application administrators, security specialists, auditors, help desk, and platform deployment personnel who plan to develop, deploy, assess, or secure solutions that incorporate Google Chrome.

## Consensus Guidance

This benchmark was created using a consensus review process comprised of subject matter experts. Consensus participants provide perspective from a diverse set of backgrounds including consulting, software development, audit and compliance, security research, operations, government, and legal.

Each CIS benchmark undergoes two phases of consensus review. The first phase occurs during initial benchmark development. During this phase, subject matter experts convene to discuss, create, and test working drafts of the benchmark. This discussion occurs until consensus has been reached on benchmark recommendations. The second phase begins after the benchmark has been published. During this phase, all feedback provided by the Internet community is reviewed by the consensus team for incorporation in the benchmark. If you are interested in participating in the consensus process, please visit <https://community.cisecurity.org>.

## Typographical Conventions

The following typographical conventions are used throughout this guide:

Convention	Meaning
<code>Stylized Monospace font</code>	Used for blocks of code, command, and script examples. Text should be interpreted exactly as presented.
Monospace font	Used for inline code, commands, or examples. Text should be interpreted exactly as presented.
< <i>italic font in brackets</i> >	Italic texts set in angle brackets denote a variable requiring substitution for a real value.
<i>Italic font</i>	Used to denote the title of a book, article, or other publication.
<b>Note</b>	Additional information or caveats

## Scoring Information

A scoring status indicates whether compliance with the given recommendation impacts the assessed target's benchmark score. The following scoring statuses are used in this benchmark:

### Scored

Failure to comply with "Scored" recommendations will decrease the final benchmark score. Compliance with "Scored" recommendations will increase the final benchmark score.

### Not Scored

Failure to comply with "Not Scored" recommendations will not decrease the final benchmark score. Compliance with "Not Scored" recommendations will not increase the final benchmark score.

## Profile Definitions

The following configuration profiles are defined by this Benchmark:

- **Level 1**

Items in this profile intend to:

- be practical and prudent;
- provide a clear security benefit; and
- not inhibit the utility of the technology beyond acceptable means.

- **Level 2**

This profile extends the "Level 1" profile. Items in this profile exhibit one or more of the following characteristics:

- are intended for environments or use cases where security is paramount
- acts as defense in depth measure
- may negatively inhibit the utility or performance of the technology

## Acknowledgements

This benchmark exemplifies the great things a community of users, vendors, and subject matter experts can accomplish through consensus collaboration. The CIS community thanks the entire consensus team with special recognition to the following individuals who contributed greatly to the creation of this guide:

### **Contributor**

Vilius Benetis

### **Editor**

Edward Oechsner

Jordan Rakoske

DRAFT



# Recommendations

## 1 Computer Configuration

The following structure of this guide mirrors how it is structured in the Google Chrome Group Policy template.

### 1.1 Google Chrome

This section contains recommendations for Google Chrome.

#### 1.1.1 (L1) Ensure 'Allow invocation of file selection dialog' is set to 'Enabled' (Scored)

##### Profile Applicability:

- Level 1

##### Description:

Chrome allows users to access files located on the local machine. By enabling this setting the user is prompted with a dialog box before the local file is accessed.

The recommended state for this setting is: Enabled

##### Rationale:

Prompting a dialog box before local file access prevents malicious links or websites from accessing local files without the user first consenting.

##### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:AllowFileSelectionDialogs
--

##### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Enabled.

Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Allow invocation of file selection dialogs

**Impact:**

If you enable this setting, users can open file selection dialogs as normal.

**Default Value:**

Not Configured

DRAFT

### 1.1.2 (L1) Ensure 'Enable alternate error pages' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome enables the user to change the error pages that are built into Google Chrome. By disabling this feature the user is not able to change the error page to an alternate one.

The recommended state for this setting is: Disabled

#### Rationale:

Alternate error pages can be used to redirect users to custom websites that contain malicious links.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:AlternateErrorPagesEnabled
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Enable alternate error pages
```

#### Impact:

If you disable this setting, alternate error pages are never used.

#### Default Value:

Not Configured

### 1.1.3 (L1) Ensure 'Enable AutoFill' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome allows users to auto-complete web forms with saved information such as address, phone number and credit card numbers. Disabling this feature will prompt a user to enter all information manually.

The recommended state for this setting is: Disabled

#### Rationale:

If an attacker gains access to a user's machine where the user has stored auto save data, information could be harvested or used to gain access to more systems.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:AutoFillEnabled
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Enable AutoFill
```

#### Impact:

If you disable this setting, AutoFill will be inaccessible to users.

#### Default Value:

Not Configured

### 1.1.4 (L1) Ensure 'Continue running background apps when Google Chrome is closed' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome allows for processes started while the browser is open to remain running once the browser has been closed. It also allows for background apps and the current browsing session to remain active after the browser has been closed. Disabling this feature will stop all processes and background applications when the browser window is closed.

The recommended state for this setting is: Disabled

#### Rationale:

If this setting is enabled, vulnerable or malicious plugins, apps and processes can continue running even after Chrome has closed.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:BackgroundModeEnabled
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Continue running background apps when Google Chrome is closed
```

#### Impact:

If this policy is set to Disabled, background mode is disabled and cannot be controlled by the user in the browser settings.

#### Default Value:

Not Configured

### 1.1.5 (L1) Ensure 'Block third party cookies' is set to 'Enabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome allows cookies to be set by web page elements that are not from the domain in the user's address bar. Enabling this feature prevents the cookies from being set.

The recommended state for this setting is: Enabled

#### Rationale:

Blocking third party cookies can help protect a user's privacy by eliminating a number of website tracking cookies.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome\BlockThirdPartyCookies
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Enabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Block third party cookies
```

#### Impact:

Enabling this setting prevents cookies from being set by web page elements that are not from the domain that is in the browser's address bar.

#### Default Value:

Not Configured

### 1.1.6 (L1) Ensure 'Allow running plugins that are outdated' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome enables the use of outdated plugins. By disabling this feature Chrome will not prompt the user to use an outdated plugin.

The recommended state for this setting is: Enabled

#### Rationale:

Running the most up-to-date version of a plugin can reduce the possibility of running a plugin that contains an exploit or security hole.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:AllowOutdatedPlugins
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Allow running plugins that are outdated
```

#### Impact:

If you disable this setting, outdated plugins will not be used and users will not be asked for permission to run them.

#### Default Value:

Not Configured

### 1.1.7 (L1) Ensure 'Always runs plugins that require authorization' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome allows plugins that are not outdated to run automatically. Disabling this setting allows the plugins to run only when permission is granted by the user.

The recommended state for this setting is: Disabled

#### Rationale:

Disabling plugins from automatically running can prevent unwanted and/or harmful plugins from running without the user's consent, preventing unauthorized data/remote access.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:AlwaysAuthorizePlugins
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Always runs plugins that require authorization
```

#### Impact:

If this setting is disabled or not set, users will be asked for permission to run plugins that require authorization. These are plugins that can compromise security.

#### Default Value:

Not Configured



### *1.1.8 (L1) Ensure 'Specify whether the plugin finder should be disabled' is set to 'Enabled' (Scored)*

#### **Profile Applicability:**

- Level 1

#### **Description:**

Chrome allows for the automatic search and installation of missing plugins. Disabling this feature will stop plugins from being downloaded and installed without the users knowledge.

The recommended state for this setting is: Enabled

#### **Rationale:**

Disabling the feature that allows plugins to automatically be installed prevents plugins that may have vulnerabilities or be against company policy from being introduced to the computer without anyone's knowledge.

#### **Audit:**

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:DisablePluginFinder
```

#### **Remediation:**

To establish the recommended configuration via Group Policy, set the following UI path to Enabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Specify whether the plugin finder should be disabled
```

#### **Impact:**

If you set this setting to enabled the automatic search and installation of missing plugins will be disabled in Google Chrome.

#### **Default Value:**

Not Configured

### 1.1.9 (L1) Ensure 'Enable Google Cloud Print Proxy' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

This setting enables Google Chrome to act as a proxy between Google Cloud Print and legacy printers connected to the machine.

The recommended state for this setting is: Disabled

#### Rationale:

Disabling this option will prevent users from printing possible confidential enterprise documents through the cloud.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:CloudPrintProxyEnabled
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Enable Google Cloud Print Proxy
```

#### Impact:

If this setting is disabled, users cannot enable the proxy, and the machine will not be allowed to share its printers with Google Cloud Print.

#### Default Value:

Not Configured

### *1.1.10 (L1) Ensure 'Enable submission of documents to Google Cloud print' is set to 'Disabled' (Scored)*

#### **Profile Applicability:**

- Level 1

#### **Description:**

This setting enables Google Chrome to submit documents to Google Cloud Print for printing. NOTE: This only affects Google Cloud Print support in Google Chrome. It does not prevent users from submitting print jobs on web sites.

The recommended state for this setting is: Disabled

#### **Rationale:**

Disabling this option will prevent users from printing possible confidential enterprise documents through the cloud.

#### **Audit:**

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:CloudPrintSubmitEnabled
```

#### **Remediation:**

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Enable submission of documents to Google Cloud print
```

#### **Impact:**

If this setting is disabled, users cannot print to Google Cloud Print from the Chromium print dialog

#### **Default Value:**

Not Configured

### 1.1.11 (L1) Ensure 'Specify a list of Disabled Plugins' is set to 'Enabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

This setting specifies a list of plugins that are disabled in Google Chrome and prevents users from changing this setting. The Recommended state is to block all plugins except what is listed in the enabled plugins list. It is up to each organization to determine which plugins they want to add to the enabled plugins list.

The recommended state for this setting is: Enabled

Note: this policy can be overridden by EnabledPlugins and DisabledPluginsExceptions settings.

#### Rationale:

Disabling all plugins will help prevent the installation of applications like Remote Desktop and other tools that could all remote access to the machine.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:DisabledPlugins
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Enabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Specify a list of Disabled Plugins
```

#### Impact:

If you enable this setting, the specified list of plugins is never used in Google Chrome. The plugins are marked as disabled in 'about:plugins' and users cannot enable them.

**Default Value:**

Not Configured

DRAFT

### *1.1.12 (L1) Ensure 'Import saved passwords from default browser on first run' is set to 'Disabled' (Scored)*

#### **Profile Applicability:**

- Level 1

#### **Description:**

This setting controls if saved passwords from the default browser can be imported.

The recommended state for this setting is: Disabled

#### **Rationale:**

In Chrome, passwords can be stored in plain-text and revealed by clicking the “show” button next to the password field by going to `chrome://settings/passwords/`.

If this setting is enabled, an attacker with access to a user’s machine with passwords stored that have been imported from another browser, credentials can be viewed in clear text and used to gain additional access.

#### **Audit:**

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:ImportSavedPasswords
```

#### **Remediation:**

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Import saved passwords from default browser on first run
```

#### **Impact:**

If disabled, the saved passwords are not imported.

**Default Value:**

Not Configured

DRAFT

### 1.1.13 (L1) Ensure 'Enable reporting of usage and crash-related data' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

This Setting controls anonymous reporting of usage and crash-related data about Google Chrome to Google.

The recommended state for this setting is: Disabled

#### Rationale:

Anonymous crash/usage data can be used to identify people, companies and information, and can be considered data exfiltration from company systems.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:MetricsReportingEnabled
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Enable reporting of usage and crash-related data
```

#### Impact:

If it is disabled, this information is not sent to Google.

#### Default Value:

Not Configured



## ***1.2 Allow Google Chrome Frame to Handle the Following Content Types***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

DRAFT

## 1.3 Configure Remote Access Options

This section contains recommendations for Configuring Remote Access Options

### 1.3.1 (L1) Ensure 'Enable firewall traversal from remote access host' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome enables the usage of STUN servers which allows remote clients to discover and connect to a machine even if they are separated by a firewall. By disabling this feature, in conjunction with filtering outgoing UDP connections, the machine will only allow connections from machines within the local network.

The recommended state for this setting is: Disabled

#### Rationale:

If this setting is enabled, then remote clients can discover and connect to this machines even if they are separated by a firewall.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:RemoteAccessHostFirewallTraversal
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Configure remote access options\Enable firewall traversal from remote access host
```

#### Impact:

If this setting is disabled and outgoing UDP connections are filtered by the firewall, then this machine will only allow connections from client machines within the local network.

**Default Value:**

Not Configured

DRAFT

### 1.3.2 (L1) Ensure 'Configure the required domain name for remote access hosts' is set to 'Enabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome allows the user to configure a required host domain that is imposed on remote access hosts. When enabled, hosts can only be shared using accounts that are registered to the specified domain.

The recommended state for this setting is: `Enabled`

#### Rationale:

If this setting is disabled or not set, then hosts can be shared using any account.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:RemoteAccessHostDomain
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to `Enabled` and enter domain.

```
Computer Configuration\Administrative Templates\Classic Administrative Templates (ADM)\Google\Google Chrome\Configure remote access options\Configure the required domain name for remote access hosts
```

#### Impact:

If this setting is enabled, then hosts can be shared only using accounts registered on the specified domain name.

#### Default Value:

Not Configured

### 1.3.3 (L1) Ensure 'Enable or disable PIN-less authentication' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome enables a user to opt-out of using user-specified PIN authentication and instead pair clients and hosts during connection time.

The recommended state for this setting is: Disabled

#### Rationale:

If this setting is enabled or not configured, then users can opt to pair clients and hosts at connection time, eliminating the need to enter a PIN every time.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:RemoteAccessHostAllowClientPairing
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Templates (ADM)\Google\Google Chrome\Configure remote access options\Enable or disable PIN-less authentication
```

#### Impact:

If this setting is disabled, then this feature will not be available.

#### Default Value:

Not Configured

### 1.3.4 (L1) Ensure 'Enable curtaining of remote access hosts' is set to 'Enabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome allows the user to disable a remote user's physical input and output while the remote connection is in progress.

The recommended state for this setting is: Enabled

#### Rationale:

If this setting is disabled or not set, then both local and remote users can interact with the host when it is being shared.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:RemoteAccessHostRequireCurtain
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Enabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Templates (ADM)\Google\Google Chrome\Configure remote access options\Enable curtaining of remote access hosts
```

#### Impact:

If this setting is enabled, then hosts' physical input and output devices are disabled while a remote connection is in progress.

#### Default Value:

Not Configured

## 1.4 Content Settings

This section contains recommendations for Content Settings

### 1.4.1 (L2) Ensure 'Default cookies setting' is set to 'Enabled (Keep cookies for the duration of the session)' (Scored)

#### Profile Applicability:

- Level 2

#### Description:

Allows you to set whether websites are allowed to set local data. Setting local data can be either allowed for all websites or denied for all websites.

The recommended state for this setting is: Enabled (Keep cookies for the duration of the session)

#### Rationale:

If this policy is left not set, 'AllowCookies' will be used and the user will be able to change it.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:DefaultCookiesSetting
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Enabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Content Settings\Default cookies setting
```

#### Impact:

If this policy is set to 'Keep cookies for the duration of the session' then cookies will be cleared when the session closes.

#### Default Value:

Not Configured

### 1.4.2 (L1) Ensure 'Default Plugin Setting' is set to 'Enabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Allows you to set whether websites are allowed to automatically run plugins. Automatically running plugins can be either allowed for all websites or denied for all websites.

The recommended state for this setting is: Enabled

#### Rationale:

Malicious plugins can cause browser instability and erratic behavior so setting the value to click to play will allow a user to only run necessary plugins.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:DefaultPluginsSetting
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Enabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Content Settings\Default Plugins Setting
```

#### Impact:

Click to play allows plugins to run but the user must click them to start their execution.

#### Default Value:

Not Configured



## ***1.5 Default HTML Renderer for Google Chrome Frame***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

## ***1.6 Default Search Provider***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

DRAFT

## 1.7 Extensions

This section contains recommendations for Extensions

### 1.7.1 (L1) Ensure 'Configure Extension Installation Blacklist' is set to 'Enabled ("\*" for all extensions)' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Enabling this setting allows you to specify which extensions the users can NOT install. Extensions already installed will be removed if blacklisted. The recommendation is: Enabled with a value of \* (for all extensions)

The recommended state for this setting is: Enabled ("\*" for all extensions)

#### Rationale:

This will block any extension that could allow remote control of the system through the browser. If there are extensions needed for securing the browser or for enterprise use these can be enabled by configuring the extension whitelist.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome\ExtensionInstallBlacklist\1
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Enabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Extensions\Configure Extension Installation Blacklist
```

#### Impact:

Any installed extension will be removed unless it is specified on the extension whitelist.

**Default Value:**

Not Configured

DRAFT

## ***1.8 Home Page***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

## ***1.9 Locally Managed Users Settings***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

## ***1.10 Native Messaging***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

DRAFT

## 1.11 Password Manager

This section contains recommendations for Password Manager

### 1.11.1 (L1) Ensure 'Enable the password manager' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome will memorize passwords and automatically provide them when a user logs into a site. By disabling this feature, the user will be prompted to enter their password each time they visit a website.

The recommended state for this setting is: Disabled

#### Rationale:

If you enable this setting, users can have Google Chrome memorize passwords and provide them automatically the next time they log in to a site. An intruder who has unrestricted access to your computer for even a minute can view and copy all of your saved passwords by running programs freely downloadable from Internet, like NirSoft's WebBrowserPassView.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:PasswordManagerEnabled
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Password manager\Enable the password manager
```

**Impact:**

If you disable this setting, users are not able to save passwords or use already saved passwords.

**Default Value:**

Not Configured

DRAFT

### 1.11.2 (L1) Ensure 'Allow users to show passwords in Password Manager' is set to 'Disabled' (Scored)

#### Profile Applicability:

- Level 1

#### Description:

Chrome will memorize passwords and save them in a feature called the Password Manager. Chrome allows users to view the saved passwords in clear text via the Password Manager feature. By disabling this feature, the user will not be able to view the passwords in clear text.

The recommended state for this setting is: Disabled

#### Rationale:

If you enable or do not set this policy, users can view their passwords in clear text in the password manager.

#### Audit:

Navigate to the UI Path articulated in the Remediation section and confirm it is set as prescribed. This group policy setting is backed by the following registry location:

```
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Google\Chrome:PasswordManagerAllowShowPasswords
```

#### Remediation:

To establish the recommended configuration via Group Policy, set the following UI path to Disabled.

```
Computer Configuration\Administrative Templates\Classic Administrative Template (ADM)\Google\Google Chrome\Password manager\Allow users to show passwords in Password Manager
```

#### Impact:

If you disable this setting, the password manager does not allow showing stored passwords in clear text in the password manager window.

#### Default Value:

Not Configured

## ***1.12 Policies for HTTP Authentication***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

## ***1.13 Proxy Server***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

## ***1.14 Startup Pages***

This section is intentionally blank and exists to ensure the structure of the Google Chrome benchmark is consistent in future releases.

DRAFT



Control		Set Correctly	
		Yes	No
<b>1</b>	<b>Computer Configuration</b>		
<b>1.1</b>	<b>Google Chrome</b>		
1.1.1	(L1) Ensure 'Allow invocation of file selection dialog' is set to 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.2	(L1) Ensure 'Enable alternate error pages' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.3	(L1) Ensure 'Enable AutoFill' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.4	(L1) Ensure 'Continue running background apps when Google Chrome is closed' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.5	(L1) Ensure 'Block third party cookies' is set to 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.6	(L1) Ensure 'Allow running plugins that are outdated' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.7	(L1) Ensure 'Always runs plugins that require authorization' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.8	(L1) Ensure 'Specify whether the plugin finder should be disabled' is set to 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.9	(L1) Ensure 'Enable Google Cloud Print Proxy' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.10	(L1) Ensure 'Enable submission of documents to Google Cloud print' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.11	(L1) Ensure 'Specify a list of Disabled Plugins' is set to 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.12	(L1) Ensure 'Import saved passwords from default browser on first run' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.1.13	(L1) Ensure 'Enable reporting of usage and crash-related data' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>1.2</b>	<b>Allow Google Chrome Frame to Handle the Following Content Types</b>		
<b>1.3</b>	<b>Configure Remote Access Options</b>		
1.3.1	(L1) Ensure 'Enable firewall traversal from remote access host' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.2	(L1) Ensure 'Configure the required domain name for remote access hosts' is set to 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.3	(L1) Ensure 'Enable or disable PIN-less authentication' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3.4	(L1) Ensure 'Enable curtaining of remote access hosts' is set to 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>1.4</b>	<b>Content Settings</b>		
1.4.1	(L2) Ensure 'Default cookies setting' is set to 'Enabled (Keep cookies for the duration of the session)' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>

1.4.2	(L1) Ensure 'Default Plugin Setting' is set to 'Enabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>1.5</b>	<b>Default HTML Renderer for Google Chrome Frame</b>		
<b>1.6</b>	<b>Default Search Provider</b>		
<b>1.7</b>	<b>Extensions</b>		
1.7.1	(L1) Ensure 'Configure Extension Installation Blacklist' is set to 'Enabled ("*" for all extensions)' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>1.8</b>	<b>Home Page</b>		
<b>1.9</b>	<b>Locally Managed Users Settings</b>		
<b>1.10</b>	<b>Native Messaging</b>		
<b>1.11</b>	<b>Password Manager</b>		
1.11.1	(L1) Ensure 'Enable the password manager' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.11.2	(L1) Ensure 'Allow users to show passwords in Password Manager' is set to 'Disabled' (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
<b>1.12</b>	<b>Policies for HTTP Authentication</b>		
<b>1.13</b>	<b>Proxy Server</b>		
<b>1.14</b>	<b>Startup Pages</b>		

# Appendix: Change History

Date	Version	Changes for this version
10-30-15	1.0.0	Initial Release
3-15-16	1.1.0	text to update on benchmarks_rule_1.11.1_Set_Enable_the_password_manager_to_Disabled
3-15-16	1.1.0	Removed version from Title
3-15-16	1.1.0	Updated all recommendation titles to include level and new wording.

DRAFT