
My Dishonest Benchmark

How to Manufacture a 100x PostgreSQL Performance Claim



Mayur@Veeam

AGENDA

This is not a “look at my TPS” talk.

The goal: recognize where **benchmarking** ends and **benchmarketing** begins.



INSPIRATION



Average Database CEO @AvgDatabaseCEO · Feb 24

New “spacetime” DB takes shots at @convex @supabase @PlanetScale @CockroachDB @tursodatabase

Compares Convex to using “paper and pencil.”



max @max_kelly · Feb 24


Replying to @RayFernando1337

This is lowkey savage...



MY DISHONEST BENCHMARK

MODERN DAY BENCHMARKING



HISTORY

BENCHMARKING DATABASE SYSTEMS
A SYSTEMATIC APPROACH

Dina Bitton
David J. DeWitt
Carolyn Turbyfill

Computer Sciences Department
University of Wisconsin-Madison


ABSTRACT

This paper describes a customized database and a comprehensive set of queries that can be used for systematic benchmarking of relational database systems. Designing this database and a set of carefully tuned benchmarks represents a first attempt in developing a scientific methodology for performance evaluation of database management systems. We have used this database to perform a comparative evaluation of the "university" and "commercial" versions of the INGRES database system, on one hand, and the IDM 500 database machine, on the other hand. We present a subset of our measurements (for the single user case only), that constitute a preliminary performance evaluation of these systems.

(DAC) [IDM500, EPST80, UBEL81] to the "commercial" and "university" versions of the INGRES database system [STON76, STON80].[2]

Since database machines have already been an active field of research for an entire decade, and a few machines have now been implemented, we feel that the time has come for measuring the actual performance enhancement that can be expected from using special purpose hardware and software for database management. When database machines designs such as CASSM [SU75], RAP [OZKA75, OZKA77], DBC [BANE78], DIRECT [DEWI79] were proposed, the future of database machines looked bright. It seemed that both successful research efforts and advances in hardware technology would lead to the widespread use of commercial database machines. However, while most projects appeared promising initially, it is only very recently

There was one small problem.



In 1983, at the University of Wisconsin, Dina Bitton, David DeWitt, and Carolyn Turbyfill created a database benchmarking framework. included (lower is better):

Join without indices

system	joinAselB	joinABprime	joinCselAselB
U-INGRES	10.2	9.6	9.4
C-INGRES	1.8	2.6	2.1
ORACLE	> 300	> 300	> 300
IDMnodac	> 300	> 300	> 300
IDMdac	> 300	> 300	> 300
DIRECT	10.2	9.5	5.6
SQL/DS	2.2	2.2	2.1

Join with indices, primary (clustered) index

system	joinAselB	joinABprime	joinCselAselB
U-INGRES	2.11	1.66	9.07
C-INGRES	0.9	1.71	1.07
ORACLE	7.94	7.22	13.78
IDMnodac	0.52	0.59	0.74
IDMdac	0.39	0.46	0.58
DIRECT	10.21	9.47	5.62

THE DEWITT CLAUSE

The DeWitt Clause changed the battlefield

1980S

Wisconsin Benchmark

Independent academic DBMS benchmarking

VENDOR PRESSURE

Commercial conflict

Poor results trigger fights

DEWITT CLAUSE

License restriction

Publishing results can require approval

RESULT

Benchmarketing

Loss of academic interest

CONSEQUENCE

The DeWitt Clause helped change who controlled the benchmark narrative

INDEPENDENT RESEARCHERS

Pulled back

Became less willing to publish comparative results

VENDORS

Stepped in

Increasingly published their own benchmark results

The benchmark wars, 40 years later

CLAIM

databricks

Databricks publishes benchmark

2.7× faster

12× better price / performance

100 TB TPC-DS
official TPC submission

REBUTTAL

snowflake

Snowflake responds

> “marketing stunt lacking integrity”

> “not transparent, audited, or reproducible”

argued setup and pricing were misleading

AFTERMATH

The benchmark war continues

- Audited result stayed published
- Vendor counter-claims kept flying
- The fight was about framing, not just speed

Same war, new logos

Database Products That Still Restrict Benchmarks

Product-specific only — not across the full vendor product line, and not community/open-source versions where those exist.

Oracle Database

Commercial database software (including on-premises licenses)

Requires prior written consent to disclose or publish results of any benchmark tests or performance tests.

Oracle License and Services Agreements
Section 8.2.5 | https://www.oracle.com/downloads/licenses

Microsoft SQL Server

Commercial database software (Retail license)

Requires prior written approval to disclose or publish the results of any benchmark tests of the software.

SQL Server 2025 Standard/Enterprise EULA
Section 11 | https://www.microsoft.com/licensing/terms

Redis (Software and Cloud)

Redis commercial software and Redis Cloud (managed service)

Requires prior written approval for benchmark testing, competitive comparisons, or disclosure of benchmark results to third parties.

Redis Software Agreement §2.2(f)
Redis Cloud Agreement §2.2(d)
https://redis.io/legal

MariaDB (Commercial Offerings)

MariaDB SkySQL (cloud), MariaDB Enterprise Server, and MariaDB Xpand

Requires prior written approval to disclose or publish benchmark results to third parties.

MariaDB License Terms
SkySQL §3.5 | Enterprise §6 | Xpand §3
https://mariadb.com/legal

EDB Postgres Advanced Server (EPAS)

Commercial PostgreSQL-compatible database

Restricts EDB competitors from using the software for competitive benchmarking or analysis (except as permitted by law).

EDB End-User License Agreement
Section 2.4(iii) | https://www.enterprisedb.com/legal

What is a DeWitt Embrace Clause?

Open benchmarking, with one catch: the vendor can test you back

01



Benchmark us

You test the vendor's product

02



Show your work

Publish results with full setup details

03



We test you back

The vendor can test your product in return

☑ **Open benchmarking, not a gag order**

⊘ **Not proof that a benchmark is fair**

Vendors with a confirmed DeWitt Embrace Clause

These vendors allow public benchmarking with disclosure and reciprocal benchmarking rights.



AWS

Disclosure + reciprocity

aws.amazon.com



Google Cloud

Disclosure + reciprocity*

cloud.google.com



Microsoft Azure

Competing-customer benchmarking rights

microsoft.com



Databricks

Disclosure + reciprocity

databricks.com



SingleStore

Calls it 'DeWitt Openness'

singlestore.com



CockroachDB Cloud

Disclosure + reciprocity

cockroachlabs.com



PlanetScale

Adopted in 2026

planetscale.com

Important: product- and policy-specific. *Google Cloud still has extra restrictions for hyperscale cloud providers.

BENCHMARK ANARCHY

Six ways to tilt a benchmark favorably towards your database

01

Tune

your own database carefully

02

Default

the comparison database

03

Choose

a workload your architecture loves

04

Ignore

cost + tail latency

05

Ignore

write amplification + crash behavior

06

Publish

the one graph where you win

TRANSPARENCY

A better fight: publish everything



01

CODE

Exact harness + implementation



02

CONFIG

Settings on every system



03

COST

Hardware + spend



04

WORKLOAD

What each side actually did

PostgreSQL has a marketing problem.

No owner. No marketing department. No PR strategy. No launch-day rocket-vs-snail charts.

THE EXPERIMENT

So let us create a heroic graph

100,000+

OPERATIONS / SECOND

by hook or crook

CONSTRAINT

Every reported number comes from a real run.

FREEDOM

I can quietly change what the number means.

REPRODUCTION PACK

Dishonest does not mean unreproducible



01

schema + pgbench workloads



02

reset scripts + cheat variants



03

result collection



04

chart/report generation code



github.com/secp256k1-sha256/talks_and_blogs/tree/main/dishonest_benchmark

Tiny TPC-C-flavoured accounting.

Not TPC-C. Not compliant. Just OLTP-shaped enough to feel familiar.

SCHEMA.SQL

Four tables, seeded with 100 branches and 1M accounts

CORE TABLES

```sql
CREATE TABLE bench_branches (
  branch_id int PRIMARY KEY,
  balance bigint NOT NULL DEFAULT 0
);

CREATE TABLE bench_accounts (
  account_id bigint PRIMARY KEY,
  branch_id int NOT NULL
    REFERENCES bench_branches(branch_id),
  balance bigint NOT NULL DEFAULT 0
);
```

LEDGER AND AUDIT TABLES

```sql
CREATE TABLE bench_ledger (
  ledger_id bigserial PRIMARY KEY,
  account_id bigint NOT NULL,
  branch_id int NOT NULL,
  amount int NOT NULL,
  created_at timestamptz NOT NULL
    DEFAULT clock_timestamp()
);

CREATE TABLE bench_audit (
  audit_id bigserial PRIMARY KEY,
  account_id bigint NOT NULL,
  action text NOT NULL,
  created_at timestamptz NOT NULL
    DEFAULT clock_timestamp()
);
```


SEED DATA

```sql
INSERT INTO bench_branches(branch_id)
SELECT g
FROM generate_series(1, 100) AS g;

INSERT INTO bench_accounts
  (account_id, branch_id, balance)
SELECT g, 1 + (g % 100), 100000
FROM generate_series(1, 1000000) AS g;
```

THE WORKLOAD

One transaction does six things



PGBENCH

32 clients run this five-statement transaction for 120 seconds

1 SETUP, READ, UPDATE

```
-- pgbench script for tests
\set aid random(1, 1000000)
\set delta random(-500, 500)

BEGIN;

SELECT balance
FROM bench_accounts
WHERE account_id = :aid;

UPDATE bench_accounts
SET balance = balance + :delta
WHERE account_id = :aid;
```

2 LEDGER AND AUDIT WRITES

```
INSERT INTO bench_ledger
  (account_id, branch_id,
   amount)
SELECT account_id, branch_id,
       :delta
FROM bench_accounts
WHERE account_id = :aid;

INSERT INTO bench_audit
  (account_id, action)
VALUES (:aid, 'debit_credit');
```

3 CLEANUP AND COMMIT

```
DELETE FROM bench_audit
WHERE audit_id IN (
  SELECT audit_id
  FROM bench_audit
  WHERE created_at < now()
    - interval '10 minutes'
  ORDER BY created_at
  LIMIT 1
);

COMMIT;
```

PGBENCH

The run: 32 clients on 8 threads for 120 seconds

RUN COMMAND

```
----*** Run pgbench ***----
pgbench -n -c 32 -j 8 -T 120 --protocol=simple \
  -f indexed_baseline.sql pgbench_darkside
```

WHAT EACH FLAG DOES

`-n`	Skip the pgbench pre-run vacuum	`--protocol=simple`	Simple query protocol
`-c 32`	32 concurrent client sessions	`-f`	Run the custom script file
`-j 8`	8 worker threads	`pgbench_darkside`	Target database
`-T 120`	Run for 120 seconds		

TEST SETUP

100

BRANCHES

1,000,000

ACCOUNTS

32

CLIENTS

8

PGBENCH JOBS

120 s

PER RUN

simple

PROTOCOL

Benchmark environment

One desktop machine, one local PostgreSQL instance, 120-second runs.


MACHINE

Host	Intel Core i7-13700, 16 cores / 24 threads
RAM	63.8 GB
Storage	Samsung SSD 980 NVMe
OS	Windows 11
Database	PostgreSQL 18.6, x86_64
Driver	pgbench 18.6

TEST SETUP

Test duration	120 seconds per measured test
Load	32 clients / 8 threads
Database	`pgbench_darkside`
Connection	`-h localhost -U postgres -d pgbench_darkside`
Password source	`PGPASSWORD=*******`
Dataset	100 branches, 1,000,000 accounts

Why not VM in a cloud?



1,162 TPS

cloud VM, 32 clients, 120 s

27.5 ms

average latency

Baseline settings before the “cheats”

jit	**off**
full_page_writes	**on**
shared_buffers	**1GB**
fsync	**on**
synchronous_commit	**on**
wal_compression	**LZ4**

Windows machine • local NVMe • tuned OLTP-ish PostgreSQL configuration

INTENTIONALLY FLAWED

Case 0: sabotage the baseline

```
DELETE FROM bench_audit
WHERE audit_id IN (
  SELECT audit_id
  FROM bench_audit
  WHERE created_at < now() - interval '10 minutes'
  ORDER BY created_at
  LIMIT 1
);
```

NO INDEX ON CREATED_AT

584

TPS

dishonest baseline

This is not PostgreSQL being slow.
This is the schema being lazy.

EXPLAIN ANALYZE

WITHOUT INDEX

```
===== PLAN WITHOUT composite index (ORDER BY created_at LIMIT 1) =====
                                QUERY PLAN
-----------------------------------------------------------------------
 Limit (actual rows=0.00 loops=1)
   Buffers: shared hit=1667
   ->  Sort (actual rows=0.00 loops=1)
         Sort Key: created_at
         Sort Method: quicksort  Memory: 25kB
         Buffers: shared hit=1667
         ->  Seq Scan on bench_audit (actual rows=0.00 loops=1)
               Filter: (created_at < (now() - '00:10:00'::interval))
               Rows Removed by Filter: 200000
               Buffers: shared hit=1667
 Planning:
   Buffers: shared hit=34
(12 rows)
```

WITH COMPOSITE INDEX

```
===== PLAN WITH composite index =====
                                                        QUERY PLAN
---------------------------------------------------------------------------------------------------------
 Limit (actual rows=0.00 loops=1)
   Buffers: shared hit=3
   -> Index Only Scan using bench_audit_created_at_audit_id_idx on bench_audit
         Index Cond: (created_at < (now() - '00:10:00'::interval))
         Heap Fetches: 0
         Index Searches: 1
         Buffers: shared hit=3
 Planning:
   Buffers: shared hit=9 read=4
(9 rows)
```

Index Only Scan reads 3 buffers, 0 heap fetches

The plan tells you exactly what I broke

WITHOUT INDEX		WITH COMPOSITE INDEX	
200,000	rows removed by filter	0	heap fetches
1,667	shared buffers hit	3	shared buffers hit
Seq Scan	→ Sort → Limit	Index Only	Scan → Limit

HONEST BASELINE

Add the obvious missing index.

```
CREATE INDEX bench_audit_created_at_audit_id_idx
ON bench_audit(created_at, audit_id);
```

22,705

TPS — HONEST BASELINE

41× OVER CASE 0

FOUR LEVERS

1

GUARANTEES

durability / WAL / crash promises

2

WORK

do less or change persistence

3

EXECUTION


server-side logic / protocol

4

METRIC

batching and a new y-axis

The scary durability knobs barely help



Why Nuclear-sounding settings barely helped

	default open_datasync	fdatasync
Measured latency	~40 µs	~2 ms
Write caching	Can remain enabled	Can prevent write caching
Benchmark impact	High TPS	Low TPS

UNLOGGED LEDGER / AUDIT

Write less WAL

LOGGED

ledger
audit

→

UNLOGGED

ledger
audit

37,780

TPS

1.66×

LESS WORK

- × SELECT account
- ✓ **UPDATE balance**
- ✓ **INSERT ledger**
- × FK check
- × INSERT audit
- × audit cleanup

45,145


TPS

1.99× VS INDEXED

Doing less work is faster.


SERVER-SIDE + PREPARED


Change the execution shape



SERVER-SIDE FUNCTIONS

Six round trips become one call





BEFORE Each statement waits on the network

AFTER The whole transaction runs inside PostgreSQL

PREPARED PROTOCOL

Parse and plan once, then only execute

Simple protocol

Every statement, every time

Parse

↓

Analyze & rewrite

↓

Plan

↓

Execute

Prepared protocol

After the first run, only Execute

Parse **skipped**

↓

Analyze & rewrite **skipped**

↓

Plan **skipped**

↓

Execute

22,705 → 34,684 TPS (+53%). Still six round trips per transaction; each statement just costs less CPU.

The respectable hero result.

80,178

TPS

3.53× VS INDEXED

This is where an honest benchmark pauses.

THE PIVOT

Up to here, the y-axis still means TPS.

Now the y-axis starts doing marketing work.

CHANGE THE UNIT

batch ×8

ONE TRANSACTION



8 account operations inside it

24,099

TPS

→

192,790

REPORTED OPS

8.49× HEADLINE

BATCH ×32

bigger batch, bigger headline

8,426
TPS

↓

269,617
REPORTED OPS

↑

Marketing metric rises.

11.87× HEADLINE

BENCHMARKETING TRICK #2

TPS ↓ OPS ↑ Headline ↑↑↑

The number is real. The comparison changed.

ALL CHEATS + BATCH ×32

Grand finale: stack the deck

SQL FUNCTION

PREPARED PROTOCOL

32 OPS / TRANSACTION

RELAXED DURABILITY

LESS INTEGRITY WORK

362,789

REPORTED OPERATIONS / SECOND

THE FULL SCOREBOARD

PostgreSQL 18.6 on Windows 11, trusted Dev Drive V: (ReFS), pgbench -c 32 -j 8 -T 120, 1 round

Method	Protocol	TPS	OPS*	Latency (ms)	× baseline	× Case 0
Case 0: bad code / missing index	simple	584	584	54.80	0.03×	1.0×
Indexed baseline	simple	22,705	22,705	1.41	1.00×	38.9×
synchronous_commit=off	simple	24,355	24,355	1.31	1.07×	41.7×
full_page_writes=off	simple	23,390	23,390	1.37	1.03×	40.1×
fsync=off	simple	24,522	24,522	1.30	1.08×	42.0×
checkpoint tuning	simple	23,124	23,124	1.38	1.02×	39.6×
all durability off	simple	24,666	24,666	1.30	1.09×	42.2×
less work (drop FK/SELECT/audit)	simple	45,143	45,143	0.71	1.99×	77.3×
UNLOGGED ledger/audit	simple	37,780	37,780	0.85	1.66×	64.7×
stored procedure	simple	74,473	74,473	0.43	3.28×	127.5×
stored function (SQL)	simple	72,743	72,743	0.44	3.20×	124.6×
prepared protocol	prepared	34,684	34,684	0.92	1.53×	59.4×
sql function + prepared	prepared	80,178	80,178	0.40	3.53×	137.3×
batching ×8	simple	24,099	192,790	1.33	8.49×	330.2×
batching ×32	simple	8,426	269,617	3.80	11.87×	461.7×
all cheats + batch ×32 (SQL fn)	**prepared**	**11,337**	**362,789**	**2.82**	**15.98×**	**621.3×**

* OPS = operations/second for batched methods, TPS otherwise. × baseline = vs indexed baseline; × Case 0 = vs the crippled Case 0. Highlighted row stacks every cheat at once. Dev Drive with Defender performance mode keeps real-time scanning out of the commit path (scans run asynchronously).

CHAMP IS HERE

362,789

REPORTED OPS

15.98×

VS INDEXED BASELINE

621×


VS CRIPPLED CASE 0

The number is not fake. The framing is the trick.

THE MARKETING CHART

Now plot the headline number instead

WARNING: TPS → OPS



Extended Trickery

The trick: always benchmark against vanilla PostgreSQL.

VECTOR SEARCH SPEED, RELATIVE TO PGVECTOR

pgvector
the baseline they pick



1x

XYZdb
the published claim



4x

pgvectorscale / VectorChord/ pg_vectorsearch
left out of the chart




20x


B = 4A and C = 20A, so C = 5B?


Against Postgres with the right extension, XYZdb is 5x slower.

400,000 vectors for just $1, enabling significant savings: 6x more vectors compared t
Pinecone's optimized storage and 26x more than pgvector/pgvecto.rs for the same p




On a benchmark dataset of 50 million Cohere embeddings with 768 dimensions each, PostgreSQL with `pgvector` and `pgvectorscale` achieves **28x lower p95 latency** and **16x higher query throughput** compared to Pinecone's storage optimized (s1) index for approximate nearest neighbor queries at 99% recall, all at 75% less cost when self-hosted on AWS EC2.






PG_VECTORSEARCH

PRISM beats HNSW on a quarter of the hardware





Tiger Data benchmark (rekall), 100M Cohere embeddings. Recall@10 vs. exact search; HNSW is pgvector with halfvec. 128 GiB = r8i.4xlarge, 512 GiB = r8i.16xlarge (4× cost). pg_vectorsearch is alpha and requires PostgreSQL 18+.
Source: Tiger Data, "Announcing pg_vectorsearch", Oct 13, 2026

Before believing the next 100× graph...

Ask what changed between the bars.

DECOMPOSE THE CLAIM

Where did the big number really come from?

Fix broken schema	**584 → 22,705 TPS**	39× headline opportunity
Durability knobs	**1.02×–1.09×**	mostly noise here
Do less / UNLOGGED	**1.99× / 1.66×**	work or guarantees changed

DECOMPOSE THE CLAIM

The last jump comes from changing execution + metric

Server-side SQL function	**72,743 TPS**	3.20× legitimate hero
Batching	**24,099 / 8,426 TPS**	headline switches to OPS
Stack everything	**362,789 OPS**	15.98× vs indexed

THE HONEST CONCLUSION

The number is not fake.

The framing is the trick.

362,789 OPS. Same PostgreSQL. Different story.

BENCHMARK-READING CHECKLIST
are we comparing the same thing?

01	**BASELINE**	Is the comparison system competently configured?
02	**WORK**	Are both sides doing the same logical work?
03	**GUARANTEES**	Same durability, consistency and crash semantics?

BENCHMARK-READING CHECKLIST

Then: interrogate the metric and omissions

04	**METRIC**	TPS, queries, rows, requests… or “operations”?
05	**OMISSIONS**	Cost, p99 latency, write amplification, operational complexity?
06	**REPRODUCIBLE**	Can I see the code, config and workload?

PostgreSQL still gets one compliment

Even a dishonest benchmark had to use real PostgreSQL features to cheat convincingly.

- INDEXES
- BATCHING
- UNLOGGED TABLES
- STORED PROCEDURES
- SQL FUNCTIONS
- PREPARED STATEMENTS

Mature. Boring. Production-grade machinery.

DATABASE WARS

The details change. The crime scene stays familiar.

The same performance ladder could be built with MySQL, MariaDB, or almost any database.



REFERENCES

01

That time Oracle tried to have a professor fired for benchmarking their database

Dan Luu

danluu.com/anon-benchmark/

02

The DeWitt Clause: Why You Rarely See Database Benchmarks

Brent Ozar

www.brentozar.com/archive/2018/05/the-dewitt-clause-why-you-rarely-see-database-benchmarks/

03

The DeWitt clause censorship should be illegal

David A. Wheeler

dwheeler.com/essays/dewitt-clause.html

THANK YOU

Now go distrust some graphs.

Questions?



Talk and scripts on GitHub

See you at the Prague PostgreSQL Meetup



RSVP

Scan to
grab a spot