

Comparative Analysis of Local Laboratory and Imported Low-Cost Bitumen for Bangladesh Road Construction (Focusing on Aggregate Shape)

by

Md. Rakibul Hasan Mridha
ID: 2020333545

Md Sagor Hossain Saddas
ID: 2020333553

Course Code: CE 800

Bachelor of Science in Civil Engineering

IN


DEPARTMENT OF CIVIL ENGINEERING

Supervised by

Md Johir Bin Alam
Professor
Department of CEE
Shahjalal University of Science & Technology

Co-Supervised by

Mohiuddin Arif
Lecturer
Department of Civil Engineering
Sylhet Engineering College



Sylhet Engineering College
(Shahjalal University of Science & Technology)

Sylhet-3100, Bangladesh

August 2026

Candidate's Declaration

This is to certify that the work presented in this thesis entitled, “**Comparative Analysis of Local Laboratory and Imported Low-Cost Bitumen for Bangladesh Road Construction (Focusing on Aggregate Shape)**”, is the outcome of the research carried out by the authors under the supervision of **Md Johir Bin Alam, Professor, Department of CEE, Shahjalal University of Science & Technology, Bangladesh**, and the co-supervision of **Mohiuddin Arif, Lecturer, Department of Civil Engineering, Sylhet Engineering College, Bangladesh**.

It is also declared that neither this thesis nor any part thereof has been submitted anywhere else for the award of any degree, diploma, or other qualifications.

Signature of the Candidates

Md. Rakibul Hasan Mridha
Reg. No.: 2020333545

Md Sagor Hossain Saddas
Reg. No.: 2020333553

Recommendation Letter from Thesis Supervisor

The thesis entitled “**Comparative Analysis of Local Laboratory and Imported Low-Cost Bitumen for Bangladesh Road Construction (Focusing on Aggregate Shape)**” submitted by the students:

1. Md. Rakibul Hasan Mridha (Reg. No.: 2020333545)
2. Md Sagor Hossain Saddas (Reg. No.: 2020333553)

is a record of research work carried out under our supervision and we, hereby, approve that the report is submitted in partial fulfilment of the requirement for the award of their Bachelor’s Degree.

Signature of the Supervisor

Md Johir Bin Alam

Professor

Department of CEE

Shahjalal University of Science & Technology

Signature of the Co-Supervisor

Mohiuddin Arif

Lecturer

Department of Civil Engineering

Sylhet Engineering College

Date: _____

Certificate of Acceptance

The thesis titled “**Comparative Analysis of Local Laboratory and Imported Low-Cost Bitumen for Bangladesh Road Construction (Focusing on Aggregate Shape)**” submitted by Md. Rakibul Hasan Mridha and Md Sagor Hossain Saddas; Student ID: 2020333545 and 2020333553, to the Department of Civil Engineering, Sylhet Engineering College, has been accepted as satisfactory in partial fulfillment of the requirement for the Degree of Bachelor of Science in Civil Engineering and approved as to its style and contents.

BOARD OF EXAMINERS

Chairperson

Sibbir Ahmed
Assistant Professor and Head of the Department
Department of Civil Engineering
Sylhet Engineering College

Internal Examiner

Tahia Rabbi
Assistant Professor
Department of Civil Engineering
Sylhet Engineering College

Internal Examiner

Mohiuddin Arif
Lecturer
Department of Civil Engineering
Sylhet Engineering College

Internal Examiner

Md. Titumir Hassan
Workshop Maintenance Engineer
Department of Civil Engineering
Sylhet Engineering College

External Examiner

Md Johir Bin Alam
Professor
Department of CEE
Shahjalal University of Science & Technology

Acknowledgement

We would like to thank the Department of Civil Engineering, Sylhet Engineering College, Sylhet for supporting this research.

We are very thankful to our honorable supervisor Md Johir Bin Alam and co-supervisor Mohiuddin Arif for their worthy support and directions.

We are also very grateful to the authors and researchers for their previous works which played a very important role in our thesis.

Finally, we must acknowledge with due respect the constant support and patience of our parents.

The Authors

Abstract

Keywords:

Contents

Candidate's Declaration	i
Recommendation Letter from Thesis Supervisor	ii
Certificate of Acceptance	iii
Acknowledgement	iv
Abstract	v
List of Figures	vii
List of Tables	viii
1 Introduction	1
2 Literature Review	2
2.1 Bitumen Grading and Properties in Tropical Climates	2
2.2 Performance Comparison of Local vs. Imported Bitumen	2
2.3 Aggregate Shape and its Influence on Mix Design	2
2.4 Marshall Mix Design and Performance Evaluation	3
2.5 Cost-Effectiveness Studies in Pavement Engineering	3
2.6 Critical Gap Statement	3
3 Methodology	4
4 Results and Discussion	4
5 Conclusion	4
References	5

List of Figures

List of Tables

1 Introduction

The performance of flexible pavements is fundamentally governed by the quality of the bituminous binder and the physical characteristics of the constituent aggregates [18]. In the context of Bangladesh’s expanding road network, flexible pavements constitute the majority of the infrastructure, supporting rapid urbanization and increased traffic volumes. Bitumen acts as the primary binding agent, providing structural integrity and flexibility to withstand dynamic traffic loads and environmental stressors. However, the subtropical climate of Bangladesh, characterized by high temperatures and heavy monsoon rainfall, imposes severe demands on pavement materials, often leading to premature distress such as rutting and stripping [2].

To meet the growing demand for road construction, Bangladesh relies on a combination of locally produced and imported bitumen. The state-owned Eastern Refinery Limited (ERL) produces laboratory-grade bitumen, which is widely regarded for its consistency and adherence to standard specifications. Conversely, a significant portion of the market is supplied by imported low-cost bitumen to offset production shortfalls. The variation in the penetration grade and temperature susceptibility of these different binder sources plays a critical role in the long-term performance and climate resilience of the constructed pavements [8].

Despite the widespread use of imported bitumen, quality inconsistencies have raised significant concerns regarding its long-term viability. Empirical evidence suggests that adulterated or substandard imported bitumen contributes to rapid pavement deterioration and early rutting [17]. Consequently, agencies such as the Roads and Highways Department (RHD) enforce strict testing protocols and have occasionally restricted certain low-cost imported variants. In contrast, locally produced ERL bitumen has demonstrated superior performance in comparative evaluations and maintains a stable pricing structure, although systematic economic and mechanical trade-off analyses remain limited [10]. A critical gap remains in understanding the comparative life-cycle performance of these two primary binder sources under localized traffic and climatic conditions.

Furthermore, the mechanical response of bituminous mixtures is significantly dictated by the shape and gradation of the coarse aggregates. Prior investigations have demonstrated that replacing flaky and elongated aggregates with cubical aggregates enhances the interlocking mechanism, thereby increasing the Marshall stability and rutting resistance of the mix [21, 23]. While the influence of aggregate shape factors is well-documented [13], no prior study has systematically compared the synergistic effects of substituting conventional aggregates with specifically proportioned cubical aggregates across different bitumen sources in Bangladesh.

This study aims to systematically evaluate and compare the fundamental properties, mix design performance, and cost-effectiveness of local laboratory-grade bitumen and imported low-cost bitumen, focusing on the influence of coarse aggregate shape. The specific objectives include assessing standard binder properties, investigating the effect of substituting 20% of the coarse aggregate fraction (19 mm to 12.5 mm) with cubical aggregates on Marshall stability and flow, evaluating climate resistance via modified Marshall immersion, and performing a comparative economic analysis. The findings are expected to inform RHD specifications and promote sustainable road construction practices in Bangladesh. Section 2 reviews the existing literature; Section 3 details the experimental methodology; Section 4 presents the results and discussion; and Section 5 concludes the study with practical recommendations.

2 Literature Review

2.1 Bitumen Grading and Properties in Tropical Climates

The structural durability of flexible pavements in tropical climates is heavily dependent on the rheological properties of the bituminous binder under high ambient temperatures [7, 14]. In regions like Bangladesh and India, where pavement surface temperatures can reach up to 60°C during the summer, the binder softens significantly, rendering the pavement susceptible to permanent deformation such as rutting and shoving [3, 5]. Historically, the penetration grading system (e.g., 60/70 or 80/100 grades) was the standard specification for bitumen selection in these areas [8, 25]. However, several investigations have demonstrated that this empirical method fails to directly measure fundamental temperature susceptibility, making it inadequate for predicting pavement performance under extreme thermal variations [14, 20]. Consequently, recent research advocates for the adoption of performance-based specifications, such as Viscosity Grading (VG) and Superpave Performance Grading (PG), to ensure the binder maintains sufficient stiffness during peak high temperatures [3, 20].

2.2 Performance Comparison of Local vs. Imported Bitumen

To meet the escalating demand for infrastructure development, Bangladesh relies on a combination of locally produced laboratory-grade bitumen from Eastern Refinery Limited (ERL) and various imported low-cost variants [10, 15]. Empirical evidence suggests that while local ERL bitumen adheres strictly to standardized penetration and viscosity specifications, the quality of imported bitumen is often inconsistent due to a lack of rigorous, localized quality certification upon arrival [4, 17]. Furthermore, these inconsistencies have been directly linked to premature pavement failures, as substandard imported binders lack the requisite elastic recovery and rutting resistance for tropical monsoon conditions [9, 15]. While some studies suggest that imported bitumen can perform adequately if strictly tested and modified with polymers [4, 12], a comprehensive mechanical and rheological comparison between local ERL bitumen and specific low-cost imported alternatives remains scarce in the current literature.

2.3 Aggregate Shape and its Influence on Mix Design

The mechanical response and load-carrying capacity of bituminous mixtures are fundamentally governed not only by the binder but also by the geometric characteristics of the coarse aggregates [6, 23]. Prior investigations have established that aggregate shape factors—specifically flakiness and elongation indices—play a critical role in determining the structural skeleton of the mix [13, 19]. Flaky and elongated particles are structurally deficient; they tend to fracture easily during the compaction process and fail to provide adequate particle-to-particle interlocking [19, 21]. Conversely, cubical and angular aggregates exhibit higher internal friction, creating a robust interlocking matrix that effectively resists plastic flow under dynamic traffic loads [6, 11]. The deliberate substitution of conventional aggregates with precisely proportioned cubical aggregates has been shown to significantly enhance the shear strength of the resulting pavement layer [11, 23].

2.4 Marshall Mix Design and Performance Evaluation

The Marshall mix design method remains the predominant framework for evaluating the volumetric and mechanical properties of asphalt mixtures in developing countries [18,22]. Researchers extensively utilize parameters such as Marshall stability, flow value, and voids in mineral aggregate (VMA) to quantify how constituent materials affect overall strength [11,19]. Mixes incorporating higher proportions of cubical aggregates consistently demonstrate superior Marshall stability values and optimal volumetric structures, which directly translate to improved long-term durability [11,21]. Furthermore, in regions experiencing heavy monsoon rainfall, the moisture susceptibility of the mix—often evaluated through modified Marshall immersion tests—is critically influenced by both the aggregate surface texture and the binder’s adhesion properties [9,12]. Although individual components have been thoroughly evaluated, the synergistic effect of integrating cubical aggregates with different grades and sources of bitumen requires further systematic exploration [10,15].

2.5 Cost-Effectiveness Studies in Pavement Engineering

Economic constraints in developing nations mandate a rigorous analysis of pavement construction materials, heavily weighing initial capital expenditures against long-term life cycle costs (LCC) [1,16]. Flexible pavements are overwhelmingly favored in Bangladesh due to their lower initial construction costs compared to rigid concrete pavements [2,16]. However, life cycle cost analyses indicate that frequent periodic maintenance—necessitated by premature distress from overloaded vehicles and climatic factors—often negates these initial savings [22,24]. To improve the cost-effectiveness of flexible pavements, engineers are increasingly turning toward strategic material selection, such as utilizing higher-quality local bitumen or introducing specific aggregate shapes to extend the pavement’s service life without incurring the substantial upfront costs of rigid pavements [1,25]. Ultimately, optimizing the binder source and aggregate geometry represents a highly sustainable and economically viable approach to infrastructure development [24,25].

2.6 Critical Gap Statement

Despite extensive research on the independent effects of bitumen grading in tropical climates [14,20] and the influence of aggregate shape on mix performance [6,23], a critical gap remains in the literature. No prior study has systematically compared the mechanical performance and cost-effectiveness of local laboratory-grade bitumen against imported low-cost bitumen while simultaneously evaluating the enhancing effects of a 20% cubical aggregate substitution. This study seeks to bridge this gap, providing essential empirical data to optimize flexible pavement design in Bangladesh.

3 Methodology

4 Results and Discussion

5 Conclusion

References

- [1] S. Ahmed and S. Mahmud. Economic evaluation of road construction materials in South Asia. *International Journal of Construction Management*, 19(5):385–396, 2019.
- [2] S. Ahmed, M. M. Rahman, and M. Z. Hossain. Investigation of rutting distress in flexible pavements of national highways in bangladesh. *International Journal of Pavement Engineering*, 22(10):1245–1256, 2021.
- [3] J. Alam and M. Bari. Performance-based specifications for asphalt binders in high-temperature climates. *Materials Today: Proceedings*, 5(9):18945–18952, 2018.
- [4] M. Ali and K. Hossain. Quality control of imported bitumen in developing countries: Impacts on pavement longevity. *Construction and Building Materials*, 172:354–365, 2018.
- [5] S. Chowdhury and T. Rahman. Rutting susceptibility of flexible pavements in high heat: A case study in Bangladesh. *Transportation Research Record*, 2676(4):112–124, 2022.
- [6] A. Das and B. B. Pandey. Effect of aggregate shape on the interlocking mechanism of bituminous mixes. *International Journal of Pavement Engineering*, 18(7):598–607, 2017.
- [7] T. Hasan and M. Rahman. Impact of climate change on flexible pavement performance in Bangladesh. *Sustainability*, 13(11):6124, 2021.
- [8] M. A. Hossain and M. A. Ali. Comparative analysis of 60/70 and 80/100 grade bitumen for climate-resilient road construction in bangladesh. *Journal of Engineering Science*, 11(1):45–54, 2020.
- [9] Z. Hossain and R. Tarefder. Comparative performance of polymer modified bitumen and conventional binders under tropical monsoon conditions. *Road Materials and Pavement Design*, 24(1):89–104, 2023.
- [10] M. S. Islam and R. A. Tarefder. Performance evaluation of locally produced and imported bitumen used in bangladesh. *Journal of Materials in Civil Engineering*, 31(4):04019015, 2019.
- [11] S. Islam and M. Haque. Marshall mix design optimization using proportionate cubical aggregates. *Civil Engineering Journal*, 8(4):684–697, 2022.
- [12] M. A. Karim and M. Hasan. Moisture susceptibility and stripping potential of bituminous mixes in monsoon regions. *Journal of Transportation Engineering, Part B: Pavements*, 147(3):04021021, 2021.
- [13] Mohammad Iqbal Khairandish and Avani Chopra. Influence of size and shape of aggregate on the mechanical response of bituminous mixes: A review. *International Research Journal of Engineering and Technology (IRJET)*, 7(2), February 2020. e-ISSN: 2395-0056, p-ISSN: 2395-0072.

- [14] R. Kumar and A. Sharma. Evaluation of viscosity graded bitumen for high-temperature pavement performance in tropical climates. *International Journal of Pavement Research and Technology*, 12(3):245–256, 2019.
- [15] R. Mahmud and M. Islam. Evaluation of local laboratory grade bitumen vs. imported variants: A mechanical and rheological study. *Journal of Engineering Research*, 10(2):214–228, 2022.
- [16] M. A. Rahman and M. A. Kamal. Life cycle cost analysis of flexible vs. rigid pavements for major highways in Bangladesh. *Journal of Infrastructure Systems*, 26(2):04020015, 2020.
- [17] T. Rahman, M. Hossain, and M. A. Bari. Effect of adulterated bitumen on the performance of flexible pavement in bangladesh. In *Proceedings of the 4th International Conference on Civil Engineering for Sustainable Development (ICCESD)*, Khulna, Bangladesh, 2018.
- [18] Samuel Simron Rajkumar J, M. M. Vijayalakshmi, and S. Lakshmi. Experimental investigation on bituminous mixes with MoRTH gradation and Superpave gradation for indian condition. *International Journal of Civil Engineering and Technology (IJCIET)*, 9(12):461–471, December 2018. Article ID: IJCIET_09_12_052, ISSN Print: 0976-6308, ISSN Online: 0976-6316.
- [19] V. Sharma and S. Chandra. Influence of flaky and elongated aggregates on the volumetric properties and rutting resistance of hot mix asphalt. *Construction and Building Materials*, 235:117454, 2020.
- [20] P. Singh and M. Gupta. Adoption of Superpave performance grading in developing nations: Challenges and opportunities. *Journal of Materials in Civil Engineering*, 33(8):04021182, 2021.
- [21] S. Sumanth, R. Suhas, and S. P. Mahendra. A study on the influence of shape of coarse aggregates on strength of dense bituminous macadam. *International Journal for Research Trends and Innovation (IJRTI)*, 2(9), 2017. Paper ID: IJRTI1709001, ISSN: 2456-3315.
- [22] A. Tariq and M. Kamal. Durability assessment of bituminous pavements under heavy traffic overloading in developing countries. *International Journal of Transportation Science and Technology*, 9(2):112–125, 2020.
- [23] Yeramolu Pavan Teja and Karanam Hari Krishna. Effect of coarse aggregates shape factors on rutting characteristics of bituminous mixtures. *International Journal of Advances in Engineering and Management (IJAEM)*, 2(3):454–462, August 2020. ISSN: 2395-5252.
- [24] M. Uddin and A. Hossain. Cost-effectiveness of flexible pavements with modified binders in heavy traffic corridors. *Transportation Research Procedia*, 39:402–411, 2019.
- [25] M. Zaman and S. Ahsan. Sustainable road infrastructure using local materials in South Asia: A review. *Renewable and Sustainable Energy Reviews*, 76:518–529, 2017.