


Capability machines as target for secure compilation


Dominique Devriese


imec-DistriNet, KU Leuven

Dagstuhl Seminar on Secure Compilation














?











Capability machines

Essential features

Revoking capabilities?

Sealing capabilities

What else do we need?

Conclusion

Capability machines

- History

- CHERI

- Principles

Essential features

Revoking capabilities?

Sealing capabilities

What else do we need?

Conclusion

Long history:

- [Dennis and Van Horn, 1966]
- Cambridge CAP, Hydra, PDP-1, ... [see Levy, "Capability-based Computer Systems", 1984]

Side product: Object capabilities in programming languages

- [Morris, 1973], E [Miller, 2006], Google Caja [Miller et al., 2008], JavaScript strict mode [ECMA, 2009]

- CHERI capability machine [Woodruff et al., 2014] [Watson et al., 2015] [...]
- (long list of contributors)
- Hybrid security model
 - Virtual memory + capabilities
 - for gradual adoption
- 64-bit MIPS-based implementation, runs on FPGA
- Toolchain: modified CLang, LLVM, CheriBSD, QEmu etc.

- Principles:
 - Least privilege
 - Fine-grained compartmentalization
 - Intentional use
- Practically
 - Capabilities represent authority
 - ~~Pointers = integers~~ Capabilities \neq integers
 - ▶ tagged memory
 - ▶ guarded manipulation

Capability machines

Essential features

- Memory capabilities

- Object capabilities

- Applications?


Revoking capabilities?

Sealing capabilities


What else do we need?

Conclusion


- Authority over memory array
- read/write/execute (depending on permissions)
- Hardware bounds check on every load/store




- Low-overhead privilege separation
- \sim encapsulated closures
 - Code pointer p
 - Environment $e = (e_1, \dots, e_n)$
 - e becomes accessible after jumping to (p, e)
- Two example designs:
 - M-Machine [Carter,1994]
 - CHERI




- Low-overhead privilege separation
- \sim encapsulated closures
 - Code pointer p
 - Environment $e = (e_1, \dots, e_n)$
 - e becomes accessible after jumping to (p, e)
- Two example designs:
 - M-Machine [Carter,1994]
 - CHERI




- Low-overhead privilege separation
- \sim encapsulated closures
 - Code pointer p
 - Environment $e = (e_1, \dots, e_n)$
 - e becomes accessible after jumping to (p, e)
- Two example designs:
 - M-Machine [Carter,1994]
 - CHERI



- Low-overhead privilege separation
- \sim encapsulated closures
 - Code pointer p
 - Environment $e = (e_1, \dots, e_n)$
 - e becomes accessible after jumping to (p, e)
- Two example designs:
 - M-Machine [Carter,1994]
 - **CHERI**



- Low-overhead privilege separation
- \sim encapsulated closures
 - Code pointer p
 - Environment $e = (e_1, \dots, e_n)$
 - e becomes accessible after jumping to (p, e)
- Two example designs:
 - M-Machine [Carter,1994]
 - **CHERI**



- Encapsulate C modules
 - (WIP)
 - El-Korashy, Tsampas, Patrignani, Garg, Piessens, Devriese
 - Enforce module-local state ("static")
- Encapsulate objects
 - Chisnall et al., ASPLOS 2017
 - Encapsulate Java objects in C/JNI code
 - direct buffers, syscalls, revocation etc.
- Other applications:
 - Fat pointers
 - Encapsulate closures?
 - Dynamic contract/type checking?

Capability machines

Essential features

Revoking capabilities?

- Revoking capabilities

- Local capabilities

- Linear capabilities

Sealing capabilities


What else do we need?


Conclusion


- *Temporary* authority delegation
- Expensive in general
 - Ocaps: indirection
 - Mark-and-sweep revocation [Chisnall et al., ASPLOS 2017]
- Cheap restricted forms
 - CHERI: Local capabilities
 - Linear capabilities


- supported by CHERI
- Rules:
 - Capabilities can be tagged as local
 - Local capabilities cannot be stored in memory
 - Except through write-local capabilities
 - ... which have to be local themselves
- Application (1/2):
 - stack and return capabilities in CHERI
 - ▶ per-compartment stack
 - ▶ local stack pointer
 - ▶ protect components against themselves
 - ▶ (no actual revocation)


- Application (2/2):
 - Skorstengaard, Devriese, Birkedal, ESOP 2018
 - ▶ single stack
 - ▶ local stack and return caps
 - ▶ revoke after return
 - ▶ requires stack clearing
- Revoking local capabilities requires efficient memory clearing
 - realistic?
 - Perhaps... [Joannou et al., ICCD 2017]






















- Rules:
 - Non-duplicable
 - Some additional instructions (split, join)
- Better for revocation
 1. Hand out capability
 2. Check that you get it back
 3. If so, no other copies in system, i.e. capability revoked
- Applications
 - Stack and return capabilities
 - ▶ Skorstengaard, Devriese, Birkedal, WIP
 - ▶ single stack, linear stack and return capability























- Applications (ctd.)
 - Separation logic
 - ▶ Van Strydonck, Devriese, Piessens, WIP
 - ▶ Reify heap chunks
 - ▶ Reify ghost code
 - ▶ Fully abstract compiler
 - ▶ Other features useful too: sealing, non-linear caps...
 - Linear types?
- Linear Affine

Capability machines

Essential features

Revoking capabilities?

Sealing capabilities

What else do we need?



Conclusion

Sealed capabilities

- Seal permission
- Seal/unseal instructions
- (CHERI: also used for ocaps)
- perfect encryption/signatures

Applications:

- Abstract types?
- Typed references?
- Polymorphism? [Sumii and Pierce, 2000] [Devriese et al., 2018]
- Information flow?




Sealed capabilities

- Seal permission
- Seal/unseal instructions
- (CHERI: also used for ocaps)
- perfect encryption/signatures

Applications:

- Abstract types?
- Typed references?
- Polymorphism? [Sumii and Pierce, 2000] [Devriese et al., 2018]
- Information flow?





Sealed capabilities

- Seal permission
- Seal/unseal instructions
- (CHERI: also used for ocaps)
- perfect encryption/signatures

Applications:

- Abstract types?
- Typed references?
- Polymorphism? [Sumii and Pierce, 2000] [Devriese et al., 2018]
- Information flow?



Capability machines

Essential features

Revoking capabilities?

Sealing capabilities

What else do we need?

Conclusion

- Read-after-write capabilities?
 - Allow malloc to not clear
 - Prevent stack frame communication (in single-stack model)
- Features of other systems (e.g., SGX)
 - Attestation?
 - Protection from untrusted OS?
 - Secure I/O?
- ... more?

Capability machines

Essential features

Revoking capabilities?

Sealing capabilities

What else do we need?

Conclusion

Capability machines for secure compilation?

- Strengths:
 - Supports higher-order interfaces
 - Many protection domains (e.g. every object, every closure?)
 - Powerful extras: sealing, local, linear capabilities
 - Existing reasoning techniques apply
 - (Relatively) simple at hardware level? (no hardware tables)
- Weaknesses:
 - Only research prototypes (so far)
 - Dynamic checking everywhere
 - Reclaiming component memory? (with HO interfaces)

- CheriBSD stack management
 - stack per compartment, trusted stack manager
 - Many compartments \Rightarrow many stacks
 - Which compartment for an indirect call?