

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                       | STRM Rationale | STRM Relationship | SCF Control                                                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                             | Strength of Relationship | Notes                                                                                                                                                                                                                                                |
|-------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 1 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.              | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation                           | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                                                          | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 1 are defined, understood, and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 1.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 1 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.              | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program                | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPP), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness.                                        | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 1 are defined, understood, and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 1.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 1 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.              | Functional     | Subset Of         | Operations Security                                                                  | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                                                                             | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 1 are defined, understood, and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 1.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 1 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.              | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                                              | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                                                                     | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 1 are defined, understood, and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 1.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 1 are documented, assigned, and understood.                                                                                 | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities                          | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPP).                                                              | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 1 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                  |
| 1.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 1 are documented, assigned, and understood.                                                                                 | Functional     | Intersects With   | Defined Roles & Responsibilities                                                     | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                                                            | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 1 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                  |
| 1.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 1 are documented, assigned, and understood.                                                                                 | Functional     | Intersects With   | User Awareness                                                                       | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                                                            | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 1 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                  |
| 1.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 1 are documented, assigned, and understood.                                                                                 | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training                                | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training:<br>(1) Before authorizing access to the system or performing assigned duties;<br>(2) When required by system changes; and<br>(3) Annually thereafter.                                              | 5                        |                                                                                                                                                                                                                                                      |
| 1.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 1 are documented, assigned, and understood.                                                                                 | Functional     | Intersects With   | Privileged Users                                                                     | SAT-03.5 | Mechanisms exist to provide specific training for privileged users to ensure privileged users understand their unique roles and responsibilities                                                                                                                                                | 5                        |                                                                                                                                                                                                                                                      |
| 1.2.1 | N/A      | Configuration standards for NSC rulesets are:<br>• Defined.<br>• Implemented.<br>• Maintained.                                                                                                  | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                                                             | 5                        | The way that NSCs are configured and operate are defined and consistently applied.                                                                                                                                                                   |
| 1.2.1 | N/A      | Configuration standards for NSC rulesets are:<br>• Defined.<br>• Implemented.<br>• Maintained.                                                                                                  | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                                                                 | 5                        | The way that NSCs are configured and operate are defined and consistently applied.                                                                                                                                                                   |
| 1.2.1 | N/A      | Configuration standards for NSC rulesets are:<br>• Defined.<br>• Implemented.<br>• Maintained.                                                                                                  | Functional     | Subset Of         | Cloud Services                                                                       | CLD-01   | Mechanisms exist to facilitate the implementation of cloud management controls to ensure cloud instances are secure and in-line with industry practices.                                                                                                                                        | 10                       | The way that NSCs are configured and operate are defined and consistently applied.                                                                                                                                                                   |
| 1.2.1 | N/A      | Configuration standards for NSC rulesets are:<br>• Defined.<br>• Implemented.<br>• Maintained.                                                                                                  | Functional     | Intersects With   | DMZ Networks                                                                         | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                                                                                    | 5                        | The way that NSCs are configured and operate are defined and consistently applied.                                                                                                                                                                   |
| 1.2.1 | N/A      | Configuration standards for NSC rulesets are:<br>• Defined.<br>• Implemented.<br>• Maintained.                                                                                                  | Functional     | Intersects With   | Defense-In-Depth (DID) Architecture                                                  | SEA-03   | Mechanisms exist to implement security functions as a layered structure minimizing interactions between layers of the design and avoiding any dependence by lower layers on the functionality or correctness of higher layers.                                                                  | 5                        | The way that NSCs are configured and operate are defined and consistently applied.                                                                                                                                                                   |
| 1.2.1 | N/A      | Configuration standards for NSC rulesets are:<br>• Defined.<br>• Implemented.<br>• Maintained.                                                                                                  | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                             | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                                                                                 | 5                        | The way that NSCs are configured and operate are defined and consistently applied.                                                                                                                                                                   |
| 1.2.2 | N/A      | All changes to network connections and to configurations of NSCs are approved and managed in accordance with the change control process defined at Requirement 6.5.1.                           | Functional     | Subset Of         | Change Management Program                                                            | CHG-01   | Mechanisms exist to facilitate the implementation of a change management program.                                                                                                                                                                                                               | 10                       | Changes to network connections and NSCs cannot result in misconfiguration, implementation of insecure services, or unauthorized network connections.                                                                                                 |
| 1.2.2 | N/A      | All changes to network connections and to configurations of NSCs are approved and managed in accordance with the change control process defined at Requirement 6.5.1.                           | Functional     | Intersects With   | Configuration Change Control                                                         | CHG-02   | Mechanisms exist to govern the technical configuration change control processes.                                                                                                                                                                                                                | 5                        | Changes to network connections and NSCs cannot result in misconfiguration, implementation of insecure services, or unauthorized network connections.                                                                                                 |
| 1.2.2 | N/A      | All changes to network connections and to configurations of NSCs are approved and managed in accordance with the change control process defined at Requirement 6.5.1.                           | Functional     | Intersects With   | Prohibition Of Changes                                                               | CHG-02.1 | Mechanisms exist to prohibit unauthorized changes, unless organization-approved change requests are received.                                                                                                                                                                                   | 5                        | Changes to network connections and NSCs cannot result in misconfiguration, implementation of insecure services, or unauthorized network connections.                                                                                                 |
| 1.2.3 | N/A      | An accurate network diagram(s) is maintained that shows all connections between the CDE and other networks, including any wireless networks.                                                    | Functional     | Intersects With   | Network Diagrams & Data Flow Diagrams (DFDs)                                         | AST-04   | Mechanisms exist to maintain network architecture diagrams that:<br>(1) Contain sufficient detail to assess the security of the network's architecture;<br>(2) Reflect the current architecture of the network environment; and<br>(3) Document all sensitive and/or regulated data flows.      | 5                        | A representation of the boundaries between the CDE, all trusted networks, and all untrusted networks, is maintained and available.                                                                                                                   |
| 1.2.3 | N/A      | An accurate network diagram(s) is maintained that shows all connections between the CDE and other networks, including any wireless networks.                                                    | Functional     | Intersects With   | Control Applicability Boundary Graphical Representation                              | AST-04.2 | Mechanisms exist to ensure control applicability is appropriately determined for Technology Assets, Applications and/or Services (TAAS) and third parties by graphically representing applicable boundaries.                                                                                    | 5                        | A representation of the boundaries between the CDE, all trusted networks, and all untrusted networks, is maintained and available.                                                                                                                   |
| 1.2.3 | N/A      | An accurate network diagram(s) is maintained that shows all connections between the CDE and other networks, including any wireless networks.                                                    | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                             | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                                                                                 | 5                        | A representation of the boundaries between the CDE, all trusted networks, and all untrusted networks, is maintained and available.                                                                                                                   |
| 1.2.3 | N/A      | An accurate network diagram(s) is maintained that shows all connections between the CDE and other networks, including any wireless networks.                                                    | Functional     | Intersects With   | Guest Networks                                                                       | NET-02.2 | Mechanisms exist to implement and manage a secure guest network.                                                                                                                                                                                                                                | 5                        | A representation of the boundaries between the CDE, all trusted networks, and all untrusted networks, is maintained and available.                                                                                                                   |
| 1.2.3 | N/A      | An accurate network diagram(s) is maintained that shows all connections between the CDE and other networks, including any wireless networks.                                                    | Functional     | Intersects With   | DMZ Networks                                                                         | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                                                                                    | 5                        | A representation of the boundaries between the CDE, all trusted networks, and all untrusted networks, is maintained and available.                                                                                                                   |
| 1.2.3 | N/A      | An accurate network diagram(s) is maintained that shows all connections between the CDE and other networks, including any wireless networks.                                                    | Functional     | Intersects With   | Wireless Link Protection                                                             | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for unauthorized wireless access points and taking appropriate action, if an unauthorized connection is discovered. | 5                        | A representation of the boundaries between the CDE, all trusted networks, and all untrusted networks, is maintained and available.                                                                                                                   |
| 1.2.4 | N/A      | An accurate data-flow diagram(s) is maintained that meets the following:<br>• Shows all account data flows across systems and networks.<br>• Updated as needed upon changes to the environment. | Functional     | Intersects With   | Network Diagrams & Data Flow Diagrams (DFDs)                                         | AST-04   | Mechanisms exist to maintain network architecture diagrams that:<br>(1) Contain sufficient detail to assess the security of the network's architecture;<br>(2) Reflect the current architecture of the network environment; and<br>(3) Document all sensitive and/or regulated data flows.      | 5                        | A representation of all transmissions of account data between system components and across network segments is maintained and available.                                                                                                             |
| 1.2.4 | N/A      | An accurate data-flow diagram(s) is maintained that meets the following:<br>• Shows all account data flows across systems and networks.<br>• Updated as needed upon changes to the environment. | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                             | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                                                                                 | 5                        | A representation of all transmissions of account data between system components and across network segments is maintained and available.                                                                                                             |
| 1.2.4 | N/A      | An accurate data-flow diagram(s) is maintained that meets the following:<br>• Shows all account data flows across systems and networks.<br>• Updated as needed upon changes to the environment. | Functional     | Intersects With   | DMZ Networks                                                                         | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                                                                                    | 5                        | A representation of all transmissions of account data between system components and across network segments is maintained and available.                                                                                                             |
| 1.2.4 | N/A      | An accurate data-flow diagram(s) is maintained that meets the following:<br>• Shows all account data flows across systems and networks.<br>• Updated as needed upon changes to the environment. | Functional     | Intersects With   | Ports, Protocols & Services In Use                                                   | TDA-02.1 | Mechanisms exist to require the developers of Technology Assets, Applications and/or Services (TAAS) to identify early in the Secure Development Life Cycle (SDLC), the functions, ports, protocols and services intended for use.                                                              | 5                        | A representation of all transmissions of account data between system components and across network segments is maintained and available.                                                                                                             |
| 1.2.5 | N/A      | All services, protocols, and ports allowed are identified, approved, and have a defined business need.                                                                                          | Functional     | Intersects With   | Least Functionality                                                                  | CFG-03   | Mechanisms exist to configure systems to provide only essential capabilities by specifically prohibiting or restricting the use of ports, protocols, and/or services.                                                                                                                           | 5                        | Unauthorized network traffic (services, protocols, or packets destined for specific ports) cannot enter or leave the network.                                                                                                                        |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                 | STRM Rationale | STRM Relationship | SCF Control                                                                        | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                 | Strength of Relationship | Notes                                                                                                                                                                                          |
|-------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.2.5 | N/A      | All services, protocols, and ports allowed are identified, approved, and have a defined business need.                                                                                                                                                                                                    | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                           | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                     | 5                        | Unauthorized network traffic (services, protocols, or packets destined for specific ports) cannot enter or leave the network.                                                                  |
| 1.2.5 | N/A      | All services, protocols, and ports allowed are identified, approved, and have a defined business need.                                                                                                                                                                                                    | Functional     | Intersects With   | DMZ Networks                                                                       | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                        | 5                        | Unauthorized network traffic (services, protocols, or packets destined for specific ports) cannot enter or leave the network.                                                                  |
| 1.2.5 | N/A      | All services, protocols, and ports allowed are identified, approved, and have a defined business need.                                                                                                                                                                                                    | Functional     | Intersects With   | Identification & Justification of Ports, Protocols & Services                      | TDA-02.5 | Mechanisms exist to require process owners to identify, document and justify the business need for the ports, protocols and other services necessary to operate their technology solutions.                                         | 5                        | Unauthorized network traffic (services, protocols, or packets destined for specific ports) cannot enter or leave the network.                                                                  |
| 1.2.5 | N/A      | All services, protocols, and ports allowed are identified, approved, and have a defined business need.                                                                                                                                                                                                    | Functional     | Intersects With   | External Connectivity Requirements - Identification of Ports, Protocols & Services | TPH-04.2 | Mechanisms exist to require External Service Providers (ESPs) to identify and document the business need for ports, protocols and other services it requires to operate its Technology Assets, Applications and/or Services (TAAS). | 5                        | Unauthorized network traffic (services, protocols, or packets destined for specific ports) cannot enter or leave the network.                                                                  |
| 1.2.6 | N/A      | Security features are defined and implemented for all services, protocols, and ports that are in use and considered to be insecure, such that the risk is mitigated.                                                                                                                                      | Functional     | Intersects With   | Secure Baseline Configurations                                                     | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                 | 5                        | The specific risks associated with the use of insecure services, protocols, and ports are understood, assessed, and appropriately mitigated.                                                   |
| 1.2.6 | N/A      | Security features are defined and implemented for all services, protocols, and ports that are in use and considered to be insecure, such that the risk is mitigated.                                                                                                                                      | Functional     | Intersects With   | Compensating Countermeasures                                                       | RSK-06.2 | Mechanisms exist to identify and implement compensating countermeasures to reduce risk and exposure to threats.                                                                                                                     | 5                        | The specific risks associated with the use of insecure services, protocols, and ports are understood, assessed, and appropriately mitigated.                                                   |
| 1.2.6 | N/A      | Security features are defined and implemented for all services, protocols, and ports that are in use and considered to be insecure, such that the risk is mitigated.                                                                                                                                      | Functional     | Intersects With   | Insecure Ports, Protocols & Services                                               | TDA-02.6 | Mechanisms exist to mitigate the risk associated with the use of insecure ports, protocols and services necessary to operate technology solutions.                                                                                  | 5                        | The specific risks associated with the use of insecure services, protocols, and ports are understood, assessed, and appropriately mitigated.                                                   |
| 1.2.6 | N/A      | Security features are defined and implemented for all services, protocols, and ports that are in use and considered to be insecure, such that the risk is mitigated.                                                                                                                                      | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                           | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                     | 5                        | The specific risks associated with the use of insecure services, protocols, and ports are understood, assessed, and appropriately mitigated.                                                   |
| 1.2.6 | N/A      | Security features are defined and implemented for all services, protocols, and ports that are in use and considered to be insecure, such that the risk is mitigated.                                                                                                                                      | Functional     | Intersects With   | DMZ Networks                                                                       | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                        | 5                        | The specific risks associated with the use of insecure services, protocols, and ports are understood, assessed, and appropriately mitigated.                                                   |
| 1.2.6 | N/A      | Security features are defined and implemented for all services, protocols, and ports that are in use and considered to be insecure, such that the risk is mitigated.                                                                                                                                      | Functional     | Intersects With   | Least Functionality                                                                | CFG-03   | Mechanisms exist to configure systems to provide only essential capabilities by specifically prohibiting or restricting the use of ports, protocols, and/or services.                                                               | 5                        | The specific risks associated with the use of insecure services, protocols, and ports are understood, assessed, and appropriately mitigated.                                                   |
| 1.2.7 | N/A      | Configurations of NSCs are reviewed at least once every six months to confirm they are relevant and effective.                                                                                                                                                                                            | Functional     | Intersects With   | Periodic Review                                                                    | CFG-03.1 | Mechanisms exist to periodically review system configurations to identify and disable unnecessary and/or non-secure functions, ports, protocols and services.                                                                       | 5                        | NSC configurations that allow or restrict access to trusted networks are verified periodically to ensure that only authorized connections with a current business justification are permitted. |
| 1.2.7 | N/A      | Configurations of NSCs are reviewed at least once every six months to confirm they are relevant and effective.                                                                                                                                                                                            | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                           | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                     | 5                        | NSC configurations that allow or restrict access to trusted networks are verified periodically to ensure that only authorized connections with a current business justification are permitted. |
| 1.2.7 | N/A      | Configurations of NSCs are reviewed at least once every six months to confirm they are relevant and effective.                                                                                                                                                                                            | Functional     | Intersects With   | Human Reviews                                                                      | NET-04.6 | Mechanisms exist to enforce the use of human reviews for Access Control Lists (ACLs) and similar rulesets on a routine basis.                                                                                                       | 5                        | NSC configurations that allow or restrict access to trusted networks are verified periodically to ensure that only authorized connections with a current business justification are permitted. |
| 1.2.7 | N/A      | Configurations of NSCs are reviewed at least once every six months to confirm they are relevant and effective.                                                                                                                                                                                            | Functional     | Intersects With   | Functional Review Of Security, Compliance & Resilience Controls                    | CPL-03.2 | Mechanisms exist to regularly review Technology Assets, Applications and/or Services (TAAS) for adherence to the organization's security, compliance and/or resilience policies and standards.                                      | 5                        | NSC configurations that allow or restrict access to trusted networks are verified periodically to ensure that only authorized connections with a current business justification are permitted. |
| 1.2.7 | N/A      | Configurations of NSCs are reviewed at least once every six months to confirm they are relevant and effective.                                                                                                                                                                                            | Functional     | Intersects With   | DMZ Networks                                                                       | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                        | 5                        | NSC configurations that allow or restrict access to trusted networks are verified periodically to ensure that only authorized connections with a current business justification are permitted. |
| 1.2.8 | N/A      | Configuration files for NSCs are:<br>• Secured from unauthorized access.<br>• Kept consistent with active network configurations.                                                                                                                                                                         | Functional     | Intersects With   | Network Device Configuration File Synchronization                                  | CFG-02.6 | Mechanisms exist to configure network devices to synchronize startup and running configuration files.                                                                                                                               | 5                        | NSCs cannot be defined or modified using untrusted configuration objects (including files).                                                                                                    |
| 1.2.8 | N/A      | Configuration files for NSCs are:<br>• Secured from unauthorized access.<br>• Kept consistent with active network configurations.                                                                                                                                                                         | Functional     | Intersects With   | Access Restriction For Change                                                      | CHG-04   | Mechanisms exist to enforce configuration restrictions in an effort to restrict the ability of users to conduct unauthorized changes.                                                                                               | 5                        | NSCs cannot be defined or modified using untrusted configuration objects (including files).                                                                                                    |
| 1.2.8 | N/A      | Configuration files for NSCs are:<br>• Secured from unauthorized access.<br>• Kept consistent with active network configurations.                                                                                                                                                                         | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                           | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                     | 5                        | NSCs cannot be defined or modified using untrusted configuration objects (including files).                                                                                                    |
| 1.2.8 | N/A      | Configuration files for NSCs are:<br>• Secured from unauthorized access.<br>• Kept consistent with active network configurations.                                                                                                                                                                         | Functional     | Intersects With   | DMZ Networks                                                                       | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                        | 5                        | NSCs cannot be defined or modified using untrusted configuration objects (including files).                                                                                                    |
| 1.3.1 | N/A      | Inbound traffic to the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                               | Functional     | Intersects With   | Data Flow Enforcement - Access Control Lists (ACLs)                                | NET-04   | Mechanisms exist to implement and govern Access Control Lists (ACLs) to provide data flow enforcement that explicitly restrict network traffic to only what is authorized.                                                          | 5                        | Unauthorized traffic cannot enter the CDE.                                                                                                                                                     |
| 1.3.1 | N/A      | Inbound traffic to the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                               | Functional     | Intersects With   | Deny Traffic by Default & Allow Traffic by Exception                               | NET-04.1 | Mechanisms exist to configure firewall and router configurations to deny network traffic by default and allow network traffic by exception (e.g., deny all, permit by exception).                                                   | 5                        | Unauthorized traffic cannot enter the CDE.                                                                                                                                                     |
| 1.3.1 | N/A      | Inbound traffic to the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                               | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                           | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                     | 5                        | Unauthorized traffic cannot enter the CDE.                                                                                                                                                     |
| 1.3.1 | N/A      | Inbound traffic to the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                               | Functional     | Intersects With   | DMZ Networks                                                                       | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                        | 5                        | Unauthorized traffic cannot enter the CDE.                                                                                                                                                     |
| 1.3.2 | N/A      | Outbound traffic from the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                            | Functional     | Intersects With   | Prevent Unauthorized Exfiltration                                                  | NET-03.5 | Automated mechanisms exist to prevent the unauthorized exfiltration of sensitive and/or regulated data across managed interfaces.                                                                                                   | 5                        | Unauthorized traffic cannot leave the CDE.                                                                                                                                                     |
| 1.3.2 | N/A      | Outbound traffic from the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                            | Functional     | Intersects With   | Data Flow Enforcement - Access Control Lists (ACLs)                                | NET-04   | Mechanisms exist to implement and govern Access Control Lists (ACLs) to provide data flow enforcement that explicitly restrict network traffic to only what is authorized.                                                          | 5                        | Unauthorized traffic cannot leave the CDE.                                                                                                                                                     |
| 1.3.2 | N/A      | Outbound traffic from the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                            | Functional     | Intersects With   | Deny Traffic by Default & Allow Traffic by Exception                               | NET-04.1 | Mechanisms exist to configure firewall and router configurations to deny network traffic by default and allow network traffic by exception (e.g., deny all, permit by exception).                                                   | 5                        | Unauthorized traffic cannot leave the CDE.                                                                                                                                                     |
| 1.3.2 | N/A      | Outbound traffic from the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                            | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                           | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                     | 5                        | Unauthorized traffic cannot leave the CDE.                                                                                                                                                     |
| 1.3.2 | N/A      | Outbound traffic from the CDE is restricted as follows:<br>• To only traffic that is necessary.<br>• All other traffic is specifically denied.                                                                                                                                                            | Functional     | Intersects With   | DMZ Networks                                                                       | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                        | 5                        | Unauthorized traffic cannot leave the CDE.                                                                                                                                                     |
| 1.3.3 | N/A      | NSCs are installed between all wireless networks and the CDE, regardless of whether the wireless network is a CDE, such that:<br>• All wireless traffic from wireless networks into the CDE is denied by default.<br>• Only wireless traffic with an authorized business purpose is allowed into the CDE. | Functional     | Intersects With   | Guest Networks                                                                     | NET-02.2 | Mechanisms exist to implement and manage a secure guest network.                                                                                                                                                                    | 5                        | Unauthorized traffic cannot traverse network boundaries between any wireless networks and wired environments in the CDE.                                                                       |
| 1.3.3 | N/A      | NSCs are installed between all wireless networks and the CDE, regardless of whether the wireless network is a CDE, such that:<br>• All wireless traffic from wireless networks into the CDE is denied by default.<br>• Only wireless traffic with an authorized business purpose is allowed into the CDE. | Functional     | Intersects With   | Boundary Protection                                                                | NET-03   | Mechanisms exist to monitor and control communications at the external network boundary and at key internal boundaries within the network.                                                                                          | 5                        | Unauthorized traffic cannot traverse network boundaries between any wireless networks and wired environments in the CDE.                                                                       |
| 1.3.3 | N/A      | NSCs are installed between all wireless networks and the CDE, regardless of whether the wireless network is a CDE, such that:<br>• All wireless traffic from wireless networks into the CDE is denied by default.<br>• Only wireless traffic with an authorized business purpose is allowed into the CDE. | Functional     | Intersects With   | Isolation of System Components                                                     | NET-03.7 | Mechanisms exist to employ boundary protections to isolate Technology Assets, Applications and/or Services (TAAS) that support critical missions and/or business functions.                                                         | 5                        | Unauthorized traffic cannot traverse network boundaries between any wireless networks and wired environments in the CDE.                                                                       |
| 1.3.3 | N/A      | NSCs are installed between all wireless networks and the CDE, regardless of whether the wireless network is a CDE, such that:<br>• All wireless traffic from wireless networks into the CDE is denied by default.<br>• Only wireless traffic with an authorized business purpose is allowed into the CDE. | Functional     | Intersects With   | Deny Traffic by Default & Allow Traffic by Exception                               | NET-04.1 | Mechanisms exist to configure firewall and router configurations to deny network traffic by default and allow network traffic by exception (e.g., deny all, permit by exception).                                                   | 5                        | Unauthorized traffic cannot traverse network boundaries between any wireless networks and wired environments in the CDE.                                                                       |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                    | STRM Rationale | STRM Relationship | SCF Control                                                                | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                             | Strength of Relationship | Notes                                                                                                                                                     |
|-------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|----------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.3.3 | N/A      | NSCs are installed between all wireless networks and the CDE, regardless of whether the wireless network is a CDE, such that:<br>• All wireless traffic from wireless networks into the CDE is denied by default.<br>• Only wireless traffic with an authorized business purpose is allowed into the CDE.                                    | Functional     | Intersects With   | Policy Decision Point (PDP)                                                | NET-04.7 | Automated mechanisms exist to evaluate access requests against established criteria to dynamically and uniformly enforce access rights and permissions.                                                                                                                                         | 5                        | Unauthorized traffic cannot traverse network boundaries between any wireless networks and wired environments in the CDE.                                  |
| 1.3.3 | N/A      | NSCs are installed between all wireless networks and the CDE, regardless of whether the wireless network is a CDE, such that:<br>• All wireless traffic from wireless networks into the CDE is denied by default.<br>• Only wireless traffic with an authorized business purpose is allowed into the CDE.                                    | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                   | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                                                                                 | 5                        | Unauthorized traffic cannot traverse network boundaries between any wireless networks and wired environments in the CDE.                                  |
| 1.3.3 | N/A      | NSCs are installed between all wireless networks and the CDE, regardless of whether the wireless network is a CDE, such that:<br>• All wireless traffic from wireless networks into the CDE is denied by default.<br>• Only wireless traffic with an authorized business purpose is allowed into the CDE.                                    | Functional     | Intersects With   | DMZ Networks                                                               | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                                                                                    | 5                        | Unauthorized traffic cannot traverse network boundaries between any wireless networks and wired environments in the CDE.                                  |
| 1.3.3 | N/A      | NSCs are installed between all wireless networks and the CDE, regardless of whether the wireless network is a CDE, such that:<br>• All wireless traffic from wireless networks into the CDE is denied by default.<br>• Only wireless traffic with an authorized business purpose is allowed into the CDE.                                    | Functional     | Intersects With   | Wireless Link Protection                                                   | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for unauthorized wireless access points and taking appropriate action, if an unauthorized connection is discovered. | 5                        | Unauthorized traffic cannot traverse network boundaries between any wireless networks and wired environments in the CDE.                                  |
| 1.4.1 | N/A      | NSCs are implemented between trusted and untrusted networks.                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Least Functionality                                                        | CFG-03   | Mechanisms exist to configure systems to provide only essential capabilities by specifically prohibiting or restricting the use of ports, protocols, and/or services.                                                                                                                           | 5                        | Unauthorized traffic cannot traverse network boundaries between trusted and untrusted networks.                                                           |
| 1.4.1 | N/A      | NSCs are implemented between trusted and untrusted networks.                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Layered Network Defenses                                                   | NET-02   | Mechanisms exist to implement security functions as a layered structure that minimizes interactions between layers of the design and avoids any dependence by lower layers on the functionality or correctness of higher layers.                                                                | 5                        | Unauthorized traffic cannot traverse network boundaries between trusted and untrusted networks.                                                           |
| 1.4.1 | N/A      | NSCs are implemented between trusted and untrusted networks.                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Boundary Protection                                                        | NET-03   | Mechanisms exist to monitor and control communications at the external network boundary and at key internal boundaries within the network.                                                                                                                                                      | 5                        | Unauthorized traffic cannot traverse network boundaries between trusted and untrusted networks.                                                           |
| 1.4.1 | N/A      | NSCs are implemented between trusted and untrusted networks.                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Separate Subnet for Connecting to Different Security Domains               | NET-03.8 | Mechanisms exist to implement separate network addresses (e.g., different subnets) to connect to systems in different security domains.                                                                                                                                                         | 5                        | Unauthorized traffic cannot traverse network boundaries between trusted and untrusted networks.                                                           |
| 1.4.1 | N/A      | NSCs are implemented between trusted and untrusted networks.                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                   | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                                                                                 | 5                        | Unauthorized traffic cannot traverse network boundaries between trusted and untrusted networks.                                                           |
| 1.4.1 | N/A      | NSCs are implemented between trusted and untrusted networks.                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | DMZ Networks                                                               | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                                                                                    | 5                        | Unauthorized traffic cannot traverse network boundaries between trusted and untrusted networks.                                                           |
| 1.4.1 | N/A      | NSCs are implemented between trusted and untrusted networks.                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Session Integrity                                                          | NET-09   | Mechanisms exist to protect the authenticity and integrity of communications sessions.                                                                                                                                                                                                          | 5                        | Unauthorized traffic cannot traverse network boundaries between trusted and untrusted networks.                                                           |
| 1.4.1 | N/A      | NSCs are implemented between trusted and untrusted networks.                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Defense-In-Depth (DID) Architecture                                        | SEA-03   | Mechanisms exist to implement security functions as a layered structure minimizing interactions between layers of the design and avoiding any dependence by lower layers on the functionality or correctness of higher layers.                                                                  | 5                        | Unauthorized traffic cannot traverse network boundaries between trusted and untrusted networks.                                                           |
| 1.4.2 | N/A      | Inbound traffic from untrusted networks to trusted networks is restricted to:<br>• Communications with system components that are authorized to provide publicly accessible services, protocols, and ports.<br>• Stateful responses to communications initiated by system components in a trusted network.<br>• All other traffic is denied. | Functional     | Intersects With   | Network Segmentation (macrosegmentation)                                   | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                                                                                 | 5                        | Only traffic that is authorized or that is a response to a system component in the trusted network can enter a trusted network from an untrusted network. |
| 1.4.2 | N/A      | Inbound traffic from untrusted networks to trusted networks is restricted to:<br>• Communications with system components that are authorized to provide publicly accessible services, protocols, and ports.<br>• Stateful responses to communications initiated by system components in a trusted network.<br>• All other traffic is denied. | Functional     | Intersects With   | DMZ Networks                                                               | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                                                                                                                    | 5                        | Only traffic that is authorized or that is a response to a system component in the trusted network can enter a trusted network from an untrusted network. |
| 1.4.2 | N/A      | Inbound traffic from untrusted networks to trusted networks is restricted to:<br>• Communications with system components that are authorized to provide publicly accessible services, protocols, and ports.<br>• Stateful responses to communications initiated by system components in a trusted network.<br>• All other traffic is denied. | Functional     | Intersects With   | Limit Network Connections                                                  | NET-03.1 | Mechanisms exist to limit the number of concurrent external network connections to its Technology Assets, Applications and/or Services (TAAS).                                                                                                                                                  | 5                        | Only traffic that is authorized or that is a response to a system component in the trusted network can enter a trusted network from an untrusted network. |
| 1.4.2 | N/A      | Inbound traffic from untrusted networks to trusted networks is restricted to:<br>• Communications with system components that are authorized to provide publicly accessible services, protocols, and ports.<br>• Stateful responses to communications initiated by system components in a trusted network.<br>• All other traffic is denied. | Functional     | Intersects With   | Data Flow Enforcement – Access Control Lists (ACLs)                        | NET-04   | Mechanisms exist to implement and govern Access Control Lists (ACLs) to provide data flow enforcement that explicitly restrict network traffic to only what is authorized.                                                                                                                      | 5                        | Only traffic that is authorized or that is a response to a system component in the trusted network can enter a trusted network from an untrusted network. |
| 1.4.2 | N/A      | Inbound traffic from untrusted networks to trusted networks is restricted to:<br>• Communications with system components that are authorized to provide publicly accessible services, protocols, and ports.<br>• Stateful responses to communications initiated by system components in a trusted network.<br>• All other traffic is denied. | Functional     | Intersects With   | Boundary Protection                                                        | NET-03   | Mechanisms exist to monitor and control communications at the external network boundary and at key internal boundaries within the network.                                                                                                                                                      | 5                        | Only traffic that is authorized or that is a response to a system component in the trusted network can enter a trusted network from an untrusted network. |
| 1.4.2 | N/A      | Inbound traffic from untrusted networks to trusted networks is restricted to:<br>• Communications with system components that are authorized to provide publicly accessible services, protocols, and ports.<br>• Stateful responses to communications initiated by system components in a trusted network.<br>• All other traffic is denied. | Functional     | Intersects With   | Deny Traffic by Default & Allow Traffic by Exception                       | NET-04.1 | Mechanisms exist to configure firewall and router configurations to deny network traffic by default and allow network traffic by exception (e.g., deny all, permit by exception).                                                                                                               | 5                        | Only traffic that is authorized or that is a response to a system component in the trusted network can enter a trusted network from an untrusted network. |
| 1.4.2 | N/A      | Inbound traffic from untrusted networks to trusted networks is restricted to:<br>• Communications with system components that are authorized to provide publicly accessible services, protocols, and ports.<br>• Stateful responses to communications initiated by system components in a trusted network.<br>• All other traffic is denied. | Functional     | Intersects With   | Least Functionality                                                        | CFG-03   | Mechanisms exist to configure systems to provide only essential capabilities by specifically prohibiting or restricting the use of ports, protocols, and/or services.                                                                                                                           | 5                        | Only traffic that is authorized or that is a response to a system component in the trusted network can enter a trusted network from an untrusted network. |
| 1.4.3 | N/A      | Anti-spoofing measures are implemented to detect and block forged source IP addresses from entering the trusted network.                                                                                                                                                                                                                     | Functional     | Intersects With   | Intrusion Detection & Prevention Systems (IDS / IPS)                       | MON-01.1 | Mechanisms exist to implement Intrusion Detection / Prevention Systems (IDS / IPS) technologies on critical systems, key network segments and network choke points.                                                                                                                             | 5                        | Packets with forged IP source addresses cannot enter a trusted network.                                                                                   |
| 1.4.3 | N/A      | Anti-spoofing measures are implemented to detect and block forged source IP addresses from entering the trusted network.                                                                                                                                                                                                                     | Functional     | Intersects With   | Data Flow Enforcement – Access Control Lists (ACLs)                        | NET-04   | Mechanisms exist to implement and govern Access Control Lists (ACLs) to provide data flow enforcement that explicitly restrict network traffic to only what is authorized.                                                                                                                      | 5                        | Packets with forged IP source addresses cannot enter a trusted network.                                                                                   |
| 1.4.3 | N/A      | Anti-spoofing measures are implemented to detect and block forged source IP addresses from entering the trusted network.                                                                                                                                                                                                                     | Functional     | Intersects With   | Network Intrusion Detection / Prevention Systems (NIDS / NIPS)             | NET-08   | Mechanisms exist to employ Network Intrusion Detection / Prevention Systems (NIDS/NIPS) to detect and/or prevent intrusions into the network.                                                                                                                                                   | 5                        | Packets with forged IP source addresses cannot enter a trusted network.                                                                                   |
| 1.4.3 | N/A      | Anti-spoofing measures are implemented to detect and block forged source IP addresses from entering the trusted network.                                                                                                                                                                                                                     | Functional     | Intersects With   | Wireless Intrusion Detection / Prevention Systems (WIDS / WIPS) Deployment | NET-08.2 | Mechanisms exist to utilize Wireless Intrusion Detection / Protection Systems (WIDS / WIPS) on wireless network segments.                                                                                                                                                                       | 5                        | Packets with forged IP source addresses cannot enter a trusted network.                                                                                   |
| 1.4.4 | N/A      | System components that store cardholder data are not directly accessible from untrusted networks.                                                                                                                                                                                                                                            | Functional     | Intersects With   | Publicly Accessible Content                                                | DCH-15   | Mechanisms exist to control publicly-accessible content.                                                                                                                                                                                                                                        | 5                        | Stored cardholder data cannot be accessed from untrusted networks.                                                                                        |
| 1.4.4 | N/A      | System components that store cardholder data are not directly accessible from untrusted networks.                                                                                                                                                                                                                                            | Functional     | Intersects With   | External System Connections                                                | NET-05.1 | Mechanisms exist to prohibit the direct connection of a sensitive system to an external network without the use of an organization-defined boundary protection device.                                                                                                                          | 5                        | Stored cardholder data cannot be accessed from untrusted networks.                                                                                        |
| 1.4.5 | N/A      | The disclosure of internal IP addresses and routing information is limited to only authorized parties.                                                                                                                                                                                                                                       | Functional     | Intersects With   | Prevent Discovery of Internal Information                                  | NET-03.3 | Mechanisms exist to prevent the public disclosure of internal network information.                                                                                                                                                                                                              | 5                        | Internal network information is protected from unauthorized disclosure.                                                                                   |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | STRM Rationale | STRM Relationship | SCF Control                                                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                      | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|-------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1.4.5 | N/A      | The disclosure of internal IP addresses and routing information is limited to only authorized parties.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Acceptable Discoverable Information                                                  | VPM-06.8 | Mechanisms exist to define what information is allowed to be discoverable by adversaries and take corrective actions to remediate non-compliant Technology Assets, Applications and/or Services (TAAS).                                                                                                                                                                                                                                  | 5                        | Internal network information is protected from unauthorized disclosure.                                                                                                                                                                 |
| 1.5.1 | N/A      | Security controls are implemented on any computing devices, including company- and employee-owned devices, that connect to both untrusted networks (including the Internet) and the CDE as follows: <ul style="list-style-type: none"> <li>Specific configuration settings are defined to prevent threats being introduced into the entity's network.</li> <li>Security controls are actively running.</li> <li>Security controls are not alterable by users of the computing devices unless specifically documented and authorized by management on a case-by-case basis for a limited period.</li> </ul> | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                                                                                                                                                                                                          | 5                        | Devices that connect to untrusted environments and also connect to the CDE cannot introduce threats to the entity's CDE.                                                                                                                |
| 1.5.1 | N/A      | Security controls are implemented on any computing devices, including company- and employee-owned devices, that connect to both untrusted networks (including the Internet) and the CDE as follows: <ul style="list-style-type: none"> <li>Specific configuration settings are defined to prevent threats being introduced into the entity's network.</li> <li>Security controls are actively running.</li> <li>Security controls are not alterable by users of the computing devices unless specifically documented and authorized by management on a case-by-case basis for a limited period.</li> </ul> | Functional     | Intersects With   | Split Tunneling                                                                      | CFG-03.4 | Mechanisms exist to prevent split tunneling for remote devices unless the split tunnel is securely provisioned using organization-defined safeguards.                                                                                                                                                                                                                                                                                    | 5                        | Devices that connect to untrusted environments and also connect to the CDE cannot introduce threats to the entity's CDE.                                                                                                                |
| 1.5.1 | N/A      | Security controls are implemented on any computing devices, including company- and employee-owned devices, that connect to both untrusted networks (including the Internet) and the CDE as follows: <ul style="list-style-type: none"> <li>Specific configuration settings are defined to prevent threats being introduced into the entity's network.</li> <li>Security controls are actively running.</li> <li>Security controls are not alterable by users of the computing devices unless specifically documented and authorized by management on a case-by-case basis for a limited period.</li> </ul> | Functional     | Intersects With   | Limits of Authorized Use                                                             | DCH-13.1 | Mechanisms exist to prohibit external parties, including Technology Assets, Applications and/or Services (TAAS), from storing, processing and transmitting data unless authorized individuals first: <ol style="list-style-type: none"> <li>Verifying the implementation of required security, compliance and/or resilience controls; or</li> <li>Retaining a processing agreement with the entity hosting the external TAAS.</li> </ol> | 5                        | Devices that connect to untrusted environments and also connect to the CDE cannot introduce threats to the entity's CDE.                                                                                                                |
| 1.5.1 | N/A      | Security controls are implemented on any computing devices, including company- and employee-owned devices, that connect to both untrusted networks (including the Internet) and the CDE as follows: <ul style="list-style-type: none"> <li>Specific configuration settings are defined to prevent threats being introduced into the entity's network.</li> <li>Security controls are actively running.</li> <li>Security controls are not alterable by users of the computing devices unless specifically documented and authorized by management on a case-by-case basis for a limited period.</li> </ul> | Functional     | Subset Of         | Endpoint Device Management (EDM)                                                     | END-01   | Mechanisms exist to facilitate the implementation of Endpoint Device Management (EDM) controls.                                                                                                                                                                                                                                                                                                                                          | 10                       | Devices that connect to untrusted environments and also connect to the CDE cannot introduce threats to the entity's CDE.                                                                                                                |
| 1.5.1 | N/A      | Security controls are implemented on any computing devices, including company- and employee-owned devices, that connect to both untrusted networks (including the Internet) and the CDE as follows: <ul style="list-style-type: none"> <li>Specific configuration settings are defined to prevent threats being introduced into the entity's network.</li> <li>Security controls are actively running.</li> <li>Security controls are not alterable by users of the computing devices unless specifically documented and authorized by management on a case-by-case basis for a limited period.</li> </ul> | Functional     | Intersects With   | Endpoint Protection Measures                                                         | END-02   | Mechanisms exist to protect the confidentiality, integrity, availability and safety of endpoint devices.                                                                                                                                                                                                                                                                                                                                 | 5                        | Devices that connect to untrusted environments and also connect to the CDE cannot introduce threats to the entity's CDE.                                                                                                                |
| 1.5.1 | N/A      | Security controls are implemented on any computing devices, including company- and employee-owned devices, that connect to both untrusted networks (including the Internet) and the CDE as follows: <ul style="list-style-type: none"> <li>Specific configuration settings are defined to prevent threats being introduced into the entity's network.</li> <li>Security controls are actively running.</li> <li>Security controls are not alterable by users of the computing devices unless specifically documented and authorized by management on a case-by-case basis for a limited period.</li> </ul> | Functional     | Intersects With   | Software Firewall                                                                    | END-05   | Mechanisms exist to utilize host-based firewall software, or a similar technology, on all endpoint devices, where technically feasible.                                                                                                                                                                                                                                                                                                  | 5                        | Devices that connect to untrusted environments and also connect to the CDE cannot introduce threats to the entity's CDE.                                                                                                                |
| 2.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 2 are: <ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation                           | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                                                                                                                                                                                                   | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 2 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 2.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 2 are: <ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program                | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPP), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness.                                                                                                                                                                                 | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 2 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 2.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 2 are: <ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                | Functional     | Subset Of         | Operations Security                                                                  | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                                                                                                                                                                                                                      | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 2 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 2.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 2 are: <ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                                              | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                                                                                                                                                                                                              | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 2 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 2.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 2 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Defined Roles & Responsibilities                                                     | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                                                                                                                                                                                                     | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 2 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 2.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 2 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | User Awareness                                                                       | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                                                                                                                                                                                                     | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 2 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 2.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 2 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities                          | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPP).                                                                                                                                                                                                       | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 2 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 2.2.1 | N/A      | Configuration standards are developed, implemented, and maintained to: <ul style="list-style-type: none"> <li>Cover all system components.</li> <li>Address all known security vulnerabilities.</li> <li>Be consistent with industry-accepted system hardening standards or vendor hardening recommendations.</li> <li>Be updated as new vulnerability issues are identified, as defined in Requirement 6.3.1.</li> <li>Be applied when new systems are configured and verified as in place before or immediately after a system component is connected to a production environment.</li> </ul>            | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                                                                                                                                                                                                      | 5                        | All system components are configured securely and consistently and in accordance with industry-accepted hardening standards or vendor recommendations.                                                                                  |
| 2.2.2 | N/A      | Vendor default accounts are managed as follows: <ul style="list-style-type: none"> <li>If the vendor default account(s) will be used, the default password is changed per Requirement 8.3.6.</li> <li>If the vendor default account(s) will not be used, the account is removed or disabled.</li> </ul>                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Asset Ownership Assignment                                                           | AST-03   | Mechanisms exist to ensure asset ownership responsibilities are assigned, tracked and managed at a team, individual, or responsible organization level to establish a common understanding of requirements for asset protection.                                                                                                                                                                                                         | 5                        | System components cannot be accessed using default passwords.                                                                                                                                                                           |
| 2.2.2 | N/A      | Vendor default accounts are managed as follows: <ul style="list-style-type: none"> <li>If the vendor default account(s) will be used, the default password is changed per Requirement 8.3.6.</li> <li>If the vendor default account(s) will not be used, the account is removed or disabled.</li> </ul>                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Default Authenticators                                                               | IAC-10.8 | Mechanisms exist to ensure default authenticators are changed as part of account creation or system installation.                                                                                                                                                                                                                                                                                                                        | 5                        | System components cannot be accessed using default passwords.                                                                                                                                                                           |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                             | STRM Rationale | STRM Relationship | SCF Control                                                | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                             | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|-------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 2.2.3 | N/A      | Primary functions requiring different security levels are managed as follows:<br>• Only one primary function exists on a system component, OR<br>• Primary functions with differing security levels that exist on the same system component are isolated from each other, OR<br>• Primary functions with differing security levels on the same system component are all secured to the level required by the function with the highest security need. | Functional     | Intersects With   | Restrict Access To Security Functions                      | END-16   | Mechanisms exist to ensure security functions are restricted to authorized individuals and enforce least privilege control requirements for necessary job functions.                                                                                                                            | 5                        | Primary functions with lower security needs cannot affect the security of primary functions with higher security needs on the same system component.                                                                                    |
| 2.2.3 | N/A      | Primary functions requiring different security levels are managed as follows:<br>• Only one primary function exists on a system component, OR<br>• Primary functions with differing security levels that exist on the same system component are isolated from each other, OR<br>• Primary functions with differing security levels on the same system component are all secured to the level required by the function with the highest security need. | Functional     | Intersects With   | Host-Based Security Function Isolation                     | END-16.1 | Mechanisms exist to implement underlying software separation mechanisms to facilitate security function isolation.                                                                                                                                                                              | 5                        | Primary functions with lower security needs cannot affect the security of primary functions with higher security needs on the same system component.                                                                                    |
| 2.2.3 | N/A      | Primary functions requiring different security levels are managed as follows:<br>• Only one primary function exists on a system component, OR<br>• Primary functions with differing security levels that exist on the same system component are isolated from each other, OR<br>• Primary functions with differing security levels on the same system component are all secured to the level required by the function with the highest security need. | Functional     | Intersects With   | Security Function Isolation                                | SEA-04.1 | Mechanisms exist to isolate security functions from non-security functions.                                                                                                                                                                                                                     | 5                        | Primary functions with lower security needs cannot affect the security of primary functions with higher security needs on the same system component.                                                                                    |
| 2.2.4 | N/A      | Only necessary services, protocols, daemons, and functions are enabled, and all unnecessary functionality is removed or disabled.                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Asset Ownership Assignment                                 | AST-03   | Mechanisms exist to ensure asset ownership responsibilities are assigned, tracked and managed at a team, individual, or responsible organization level to establish a common                                                                                                                    | 5                        | System components cannot be compromised by exploiting unnecessary functionality present in the system component.                                                                                                                        |
| 2.2.4 | N/A      | Only necessary services, protocols, daemons, and functions are enabled, and all unnecessary functionality is removed or disabled.                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Least Functionality                                        | CFG-03   | Mechanisms exist to configure systems to provide only essential capabilities by specifically prohibiting or restricting the use of ports, protocols, and/or services.                                                                                                                           | 5                        | System components cannot be compromised by exploiting unnecessary functionality present in the system component.                                                                                                                        |
| 2.2.4 | N/A      | Only necessary services, protocols, daemons, and functions are enabled, and all unnecessary functionality is removed or disabled.                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Compensating Countermeasures                               | RSK-06.2 | Mechanisms exist to identify and implement compensating countermeasures to reduce risk and exposure to threats.                                                                                                                                                                                 | 5                        | System components cannot be compromised by exploiting unnecessary functionality present in the system component.                                                                                                                        |
| 2.2.5 | N/A      | If any insecure services, protocols, or daemons are present:<br>• Business justification is documented.<br>• Additional security features are documented and implemented that reduce the risk of using insecure services, protocols, or daemons.                                                                                                                                                                                                      | Functional     | Intersects With   | Asset Ownership Assignment                                 | AST-03   | Mechanisms exist to ensure asset ownership responsibilities are assigned, tracked and managed at a team, individual, or responsible organization level to establish a common understanding of requirements for asset protection.                                                                | 5                        | System components cannot be compromised by exploiting insecure services, protocols, or daemons.                                                                                                                                         |
| 2.2.5 | N/A      | If any insecure services, protocols, or daemons are present:<br>• Business justification is documented.<br>• Additional security features are documented and implemented that reduce the risk of using insecure services, protocols, or daemons.                                                                                                                                                                                                      | Functional     | Intersects With   | Insecure Ports, Protocols & Services                       | TDA-02.6 | Mechanisms exist to mitigate the risk associated with the use of insecure ports, protocols and services necessary to operate technology solutions.                                                                                                                                              | 5                        | System components cannot be compromised by exploiting insecure services, protocols, or daemons.                                                                                                                                         |
| 2.2.6 | N/A      | System security parameters are configured to prevent misuse.                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Physical Diagnostic & Test Interfaces                      | TDA-05.1 | Mechanisms exist to secure physical diagnostic and test interfaces to prevent misuse.                                                                                                                                                                                                           | 5                        | System components cannot be compromised because of incorrect security parameter configuration.                                                                                                                                          |
| 2.2.7 | N/A      | All non-console administrative access is encrypted using strong cryptography.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Subset Of         | Use of Cryptographic Controls                              | CRY-01   | Mechanisms exist to facilitate the implementation of cryptographic protections controls using known public standards and trusted cryptographic technologies.                                                                                                                                    | 10                       | Cleartext administrative authorization factors cannot be read or intercepted from any network transmissions.                                                                                                                            |
| 2.2.7 | N/A      | All non-console administrative access is encrypted using strong cryptography.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Automated Authentication Through Cryptographic             | CRY-02   | Automated mechanisms exist to enable systems to authenticate to a cryptographic module.                                                                                                                                                                                                         | 5                        | Cleartext administrative authorization factors cannot be read or intercepted from any network transmissions.                                                                                                                            |
| 2.2.7 | N/A      | All non-console administrative access is encrypted using strong cryptography.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Non-Console Administrative Access                          | CRY-06   | Cryptographic mechanisms exist to protect the confidentiality and integrity of non-console administrative access.                                                                                                                                                                               | 5                        | Cleartext administrative authorization factors cannot be read or intercepted from any network transmissions.                                                                                                                            |
| 2.2.7 | N/A      | All non-console administrative access is encrypted using strong cryptography.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Remote Maintenance Cryptographic Protection                | MNT-05.3 | Cryptographic mechanisms exist to protect the integrity and confidentiality of remote, non-local maintenance and diagnostic communications.                                                                                                                                                     | 5                        | Cleartext administrative authorization factors cannot be read or intercepted from any network transmissions.                                                                                                                            |
| 2.3.1 | N/A      | For wireless environments connected to the CDE or transmitting account data, all wireless vendor defaults are changed at installation or are confirmed to be secure, including but not limited to:<br>• Default wireless encryption keys.<br>• Passwords on wireless access points.<br>• SNMP defaults.<br>• Any other security-related wireless vendor defaults.                                                                                     | Functional     | Intersects With   | Wireless Access Authentication & Encryption                | CRY-07   | Mechanisms exist to protect the confidentiality and integrity of wireless networking technologies by implementing authentication and strong encryption.                                                                                                                                         | 5                        | Wireless networks cannot be accessed using vendor default passwords or default configurations.                                                                                                                                          |
| 2.3.1 | N/A      | For wireless environments connected to the CDE or transmitting account data, all wireless vendor defaults are changed at installation or are confirmed to be secure, including but not limited to:<br>• Default wireless encryption keys.<br>• Passwords on wireless access points.<br>• SNMP defaults.<br>• Any other security-related wireless vendor defaults.                                                                                     | Functional     | Intersects With   | Default Authenticators                                     | IAC-10.8 | Mechanisms exist to ensure default authenticators are changed as part of account creation or system installation.                                                                                                                                                                               | 5                        | Wireless networks cannot be accessed using vendor default passwords or default configurations.                                                                                                                                          |
| 2.3.1 | N/A      | For wireless environments connected to the CDE or transmitting account data, all wireless vendor defaults are changed at installation or are confirmed to be secure, including but not limited to:<br>• Default wireless encryption keys.<br>• Passwords on wireless access points.<br>• SNMP defaults.<br>• Any other security-related wireless vendor defaults.                                                                                     | Functional     | Intersects With   | Wireless Link Protection                                   | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for unauthorized wireless access points and taking appropriate action, if an unauthorized connection is discovered. | 5                        | Wireless networks cannot be accessed using vendor default passwords or default configurations.                                                                                                                                          |
| 2.3.1 | N/A      | For wireless environments connected to the CDE or transmitting account data, all wireless vendor defaults are changed at installation or are confirmed to be secure, including but not limited to:<br>• Default wireless encryption keys.<br>• Passwords on wireless access points.<br>• SNMP defaults.<br>• Any other security-related wireless vendor defaults.                                                                                     | Functional     | Intersects With   | Authentication & Encryption                                | NET-15.1 | Mechanisms exist to secure Wi-Fi (e.g., IEEE 802.11) and prevent unauthorized access by:<br>(1) Authenticating devices trying to connect; and<br>(2) Encrypting transmitted data.                                                                                                               | 5                        | Wireless networks cannot be accessed using vendor default passwords or default configurations.                                                                                                                                          |
| 2.3.2 | N/A      | For wireless environments connected to the CDE or transmitting account data, wireless encryption keys are changed as follows:<br>• Whenever personnel with knowledge of the key leave the company or the role for which the knowledge was necessary.<br>• Whenever a key is suspected of or known to be compromised.                                                                                                                                  | Functional     | Intersects With   | Wireless Access Authentication & Encryption                | CRY-07   | Mechanisms exist to protect the confidentiality and integrity of wireless networking technologies by implementing authentication and strong encryption.                                                                                                                                         | 5                        | Knowledge of wireless encryption keys cannot allow unauthorized access to wireless networks.                                                                                                                                            |
| 2.3.2 | N/A      | For wireless environments connected to the CDE or transmitting account data, wireless encryption keys are changed as follows:<br>• Whenever personnel with knowledge of the key leave the company or the role for which the knowledge was necessary.<br>• Whenever a key is suspected of or known to be compromised.                                                                                                                                  | Functional     | Intersects With   | Cryptographic Key Loss or Change                           | CRY-09.3 | Mechanisms exist to ensure the availability of information in the event of the loss of cryptographic keys by individual users.                                                                                                                                                                  | 5                        | Knowledge of wireless encryption keys cannot allow unauthorized access to wireless networks.                                                                                                                                            |
| 2.3.2 | N/A      | For wireless environments connected to the CDE or transmitting account data, wireless encryption keys are changed as follows:<br>• Whenever personnel with knowledge of the key leave the company or the role for which the knowledge was necessary.<br>• Whenever a key is suspected of or known to be compromised.                                                                                                                                  | Functional     | Intersects With   | Wireless Link Protection                                   | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for unauthorized wireless access points and taking appropriate action, if an unauthorized connection is discovered. | 5                        | Knowledge of wireless encryption keys cannot allow unauthorized access to wireless networks.                                                                                                                                            |
| 2.3.2 | N/A      | For wireless environments connected to the CDE or transmitting account data, wireless encryption keys are changed as follows:<br>• Whenever personnel with knowledge of the key leave the company or the role for which the knowledge was necessary.<br>• Whenever a key is suspected of or known to be compromised.                                                                                                                                  | Functional     | Intersects With   | Authentication & Encryption                                | NET-15.1 | Mechanisms exist to secure Wi-Fi (e.g., IEEE 802.11) and prevent unauthorized access by:<br>(1) Authenticating devices trying to connect; and<br>(2) Encrypting transmitted data.                                                                                                               | 5                        | Knowledge of wireless encryption keys cannot allow unauthorized access to wireless networks.                                                                                                                                            |
| 3.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 3 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                                                          | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 3 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                      | Strength of Relationship | Notes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|---------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 3 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPP), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness. | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 3 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent.                                                                                                                                                                                                                                                                                        |
| 3.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 3 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Subset Of         | Operations Security                                                   | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                                      | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 3 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent.                                                                                                                                                                                                                                                                                        |
| 3.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 3 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                              | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 3 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent.                                                                                                                                                                                                                                                                                        |
| 3.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 3 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities           | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPP).                       | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 3 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                                                                                                                                                                                                                                                                                            |
| 3.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 3 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Defined Roles & Responsibilities                                      | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                     | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 3 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                                                                                                                                                                                                                                                                                            |
| 3.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 3 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | User Awareness                                                        | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                     | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 3 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                                                                                                                                                                                                                                                                                            |
| 3.2.1   | N/A      | Account data storage is kept to a minimum through implementation of data retention and disposal policies, procedures, and processes that include at least the following:<br>• Coverage for all locations of stored account data.<br>• Coverage for any sensitive authentication data (SAD) stored prior to completion of authorization. This bullet is a best practice until its effective date; refer to Applicability Notes below for details.<br>• Limiting data storage amount and retention time to that which is required for legal or regulatory, and/or business requirements.<br>• Specific retention requirements for stored account data that defines length of retention period and includes a documented business justification.<br>• Processes for secure deletion or rendering account data unrecoverable when no longer needed per the retention policy.<br>• A process for verifying, at least once every three months, that stored account data exceeding the defined retention period has been securely deleted or rendered unrecoverable. | Functional     | Intersects With   | Media & Data Retention                                                | DCH-18   | Mechanisms exist to retain media and data in accordance with applicable statutory, regulatory and contractual obligations.                                                                                                                               | 5                        | Account data is retained only where necessary and for the least amount of time needed and is securely deleted or rendered unrecoverable when no longer needed.                                                                                                                                                                                                                                                                                                                                                                 |
| 3.2.1   | N/A      | Account data storage is kept to a minimum through implementation of data retention and disposal policies, procedures, and processes that include at least the following:<br>• Coverage for all locations of stored account data.<br>• Coverage for any sensitive authentication data (SAD) stored prior to completion of authorization. This bullet is a best practice until its effective date; refer to Applicability Notes below for details.<br>• Limiting data storage amount and retention time to that which is required for legal or regulatory, and/or business requirements.<br>• Specific retention requirements for stored account data that defines length of retention period and includes a documented business justification.<br>• Processes for secure deletion or rendering account data unrecoverable when no longer needed per the retention policy.<br>• A process for verifying, at least once every three months, that stored account data exceeding the defined retention period has been securely deleted or rendered unrecoverable. | Functional     | Intersects With   | Third-Party Processing, Storage and Service Locations                 | TPM-04.4 | Mechanisms exist to restrict the location of information processing/storage based on business requirements.                                                                                                                                              | 5                        | Account data is retained only where necessary and for the least amount of time needed and is securely deleted or rendered unrecoverable when no longer needed.                                                                                                                                                                                                                                                                                                                                                                 |
| 3.3.1   | N/A      | SAD is not retained after authorization, even if encrypted. All sensitive authentication data received is rendered unrecoverable upon completion of the authorization process.<br>The card verification code is not retained upon completion of the authorization process.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Storing Authentication Data                                           | DCH-06.5 | Mechanisms exist to prohibit the storage of sensitive transaction authentication data after authorization.                                                                                                                                               | 5                        | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 3.3.1.2 | N/A      | The card verification code is not retained upon completion of the authorization process.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Storing Authentication Data                                           | DCH-06.5 | Mechanisms exist to prohibit the storage of sensitive transaction authentication data after authorization.                                                                                                                                               | 5                        | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 3.3.1.3 | N/A      | The personal identification number (PIN) and the PIN block are not retained upon completion of the authorization process.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Storing Authentication Data                                           | DCH-06.5 | Mechanisms exist to prohibit the storage of sensitive transaction authentication data after authorization.                                                                                                                                               | 5                        | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 3.3.2   | N/A      | SAD that is stored electronically prior to completion of authorization is encrypted using strong cryptography.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Subset Of         | Use of Cryptographic Controls                                         | CRY-01   | Mechanisms exist to facilitate the implementation of cryptographic protections controls using known public standards and trusted cryptographic technologies.                                                                                             | 10                       | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 3.3.2   | N/A      | SAD that is stored electronically prior to completion of authorization is encrypted using strong cryptography.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Encrypting Data At Rest                                               | CRY-05   | Cryptographic mechanisms exist to prevent unauthorized disclosure of data at rest.                                                                                                                                                                       | 5                        | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 3.4.1   | N/A      | PAN is masked when displayed (the BIN and last four digits are the maximum number of digits to be displayed), such that only personnel with a legitimate business need can see more than the BIN and last four digits of the PAN.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Masking Displayed Data                                                | DCH-03.2 | Mechanisms exist to apply data masking to sensitive and/or regulated information that is displayed or printed.                                                                                                                                           | 5                        | PAN displays are restricted to the minimum number of digits necessary to meet a defined business need.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 3.4.1   | N/A      | PAN is masked when displayed (the BIN and last four digits are the maximum number of digits to be displayed), such that only personnel with a legitimate business need can see more than the BIN and last four digits of the PAN.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Restrict Access To Security Functions                                 | END-16   | Mechanisms exist to ensure security functions are restricted to authorized individuals and enforce least privilege control requirements for necessary job functions.                                                                                     | 5                        | PAN displays are restricted to the minimum number of digits necessary to meet a defined business need.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 3.4.1   | N/A      | PAN is masked when displayed (the BIN and last four digits are the maximum number of digits to be displayed), such that only personnel with a legitimate business need can see more than the BIN and last four digits of the PAN.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Data Anonymization                                                    | PRI-05.3 | Mechanisms exist to mask sensitive and/or regulated data through data anonymization, pseudonymization, redaction and/or de-identification.                                                                                                               | 5                        | PAN displays are restricted to the minimum number of digits necessary to meet a defined business need.                                                                                                                                                                                                                                                                                                                                                                                                                         |
| 3.4.2   | N/A      | When using remote-access technologies, technical controls prevent copy and/or relocation of PAN for all personnel, except for those with documented, explicit authorization and a legitimate, defined business need.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Least Privilege                                                       | IAC-21   | Mechanisms exist to utilize the concept of least privilege, allowing only authorized access to processes necessary to accomplish assigned tasks in accordance with organizational business functions.                                                    | 5                        | PAN cannot be copied or relocated by unauthorized personnel using remote-access technologies.                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 3.4.2   | N/A      | When using remote-access technologies, technical controls prevent copy and/or relocation of PAN for all personnel, except for those with documented, explicit authorization and a legitimate, defined business need.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Remote Access                                                         | NET-14   | Mechanisms exist to define, control and review organization-approved, secure remote access methods.                                                                                                                                                      | 5                        | PAN cannot be copied or relocated by unauthorized personnel using remote-access technologies.                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| 3.5.1   | N/A      | PAN is rendered unreadable anywhere it is stored by using any of the following approaches:<br>• One-way hashes based on strong cryptography of the entire PAN.<br>• Truncation (hashing cannot be used to replace the truncated segment of PAN).<br>- If hashed and truncated versions of the same PAN, or different truncation formats of the same PAN, are present in an environment, additional controls are in place such that the different versions cannot be correlated to reconstruct the original PAN.<br>• Index tokens.<br>• Strong cryptography with associated key- management processes and procedures.                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Sensitive / Regulated Data Protection                                 | DCH-01.2 | Mechanisms exist to protect sensitive and/or regulated data wherever it is processed and/or stored.                                                                                                                                                      | 5                        | Cleartext PAN cannot be read from storage media.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| 3.5.1.1 | N/A      | Hashes used to render PAN unreadable (per the first bullet of Requirement 3.5.1) are keyed cryptographic hashes of the entire PAN, with associated key-management processes and procedures in accordance with Requirements 3.6 and 3.7.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Cryptographic Key Management                                          | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of                                                                                                                       | 5                        | This requirement applies to PANs stored in primary storage (databases, or flat files such as text files spreadsheets) as well as non-primary storage (backup, audit logs, exception, or troubleshooting logs) must all be protected. This requirement does not preclude the use of temporary files containing cleartext PAN while encrypting and decrypting PAN. This requirement is considered a best practice until 31 March 2025, after which it will be required and must be fully considered during a PCI DSS assessment. |



| NIST IR 8477-Based Set Theory Relationship Mapping (STRM)                                                                        |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                |                   |                                                            |          |                                                                                                                                                                             |                          |                                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Reference Document: Secure Controls Framework (SCF) version 2026.2                                                               |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                |                   |                                                            |          |                                                                                                                                                                             |                          |                                                                                                                                          |
| STRM Guidance: https://securecontrolframework.com/start-here/set-theory-relationship-mapping-strm/                               |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                |                   |                                                            |          |                                                                                                                                                                             |                          |                                                                                                                                          |
| Focal Document: Payment Card Industry Data Security Standard (PCI DSS) v4.0.1 - Self - Assessment Questionnaire (SAQ) D Merchant |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                |                   |                                                            |          |                                                                                                                                                                             |                          |                                                                                                                                          |
| Focal Document URL: https://least.pcisecuritystandards.org/document_library?category=pcids&document=pci_dss                      |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                |                   |                                                            |          |                                                                                                                                                                             |                          |                                                                                                                                          |
| Published STRM URL: https://content.securecontrolframework.com/strm/scf-strm-general-pci-dss-4-0-1-saq-d-merchant.pdf            |          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                |                   |                                                            |          |                                                                                                                                                                             |                          |                                                                                                                                          |
| FDE #                                                                                                                            | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | STRM Rationale | STRM Relationship | SCF Control                                                | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                         | Strength of Relationship | Notes                                                                                                                                    |
| 3.5.1.2                                                                                                                          | N/A      | If disk-level or partition-level encryption (rather than file-, column-, or field-level database encryption) is used to render PAN unreadable, it is implemented only as follows: <ul style="list-style-type: none"><li>On removable electronic media</li></ul> OR <ul style="list-style-type: none"><li>If used for non-removable electronic media, PAN is also rendered unreadable via another mechanism that meets Requirement 3.5.1.</li></ul>                                                                                                                                                       | Functional     | Intersects With   | Encrypting Data At Rest                                    | CRY-05   | Cryptographic mechanisms exist to prevent unauthorized disclosure of data at rest.                                                                                          | 5                        | This requirement is not eligible for the customized approach. (continued on next page)                                                   |
| 3.5.1.3                                                                                                                          | N/A      | If disk-level or partition-level encryption is used (rather than file-, column-, or field-level database encryption) to render PAN unreadable, it is managed as follows: <ul style="list-style-type: none"><li>Logical access is managed separately and independently of native operating system authentication and access control mechanisms.</li><li>Decryption keys are not associated with user accounts.</li><li>Authentication factors (passwords, passphrases, or cryptographic keys) that allow access to unencrypted data are stored securely.</li></ul>                                        | Functional     | Intersects With   | Encrypting Data At Rest                                    | CRY-05   | Cryptographic mechanisms exist to prevent unauthorized disclosure of data at rest.                                                                                          | 5                        | Disk encryption implementations are configured to require independent authentication and logical access controls for decryption.         |
| 3.6.1                                                                                                                            | N/A      | Procedures are defined and implemented to protect cryptographic keys used to protect stored account data against disclosure and misuse that include: <ul style="list-style-type: none"><li>Access to keys is restricted to the fewest number of custodians necessary.</li><li>Key-encrypting keys are at least as strong as the data-encrypting keys they protect.</li><li>Key-encrypting keys are stored separately from data-encrypting keys.</li><li>Keys are stored securely in the fewest possible locations and forms.</li></ul>                                                                   | Functional     | Intersects With   | Availability                                               | CRY-08.1 | Resiliency mechanisms exist to ensure the availability of data in the event of the loss of cryptographic keys.                                                              | 5                        | Processes that protect cryptographic keys used to protect stored account data against disclosure and misuse are defined and implemented. |
| 3.6.1                                                                                                                            | N/A      | Procedures are defined and implemented to protect cryptographic keys used to protect stored account data against disclosure and misuse that include: <ul style="list-style-type: none"><li>Access to keys is restricted to the fewest number of custodians necessary.</li><li>Key-encrypting keys are at least as strong as the data-encrypting keys they protect.</li><li>Key-encrypting keys are stored separately from data-encrypting keys.</li><li>Keys are stored securely in the fewest possible locations and forms.</li></ul>                                                                   | Functional     | Intersects With   | Cryptographic Key Management                               | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                    | 5                        | Processes that protect cryptographic keys used to protect stored account data against disclosure and misuse are defined and implemented. |
| 3.6.1                                                                                                                            | N/A      | Procedures are defined and implemented to protect cryptographic keys used to protect stored account data against disclosure and misuse that include: <ul style="list-style-type: none"><li>Access to keys is restricted to the fewest number of custodians necessary.</li><li>Key-encrypting keys are at least as strong as the data-encrypting keys they protect.</li><li>Key-encrypting keys are stored separately from data-encrypting keys.</li><li>Keys are stored securely in the fewest possible locations and forms.</li></ul>                                                                   | Functional     | Intersects With   | Cryptographic Key Loss or Change                           | CRY-09.3 | Mechanisms exist to ensure the availability of information in the event of the loss of cryptographic keys by individual users.                                              | 5                        | Processes that protect cryptographic keys used to protect stored account data against disclosure and misuse are defined and implemented. |
| 3.6.1                                                                                                                            | N/A      | Procedures are defined and implemented to protect cryptographic keys used to protect stored account data against disclosure and misuse that include: <ul style="list-style-type: none"><li>Access to keys is restricted to the fewest number of custodians necessary.</li><li>Key-encrypting keys are at least as strong as the data-encrypting keys they protect.</li><li>Key-encrypting keys are stored separately from data-encrypting keys.</li><li>Keys are stored securely in the fewest possible locations and forms.</li></ul>                                                                   | Functional     | Intersects With   | Control & Distribution of Cryptographic Keys               | CRY-09.4 | Mechanisms exist to facilitate the secure distribution of symmetric and asymmetric cryptographic keys using industry recognized key management technology and processes.    | 5                        | Processes that protect cryptographic keys used to protect stored account data against disclosure and misuse are defined and implemented. |
| 3.6.1.2                                                                                                                          | N/A      | Secret and private keys used to encrypt/decrypt stored account data are stored in one (or more) of the following forms at all times: <ul style="list-style-type: none"><li>Encrypted with a key-encrypting key that is at least as strong as the data-encrypting key, and that is stored separately from the data-encrypting key.</li><li>Within a secure cryptographic device (SCD), such as a hardware security module (HSM) or PITS-approved point-of-interaction device.</li><li>As at least two full-length key components or key shares, in accordance with an industry-accepted method.</li></ul> | Functional     | Intersects With   | Automated Authentication Through Cryptographic Modules     | CRY-02   | Automated mechanisms exist to enable systems to authenticate to a cryptographic module.                                                                                     | 5                        | Secret and private keys are stored in a secure form that prevents unauthorized retrieval or access.                                      |
| 3.6.1.2                                                                                                                          | N/A      | Secret and private keys used to encrypt/decrypt stored account data are stored in one (or more) of the following forms at all times: <ul style="list-style-type: none"><li>Encrypted with a key-encrypting key that is at least as strong as the data-encrypting key, and that is stored separately from the data-encrypting key.</li><li>Within a secure cryptographic device (SCD), such as a hardware security module (HSM) or PITS-approved point-of-interaction device.</li><li>As at least two full-length key components or key shares, in accordance with an industry-accepted method.</li></ul> | Functional     | Intersects With   | Cryptographic Key Management                               | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                    | 5                        | Secret and private keys are stored in a secure form that prevents unauthorized retrieval or access.                                      |
| 3.6.1.2                                                                                                                          | N/A      | Secret and private keys used to encrypt/decrypt stored account data are stored in one (or more) of the following forms at all times: <ul style="list-style-type: none"><li>Encrypted with a key-encrypting key that is at least as strong as the data-encrypting key, and that is stored separately from the data-encrypting key.</li><li>Within a secure cryptographic device (SCD), such as a hardware security module (HSM) or PITS-approved point-of-interaction device.</li><li>As at least two full-length key components or key shares, in accordance with an industry-accepted method.</li></ul> | Functional     | Intersects With   | Cryptographic Module Authentication                        | IAC-12   | Mechanisms exist to ensure cryptographic modules adhere to applicable statutory, regulatory and contractual requirements for security strength.                             | 5                        | Secret and private keys are stored in a secure form that prevents unauthorized retrieval or access.                                      |
| 3.6.1.3                                                                                                                          | N/A      | Access to cleartext cryptographic key components is restricted to the fewest number of custodians necessary.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Cryptographic Key Management                               | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                    | 5                        | Access to cleartext cryptographic key components is restricted to necessary personnel.                                                   |
| 3.6.1.4                                                                                                                          | N/A      | Cryptographic keys are stored in the fewest possible locations.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Cryptographic Key Management                               | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                    | 5                        | Cryptographic keys are retained only where necessary.                                                                                    |
| 3.7.1                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include generation of strong cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Cryptographic Key Management                               | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                    | 5                        | Strong cryptographic keys are generated.                                                                                                 |
| 3.7.1                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include generation of strong cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                      | 5                        | Strong cryptographic keys are generated.                                                                                                 |
| 3.7.1                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include generation of strong cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                    | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks. | 5                        | Strong cryptographic keys are generated.                                                                                                 |
| 3.7.2                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include secure distribution of cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Cryptographic Key Management                               | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                    | 5                        | Cryptographic keys are secured during distribution.                                                                                      |
| 3.7.2                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include secure distribution of cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                      | 5                        | Cryptographic keys are secured during distribution.                                                                                      |
| 3.7.2                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include secure distribution of cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                    | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks. | 5                        | Cryptographic keys are secured during distribution.                                                                                      |
| 3.7.3                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include secure storage of cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Cryptographic Key Management                               | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                    | 5                        | Cryptographic keys are secured when stored.                                                                                              |
| 3.7.3                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include secure storage of cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                      | 5                        | Cryptographic keys are secured when stored.                                                                                              |
| 3.7.3                                                                                                                            | N/A      | Key-management policies and procedures are implemented to include secure storage of cryptographic keys used to protect stored account data.                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                    | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks. | 5                        | Cryptographic keys are secured when stored.                                                                                              |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                     | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|-------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 3.7.4 | N/A      | Key management policies and procedures are implemented for cryptographic key changes for keys that have reached the end of their cryptoperiod, as defined by the associated application                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Cryptographic Key Management                                          | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                                                                                | 5                        |                                                                                                                                                                                                                                         |
| 3.7.5 | N/A      | Key management policies and procedures are implemented to include the retirement, replacement, or destruction of keys used to protect stored account data, as deemed necessary when:<br>• The key has reached the end of its defined cryptoperiod.<br>• The integrity of the key has been weakened, including when personnel with knowledge of a cleartext key component leaves the company, or the role for which the key component was known.                                                                                                                           | Functional     | Intersects With   | Transmission Integrity                                                | CRY-04   | Cryptographic mechanisms exist to protect the integrity of data being transmitted.                                                                                                                                                      | 5                        | Keys are removed from active use when it is suspected or known that the integrity of the key is weakened.                                                                                                                               |
| 3.7.5 | N/A      | Key management policies and procedures are implemented to include the retirement, replacement, or destruction of keys used to protect stored account data, as deemed necessary when:<br>• The key has reached the end of its defined cryptoperiod.<br>• The integrity of the key has been weakened, including when personnel with knowledge of a cleartext key component leaves the company, or the role for which the key component was known.                                                                                                                           | Functional     | Intersects With   | Cryptographic Key Management                                          | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                                                                                | 5                        | Keys are removed from active use when it is suspected or known that the integrity of the key is weakened.                                                                                                                               |
| 3.7.5 | N/A      | Key management policies and procedures are implemented to include the retirement, replacement, or destruction of keys used to protect stored account data, as deemed necessary when:<br>• The key has reached the end of its defined cryptoperiod.<br>• The integrity of the key has been weakened, including when personnel with knowledge of a cleartext key component leaves the company, or the role for which the key component was known.<br>• The key is suspected of or known to be compromised. Retired or replaced keys are not used for encryption operations. | Functional     | Intersects With   | Cryptographic Key Loss or Change                                      | CRY-09.3 | Mechanisms exist to ensure the availability of information in the event of the loss of cryptographic keys by individual users.                                                                                                          | 5                        | Keys are removed from active use when it is suspected or known that the integrity of the key is weakened.                                                                                                                               |
| 3.7.5 | N/A      | Key management policies and procedures are implemented to include the retirement, replacement, or destruction of keys used to protect stored account data, as deemed necessary when:<br>• The key has reached the end of its defined cryptoperiod.<br>• The integrity of the key has been weakened, including when personnel with knowledge of a cleartext key component leaves the company, or the role for which the key component was known.<br>• The key is suspected of or known to be compromised. Retired or replaced keys are not used for encryption operations. | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                  | 5                        | Keys are removed from active use when it is suspected or known that the integrity of the key is weakened.                                                                                                                               |
| 3.7.5 | N/A      | Key management policies and procedures are implemented to include the retirement, replacement, or destruction of keys used to protect stored account data, as deemed necessary when:<br>• The key has reached the end of its defined cryptoperiod.<br>• The integrity of the key has been weakened, including when personnel with knowledge of a cleartext key component leaves the company, or the role for which the key component was known.<br>• The key is suspected of or known to be compromised. Retired or replaced keys are not used for encryption operations. | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                             | 5                        | Keys are removed from active use when it is suspected or known that the integrity of the key is weakened.                                                                                                                               |
| 3.7.6 | N/A      | Where manual cleartext cryptographic key- management operations are performed by personnel, key-management policies and procedures are implemented include managing these operations using split knowledge and dual control.                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Cryptographic Key Management                                          | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                                                                                | 5                        | Cleartext secret or private keys cannot be known by anyone. Operations involving cleartext keys cannot be carried out by a single person.                                                                                               |
| 3.7.6 | N/A      | Where manual cleartext cryptographic key- management operations are performed by personnel, key-management policies and procedures are implemented include managing these operations using split knowledge and dual control.                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                  | 5                        | Cleartext secret or private keys cannot be known by anyone. Operations involving cleartext keys cannot be carried out by a single person.                                                                                               |
| 3.7.6 | N/A      | Where manual cleartext cryptographic key- management operations are performed by personnel, key-management policies and procedures are implemented include managing these operations using split knowledge and dual control.                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                             | 5                        | Cleartext secret or private keys cannot be known by anyone. Operations involving cleartext keys cannot be carried out by a single person.                                                                                               |
| 3.7.7 | N/A      | Key management policies and procedures are implemented to include the prevention of unauthorized substitution of cryptographic keys.                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Cryptographic Key Management                                          | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                                                                                | 5                        | Cryptographic keys cannot be substituted by unauthorized personnel.                                                                                                                                                                     |
| 3.7.7 | N/A      | Key management policies and procedures are implemented to include the prevention of unauthorized substitution of cryptographic keys.                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                  | 5                        | Cryptographic keys cannot be substituted by unauthorized personnel.                                                                                                                                                                     |
| 3.7.7 | N/A      | Key management policies and procedures are implemented to include the prevention of unauthorized substitution of cryptographic keys.                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                             | 5                        | Cryptographic keys cannot be substituted by unauthorized personnel.                                                                                                                                                                     |
| 3.7.8 | N/A      | Key management policies and procedures are implemented to include that cryptographic key custodians formally acknowledge (in writing or electronically) that they understand and accept                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Defined Roles & Responsibilities                                      | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                    | 5                        | Key custodians are knowledgeable about their responsibilities in relation to cryptographic operations and can access assistance and guidance when required.                                                                             |
| 3.7.8 | N/A      | Key management policies and procedures are implemented to include that cryptographic key custodians formally acknowledge (in writing or electronically) that they understand and accept                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                  | 5                        | Key custodians are knowledgeable about their responsibilities in relation to cryptographic operations and can access assistance and guidance when required.                                                                             |
| 3.7.8 | N/A      | Key management policies and procedures are implemented to include that cryptographic key custodians formally acknowledge (in writing or electronically) that they understand and accept their key-custodian responsibilities.                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                             | 5                        | Key custodians are knowledgeable about their responsibilities in relation to cryptographic operations and can access assistance and guidance when required.                                                                             |
| 4.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 4 are:<br>• Documented.<br>• Kept up to date.                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                  | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 4 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 4.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 4 are:<br>• Documented.<br>• Kept up to date.                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCR), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 4 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 4.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 4 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Subset Of         | Operations Security                                                   | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                     | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 4 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 4.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 4 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                             | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 4 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 4.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 4 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities           | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCR).        | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 4 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |



| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|---------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 4.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 4 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Defined Roles & Responsibilities                                      | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 4 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 4.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 4 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | User Awareness                                                        | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 4 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 4.2.1   | N/A      | Strong cryptography and security protocols are implemented as follows to safeguard PAN during transmission over open, public networks:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Transmission Confidentiality                                          | CRY-03   | Cryptographic mechanisms exist to protect the confidentiality of data being transmitted.                                                                                                                                           | 5                        | Cleartext PAN cannot be read or intercepted from any transmissions over open, public networks.                                                                                                                                          |
| 4.2.1   | N/A      | Strong cryptography and security protocols are implemented as follows to safeguard PAN during transmission over open, public networks:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Safeguarding Data Over Open Networks                                  | NET-12   | Cryptographic mechanisms exist to implement strong cryptography and security protocols to safeguard sensitive and/or regulated data during transmission over open, public networks.                                                | 5                        | Cleartext PAN cannot be read or intercepted from any transmissions over open, public networks.                                                                                                                                          |
| 4.2.1   | N/A      | Strong cryptography and security protocols are implemented as follows to safeguard PAN during transmission over open, public networks:<br><ul style="list-style-type: none"> <li>Only trusted keys and certificates are accepted.</li> <li>Certificates used to safeguard PAN during transmission over open, public networks are confirmed as valid and are not expired or revoked. This bullet is a best practice until its effective date; refer to applicability notes below for details.</li> <li>The protocol in use supports only secure versions or configurations and does not support fallback to, or use of insecure versions, algorithms, key sizes, or implementations.</li> <li>The encryption strength is appropriate for the encryption methodology in use.</li> </ul> | Functional     | Intersects With   | Authentication & Encryption                                           | NET-15.1 | Mechanisms exist to secure Wi-Fi (e.g., IEEE 802.11) and prevent unauthorized access by:<br>(1) Authenticating devices trying to connect; and<br>(2) Encrypting transmitted data.                                                  | 5                        | Cleartext PAN cannot be read or intercepted from any transmissions over open, public networks.                                                                                                                                          |
| 4.2.1.1 | N/A      | An inventory of the entity's trusted keys and certificates used to protect PAN during transmission is maintained.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Cryptographic Key Management                                          | CRY-09   | Mechanisms exist to facilitate cryptographic key management controls to protect the confidentiality, integrity and availability of keys.                                                                                           | 5                        | All keys and certificates used to protect PAN during transmission are identified and confirmed as trusted.                                                                                                                              |
| 4.2.1.2 | N/A      | Wireless networks transmitting PAN or connected to the CDE use industry best practices to implement strong cryptography for authentication and transmission.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Transmission Confidentiality                                          | CRY-03   | Cryptographic mechanisms exist to protect the confidentiality of data being transmitted.                                                                                                                                           | 5                        | Cleartext PAN cannot be read or intercepted from wireless network transmissions.                                                                                                                                                        |
| 4.2.1.2 | N/A      | Wireless networks transmitting PAN or connected to the CDE use industry best practices to implement strong cryptography for authentication and transmission.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Wireless Access Authentication & Encryption                           | CRY-07   | Mechanisms exist to protect the confidentiality and integrity of wireless networking technologies by implementing authentication and strong encryption.                                                                            | 5                        | Cleartext PAN cannot be read or intercepted from wireless network transmissions.                                                                                                                                                        |
| 4.2.1.2 | N/A      | Wireless networks transmitting PAN or connected to the CDE use industry best practices to implement strong cryptography for authentication and transmission.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Wireless Link Protection                                              | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for                                                    | 5                        | Cleartext PAN cannot be read or intercepted from wireless network transmissions.                                                                                                                                                        |
| 4.2.2   | N/A      | PAN is secured with strong cryptography whenever it is sent via end-user messaging technologies.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | End-User Messaging Technologies                                       | NET-12.2 | Mechanisms exist to prohibit the transmission of unprotected sensitive and/or regulated data by end-user messaging technologies.                                                                                                   | 5                        | Cleartext PAN cannot be read or intercepted from transmissions using end-user messaging technologies.                                                                                                                                   |
| 5.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 5 are:<br><ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                             | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 5 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 5.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 5 are:<br><ul style="list-style-type: none"> <li>Documented.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPP), including policies, standards and procedures, at planned intervals or if significant changes occur                                               | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 5 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 5.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 5 are:<br><ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Subset Of         | Operations Security                                                   | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 5 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 5.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 5 are:<br><ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                        | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 5 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 5.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 5 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Documented Protection Measures                                        | END-04.2 | Mechanisms exist to document antim malware technologies.                                                                                                                                                                           | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 5 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 5.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 5 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities           | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPP). | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 5 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 5.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 5 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Defined Roles & Responsibilities                                      | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 5 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 5.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 5 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | User Awareness                                                        | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 5 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 5.2.1   | N/A      | An anti-malware solution(s) is deployed on all system components, except for those system components identified in periodic evaluations per Requirement 5.2.3 that concludes the                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Malicious Code Protection (Anti-Malware)                              | END-04   | Mechanisms exist to utilize antim malware technologies to detect and eradicate malicious code.                                                                                                                                     | 5                        | Automated mechanisms are implemented to prevent systems from becoming an attack vector for malware.                                                                                                                                     |
| 5.2.2   | N/A      | The deployed anti-malware solution(s):<br><ul style="list-style-type: none"> <li>Detects all known types of malware.</li> <li>Removes, blocks, or contains all known types of malware.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Malicious Code Protection (Anti-Malware)                              | END-04   | Mechanisms exist to utilize antim malware technologies to detect and eradicate malicious code.                                                                                                                                     | 5                        | Malware cannot execute or infect other system components.                                                                                                                                                                               |
| 5.2.3   | N/A      | Any system components that are not at risk for malware are evaluated periodically to include the following:<br><ul style="list-style-type: none"> <li>A documented list of all system components not at risk for malware.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Evolving Malware Threats                                              | END-04.6 | Mechanisms exist to perform periodic evaluations evolving malware threats to assess systems that are generally not considered to be commonly affected by malicious software.                                                       | 5                        | The entity maintains awareness of evolving malware threats to ensure that any systems not protected from malware are not at risk of infection.                                                                                          |
| 5.2.3.1 | N/A      | The frequency of periodic evaluations of system components identified as not at risk for malware is defined in the entity's targeted risk analysis, which is performed according to all                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Evolving Malware Threats                                              | END-04.6 | Mechanisms exist to perform periodic evaluations evolving malware threats to assess systems that are generally not considered to be commonly affected by malicious software.                                                       | 5                        | Systems not known to be at risk from malware are re-evaluated at a frequency that addresses the entity's risk.                                                                                                                          |
| 5.3.1   | N/A      | The anti-malware solution(s) is kept current via automatic updates.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Malicious Code Protection (Anti-Malware)                              | END-04   | Mechanisms exist to utilize antim malware technologies to detect and eradicate malicious code.                                                                                                                                     | 5                        | Anti-malware mechanisms can detect and address the latest malware threats.                                                                                                                                                              |
| 5.3.1   | N/A      | The anti-malware solution(s) is kept current via automatic updates.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Automatic Antimalware Signature Updates                               | END-04.1 | Automated mechanisms exist to update antim malware technologies, including signature definitions.                                                                                                                                  | 5                        | Anti-malware mechanisms can detect and address the latest malware threats.                                                                                                                                                              |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                 | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                                                                            | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|---------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5.3.2   | N/A      | The anti-malware solution(s):<br>• Performs periodic scans and active or real-time scans.                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Malicious Code Protection (Anti-Malware)                              | END-04   | Mechanisms exist to utilize antim malware technologies to detect and eradicate malicious code.                                                                                                                                                                                                                                                                                                                                                                                                 | 5                        | Malware cannot complete execution.                                                                                                                                                                                                      |
| 5.3.2   | N/A      | The anti-malware solution(s):<br>• Performs periodic scans and active or real-time scans.                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Always On Protection                                                  | END-04.7 | Mechanisms exist to ensure that anti-malware technologies are continuously running in real-time and cannot be disabled or                                                                                                                                                                                                                                                                                                                                                                      | 5                        | Malware cannot complete execution.                                                                                                                                                                                                      |
| 5.3.2.1 | N/A      | If periodic malware scans are performed to meet Requirement 5.3.2, the frequency of scans is defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1.                                                                                                                                | Functional     | Intersects With   | Malicious Code Protection (Anti-Malware)                              | END-04   | Mechanisms exist to utilize antim malware technologies to detect and eradicate malicious code.                                                                                                                                                                                                                                                                                                                                                                                                 | 5                        | Scans by the malware solution are performed at a frequency that addresses the entity's risk.                                                                                                                                            |
| 5.3.2.1 | N/A      | If periodic malware scans are performed to meet Requirement 5.3.2, the frequency of scans is defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1.                                                                                                                                | Functional     | Intersects With   | Always On Protection                                                  | END-04.7 | Mechanisms exist to ensure that anti-malware technologies are continuously running in real-time and cannot be disabled or altered by non-privileged users, unless specifically authorized by management on a case-by-case basis for a limited time period.                                                                                                                                                                                                                                     | 5                        | Scans by the malware solution are performed at a frequency that addresses the entity's risk.                                                                                                                                            |
| 5.3.3   | N/A      | For removable electronic media, the anti-malware solution(s):<br>• Performs automatic scans of when the media is inserted, connected, or logically mounted, OR                                                                                                                                                                                            | Functional     | Intersects With   | Malicious Code Protection (Anti-Malware)                              | END-04   | Mechanisms exist to utilize antim malware technologies to detect and eradicate malicious code.                                                                                                                                                                                                                                                                                                                                                                                                 | 5                        | Malware cannot be introduced to system components via external removable media.                                                                                                                                                         |
| 5.3.3   | N/A      | For removable electronic media, the anti-malware solution(s):<br>• Performs automatic scans of when the media is inserted, connected, or logically mounted, OR<br>• Performs continuous behavioral analysis of systems or                                                                                                                                 | Functional     | Intersects With   | Always On Protection                                                  | END-04.7 | Mechanisms exist to ensure that anti-malware technologies are continuously running in real-time and cannot be disabled or altered by non-privileged users, unless specifically authorized by management on a case-by-case basis for a limited time period.                                                                                                                                                                                                                                     | 5                        | Malware cannot be introduced to system components via external removable media.                                                                                                                                                         |
| 5.3.4   | N/A      | Audit logs for the anti-malware solution(s) are enabled and retained in accordance with Requirement 10.5.1.                                                                                                                                                                                                                                               | Functional     | Intersects With   | Malicious Code Protection (Anti-Malware)                              | END-04   | Mechanisms exist to utilize antim malware technologies to detect and eradicate malicious code.                                                                                                                                                                                                                                                                                                                                                                                                 | 5                        | Historical records of anti-malware actions are immediately available and retained for at least 12 months.                                                                                                                               |
| 5.3.4   | N/A      | Audit logs for the anti-malware solution(s) are enabled and retained in accordance with Requirement 10.5.1.                                                                                                                                                                                                                                               | Functional     | Intersects With   | Centralized Management of Antimalware Technologies                    | END-04.3 | Mechanisms exist to centrally-manage antim malware technologies.                                                                                                                                                                                                                                                                                                                                                                                                                               | 5                        | Historical records of anti-malware actions are immediately available and retained for at least 12 months.                                                                                                                               |
| 5.3.5   | N/A      | Anti-malware mechanisms cannot be disabled or altered by users, unless specifically documented, and authorized by                                                                                                                                                                                                                                         | Functional     | Intersects With   | Malicious Code Protection (Anti-Malware)                              | END-04   | Mechanisms exist to utilize antim malware technologies to detect and eradicate malicious code.                                                                                                                                                                                                                                                                                                                                                                                                 | 5                        | Anti-malware mechanisms cannot be modified by unauthorized personnel.                                                                                                                                                                   |
| 5.3.5   | N/A      | Anti-malware mechanisms cannot be disabled or altered by users, unless specifically documented, and authorized by                                                                                                                                                                                                                                         | Functional     | Intersects With   | Always On Protection                                                  | END-04.7 | Mechanisms exist to ensure that anti-malware technologies are continuously running in real-time and cannot be disabled or                                                                                                                                                                                                                                                                                                                                                                      | 5                        | Anti-malware mechanisms cannot be modified by unauthorized personnel.                                                                                                                                                                   |
| 5.4.1   | N/A      | Processes and automated mechanisms are in place to detect and protect personnel against phishing attacks.                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Phishing & Spam Protection                                            | END-08   | Mechanisms exist to utilize anti-phishing and spam protection technologies to detect and take action on unsolicited messages transported by electronic mail.                                                                                                                                                                                                                                                                                                                                   | 5                        | Mechanisms are in place to protect against and mitigate risk posed by phishing attacks.                                                                                                                                                 |
| 6.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 6 are:<br>• Documented.<br>• Kept up to date.<br>• In use.                                                                                                                                                                                                            | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                                                                                                                                                                                                                                                         | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 6 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 6.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 6 are:<br>• Documented.                                                                                                                                                                                                                                               | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRIP), including policies, standards and procedures, at planned intervals or if significant changes occur                                                                                                                                                                                                                                                                                                           | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 6 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 6.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 6 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                        | Functional     | Subset Of         | Operations Security                                                   | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                                                                                                                                                                                                                                                                            | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 6 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 6.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 6 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                        | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                                                                                                                                                                                                                                                                    | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 6 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 6.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 6 are documented, assigned, and understood.                                                                                                                                                                                                                                           | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities           | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRIP).                                                                                                                                                                                                                                                             | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 6 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 6.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 6 are documented, assigned, and understood.                                                                                                                                                                                                                                           | Functional     | Intersects With   | Defined Roles & Responsibilities                                      | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                                                                                                                                                                                                                                                           | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 6 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 6.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 6 are documented, assigned, and understood.                                                                                                                                                                                                                                           | Functional     | Intersects With   | User Awareness                                                        | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                                                                                                                                                                                                                                                           | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 6 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 6.2.1   | N/A      | Bespoke and custom software are developed securely, as follows:<br>• Based on industry standards and/or best practices for secure                                                                                                                                                                                                                         | Functional     | Intersects With   | Threat Analysis & Flaw Remediation During Development                 | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during                                                                                                                                                                                                                                                                                                  | 5                        | Bespoke and custom software is developed in accordance with PCI DSS and secure development processes throughout the software lifecycle.                                                                                                 |
| 6.2.1   | N/A      | Bespoke and custom software are developed securely, as follows:<br>• Based on industry standards and/or best practices for secure                                                                                                                                                                                                                         | Functional     | Subset Of         | Secure Engineering Principles                                         | SEA-01   | Mechanisms exist to facilitate the implementation of industry-recognized security, compliance and resilience practices in the specification, design, development, implementation and                                                                                                                                                                                                                                                                                                           | 10                       | Bespoke and custom software is developed in accordance with PCI DSS and secure development processes throughout the software lifecycle.                                                                                                 |
| 6.2.1   | N/A      | Bespoke and custom software are developed securely, as follows:<br>• Based on industry standards and/or best practices for secure development.<br>• In accordance with PCI DSS (for example, secure authentication and logging).<br>• Incorporating consideration of information security issues during each stage of the software development lifecycle. | Functional     | Subset Of         | Technology Development & Acquisition                                  | TDA-01   | Mechanisms exist to facilitate the implementation of tailored development and acquisition strategies, contract tools and procurement methods to meet unique business needs.                                                                                                                                                                                                                                                                                                                    | 10                       | Bespoke and custom software is developed in accordance with PCI DSS and secure development processes throughout the software lifecycle.                                                                                                 |
| 6.2.1   | N/A      | Bespoke and custom software are developed securely, as follows:<br>• Based on industry standards and/or best practices for secure development.<br>• In accordance with PCI DSS (for example, secure authentication and logging).<br>• Incorporating consideration of information security issues during each stage of the software development lifecycle. | Functional     | Intersects With   | Development Methods, Techniques & Processes                           | TDA-02.3 | Mechanisms exist to require software developers to ensure that their software development processes employ industry-recognized secure practices for secure programming, engineering methods, quality control processes and validation techniques to minimize flawed and/or malformed software.                                                                                                                                                                                                 | 5                        | Bespoke and custom software is developed in accordance with PCI DSS and secure development processes throughout the software lifecycle.                                                                                                 |
| 6.2.1   | N/A      | Bespoke and custom software are developed securely, as follows:<br>• Based on industry standards and/or best practices for secure development.<br>• In accordance with PCI DSS (for example, secure authentication and logging).<br>• Incorporating consideration of information security issues during each stage of the software development lifecycle. | Functional     | Intersects With   | Developer Architecture & Design                                       | TDA-05   | Mechanisms exist to require the developers of Technology Assets, Applications and/or Services (TAAS) to produce a design specification and security architecture that:<br>(1) Is consistent with and supportive of the organization's security architecture which is established within and is an integrated part of the organization's enterprise architecture.<br>(2) Accurately and completely describes the required security functionality and the allocation of security, compliance and | 5                        | Bespoke and custom software is developed in accordance with PCI DSS and secure development processes throughout the software lifecycle.                                                                                                 |
| 6.2.1   | N/A      | Bespoke and custom software are developed securely, as follows:<br>• Based on industry standards and/or best practices for secure development.<br>• In accordance with PCI DSS (for example, secure authentication and logging).<br>• Incorporating consideration of information security issues during each stage of the software development lifecycle. | Functional     | Intersects With   | Secure Software Development Practices (SSDP)                          | TDA-06   | Mechanisms exist to develop applications based on Secure Software Development Practices (SSDP).                                                                                                                                                                                                                                                                                                                                                                                                | 5                        | Bespoke and custom software is developed in accordance with PCI DSS and secure development processes throughout the software lifecycle.                                                                                                 |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                               | STRM Rationale | STRM Relationship | SCF Control                                                      | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                        | Strength of Relationship | Notes                                                                                                                                                                                                                                                       |
|---------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6.2.1   | N/A      | Bespoke and custom software are developed securely, as follows:<br>• Based on industry standards and/or best practices for secure development.<br>• In accordance with PCI DSS (for example, secure authentication and logging).<br>• Incorporating consideration of information security issues during each stage of the software development lifecycle.                                               | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation                     | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production.                                                                                                                                                                   | 5                        | Bespoke and custom software is developed in accordance with PCI DSS and secure development processes throughout the software lifecycle.                                                                                                                     |
| 6.2.2   | N/A      | Software development personnel working on bespoke and custom software are trained at least once every 12 months as follows:<br>• On software security relevant to their job function and development languages.<br>• Including secure software design and secure coding techniques.<br>• Including, if security testing tools are used, how to use the tools for detecting vulnerabilities in software. | Functional     | Intersects With   | Competency Requirements for Security-Related Positions           | HRS-03.2 | Mechanisms exist to ensure that all security-related positions are staffed by qualified individuals who have the necessary skill set.                                                                                                                                                                                                                                                                                      | 5                        | Software development personnel remain knowledgeable about secure development practices; software security; and attacks against the languages, frameworks, or applications they develop. Personnel are able to access assistance and guidance when required. |
| 6.2.2   | N/A      | Software development personnel working on bespoke and custom software are trained at least once every 12 months as follows:<br>• On software security relevant to their job function and development languages.<br>• Including secure software design and secure coding techniques.<br>• Including, if security testing tools are used, how to use the tools for detecting vulnerabilities in software. | Functional     | Intersects With   | Threat Analysis & Flaw Remediation During Development            | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                                                                                                                                                                                                 | 5                        | Software development personnel remain knowledgeable about secure development practices; software security; and attacks against the languages, frameworks, or applications they develop. Personnel are able to access assistance and guidance when required. |
| 6.2.2   | N/A      | Software development personnel working on bespoke and custom software are trained at least once every 12 months as follows:<br>• On software security relevant to their job function and development languages.<br>• Including secure software design and secure coding techniques.<br>• Including, if security testing tools are used, how to use the tools for detecting vulnerabilities in software. | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training            | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training:<br>(1) Before authorizing access to the system or performing assigned duties;<br>(2) When required by system changes; and<br>(3) Annually thereafter.                                                                                                                                                                         | 5                        | Software development personnel remain knowledgeable about secure development practices; software security; and attacks against the languages, frameworks, or applications they develop. Personnel are able to access assistance and guidance when required. |
| 6.2.2   | N/A      | Software development personnel working on bespoke and custom software are trained at least once every 12 months as follows:<br>• On software security relevant to their job function and development languages.<br>• Including secure software design and secure coding techniques.<br>• Including, if security testing tools are used, how to use the tools for detecting vulnerabilities in software. | Functional     | Intersects With   | Continuing Professional Education (CPE) - DevOps Personnel       | SAT-03.8 | Mechanisms exist to ensure application development and operations (DevOps) personnel receive Continuing Professional Education (CPE) training on Secure Software Development Practices (SSDP) to appropriately address evolving threats.                                                                                                                                                                                   | 5                        | Software development personnel remain knowledgeable about secure development practices; software security; and attacks against the languages, frameworks, or applications they develop. Personnel are able to access assistance and guidance when required. |
| 6.2.2   | N/A      | Software development personnel working on bespoke and custom software are trained at least once every 12 months as follows:<br>• On software security relevant to their job function and development languages.<br>• Including secure software design and secure coding techniques.<br>• Including, if security testing tools are used, how to use the tools for detecting vulnerabilities in software. | Functional     | Intersects With   | Software Assurance Maturity Model (SAMM)                         | TDA-06.3 | Mechanisms exist to utilize a Software Assurance Maturity Model (SAMM) to govern a secure development lifecycle for the development of Technology Assets, Applications and/or Services (TAAS).                                                                                                                                                                                                                             | 5                        | Software development personnel remain knowledgeable about secure development practices; software security; and attacks against the languages, frameworks, or applications they develop. Personnel are able to access assistance and guidance when required. |
| 6.2.2   | N/A      | Software development personnel working on bespoke and custom software are trained at least once every 12 months as follows:<br>• On software security relevant to their job function and development languages.<br>• Including secure software design and secure coding techniques.<br>• Including, if security testing tools are used, how to use the tools for detecting vulnerabilities in software. | Functional     | Intersects With   | Developer Screening                                              | TDA-13   | Mechanisms exist to ensure that the developers of Technology Assets, Applications and/or Services (TAAS) have the requisite skillset and appropriate access authorizations.                                                                                                                                                                                                                                                | 5                        | Software development personnel remain knowledgeable about secure development practices; software security; and attacks against the languages, frameworks, or applications they develop. Personnel are able to access assistance and guidance when required. |
| 6.2.2   | N/A      | Software development personnel working on bespoke and custom software are trained at least once every 12 months as follows:<br>• On software security relevant to their job function and development languages.<br>• Including secure software design and secure coding techniques.<br>• Including, if security testing tools are used, how to use the tools for detecting vulnerabilities in software. | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation                     | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production.                                                                                                                                                                   | 5                        | Software development personnel remain knowledgeable about secure development practices; software security; and attacks against the languages, frameworks, or applications they develop. Personnel are able to access assistance and guidance when required. |
| 6.2.3   | N/A      | Bespoke and custom software is reviewed prior to being released into production or to customers, to identify and correct potential coding vulnerabilities, as follows:<br>• Code reviews ensure code is developed according to secure coding guidelines.<br>• Code reviews look for both existing and emerging software vulnerabilities.<br>• Appropriate corrections are implemented prior to release. | Functional     | Intersects With   | Threat Analysis & Flaw Remediation During Development            | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                                                                                                                                                                                                 | 5                        | Bespoke and custom software cannot be exploited via coding vulnerabilities.                                                                                                                                                                                 |
| 6.2.3   | N/A      | Bespoke and custom software is reviewed prior to being released into production or to customers, to identify and correct potential coding vulnerabilities, as follows:<br>• Code reviews ensure code is developed according to secure coding guidelines.<br>• Code reviews look for both existing and emerging software vulnerabilities.<br>• Appropriate corrections are implemented prior to release. | Functional     | Intersects With   | Software Design Review                                           | TDA-06.5 | Mechanisms exist to have an independent review of the software design to validate:<br>(1) Applicable security, compliance and resilience requirements are met; and<br>(2) Identified risks are remediated.                                                                                                                                                                                                                 | 5                        | Bespoke and custom software cannot be exploited via coding vulnerabilities.                                                                                                                                                                                 |
| 6.2.3   | N/A      | Bespoke and custom software is reviewed prior to being released into production or to customers, to identify and correct potential coding vulnerabilities, as follows:<br>• Code reviews ensure code is developed according to secure coding guidelines.<br>• Code reviews look for both existing and emerging software vulnerabilities.<br>• Appropriate corrections are implemented prior to release. | Functional     | Intersects With   | Security, Compliance & Resilience Testing Throughout Development | TDA-09   | Mechanisms exist to require system developers/integrators consult with security, compliance and/or resilience personnel to:<br>(1) Create and implement a Security Testing and Evaluation (ST&E) plan, or similar capability;<br>(2) Implement a verifiable flaw remediation process to correct weaknesses and deficiencies identified during the control testing and evaluation process; and<br>(3) Document the results. | 5                        | Bespoke and custom software cannot be exploited via coding vulnerabilities.                                                                                                                                                                                 |
| 6.2.3   | N/A      | Bespoke and custom software is reviewed prior to being released into production or to customers, to identify and correct potential coding vulnerabilities, as follows:<br>• Code reviews ensure code is developed according to secure coding guidelines.<br>• Code reviews look for both existing and emerging software vulnerabilities.<br>• Appropriate corrections are implemented prior to release. | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation                     | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production.                                                                                                                                                                   | 5                        | Bespoke and custom software cannot be exploited via coding vulnerabilities.                                                                                                                                                                                 |
| 6.2.3.1 | N/A      | If manual code reviews are performed for bespoke and custom software prior to release to production, code changes are:<br>• Reviewed by individuals other than the originating code author, and who are knowledgeable about code-review techniques and secure coding practices.<br>• Reviewed and approved by management prior to release.                                                              | Functional     | Intersects With   | Threat Analysis & Flaw Remediation During Development            | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                                                                                                                                                                                                 | 5                        | The manual code review process cannot be bypassed and is effective at discovering security vulnerabilities.                                                                                                                                                 |
| 6.2.3.1 | N/A      | If manual code reviews are performed for bespoke and custom software prior to release to production, code changes are:<br>• Reviewed by individuals other than the originating code author, and who are knowledgeable about code-review techniques and secure coding practices.<br>• Reviewed and approved by management prior to release.                                                              | Functional     | Intersects With   | Security, Compliance & Resilience Testing Throughout Development | TDA-09   | Mechanisms exist to require system developers/integrators consult with security, compliance and/or resilience personnel to:<br>(1) Create and implement a Security Testing and Evaluation (ST&E) plan, or similar capability;<br>(2) Implement a verifiable flaw remediation process to correct weaknesses and deficiencies identified during the control testing and evaluation process; and<br>(3) Document the results. | 5                        | The manual code review process cannot be bypassed and is effective at discovering security vulnerabilities.                                                                                                                                                 |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | STRM Rationale | STRM Relationship | SCF Control                                                      | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                                                                   | Strength of Relationship | Notes                                                                                                       |
|---------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------|
| 6.2.3.1 | N/A      | If manual code reviews are performed for bespoke and custom software prior to release to production, code changes are: <ul style="list-style-type: none"><li>Reviewed by individuals other than the originating code author, and who are knowledgeable about code-review techniques and secure coding practices.</li><li>Reviewed and approved by management prior to release.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation                     | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production.                                                                                                                                                                                                                              | 5                        | The manual code review process cannot be bypassed and is effective at discovering security vulnerabilities. |
| 6.2.4   | N/A      | Software engineering techniques or other methods are defined and in use by software development personnel to prevent or mitigate common software attacks and related vulnerabilities in bespoke and custom software, including but not limited to the following: <ul style="list-style-type: none"><li>Injection attacks, including SQL, LDAP, XPath, or other command, parameter, object, fault, or injection-type flaws.</li><li>Attacks on data and data structures, including attempts to manipulate buffers, pointers, input data, or shared data.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Security, Compliance & Resilience Testing Throughout Development | TDA-09   | Mechanisms exist to require system developers/integrators consult with security, compliance and/or resilience personnel to: <ul style="list-style-type: none"><li>(1) Create and implement a Security Testing and Evaluation (ST&amp;E) plan, or similar capability;</li><li>(2) Implement a verifiable flaw remediation process to correct weaknesses and deficiencies identified during the control testing and evaluation process; and</li><li>(3) Document the results.</li></ul> | 5                        | Bespoke and custom software cannot be exploited via common attacks and related vulnerabilities.             |
| 6.2.4   | N/A      | Software engineering techniques or other methods are defined and in use by software development personnel to prevent or mitigate common software attacks and related vulnerabilities in bespoke and custom software, including but not limited to the following: <ul style="list-style-type: none"><li>Injection attacks, including SQL, LDAP, XPath, or other command, parameter, object, fault, or injection-type flaws.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Threat Analysis & Flaw Remediation During Development            | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                                                                                                                                                                                                                                                            | 5                        | Bespoke and custom software cannot be exploited via common attacks and related vulnerabilities.             |
| 6.2.4   | N/A      | Software engineering techniques or other methods are defined and in use by software development personnel to prevent or mitigate common software attacks and related vulnerabilities in bespoke and custom software, including but not limited to the following: <ul style="list-style-type: none"><li>Injection attacks, including SQL, LDAP, XPath, or other command, parameter, object, fault, or injection-type flaws.</li><li>Attacks on data and data structures, including attempts to manipulate buffers, pointers, input data, or shared data.</li><li>Attacks on cryptography usage, including attempts to exploit weak, insecure, or inappropriate cryptographic implementations, algorithms, cipher suites, or modes of operation.</li><li>Attacks on business logic, including attempts to abuse or bypass application features and functionalities through the manipulation of APIs, communication protocols and channels, client-side functionality, or other system/application functions and resources. This includes cross-site scripting (XSS) and cross-site request forgery (CSRF).</li><li>Attacks on access control mechanisms, including attempts to bypass or abuse identification, authentication, or authorization mechanisms, or attempts to exploit weaknesses in the implementation of such mechanisms.</li><li>Attacks via any "high-risk" vulnerabilities identified in the vulnerability identification process, as defined in Requirement 6.3.1.</li></ul> | Functional     | Intersects With   | Secure Software Development Practices (SSDP)                     | TDA-06   | Mechanisms exist to develop applications based on Secure Software Development Practices (SSDP).                                                                                                                                                                                                                                                                                                                                                                                       | 5                        | Bespoke and custom software cannot be exploited via common attacks and related vulnerabilities.             |
| 6.2.4   | N/A      | Software engineering techniques or other methods are defined and in use by software development personnel to prevent or mitigate common software attacks and related vulnerabilities in bespoke and custom software, including but not limited to the following: <ul style="list-style-type: none"><li>Injection attacks, including SQL, LDAP, XPath, or other command, parameter, object, fault, or injection-type flaws.</li><li>Attacks on data and data structures, including attempts to manipulate buffers, pointers, input data, or shared data.</li><li>Attacks on cryptography usage, including attempts to exploit weak, insecure, or inappropriate cryptographic implementations, algorithms, cipher suites, or modes of operation.</li><li>Attacks on business logic, including attempts to abuse or bypass application features and functionalities through the manipulation of APIs, communication protocols and channels, client-side functionality, or other system/application functions and resources. This includes cross-site scripting (XSS) and cross-site request forgery (CSRF).</li><li>Attacks on access control mechanisms, including attempts to bypass or abuse identification, authentication, or authorization mechanisms, or attempts to exploit weaknesses in the implementation of such mechanisms.</li><li>Attacks via any "high-risk" vulnerabilities identified in the vulnerability identification process, as defined in Requirement 6.3.1.</li></ul> | Functional     | Intersects With   | Static Code Analysis                                             | TDA-09.2 | Mechanisms exist to require the developers of Technology Assets, Applications and/or Services (TAAS) to employ static code analysis tools to identify and remediate common flaws and document the results of the analysis.                                                                                                                                                                                                                                                            | 5                        | Bespoke and custom software cannot be exploited via common attacks and related vulnerabilities.             |
| 6.2.4   | N/A      | Software engineering techniques or other methods are defined and in use by software development personnel to prevent or mitigate common software attacks and related vulnerabilities in bespoke and custom software, including but not limited to the following: <ul style="list-style-type: none"><li>Injection attacks, including SQL, LDAP, XPath, or other command, parameter, object, fault, or injection-type flaws.</li><li>Attacks on data and data structures, including attempts to manipulate buffers, pointers, input data, or shared data.</li><li>Attacks on cryptography usage, including attempts to exploit weak, insecure, or inappropriate cryptographic implementations, algorithms, cipher suites, or modes of operation.</li><li>Attacks on business logic, including attempts to abuse or bypass application features and functionalities through the manipulation of APIs, communication protocols and channels, client-side functionality, or other system/application functions and resources. This includes cross-site scripting (XSS) and cross-site request forgery (CSRF).</li><li>Attacks on access control mechanisms, including attempts to bypass or abuse identification, authentication, or authorization mechanisms, or attempts to exploit weaknesses in the implementation of such mechanisms.</li><li>Attacks via any "high-risk" vulnerabilities identified in the vulnerability identification process, as defined in Requirement 6.3.1.</li></ul> | Functional     | Intersects With   | Dynamic Code Analysis                                            | TDA-09.3 | Mechanisms exist to require the developers of Technology Assets, Applications and/or Services (TAAS) to employ dynamic code analysis tools to identify and remediate common flaws and document the results of the analysis.                                                                                                                                                                                                                                                           | 5                        | Bespoke and custom software cannot be exploited via common attacks and related vulnerabilities.             |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | STRM Rationale | STRM Relationship | SCF Control                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                      | Strength of Relationship | Notes                                                                                                                                        |
|-------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| 6.2.4 | N/A      | Software engineering techniques or other methods are defined and in use by software development personnel to prevent or mitigate common software attacks and related vulnerabilities in bespoke and custom software, including but not limited to the following: <ul style="list-style-type: none"> <li>Injection attacks, including SQL, LDAP, XPath, or other command, parameter, object, fault, or injection-type flaws.</li> <li>Attacks on data and data structures, including attempts to manipulate buffers, pointers, input data, or shared data.</li> <li>Attacks on cryptography usage, including attempts to exploit weak, insecure, or inappropriate cryptographic implementations, algorithms, cipher suites, or modes of operation.</li> <li>Attacks on business logic, including attempts to abuse or bypass application features and functionalities through the manipulation of APIs, communication protocols and channels, client-side functionality, or other system/application functions and resources. This includes cross-site scripting (XSS) and cross-site request forgery (CSRF).</li> <li>Attacks on access control mechanisms, including attempts to bypass or abuse identification, authentication, or authorization mechanisms, or attempts to exploit weaknesses in the implementation of such mechanisms.</li> <li>Attacks via any "high-risk" vulnerabilities identified in the vulnerability identification process, as defined in Requirement 6.3.1.</li> </ul> | Functional     | Intersects With   | Malformed Input Testing                               | TDA-09.4 | Mechanisms exist to utilize testing methods to ensure Technology Assets, Applications and/or Services (TAAS) continue to operate as intended when subject to invalid or unexpected inputs on its interfaces.                                             | 5                        | Bespoke and custom software cannot be exploited via common attacks and related vulnerabilities.                                              |
| 6.2.4 | N/A      | Software engineering techniques or other methods are defined and in use by software development personnel to prevent or mitigate common software attacks and related vulnerabilities in bespoke and custom software, including but not limited to the following: <ul style="list-style-type: none"> <li>Injection attacks, including SQL, LDAP, XPath, or other command, parameter, object, fault, or injection-type flaws.</li> <li>Attacks on data and data structures, including attempts to manipulate buffers, pointers, input data, or shared data.</li> <li>Attacks on cryptography usage, including attempts to exploit weak, insecure, or inappropriate cryptographic implementations, algorithms, cipher suites, or modes of operation.</li> <li>Attacks on business logic, including attempts to abuse or bypass application features and functionalities through the manipulation of APIs, communication protocols and channels, client-side functionality, or other system/application functions and resources. This includes cross-site scripting (XSS) and cross-site request forgery (CSRF).</li> <li>Attacks on access control mechanisms, including attempts to bypass or abuse identification, authentication, or authorization mechanisms, or attempts to exploit weaknesses in the implementation of such mechanisms.</li> <li>Attacks via any "high-risk" vulnerabilities identified in the vulnerability identification process, as defined in Requirement 6.3.1.</li> </ul> | Functional     | Intersects With   | Application Penetration Testing                       | TDA-09.5 | Mechanisms exist to perform application-level penetration testing of custom-made Technology Assets, Applications and/or Services (TAAS).                                                                                                                 | 5                        | Bespoke and custom software cannot be exploited via common attacks and related vulnerabilities.                                              |
| 6.2.4 | N/A      | Software engineering techniques or other methods are defined and in use by software development personnel to prevent or mitigate common software attacks and related vulnerabilities in bespoke and custom software, including but not limited to the following: <ul style="list-style-type: none"> <li>Injection attacks, including SQL, LDAP, XPath, or other command, parameter, object, fault, or injection-type flaws.</li> <li>Attacks on data and data structures, including attempts to manipulate buffers, pointers, input data, or shared data.</li> <li>Attacks on cryptography usage, including attempts to exploit weak, insecure, or inappropriate cryptographic implementations, algorithms, cipher suites, or modes of operation.</li> <li>Attacks on business logic, including attempts to abuse or bypass application features and functionalities through the manipulation of APIs, communication protocols and channels, client-side functionality, or other system/application functions and resources. This includes cross-site scripting (XSS) and cross-site request forgery (CSRF).</li> <li>Attacks on access control mechanisms, including attempts to bypass or abuse identification, authentication, or authorization mechanisms, or attempts to exploit weaknesses in the implementation of such mechanisms.</li> <li>Attacks via any "high-risk" vulnerabilities identified in the vulnerability identification process, as defined in Requirement 6.3.1.</li> </ul> | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation          | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production. | 5                        | Bespoke and custom software cannot be exploited via common attacks and related vulnerabilities.                                              |
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows: <ul style="list-style-type: none"> <li>New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Threat Analysis & Flaw Remediation During Development | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                               | 5                        | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | STRM Rationale | STRM Relationship | SCF Control                                          | SCF #     | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Strength of Relationship | Notes                                                                                                                                        |
|-------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows:<br><ul style="list-style-type: none"> <li>• New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>• Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>• Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>• Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul> | Functional     | Intersects With   | Contacts With Groups & Associations                  | GOV-07    | Mechanisms exist to establish contact with selected groups and associations within the security, compliance and resilience communities to:<br>(1) Facilitate ongoing cybersecurity and data protection education and training for organizational personnel;<br>(2) Maintain currency with recommended cybersecurity and data protection practices, techniques and technologies; and<br>(3) Share current cybersecurity and/or data protection-related information including threats, vulnerabilities and incidents. | 5                        | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows:<br><ul style="list-style-type: none"> <li>• New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>• Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>• Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>• Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul> | Functional     | Intersects With   | Threat Intelligence Feeds                            | THR-03    | Mechanisms exist to maintain situational awareness of vulnerabilities and evolving threats by leveraging the knowledge of attacker tactics, techniques and procedures to facilitate the implementation of preventative and compensating controls.                                                                                                                                                                                                                                                                   | 5                        | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows:<br><ul style="list-style-type: none"> <li>• New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>• Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>• Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>• Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul> | Functional     | Intersects With   | Vulnerability Disclosure Program (VDP)               | THR-06    | Mechanisms exist to establish a Vulnerability Disclosure Program (VDP) to assist with the secure development and maintenance of Technology Assets, Applications and/or Services (TAAS) that receives unsolicited input from the public about vulnerabilities in organizational TAAS.                                                                                                                                                                                                                                | 5                        | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows:<br><ul style="list-style-type: none"> <li>• New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>• Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>• Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>• Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul> | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation         | TDA-15    | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production.                                                                                                                                                                                                                                                            | 5                        | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows:<br><ul style="list-style-type: none"> <li>• New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>• Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>• Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>• Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul> | Functional     | Subset Of         | Vulnerability & Patch Management Program (VPMP)      | VPMP-01   | Mechanisms exist to facilitate the implementation and monitoring of vulnerability management controls.                                                                                                                                                                                                                                                                                                                                                                                                              | 10                       | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows:<br><ul style="list-style-type: none"> <li>• New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>• Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>• Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>• Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul> | Functional     | Intersects With   | Attack Surface Scope                                 | VPMP-01.1 | Mechanisms exist to define and manage the scope for its attack surface management activities.                                                                                                                                                                                                                                                                                                                                                                                                                       | 5                        | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows:<br><ul style="list-style-type: none"> <li>• New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>• Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>• Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>• Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul> | Functional     | Intersects With   | Vulnerability Ranking                                | VPMP-03   | Mechanisms exist to identify and assign a risk ranking to newly discovered security vulnerabilities using reputable outside sources for security vulnerability information.                                                                                                                                                                                                                                                                                                                                         | 5                        | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |
| 6.3.1 | N/A      | Security vulnerabilities are identified and managed as follows:<br><ul style="list-style-type: none"> <li>• New security vulnerabilities are identified using industry-recognized sources for security vulnerability information, including alerts from international and national computer emergency response teams (CERTs).</li> <li>• Vulnerabilities are assigned a risk ranking based on industry best practices and consideration of potential impact.</li> <li>• Risk rankings identify, at a minimum, all vulnerabilities considered to be a high-risk or critical to the environment.</li> <li>• Vulnerabilities for bespoke and custom, and third-party software (for example operating systems and databases) are covered.</li> </ul> | Functional     | Intersects With   | Centralized Management of Flaw Remediation Processes | VPMP-05.1 | Mechanisms exist to centrally-manage the flaw remediation process.                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 5                        | New system and software vulnerabilities that may impact the security of account data or the CDE are monitored, cataloged, and risk assessed. |



| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | STRM Rationale | STRM Relationship | SCF Control                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Strength of Relationship | Notes                                                                                                        |
|-------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------|
| 6.3.2 | N/A      | An inventory of bespoke and custom software, and third-party software components incorporated into bespoke and custom software is maintained to facilitate vulnerability and patch management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Subset Of         | Asset Governance                                      | AST-01   | Mechanisms exist to facilitate an IT Asset Management (ITAM) program to implement and manage asset management controls.                                                                                                                                                                                                                                                                                                                                                                                                                               | 10                       | Known vulnerabilities in third-party software components cannot be exploited in bespoke and custom software. |
| 6.3.2 | N/A      | An inventory of bespoke and custom software, and third-party software components incorporated into bespoke and custom software is maintained to facilitate vulnerability and patch management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Asset Inventories                                     | AST-02   | Mechanisms exist to perform inventories of Technology Assets, Applications, Services and/or Data (TAASD) that:<br>(1) Accurately reflects the current TAASD in use;<br>(2) Identifies authorized software products, including business justification details;<br>(3) Is at the level of granularity deemed necessary for tracking and reporting;<br>(4) Includes organization-defined information deemed necessary to achieve effective property accountability; and<br>(5) Is available for review and audit by designated organizational personnel. | 5                        | Known vulnerabilities in third-party software components cannot be exploited in bespoke and custom software. |
| 6.3.2 | N/A      | An inventory of bespoke and custom software, and third-party software components incorporated into bespoke and custom software is maintained to facilitate vulnerability and patch management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Compliance-Specific Asset Identification              | AST-04.3 | Mechanisms exist to create and maintain a current inventory of Technology Assets, Applications, Services and/or Data (TAASD) that are in scope for statutory, regulatory and/or contractual compliance obligations that provides sufficient detail to                                                                                                                                                                                                                                                                                                 | 5                        | Known vulnerabilities in third-party software components cannot be exploited in bespoke and custom software. |
| 6.3.2 | N/A      | An inventory of bespoke and custom software, and third-party software components incorporated into bespoke and custom software is maintained to facilitate vulnerability and patch management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Software Bill of Materials (SBOM)                     | TDA-04.2 | Mechanisms exist to generate, or obtain, a Software Bill of Materials (SBOM) for Technology Assets, Applications and/or Services (TAAS) that lists software packages in use, including versions and applicable licenses.                                                                                                                                                                                                                                                                                                                              | 5                        | Known vulnerabilities in third-party software components cannot be exploited in bespoke and custom software. |
| 6.3.2 | N/A      | An inventory of bespoke and custom software, and third-party software components incorporated into bespoke and custom software is maintained to facilitate vulnerability and patch management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Attack Surface Scope                                  | VPM-01.1 | Mechanisms exist to define and manage the scope for its attack surface management activities.                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 5                        | Known vulnerabilities in third-party software components cannot be exploited in bespoke and custom software. |
| 6.3.2 | N/A      | An inventory of bespoke and custom software, and third-party software components incorporated into bespoke and custom software is maintained to facilitate vulnerability and patch management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Centralized Management of Flaw Remediation Processes  | VPM-05.1 | Mechanisms exist to centrally-manage the flaw remediation process.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 5                        | Known vulnerabilities in third-party software components cannot be exploited in bespoke and custom software. |
| 6.3.3 | N/A      | All system components are protected from known vulnerabilities by installing applicable security patches/updates as follows:<br>• Critical or high-security patches/updates (identified according to the risk ranking process at Requirement 6.3.1) are installed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Functional     | Subset Of         | Vulnerability & Patch Management Program (VPM)        | VPM-01   | Mechanisms exist to facilitate the implementation and monitoring of vulnerability management controls.                                                                                                                                                                                                                                                                                                                                                                                                                                                | 10                       | System components cannot be compromised via the exploitation of a known vulnerability.                       |
| 6.3.3 | N/A      | All system components are protected from known vulnerabilities by installing applicable security patches/updates as follows:<br>• Critical or high-security patches/updates (identified according to the risk ranking process at Requirement 6.3.1) are installed                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Continuous Vulnerability Remediation Activities       | VPM-04   | Mechanisms exist to address new threats and vulnerabilities on an ongoing basis and ensure assets are protected against known attacks.                                                                                                                                                                                                                                                                                                                                                                                                                | 5                        | System components cannot be compromised via the exploitation of a known vulnerability.                       |
| 6.3.3 | N/A      | All system components are protected from known vulnerabilities by installing applicable security patches/updates as follows:<br>• Critical or high-security patches/updates (identified according to the risk ranking process at Requirement 6.3.1) are installed within one month of release.<br>• All other applicable security patches/updates are installed within an appropriate time frame as determined by the entity (for example, within three months of release).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Software & Firmware Patching                          | VPM-05   | Mechanisms exist to conduct software patching for all deployed Technology Assets, Applications and/or Services (TAAS), including firmware.                                                                                                                                                                                                                                                                                                                                                                                                            | 5                        | System components cannot be compromised via the exploitation of a known vulnerability.                       |
| 6.3.3 | N/A      | All system components are protected from known vulnerabilities by installing applicable security patches/updates as follows:<br>• Critical or high-security patches/updates (identified according to the risk ranking process at Requirement 6.3.1) are installed within one month of release.<br>• All other applicable security patches/updates are installed within an appropriate time frame as determined by the entity (for example, within three months of release).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Centralized Management of Flaw Remediation Processes  | VPM-05.1 | Mechanisms exist to centrally-manage the flaw remediation process.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 5                        | System components cannot be compromised via the exploitation of a known vulnerability.                       |
| 6.4.1 | N/A      | For public-facing web applications, new threats and vulnerabilities are addressed on an ongoing basis and these applications are protected against known attacks as follows:<br>• Reviewing public-facing web applications via manual or automated application vulnerability security assessment tools or methods as follows:<br>– At least once every 12 months and after significant changes.<br>– By an entity that specializes in application security.<br>– Including, at a minimum, all common software attacks in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Threat Analysis & Flaw Remediation During Development | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                                                                                                                                                                                                                                                                                                                            | 5                        | Public-facing web applications are protected against malicious attacks.                                      |
| 6.4.1 | N/A      | For public-facing web applications, new threats and vulnerabilities are addressed on an ongoing basis and these applications are protected against known attacks as follows:<br>• Reviewing public-facing web applications via manual or automated application vulnerability security assessment tools or methods as follows:<br>– At least once every 12 months and after significant changes.<br>– By an entity that specializes in application security.<br>– Including, at a minimum, all common software attacks in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation          | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production.                                                                                                                                                                                                                                                                                              | 5                        | Public-facing web applications are protected against malicious attacks.                                      |
| 6.4.1 | N/A      | For public-facing web applications, new threats and vulnerabilities are addressed on an ongoing basis and these applications are protected against known attacks as follows:<br>• Reviewing public-facing web applications via manual or automated application vulnerability security assessment tools or methods as follows:<br>– At least once every 12 months and after significant changes.<br>– By an entity that specializes in application security.<br>– Including, at a minimum, all common software attacks in Requirement 6.2.4.<br>– All vulnerabilities are ranked in accordance with requirement 6.3.1.<br>– All vulnerabilities are corrected.<br>– The application is re-evaluated after the corrections<br>OR<br>• Installing an automated technical solution(s) that continually detects and prevents web-based attacks as follows:<br>– Installed in front of public-facing web applications to detect and prevent web-based attacks.<br>– Actively running and up to date as applicable.<br>– Generating audit logs.<br>– Configured to either block web-based attacks or generate an alert that is immediately investigated. | Functional     | Intersects With   | Centralized Management of Flaw Remediation Processes  | VPM-05.1 | Mechanisms exist to centrally-manage the flaw remediation process.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 5                        | Public-facing web applications are protected against malicious attacks.                                      |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | STRM Rationale | STRM Relationship | SCF Control                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                       | Strength of Relationship | Notes                                                                                |
|-------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------|
| 6.4.1 | N/A      | For public-facing web applications, new threats and vulnerabilities are addressed on an ongoing basis and these applications are protected against known attacks as follows:<br><ul style="list-style-type: none"> <li>Reviewing public-facing web applications via manual or automated application vulnerability security assessment tools or methods as follows: <ul style="list-style-type: none"> <li>At least once every 12 months and after significant changes.</li> <li>By an entity that specializes in application security.</li> <li>Including, at a minimum, all common software attacks in Requirement 6.2.4.</li> </ul> </li> <li>All vulnerabilities are ranked in accordance with requirement 6.3.1.</li> <li>All vulnerabilities are corrected.</li> <li>The application is re-evaluated after the corrections</li> </ul> OR<br><ul style="list-style-type: none"> <li>Installing an automated technical solution(s) that continually detects and prevents web-based attacks as follows: <ul style="list-style-type: none"> <li>Installed in front of public-facing web applications to detect and prevent web-based attacks.</li> <li>Actively running and up to date as applicable.</li> <li>Generating audit logs.</li> <li>Configured to either block web-based attacks or generate an alert that is immediately investigated.</li> </ul> </li> </ul> | Functional     | Intersects With   | Vulnerability Scanning                                | VPM-06   | Mechanisms exist to detect vulnerabilities and configuration errors by routine vulnerability scanning of systems and applications.                                                                                                                                                                                                        | 5                        | Public-facing web applications are protected against malicious attacks.              |
| 6.4.1 | N/A      | For public-facing web applications, new threats and vulnerabilities are addressed on an ongoing basis and these applications are protected against known attacks as follows:<br><ul style="list-style-type: none"> <li>Reviewing public-facing web applications via manual or automated application vulnerability security assessment tools or methods as follows: <ul style="list-style-type: none"> <li>At least once every 12 months and after significant changes.</li> <li>By an entity that specializes in application security.</li> <li>Including, at a minimum, all common software attacks in Requirement 6.2.4.</li> </ul> </li> <li>All vulnerabilities are ranked in accordance with requirement 6.3.1.</li> <li>All vulnerabilities are corrected.</li> <li>The application is re-evaluated after the corrections</li> </ul> OR<br><ul style="list-style-type: none"> <li>Installing an automated technical solution(s) that continually detects and prevents web-based attacks as follows: <ul style="list-style-type: none"> <li>Installed in front of public-facing web applications to detect and prevent web-based attacks.</li> <li>Actively running and up to date as applicable.</li> <li>Generating audit logs.</li> <li>Configured to either block web-based attacks or generate an alert that is immediately investigated.</li> </ul> </li> </ul> | Functional     | Intersects With   | External Vulnerability Assessment Scans               | VPM-06.6 | Mechanisms exist to perform quarterly external vulnerability scans (outside the organization's network looking inward) via a reputable vulnerability service provider, which include rescans until passing results are obtained or all "high" vulnerabilities are resolved, as defined by the Common Vulnerability Scoring System (CVSS). | 5                        | Public-facing web applications are protected against malicious attacks.              |
| 6.4.1 | N/A      | For public-facing web applications, new threats and vulnerabilities are addressed on an ongoing basis and these applications are protected against known attacks as follows:<br><ul style="list-style-type: none"> <li>Reviewing public-facing web applications via manual or automated application vulnerability security assessment tools or methods as follows: <ul style="list-style-type: none"> <li>At least once every 12 months and after significant changes.</li> <li>By an entity that specializes in application security.</li> <li>Including, at a minimum, all common software attacks in Requirement 6.2.4.</li> </ul> </li> <li>All vulnerabilities are ranked in accordance with requirement 6.3.1.</li> <li>All vulnerabilities are corrected.</li> <li>The application is re-evaluated after the corrections</li> </ul> OR<br><ul style="list-style-type: none"> <li>Installing an automated technical solution(s) that continually detects and prevents web-based attacks as follows: <ul style="list-style-type: none"> <li>Installed in front of public-facing web applications to detect and prevent web-based attacks.</li> <li>Actively running and up to date as applicable.</li> <li>Generating audit logs.</li> <li>Configured to either block web-based attacks or generate an alert that is immediately investigated.</li> </ul> </li> </ul> | Functional     | Subset Of         | Web Security                                          | WEB-01   | Mechanisms exist to facilitate the implementation of an enterprise-wide web management policy, as well as associated standards, controls and procedures.                                                                                                                                                                                  | 10                       | Public-facing web applications are protected against malicious attacks.              |
| 6.4.1 | N/A      | For public-facing web applications, new threats and vulnerabilities are addressed on an ongoing basis and these applications are protected against known attacks as follows:<br><ul style="list-style-type: none"> <li>Reviewing public-facing web applications via manual or automated application vulnerability security assessment tools or methods as follows: <ul style="list-style-type: none"> <li>At least once every 12 months and after significant changes.</li> <li>By an entity that specializes in application security.</li> <li>Including, at a minimum, all common software attacks in Requirement 6.2.4.</li> </ul> </li> <li>All vulnerabilities are ranked in accordance with requirement 6.3.1.</li> <li>All vulnerabilities are corrected.</li> <li>The application is re-evaluated after the corrections</li> </ul> OR<br><ul style="list-style-type: none"> <li>Installing an automated technical solution(s) that continually detects and prevents web-based attacks as follows: <ul style="list-style-type: none"> <li>Installed in front of public-facing web applications to detect and prevent web-based attacks.</li> <li>Actively running and up to date as applicable.</li> <li>Generating audit logs.</li> <li>Configured to either block web-based attacks or generate an alert that is immediately investigated.</li> </ul> </li> </ul> | Functional     | Intersects With   | Web Application Firewall (WAF)                        | WEB-03   | Mechanisms exist to deploy Web Application Firewalls (WAFs) to provide defense-in-depth protection for application-specific threats.                                                                                                                                                                                                      | 5                        | Public-facing web applications are protected against malicious attacks.              |
| 6.4.2 | N/A      | For public-facing web applications, an automated technical solution is deployed that continually detects and prevents web-based attacks, with at least the following:<br><ul style="list-style-type: none"> <li>Is installed in front of public-facing web applications and is configured to detect and prevent web-based attacks.</li> <li>Actively running and up to date as applicable.</li> <li>Generating audit logs.</li> <li>Configured to either block web-based attacks or generate an alert that is immediately investigated.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Threat Analysis & Flow Remediation During Development | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                                                                                                                | 5                        | Public-facing web applications are protected in real time against malicious attacks. |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | STRM Rationale | STRM Relationship | SCF Control                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                                          | Strength of Relationship | Notes                                                                                                                                                                 |
|-------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6.4.2 | N/A      | For public-facing web applications, an automated technical solution is deployed that continually detects and prevents web-based attacks, with at least the following:<br>• Is installed in front of public-facing web applications and is configured to detect and prevent web-based attacks.<br>• Actively running and up to date as applicable.<br>• Generating audit logs.<br>• Configured to either block web-based attacks or generate an alert that is immediately investigated.                                                                                         | Functional     | Intersects With   | Content of Event Logs                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum:<br>(1) Establish what type of event occurred;<br>(2) When (date and time) the event occurred;<br>(3) Where the event occurred;<br>(4) The source of the event;<br>(5) The outcome (success or failure) of the event; and<br>(6) The identity of any user/subject associated with the event. | 5                        | Public-facing web applications are protected in real time against malicious attacks.                                                                                  |
| 6.4.2 | N/A      | For public-facing web applications, an automated technical solution is deployed that continually detects and prevents web-based attacks, with at least the following:<br>• Is installed in front of public-facing web applications and is configured to detect and prevent web-based attacks.<br>• Actively running and up to date as applicable.<br>• Generating audit logs.<br>• Configured to either block web-based attacks or generate an alert that is immediately investigated.                                                                                         | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation         | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production.                                                                                                                                                                                                     | 5                        | Public-facing web applications are protected in real time against malicious attacks.                                                                                  |
| 6.4.2 | N/A      | For public-facing web applications, an automated technical solution is deployed that continually detects and prevents web-based attacks, with at least the following:<br>• Is installed in front of public-facing web applications and is configured to detect and prevent web-based attacks.<br>• Actively running and up to date as applicable.<br>• Generating audit logs.<br>• Configured to either block web-based attacks or generate an alert that is immediately investigated.                                                                                         | Functional     | Intersects With   | Centralized Management of Flaw Remediation Processes | VPM-05.1 | Mechanisms exist to centrally-manage the flaw remediation process.                                                                                                                                                                                                                                                                                                                                                                                           | 5                        | Public-facing web applications are protected in real time against malicious attacks.                                                                                  |
| 6.4.2 | N/A      | For public-facing web applications, an automated technical solution is deployed that continually detects and prevents web-based attacks, with at least the following:<br>• Is installed in front of public-facing web applications and is configured to detect and prevent web-based attacks.<br>• Actively running and up to date as applicable.<br>• Generating audit logs.<br>• Configured to either block web-based attacks or generate an alert that is immediately investigated.                                                                                         | Functional     | Subset Of         | Web Security                                         | WEB-01   | Mechanisms exist to facilitate the implementation of an enterprise-wide web management policy, as well as associated standards, controls and procedures.                                                                                                                                                                                                                                                                                                     | 10                       | Public-facing web applications are protected in real time against malicious attacks.                                                                                  |
| 6.4.2 | N/A      | For public-facing web applications, an automated technical solution is deployed that continually detects and prevents web-based attacks, with at least the following:<br>• Is installed in front of public-facing web applications and is configured to detect and prevent web-based attacks.<br>• Actively running and up to date as applicable.<br>• Generating audit logs.<br>• Configured to either block web-based attacks or generate an alert that is immediately investigated.                                                                                         | Functional     | Intersects With   | Web Application Firewall (WAF)                       | WEB-03   | Mechanisms exist to deploy Web Application Firewalls (WAFs) to provide defense-in-depth protection for application-specific threats.                                                                                                                                                                                                                                                                                                                         | 5                        | Public-facing web applications are protected in real time against malicious attacks.                                                                                  |
| 6.4.3 | N/A      | All payment page scripts that are loaded and executed in the consumer's browser are managed as follows:<br>• A method is implemented to confirm that each script is authorized.<br>• A method is implemented to assure the integrity of each script.<br>• An inventory of all scripts is maintained with written justification as to why each is necessary.                                                                                                                                                                                                                    | Functional     | Intersects With   | Centralized Management of Flaw Remediation Processes | VPM-05.1 | Mechanisms exist to centrally-manage the flaw remediation process.                                                                                                                                                                                                                                                                                                                                                                                           | 5                        | Unauthorized code cannot be present in the payment page as it is rendered in the consumer's browser.                                                                  |
| 6.4.3 | N/A      | All payment page scripts that are loaded and executed in the consumer's browser are managed as follows:<br>• A method is implemented to confirm that each script is authorized.<br>• A method is implemented to assure the integrity of each script.<br>• An inventory of all scripts is maintained with written justification as to why each is necessary.                                                                                                                                                                                                                    | Functional     | Intersects With   | Unauthorized Code                                    | WEB-01.1 | Mechanisms exist to prevent unauthorized code from being present in a secure page as it is rendered in a client's browser.                                                                                                                                                                                                                                                                                                                                   | 5                        | Unauthorized code cannot be present in the payment page as it is rendered in the consumer's browser.                                                                  |
| 6.5.1 | N/A      | Changes to an system components in the production environment are made according to established procedures that include:<br>• Reason for, and description of, the change.<br>• Documentation of security impact.<br>• Documented change approval by authorized parties.<br>• Testing to verify that the change does not adversely impact system security.                                                                                                                                                                                                                      | Functional     | Subset Of         | Change Management Program                            | CHG-01   | Mechanisms exist to facilitate the implementation of a change management program.                                                                                                                                                                                                                                                                                                                                                                            | 10                       | All changes are tracked, authorized, and evaluated for impact and security, and changes are managed to avoid unintended effects to the security of system components. |
| 6.5.1 | N/A      | Changes to an system components in the production environment are made according to established procedures that include:<br>• Reason for, and description of, the change.<br>• Documentation of security impact.<br>• Documented change approval by authorized parties.<br>• Testing to verify that the change does not adversely impact system security.                                                                                                                                                                                                                      | Functional     | Intersects With   | Configuration Change Control                         | CHG-02   | Mechanisms exist to govern the technical configuration change control processes.                                                                                                                                                                                                                                                                                                                                                                             | 5                        | All changes are tracked, authorized, and evaluated for impact and security, and changes are managed to avoid unintended effects to the security of system components. |
| 6.5.1 | N/A      | Changes to all system components in the production environment are made according to established procedures that include:<br>• Reason for, and description of, the change.<br>• Documentation of security impact.<br>• Documented change approval by authorized parties.<br>• Testing to verify that the change does not adversely impact system security.<br>• For bespoke and custom software changes, all updates are tested for compliance with Requirement 6.2.4 before being deployed into production.<br>• Procedures to address failures and return to a secure state. | Functional     | Intersects With   | Prohibition Of Changes                               | CHG-02.1 | Mechanisms exist to prohibit unauthorized changes, unless organization-approved change requests are received.                                                                                                                                                                                                                                                                                                                                                | 5                        | All changes are tracked, authorized, and evaluated for impact and security, and changes are managed to avoid unintended effects to the security of system components. |
| 6.5.1 | N/A      | Changes to all system components in the production environment are made according to established procedures that include:<br>• Reason for, and description of, the change.<br>• Documentation of security impact.<br>• Documented change approval by authorized parties.<br>• Testing to verify that the change does not adversely impact system security.<br>• For bespoke and custom software changes, all updates are tested for compliance with Requirement 6.2.4 before being deployed into production.<br>• Procedures to address failures and return to a secure state. | Functional     | Intersects With   | Test, Validate & Document Changes                    | CHG-02.2 | Mechanisms exist to appropriately test and document proposed changes in a non-production environment before changes are implemented in a production environment.                                                                                                                                                                                                                                                                                             | 5                        | All changes are tracked, authorized, and evaluated for impact and security, and changes are managed to avoid unintended effects to the security of system components. |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                               | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|-------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 6.5.1 | N/A      | Changes to all system components in the production environment are made according to established procedures that include: <ul style="list-style-type: none"> <li>Reason for, and description of, the change.</li> <li>Documentation of security impact.</li> <li>Documented change approval by authorized parties.</li> <li>Testing to verify that the change does not adversely impact system security.</li> <li>For bespoke and custom software changes, all updates are tested for compliance with Requirement 6.2.4 before being deployed into production.</li> <li>Procedures to address failures and return to a secure state.</li> </ul> | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                                                                                                                                       | 5                        | All changes are tracked, authorized, and evaluated for impact and security, and changes are managed to avoid unintended effects to the security of system components.                                                                   |
| 6.5.2 | N/A      | Upon completion of a significant change, all applicable PCI DSS requirements are confirmed to be in place on all new or changed systems and networks, and documentation is updated as applicable.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Asset Ownership Assignment                                            | AST-03   | Mechanisms exist to ensure asset ownership responsibilities are assigned, tracked and managed at a team, individual, or responsible organization level to establish a common understanding of requirements for asset protection.                                                                                                                                  | 5                        | All system components are verified after a significant change to be compliant with the applicable PCI DSS requirements.                                                                                                                 |
| 6.5.2 | N/A      | Upon completion of a significant change, all applicable PCI DSS requirements are confirmed to be in place on all new or changed systems and networks, and documentation is updated as applicable.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Subset Of         | Change Management Program                                             | CHG-01   | Mechanisms exist to facilitate the implementation of a change management program.                                                                                                                                                                                                                                                                                 | 10                       | All system components are verified after a significant change to be compliant with the applicable PCI DSS requirements.                                                                                                                 |
| 6.5.2 | N/A      | Upon completion of a significant change, all applicable PCI DSS requirements are confirmed to be in place on all new or changed systems and networks, and documentation is updated as applicable.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Test, Validate & Document Changes                                     | CHG-02.2 | Mechanisms exist to appropriately test and document proposed changes in a non-production environment before changes are implemented in a production environment.                                                                                                                                                                                                  | 5                        | All system components are verified after a significant change to be compliant with the applicable PCI DSS requirements.                                                                                                                 |
| 6.5.2 | N/A      | Upon completion of a significant change, all applicable PCI DSS requirements are confirmed to be in place on all new or changed systems and networks, and documentation is updated as applicable.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Security Impact Analysis for Changes                                  | CHG-03   | Mechanisms exist to analyze proposed changes for potential security impacts, prior to the implementation of the change.                                                                                                                                                                                                                                           | 5                        | All system components are verified after a significant change to be compliant with the applicable PCI DSS requirements.                                                                                                                 |
| 6.5.2 | N/A      | Upon completion of a significant change, all applicable PCI DSS requirements are confirmed to be in place on all new or changed systems and networks, and documentation is updated as applicable.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Control Functionality Verification                                    | CHG-06   | Mechanisms exist to verify the functionality of security, compliance and resilience controls following implemented changes to ensure applicable controls operate as designed.                                                                                                                                                                                     | 5                        | All system components are verified after a significant change to be compliant with the applicable PCI DSS requirements.                                                                                                                 |
| 6.5.2 | N/A      | Upon completion of a significant change, all applicable PCI DSS requirements are confirmed to be in place on all new or changed systems and networks, and documentation is updated as applicable.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Report Verification Results                                           | CHG-06.1 | Mechanisms exist to report the results of security, compliance and resilience capability verification to appropriate organizational management.                                                                                                                                                                                                                   | 5                        | All system components are verified after a significant change to be compliant with the applicable PCI DSS requirements.                                                                                                                 |
| 6.5.2 | N/A      | Upon completion of a significant change, all applicable PCI DSS requirements are confirmed to be in place on all new or changed systems and networks, and documentation is updated as applicable.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Default Authenticators                                                | IAC-10.8 | Mechanisms exist to ensure default authenticators are changed as part of account creation or system installation.                                                                                                                                                                                                                                                 | 5                        | All system components are verified after a significant change to be compliant with the applicable PCI DSS requirements.                                                                                                                 |
| 6.5.3 | N/A      | Pre-production environments are separated from production environments and the separation is enforced with access controls.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Subset Of         | Change Management Program                                             | CHG-01   | Mechanisms exist to facilitate the implementation of a change management program.                                                                                                                                                                                                                                                                                 | 10                       | Pre-production environments cannot introduce risks and vulnerabilities into production environments.                                                                                                                                    |
| 6.5.3 | N/A      | Pre-production environments are separated from production environments and the separation is enforced with access controls.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Secure Development Environments                                       | TDA-07   | Mechanisms exist to maintain a segmented development network to ensure a secure development environment.                                                                                                                                                                                                                                                          | 5                        | Pre-production environments cannot introduce risks and vulnerabilities into production environments.                                                                                                                                    |
| 6.5.3 | N/A      | Pre-production environments are separated from production environments and the separation is enforced with access controls.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Separation of Development, Testing and Operational Environments       | TDA-08   | Mechanisms exist to manage separate development, testing and operational environments to reduce the risks of unauthorized access or changes to the operational environment and to ensure                                                                                                                                                                          | 5                        | Pre-production environments cannot introduce risks and vulnerabilities into production environments.                                                                                                                                    |
| 6.5.4 | N/A      | Roles and functions are separated between production and pre-production environments to provide accountability such that only reviewed and approved changes are deployed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Separation of Duties (SoD)                                            | HRS-11   | Mechanisms exist to implement and maintain Separation of Duties (SoD) to prevent potential inappropriate activity without collusion.                                                                                                                                                                                                                              | 5                        | Job roles and accountability that differentiate between pre-production and production activities are defined and managed to minimize the risk of unauthorized, unintentional, or inappropriate                                          |
| 6.5.5 | N/A      | Live PANs are not used in pre-production environments, except where those environments are included in the CDE and protected in accordance with all applicable PCI DSS requirements.                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Internal Use of Personal Data (PD) For Testing, Training and Research | PRI-05.1 | Mechanisms exist to address the use of Personal Data (PD) for internal testing, training and research that: <ul style="list-style-type: none"> <li>(1) Takes measures to limit or minimize the amount of PD used for internal testing, training and research purposes; and</li> <li>(2) Authorizes the use of PD when such information is required for</li> </ul> | 5                        | Live PANs cannot be present in pre-production environments outside the CDE.                                                                                                                                                             |
| 6.5.5 | N/A      | Live PANs are not used in pre-production environments, except where those environments are included in the CDE and protected in accordance with all applicable PCI DSS requirements.                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Usage Restrictions of Personal Data (PD)                              | PRI-05.4 | Mechanisms exist to restrict collecting, receiving, processing, storing, transmitting, sharing and/or updating Personal Data (PD) to: <ul style="list-style-type: none"> <li>(1) The purpose(s) originally collected, consistent with the data</li> </ul>                                                                                                         | 5                        | Live PANs cannot be present in pre-production environments outside the CDE.                                                                                                                                                             |
| 6.5.5 | N/A      | Live PANs are not used in pre-production environments, except where those environments are included in the CDE and protected in accordance with all applicable PCI DSS requirements.                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Use of Live Data                                                      | TDA-10   | Mechanisms exist to approve, document and control the use of live data in development and test environments.                                                                                                                                                                                                                                                      | 5                        | Live PANs cannot be present in pre-production environments outside the CDE.                                                                                                                                                             |
| 6.5.6 | N/A      | Test data and test accounts are removed from system components before the system goes into production.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Development & Test Environment Configurations                         | CFG-02.4 | Mechanisms exist to manage baseline configurations for development and test environments separately from operational baseline configurations to minimize the risk of unintentional changes.                                                                                                                                                                       | 5                        |                                                                                                                                                                                                                                         |
| 6.5.6 | N/A      | Test data and test accounts are removed from system components before the system goes into production.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Configuration Change Control                                          | CHG-02   | Mechanisms exist to govern the technical configuration change control processes.                                                                                                                                                                                                                                                                                  | 5                        |                                                                                                                                                                                                                                         |
| 6.5.6 | N/A      | Test data and test accounts are removed from system components before the system goes into production.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Security Impact Analysis for Changes                                  | CHG-03   | Mechanisms exist to analyze proposed changes for potential security impacts, prior to the implementation of the change.                                                                                                                                                                                                                                           | 5                        |                                                                                                                                                                                                                                         |
| 6.5.6 | N/A      | Test data and test accounts are removed from system components before the system goes into production.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Separation of Development, Testing and Operational                    | TDA-08   | Mechanisms exist to manage separate development, testing and operational environments to reduce the risks of unauthorized                                                                                                                                                                                                                                         | 5                        |                                                                                                                                                                                                                                         |
| 6.5.6 | N/A      | Test data and test accounts are removed from system components before the system goes into production.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Secure Migration Practices                                            | TDA-08.1 | Mechanisms exist to ensure secure migration practices purge Technology Assets, Applications and/or Services (TAAS) of                                                                                                                                                                                                                                             | 5                        |                                                                                                                                                                                                                                         |
| 6.5.6 | N/A      | Test data and test accounts are removed from system components before the system goes into production.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Security, Compliance & Resilience Testing Throughout Development      | TDA-09   | Mechanisms exist to require system developers/integrators consult with security, compliance and/or resilience personnel to: <ul style="list-style-type: none"> <li>(1) Create and implement a Security Testing and Evaluation (ST&amp;E) plan, or similar capability;</li> <li>(2) Implement a verifiable flaw remediation process to correct</li> </ul>          | 5                        |                                                                                                                                                                                                                                         |
| 7.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 7 are: <ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                                                                                                                            | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 7 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 7.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 7 are: <ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRIP), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness.                                                                                                          | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 7 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                               | STRM Rationale | STRM Relationship | SCF Control                                                  | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|-------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 7 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                      | Functional     | Subset Of         | Operations Security                                          | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 7 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 7.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 7 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                      | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                      | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                        | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 7 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 7.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 7 are documented, assigned, and understood.                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities  | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPP). | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 7 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 7.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 7 are documented, assigned, and understood.                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Defined Roles & Responsibilities                             | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 7 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 7.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 7 are documented, assigned, and understood.                                                                                                                                                                                                                                                         | Functional     | Intersects With   | User Awareness                                               | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 7 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 7.2.1 | N/A      | An access control model is defined and includes granting access as follows:<br>• Appropriate access depending on the entity's business and                                                                                                                                                                                                                              | Functional     | Subset Of         | Identity & Access Management (IAM)                           | IAC-01   | Mechanisms exist to facilitate the implementation of identification and access management controls.                                                                                                                                | 10                       | Access requirements are established according to job functions following least-privilege and need-to-know principles.                                                                                                                   |
| 7.2.1 | N/A      | An access control model is defined and includes granting access as follows:<br>• Appropriate access depending on the entity's business and                                                                                                                                                                                                                              | Functional     | Intersects With   | Identification & Authentication for Organizational Users     | IAC-02   | Mechanisms exist to uniquely identify and centrally Authenticate, Authorize and Audit (AAA) organizational users and processes acting on behalf of organizational users.                                                           | 5                        | Access requirements are established according to job functions following least-privilege and need-to-know principles.                                                                                                                   |
| 7.2.1 | N/A      | An access control model is defined and includes granting access as follows:<br>• Appropriate access depending on the entity's business and access needs.<br>• Access to system components and data resources that is based on users' job classification and functions.<br>• The least privileges required (for example, user, administrator) to perform a job function. | Functional     | Intersects With   | Identification & Authentication for Non-Organizational Users | IAC-03   | Mechanisms exist to uniquely identify and centrally Authenticate, Authorize and Audit (AAA) third-party users and processes that provide services to the organization.                                                             | 5                        | Access requirements are established according to job functions following least-privilege and need-to-know principles.                                                                                                                   |
| 7.2.1 | N/A      | An access control model is defined and includes granting access as follows:<br>• Appropriate access depending on the entity's business and access needs.<br>• Access to system components and data resources that is based on users' job classification and functions.<br>• The least privileges required (for example, user, administrator) to perform a job function. | Functional     | Intersects With   | Role-Based Access Control (RBAC)                             | IAC-08   | Mechanisms exist to enforce Role-Based Access Control (RBAC) for Technology Assets, Applications, Services and/or Data (TAASD) to restrict access to individuals assigned specific roles with legitimate business needs.           | 5                        | Access requirements are established according to job functions following least-privilege and need-to-know principles.                                                                                                                   |
| 7.2.1 | N/A      | An access control model is defined and includes granting access as follows:<br>• Appropriate access depending on the entity's business and access needs.<br>• Access to system components and data resources that is based on users' job classification and functions.<br>• The least privileges required (for example, user, administrator) to perform a job function. | Functional     | Intersects With   | Access Enforcement                                           | IAC-20   | Mechanisms exist to enforce Logical Access Control (LAC) permissions that conform to the principle of "least privilege."                                                                                                           | 5                        | Access requirements are established according to job functions following least-privilege and need-to-know principles.                                                                                                                   |
| 7.2.1 | N/A      | An access control model is defined and includes granting access as follows:<br>• Appropriate access depending on the entity's business and access needs.<br>• Access to system components and data resources that is based on users' job classification and functions.<br>• The least privileges required (for example, user, administrator) to perform a job function. | Functional     | Intersects With   | Access To Sensitive / Regulated Data                         | IAC-20.1 | Mechanisms exist to limit access to sensitive and/or regulated data to only those individuals whose job requires such access.                                                                                                      | 5                        | Access requirements are established according to job functions following least-privilege and need-to-know principles.                                                                                                                   |
| 7.2.1 | N/A      | An access control model is defined and includes granting access as follows:<br>• Appropriate access depending on the entity's business and access needs.<br>• Access to system components and data resources that is based on users' job classification and functions.<br>• The least privileges required (for example, user, administrator) to perform a job function. | Functional     | Intersects With   | Least Privilege                                              | IAC-21   | Mechanisms exist to utilize the concept of least privilege, allowing only authorized access to processes necessary to accomplish assigned tasks in accordance with organizational business functions.                              | 5                        | Access requirements are established according to job functions following least-privilege and need-to-know principles.                                                                                                                   |
| 7.2.2 | N/A      | Access is assigned to users, including privileged users, based on:<br>• Job classification and function.<br>• Least privileges necessary to perform job responsibilities.                                                                                                                                                                                               | Functional     | Intersects With   | Role-Based Access Control (RBAC)                             | IAC-08   | Mechanisms exist to enforce Role-Based Access Control (RBAC) for Technology Assets, Applications, Services and/or Data (TAASD) to restrict access to individuals assigned specific roles with legitimate business needs.           | 5                        | Access to systems and data is limited to only the access needed to perform job functions, as defined in the related access roles.                                                                                                       |
| 7.2.2 | N/A      | Access is assigned to users, including privileged users, based on:<br>• Job classification and function.<br>• Least privileges necessary to perform job responsibilities.                                                                                                                                                                                               | Functional     | Intersects With   | Access Enforcement                                           | IAC-20   | Mechanisms exist to enforce Logical Access Control (LAC) permissions that conform to the principle of "least privilege."                                                                                                           | 5                        | Access to systems and data is limited to only the access needed to perform job functions, as defined in the related access roles.                                                                                                       |
| 7.2.2 | N/A      | Access is assigned to users, including privileged users, based on:<br>• Job classification and function.<br>• Least privileges necessary to perform job responsibilities.                                                                                                                                                                                               | Functional     | Intersects With   | Access To Sensitive / Regulated Data                         | IAC-20.1 | Mechanisms exist to limit access to sensitive and/or regulated data to only those individuals whose job requires such access.                                                                                                      | 5                        | Access to systems and data is limited to only the access needed to perform job functions, as defined in the related access roles.                                                                                                       |
| 7.2.2 | N/A      | Access is assigned to users, including privileged users, based on:<br>• Job classification and function.<br>• Least privileges necessary to perform job responsibilities.                                                                                                                                                                                               | Functional     | Intersects With   | Least Privilege                                              | IAC-21   | Mechanisms exist to utilize the concept of least privilege, allowing only authorized access to processes necessary to accomplish assigned tasks in accordance with organizational business functions.                              | 5                        | Access to systems and data is limited to only the access needed to perform job functions, as defined in the related access roles.                                                                                                       |
| 7.2.3 | N/A      | Required privileges are approved by authorized personnel.                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | User Provisioning & De-Provisioning                          | IAC-07   | Mechanisms exist to utilize a formal user registration and de-registration process that governs the assignment of access rights.                                                                                                   | 5                        | Access privileges cannot be granted to users without appropriate, documented authorization.                                                                                                                                             |
| 7.2.3 | N/A      | Required privileges are approved by authorized personnel.                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Change of Roles & Duties                                     | IAC-07.1 | Mechanisms exist to revoke user access rights following changes in personnel roles and duties, if no longer necessary or permitted.                                                                                                | 5                        | Access privileges cannot be granted to users without appropriate, documented authorization.                                                                                                                                             |
| 7.2.3 | N/A      | Required privileges are approved by authorized personnel.                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Privileged Account Management (PAM)                          | IAC-16   | Mechanisms exist to restrict and control privileged access rights for users and Technology Assets, Applications and/or Services (TAAS).                                                                                            | 5                        | Access privileges cannot be granted to users without appropriate, documented authorization.                                                                                                                                             |
| 7.2.3 | N/A      | Required privileges are approved by authorized personnel.                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Management Approval For Privileged Accounts                  | IAC-21.3 | Mechanisms exist to restrict the assignment of privileged accounts to management-approved personnel and/or roles.                                                                                                                  | 5                        | Access privileges cannot be granted to users without appropriate, documented authorization.                                                                                                                                             |
| 7.2.4 | N/A      | All user accounts and related access privileges, including third-party/vendor accounts, are reviewed as follows:<br>• At least once every six months.                                                                                                                                                                                                                   | Functional     | Intersects With   | Privileged Account Inventories                               | IAC-16.1 | Mechanisms exist to inventory all privileged accounts and validate that each person with elevated privileges is authorized by the appropriate level of organizational management.                                                  | 5                        | Account privilege assignments are verified periodically by management as correct, and nonconformities are remediated.                                                                                                                   |
| 7.2.4 | N/A      | All user accounts and related access privileges, including third-party/vendor accounts, are reviewed as follows:                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Periodic Review of Account Privileges                        | IAC-17   | Mechanisms exist to periodically-review the privileges assigned to individuals and service accounts to validate the need for such                                                                                                  | 5                        | Account privilege assignments are verified periodically by management as correct, and nonconformities are remediated.                                                                                                                   |
| 7.2.5 | N/A      | All application and system accounts and related access privileges are assigned and managed as follows:<br>• Based on the least privileges necessary for the operability of the system or application.<br>• Access is limited to the systems, applications, or processes that specifically require their use.                                                            | Functional     | Intersects With   | Role-Based Access Control (RBAC)                             | IAC-08   | Mechanisms exist to enforce Role-Based Access Control (RBAC) for Technology Assets, Applications, Services and/or Data (TAASD) to restrict access to individuals assigned specific roles with legitimate business needs.           | 5                        | Access rights granted to application and system accounts are limited to only the access needed for the operability of that application or system.                                                                                       |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                              | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                     | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|---------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 7.2.5   | N/A      | All application and system accounts and related access privileges are assigned and managed as follows:<br>• Based on the least privileges necessary for the operability of the system or application.<br>• Access is limited to the systems, applications, or processes that specifically require their use.                           | Functional     | Intersects With   | Access Enforcement                                                    | IAC-20   | Mechanisms exist to enforce Logical Access Control (LAC) permissions that conform to the principle of "least privilege."                                                                                                                | 5                        | Access rights granted to application and system accounts are limited to only the access needed for the operability of that application or system.                                                                                       |
| 7.2.5   | N/A      | All application and system accounts and related access privileges are assigned and managed as follows:<br>• Based on the least privileges necessary for the operability of the system or application.<br>• Access is limited to the systems, applications, or processes that specifically require their use.                           | Functional     | Intersects With   | Remote Access                                                         | NET-14   | Mechanisms exist to define, control and review organization-approved, secure remote access methods.                                                                                                                                     | 5                        | Access rights granted to application and system accounts are limited to only the access needed for the operability of that application or system.                                                                                       |
| 7.2.5   | N/A      | All application and system accounts and related access privileges are assigned and managed as follows:<br>• Based on the least privileges necessary for the operability of the system or application.<br>• Access is limited to the systems, applications, or processes that specifically require their use.                           | Functional     | Intersects With   | Privileged Account Management (PAM)                                   | IAC-16   | Mechanisms exist to restrict and control privileged access rights for users and Technology Assets, Applications and/or Services (TAAS).                                                                                                 | 5                        | Access rights granted to application and system accounts are limited to only the access needed for the operability of that application or system.                                                                                       |
| 7.2.5   | N/A      | All application and system accounts and related access privileges are assigned and managed as follows:<br>• Based on the least privileges necessary for the operability of the system or application.<br>• Access is limited to the systems, applications, or processes that specifically require their use.                           | Functional     | Intersects With   | Access To Sensitive / Regulated Data                                  | IAC-20.1 | Mechanisms exist to limit access to sensitive and/or regulated data to only those individuals whose job requires such access.                                                                                                           | 5                        | Access rights granted to application and system accounts are limited to only the access needed for the operability of that application or system.                                                                                       |
| 7.2.5.1 | N/A      | All access by application and system accounts and related access privileges are reviewed as follows:<br>• Periodically (at the frequency defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1).<br>• The application/system access remains appropriate for the | Functional     | Intersects With   | Periodic Review of Account Privileges                                 | IAC-17   | Mechanisms exist to periodically-review the privileges assigned to individuals and service accounts to validate the need for such privileges and reassign or remove unnecessary privileges, as necessary.                               | 5                        | Application and system account privilege assignments are verified periodically by management as correct, and nonconformities are remediated.                                                                                            |
| 7.2.6   | N/A      | All user access to query repositories of stored cardholder data is restricted as follows:<br>• Via applications or other programmatic methods, with access and allowed actions based on user roles and least privileges.<br>• Only the responsible administrator(s) can directly access or query repositories of stored CHD.           | Functional     | Intersects With   | Access Enforcement                                                    | IAC-20   | Mechanisms exist to enforce Logical Access Control (LAC) permissions that conform to the principle of "least privilege."                                                                                                                | 5                        | Direct unfiltered (ad hoc) query access to cardholder data repositories is prohibited, unless performed by an authorized administrator.                                                                                                 |
| 7.2.6   | N/A      | All user access to query repositories of stored cardholder data is restricted as follows:<br>• Via applications or other programmatic methods, with access and allowed actions based on user roles and least privileges.<br>• Only the responsible administrator(s) can directly access or query repositories of stored CHD.           | Functional     | Intersects With   | Access To Sensitive / Regulated Data                                  | IAC-20.1 | Mechanisms exist to limit access to sensitive and/or regulated data to only those individuals whose job requires such access.                                                                                                           | 5                        | Direct unfiltered (ad hoc) query access to cardholder data repositories is prohibited, unless performed by an authorized administrator.                                                                                                 |
| 7.2.6   | N/A      | All user access to query repositories of stored cardholder data is restricted as follows:<br>• Via applications or other programmatic methods, with access and allowed actions based on user roles and least privileges.<br>• Only the responsible administrator(s) can directly access or query repositories of stored CHD.           | Functional     | Intersects With   | Database Access                                                       | IAC-20.2 | Mechanisms exist to restrict access to databases containing sensitive and/or regulated data to only necessary Technology Assets, Applications and/or Services (TAAS) or those individuals whose job requires such access.               | 5                        | Direct unfiltered (ad hoc) query access to cardholder data repositories is prohibited, unless performed by an authorized administrator.                                                                                                 |
| 7.2.6   | N/A      | All user access to query repositories of stored cardholder data is restricted as follows:<br>• Via applications or other programmatic methods, with access and allowed actions based on user roles and least privileges.<br>• Only the responsible administrator(s) can directly access or query repositories of stored CHD.           | Functional     | Intersects With   | Least Privilege                                                       | IAC-21   | Mechanisms exist to utilize the concept of least privilege, allowing only authorized access to processes necessary to accomplish assigned tasks in accordance with organizational business functions.                                   | 5                        | Direct unfiltered (ad hoc) query access to cardholder data repositories is prohibited, unless performed by an authorized administrator.                                                                                                 |
| 7.2.6   | N/A      | All user access to query repositories of stored cardholder data is restricted as follows:<br>• Via applications or other programmatic methods, with access and allowed actions based on user roles and least privileges.<br>• Only the responsible administrator(s) can directly access or query repositories of stored CHD.           | Functional     | Intersects With   | Database Logging                                                      | MON-03.7 | Mechanisms exist to ensure databases produce audit records that contain sufficient information to monitor database activities.                                                                                                          | 5                        | Direct unfiltered (ad hoc) query access to cardholder data repositories is prohibited, unless performed by an authorized administrator.                                                                                                 |
| 7.3.1   | N/A      | An access control system(s) is in place that restricts access based on a user's need to know and covers all system components.                                                                                                                                                                                                         | Functional     | Subset Of         | Identity & Access Management (IAM)                                    | IAC-01   | Mechanisms exist to facilitate the implementation of identification and access management controls.                                                                                                                                     | 10                       | Access rights and privileges are managed via mechanisms intended for that purpose.                                                                                                                                                      |
| 7.3.1   | N/A      | An access control system(s) is in place that restricts access based on a user's need to know and covers all system components.                                                                                                                                                                                                         | Functional     | Intersects With   | Identification & Authentication for Organizational Users              | IAC-02   | Mechanisms exist to uniquely identify and centrally Authenticate, Authorize and Audit (AAA) organizational users and processes acting on behalf of organizational users.                                                                | 5                        | Access rights and privileges are managed via mechanisms intended for that purpose.                                                                                                                                                      |
| 7.3.1   | N/A      | An access control system(s) is in place that restricts access based on a user's need to know and covers all system components.                                                                                                                                                                                                         | Functional     | Intersects With   | Role-Based Access Control (RBAC)                                      | IAC-08   | Mechanisms exist to enforce Role-Based Access Control (RBAC) for Technology Assets, Applications, Services and/or Data (TAASD) to restrict access to individuals assigned specific roles                                                | 5                        | Access rights and privileges are managed via mechanisms intended for that purpose.                                                                                                                                                      |
| 7.3.1   | N/A      | An access control system(s) is in place that restricts access based on a user's need to know and covers all system components.                                                                                                                                                                                                         | Functional     | Intersects With   | Least Privilege                                                       | IAC-21   | Mechanisms exist to utilize the concept of least privilege, allowing only authorized access to processes necessary to accomplish assigned tasks in accordance with organizational                                                       | 5                        | Access rights and privileges are managed via mechanisms intended for that purpose.                                                                                                                                                      |
| 7.3.2   | N/A      | The access control system(s) is configured to enforce permissions assigned to individuals, applications, and systems based on job classification and function.                                                                                                                                                                         | Functional     | Subset Of         | Identity & Access Management (IAM)                                    | IAC-01   | Mechanisms exist to facilitate the implementation of identification and access management controls.                                                                                                                                     | 10                       | Individual account access rights and privileges to systems, applications, and data are only inherited from group membership.                                                                                                            |
| 7.3.2   | N/A      | The access control system(s) is configured to enforce permissions assigned to individuals, applications, and systems based on job classification and function.                                                                                                                                                                         | Functional     | Intersects With   | Identification & Authentication for Organizational Users              | IAC-02   | Mechanisms exist to uniquely identify and centrally Authenticate, Authorize and Audit (AAA) organizational users and processes acting on behalf of organizational users.                                                                | 5                        | Individual account access rights and privileges to systems, applications, and data are only inherited from group membership.                                                                                                            |
| 7.3.2   | N/A      | The access control system(s) is configured to enforce permissions assigned to individuals, applications, and systems based on job classification and function.                                                                                                                                                                         | Functional     | Intersects With   | Role-Based Access Control (RBAC)                                      | IAC-08   | Mechanisms exist to enforce Role-Based Access Control (RBAC) for Technology Assets, Applications, Services and/or Data (TAASD) to restrict access to individuals assigned specific roles                                                | 5                        | Individual account access rights and privileges to systems, applications, and data are only inherited from group membership.                                                                                                            |
| 7.3.2   | N/A      | The access control system(s) is configured to enforce permissions assigned to individuals, applications, and systems based on job classification and function.                                                                                                                                                                         | Functional     | Intersects With   | Least Privilege                                                       | IAC-21   | Mechanisms exist to utilize the concept of least privilege, allowing only authorized access to processes necessary to accomplish assigned tasks in accordance with organizational                                                       | 5                        | Individual account access rights and privileges to systems, applications, and data are only inherited from group membership.                                                                                                            |
| 7.3.3   | N/A      | The access control system(s) is set to "deny all" by default.                                                                                                                                                                                                                                                                          | Functional     | Subset Of         | Identity & Access Management (IAM)                                    | IAC-01   | Mechanisms exist to facilitate the implementation of identification and access management controls.                                                                                                                                     | 10                       | Access rights and privileges are prohibited unless expressly permitted.                                                                                                                                                                 |
| 7.3.3   | N/A      | The access control system(s) is set to "deny all" by default.                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Identification & Authentication for Organizational Users              | IAC-02   | Mechanisms exist to uniquely identify and centrally Authenticate, Authorize and Audit (AAA) organizational users and processes acting on behalf of organizational users.                                                                | 5                        | Access rights and privileges are prohibited unless expressly permitted.                                                                                                                                                                 |
| 7.3.3   | N/A      | The access control system(s) is set to "deny all" by default.                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Role-Based Access Control (RBAC)                                      | IAC-08   | Mechanisms exist to enforce Role-Based Access Control (RBAC) for Technology Assets, Applications, Services and/or Data (TAASD) to restrict access to individuals assigned specific roles                                                | 5                        | Access rights and privileges are prohibited unless expressly permitted.                                                                                                                                                                 |
| 7.3.3   | N/A      | The access control system(s) is set to "deny all" by default.                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Least Privilege                                                       | IAC-21   | Mechanisms exist to utilize the concept of least privilege, allowing only authorized access to processes necessary to accomplish assigned tasks in accordance with organizational                                                       | 5                        | Access rights and privileges are prohibited unless expressly permitted.                                                                                                                                                                 |
| 8.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 8 are:<br>• Documented.<br>• Kept up to date.                                                                                                                                                                                                      | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                  | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 8 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 8.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 8 are:<br>• Documented.<br>• Kept up to date.                                                                                                                                                                                                      | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCR), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 8 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | STRM Rationale | STRM Relationship | SCF Control                                                 | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|-------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 8.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 8 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Subset Of         | Operations Security                                         | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 8 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 8.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 8 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                     | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                        | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 8 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 8.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 8 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPR). | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 8 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 8.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 8 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Defined Roles & Responsibilities                            | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 8 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 8.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 8 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | User Awareness                                              | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 8 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 8.2.1 | N/A      | All users are assigned a unique ID before access to system components or cardholder data is allowed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Identifier Management (User Names)                          | IAC-09   | Mechanisms exist to govern naming standards for usernames and Technology Assets, Applications and/or Services (TAAS).                                                                                                              | 5                        | All actions by all users are attributable to an individual.                                                                                                                                                                             |
| 8.2.1 | N/A      | All users are assigned a unique ID before access to system components or cardholder data is allowed.                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | User Identity (ID) Management                               | IAC-09.1 | Mechanisms exist to ensure proper user identification management for non-consumer users and administrators.                                                                                                                        | 5                        | All actions by all users are attributable to an individual.                                                                                                                                                                             |
| 8.2.2 | N/A      | Group, shared, or generic accounts, or other shared authentication credentials are only used when necessary on an                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Group Authentication                                        | IAC-02.1 | Mechanisms exist to require individuals to be authenticated with an individual authenticator when a group authenticator is                                                                                                         | 5                        | All actions performed by users with generic, system, or shared IDs are attributable to an individual person.                                                                                                                            |
| 8.2.2 | N/A      | Group, shared, or generic accounts, or other shared authentication credentials are only used when necessary on an                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Restrictions on Shared Groups / Accounts                    | IAC-15.5 | Mechanisms exist to authorize the use of shared/group accounts only under certain organization-defined conditions.                                                                                                                 | 5                        | All actions performed by users with generic, system, or shared IDs are attributable to an individual person.                                                                                                                            |
| 8.2.2 | N/A      | Group, shared, or generic accounts, or other shared authentication credentials are only used when necessary on an exception basis, and are managed as follows:<br>• Account use is prevented unless needed for an exceptional circumstance.<br>• Use is limited to the time needed for the exceptional circumstance.<br>• Business justification for use is documented.<br>• Use is explicitly approved by management.<br>• Individual user identity is confirmed before access to an account is granted.<br>• Every action taken is attributable to an individual user. | Functional     | Intersects With   | Credential Sharing                                          | IAC-19   | Mechanisms exist to prevent the sharing of generic IDs, passwords or other generic authentication methods.                                                                                                                         | 5                        | All actions performed by users with generic, system, or shared IDs are attributable to an individual person.                                                                                                                            |
| 8.2.4 | N/A      | Addition, deletion, and modification of user IDs, authentication factors, and other identifier objects are managed as follows:<br>• Authorized with the appropriate approval.<br>• Implemented with only the privileges specified on the documented approval.                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | User Provisioning & De-Provisioning                         | IAC-07   | Mechanisms exist to utilize a formal user registration and de-registration process that governs the assignment of access rights.                                                                                                   | 5                        | Lifecycle events for user IDs and authentication factors cannot occur without appropriate authorization.                                                                                                                                |
| 8.2.4 | N/A      | Addition, deletion, and modification of user IDs, authentication factors, and other identifier objects are managed as follows:<br>• Authorized with the appropriate approval.<br>• Implemented with only the privileges specified on the documented approval.                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Change of Roles & Duties                                    | IAC-07.1 | Mechanisms exist to revoke user access rights following changes in personnel roles and duties, if no longer necessary or permitted.                                                                                                | 5                        | Lifecycle events for user IDs and authentication factors cannot occur without appropriate authorization.                                                                                                                                |
| 8.2.4 | N/A      | Addition, deletion, and modification of user IDs, authentication factors, and other identifier objects are managed as follows:<br>• Authorized with the appropriate approval.<br>• Implemented with only the privileges specified on the documented approval.                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Termination of Employment                                   | IAC-07.2 | Mechanisms exist to revoke user access rights in a timely manner, upon termination of employment or contract.                                                                                                                      | 5                        | Lifecycle events for user IDs and authentication factors cannot occur without appropriate authorization.                                                                                                                                |
| 8.2.4 | N/A      | Addition, deletion, and modification of user IDs, authentication factors, and other identifier objects are managed as follows:<br>• Authorized with the appropriate approval.<br>• Implemented with only the privileges specified on the documented approval.                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Authenticator Management                                    | IAC-10   | Mechanisms exist to:<br>(1) Securely manage authenticators for users and devices; and<br>(2) Ensure the strength of authentication is appropriate to the classification of the data being accessed.                                | 5                        | Lifecycle events for user IDs and authentication factors cannot occur without appropriate authorization.                                                                                                                                |
| 8.2.4 | N/A      | Addition, deletion, and modification of user IDs, authentication factors, and other identifier objects are managed as follows:<br>• Authorized with the appropriate approval.<br>• Implemented with only the privileges specified on the documented approval.                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Account Management                                          | IAC-15   | Mechanisms exist to:<br>(1) Define authorized system account types;<br>(2) Define prohibited system account types; and<br>(3) Proactively govern individual, group, system, service, application, guest and temporary accounts.    | 5                        | Lifecycle events for user IDs and authentication factors cannot occur without appropriate authorization.                                                                                                                                |
| 8.2.5 | N/A      | Access for terminated users is immediately revoked.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Personnel Termination                                       | HRS-09   | Mechanisms exist to govern the termination of individual employment.                                                                                                                                                               | 5                        | The accounts of terminated users cannot be used.                                                                                                                                                                                        |
| 8.2.5 | N/A      | Access for terminated users is immediately revoked.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | High-Risk Terminations                                      | HRS-09.2 | Mechanisms exist to expedite the process of removing "high risk" individual's access to Technology Assets, Applications, Services and/or Data (TAASD) upon termination, as determined by management.                               | 5                        | The accounts of terminated users cannot be used.                                                                                                                                                                                        |
| 8.2.5 | N/A      | Access for terminated users is immediately revoked.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Change of Roles & Duties                                    | IAC-07.1 | Mechanisms exist to revoke user access rights following changes in personnel roles and duties, if no longer necessary or                                                                                                           | 5                        | The accounts of terminated users cannot be used.                                                                                                                                                                                        |
| 8.2.5 | N/A      | Access for terminated users is immediately revoked.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Termination of Employment                                   | IAC-07.2 | Mechanisms exist to revoke user access rights in a timely manner, upon termination of employment or contract.                                                                                                                      | 5                        | The accounts of terminated users cannot be used.                                                                                                                                                                                        |
| 8.2.5 | N/A      | Access for terminated users is immediately revoked.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Revocation of Access Authorizations                         | IAC-20.6 | Mechanisms exist to revoke logical and physical access authorizations.                                                                                                                                                             | 5                        | The accounts of terminated users cannot be used.                                                                                                                                                                                        |
| 8.2.6 | N/A      | Inactive user accounts are removed or disabled within 90 days of inactivity.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Disable Inactive Accounts                                   | IAC-15.3 | Automated mechanisms exist to disable inactive accounts after an organization-defined time period.                                                                                                                                 | 5                        | Inactive user accounts cannot be used.                                                                                                                                                                                                  |
| 8.2.7 | N/A      | Accounts used by third parties to access, support, or maintain system components via remote access are managed as follows:                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Remote Maintenance                                          | MNT-05   | Mechanisms exist to authorize, monitor and control remote, non-local maintenance and diagnostic activities.                                                                                                                        | 5                        | Third party remote access cannot be used except where specifically authorized and use is overseen by management.                                                                                                                        |
| 8.2.7 | N/A      | Accounts used by third parties to access, support, or maintain system components via remote access are managed as follows:                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Auditing Remote Maintenance                                 | MNT-05.1 | Mechanisms exist to audit remote, non-local maintenance and diagnostic sessions, as well as review the maintenance action                                                                                                          | 5                        | Third party remote access cannot be used except where specifically authorized and use is overseen by management.                                                                                                                        |
| 8.2.7 | N/A      | Accounts used by third parties to access, support, or maintain system components via remote access are managed as follows:<br>• Enabled only during the time period needed and disabled when not in use.<br>• Use is monitored for unexpected activity.                                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Remote Maintenance Disconnect Verification                  | MNT-05.4 | Mechanisms exist to provide remote disconnect verification to ensure remote, non-local maintenance and diagnostic sessions are properly terminated.                                                                                | 5                        | Third party remote access cannot be used except where specifically authorized and use is overseen by management.                                                                                                                        |



| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                   | STRM Rationale | STRM Relationship | SCF Control                                                | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                       | Strength of Relationship | Notes                                                                                                                                |
|-------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------|
| 8.2.7 | N/A      | Accounts used by third parties to access, support, or maintain system components via remote access are managed as follows:<br>• Enabled only during the time period needed and disabled when not in use.<br>• Use is monitored for unexpected activity.                                                                                                                                                     | Functional     | Intersects With   | Remote Access                                              | NET-14   | Mechanisms exist to define, control and review organization-approved, secure remote access methods.                                                                                                                                                                       | 5                        | Third party remote access cannot be used except where specifically authorized and use is overseen by management.                     |
| 8.2.7 | N/A      | Accounts used by third parties to access, support, or maintain system components via remote access are managed as follows:<br>• Enabled only during the time period needed and disabled when not in use.<br>• Use is monitored for unexpected activity.                                                                                                                                                     | Functional     | Intersects With   | Third-Party Remote Access Governance                       | NET-14.6 | Mechanisms exist to proactively control and monitor third-party accounts used to access, support, or maintain system components via remote access.                                                                                                                        | 5                        | Third party remote access cannot be used except where specifically authorized and use is overseen by management.                     |
| 8.2.8 | N/A      | If a user session has been idle for more than 15 minutes, the user is required to re-authenticate to re-activate the terminal or session.                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Re-Authentication                                          | IAC-14   | Mechanisms exist to force users and devices to re-authenticate according to organization-defined circumstances that necessitate re-authentication.                                                                                                                        | 5                        | A user session cannot be used except by the authorized user.                                                                         |
| 8.2.8 | N/A      | If a user session has been idle for more than 15 minutes, the user is required to re-authenticate to re-activate the terminal or session.                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Session Lock                                               | IAC-24   | Mechanisms exist to initiate a session lock after an organization-defined time period of inactivity, or upon receiving a request from a user and retain the session lock until the user reestablishes access using established identification and authentication methods. | 5                        | A user session cannot be used except by the authorized user.                                                                         |
| 8.2.8 | N/A      | If a user session has been idle for more than 15 minutes, the user is required to re-authenticate to re-activate the terminal or session.                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Session Termination                                        | IAC-25   | Automated mechanisms exist to log out users, both locally on the network and for remote sessions, at the end of the session or after an organization-defined period of inactivity.                                                                                        | 5                        | A user session cannot be used except by the authorized user.                                                                         |
| 8.2.8 | N/A      | If a user session has been idle for more than 15 minutes, the user is required to re-authenticate to re-activate the terminal or session.                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Network Connection Termination                             | NET-07   | Mechanisms exist to terminate network connections at the end of a session or after an organization-defined time period of inactivity.                                                                                                                                     | 5                        | A user session cannot be used except by the authorized user.                                                                         |
| 8.3.1 | N/A      | All user access to system components for users and administrators is authenticated via at least one of the following authentication factors:<br>• Something you know, such as a password or passphrase.                                                                                                                                                                                                     | Functional     | Intersects With   | Authenticator Management                                   | IAC-10   | Mechanisms exist to:<br>(1) Securely manage authenticators for users and devices; and<br>(2) Ensure the strength of authentication is appropriate to the                                                                                                                  | 5                        | An account cannot be accessed except with a combination of user identity and an authentication factor.                               |
| 8.3.1 | N/A      | All user access to system components for users and administrators is authenticated via at least one of the following authentication factors:<br>• Something you know, such as a password or passphrase.                                                                                                                                                                                                     | Functional     | Intersects With   | Password-Based Authentication                              | IAC-10.1 | Mechanisms exist to enforce complexity, length and lifespan considerations to ensure strong criteria for password-based authentication.                                                                                                                                   | 5                        | An account cannot be accessed except with a combination of user identity and an authentication factor.                               |
| 8.3.1 | N/A      | All user access to system components for users and administrators is authenticated via at least one of the following authentication factors:<br>• Something you know, such as a password or passphrase.<br>• Something you have, such as a token device or smart card.<br>• Something you are, such as a biometric element.                                                                                 | Functional     | Intersects With   | PKI-Based Authentication                                   | IAC-10.2 | Automated mechanisms exist to validate certificates by constructing and verifying a certification path to an accepted trust anchor including checking certificate status information for PKI-based authentication.                                                        | 5                        | An account cannot be accessed except with a combination of user identity and an authentication factor.                               |
| 8.3.2 | N/A      | Strong cryptography is used to render all authentication factors unreadable during transmission and storage on all system components.                                                                                                                                                                                                                                                                       | Functional     | Subset Of         | Use of Cryptographic Controls                              | CRY-01   | Mechanisms exist to facilitate the implementation of cryptographic protections controls using known public standards and trusted cryptographic technologies.                                                                                                              | 10                       | Cleartext authentication factors cannot be obtained, derived, or reused from the interception of communications or from stored data. |
| 8.3.2 | N/A      | Strong cryptography is used to render all authentication factors unreadable during transmission and storage on all system components.                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Secure Baseline Configurations                             | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                                       | 5                        | Cleartext authentication factors cannot be obtained, derived, or reused from the interception of communications or from stored data. |
| 8.3.2 | N/A      | Strong cryptography is used to render all authentication factors unreadable during transmission and storage on all system components.                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Transmission Confidentiality                               | CRY-03   | Cryptographic mechanisms exist to protect the confidentiality of data being transmitted.                                                                                                                                                                                  | 5                        | Cleartext authentication factors cannot be obtained, derived, or reused from the interception of communications or from stored data. |
| 8.3.2 | N/A      | Strong cryptography is used to render all authentication factors unreadable during transmission and storage on all system components.                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Encrypting Data At Rest                                    | CRY-05   | Cryptographic mechanisms exist to prevent unauthorized disclosure of data at rest.                                                                                                                                                                                        | 5                        | Cleartext authentication factors cannot be obtained, derived, or reused from the interception of communications or from stored data. |
| 8.3.3 | N/A      | User identity is verified before modifying any authentication factor.                                                                                                                                                                                                                                                                                                                                       | Functional     | Subset Of         | Identity & Access Management (IAM)                         | IAC-01   | Mechanisms exist to facilitate the implementation of identification and access management controls.                                                                                                                                                                       | 10                       |                                                                                                                                      |
| 8.3.3 | N/A      | User identity is verified before modifying any authentication factor.                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Identification & Authentication for Organizational Users   | IAC-02   | Mechanisms exist to uniquely identify and centrally Authenticate, Authorize and Audit (AAA) organizational users and processes acting on behalf of organizational users.                                                                                                  | 5                        |                                                                                                                                      |
| 8.3.3 | N/A      | User identity is verified before modifying any authentication factor.                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Authenticator Management                                   | IAC-10   | Mechanisms exist to:<br>(1) Securely manage authenticators for users and devices; and                                                                                                                                                                                     | 5                        |                                                                                                                                      |
| 8.3.3 | N/A      | User identity is verified before modifying any authentication factor.                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Password-Based Authentication                              | IAC-10.1 | Mechanisms exist to enforce complexity, length and lifespan considerations to ensure strong criteria for password-based authentication.                                                                                                                                   | 5                        |                                                                                                                                      |
| 8.3.3 | N/A      | User identity is verified before modifying any authentication factor.                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Identity Proofing (Identity Verification)                  | IAC-28   | Mechanisms exist to verify the identity of a user before issuing authenticators or modifying access permissions.                                                                                                                                                          | 5                        |                                                                                                                                      |
| 8.3.4 | N/A      | Invalid authentication attempts are limited by:<br>• Locking out the user ID after not more than 10 attempts.<br>• Setting the lockout duration to a minimum of 30 minutes or                                                                                                                                                                                                                               | Functional     | Intersects With   | Account Lockout                                            | IAC-22   | Mechanisms exist to enforce a limit for consecutive invalid login attempts by a user during an organization-defined time period and automatically locks the account when the maximum number                                                                               | 5                        | An authentication factor cannot be guessed in a brute force, online attack.                                                          |
| 8.3.5 | N/A      | If passwords/passphrases are used as authentication factors to meet Requirement 8.3.1, they are set and reset for each user as follows:<br>• Set to a unique value for first-time use and upon reset.                                                                                                                                                                                                       | Functional     | Intersects With   | Authenticator Management                                   | IAC-10   | Mechanisms exist to:<br>(1) Securely manage authenticators for users and devices; and                                                                                                                                                                                     | 5                        | An initial or reset password/passphrase assigned to a user cannot be used by an unauthorized user.                                   |
| 8.3.5 | N/A      | If passwords/passphrases are used as authentication factors to meet Requirement 8.3.1, they are set and reset for each user as follows:<br>• Set to a unique value for first-time use and upon reset.<br>• Forced to be changed immediately after the first use.                                                                                                                                            | Functional     | Intersects With   | User Provisioning & De-Provisioning                        | IAC-07   | Mechanisms exist to utilize a formal user registration and de-registration process that governs the assignment of access rights.                                                                                                                                          | 5                        | An initial or reset password/passphrase assigned to a user cannot be used by an unauthorized user.                                   |
| 8.3.5 | N/A      | If passwords/passphrases are used as authentication factors to meet Requirement 8.3.1, they are set and reset for each user as follows:<br>• Set to a unique value for first-time use and upon reset.<br>• Forced to be changed immediately after the first use.                                                                                                                                            | Functional     | Intersects With   | Password-Based Authentication                              | IAC-10.1 | Mechanisms exist to enforce complexity, length and lifespan considerations to ensure strong criteria for password-based authentication.                                                                                                                                   | 5                        | An initial or reset password/passphrase assigned to a user cannot be used by an unauthorized user.                                   |
| 8.3.6 | N/A      | If passwords/passphrases are used as authentication factors to meet Requirement 8.3.1, they meet the following minimum level of complexity:<br>• A minimum length of 12 characters (or if the system does not support 12 characters, a minimum length of eight characters).                                                                                                                                 | Functional     | Intersects With   | Password-Based Authentication                              | IAC-10.1 | Mechanisms exist to enforce complexity, length and lifespan considerations to ensure strong criteria for password-based authentication.                                                                                                                                   | 5                        | A guessed password/passphrase cannot be verified by either an online or offline brute force attack.                                  |
| 8.3.7 | N/A      | Individuals are not allowed to submit a new password/passphrase that is the same as any of the last four passwords/passphrases used.                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Authenticator Management                                   | IAC-10   | Mechanisms exist to:<br>(1) Securely manage authenticators for users and devices; and<br>(2) Ensure the strength of authentication is appropriate to the classification of the data being accessed.                                                                       | 5                        | A previously used password cannot be used to gain access to an account for at least 12 months.                                       |
| 8.3.7 | N/A      | Individuals are not allowed to submit a new password/passphrase that is the same as any of the last four passwords/passphrases used.                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Password-Based Authentication                              | IAC-10.1 | Mechanisms exist to enforce complexity, length and lifespan considerations to ensure strong criteria for password-based authentication.                                                                                                                                   | 5                        | A previously used password cannot be used to gain access to an account for at least 12 months.                                       |
| 8.3.8 | N/A      | Authentication policies and procedures are documented and communicated to all users including:<br>• Guidance on selecting strong authentication factors.<br>• Guidance for how users should protect their authentication factors.                                                                                                                                                                           | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                                    | 5                        | Users are knowledgeable about the correct use of authentication factors and can access assistance and guidance when required.        |
| 8.3.8 | N/A      | Authentication policies and procedures are documented and communicated to all users including:<br>• Guidance on selecting strong authentication factors.                                                                                                                                                                                                                                                    | Functional     | Subset Of         | Identity & Access Management (IAM)                         | IAC-01   | Mechanisms exist to facilitate the implementation of identification and access management controls.                                                                                                                                                                       | 10                       | Users are knowledgeable about the correct use of authentication factors and can access assistance and guidance when required.        |
| 8.3.8 | N/A      | Authentication policies and procedures are documented and communicated to all users including:<br>• Guidance on selecting strong authentication factors.<br>• Instructions not to reuse previously used passwords/passphrases.<br>• Instructions to change passwords/passphrases if there is any suspicion or knowledge that the password/passphrases have been compromised and how to report the incident. | Functional     | Subset Of         | Operations Security                                        | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                                                       | 10                       | Users are knowledgeable about the correct use of authentication factors and can access assistance and guidance when required.        |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                            | STRM Rationale | STRM Relationship | SCF Control                                              | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                          | Strength of Relationship | Notes                                                                                                                         |
|--------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|----------------------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| 8.3.8  | N/A      | Authentication policies and procedures are documented and communicated to all users including:<br>• Guidance on selecting strong authentication factors.<br>• Guidance for how users should protect their authentication factors.<br>• Instructions not to reuse previously used passwords/passphrases.<br>• Instructions to change passwords/passphrases if there is any suspicion or knowledge that the password/passphrases have been compromised and how to report the incident. | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                  | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                                  | 5                        | Users are knowledgeable about the correct use of authentication factors and can access assistance and guidance when required. |
| 8.3.8  | N/A      | Authentication policies and procedures are documented and communicated to all users including:<br>• Guidance on selecting strong authentication factors.<br>• Guidance for how users should protect their authentication factors.<br>• Instructions not to reuse previously used passwords/passphrases.<br>• Instructions to change passwords/passphrases if there is any suspicion or knowledge that the password/passphrases have been compromised and how to report the incident. | Functional     | Subset Of         | Security, Compliance & Resilience-Minded Workforce       | SAT-01   | Mechanisms exist to facilitate the implementation of security workforce development and awareness controls.                                                                                                                                                  | 10                       | Users are knowledgeable about the correct use of authentication factors and can access assistance and guidance when required. |
| 8.3.8  | N/A      | Authentication policies and procedures are documented and communicated to all users including:<br>• Guidance on selecting strong authentication factors.<br>• Guidance for how users should protect their authentication factors.<br>• Instructions not to reuse previously used passwords/passphrases.<br>• Instructions to change passwords/passphrases if there is any suspicion or knowledge that the password/passphrases have been compromised and how to report the incident. | Functional     | Intersects With   | Security, Compliance & Resilience Awareness Training     | SAT-02   | Mechanisms exist to provide all employees and contractors appropriate security, compliance and resilience awareness education and training that is relevant for their job function.                                                                          | 5                        | Users are knowledgeable about the correct use of authentication factors and can access assistance and guidance when required. |
| 8.3.8  | N/A      | Authentication policies and procedures are documented and communicated to all users including:<br>• Guidance on selecting strong authentication factors.<br>• Guidance for how users should protect their authentication factors.<br>• Instructions not to reuse previously used passwords/passphrases.<br>• Instructions to change passwords/passphrases if there is any suspicion or knowledge that the password/passphrases have been compromised and how to report the incident. | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training    | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training:<br>(1) Before authorizing access to the system or performing assigned duties;<br>(2) When required by system changes; and<br>(3) Annually thereafter.           | 5                        | Users are knowledgeable about the correct use of authentication factors and can access assistance and guidance when required. |
| 8.3.9  | N/A      | If passwords/passphrases are used as the only authentication factor for user access (i.e., in any single-factor authentication implementation) then either:<br>• Passwords/passphrases are changed at least once every 90 days.<br>OR<br>• The security posture of accounts is dynamically analyzed, and real-time access to resources is automatically determined accordingly.                                                                                                      | Functional     | Intersects With   | Identification & Authentication for Organizational Users | IAC-02   | Mechanisms exist to uniquely identify and centrally Authenticate, Authorize and Audit (AAA) organizational users and processes acting on behalf of organizational users.                                                                                     | 5                        | An undetected compromised password/passphrase cannot be used indefinitely.                                                    |
| 8.3.9  | N/A      | If passwords/passphrases are used as the only authentication factor for user access (i.e., in any single-factor authentication implementation) then either:<br>• Passwords/passphrases are changed at least once every 90 days.<br>OR<br>• The security posture of accounts is dynamically analyzed, and real-time access to resources is automatically determined accordingly.                                                                                                      | Functional     | Intersects With   | Authenticator Management                                 | IAC-10   | Mechanisms exist to:<br>(1) Securely manage authenticators for users and devices; and<br>(2) Ensure the strength of authentication is appropriate to the classification of the data being accessed.                                                          | 5                        | An undetected compromised password/passphrase cannot be used indefinitely.                                                    |
| 8.3.9  | N/A      | If passwords/passphrases are used as the only authentication factor for user access (i.e., in any single-factor authentication implementation) then either:<br>• Passwords/passphrases are changed at least once every 90 days.<br>OR<br>• The security posture of accounts is dynamically analyzed, and real-time access to resources is automatically determined accordingly.                                                                                                      | Functional     | Intersects With   | Password-Based Authentication                            | IAC-10.1 | Mechanisms exist to enforce complexity, length and lifespan considerations to ensure strong criteria for password-based authentication.                                                                                                                      | 5                        | An undetected compromised password/passphrase cannot be used indefinitely.                                                    |
| 8.3.11 | N/A      | Where authentication factors such as physical or logical security tokens, smart cards, or certificates are used:<br>• Factors are assigned to an individual user and not shared among multiple users.<br>• Physical and/or logical controls ensure only the intended user can use that factor to gain access.                                                                                                                                                                        | Functional     | Intersects With   | Authenticator Management                                 | IAC-10   | Mechanisms exist to:<br>(1) Securely manage authenticators for users and devices; and<br>(2) Ensure the strength of authentication is appropriate to the classification of the data being accessed.                                                          | 5                        | An authentication factor cannot be used by anyone other than the user to which it is assigned.                                |
| 8.3.11 | N/A      | Where authentication factors such as physical or logical security tokens, smart cards, or certificates are used:<br>• Factors are assigned to an individual user and not shared among multiple users.<br>• Physical and/or logical controls ensure only the intended user can use that factor to gain access.                                                                                                                                                                        | Functional     | Intersects With   | PKI-Based Authentication                                 | IAC-10.2 | Automated mechanisms exist to validate certificates by constructing and verifying a certification path to an accepted trust anchor including checking certificate status information for PKI-based authentication.                                           | 5                        | An authentication factor cannot be used by anyone other than the user to which it is assigned.                                |
| 8.3.11 | N/A      | Where authentication factors such as physical or logical security tokens, smart cards, or certificates are used:<br>• Factors are assigned to an individual user and not shared among multiple users.<br>• Physical and/or logical controls ensure only the intended user can use that factor to gain access.                                                                                                                                                                        | Functional     | Intersects With   | Protection of Authenticators                             | IAC-10.5 | Mechanisms exist to protect authenticators commensurate with the sensitivity of the information to which use of the authenticator permits access.                                                                                                            | 5                        | An authentication factor cannot be used by anyone other than the user to which it is assigned.                                |
| 8.3.11 | N/A      | Where authentication factors such as physical or logical security tokens, smart cards, or certificates are used:<br>• Factors are assigned to an individual user and not shared among multiple users.<br>• Physical and/or logical controls ensure only the intended user can use that factor to gain access.                                                                                                                                                                        | Functional     | Intersects With   | Hardware Token-Based Authentication                      | IAC-10.7 | Automated mechanisms exist to ensure organization-defined token quality requirements are satisfied for hardware token-based authentication.                                                                                                                  | 5                        | An authentication factor cannot be used by anyone other than the user to which it is assigned.                                |
| 8.3.11 | N/A      | Where authentication factors such as physical or logical security tokens, smart cards, or certificates are used:<br>• Factors are assigned to an individual user and not shared among multiple users.<br>• Physical and/or logical controls ensure only the intended user can use that factor to gain access.                                                                                                                                                                        | Functional     | Intersects With   | User Responsibilities for Account Management             | IAC-18   | Mechanisms exist to compel users to follow accepted practices in the use of authentication mechanisms (e.g., passwords, passphrases, physical or logical security tokens, smart cards, certificates, etc.).                                                  | 5                        | An authentication factor cannot be used by anyone other than the user to which it is assigned.                                |
| 8.3.11 | N/A      | Where authentication factors such as physical or logical security tokens, smart cards, or certificates are used:<br>• Factors are assigned to an individual user and not shared among multiple users.<br>• Physical and/or logical controls ensure only the intended user can use that factor to gain access.                                                                                                                                                                        | Functional     | Intersects With   | Physical Access Authorizations                           | PES-02   | Physical access control mechanisms exist to maintain a current list of personnel with authorized access to organizational facilities (except for those areas within the facility officially designated as publicly accessible).                              | 5                        | An authentication factor cannot be used by anyone other than the user to which it is assigned.                                |
| 8.3.11 | N/A      | Where authentication factors such as physical or logical security tokens, smart cards, or certificates are used:<br>• Factors are assigned to an individual user and not shared among multiple users.<br>• Physical and/or logical controls ensure only the intended user can use that factor to gain access.                                                                                                                                                                        | Functional     | Intersects With   | Role-Based Physical Access                               | PES-02.1 | Physical access control mechanisms exist to authorize physical access to facilities based on the position or role of the individual.                                                                                                                         | 5                        | An authentication factor cannot be used by anyone other than the user to which it is assigned.                                |
| 8.4.1  | N/A      | MFA is implemented for all non-console access into the CDE for personnel with administrative access.                                                                                                                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Network Access to Privileged Accounts                    | IAC-06.1 | Mechanisms exist to utilize Multi-Factor Authentication (MFA) to authenticate network access for privileged accounts.                                                                                                                                        | 5                        | Administrative access to the CDE cannot be obtained by the use of a single authentication factor.                             |
| 8.4.2  | N/A      | MFA is implemented for all access into the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Multi-Factor Authentication (MFA)                        | IAC-06   | Automated mechanisms exist to enforce Multi-Factor Authentication (MFA) for:<br>(1) Remote network access;<br>(2) Third-party Technology Assets, Applications and/or Services (TAAS); and/or<br>(3) Non-console access to critical TAAS that store, transmit | 5                        | Access into the CDE cannot be obtained by the use of a single authentication factor.                                          |

| FDE # | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | STRM Rationale | STRM Relationship | SCF Control                                         | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                          | Strength of Relationship | Notes                                                                                                                                                    |
|-------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| 8.4.2 | N/A      | MFA is implemented for all access into the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Network Access to Privileged Accounts               | IAC-06.1 | Mechanisms exist to utilize Multi-Factor Authentication (MFA) to authenticate network access for privileged accounts.                                                                                                                                                                                        | 5                        | Access into the CDE cannot be obtained by the use of a single authentication factor.                                                                     |
| 8.4.2 | N/A      | MFA is implemented for all access into the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Network Access to Non-Privileged Accounts           | IAC-06.2 | Mechanisms exist to utilize Multi-Factor Authentication (MFA) to authenticate network access for non-privileged accounts.                                                                                                                                                                                    | 5                        | Access into the CDE cannot be obtained by the use of a single authentication factor.                                                                     |
| 8.4.2 | N/A      | MFA is implemented for all access into the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Local Access to Privileged Accounts                 | IAC-06.3 | Mechanisms exist to utilize Multi-Factor Authentication (MFA) to authenticate local access for privileged accounts.                                                                                                                                                                                          | 5                        | Access into the CDE cannot be obtained by the use of a single authentication factor.                                                                     |
| 8.4.2 | N/A      | MFA is implemented for all access into the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Out-of-Band Multi-Factor Authentication             | IAC-06.4 | Mechanisms exist to implement Multi-Factor Authentication (MFA) for access to privileged and non-privileged accounts such                                                                                                                                                                                    | 5                        | Access into the CDE cannot be obtained by the use of a single authentication factor.                                                                     |
| 8.4.3 | N/A      | MFA is implemented for all remote network access originating from outside the entity's network that could access or impact the CDE as follows:<br>• All remote access by all personnel, both users and                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Multi-Factor Authentication (MFA)                   | IAC-06   | Automated mechanisms exist to enforce Multi-Factor Authentication (MFA) for:                                                                                                                                                                                                                                 | 5                        | Remote access to the entity's network cannot be obtained by using a single authentication factor.                                                        |
| 8.4.3 | N/A      | MFA is implemented for all remote network access originating from outside the entity's network that could access or impact the CDE as follows:<br>• All remote access by all personnel, both users and                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Network Access to Privileged Accounts               | IAC-06.1 | Mechanisms exist to utilize Multi-Factor Authentication (MFA) to authenticate network access for privileged accounts.                                                                                                                                                                                        | 5                        | Remote access to the entity's network cannot be obtained by using a single authentication factor.                                                        |
| 8.4.3 | N/A      | MFA is implemented for all remote network access originating from outside the entity's network that could access or impact the CDE as follows:<br>• All remote access by all personnel, both users and administrators, originating from outside the entity's network.<br>• All remote access by third parties and vendors.                                                                                                                                                                                                                                 | Functional     | Intersects With   | Network Access to Non-Privileged Accounts           | IAC-06.2 | Mechanisms exist to utilize Multi-Factor Authentication (MFA) to authenticate network access for non-privileged accounts.                                                                                                                                                                                    | 5                        | Remote access to the entity's network cannot be obtained by using a single authentication factor.                                                        |
| 8.5.1 | N/A      | MFA systems are implemented as follows:<br>• The MFA system is not susceptible to replay attacks.<br>• MFA systems cannot be bypassed by any users, including administrative users unless specifically documented, and authorized by management on an exception basis, for a limited time period.                                                                                                                                                                                                                                                          | Functional     | Subset Of         | Identity & Access Management (IAM)                  | IAC-01   | Mechanisms exist to facilitate the implementation of identification and access management controls.                                                                                                                                                                                                          | 10                       | MFA systems are resistant to attack and strictly control any administrative overrides.                                                                   |
| 8.5.1 | N/A      | MFA systems are implemented as follows:<br>• The MFA system is not susceptible to replay attacks.<br>• MFA systems cannot be bypassed by any users, including administrative users unless specifically documented, and authorized by management on an exception basis, for a limited time period.                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Replay-Resistant Authentication                     | IAC-02.2 | Automated mechanisms exist to employ replay-resistant authentication.                                                                                                                                                                                                                                        | 5                        | MFA systems are resistant to attack and strictly control any administrative overrides.                                                                   |
| 8.5.1 | N/A      | MFA systems are implemented as follows:<br>• The MFA system is not susceptible to replay attacks.<br>• MFA systems cannot be bypassed by any users, including administrative users unless specifically documented, and authorized by management on an exception basis, for a limited time period.<br>• At least two different types of authentication factors are used.<br>• Success of all authentication factors is required before access is granted.                                                                                                   | Functional     | Intersects With   | Multi-Factor Authentication (MFA)                   | IAC-06   | Automated mechanisms exist to enforce Multi-Factor Authentication (MFA) for:<br>(1) Remote network access;<br>(2) Third-party Technology Assets, Applications and/or Services (TAAS); and/or<br>(3) Non-console access to critical TAAS that store, transmit and/or process sensitive and/or regulated data. | 5                        | MFA systems are resistant to attack and strictly control any administrative overrides.                                                                   |
| 8.5.1 | N/A      | MFA systems are implemented as follows:<br>• The MFA system is not susceptible to replay attacks.<br>• MFA systems cannot be bypassed by any users, including administrative users unless specifically documented, and authorized by management on an exception basis, for a limited time period.<br>• At least two different types of authentication factors are used.<br>• Success of all authentication factors is required before access is granted.                                                                                                   | Functional     | Subset Of         | Secure Engineering Principles                       | SEA-01   | Mechanisms exist to facilitate the implementation of industry-recognized security, compliance and resilience practices in the specification, design, development, implementation and modification of Technology Assets, Applications and/or Services (TAAS).                                                 | 10                       | MFA systems are resistant to attack and strictly control any administrative overrides.                                                                   |
| 8.6.1 | N/A      | If accounts used by systems or applications can be used for interactive login, they are managed as follows:<br>• Interactive use is prevented unless needed for an exceptional circumstance.<br>• Interactive use is limited to the time needed for the exceptional circumstance.<br>• Business justification for interactive use is documented.<br>• Interactive use is explicitly approved by management.<br>• Individual user identity is confirmed before access to account is granted.                                                                | Functional     | Subset Of         | Identity & Access Management (IAM)                  | IAC-01   | Mechanisms exist to facilitate the implementation of identification and access management controls.                                                                                                                                                                                                          | 10                       | When used interactively, all actions with accounts designated as system or application accounts are authorized and attributable to an individual person. |
| 8.6.1 | N/A      | If accounts used by systems or applications can be used for interactive login, they are managed as follows:<br>• Interactive use is prevented unless needed for an exceptional circumstance.<br>• Interactive use is limited to the time needed for the exceptional circumstance.<br>• Business justification for interactive use is documented.<br>• Interactive use is explicitly approved by management.<br>• Individual user identity is confirmed before access to account is granted.                                                                | Functional     | Intersects With   | Sharing Identification & Authentication Information | IAC-05.1 | Mechanisms exist to ensure external service providers provide current and accurate information for any third-party user with access to the organization's data or assets.                                                                                                                                    | 5                        | When used interactively, all actions with accounts designated as system or application accounts are authorized and attributable to an individual person. |
| 8.6.1 | N/A      | If accounts used by systems or applications can be used for interactive login, they are managed as follows:<br>• Interactive use is prevented unless needed for an exceptional circumstance.<br>• Interactive use is limited to the time needed for the exceptional circumstance.<br>• Business justification for interactive use is documented.<br>• Interactive use is explicitly approved by management.<br>• Individual user identity is confirmed before access to account is granted.<br>• Every action taken is attributable to an individual user. | Functional     | Intersects With   | Account Management                                  | IAC-15   | Mechanisms exist to:<br>(1) Define authorized system account types;<br>(2) Define prohibited system account types; and<br>(3) Proactively govern individual, group, system, service, application, guest and temporary accounts.                                                                              | 5                        | When used interactively, all actions with accounts designated as system or application accounts are authorized and attributable to an individual person. |
| 8.6.1 | N/A      | If accounts used by systems or applications can be used for interactive login, they are managed as follows:<br>• Interactive use is prevented unless needed for an exceptional circumstance.<br>• Interactive use is limited to the time needed for the exceptional circumstance.<br>• Business justification for interactive use is documented.<br>• Interactive use is explicitly approved by management.<br>• Individual user identity is confirmed before access to account is granted.<br>• Every action taken is attributable to an individual user. | Functional     | Intersects With   | System Account Reviews                              | IAC-15.7 | Mechanisms exist to review all system accounts and disable any account that cannot be associated with a business process and owner.                                                                                                                                                                          | 5                        | When used interactively, all actions with accounts designated as system or application accounts are authorized and attributable to an individual person. |
| 8.6.1 | N/A      | If accounts used by systems or applications can be used for interactive login, they are managed as follows:<br>• Interactive use is prevented unless needed for an exceptional circumstance.<br>• Interactive use is limited to the time needed for the exceptional circumstance.<br>• Business justification for interactive use is documented.<br>• Interactive use is explicitly approved by management.<br>• Individual user identity is confirmed before access to account is granted.<br>• Every action taken is attributable to an individual user. | Functional     | Intersects With   | Credential Sharing                                  | IAC-19   | Mechanisms exist to prevent the sharing of generic IDs, passwords or other generic authentication methods.                                                                                                                                                                                                   | 5                        | When used interactively, all actions with accounts designated as system or application accounts are authorized and attributable to an individual person. |
| 8.6.1 | N/A      | If accounts used by systems or applications can be used for interactive login, they are managed as follows:<br>• Interactive use is prevented unless needed for an exceptional circumstance.<br>• Interactive use is limited to the time needed for the exceptional circumstance.<br>• Business justification for interactive use is documented.<br>• Interactive use is explicitly approved by management.<br>• Individual user identity is confirmed before access to account is granted.<br>• Every action taken is attributable to an individual user. | Functional     | Intersects With   | Use of Privileged Utility Programs                  | IAC-20.3 | Mechanisms exist to restrict and tightly control utility programs that are capable of overriding system and application controls.                                                                                                                                                                            | 5                        | When used interactively, all actions with accounts designated as system or application accounts are authorized and attributable to an individual person. |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                | Strength of Relationship | Notes                                                                                                                                                                                                                                   |
|---------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 8.6.1   | N/A      | If accounts used by systems or applications can be used for interactive login, they are managed as follows:<br>• Interactive use is prevented unless needed for an exceptional circumstance.<br>• Interactive use is limited to the time needed for the exceptional circumstance.<br>• Business justification for interactive use is documented.<br>• Interactive use is explicitly approved by management.<br>• Individual user identity is confirmed before access to account is granted.<br>• Every action taken is attributable to an individual user. | Functional     | Intersects With   | Least Privilege                                                       | IAC-21   | Mechanisms exist to utilize the concept of least privilege, allowing only authorized access to processes necessary to accomplish assigned tasks in accordance with organizational business functions.                                                              | 5                        | When used interactively, all actions with accounts designated as system or application accounts are authorized and attributable to an individual person.                                                                                |
| 8.6.2   | N/A      | Passwords/passphrases for any application and system accounts that can be used for interactive login are not hard coded in scripts, configuration/property files, or bespoke and custom source code.                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | No Embedded Unencrypted Static Authenticators                         | IAC-10.6 | Mechanisms exist to ensure that unencrypted, static authenticators are not embedded in applications, scripts or stored on function keys.                                                                                                                           | 5                        | Passwords/passphrases used by application and system accounts cannot be used by unauthorized personnel.                                                                                                                                 |
| 8.6.3   | N/A      | Passwords/passphrases for any application and system accounts are protected against misuse as follows:<br>• Passwords/passphrases are changed periodically (at the frequency defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1) and upon suspicion or confirmation of compromise.<br>• Passwords/passphrases are constructed with sufficient complexity appropriate for how frequently the entity changes the passwords/passphrases.                                            | Functional     | Intersects With   | Authenticator Management                                              | IAC-10   | Mechanisms exist to:<br>(1) Securely manage authenticators for users and devices; and<br>(2) Ensure the strength of authentication is appropriate to the classification of the data being accessed.                                                                | 5                        | Passwords/passphrases used by application and system accounts cannot be used indefinitely and are structured to resist brute-force and guessing attacks.                                                                                |
| 8.6.3   | N/A      | Passwords/passphrases for any application and system accounts are protected against misuse as follows:<br>• Passwords/passphrases are changed periodically (at the frequency defined in the entity's targeted risk analysis, which is                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Password-Based Authentication                                         | IAC-10.1 | Mechanisms exist to enforce complexity, length and lifespan considerations to ensure strong criteria for password-based authentication.                                                                                                                            | 5                        | Passwords/passphrases used by application and system accounts cannot be used indefinitely and are structured to resist brute-force and guessing attacks.                                                                                |
| 9.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 9 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                             | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 9 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 9.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 9 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPP), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness.           | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 9 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 9.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 9 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Subset Of         | Operations Security                                                   | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                                                | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 9 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 9.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 9 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                               | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                                        | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 9 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 9.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 9 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Subset Of         | Physical & Environmental Protections                                  | PES-01   | Mechanisms exist to facilitate the operation of physical and environmental protection controls.                                                                                                                                                                    | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 9 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 9.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 9 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities           | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPP).                                 | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 9 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 9.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 9 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Defined Roles & Responsibilities                                      | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 9 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 9.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 9 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | User Awareness                                                        | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                               | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 9 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 9.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 9 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Physical Access Control                                               | PES-03   | Physical access control mechanisms exist to enforce physical access authorizations for all physical access points (including designated entry/exit points) to facilities (excluding those areas                                                                    | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 9 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 9.2.1   | N/A      | Appropriate facility entry controls are in place to restrict physical access to systems in the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Physical Access Authorizations                                        | PES-02   | Physical access control mechanisms exist to maintain a current list of personnel with authorized access to organizational facilities (except for those areas within the facility officially                                                                        | 5                        | System components in the CDE cannot be physically accessed by unauthorized personnel.                                                                                                                                                   |
| 9.2.1   | N/A      | Appropriate facility entry controls are in place to restrict physical access to systems in the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Role-Based Physical Access                                            | PES-02.1 | Physical access control mechanisms exist to authorize physical access to facilities based on the position or role of the individual.                                                                                                                               | 5                        | System components in the CDE cannot be physically accessed by unauthorized personnel.                                                                                                                                                   |
| 9.2.1   | N/A      | Appropriate facility entry controls are in place to restrict physical access to systems in the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Physical Access Control                                               | PES-03   | Physical access control mechanisms exist to enforce physical access authorizations for all physical access points (including designated entry/exit points) to facilities (excluding those areas within the facility officially designated as publicly accessible). | 5                        | System components in the CDE cannot be physically accessed by unauthorized personnel.                                                                                                                                                   |
| 9.2.1   | N/A      | Appropriate facility entry controls are in place to restrict physical access to systems in the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Controlled Ingress & Egress Points                                    | PES-03.1 | Physical access control mechanisms exist to limit and monitor physical access through controlled ingress and egress points.                                                                                                                                        | 5                        | System components in the CDE cannot be physically accessed by unauthorized personnel.                                                                                                                                                   |
| 9.2.1   | N/A      | Appropriate facility entry controls are in place to restrict physical access to systems in the CDE.                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Physical Access Logs                                                  | PES-03.3 | Physical access control mechanisms generate a log entry for each access attempt through controlled ingress and egress points.                                                                                                                                      | 5                        | System components in the CDE cannot be physically accessed by unauthorized personnel.                                                                                                                                                   |
| 9.2.1.1 | N/A      | Individual physical access to sensitive areas within the CDE is monitored with either video cameras or physical access control mechanisms (or both) as follows:                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Physical Access Logs                                                  | PES-03.3 | Physical access control mechanisms generate a log entry for each access attempt through controlled ingress and egress points.                                                                                                                                      | 5                        | Trusted, verifiable records are maintained of individual physical entry to, and exit from, sensitive areas.                                                                                                                             |
| 9.2.1.1 | N/A      | Individual physical access to sensitive areas within the CDE is monitored with either video cameras or physical access control mechanisms (or both) as follows:                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Monitoring Physical Access                                            | PES-05   | Physical access control mechanisms exist to monitor for, detect and respond to physical security incidents.                                                                                                                                                        | 5                        | Trusted, verifiable records are maintained of individual physical entry to, and exit from, sensitive areas.                                                                                                                             |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                         | STRM Rationale | STRM Relationship | SCF Control                                      | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                     | Strength of Relationship | Notes                                                                                                                                                |
|---------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| 9.2.1.1 | N/A      | Individual physical access to sensitive areas within the CDE is monitored with either video cameras or physical access control mechanisms (or both) as follows:<br>• Entry and exit points to/from sensitive areas within the CDE are monitored.<br>• Monitoring devices or mechanisms are protected from tampering or disabling.<br>• Collected data is reviewed and correlated with other entries.<br>• Collected data is stored for at least three months, unless otherwise restricted by law. | Functional     | Intersects With   | Intrusion Alarms / Surveillance Equipment        | PES-05.1 | Physical access control mechanisms exist to monitor physical intrusion alarms and surveillance equipment.                                                                                                                               | 5                        | Trusted, verifiable records are maintained of individual physical entry to, and exit from, sensitive areas.                                          |
| 9.2.1.1 | N/A      | Individual physical access to sensitive areas within the CDE is monitored with either video cameras or physical access control mechanisms (or both) as follows:<br>• Entry and exit points to/from sensitive areas within the CDE are monitored.<br>• Monitoring devices or mechanisms are protected from tampering or disabling.<br>• Collected data is reviewed and correlated with other entries.<br>• Collected data is stored for at least three months, unless otherwise restricted by law. | Functional     | Intersects With   | Monitoring Physical Access To Critical Systems   | PES-05.2 | Facility security mechanisms exist to monitor physical access to critical systems or sensitive and/or regulated data, in addition to the physical access monitoring of the facility.                                                    | 5                        | Trusted, verifiable records are maintained of individual physical entry to, and exit from, sensitive areas.                                          |
| 9.2.2   | N/A      | Physical and/or logical controls are implemented to restrict use of publicly accessible network jacks within the facility.                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Access Control for Output Devices                | PES-12.2 | Physical security mechanisms exist to restrict access to printers and other system output devices to prevent unauthorized individuals from obtaining the output.                                                                        | 5                        | Unauthorized devices cannot connect to the entity's network from public areas within the facility.                                                   |
| 9.2.2   | N/A      | Physical and/or logical controls are implemented to restrict use of publicly accessible network jacks within the facility.                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Equipment Siting & Protection                    | PES-12   | Physical security mechanisms exist to locate system components within the facility to minimize potential damage from physical and environmental hazards and to minimize the opportunity for unauthorized access.                        | 5                        | Unauthorized devices cannot connect to the entity's network from public areas within the facility.                                                   |
| 9.2.2   | N/A      | Physical and/or logical controls are implemented to restrict use of publicly accessible network jacks within the facility.                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Transmission Medium Security                     | PES-12.1 | Physical security mechanisms exist to protect power and telecommunications cabling carrying data or supporting information services from interception, interference or damage.                                                          | 5                        | Unauthorized devices cannot connect to the entity's network from public areas within the facility.                                                   |
| 9.2.3   | N/A      | Physical access to wireless access points, gateways, networking/communications hardware, and telecommunication lines within the facility is restricted.                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Equipment Siting & Protection                    | PES-12   | Physical security mechanisms exist to locate system components within the facility to minimize potential damage from physical and environmental hazards and to minimize the opportunity for unauthorized access.                        | 5                        | Physical networking equipment cannot be accessed by unauthorized personnel.                                                                          |
| 9.2.3   | N/A      | Physical access to wireless access points, gateways, networking/communications hardware, and telecommunication lines within the facility is restricted.                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Transmission Medium Security                     | PES-12.1 | Physical security mechanisms exist to protect power and telecommunications cabling carrying data or supporting information services from interception, interference or damage.                                                          | 5                        | Physical networking equipment cannot be accessed by unauthorized personnel.                                                                          |
| 9.2.3   | N/A      | Physical access to wireless access points, gateways, networking/communications hardware, and telecommunication lines within the facility is restricted.                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Access Control for Output Devices                | PES-12.2 | Physical security mechanisms exist to restrict access to printers and other system output devices to prevent unauthorized individuals from obtaining the output.                                                                        | 5                        | Physical networking equipment cannot be accessed by unauthorized personnel.                                                                          |
| 9.2.4   | N/A      | Access to consoles in sensitive areas is restricted via locking when not in use.                                                                                                                                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Equipment Siting & Protection                    | PES-12   | Physical security mechanisms exist to locate system components within the facility to minimize potential damage from physical and environmental hazards and to minimize the opportunity for unauthorized access.                        | 5                        | Physical consoles within sensitive areas cannot be used by unauthorized personnel.                                                                   |
| 9.2.4   | N/A      | Access to consoles in sensitive areas is restricted via locking when not in use.                                                                                                                                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Lockable Physical Casings                        | PES-03.2 | Physical access control mechanisms exist to protect system components from unauthorized physical access (e.g., lockable physical casings).                                                                                              | 5                        | Physical consoles within sensitive areas cannot be used by unauthorized personnel.                                                                   |
| 9.3.1   | N/A      | Procedures are implemented for authorizing and managing physical access of personnel to the CDE, including:<br>• Identifying personnel.<br>• Managing changes to an individual's physical access                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Role-Based Physical Access                       | PES-02.1 | Physical access control mechanisms exist to authorize physical access to facilities based on the position or role of the individual.                                                                                                    | 5                        | Requirements for access to the physical CDE are defined and enforced to identify and authorize personnel.                                            |
| 9.3.1   | N/A      | Procedures are implemented for authorizing and managing physical access of personnel to the CDE, including:<br>• Identifying personnel.<br>• Managing changes to an individual's physical access requirements.                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Physical Access Authorizations                   | PES-02   | Physical access control mechanisms exist to maintain a current list of personnel with authorized access to organizational facilities (except for those areas within the facility officially                                             | 5                        | Requirements for access to the physical CDE are defined and enforced to identify and authorize personnel.                                            |
| 9.3.1   | N/A      | Procedures are implemented for authorizing and managing physical access of personnel to the CDE, including:<br>• Identifying personnel.<br>• Managing changes to an individual's physical access requirements.<br>• Revoking or terminating personnel identification.<br>• Limiting access to the identification process or system to authorized personnel.                                                                                                                                       | Functional     | Intersects With   | Controlled Ingress & Egress Points               | PES-03.1 | Physical access control mechanisms exist to limit and monitor physical access through controlled ingress and egress points.                                                                                                             | 5                        | Requirements for access to the physical CDE are defined and enforced to identify and authorize personnel.                                            |
| 9.3.1.1 | N/A      | Physical access to sensitive areas within the CDE for personnel is controlled as follows:<br>• Access is authorized and based on individual job function.<br>• Access is revoked immediately upon termination.<br>• All physical access mechanisms, such as keys, access cards, etc., are returned or disabled upon termination.                                                                                                                                                                  | Functional     | Intersects With   | Role-Based Physical Access                       | PES-02.1 | Physical access control mechanisms exist to authorize physical access to facilities based on the position or role of the individual.                                                                                                    | 5                        | Sensitive areas cannot be accessed by unauthorized personnel.                                                                                        |
| 9.3.1.1 | N/A      | Physical access to sensitive areas within the CDE for personnel is controlled as follows:<br>• Access is authorized and based on individual job function.<br>• Access is revoked immediately upon termination.<br>• All physical access mechanisms, such as keys, access cards, etc., are returned or disabled upon termination.                                                                                                                                                                  | Functional     | Intersects With   | Working in Secure Areas                          | PES-04.1 | Physical security mechanisms exist to allow only authorized personnel access to secure areas.                                                                                                                                           | 5                        | Sensitive areas cannot be accessed by unauthorized personnel.                                                                                        |
| 9.3.1.1 | N/A      | Physical access to sensitive areas within the CDE for personnel is controlled as follows:<br>• Access is authorized and based on individual job function.<br>• Access is revoked immediately upon termination.<br>• All physical access mechanisms, such as keys, access cards, etc., are returned or disabled upon termination.                                                                                                                                                                  | Functional     | Intersects With   | Physical Security of Offices, Rooms & Facilities | PES-04   | Mechanisms exist to identify systems, equipment and respective operating environments that require limited physical access so that appropriate physical access controls are designed and implemented for offices, rooms and facilities. | 5                        | Sensitive areas cannot be accessed by unauthorized personnel.                                                                                        |
| 9.3.2   | N/A      | Procedures are implemented for authorizing and managing visitor access to the CDE, including:<br>• Visitors are authorized before entering.<br>• Visitors are escorted at all times.<br>• Visitors are clearly identified and given a badge or other identification that expires.                                                                                                                                                                                                                 | Functional     | Subset Of         | Operations Security                              | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                     | 10                       |                                                                                                                                                      |
| 9.3.2   | N/A      | Procedures are implemented for authorizing and managing visitor access to the CDE, including:<br>• Visitors are authorized before entering.<br>• Visitors are escorted at all times.<br>• Visitors are clearly identified and given a badge or other identification that expires.                                                                                                                                                                                                                 | Functional     | Intersects With   | Standardized Operating Procedures (SOP)          | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                             | 5                        |                                                                                                                                                      |
| 9.3.2   | N/A      | Procedures are implemented for authorizing and managing visitor access to the CDE, including:<br>• Visitors are authorized before entering.<br>• Visitors are escorted at all times.<br>• Visitors are clearly identified and given a badge or other identification that expires.<br>• Visitor badges or other identification visibly distinguishes visitors from personnel.                                                                                                                      | Functional     | Intersects With   | Visitor Control                                  | PES-06   | Physical access control mechanisms exist to identify, authorize and monitor visitors before allowing access to the facility (other than areas designated as publicly accessible).                                                       | 5                        | Requirements for visitor access to the CDE are defined and enforced. Visitors cannot exceed any authorized physical access allowed while in the CDE. |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                           | STRM Rationale | STRM Relationship | SCF Control                                 | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                            | Strength of Relationship | Notes                                                                                                                                                |
|---------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|---------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| 9.3.2   | N/A      | Procedures are implemented for authorizing and managing visitor access to the CDE, including:<br>• Visitors are authorized before entering.<br>• Visitors are escorted at all times.<br>• Visitors are clearly identified and given a badge or other identification that expires.<br>• Visitor badges or other identification visibly distinguishes visitors from personnel.        | Functional     | Intersects With   | Distinguish Visitors from On-Site Personnel | PES-06.1 | Physical access control mechanisms exist to easily distinguish between onsite personnel and visitors, especially in areas where sensitive and/or regulated data is accessible.                                                                                 | 5                        | Requirements for visitor access to the CDE are defined and enforced. Visitors cannot exceed any authorized physical access allowed while in the CDE. |
| 9.3.2   | N/A      | Procedures are implemented for authorizing and managing visitor access to the CDE, including:<br>• Visitors are authorized before entering.<br>• Visitors are escorted at all times.<br>• Visitors are clearly identified and given a badge or other identification that expires.<br>• Visitor badges or other identification visibly distinguishes visitors from personnel.        | Functional     | Intersects With   | Identification Requirement                  | PES-06.2 | Physical access control mechanisms exist to requires at least one(1) form of government-issued or organization-issued photo identification to authenticate individuals before they can gain access to the facility.                                            | 5                        | Requirements for visitor access to the CDE are defined and enforced. Visitors cannot exceed any authorized physical access allowed while in the CDE. |
| 9.3.2   | N/A      | Procedures are implemented for authorizing and managing visitor access to the CDE, including:<br>• Visitors are authorized before entering.<br>• Visitors are escorted at all times.<br>• Visitors are clearly identified and given a badge or other identification that expires.<br>• Visitor badges or other identification visibly distinguishes visitors from personnel.        | Functional     | Intersects With   | Restrict Unescorted Access                  | PES-06.3 | Physical access control mechanisms exist to restrict unescorted access to facilities to personnel with required security clearances, formal access authorizations and validate the need for access.                                                            | 5                        | Requirements for visitor access to the CDE are defined and enforced. Visitors cannot exceed any authorized physical access allowed while in the CDE. |
| 9.3.3   | N/A      | Visitor badges or identification are surrendered or deactivated before visitors leave the facility or at the date of expiration.                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Visitor Control                             | PES-06   | Physical access control mechanisms exist to identify, authorize and monitor visitors before allowing access to the facility (other than areas designated as publicly accessible).                                                                              | 5                        | Visitor identification or badges cannot be reused after expiration.                                                                                  |
| 9.3.3   | N/A      | Visitor badges or identification are surrendered or deactivated before visitors leave the facility or at the date of expiration.                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Visitor Access Revocation                   | PES-06.6 | Mechanisms exist to ensure visitor badges, or other issued identification, are surrendered before visitors leave the facility or are deactivated at a pre-determined time/date of expiration.                                                                  | 5                        | Visitor identification or badges cannot be reused after expiration.                                                                                  |
| 9.3.4   | N/A      | A visitor log is used to maintain a physical record of visitor activity within the facility and within sensitive areas, including:<br>• The visitor's name and the organization represented.                                                                                                                                                                                        | Functional     | Intersects With   | Visitor Control                             | PES-06   | Physical access control mechanisms exist to identify, authorize and monitor visitors before allowing access to the facility (other than areas designated as publicly accessible).                                                                              | 5                        | Records of visitor access that enable the identification of individuals are maintained.                                                              |
| 9.3.4   | N/A      | A visitor log is used to maintain a physical record of visitor activity within the facility and within sensitive areas, including:<br>• The visitor's name and the organization represented.<br>• The date and time of the visit.                                                                                                                                                   | Functional     | Intersects With   | Automated Records Management & Review       | PES-06.4 | Automated mechanisms exist to facilitate the maintenance and review of visitor access records.                                                                                                                                                                 | 5                        | Records of visitor access that enable the identification of individuals are maintained.                                                              |
| 9.3.4   | N/A      | A visitor log is used to maintain a physical record of visitor activity within the facility and within sensitive areas, including:<br>• The visitor's name and the organization represented.<br>• The date and time of the visit.<br>• The name of the personnel authorizing physical access.<br>• Retaining the log for at least three months, unless otherwise restricted by law. | Functional     | Intersects With   | Minimize Visitor Personal Data (PD)         | PES-06.5 | Mechanisms exist to minimize the collection of Personal Data (PD) contained in visitor access records.                                                                                                                                                         | 5                        | Records of visitor access that enable the identification of individuals are maintained.                                                              |
| 9.4.1   | N/A      | All media with cardholder data is physically secured.                                                                                                                                                                                                                                                                                                                               | Functional     | Subset Of         | Data Protection                             | DCH-01   | Mechanisms exist to facilitate the implementation of data protection controls.                                                                                                                                                                                 | 10                       | Media with cardholder data cannot be accessed by unauthorized personnel.                                                                             |
| 9.4.1   | N/A      | All media with cardholder data is physically secured.                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Data Stewardship                            | DCH-01.1 | Mechanisms exist to ensure data stewardship is assigned, documented and communicated.                                                                                                                                                                          | 5                        | Media with cardholder data cannot be accessed by unauthorized personnel.                                                                             |
| 9.4.1   | N/A      | All media with cardholder data is physically secured.                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Media Storage                               | DCH-06   | Mechanisms exist to:<br>(1) Physically control and securely store digital and non-digital                                                                                                                                                                      | 5                        | Media with cardholder data cannot be accessed by unauthorized personnel.                                                                             |
| 9.4.1   | N/A      | All media with cardholder data is physically secured.                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Physically Secure All Media                 | DCH-06.1 | Mechanisms exist to physically secure all media that contains sensitive information.                                                                                                                                                                           | 5                        | Media with cardholder data cannot be accessed by unauthorized personnel.                                                                             |
| 9.4.1.1 | N/A      | Offline media backups with cardholder data are stored in a secure location.                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Data Backups                                | BCD-11   | Mechanisms exist to create recurring backups of data, software and/or system images, as well as verify the integrity of these backups, to ensure the availability of the data to satisfy Recovery Time Objectives (RTOs) and Recovery Point Objectives (RPOs). | 5                        | Offline backups cannot be accessed by unauthorized personnel.                                                                                        |
| 9.4.1.1 | N/A      | Offline media backups with cardholder data are stored in a secure location.                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Separate Storage for Critical Information   | BCD-11.2 | Mechanisms exist to store backup copies of critical software and other security-related information in a separate facility or in a fire-                                                                                                                       | 5                        | Offline backups cannot be accessed by unauthorized personnel.                                                                                        |
| 9.4.1.2 | N/A      | The security of the offline media backup location(s) with cardholder data is reviewed at least once every 12 months.                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Data Storage Location Reviews               | BCD-02.4 | Mechanisms exist to perform periodic security reviews of storage locations that contain sensitive and/or regulated data.                                                                                                                                       | 5                        | The security controls protecting offline backups are verified periodically by inspection.                                                            |
| 9.4.1.2 | N/A      | The security of the offline media backup location(s) with cardholder data is reviewed at least once every 12 months.                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Data Backups                                | BCD-11   | Mechanisms exist to create recurring backups of data, software and/or system images, as well as verify the integrity of these backups, to ensure the availability of the data to satisfy Recovery Time Objectives (RTOs) and Recovery Point Objectives (RPOs). | 5                        | The security controls protecting offline backups are verified periodically by inspection.                                                            |
| 9.4.1.2 | N/A      | The security of the offline media backup location(s) with cardholder data is reviewed at least once every 12 months.                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Media Storage                               | DCH-06   | Mechanisms exist to:<br>(1) Physically control and securely store digital and non-digital                                                                                                                                                                      | 5                        | The security controls protecting offline backups are verified periodically by inspection.                                                            |
| 9.4.1.2 | N/A      | The security of the offline media backup location(s) with cardholder data is reviewed at least once every 12 months.                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Physically Secure All Media                 | DCH-06.1 | Mechanisms exist to physically secure all media that contains sensitive information.                                                                                                                                                                           | 5                        | The security controls protecting offline backups are verified periodically by inspection.                                                            |
| 9.4.1.2 | N/A      | The security of the offline media backup location(s) with cardholder data is reviewed at least once every 12 months.                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Sensitive Data Inventories                  | DCH-06.2 | Mechanisms exist to maintain inventory logs of all sensitive media and conduct sensitive media inventories at least annually.                                                                                                                                  | 5                        | The security controls protecting offline backups are verified periodically by inspection.                                                            |
| 9.4.2   | N/A      | All media with cardholder data is classified in accordance with the sensitivity of the data.                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Data & Asset Classification                 | DCH-02   | Mechanisms exist to ensure data and assets are categorized in accordance with applicable statutory, regulatory and contractual                                                                                                                                 | 5                        | Media are classified and protected appropriately.                                                                                                    |
| 9.4.2   | N/A      | All media with cardholder data is classified in accordance with the sensitivity of the data.                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Risk-Based Security Categorization          | RSK-02   | Mechanisms exist to categorize Technology Assets, Applications, Services and/or Data (TAASD) in accordance with applicable laws, regulations and contractual obligations that:                                                                                 | 5                        | Media are classified and protected appropriately.                                                                                                    |
| 9.4.3   | N/A      | Media with cardholder data sent outside the facility is secured as follows:<br>• Media sent outside the facility is logged.                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Media Transportation                        | DCH-07   | Mechanisms exist to protect and control digital and non-digital media during transport outside of controlled areas using appropriate security measures.                                                                                                        | 5                        | Media is secured and tracked when transported outside the facility.                                                                                  |
| 9.4.3   | N/A      | Media with cardholder data sent outside the facility is secured as follows:<br>• Media sent outside the facility is logged.<br>• Media is sent by secured courier or other delivery method that can be accurately tracked.<br>• Offsite tracking logs include details about media location.                                                                                         | Functional     | Intersects With   | Custodians                                  | DCH-07.1 | Mechanisms exist to identify custodians throughout the transport of digital or non-digital media.                                                                                                                                                              | 5                        | Media is secured and tracked when transported outside the facility.                                                                                  |
| 9.4.4   | N/A      | Management approves all media with cardholder data that is moved outside the facility (including when media is distributed to individuals).                                                                                                                                                                                                                                         | Functional     | Intersects With   | Security of Assets & Media                  | AST-05   | Mechanisms exist to maintain strict control over Technology Assets, Applications, Services and/or Data (TAASD) to preserve confidentiality and integrity.                                                                                                      | 5                        | Media cannot leave a facility without the approval of accountable personnel.                                                                         |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                          | STRM Rationale | STRM Relationship | SCF Control                                         | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                    | Strength of Relationship | Notes                                                                                                                                                                                                                          |
|---------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 9.4.4   | N/A      | Management approves all media with cardholder data that is moved outside the facility (including when media is distributed to individuals).                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Management Approval For External Media Transfer     | AST-05.1 | Mechanisms exist to obtain management approval for any sensitive and/or regulated media that is transferred outside of the organization's facilities.                                                                                                                                                                                                                  | 5                        | Media cannot leave a facility without the approval of accountable personnel.                                                                                                                                                   |
| 9.4.5   | N/A      | Inventory logs of all electronic media with cardholder data are maintained.                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Sensitive Data Inventories                          | DCH-06.2 | Mechanisms exist to maintain inventory logs of all sensitive media and conduct sensitive media inventories at least annually.                                                                                                                                                                                                                                          | 5                        | Accurate inventories of stored electronic media are maintained.                                                                                                                                                                |
| 9.4.5.1 | N/A      | Inventories of electronic media with cardholder data are conducted at least once every 12 months.                                                                                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Sensitive Data Inventories                          | DCH-06.2 | Mechanisms exist to maintain inventory logs of all sensitive media and conduct sensitive media inventories at least annually.                                                                                                                                                                                                                                          | 5                        | Media inventories are verified periodically.                                                                                                                                                                                   |
| 9.4.6   | N/A      | Hard-copy materials with cardholder data are destroyed when no longer needed for business or legal reasons, as follows:<br>• Materials are cross-cut shredded, incinerated, or pulped so                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Personal Data (PD) Retention & Disposal             | PRI-05   | Mechanisms exist to:<br>(1) Retain Personal Data (PD), including metadata, for an organization-defined time period to fulfill the purpose(s)                                                                                                                                                                                                                           | 5                        | Cardholder data cannot be recovered from media that has been destroyed or which is pending destruction.                                                                                                                        |
| 9.4.6   | N/A      | Hard-copy materials with cardholder data are destroyed when no longer needed for business or legal reasons, as follows:<br>• Materials are cross-cut shredded, incinerated, or pulped so                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Physical Media Disposal                             | DCH-08   | Mechanisms exist to securely dispose of media when it is no longer required, using formal procedures.                                                                                                                                                                                                                                                                  | 5                        | Cardholder data cannot be recovered from media that has been destroyed or which is pending destruction.                                                                                                                        |
| 9.4.6   | N/A      | Hard-copy materials with cardholder data are destroyed when no longer needed for business or legal reasons, as follows:<br>• Materials are cross-cut shredded, incinerated, or pulped so that cardholder data cannot be reconstructed.<br>• Materials are stored in secure storage containers prior to destruction.                                                                                                                                                | Functional     | Intersects With   | Media & Data Retention                              | DCH-18   | Mechanisms exist to retain media and data in accordance with applicable statutory, regulatory and contractual obligations.                                                                                                                                                                                                                                             | 5                        | Cardholder data cannot be recovered from media that has been destroyed or which is pending destruction.                                                                                                                        |
| 9.4.7   | N/A      | Electronic media with cardholder data is destroyed when no longer needed for business or legal reasons via one of the following:<br>• The electronic media is destroyed.<br>• The cardholder data is rendered unrecoverable so that it cannot be reconstructed.                                                                                                                                                                                                    | Functional     | Intersects With   | Secure Disposal, Destruction or Re-Use of Equipment | AST-09   | Mechanisms exist to securely dispose of, destroy or repurpose system components using organization-defined techniques and methods to prevent information being recovered from these components.                                                                                                                                                                        | 5                        | Cardholder data cannot be recovered from media that has been erased or destroyed.                                                                                                                                              |
| 9.4.7   | N/A      | Electronic media with cardholder data is destroyed when no longer needed for business or legal reasons via one of the following:<br>• The electronic media is destroyed.<br>• The cardholder data is rendered unrecoverable so that it cannot be reconstructed.                                                                                                                                                                                                    | Functional     | Intersects With   | Personal Data (PD) Retention & Disposal             | PRI-05   | Mechanisms exist to:<br>(1) Retain Personal Data (PD), including metadata, for an organization-defined time period to fulfill the purpose(s) identified in the notice or as required by law;<br>(2) Dispose of, destroys, erases, and/or anonymizes the PD, regardless of the method of storage; and<br>(3) Use organization-defined techniques or methods to ensure   | 5                        | Cardholder data cannot be recovered from media that has been erased or destroyed.                                                                                                                                              |
| 9.4.7   | N/A      | Electronic media with cardholder data is destroyed when no longer needed for business or legal reasons via one of the following:<br>• The electronic media is destroyed.<br>• The cardholder data is rendered unrecoverable so that it cannot be reconstructed.                                                                                                                                                                                                    | Functional     | Intersects With   | Media & Data Retention                              | DCH-18   | Mechanisms exist to retain media and data in accordance with applicable statutory, regulatory and contractual obligations.                                                                                                                                                                                                                                             | 5                        | Cardholder data cannot be recovered from media that has been erased or destroyed.                                                                                                                                              |
| 9.4.7   | N/A      | Electronic media with cardholder data is destroyed when no longer needed for business or legal reasons via one of the following:<br>• The electronic media is destroyed.<br>• The cardholder data is rendered unrecoverable so that it cannot be reconstructed.                                                                                                                                                                                                    | Functional     | Intersects With   | System Media Sanitization                           | DCH-09   | Mechanisms exist to sanitize system media with the strength and integrity commensurate with the classification or sensitivity of the information prior to disposal, release out of organizational control or release for reuse.                                                                                                                                        | 5                        | Cardholder data cannot be recovered from media that has been erased or destroyed.                                                                                                                                              |
| 9.4.7   | N/A      | Electronic media with cardholder data is destroyed when no longer needed for business or legal reasons via one of the following:<br>• The electronic media is destroyed.<br>• The cardholder data is rendered unrecoverable so that it cannot be reconstructed.                                                                                                                                                                                                    | Functional     | Intersects With   | System Media Sanitization Documentation             | DCH-09.1 | Mechanisms exist to supervise, track, document and verify system media sanitization and disposal actions.                                                                                                                                                                                                                                                              | 5                        | Cardholder data cannot be recovered from media that has been erased or destroyed.                                                                                                                                              |
| 9.5.1   | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or                                                                                                                                                        | Functional     | Subset Of         | Asset Governance                                    | AST-01   | Mechanisms exist to facilitate an IT Asset Management (ITAM) program to implement and manage asset management controls.                                                                                                                                                                                                                                                | 10                       | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1   | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or                                                                                                                                                        | Functional     | Intersects With   | Asset Inventories                                   | AST-02   | Mechanisms exist to perform inventories of Technology Assets, Applications, Services and/or Data (TAASD) that:<br>(1) Accurately reflects the current TAASD in use;<br>(2) Identifies authorized software products, including business justification details;<br>(3) Is at the level of granularity deemed necessary for tracking                                      | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1   | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices. | Functional     | Intersects With   | Unattended End-User Equipment                       | AST-06   | Mechanisms exist to implement enhanced protection measures for unattended technology assets to protect against tampering and unauthorized access.                                                                                                                                                                                                                      | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1   | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices. | Functional     | Intersects With   | Kiosks & Point of Interaction (PoI) Devices         | AST-07   | Mechanisms exist to appropriately protect devices that capture sensitive and/or regulated data via direct physical interaction from tampering and substitution.                                                                                                                                                                                                        | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1   | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices. | Functional     | Intersects With   | Logical Tampering Protection                        | AST-15   | Mechanisms exist to assess the integrity of critical Technology Assets, Applications and/or Services (TAAS) to detect evidence of tampering, where:<br>(1) Logical assessments evaluate the integrity of critical components (e.g., configuration settings); and<br>(2) Physical assessments evaluate assets for evidence of unauthorized access and/or modifications. | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1   | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices. | Functional     | Intersects With   | Technology Asset Inspections                        | AST-15.1 | Mechanisms exist to physically and logically inspect critical technology assets to detect evidence of tampering.                                                                                                                                                                                                                                                       | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1   | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices. | Functional     | Subset Of         | Security, Compliance & Resilience-Minded Workforce  | SAT-01   | Mechanisms exist to facilitate the implementation of security workforce development and awareness controls.                                                                                                                                                                                                                                                            | 10                       | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |



| FDE #     | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | STRM Rationale | STRM Relationship | SCF Control                                               | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                                                  | Strength of Relationship | Notes                                                                                                                                                                                                                          |
|-----------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 9.5.1     | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices.                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Security, Compliance & Resilience Awareness Training      | SAT-02   | Mechanisms exist to provide all employees and contractors appropriate security, compliance and resilience awareness education and training that is relevant for their job function.                                                                                                                                                                                                                                                                                  | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1     | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices.                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training     | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training:<br>(1) Before authorizing access to the system or performing assigned duties;<br>(2) When required by system changes; and<br>(3) Annually thereafter.                                                                                                                                                                                                                   | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1     | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices.                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Sensitive / Regulated Data Storage, Handling & Processing | SAT-03.3 | Mechanisms exist to ensure that every user accessing a system processing, storing or transmitting sensitive and/or regulated data is formally trained in data handling requirements.                                                                                                                                                                                                                                                                                 | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1     | N/A      | POI devices that capture payment card data via direct physical interaction with the payment card form factor are protected from tampering and unauthorized substitution, including the following:<br>• Maintaining a list of POI devices.<br>• Periodically inspecting POI devices to look for tampering or unauthorized substitution.<br>• Training personnel to be aware of suspicious behavior and to report tampering or unauthorized substitution of devices.                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Cyber Threat Environment                                  | SAT-03.6 | Mechanisms exist to provide role-based security, compliance and resilience awareness training that is current and relevant to the cyber threats that users might encounter in day-to-day business operations.                                                                                                                                                                                                                                                        | 5                        | The entity has defined procedures to protect and manage point of interaction devices. Expectations, controls, and oversight for the management and protection of POI devices are defined and adhered to by affected personnel. |
| 9.5.1.1   | N/A      | An up-to-date list of POI devices is maintained, including:<br>• Make and model of the device.<br>• Location of device.<br>• Device serial number or other methods of unique identification.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Subset Of         | Asset Governance                                          | AST-01   | Mechanisms exist to facilitate an IT Asset Management (ITAM) program to implement and manage asset management controls.                                                                                                                                                                                                                                                                                                                                              | 10                       | The identity and location of POI devices is recorded and known at all times.                                                                                                                                                   |
| 9.5.1.1   | N/A      | An up-to-date list of POI devices is maintained, including:<br>• Make and model of the device.<br>• Location of device.<br>• Device serial number or other methods of unique identification.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Asset Inventories                                         | AST-02   | Mechanisms exist to perform inventories of Technology Assets, Applications, Services and/or Data (TAASD) that:<br>(1) Accurately reflects the current TAASD in use;<br>(2) Identifies authorized software products, including business justification details;<br>(3) Is at the level of granularity deemed necessary for tracking and reporting;<br>(4) Includes organization-defined information deemed necessary to achieve effective property accountability; and | 5                        | The identity and location of POI devices is recorded and known at all times.                                                                                                                                                   |
| 9.5.1.1   | N/A      | An up-to-date list of POI devices is maintained, including:<br>• Make and model of the device.<br>• Location of device.<br>• Device serial number or other methods of unique identification.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Kiosks & Point of Interaction (PoI) Devices               | AST-07   | Mechanisms exist to appropriately protect devices that capture sensitive and/or regulated data via direct physical interaction from tampering and substitution.                                                                                                                                                                                                                                                                                                      | 5                        | The identity and location of POI devices is recorded and known at all times.                                                                                                                                                   |
| 9.5.1.2   | N/A      | POI device surfaces are periodically inspected to detect tampering and unauthorized substitution.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Kiosks & Point of Interaction (PoI) Devices               | AST-07   | Mechanisms exist to appropriately protect devices that capture sensitive and/or regulated data via direct physical interaction from tampering and substitution.                                                                                                                                                                                                                                                                                                      | 5                        | Point of Interaction Devices cannot be tampered with, substituted without authorization, or have skimming attachments installed without timely detection.                                                                      |
| 9.5.1.2   | N/A      | POI device surfaces are periodically inspected to detect tampering and unauthorized substitution.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Physical Tampering Detection                              | AST-08   | Mechanisms exist to periodically inspect systems and system components for indicators of compromise (IoC).                                                                                                                                                                                                                                                                                                                                                           | 5                        | Point of Interaction Devices cannot be tampered with, substituted without authorization, or have skimming attachments installed without timely detection.                                                                      |
| 9.5.1.2   | N/A      | POI device surfaces are periodically inspected to detect tampering and unauthorized substitution.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Technology Asset Inspections                              | AST-15.1 | Mechanisms exist to physically and logically inspect critical technology assets to detect evidence of tampering.                                                                                                                                                                                                                                                                                                                                                     | 5                        | Point of Interaction Devices cannot be tampered with, substituted without authorization, or have skimming attachments installed without timely detection.                                                                      |
| 9.5.1.2.1 | N/A      | The frequency of periodic POI device inspections and the type of inspections performed is defined in the entity's targeted risk analysis, which is performed according to all elements specified                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Physical Tampering Detection                              | AST-08   | Mechanisms exist to periodically inspect systems and system components for indicators of compromise (IoC).                                                                                                                                                                                                                                                                                                                                                           | 5                        | POI devices are inspected at a frequency that addresses the entity's risk.                                                                                                                                                     |
| 9.5.1.3   | N/A      | Training is provided for personnel in POI environments to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be repair or maintenance personnel, before granting them access to modify or troubleshoot devices.<br>• Procedures to ensure devices are not installed, replaced, or returned without verification.<br>• Being aware of suspicious behavior around devices.<br>• Reporting suspicious behavior and indications of device tampering or substitution to appropriate personnel. | Functional     | Subset Of         | Security, Compliance & Resilience-Minded Workforce        | SAT-01   | Mechanisms exist to facilitate the implementation of security workforce development and awareness controls.                                                                                                                                                                                                                                                                                                                                                          | 10                       | Personnel are knowledgeable about the types of attacks against POI devices, the entity's technical and procedural countermeasures, and can access assistance and guidance when required.                                       |
| 9.5.1.3   | N/A      | Training is provided for personnel in POI environments to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be repair or maintenance personnel, before granting them access to modify or troubleshoot devices.<br>• Procedures to ensure devices are not installed, replaced, or returned without verification.<br>• Being aware of suspicious behavior around devices.<br>• Reporting suspicious behavior and indications of device tampering or substitution to appropriate personnel. | Functional     | Intersects With   | Security, Compliance & Resilience Awareness Training      | SAT-02   | Mechanisms exist to provide all employees and contractors appropriate security, compliance and resilience awareness education and training that is relevant for their job function.                                                                                                                                                                                                                                                                                  | 5                        | Personnel are knowledgeable about the types of attacks against POI devices, the entity's technical and procedural countermeasures, and can access assistance and guidance when required.                                       |
| 9.5.1.3   | N/A      | Training is provided for personnel in POI environments to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be repair or maintenance personnel, before granting them access to modify or troubleshoot devices.<br>• Procedures to ensure devices are not installed, replaced, or returned without verification.<br>• Being aware of suspicious behavior around devices.<br>• Reporting suspicious behavior and indications of device tampering or substitution to appropriate personnel. | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training     | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training:<br>(1) Before authorizing access to the system or performing assigned duties;<br>(2) When required by system changes; and<br>(3) Annually thereafter.                                                                                                                                                                                                                   | 5                        | Personnel are knowledgeable about the types of attacks against POI devices, the entity's technical and procedural countermeasures, and can access assistance and guidance when required.                                       |
| 9.5.1.3   | N/A      | Training is provided for personnel in POI environments to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be repair or maintenance personnel, before granting them access to modify or troubleshoot devices.<br>• Procedures to ensure devices are not installed, replaced, or returned without verification.<br>• Being aware of suspicious behavior around devices.<br>• Reporting suspicious behavior and indications of device tampering or substitution to appropriate personnel. | Functional     | Intersects With   | Sensitive / Regulated Data Storage, Handling & Processing | SAT-03.3 | Mechanisms exist to ensure that every user accessing a system processing, storing or transmitting sensitive and/or regulated data is formally trained in data handling requirements.                                                                                                                                                                                                                                                                                 | 5                        | Personnel are knowledgeable about the types of attacks against POI devices, the entity's technical and procedural countermeasures, and can access assistance and guidance when required.                                       |
| 9.5.1.3   | N/A      | Training is provided for personnel in POI environments to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be aware of attempted tampering or replacement of POI devices, and includes:<br>• Verifying the identity of any third-party persons claiming to be repair or maintenance personnel, before granting them access to modify or troubleshoot devices.<br>• Procedures to ensure devices are not installed, replaced, or returned without verification.<br>• Being aware of suspicious behavior around devices.<br>• Reporting suspicious behavior and indications of device tampering or substitution to appropriate personnel. | Functional     | Intersects With   | Cyber Threat Environment                                  | SAT-03.6 | Mechanisms exist to provide role-based security, compliance and resilience awareness training that is current and relevant to the cyber threats that users might encounter in day-to-day business operations.                                                                                                                                                                                                                                                        | 5                        | Personnel are knowledgeable about the types of attacks against POI devices, the entity's technical and procedural countermeasures, and can access assistance and guidance when required.                                       |

| FDE #    | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                           | STRM Rationale | STRM Relationship | SCF Control                                                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                      | Strength of Relationship | Notes                                                                                                                                                                                                                                    |
|----------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 10 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties. | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation                           | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                   | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 10 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 10.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 10 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties. | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program                | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPP), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness. | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 10 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 10.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 10 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties. | Functional     | Subset Of         | Operations Security                                                                  | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                                      | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 10 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 10.1.1   | N/A      | All security policies and operational procedures that are identified in Requirement 10 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties. | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                                              | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                              | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 10 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 10.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 10 are documented, assigned, and understood.                                                                    | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities                          | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPP).                       | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 10 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 10.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 10 are documented, assigned, and understood.                                                                    | Functional     | Intersects With   | Defined Roles & Responsibilities                                                     | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                     | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 10 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 10.1.2   | N/A      | Roles and responsibilities for performing activities in Requirement 10 are documented, assigned, and understood.                                                                    | Functional     | Intersects With   | User Awareness                                                                       | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                     | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 10 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                     |
| 10.2.1   | N/A      | Audit logs are enabled and active for all system components and cardholder data.                                                                                                    | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                          | 5                        | Records of all activities affecting system components and cardholder data are captured.                                                                                                                                                  |
| 10.2.1   | N/A      | Audit logs are enabled and active for all system components and cardholder data.                                                                                                    | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                      | 5                        | Records of all activities affecting system components and cardholder data are captured.                                                                                                                                                  |
| 10.2.1   | N/A      | Audit logs are enabled and active for all system components and cardholder data.                                                                                                    | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum:<br>(1) Establish what type of event occurred;                                           | 5                        | Records of all activities affecting system components and cardholder data are captured.                                                                                                                                                  |
| 10.2.1   | N/A      | Audit logs are enabled and active for all system components and cardholder data.                                                                                                    | Functional     | Intersects With   | Audit Trails                                                                         | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                                                                                          | 5                        | Records of all activities affecting system components and cardholder data are captured.                                                                                                                                                  |
| 10.2.1.1 | N/A      | Audit logs capture all individual user access to cardholder data.                                                                                                                   | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                      | 5                        | Records of all individual user access to cardholder data are captured.                                                                                                                                                                   |
| 10.2.1.1 | N/A      | Audit logs capture all individual user access to cardholder data.                                                                                                                   | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services                            | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                          | 5                        | Records of all individual user access to cardholder data are captured.                                                                                                                                                                   |
| 10.2.1.1 | N/A      | Audit logs capture all individual user access to cardholder data.                                                                                                                   | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum:<br>(1) Establish what type of event occurred;                                           | 5                        | Records of all individual user access to cardholder data are captured.                                                                                                                                                                   |
| 10.2.1.1 | N/A      | Audit logs capture all individual user access to cardholder data.                                                                                                                   | Functional     | Intersects With   | Audit Trails                                                                         | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                                                                                          | 5                        | Records of all individual user access to cardholder data are captured.                                                                                                                                                                   |
| 10.2.1.1 | N/A      | Audit logs capture all individual user access to cardholder data.                                                                                                                   | Functional     | Intersects With   | Privileged Functions Logging                                                         | MON-03.3 | Mechanisms exist to log and review the actions of users and/or services with elevated privileges.                                                                                                                                                        | 5                        | Records of all individual user access to cardholder data are captured.                                                                                                                                                                   |
| 10.2.1.2 | N/A      | Audit logs capture all actions taken by any individual with administrative access, including any interactive use of                                                                 | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                  | 5                        | Records of all actions performed by individuals with elevated privileges are captured.                                                                                                                                                   |
| 10.2.1.2 | N/A      | Audit logs capture all actions taken by any individual with administrative access, including any interactive use of                                                                 | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services                            | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                          | 5                        | Records of all actions performed by individuals with elevated privileges are captured.                                                                                                                                                   |
| 10.2.1.2 | N/A      | Audit logs capture all actions taken by any individual with administrative access, including any interactive use of application or system accounts.                                 | Functional     | Intersects With   | Auditing Use of Privileged Functions                                                 | IAC-21.4 | Mechanisms exist to audit the execution of privileged functions.                                                                                                                                                                                         | 5                        | Records of all actions performed by individuals with elevated privileges are captured.                                                                                                                                                   |
| 10.2.1.2 | N/A      | Audit logs capture all actions taken by any individual with administrative access, including any interactive use of application or system accounts.                                 | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum:<br>(1) Establish what type of event occurred;                                           | 5                        | Records of all actions performed by individuals with elevated privileges are captured.                                                                                                                                                   |
| 10.2.1.2 | N/A      | Audit logs capture all actions taken by any individual with administrative access, including any interactive use of application or system accounts.                                 | Functional     | Intersects With   | Audit Trails                                                                         | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                                                                                          | 5                        | Records of all actions performed by individuals with elevated privileges are captured.                                                                                                                                                   |
| 10.2.1.2 | N/A      | Audit logs capture all actions taken by any individual with administrative access, including any interactive use of application or system accounts.                                 | Functional     | Intersects With   | Privileged Functions Logging                                                         | MON-03.3 | Mechanisms exist to log and review the actions of users and/or services with elevated privileges.                                                                                                                                                        | 5                        | Records of all actions performed by individuals with elevated privileges are captured.                                                                                                                                                   |
| 10.2.1.3 | N/A      | Audit logs capture all access to audit logs.                                                                                                                                        | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                      | 5                        | Records of all access to audit logs are captured.                                                                                                                                                                                        |
| 10.2.1.3 | N/A      | Audit logs capture all access to audit logs.                                                                                                                                        | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                          | 5                        | Records of all access to audit logs are captured.                                                                                                                                                                                        |
| 10.2.1.3 | N/A      | Audit logs capture all access to audit logs.                                                                                                                                        | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum:<br>(1) Establish what type of event occurred;                                           | 5                        | Records of all access to audit logs are captured.                                                                                                                                                                                        |

| FDE #    | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                            | STRM Rationale | STRM Relationship | SCF Control                                                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                        | Strength of Relationship | Notes                                                                                                                                                               |
|----------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.2.1.3 | N/A      | Audit logs capture all access to audit logs.                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Audit Trails                                                                         | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                                                                                                                                                                                                                                                                            | 5                        | Records of all access to audit logs are captured.                                                                                                                   |
| 10.2.1.3 | N/A      | Audit logs capture all access to audit logs.                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Privileged Functions Logging                                                         | MON-03.3 | Mechanisms exist to log and review the actions of users and/or services with elevated privileges.                                                                                                                                                                                                                                                                                                                                          | 5                        | Records of all access to audit logs are captured.                                                                                                                   |
| 10.2.1.4 | N/A      | Audit logs capture all invalid logical access attempts.                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                                                                                                                                                    | 5                        | Records of all invalid access attempts are captured.                                                                                                                |
| 10.2.1.4 | N/A      | Audit logs capture all invalid logical access attempts.                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services                            | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                                                                                                                                                                                                            | 5                        | Records of all invalid access attempts are captured.                                                                                                                |
| 10.2.1.4 | N/A      | Audit logs capture all invalid logical access attempts.                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum: (1) Establish what type of event occurred;                                                                                                                                                                                                                                | 5                        | Records of all invalid access attempts are captured.                                                                                                                |
| 10.2.1.4 | N/A      | Audit logs capture all invalid logical access attempts.                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Audit Trails                                                                         | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                                                                                                                                                                                                                                                                            | 5                        | Records of all invalid access attempts are captured.                                                                                                                |
| 10.2.1.4 | N/A      | Audit logs capture all invalid logical access attempts.                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Privileged Functions Logging                                                         | MON-03.3 | Mechanisms exist to log and review the actions of users and/or services with elevated privileges.                                                                                                                                                                                                                                                                                                                                          | 5                        | Records of all invalid access attempts are captured.                                                                                                                |
| 10.2.1.5 | N/A      | Audit logs capture all changes to identification and authentication credentials including, but not limited to:                                                                                                                                                                                                       | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum: (1) Establish what type of event occurred;                                                                                                                                                                                                                                | 5                        | Records of all changes to identification and authentication credentials are captured.                                                                               |
| 10.2.1.5 | N/A      | Audit logs capture all changes to identification and authentication credentials including, but not limited to:                                                                                                                                                                                                       | Functional     | Intersects With   | Audit Trails                                                                         | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                                                                                                                                                                                                                                                                            | 5                        | Records of all changes to identification and authentication credentials are captured.                                                                               |
| 10.2.1.5 | N/A      | Audit logs capture all changes to identification and authentication credentials including, but not limited to:<br>• Creation of new accounts.<br>• Elevation of privileges.<br>• All changes, additions, or deletions to accounts with administrative access.                                                        | Functional     | Intersects With   | Privileged Functions Logging                                                         | MON-03.3 | Mechanisms exist to log and review the actions of users and/or services with elevated privileges.                                                                                                                                                                                                                                                                                                                                          | 5                        | Records of all changes to identification and authentication credentials are captured.                                                                               |
| 10.2.1.5 | N/A      | Audit logs capture all changes to identification and authentication credentials including, but not limited to:<br>• Creation of new accounts.<br>• Elevation of privileges.<br>• All changes, additions, or deletions to accounts with administrative access.                                                        | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                                                                                                                                                                                                        | 5                        | Records of all changes to identification and authentication credentials are captured.                                                                               |
| 10.2.1.5 | N/A      | Audit logs capture all changes to identification and authentication credentials including, but not limited to:<br>• Creation of new accounts.<br>• Elevation of privileges.<br>• All changes, additions, or deletions to accounts with administrative access.                                                        | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                                                                                                                                                                                                            | 5                        | Records of all changes to identification and authentication credentials are captured.                                                                               |
| 10.2.1.6 | N/A      | Audit logs capture the following:<br>• All initialization of new audit logs, and<br>• All starting, stopping, or pausing of the existing audit logs.                                                                                                                                                                 | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                                                                                                                                                                                                        | 5                        | Records of all changes to audit log activity status are captured.                                                                                                   |
| 10.2.1.6 | N/A      | Audit logs capture the following:<br>• All initialization of new audit logs, and<br>• All starting, stopping, or pausing of the existing audit logs.                                                                                                                                                                 | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                                                                                                                                                                                                            | 5                        | Records of all changes to audit log activity status are captured.                                                                                                   |
| 10.2.1.6 | N/A      | Audit logs capture the following:<br>• All initialization of new audit logs, and<br>• All starting, stopping, or pausing of the existing audit logs.                                                                                                                                                                 | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum: (1) Establish what type of event occurred;                                                                                                                                                                                                                                | 5                        | Records of all changes to audit log activity status are captured.                                                                                                   |
| 10.2.1.6 | N/A      | Audit logs capture the following:<br>• All initialization of new audit logs, and<br>• All starting, stopping, or pausing of the existing audit logs.                                                                                                                                                                 | Functional     | Intersects With   | Audit Trails                                                                         | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                                                                                                                                                                                                                                                                            | 5                        | Records of all changes to audit log activity status are captured.                                                                                                   |
| 10.2.1.6 | N/A      | Audit logs capture the following:<br>• All initialization of new audit logs, and<br>• All starting, stopping, or pausing of the existing audit logs.                                                                                                                                                                 | Functional     | Intersects With   | Privileged Functions Logging                                                         | MON-03.3 | Mechanisms exist to log and review the actions of users and/or services with elevated privileges.                                                                                                                                                                                                                                                                                                                                          | 5                        | Records of all changes to audit log activity status are captured.                                                                                                   |
| 10.2.1.7 | N/A      | Audit logs capture all creation and deletion of system-level objects.                                                                                                                                                                                                                                                | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                                                                                                                                                                                                            | 5                        | Records of alterations that indicate a system has been modified from its intended functionality are captured.                                                       |
| 10.2.1.7 | N/A      | Audit logs capture all creation and deletion of system-level objects.                                                                                                                                                                                                                                                | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards.                                                                                                                                                                                                                        | 5                        | Records of alterations that indicate a system has been modified from its intended functionality are captured.                                                       |
| 10.2.1.7 | N/A      | Audit logs capture all creation and deletion of system-level objects.                                                                                                                                                                                                                                                | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum: (1) Establish what type of event occurred;                                                                                                                                                                                                                                | 5                        | Records of alterations that indicate a system has been modified from its intended functionality are captured.                                                       |
| 10.2.1.7 | N/A      | Audit logs capture all creation and deletion of system-level objects.                                                                                                                                                                                                                                                | Functional     | Intersects With   | Audit Trails                                                                         | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                                                                                                                                                                                                                                                                            | 5                        | Records of alterations that indicate a system has been modified from its intended functionality are captured.                                                       |
| 10.2.1.7 | N/A      | Audit logs capture all creation and deletion of system-level objects.                                                                                                                                                                                                                                                | Functional     | Intersects With   | Privileged Functions Logging                                                         | MON-03.3 | Mechanisms exist to log and review the actions of users and/or services with elevated privileges.                                                                                                                                                                                                                                                                                                                                          | 5                        | Records of alterations that indicate a system has been modified from its intended functionality are captured.                                                       |
| 10.2.2   | N/A      | Audit logs record the following details for each auditable event:<br>• User identification.                                                                                                                                                                                                                          | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum: (1) Establish what type of event occurred;                                                                                                                                                                        | 5                        | Sufficient data to be able to identify successful and failed attempts and who, what, when, where, and how for each event                                            |
| 10.2.2   | N/A      | Audit logs record the following details for each auditable event:<br>• User identification.                                                                                                                                                                                                                          | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services                            | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                                                                                                                                                                                                                                            | 5                        | Sufficient data to be able to identify successful and failed attempts and who, what, when, where, and how for each event                                            |
| 10.2.2   | N/A      | Audit logs record the following details for each auditable event:<br>• User identification.<br>• Type of event.<br>• Date and time.<br>• Success and failure indication.<br>• Origination of event.<br>• Identity or name of affected data, system component, resource, or service (for example, name and protocol). | Functional     | Intersects With   | Content of Event Logs                                                                | MON-03   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to produce event logs that contain sufficient information to, at a minimum: (1) Establish what type of event occurred; (2) When (date and time) the event occurred; (3) Where the event occurred; (4) The source of the event; (5) The outcome (success or failure) of the event; and (6) The identity of any user/subject associated with the event. | 5                        | Sufficient data to be able to identify successful and failed attempts and who, what, when, where, and how for each event listed in requirement 10.2.1 are captured. |

| FDE #    | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                  | STRM Rationale | STRM Relationship | SCF Control                                                | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                           | Strength of Relationship | Notes                                                                                                                                                               |
|----------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.2.2   | N/A      | Audit logs record the following details for each auditable event:<br>• User identification.<br>• Type of event.<br>• Date and time.<br>• Success and failure indication.<br>• Origination of event.<br>• Identity or name of affected data, system component, resource, or service (for example, name and protocol).                                                                                                                       | Functional     | Intersects With   | Audit Trails                                               | MON-03.2 | Mechanisms exist to link system access to individual users or service accounts.                                                                                                               | 5                        | Sufficient data to be able to identify successful and failed attempts and who, what, when, where, and how for each event listed in requirement 10.2.1 are captured. |
| 10.3.1   | N/A      | Read access to audit logs files is limited to those with a job-related need.                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Protection of Event Logs                                   | MON-08   | Mechanisms exist to protect event logs and audit tools from unauthorized access, modification and deletion.                                                                                   | 5                        | Stored activity records cannot be accessed by unauthorized personnel.                                                                                               |
| 10.3.1   | N/A      | Read access to audit logs files is limited to those with a job-related need.                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Access by Subset of Privileged Users                       | MON-08.2 | Mechanisms exist to restrict access to the management of event logs to privileged users with a specific business need.                                                                        | 5                        | Stored activity records cannot be accessed by unauthorized personnel.                                                                                               |
| 10.3.2   | N/A      | Audit log files are protected to prevent modifications by individuals.                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Protection of Event Logs                                   | MON-08   | Mechanisms exist to protect event logs and audit tools from unauthorized access, modification and deletion.                                                                                   | 5                        | Stored activity records cannot be modified by personnel.                                                                                                            |
| 10.3.2   | N/A      | Audit log files are protected to prevent modifications by individuals.                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Access by Subset of Privileged Users                       | MON-08.2 | Mechanisms exist to restrict access to the management of event logs to privileged users with a specific business need.                                                                        | 5                        | Stored activity records cannot be modified by personnel.                                                                                                            |
| 10.3.3   | N/A      | Audit log files, including those for external-facing technologies, are promptly backed up to a secure, central, internal log server(s).                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Centralized Collection of Security Event Logs              | MON-02   | Mechanisms exist to utilize a Security Incident Event Manager (SIEM), or similar automated tool, to support the centralized                                                                   | 5                        | Stored activity records are secured and preserved in a central location to prevent unauthorized modification.                                                       |
| 10.3.3   | N/A      | Audit log files, including those for external-facing technologies, are promptly backed up to a secure, central, internal log server(s).                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Central Review & Analysis                                  | MON-02.2 | Automated mechanisms exist to centrally collect, review and analyze audit records from multiple sources.                                                                                      | 5                        | Stored activity records are secured and preserved in a central location to prevent unauthorized modification.                                                       |
| 10.3.3   | N/A      | Audit log files, including those for external-facing technologies, are promptly backed up to a secure, central, internal log server(s) or other media that is difficult to modify.                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Event Log Backup on Separate Physical Systems / Components | MON-08.1 | Mechanisms exist to back up event logs onto a physically different system or system component than the Security Incident Event Manager (SIEM) or similar automated tool.                      | 5                        | Stored activity records are secured and preserved in a central location to prevent unauthorized modification.                                                       |
| 10.3.4   | N/A      | File integrity monitoring or change-detection mechanisms is used on audit logs to ensure that existing log data cannot be changed without generating alerts.                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Endpoint File Integrity Monitoring (FIM)                   | END-06   | Mechanisms exist to utilize File Integrity Monitor (FIM), or similar technologies, to detect and report on unauthorized changes to selected files and configuration settings.                 | 5                        | Stored activity records cannot be modified without an alert being generated.                                                                                        |
| 10.3.4   | N/A      | File integrity monitoring or change-detection mechanisms is used on audit logs to ensure that existing log data cannot be changed without generating alerts.                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | File Integrity Monitoring (FIM)                            | MON-01.7 | Mechanisms exist to utilize a File Integrity Monitor (FIM), or similar change-detection technology, on critical Technology Assets, Applications and/or Services (TAAS) to generate alerts for | 5                        | Stored activity records cannot be modified without an alert being generated.                                                                                        |
| 10.4.1   | N/A      | The following audit logs are reviewed at least once daily:<br>• All security events.<br>• Logs of all system components that store, process, or transmit CHD and/or SAD.                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Automated Tools for Real-Time Analysis                     | MON-01.2 | Mechanisms exist to utilize a Security Incident Event Manager (SIEM), or similar automated tool, to support near real-time analysis and incident escalation.                                  | 5                        | Potentially suspicious or anomalous activities are quickly identified to minimize impact.                                                                           |
| 10.4.1   | N/A      | The following audit logs are reviewed at least once daily:<br>• All security events.<br>• Logs of all system components that store, process, or transmit CHD and/or SAD.                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | System Generated Alerts                                    | MON-01.4 | Mechanisms exist to generate, monitor, correlate and respond to alerts from physical, cybersecurity, data protection and supply chain activities to achieve integrated situational awareness. | 5                        | Potentially suspicious or anomalous activities are quickly identified to minimize impact.                                                                           |
| 10.4.1   | N/A      | The following audit logs are reviewed at least once daily:<br>• All security events.<br>• Logs of all system components that store, process, or transmit CHD and/or SAD.<br>• Logs of all critical system components.<br>• Logs of all servers and system components that perform security functions (for example, network security controls, intrusion-detection systems/intrusion-prevention systems (IDS/IPS), authentication servers). | Functional     | Intersects With   | Centralized Collection of Security Event Logs              | MON-02   | Mechanisms exist to utilize a Security Incident Event Manager (SIEM), or similar automated tool, to support the centralized collection of security-related event logs.                        | 5                        | Potentially suspicious or anomalous activities are quickly identified to minimize impact.                                                                           |
| 10.4.1   | N/A      | The following audit logs are reviewed at least once daily:<br>• All security events.<br>• Logs of all system components that store, process, or transmit CHD and/or SAD.<br>• Logs of all critical system components.<br>• Logs of all servers and system components that perform security functions (for example, network security controls, intrusion-detection systems/intrusion-prevention systems (IDS/IPS), authentication servers). | Functional     | Intersects With   | Security Event Monitoring                                  | MON-01.8 | Mechanisms exist to review event logs on an ongoing basis and escalate incidents in accordance with established timelines and procedures.                                                     | 5                        | Potentially suspicious or anomalous activities are quickly identified to minimize impact.                                                                           |
| 10.4.1   | N/A      | The following audit logs are reviewed at least once daily:<br>• All security events.<br>• Logs of all system components that store, process, or transmit CHD and/or SAD.<br>• Logs of all critical system components.<br>• Logs of all servers and system components that perform security functions (for example, network security controls, intrusion-detection systems/intrusion-prevention systems (IDS/IPS), authentication servers). | Functional     | Intersects With   | Central Review & Analysis                                  | MON-02.2 | Automated mechanisms exist to centrally collect, review and analyze audit records from multiple sources.                                                                                      | 5                        | Potentially suspicious or anomalous activities are quickly identified to minimize impact.                                                                           |
| 10.4.1.1 | N/A      | Automated mechanisms are used to perform audit log reviews.                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Automated Tools for Real-Time Analysis                     | MON-01.2 | Mechanisms exist to utilize a Security Incident Event Manager (SIEM), or similar automated tool, to support near real-time analysis and incident escalation.                                  | 5                        | Potentially suspicious or anomalous activities are identified via a repeatable and consistent mechanism.                                                            |
| 10.4.1.1 | N/A      | Automated mechanisms are used to perform audit log reviews.                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | System Generated Alerts                                    | MON-01.4 | Mechanisms exist to generate, monitor, correlate and respond to alerts from physical, cybersecurity, data protection and supply chain activities to achieve integrated situational awareness. | 5                        | Potentially suspicious or anomalous activities are identified via a repeatable and consistent mechanism.                                                            |
| 10.4.1.1 | N/A      | Automated mechanisms are used to perform audit log reviews.                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Security Event Monitoring                                  | MON-01.8 | Mechanisms exist to review event logs on an ongoing basis and escalate incidents in accordance with established timelines and procedures.                                                     | 5                        | Potentially suspicious or anomalous activities are identified via a repeatable and consistent mechanism.                                                            |
| 10.4.1.1 | N/A      | Automated mechanisms are used to perform audit log reviews.                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Centralized Collection of Security Event Logs              | MON-02   | Mechanisms exist to utilize a Security Incident Event Manager (SIEM), or similar automated tool, to support the centralized collection of security-related event logs.                        | 5                        | Potentially suspicious or anomalous activities are identified via a repeatable and consistent mechanism.                                                            |
| 10.4.1.1 | N/A      | Automated mechanisms are used to perform audit log reviews.                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Correlate Monitoring Information                           | MON-02.1 | Automated mechanisms exist to correlate both technical and non-technical information from across the enterprise by a Security Incident Event Manager (SIEM) or similar automated              | 5                        | Potentially suspicious or anomalous activities are identified via a repeatable and consistent mechanism.                                                            |
| 10.4.1.1 | N/A      | Automated mechanisms are used to perform audit log reviews.                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Central Review & Analysis                                  | MON-02.2 | Automated mechanisms exist to centrally collect, review and analyze audit records from multiple sources.                                                                                      | 5                        | Potentially suspicious or anomalous activities are identified via a repeatable and consistent mechanism.                                                            |
| 10.4.2   | N/A      | Logs of all other system components (those not specified in Requirement 10.4.1) are reviewed periodically.                                                                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Security Event Monitoring                                  | MON-01.8 | Mechanisms exist to review event logs on an ongoing basis and escalate incidents in accordance with established timelines and procedures.                                                     | 5                        | Potentially suspicious or anomalous activities for other system components (not included in 10.4.1) are reviewed in accordance with the entity's identified risk.   |
| 10.4.2.1 | N/A      | The frequency of periodic log reviews for all other system components (not defined in Requirement 10.4.1) is defined in the                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Security Event Monitoring                                  | MON-01.8 | Mechanisms exist to review event logs on an ongoing basis and escalate incidents in accordance with established timelines and                                                                 | 5                        | Log reviews for lower-risk system components are performed at a frequency that addresses the entity's risk.                                                         |
| 10.4.3   | N/A      | Exceptions and anomalies identified during the review process are addressed.                                                                                                                                                                                                                                                                                                                                                               | Functional     | Subset Of         | Continuous Monitoring                                      | MON-01   | Mechanisms exist to facilitate the implementation of enterprise-wide monitoring controls.                                                                                                     | 10                       | Suspicious or anomalous activities are addressed.                                                                                                                   |
| 10.4.3   | N/A      | Exceptions and anomalies identified during the review process are addressed.                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | System Generated Alerts                                    | MON-01.4 | Mechanisms exist to generate, monitor, correlate and respond to alerts from physical, cybersecurity, data protection and supply chain activities to achieve integrated situational awareness. | 5                        | Suspicious or anomalous activities are addressed.                                                                                                                   |
| 10.4.3   | N/A      | Exceptions and anomalies identified during the review process are addressed.                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Security Event Monitoring                                  | MON-01.8 | Mechanisms exist to review event logs on an ongoing basis and escalate incidents in accordance with established timelines and                                                                 | 5                        | Suspicious or anomalous activities are addressed.                                                                                                                   |
| 10.5.1   | N/A      | Retain audit log history for at least 12 months, with at least the most recent three months immediately available for analysis.                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Media & Data Retention                                     | DCH-18   | Mechanisms exist to retain media and data in accordance with applicable statutory, regulatory and contractual obligations.                                                                    | 5                        | Historical records of activity are available immediately to support incident response and are retained for at least 12 months.                                      |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | STRM Rationale | STRM Relationship | SCF Control                                                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                 | Strength of Relationship | Notes                                                                                                                          |
|--------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| 10.5.1 | N/A      | Retain audit log history for at least 12 months, with at least the most recent three months immediately available for analysis.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Event Log Retention                                                                  | MON-10   | Mechanisms exist to retain event logs for a time period consistent with records retention requirements to provide support for after-the-fact investigations of security incidents and                               | 5                        | Historical records of activity are available immediately to support incident response and are retained for at least 12 months. |
| 10.5.1 | N/A      | Retain audit log history for at least 12 months, with at least the most recent three months immediately available for analysis.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Personal Data (PD) Retention & Disposal                                              | PRR-05   | Mechanisms exist to:<br>(1) Retain Personal Data (PD), including metadata, for an organization-defined time period to fulfill the purpose(s)                                                                        | 5                        | Historical records of activity are available immediately to support incident response and are retained for at least 12 months. |
| 10.6.1 | N/A      | System clocks and time are synchronized using time-synchronization technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards. | 5                        | Common time is established across all systems.                                                                                 |
| 10.6.1 | N/A      | System clocks and time are synchronized using time-synchronization technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                     | 5                        | Common time is established across all systems.                                                                                 |
| 10.6.1 | N/A      | System clocks and time are synchronized using time-synchronization technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | System-Wide / Time-Correlated Audit Trail                                            | MON-02.7 | Automated mechanisms exist to compile audit records into an organization-wide audit trail that is time-correlated.                                                                                                  | 5                        | Common time is established across all systems.                                                                                 |
| 10.6.1 | N/A      | System clocks and time are synchronized using time-synchronization technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Time Stamps                                                                          | MON-07   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to use an authoritative time source to generate time stamps for event logs.                                                    | 5                        | Common time is established across all systems.                                                                                 |
| 10.6.1 | N/A      | System clocks and time are synchronized using time-synchronization technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Synchronization With Authoritative Time Source                                       | MON-07.1 | Mechanisms exist to synchronize internal system clocks with an authoritative time source.                                                                                                                           | 5                        | Common time is established across all systems.                                                                                 |
| 10.6.1 | N/A      | System clocks and time are synchronized using time-synchronization technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Clock Synchronization                                                                | SEA-20   | Mechanisms exist to utilize time-synchronization technology to synchronize all critical system clocks.                                                                                                              | 5                        | Common time is established across all systems.                                                                                 |
| 10.6.2 | N/A      | Systems are configured to the correct and consistent time as follows:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications                                                                                               | 5                        | The time on all systems is accurate and consistent.                                                                            |
| 10.6.2 | N/A      | Systems are configured to the correct and consistent time as follows:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services                            | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more                                                                                          | 5                        | The time on all systems is accurate and consistent.                                                                            |
| 10.6.2 | N/A      | Systems are configured to the correct and consistent time as follows:<br>• One or more designated time servers are in use.<br>• Only the designated central time server(s) receives time from external sources.<br>• Time received from external sources is based on International Atomic Time or Coordinated Universal Time (UTC).<br>• The designated time server(s) accept time updates only from specific industry-accepted external sources.<br>• Where there is more than one designated time server, the time servers peer with one another to keep accurate time.<br>• Internal systems receive time information only from designated central time server(s). | Functional     | Intersects With   | System-Wide / Time-Correlated Audit Trail                                            | MON-02.7 | Automated mechanisms exist to compile audit records into an organization-wide audit trail that is time-correlated.                                                                                                  | 5                        | The time on all systems is accurate and consistent.                                                                            |
| 10.6.2 | N/A      | Systems are configured to the correct and consistent time as follows:<br>• One or more designated time servers are in use.<br>• Only the designated central time server(s) receives time from external sources.<br>• Time received from external sources is based on International Atomic Time or Coordinated Universal Time (UTC).<br>• The designated time server(s) accept time updates only from specific industry-accepted external sources.<br>• Where there is more than one designated time server, the time servers peer with one another to keep accurate time.<br>• Internal systems receive time information only from designated central time server(s). | Functional     | Intersects With   | Time Stamps                                                                          | MON-07   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to use an authoritative time source to generate time stamps for event logs.                                                    | 5                        | The time on all systems is accurate and consistent.                                                                            |
| 10.6.2 | N/A      | Systems are configured to the correct and consistent time as follows:<br>• One or more designated time servers are in use.<br>• Only the designated central time server(s) receives time from external sources.<br>• Time received from external sources is based on International Atomic Time or Coordinated Universal Time (UTC).<br>• The designated time server(s) accept time updates only from specific industry-accepted external sources.<br>• Where there is more than one designated time server, the time servers peer with one another to keep accurate time.<br>• Internal systems receive time information only from designated central time server(s). | Functional     | Intersects With   | Synchronization With Authoritative Time Source                                       | MON-07.1 | Mechanisms exist to synchronize internal system clocks with an authoritative time source.                                                                                                                           | 5                        | The time on all systems is accurate and consistent.                                                                            |
| 10.6.2 | N/A      | Systems are configured to the correct and consistent time as follows:<br>• One or more designated time servers are in use.<br>• Only the designated central time server(s) receives time from external sources.<br>• Time received from external sources is based on International Atomic Time or Coordinated Universal Time (UTC).<br>• The designated time server(s) accept time updates only from specific industry-accepted external sources.<br>• Where there is more than one designated time server, the time servers peer with one another to keep accurate time.<br>• Internal systems receive time information only from designated central time server(s). | Functional     | Intersects With   | Clock Synchronization                                                                | SEA-20   | Mechanisms exist to utilize time-synchronization technology to synchronize all critical system clocks.                                                                                                              | 5                        | The time on all systems is accurate and consistent.                                                                            |
| 10.6.3 | N/A      | Time synchronization settings and data are protected as follows:<br>• Access to time data is restricted to only personnel with a business need.<br>• Any changes to time settings on critical systems are logged, monitored, and reviewed.                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Secure Baseline Configurations                                                       | CFG-02   | Mechanisms exist to develop, document and maintain secure baseline configurations for Technology Assets, Applications and/or Services (TAAS) that are consistent with industry-accepted system hardening standards. | 5                        | System time settings cannot be modified by unauthorized personnel.                                                             |
| 10.6.3 | N/A      | Time synchronization settings and data are protected as follows:<br>• Access to time data is restricted to only personnel with a business need.<br>• Any changes to time settings on critical systems are logged, monitored, and reviewed.                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Configure Technology Assets, Applications and/or Services (TAAS) for High-Risk Areas | CFG-02.5 | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) utilized in high-risk areas with more restrictive baseline configurations.                                                     | 5                        | System time settings cannot be modified by unauthorized personnel.                                                             |
| 10.6.3 | N/A      | Time synchronization settings and data are protected as follows:<br>• Access to time data is restricted to only personnel with a business need.<br>• Any changes to time settings on critical systems are logged, monitored, and reviewed.                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | System-Wide / Time-Correlated Audit Trail                                            | MON-02.7 | Automated mechanisms exist to compile audit records into an organization-wide audit trail that is time-correlated.                                                                                                  | 5                        | System time settings cannot be modified by unauthorized personnel.                                                             |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | STRM Rationale | STRM Relationship | SCF Control                                                     | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                         | Strength of Relationship | Notes                                                                                |
|--------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------|
| 10.6.3 | N/A      | Time synchronization settings and data are protected as follows:<br>• Access to time data is restricted to only personnel with a business need.<br>• Any changes to time settings on critical systems are logged, monitored, and reviewed.                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Time Stamps                                                     | MON-07   | Mechanisms exist to configure Technology Assets, Applications and/or Services (TAAS) to use an authoritative time source to generate time stamps for event logs.                                                            | 5                        | System time settings cannot be modified by unauthorized personnel.                   |
| 10.6.3 | N/A      | Time synchronization settings and data are protected as follows:<br>• Access to time data is restricted to only personnel with a business need.<br>• Any changes to time settings on critical systems are logged, monitored, and reviewed.                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Synchronization With Authoritative Time Source                  | MON-07.1 | Mechanisms exist to synchronize internal system clocks with an authoritative time source.                                                                                                                                   | 5                        | System time settings cannot be modified by unauthorized personnel.                   |
| 10.6.3 | N/A      | Time synchronization settings and data are protected as follows:<br>• Access to time data is restricted to only personnel with a business need.<br>• Any changes to time settings on critical systems are logged, monitored, and reviewed.                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Clock Synchronization                                           | SEA-20   | Mechanisms exist to utilize time-synchronization technology to synchronize all critical system clocks.                                                                                                                      | 5                        | System time settings cannot be modified by unauthorized personnel.                   |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Respond To Unauthorized Changes                                 | CFG-02.8 | Mechanisms exist to respond to unauthorized changes to configuration settings as security incidents.                                                                                                                        | 5                        | Failures in critical security control systems are promptly identified and addressed. |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Security, Compliance & Resilience Controls Oversight            | CPL-02   | Mechanisms exist to provide a security, compliance and resilience controls oversight function that reports to the organization's executive leadership.                                                                      | 5                        | Failures in critical security control systems are promptly identified and addressed. |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used). | Functional     | Intersects With   | Control Conformity Monitoring                                   | CPL-03   | Mechanisms exist to validate that Technology Assets, Applications, Services and/or Data (TAASD) conform to the organization's security, compliance and/or resilience policies, standards and other applicable requirements. | 5                        | Failures in critical security control systems are promptly identified and addressed. |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used). | Functional     | Intersects With   | Functional Review Of Security, Compliance & Resilience Controls | CPL-03.2 | Mechanisms exist to regularly review Technology Assets, Applications and/or Services (TAAS) for adherence to the organization's security, compliance and/or resilience policies and standards.                              | 5                        | Failures in critical security control systems are promptly identified and addressed. |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used). | Functional     | Intersects With   | Endpoint Detection & Response (EDR)                             | END-06.2 | Mechanisms exist to detect and respond to unauthorized configuration changes as cybersecurity incidents.                                                                                                                    | 5                        | Failures in critical security control systems are promptly identified and addressed. |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used). | Functional     | Subset Of         | Incident Response Operations                                    | IRO-01   | Mechanisms exist to implement and govern processes and documentation to facilitate an organization-wide response capability for cybersecurity and data protection-related incidents.                                        | 10                       | Failures in critical security control systems are promptly identified and addressed. |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used). | Functional     | Subset Of         | Continuous Monitoring                                           | MON-01   | Mechanisms exist to facilitate the implementation of enterprise-wide monitoring controls.                                                                                                                                   | 10                       | Failures in critical security control systems are promptly identified and addressed. |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used). | Functional     | Intersects With   | System Generated Alerts                                         | MON-01.4 | Mechanisms exist to generate, monitor, correlate and respond to alerts from physical, cybersecurity, data protection and supply chain activities to achieve integrated situational awareness.                               | 5                        | Failures in critical security control systems are promptly identified and addressed. |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used). | Functional     | Intersects With   | Risk Remediation                                                | RSK-06   | Mechanisms exist to remediate risks to an acceptable level.                                                                                                                                                                 | 5                        | Failures in critical security control systems are promptly identified and addressed. |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | STRM Rationale | STRM Relationship | SCF Control                                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                         | Strength of Relationship | Notes                                                                                                                                                                                                                      |
|--------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|----------------------------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used).                                                                                                                                          | Functional     | Intersects With   | Risk Response                                                        | RSX-06.1 | Mechanisms exist to ensure proper risk response actions were performed to remediate findings from security, compliance and/or resilience-related:<br>(1) Assessments;<br>(2) Audits; and/or<br>(3) Incidents.               | 5                        | Failures in critical security control systems are promptly identified and addressed.                                                                                                                                       |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used).                                                                                                                                          | Functional     | Intersects With   | Centralized Management of Security, Compliance & Resilience Controls | SEA-01.1 | Mechanisms exist to centrally-manage the organization-wide management and implementation of security, compliance and resilience controls and related processes.                                                             | 5                        | Failures in critical security control systems are promptly identified and addressed.                                                                                                                                       |
| 10.7.2 | N/A      | Failures of critical security control systems are detected, alerted, and addressed promptly, including but not limited to failure of the following critical security control systems:<br>• Network security controls.<br>• IDS/IPS.<br>• Change-detection mechanisms.<br>• Anti-malware solutions.<br>• Physical access controls.<br>• Logical access controls.<br>• Audit logging mechanisms.<br>• Segmentation controls (if used).<br>• Audit log review mechanisms.<br>• Automated security testing tools (if used).                                                                                                                                          | Functional     | Intersects With   | Third-Party Incident Response & Recovery Capabilities                | TPM-11   | Mechanisms exist to ensure response/recovery planning and testing are conducted with critical suppliers/providers.                                                                                                          | 5                        | Failures in critical security control systems are promptly identified and addressed.                                                                                                                                       |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to:<br>• Restoring security functions.<br>• Identifying and documenting the duration (date and time from start to end) of the security failure.<br>• Identifying and documenting the cause(s) of failure and documenting required remediation.<br>• Identifying and addressing any security issues that arose during the failure.<br>• Determining whether further actions are required as a result of the security failure.<br>• Implementing controls to prevent the cause of failure from reoccurring.                                                | Functional     | Intersects With   | Respond To Unauthorized Changes                                      | CFG-02.8 | Mechanisms exist to respond to unauthorized changes to configuration settings as security incidents.                                                                                                                        | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence. |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to:<br>• Restoring security functions.<br>• Identifying and documenting the duration (date and time from start to end) of the security failure.<br>• Identifying and documenting the cause(s) of failure and documenting required remediation.<br>• Identifying and addressing any security issues that arose during the failure.<br>• Determining whether further actions are required as a result of the security failure.<br>• Implementing controls to prevent the cause of failure from reoccurring.                                                | Functional     | Intersects With   | Control Functionality Verification                                   | CHG-06   | Mechanisms exist to verify the functionality of security, compliance and resilience controls following implemented changes to ensure applicable controls operate as designed.                                               | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence. |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to:<br>• Restoring security functions.<br>• Identifying and documenting the duration (date and time from start to end) of the security failure.<br>• Identifying and documenting the cause(s) of failure and documenting required remediation.<br>• Identifying and addressing any security issues that arose during the failure.<br>• Determining whether further actions are required as a result of the security failure.<br>• Implementing controls to prevent the cause of failure from reoccurring.<br>• Resuming monitoring of security controls. | Functional     | Intersects With   | Security, Compliance & Resilience Controls Oversight                 | CPL-02   | Mechanisms exist to provide a security, compliance and resilience controls oversight function that reports to the organization's executive leadership.                                                                      | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence. |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to:<br>• Restoring security functions.<br>• Identifying and documenting the duration (date and time from start to end) of the security failure.<br>• Identifying and documenting the cause(s) of failure and documenting required remediation.<br>• Identifying and addressing any security issues that arose during the failure.<br>• Determining whether further actions are required as a result of the security failure.<br>• Implementing controls to prevent the cause of failure from reoccurring.<br>• Resuming monitoring of security controls. | Functional     | Intersects With   | Control Conformity Monitoring                                        | CPL-03   | Mechanisms exist to validate that Technology Assets, Applications, Services and/or Data (TAASD) conform to the organization's security, compliance and/or resilience policies, standards and other applicable requirements. | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence. |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to:<br>• Restoring security functions.<br>• Identifying and documenting the duration (date and time from start to end) of the security failure.<br>• Identifying and documenting the cause(s) of failure and documenting required remediation.<br>• Identifying and addressing any security issues that arose during the failure.<br>• Determining whether further actions are required as a result of the security failure.<br>• Implementing controls to prevent the cause of failure from reoccurring.<br>• Resuming monitoring of security controls. | Functional     | Intersects With   | Functional Review Of Security, Compliance & Resilience Controls      | CPL-03.2 | Mechanisms exist to regularly review Technology Assets, Applications and/or Services (TAAS) for adherence to the organization's security, compliance and/or resilience policies and standards.                              | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence. |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to:<br>• Restoring security functions.<br>• Identifying and documenting the duration (date and time from start to end) of the security failure.<br>• Identifying and documenting the cause(s) of failure and documenting required remediation.<br>• Identifying and addressing any security issues that arose during the failure.<br>• Determining whether further actions are required as a result of the security failure.<br>• Implementing controls to prevent the cause of failure from reoccurring.<br>• Resuming monitoring of security controls. | Functional     | Intersects With   | Endpoint Detection & Response (EDR)                                  | END-06.2 | Mechanisms exist to detect and respond to unauthorized configuration changes as cybersecurity incidents.                                                                                                                    | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence. |



| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | STRM Rationale | STRM Relationship | SCF Control                                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                          | Strength of Relationship | Notes                                                                                                                                                                                                                                    |
|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|----------------------------------------------------------------------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to: <ul style="list-style-type: none"> <li>Restoring security functions.</li> <li>Identifying and documenting the duration (date and time from start to end) of the security failure.</li> <li>Identifying and documenting the cause(s) of failure and documenting required remediation.</li> <li>Identifying and addressing any security issues that arose during the failure.</li> <li>Determining whether further actions are required as a result of the security failure.</li> <li>Implementing controls to prevent the cause of failure from reoccurring.</li> <li>Resuming monitoring of security controls.</li> </ul> | Functional     | Subset Of         | Incident Response Operations                                         | IRO-01   | Mechanisms exist to implement and govern processes and documentation to facilitate an organization-wide response capability for cybersecurity and data protection-related incidents.                                                                         | 10                       | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence.               |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to: <ul style="list-style-type: none"> <li>Restoring security functions.</li> <li>Identifying and documenting the duration (date and time from start to end) of the security failure.</li> <li>Identifying and documenting the cause(s) of failure and documenting required remediation.</li> <li>Identifying and addressing any security issues that arose during the failure.</li> <li>Determining whether further actions are required as a result of the security failure.</li> <li>Implementing controls to prevent the cause of failure from reoccurring.</li> <li>Resuming monitoring of security controls.</li> </ul> | Functional     | Subset Of         | Continuous Monitoring                                                | MON-01   | Mechanisms exist to facilitate the implementation of enterprise-wide monitoring controls.                                                                                                                                                                    | 10                       | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence.               |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to: <ul style="list-style-type: none"> <li>Restoring security functions.</li> <li>Identifying and documenting the duration (date and time from start to end) of the security failure.</li> <li>Identifying and documenting the cause(s) of failure and documenting required remediation.</li> <li>Identifying and addressing any security issues that arose during the failure.</li> <li>Determining whether further actions are required as a result of the security failure.</li> <li>Implementing controls to prevent the cause of failure from reoccurring.</li> <li>Resuming monitoring of security controls.</li> </ul> | Functional     | Intersects With   | System Generated Alerts                                              | MON-01.4 | Mechanisms exist to generate, monitor, correlate and respond to alerts from physical, cybersecurity, data protection and supply chain activities to achieve integrated situational awareness.                                                                | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence.               |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to: <ul style="list-style-type: none"> <li>Restoring security functions.</li> <li>Identifying and documenting the duration (date and time from start to end) of the security failure.</li> <li>Identifying and documenting the cause(s) of failure and documenting required remediation.</li> <li>Identifying and addressing any security issues that arose during the failure.</li> <li>Determining whether further actions are required as a result of the security failure.</li> <li>Implementing controls to prevent the cause of failure from reoccurring.</li> <li>Resuming monitoring of security controls.</li> </ul> | Functional     | Intersects With   | Risk Remediation                                                     | RSK-06   | Mechanisms exist to remediate risks to an acceptable level.                                                                                                                                                                                                  | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence.               |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to: <ul style="list-style-type: none"> <li>Restoring security functions.</li> <li>Identifying and documenting the duration (date and time from start to end) of the security failure.</li> <li>Identifying and documenting the cause(s) of failure and documenting required remediation.</li> <li>Identifying and addressing any security issues that arose during the failure.</li> <li>Determining whether further actions are required as a result of the security failure.</li> <li>Implementing controls to prevent the cause of failure from reoccurring.</li> <li>Resuming monitoring of security controls.</li> </ul> | Functional     | Intersects With   | Risk Response                                                        | RSK-06.1 | Mechanisms exist to ensure proper risk response actions were performed to remediate findings from security, compliance and/or resilience-related: <ol style="list-style-type: none"> <li>Assessments;</li> <li>Audits; and/or</li> <li>Incidents.</li> </ol> | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence.               |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to: <ul style="list-style-type: none"> <li>Restoring security functions.</li> <li>Identifying and documenting the duration (date and time from start to end) of the security failure.</li> <li>Identifying and documenting the cause(s) of failure and documenting required remediation.</li> <li>Identifying and addressing any security issues that arose during the failure.</li> <li>Determining whether further actions are required as a result of the security failure.</li> <li>Implementing controls to prevent the cause of failure from reoccurring.</li> <li>Resuming monitoring of security controls.</li> </ul> | Functional     | Intersects With   | Centralized Management of Security, Compliance & Resilience Controls | SEA-01.1 | Mechanisms exist to centrally-manage the organization-wide management and implementation of security, compliance and resilience controls and related processes.                                                                                              | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence.               |
| 10.7.3 | N/A      | Failures of any critical security controls systems are responded to promptly, including but not limited to: <ul style="list-style-type: none"> <li>Restoring security functions.</li> <li>Identifying and documenting the duration (date and time from start to end) of the security failure.</li> <li>Identifying and documenting the cause(s) of failure and documenting required remediation.</li> <li>Identifying and addressing any security issues that arose during the failure.</li> <li>Determining whether further actions are required as a result of the security failure.</li> <li>Implementing controls to prevent the cause of failure from reoccurring.</li> <li>Resuming monitoring of security controls.</li> </ul> | Functional     | Intersects With   | Third-Party Incident Response & Recovery Capabilities                | TPM-11   | Mechanisms exist to ensure response/recovery planning and testing are conducted with critical suppliers/providers.                                                                                                                                           | 5                        | Failures of critical security control systems are analyzed, contained, and resolved, and security controls restored to minimize impact. Resulting security issues are addressed, and measures taken to prevent recurrence.               |
| 11.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 11 are: <ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Subset Of         | Operations Security                                                  | OPS-01   | Mechanisms exist to facilitate the implementation of operational security controls.                                                                                                                                                                          | 10                       | Expectations, controls, and oversight for meeting activities within Requirement 11 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |
| 11.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 11 are: <ul style="list-style-type: none"> <li>Documented.</li> <li>Kept up to date.</li> <li>In use.</li> <li>Known to all affected parties.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Standardized Operating Procedures (SOP)                              | OPS-01.1 | Mechanisms exist to identify and document Standardized Operating Procedures (SOP), or similar documentation, to enable the proper execution of day-to-day / assigned tasks.                                                                                  | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 11 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent. |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                                                                                                                                                  | Strength of Relationship | Notes                                                                                                                                                                                                                                                                                  |
|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 11 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                                                                                                                                                                                                                               | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 11 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent.                                               |
| 11.1.1 | N/A      | All security policies and operational procedures that are identified in Requirement 11 are:<br>• Documented.<br>• Kept up to date.<br>• In use.<br>• Known to all affected parties.                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPP), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness.                                                                                                                                                                                                             | 5                        | Expectations, controls, and oversight for meeting activities within Requirement 11 are defined and adhered to by affected personnel. All supporting activities are repeatable, consistently applied, and conform to management's intent.                                               |
| 11.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 11 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Defined Roles & Responsibilities                                      | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                                                                                                                                                                                                                                 | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 11 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                                                   |
| 11.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 11 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | User Awareness                                                        | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                                                                                                                                                                                                                                 | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 11 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                                                   |
| 11.1.2 | N/A      | Roles and responsibilities for performing activities in Requirement 11 are documented, assigned, and understood.                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities           | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPP).                                                                                                                                                                                                                                   | 5                        | Day-to-day responsibilities for performing all the activities in Requirement 11 are allocated. Personnel are accountable for successful, continuous operation of these requirements.                                                                                                   |
| 11.2.1 | N/A      | Authorized and unauthorized wireless access points are managed as follows:<br>• The presence of wireless (Wi-Fi) access points is tested for.<br>• All authorized and unauthorized wireless access points are                                                                                                                                                                                                                                                                                                                               | Functional     | Subset Of         | Network Security Controls (NSC)                                       | NET-01   | Mechanisms exist to develop, govern & update procedures to facilitate the implementation of Network Security Controls (NSC).                                                                                                                                                                                                                                                                                                                                         | 10                       | Unauthorized wireless access points are identified and addressed periodically.                                                                                                                                                                                                         |
| 11.2.1 | N/A      | Authorized and unauthorized wireless access points are managed as follows:<br>• The presence of wireless (Wi-Fi) access points is tested for.<br>• All authorized and unauthorized wireless access points are                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Guest Networks                                                        | NET-02.2 | Mechanisms exist to implement and manage a secure guest network.                                                                                                                                                                                                                                                                                                                                                                                                     | 5                        | Unauthorized wireless access points are identified and addressed periodically.                                                                                                                                                                                                         |
| 11.2.1 | N/A      | Authorized and unauthorized wireless access points are managed as follows:<br>• The presence of wireless (Wi-Fi) access points is tested for.<br>• All authorized and unauthorized wireless access points are detected and identified,<br>• Testing, detection, and identification occurs at least once every three months.<br>• If automated monitoring is used, personnel are notified via generated alerts.                                                                                                                              | Functional     | Intersects With   | Limit Network Connections                                             | NET-03.1 | Mechanisms exist to limit the number of concurrent external network connections to its Technology Assets, Applications and/or Services (TAAS).                                                                                                                                                                                                                                                                                                                       | 5                        | Unauthorized wireless access points are identified and addressed periodically.                                                                                                                                                                                                         |
| 11.2.1 | N/A      | Authorized and unauthorized wireless access points are managed as follows:<br>• The presence of wireless (Wi-Fi) access points is tested for.<br>• All authorized and unauthorized wireless access points are detected and identified,<br>• Testing, detection, and identification occurs at least once every three months.<br>• If automated monitoring is used, personnel are notified via generated alerts.                                                                                                                              | Functional     | Intersects With   | Wireless Link Protection                                              | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for unauthorized wireless access points and taking appropriate action, if an unauthorized connection is discovered.                                                                                                                                                                      | 5                        | Unauthorized wireless access points are identified and addressed periodically.                                                                                                                                                                                                         |
| 11.2.1 | N/A      | Authorized and unauthorized wireless access points are managed as follows:<br>• The presence of wireless (Wi-Fi) access points is tested for.<br>• All authorized and unauthorized wireless access points are detected and identified,<br>• Testing, detection, and identification occurs at least once every three months.<br>• If automated monitoring is used, personnel are notified via generated alerts.                                                                                                                              | Functional     | Intersects With   | Wireless Networking                                                   | NET-15   | Mechanisms exist to control authorized wireless usage and monitor for unauthorized wireless access.                                                                                                                                                                                                                                                                                                                                                                  | 5                        | Unauthorized wireless access points are identified and addressed periodically.                                                                                                                                                                                                         |
| 11.2.1 | N/A      | Authorized and unauthorized wireless access points are managed as follows:<br>• The presence of wireless (Wi-Fi) access points is tested for.<br>• All authorized and unauthorized wireless access points are detected and identified,<br>• Testing, detection, and identification occurs at least once every three months.<br>• If automated monitoring is used, personnel are notified via generated alerts.                                                                                                                              | Functional     | Intersects With   | Rogue Wireless Detection                                              | NET-15.5 | Mechanisms exist to test for the presence of Wireless Access Points (WAPs) and identify all authorized and unauthorized WAPs within the facility(ies).                                                                                                                                                                                                                                                                                                               | 5                        | Unauthorized wireless access points are identified and addressed periodically.                                                                                                                                                                                                         |
| 11.2.2 | N/A      | An inventory of authorized wireless access points is maintained, including a documented business justification.                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Subset Of         | Asset Governance                                                      | AST-01   | Mechanisms exist to facilitate an IT Asset Management (ITAM) program to implement and manage asset management controls.                                                                                                                                                                                                                                                                                                                                              | 10                       | Unauthorized wireless access points are not mistaken for authorized wireless access points.                                                                                                                                                                                            |
| 11.2.2 | N/A      | An inventory of authorized wireless access points is maintained, including a documented business justification.                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Asset Inventories                                                     | AST-02   | Mechanisms exist to perform inventories of Technology Assets, Applications, Services and/or Data (TAASD) that:<br>(1) Accurately reflects the current TAASD in use;<br>(2) Identifies authorized software products, including business justification details;<br>(3) Is at the level of granularity deemed necessary for tracking and reporting;<br>(4) Includes organization-defined information deemed necessary to achieve effective property accountability; and | 5                        | Unauthorized wireless access points are not mistaken for authorized wireless access points.                                                                                                                                                                                            |
| 11.2.2 | N/A      | An inventory of authorized wireless access points is maintained, including a documented business justification.                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Guest Networks                                                        | NET-02.2 | Mechanisms exist to implement and manage a secure guest network.                                                                                                                                                                                                                                                                                                                                                                                                     | 5                        | Unauthorized wireless access points are not mistaken for authorized wireless access points.                                                                                                                                                                                            |
| 11.2.2 | N/A      | An inventory of authorized wireless access points is maintained, including a documented business justification.                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Wireless Link Protection                                              | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for unauthorized wireless access points and taking appropriate action, if an unauthorized connection is discovered.                                                                                                                                                                      | 5                        | Unauthorized wireless access points are not mistaken for authorized wireless access points.                                                                                                                                                                                            |
| 11.2.2 | N/A      | An inventory of authorized wireless access points is maintained, including a documented business justification.                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Wireless Networking                                                   | NET-15   | Mechanisms exist to control authorized wireless usage and monitor for unauthorized wireless access.                                                                                                                                                                                                                                                                                                                                                                  | 5                        | Unauthorized wireless access points are not mistaken for authorized wireless access points.                                                                                                                                                                                            |
| 11.3.1 | N/A      | Internal vulnerability scans are performed as follows:<br>• At least once every three months.<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Attack Surface Scope                                                  | VPM-01.1 | Mechanisms exist to define and manage the scope for its attack surface management activities.                                                                                                                                                                                                                                                                                                                                                                        | 5                        | The security posture of all system components is verified periodically using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.(continued on next page) |
| 11.3.1 | N/A      | Internal vulnerability scans are performed as follows:<br>• At least once every three months.                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Vulnerability Remediation Process                                     | VPM-02   | Mechanisms exist to ensure that vulnerabilities are properly identified, tracked and remediated.                                                                                                                                                                                                                                                                                                                                                                     | 5                        | The security posture of all system components is verified periodically using automated tools designed to detect                                                                                                                                                                        |
| 11.3.1 | N/A      | Internal vulnerability scans are performed as follows:<br>• At least once every three months.<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.<br>• Rescans are performed that confirm all high- risk and critical vulnerabilities (as noted above) have been resolved.<br>• Scan tool is kept up to date with latest vulnerability information.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists. | Functional     | Intersects With   | Vulnerability Scanning                                                | VPM-06   | Mechanisms exist to detect vulnerabilities and configuration errors by routine vulnerability scanning of systems and applications.                                                                                                                                                                                                                                                                                                                                   | 5                        | The security posture of all system components is verified periodically using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.(continued on next page) |

| FDE #    | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | STRM Rationale | STRM Relationship | SCF Control                             | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                     | Strength of Relationship | Notes                                                                                                                                                                                                                                                                                                         |
|----------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11.3.1   | N/A      | Internal vulnerability scans are performed as follows:<br>• At least once every three months.<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.<br>• Rescans are performed that confirm all high-risk and critical vulnerabilities (as noted above) have been resolved.<br>• Scan tool is kept up to date with latest vulnerability information.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists. | Functional     | Intersects With   | Update Tool Capability                  | VPM-06.1 | Mechanisms exist to update vulnerability scanning tools.                                                                                                                                                                                                                                                | 5                        | The security posture of all system components is verified periodically using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.(continued on next page)                        |
| 11.3.1   | N/A      | Internal vulnerability scans are performed as follows:<br>• At least once every three months.<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.<br>• Rescans are performed that confirm all high-risk and critical vulnerabilities (as noted above) have been resolved.<br>• Scan tool is kept up to date with latest vulnerability information.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists. | Functional     | Intersects With   | Breadth / Depth of Coverage             | VPM-06.2 | Mechanisms exist to identify the breadth and depth of coverage for vulnerability scanning that define the system components scanned and types of vulnerabilities that are checked for.                                                                                                                  | 5                        | The security posture of all system components is verified periodically using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.(continued on next page)                        |
| 11.3.1   | N/A      | Internal vulnerability scans are performed as follows:<br>• At least once every three months.<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.<br>• Rescans are performed that confirm all high-risk and critical vulnerabilities (as noted above) have been resolved.<br>• Scan tool is kept up to date with latest vulnerability information.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists. | Functional     | Intersects With   | Internal Vulnerability Assessment Scans | VPM-06.7 | Mechanisms exist to perform quarterly internal vulnerability scans, which includes all segments of the organization's internal network, as well as rescans until passing results are obtained or all "high" vulnerabilities are resolved, as defined by the Common Vulnerability Scoring System (CVSS). | 5                        | The security posture of all system components is verified periodically using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.(continued on next page)                        |
| 11.3.1.1 | N/A      | All other applicable vulnerabilities (those not ranked as high-risk or critical per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are managed as follows:<br>• Addressed based on the risk defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1.<br>• Rescans are conducted as needed.                                                                                                                                                    | Functional     | Intersects With   | Attack Surface Scope                    | VPM-01.1 | Mechanisms exist to define and manage the scope for its attack surface management activities.                                                                                                                                                                                                           | 5                        | Lower ranked vulnerabilities (lower than high or critical) are addressed at a frequency in accordance with the entity's risk.                                                                                                                                                                                 |
| 11.3.1.1 | N/A      | All other applicable vulnerabilities (those not ranked as high-risk or critical per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are managed as follows:<br>• Addressed based on the risk defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1.<br>• Rescans are conducted as needed.                                                                                                                                                    | Functional     | Intersects With   | Vulnerability Remediation Process       | VPM-02   | Mechanisms exist to ensure that vulnerabilities are properly identified, tracked and remediated.                                                                                                                                                                                                        | 5                        | Lower ranked vulnerabilities (lower than high or critical) are addressed at a frequency in accordance with the entity's risk.                                                                                                                                                                                 |
| 11.3.1.1 | N/A      | All other applicable vulnerabilities (those not ranked as high-risk or critical per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are managed as follows:<br>• Addressed based on the risk defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1.<br>• Rescans are conducted as needed.                                                                                                                                                    | Functional     | Intersects With   | Vulnerability Scanning                  | VPM-06   | Mechanisms exist to detect vulnerabilities and configuration errors by routine vulnerability scanning of systems and applications.                                                                                                                                                                      | 5                        | Lower ranked vulnerabilities (lower than high or critical) are addressed at a frequency in accordance with the entity's risk.                                                                                                                                                                                 |
| 11.3.1.2 | N/A      | Internal vulnerability scans are performed via automated scanning as follows:<br>• Systems that are unable to accept credentials for authenticated scanning are documented.<br>• Sufficient privileges are used for those systems that accept credentials for scanning.<br>• If accounts used for authenticated scanning can be used for interactive login, they are managed in accordance with Requirement 8.2.2.                                                                                                                         | Functional     | Intersects With   | Attack Surface Scope                    | VPM-01.1 | Mechanisms exist to define and manage the scope for its attack surface management activities.                                                                                                                                                                                                           | 5                        | Automated tools used to detect vulnerabilities can detect vulnerabilities local to each system, which are not visible remotely.                                                                                                                                                                               |
| 11.3.1.2 | N/A      | Internal vulnerability scans are performed via automated scanning as follows:<br>• Systems that are unable to accept credentials for authenticated scanning are documented.<br>• Sufficient privileges are used for those systems that accept credentials for scanning.<br>• If accounts used for authenticated scanning can be used for interactive login, they are managed in accordance with Requirement 8.2.2.                                                                                                                         | Functional     | Intersects With   | Vulnerability Remediation Process       | VPM-02   | Mechanisms exist to ensure that vulnerabilities are properly identified, tracked and remediated.                                                                                                                                                                                                        | 5                        | Automated tools used to detect vulnerabilities can detect vulnerabilities local to each system, which are not visible remotely.                                                                                                                                                                               |
| 11.3.1.2 | N/A      | Internal vulnerability scans are performed via authenticated scanning as follows:<br>• Systems that are unable to accept credentials for authenticated scanning are documented.<br>• Sufficient privileges are used for those systems that accept credentials for scanning.<br>• If accounts used for authenticated scanning can be used for interactive login, they are managed in accordance with Requirement 8.2.2.                                                                                                                     | Functional     | Intersects With   | Vulnerability Scanning                  | VPM-06   | Mechanisms exist to detect vulnerabilities and configuration errors by routine vulnerability scanning of systems and applications.                                                                                                                                                                      | 5                        | Automated tools used to detect vulnerabilities can detect vulnerabilities local to each system, which are not visible remotely.                                                                                                                                                                               |
| 11.3.1.2 | N/A      | Internal vulnerability scans are performed via authenticated scanning as follows:<br>• Systems that are unable to accept credentials for authenticated scanning are documented.<br>• Sufficient privileges are used for those systems that accept credentials for scanning.<br>• If accounts used for authenticated scanning can be used for interactive login, they are managed in accordance with Requirement 8.2.2.                                                                                                                     | Functional     | Intersects With   | Internal Vulnerability Assessment Scans | VPM-06.7 | Mechanisms exist to perform quarterly internal vulnerability scans, which includes all segments of the organization's internal network, as well as rescans until passing results are obtained or all "high" vulnerabilities are resolved, as defined by the Common Vulnerability Scoring System (CVSS). | 5                        | Automated tools used to detect vulnerabilities can detect vulnerabilities local to each system, which are not visible remotely.                                                                                                                                                                               |
| 11.3.1.3 | N/A      | Internal vulnerability scans are performed after any significant change as follows:<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                    | Functional     | Intersects With   | Attack Surface Scope                    | VPM-01.1 | Mechanisms exist to define and manage the scope for its attack surface management activities.                                                                                                                                                                                                           | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework. |
| 11.3.1.3 | N/A      | Internal vulnerability scans are performed after any significant change as follows:<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                    | Functional     | Intersects With   | Vulnerability Remediation Process       | VPM-02   | Mechanisms exist to ensure that vulnerabilities are properly identified, tracked and remediated.                                                                                                                                                                                                        | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework. |
| 11.3.1.3 | N/A      | Internal vulnerability scans are performed after any significant change as follows:<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                    | Functional     | Intersects With   | Vulnerability Scanning                  | VPM-06   | Mechanisms exist to detect vulnerabilities and configuration errors by routine vulnerability scanning of systems and applications.                                                                                                                                                                      | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework. |

| FDE #    | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | STRM Rationale | STRM Relationship | SCF Control                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                       | Strength of Relationship | Notes                                                                                                                                                                                                                                                                                                         |
|----------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11.3.1.3 | N/A      | Internal vulnerability scans are performed after any significant change as follows:<br>• High-risk and critical vulnerabilities (per the entity's vulnerability risk rankings defined at Requirement 6.3.1) are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Internal Vulnerability Assessment Scans               | VPM-06.7 | Mechanisms exist to perform quarterly internal vulnerability scans, which includes all segments of the organization's internal network, as well as rescans until passing results are obtained or all "high" vulnerabilities are resolved, as defined by the Common Vulnerability Scoring System (CVSS).                                   | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using automated tools designed to detect vulnerabilities operating inside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework. |
| 11.3.2   | N/A      | External vulnerability scans are performed as follows:<br>• At least once every three months.<br>• By a PCI SSC Approved Scanning Vendor (ASV).<br>• Vulnerabilities are resolved and ASV Program Guide requirements for a passing scan are met.<br>• Rescans are performed as needed to confirm that vulnerabilities are resolved per the ASV Program Guide requirements for a passing scan.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Attack Surface Scope                                  | VPM-01.1 | Mechanisms exist to define and manage the scope for its attack surface management activities.                                                                                                                                                                                                                                             | 5                        | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                 |
| 11.3.2   | N/A      | External vulnerability scans are performed as follows:<br>• At least once every three months.<br>• By a PCI SSC Approved Scanning Vendor (ASV).<br>• Vulnerabilities are resolved and ASV Program Guide requirements for a passing scan are met.<br>• Rescans are performed as needed to confirm that vulnerabilities are resolved per the ASV Program Guide requirements for a passing scan.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Vulnerability Remediation Process                     | VPM-02   | Mechanisms exist to ensure that vulnerabilities are properly identified, tracked and remediated.                                                                                                                                                                                                                                          | 5                        | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                 |
| 11.3.2   | N/A      | External vulnerability scans are performed as follows:<br>• At least once every three months.<br>• By a PCI SSC Approved Scanning Vendor (ASV).<br>• Vulnerabilities are resolved and ASV Program Guide requirements for a passing scan are met.<br>• Rescans are performed as needed to confirm that vulnerabilities are resolved per the ASV Program Guide requirements for a passing scan.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Vulnerability Scanning                                | VPM-06   | Mechanisms exist to detect vulnerabilities and configuration errors by routine vulnerability scanning of systems and applications.                                                                                                                                                                                                        | 5                        | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                 |
| 11.3.2   | N/A      | External vulnerability scans are performed as follows:<br>• At least once every three months.<br>• By a PCI SSC Approved Scanning Vendor (ASV).<br>• Vulnerabilities are resolved and ASV Program Guide requirements for a passing scan are met.<br>• Rescans are performed as needed to confirm that vulnerabilities are resolved per the ASV Program Guide requirements for a passing scan.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | External Vulnerability Assessment Scans               | VPM-06.6 | Mechanisms exist to perform quarterly external vulnerability scans (outside the organization's network looking inward) via a reputable vulnerability service provider, which include rescans until passing results are obtained or all "high" vulnerabilities are resolved, as defined by the Common Vulnerability Scoring System (CVSS). | 5                        | This requirement is not eligible for the customized approach.                                                                                                                                                                                                                                                 |
| 11.3.2.1 | N/A      | External vulnerability scans are performed after any significant change as follows:<br>• Vulnerabilities that are scored 4.0 or higher by the CVSS are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Vulnerability Scanning                                | VPM-06   | Mechanisms exist to detect vulnerabilities and configuration errors by routine vulnerability scanning of systems and applications.                                                                                                                                                                                                        | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using tools designed to detect vulnerabilities operating from outside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.     |
| 11.3.2.1 | N/A      | External vulnerability scans are performed after any significant change as follows:<br>• Vulnerabilities that are scored 4.0 or higher by the CVSS are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Attack Surface Scope                                  | VPM-01.1 | Mechanisms exist to define and manage the scope for its attack surface management activities.                                                                                                                                                                                                                                             | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using tools designed to detect vulnerabilities operating from outside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.     |
| 11.3.2.1 | N/A      | External vulnerability scans are performed after any significant change as follows:<br>• Vulnerabilities that are scored 4.0 or higher by the CVSS are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Breadth / Depth of Coverage                           | VPM-06.2 | Mechanisms exist to identify the breadth and depth of coverage for vulnerability scanning that define the system components scanned and types of vulnerabilities that are checked for.                                                                                                                                                    | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using tools designed to detect vulnerabilities operating from outside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.     |
| 11.3.2.1 | N/A      | External vulnerability scans are performed after any significant change as follows:<br>• Vulnerabilities that are scored 4.0 or higher by the CVSS are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | External Vulnerability Assessment Scans               | VPM-06.6 | Mechanisms exist to perform quarterly external vulnerability scans (outside the organization's network looking inward) via a reputable vulnerability service provider, which include rescans until passing results are obtained or all "high" vulnerabilities are resolved, as defined by the Common Vulnerability Scoring System (CVSS). | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using tools designed to detect vulnerabilities operating from outside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.     |
| 11.3.2.1 | N/A      | External vulnerability scans are performed after any significant change as follows:<br>• Vulnerabilities that are scored 4.0 or higher by the CVSS are resolved.<br>• Rescans are conducted as needed.<br>• Scans are performed by qualified personnel and organizational independence of the tester exists (not required to be a QSA or ASV).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Vulnerability Remediation Process                     | VPM-02   | Mechanisms exist to ensure that vulnerabilities are properly identified, tracked and remediated.                                                                                                                                                                                                                                          | 5                        | The security posture of all system components is verified following significant changes to the network or systems, by using tools designed to detect vulnerabilities operating from outside the network. Detected vulnerabilities are assessed and rectified based on a formal risk assessment framework.     |
| 11.4.1   | N/A      | A penetration testing methodology is defined, documented, and implemented by the entity, and includes:<br>• Industry-accepted penetration testing approaches.<br>• Coverage for the entire CDE perimeter and critical systems.<br>• Testing from both inside and outside the network.<br>• Testing to validate any segmentation and scope-reduction controls.<br>• Application-layer penetration testing to identify, at a minimum,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Media & Data Retention                                | DCH-18   | Mechanisms exist to retain media and data in accordance with applicable statutory, regulatory and contractual obligations.                                                                                                                                                                                                                | 5                        | A formal methodology is defined for thorough technical testing that attempts to exploit vulnerabilities and security weaknesses via simulated attack methods by a competent manual attacker.                                                                                                                  |
| 11.4.1   | N/A      | A penetration testing methodology is defined, documented, and implemented by the entity, and includes:<br>• Industry-accepted penetration testing approaches.<br>• Coverage for the entire CDE perimeter and critical systems.<br>• Testing from both inside and outside the network.<br>• Testing to validate any segmentation and scope-reduction controls.<br>• Application-layer penetration testing to identify, at a minimum,                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Threat Analysis & Flow Remediation During Development | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                                                                                                                | 5                        | A formal methodology is defined for thorough technical testing that attempts to exploit vulnerabilities and security weaknesses via simulated attack methods by a competent manual attacker.                                                                                                                  |
| 11.4.1   | N/A      | A penetration testing methodology is defined, documented, and implemented by the entity, and includes:<br>• Industry-accepted penetration testing approaches.<br>• Coverage for the entire CDE perimeter and critical systems.<br>• Testing from both inside and outside the network.<br>• Testing to validate any segmentation and scope-reduction controls.<br>• Application-layer penetration testing to identify, at a minimum, the vulnerabilities listed in Requirement 6.2.4.<br>• Network-layer penetration tests that encompass all components that support network functions as well as operating systems.<br>• Review and consideration of threats and vulnerabilities experienced in the last 12 months.<br>• Documented approach to assessing and addressing the risk posed by exploitable vulnerabilities and security weaknesses found during penetration testing.<br>• Retention of penetration testing results and remediation activities results for at least 12 months. | Functional     | Intersects With   | Developer Threat Analysis & Flow Remediation          | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production.                                                                                  | 5                        | A formal methodology is defined for thorough technical testing that attempts to exploit vulnerabilities and security weaknesses via simulated attack methods by a competent manual attacker.                                                                                                                  |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | STRM Rationale | STRM Relationship | SCF Control                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                      | Strength of Relationship | Notes                                                                                                                                                                                                                                                              |
|--------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11.4.1 | N/A      | A penetration testing methodology is defined, documented, and implemented by the entity, and includes: <ul style="list-style-type: none"> <li>Industry-accepted penetration testing approaches.</li> <li>Coverage for the entire CDE perimeter and critical systems.</li> <li>Testing from both inside and outside the network.</li> <li>Testing to validate any segmentation and scope-reduction controls.</li> <li>Application-layer penetration testing to identify, at a minimum, the vulnerabilities listed in Requirement 6.2.4.</li> <li>Network-layer penetration tests that encompass all components that support network functions as well as operating systems.</li> <li>Review and consideration of threats and vulnerabilities experienced in the last 12 months.</li> <li>Documented approach to assessing and addressing the risk posed by exploitable vulnerabilities and security weaknesses found during penetration testing.</li> <li>Retention of penetration testing results and remediation activities results for at least 12 months.</li> </ul> | Functional     | Intersects With   | Penetration Testing                                   | VPM-07   | Mechanisms exist to conduct penetration testing on Technology Assets, Applications and/or Services (TAAS).                                                                                                                                               | 5                        | A formal methodology is defined for thorough technical testing that attempts to exploit vulnerabilities and security weaknesses via simulated attack methods by a competent manual attacker.                                                                       |
| 11.4.1 | N/A      | A penetration testing methodology is defined, documented, and implemented by the entity, and includes: <ul style="list-style-type: none"> <li>Industry-accepted penetration testing approaches.</li> <li>Coverage for the entire CDE perimeter and critical systems.</li> <li>Testing from both inside and outside the network.</li> <li>Testing to validate any segmentation and scope-reduction controls.</li> <li>Application-layer penetration testing to identify, at a minimum, the vulnerabilities listed in Requirement 6.2.4.</li> <li>Network-layer penetration tests that encompass all components that support network functions as well as operating systems.</li> <li>Review and consideration of threats and vulnerabilities experienced in the last 12 months.</li> <li>Documented approach to assessing and addressing the risk posed by exploitable vulnerabilities and security weaknesses found during penetration testing.</li> <li>Retention of penetration testing results and remediation activities results for at least 12 months.</li> </ul> | Functional     | Intersects With   | Independent Penetration Agent or Team                 | VPM-07.1 | Mechanisms exist to utilize an independent assessor or penetration team to perform penetration testing.                                                                                                                                                  | 5                        | A formal methodology is defined for thorough technical testing that attempts to exploit vulnerabilities and security weaknesses via simulated attack methods by a competent manual attacker.                                                                       |
| 11.4.2 | N/A      | Internal penetration testing is performed: <ul style="list-style-type: none"> <li>Per the entity's defined methodology.</li> <li>At least once every 12 months</li> <li>After any significant infrastructure or application upgrade or change</li> <li>By a qualified internal resource or qualified external third-party</li> <li>Organizational independence of the tester exists (not required to be a QSA or ASV).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Penetration Testing                                   | VPM-07   | Mechanisms exist to conduct penetration testing on Technology Assets, Applications and/or Services (TAAS).                                                                                                                                               | 5                        | Internal system defenses are verified by technical testing according to the entity's defined methodology as frequently as needed to address evolving and new attacks and threats and ensure that significant changes do not introduce unknown vulnerabilities.     |
| 11.4.2 | N/A      | Internal penetration testing is performed: <ul style="list-style-type: none"> <li>Per the entity's defined methodology.</li> <li>At least once every 12 months</li> <li>After any significant infrastructure or application upgrade or change</li> <li>By a qualified internal resource or qualified external third-party</li> <li>Organizational independence of the tester exists (not required to be a QSA or ASV).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Independent Penetration Agent or Team                 | VPM-07.1 | Mechanisms exist to utilize an independent assessor or penetration team to perform penetration testing.                                                                                                                                                  | 5                        | Internal system defenses are verified by technical testing according to the entity's defined methodology as frequently as needed to address evolving and new attacks and threats and ensure that significant changes do not introduce unknown vulnerabilities.     |
| 11.4.3 | N/A      | External penetration testing is performed: <ul style="list-style-type: none"> <li>Per the entity's defined methodology</li> <li>At least once every 12 months</li> <li>After any significant infrastructure or application upgrade or change</li> <li>By a qualified internal resource or qualified external third party</li> <li>Organizational independence of the tester exists (not required to be a QSA or ASV).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Independent Penetration Agent or Team                 | VPM-07.1 | Mechanisms exist to utilize an independent assessor or penetration team to perform penetration testing.                                                                                                                                                  | 5                        | External system defenses are verified by technical testing according to the entity's defined methodology as frequently as needed to address evolving and new attacks and threats, and to ensure that significant changes do not introduce unknown vulnerabilities. |
| 11.4.3 | N/A      | (continued on next page)<br>External penetration testing is performed: <ul style="list-style-type: none"> <li>Per the entity's defined methodology</li> <li>At least once every 12 months</li> <li>After any significant infrastructure or application upgrade or change</li> <li>By a qualified internal resource or qualified external third party</li> <li>Organizational independence of the tester exists (not required to be a QSA or ASV).</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Penetration Testing                                   | VPM-07   | Mechanisms exist to conduct penetration testing on Technology Assets, Applications and/or Services (TAAS).                                                                                                                                               | 5                        | External system defenses are verified by technical testing according to the entity's defined methodology as frequently as needed to address evolving and new attacks and threats, and to ensure that significant changes do not introduce unknown vulnerabilities. |
| 11.4.4 | N/A      | Exploitable vulnerabilities and security weaknesses found during penetration testing are corrected as follows: <ul style="list-style-type: none"> <li>In accordance with the entity's assessment of the risk posed by the security issue as defined in Requirement 6.3.1.</li> <li>Penetration testing is repeated to verify the corrections.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Threat Analysis & Flaw Remediation During Development | IAO-04   | Mechanisms exist to require system developers and integrators to create and execute a Security Testing and Evaluation (ST&E) plan, or similar process, to identify and remediate flaws during development.                                               | 5                        | Vulnerabilities and security weaknesses found while verifying system defenses are mitigated.                                                                                                                                                                       |
| 11.4.4 | N/A      | Exploitable vulnerabilities and security weaknesses found during penetration testing are corrected as follows: <ul style="list-style-type: none"> <li>In accordance with the entity's assessment of the risk posed by the security issue as defined in Requirement 6.3.1.</li> <li>Penetration testing is repeated to verify the corrections.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Developer Threat Analysis & Flaw Remediation          | TDA-15   | Mechanisms exist to require system developers and integrators to develop and implement an ongoing Security Testing and Evaluation (ST&E) plan, or similar process, to objectively identify and remediate vulnerabilities prior to release to production. | 5                        | Vulnerabilities and security weaknesses found while verifying system defenses are mitigated.                                                                                                                                                                       |
| 11.4.4 | N/A      | Exploitable vulnerabilities and security weaknesses found during penetration testing are corrected as follows: <ul style="list-style-type: none"> <li>In accordance with the entity's assessment of the risk posed by the security issue as defined in Requirement 6.3.1.</li> <li>Penetration testing is repeated to verify the corrections.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Penetration Testing                                   | VPM-07   | Mechanisms exist to conduct penetration testing on Technology Assets, Applications and/or Services (TAAS).                                                                                                                                               | 5                        | Vulnerabilities and security weaknesses found while verifying system defenses are mitigated.                                                                                                                                                                       |
| 11.4.5 | N/A      | If segmentation is used to isolate the CDE from other networks, penetration tests are performed on segmentation controls as follows: <ul style="list-style-type: none"> <li>At least once every 12 months and after any changes to segmentation controls/methods</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Restrict Access To Security Functions                 | END-16   | Mechanisms exist to ensure security functions are restricted to authorized individuals and enforce least privilege control requirements for necessary job functions.                                                                                     | 5                        | If segmentation is used, it is verified periodically by technical testing to be continually effective, including after any changes, in isolating the CDE from all out-of-scope systems.                                                                            |
| 11.4.5 | N/A      | If segmentation is used to isolate the CDE from other networks, penetration tests are performed on segmentation controls as follows: <ul style="list-style-type: none"> <li>At least once every 12 months and after any changes to segmentation controls/methods</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Network Segmentation (macrosegmentation)              | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                                                                          | 5                        | If segmentation is used, it is verified periodically by technical testing to be continually effective, including after any changes, in isolating the CDE from all out-of-scope systems.                                                                            |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | STRM Rationale | STRM Relationship | SCF Control                                          | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                 | Strength of Relationship | Notes                                                                                                                                                                                                                                                                                                                            |
|--------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11.4.5 | N/A      | <p>If segmentation is used to isolate the CDE from other networks, penetration tests are performed on segmentation controls as follows:</p> <ul style="list-style-type: none"> <li>At least once every 12 months and after any changes to segmentation controls/methods</li> <li>Covering all segmentation controls/methods in use.</li> <li>According to the entity's defined penetration testing methodology.</li> </ul> <p>Confirming that the segmentation controls/methods are operational and effective, and isolate the CDE from all out-of-scope systems.</p> <p>Confirming effectiveness of any use of isolation to separate systems with differing security levels (see Requirement 2.2.3).</p> <p>Performed by a qualified internal resource or qualified external third party.</p> <p>Organizational independence of the tester exists (not required to be a QSA or ASV).</p> | Functional     | Intersects With   | DMZ Networks                                         | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                        | 5                        | If segmentation is used, it is verified periodically by technical testing to be continually effective, including after any changes, in isolating the CDE from all out- of-scope systems.                                                                                                                                         |
| 11.4.5 | N/A      | <p>If segmentation is used to isolate the CDE from other networks, penetration tests are performed on segmentation controls as follows:</p> <ul style="list-style-type: none"> <li>At least once every 12 months and after any changes to segmentation controls/methods</li> <li>Covering all segmentation controls/methods in use.</li> <li>According to the entity's defined penetration testing methodology.</li> </ul> <p>Confirming that the segmentation controls/methods are operational and effective, and isolate the CDE from all out-of-scope systems.</p> <p>Confirming effectiveness of any use of isolation to separate systems with differing security levels (see Requirement 2.2.3).</p> <p>Performed by a qualified internal resource or qualified external third party.</p> <p>Organizational independence of the tester exists (not required to be a QSA or ASV).</p> | Functional     | Intersects With   | Security Function Isolation                          | SEA-04.1 | Mechanisms exist to isolate security functions from non-security functions.                                                                                         | 5                        | If segmentation is used, it is verified periodically by technical testing to be continually effective, including after any changes, in isolating the CDE from all out- of-scope systems.                                                                                                                                         |
| 11.4.5 | N/A      | <p>If segmentation is used to isolate the CDE from other networks, penetration tests are performed on segmentation controls as follows:</p> <ul style="list-style-type: none"> <li>At least once every 12 months and after any changes to segmentation controls/methods</li> <li>Covering all segmentation controls/methods in use.</li> <li>According to the entity's defined penetration testing methodology.</li> </ul> <p>Confirming that the segmentation controls/methods are operational and effective, and isolate the CDE from all out-of-scope systems.</p> <p>Confirming effectiveness of any use of isolation to separate systems with differing security levels (see Requirement 2.2.3).</p> <p>Performed by a qualified internal resource or qualified external third party.</p> <p>Organizational independence of the tester exists (not required to be a QSA or ASV).</p> | Functional     | Intersects With   | Secure Development Environments                      | TDA-07   | Mechanisms exist to maintain a segmented development network to ensure a secure development environment.                                                            | 5                        |                                                                                                                                                                                                                                                                                                                                  |
| 11.4.5 | N/A      | <p>If segmentation is used to isolate the CDE from other networks, penetration tests are performed on segmentation controls as follows:</p> <ul style="list-style-type: none"> <li>At least once every 12 months and after any changes to segmentation controls/methods</li> <li>Covering all segmentation controls/methods in use.</li> <li>According to the entity's defined penetration testing methodology.</li> </ul> <p>Confirming that the segmentation controls/methods are operational and effective, and isolate the CDE from all out-of-scope systems.</p> <p>Confirming effectiveness of any use of isolation to separate systems with differing security levels (see Requirement 2.2.3).</p> <p>Performed by a qualified internal resource or qualified external third party.</p> <p>Organizational independence of the tester exists (not required to be a QSA or ASV).</p> | Functional     | Intersects With   | Penetration Testing                                  | VPM-07   | Mechanisms exist to conduct penetration testing on Technology Assets, Applications and/or Services (TAAS).                                                          | 5                        | If segmentation is used, it is verified periodically by technical testing to be continually effective, including after any changes, in isolating the CDE from all out- of-scope systems.                                                                                                                                         |
| 11.4.5 | N/A      | <p>If segmentation is used to isolate the CDE from other networks, penetration tests are performed on segmentation controls as follows:</p> <ul style="list-style-type: none"> <li>At least once every 12 months and after any changes to segmentation controls/methods</li> <li>Covering all segmentation controls/methods in use.</li> <li>According to the entity's defined penetration testing methodology.</li> </ul> <p>Confirming that the segmentation controls/methods are operational and effective, and isolate the CDE from all out-of-scope systems.</p> <p>Confirming effectiveness of any use of isolation to separate systems with differing security levels (see Requirement 2.2.3).</p> <p>Performed by a qualified internal resource or qualified external third party.</p> <p>Organizational independence of the tester exists (not required to be a QSA or ASV).</p> | Functional     | Intersects With   | Independent Penetration Agent or Team                | VPM-07.1 | Mechanisms exist to utilize an independent assessor or penetration team to perform penetration testing.                                                             | 5                        | If segmentation is used, it is verified periodically by technical testing to be continually effective, including after any changes, in isolating the CDE from all out- of-scope systems.                                                                                                                                         |
| 11.5.1 | N/A      | <p>Intrusion-detection and/or intrusion- prevention techniques are used to detect and/or prevent intrusions into the network as follows:</p> <ul style="list-style-type: none"> <li>All traffic is monitored at the perimeter of the CDE.</li> <li>All traffic is monitored at critical points in the CDE.</li> <li>Personnel are alerted to suspected compromises.</li> <li>All intrusion-detection and prevention engines, baselines, and signatures are kept up to date.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Intrusion Detection & Prevention Systems (IDS & IPS) | MON-01.1 | Mechanisms exist to implement Intrusion Detection / Prevention Systems (IDS / IPS) technologies on critical systems, key network segments and network choke points. | 5                        | Mechanisms to detect real-time suspicious or anomalous network traffic that may be indicative of threat actor activity are implemented. Alerts generated by these mechanisms are responded to by personnel, or by automated means that ensure that system components cannot be compromised as a result of the detected activity. |
| 11.5.1 | N/A      | <p>Intrusion-detection and/or intrusion- prevention techniques are used to detect and/or prevent intrusions into the network as follows:</p> <ul style="list-style-type: none"> <li>All traffic is monitored at the perimeter of the CDE.</li> <li>All traffic is monitored at critical points in the CDE.</li> <li>Personnel are alerted to suspected compromises.</li> <li>All intrusion-detection and prevention engines, baselines, and signatures are kept up to date.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Boundary Protection                                  | NET-03   | Mechanisms exist to monitor and control communications at the external network boundary and at key internal boundaries within the network.                          | 5                        | Mechanisms to detect real-time suspicious or anomalous network traffic that may be indicative of threat actor activity are implemented. Alerts generated by these mechanisms are responded to by personnel, or by automated means that ensure that system components cannot be compromised as a result of the detected activity. |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | STRM Rationale | STRM Relationship | SCF Control                                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                      | Strength of Relationship | Notes                                                                                                                                                                                                                                                                                                                            |
|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-----------------------------------------------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 11.5.1 | N/A      | Intrusion-detection and/or intrusion- prevention techniques are used to detect and/or prevent intrusions into the network as follows:<br><ul style="list-style-type: none"> <li>All traffic is monitored at the perimeter of the CDE.</li> <li>All traffic is monitored at critical points in the CDE.</li> <li>Personnel are alerted to suspected compromises.</li> <li>All intrusion-detection and prevention engines, baselines, and signatures are kept up to date.</li> </ul>                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Network Intrusion Detection / Prevention Systems (NIDS / NIPS)        | NET-08   | Mechanisms exist to employ Network Intrusion Detection / Prevention Systems (NIDS/NIPS) to detect and/or prevent intrusions into the network.                                                                                                            | 5                        | Mechanisms to detect real-time suspicious or anomalous network traffic that may be indicative of threat actor activity are implemented. Alerts generated by these mechanisms are responded to by personnel, or by automated means that ensure that system components cannot be compromised as a result of the detected activity. |
| 11.5.1 | N/A      | Intrusion-detection and/or intrusion- prevention techniques are used to detect and/or prevent intrusions into the network as follows:<br><ul style="list-style-type: none"> <li>All traffic is monitored at the perimeter of the CDE.</li> <li>All traffic is monitored at critical points in the CDE.</li> <li>Personnel are alerted to suspected compromises.</li> <li>All intrusion-detection and prevention engines, baselines, and signatures are kept up to date.</li> </ul>                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Suspicious Communications & Anomalous System Behavior                 | SAT-03.2 | Mechanisms exist to provide training to personnel on organization-defined indicators of malware to recognize suspicious communications and anomalous behavior.                                                                                           | 5                        | Mechanisms to detect real-time suspicious or anomalous network traffic that may be indicative of threat actor activity are implemented. Alerts generated by these mechanisms are responded to by personnel, or by automated means that ensure that system components cannot be compromised as a result of the detected activity. |
| 11.5.2 | N/A      | A change-detection mechanism (for example, file integrity monitoring tools) is deployed as follows:<br><ul style="list-style-type: none"> <li>To alert personnel to unauthorized modification (including changes, additions, and deletions) of critical files.</li> <li>To perform critical file comparisons at least once weekly.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Endpoint File Integrity Monitoring (FIM)                              | END-06   | Mechanisms exist to utilize File Integrity Monitor (FIM), or similar technologies, to detect and report on unauthorized changes to selected files and configuration settings.                                                                            | 5                        | Critical files cannot be modified by unauthorized personnel without an alert being generated.                                                                                                                                                                                                                                    |
| 11.5.2 | N/A      | A change-detection mechanism (for example, file integrity monitoring tools) is deployed as follows:<br><ul style="list-style-type: none"> <li>To alert personnel to unauthorized modification (including changes, additions, and deletions) of critical files.</li> <li>To perform critical file comparisons at least once weekly.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | File Integrity Monitoring (FIM)                                       | MON-01.7 | Mechanisms exist to utilize a File Integrity Monitor (FIM), or similar change-detection technology, on critical Technology Assets, Applications and/or Services (TAAS) to generate alerts for unauthorized modifications.                                | 5                        | Critical files cannot be modified by unauthorized personnel without an alert being generated.                                                                                                                                                                                                                                    |
| 11.6.1 | N/A      | A change- and tamper-detection mechanism is deployed as follows:<br><ul style="list-style-type: none"> <li>To alert personnel to unauthorized modification (including indicators of compromise, changes, additions, and deletions) to the HTTP headers and the contents of payment pages as received by the consumer browser.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Periodic Review                                                       | CFG-03.1 | Mechanisms exist to periodically review system configurations to identify and disable unnecessary and/or non-secure functions, ports, protocols and services.                                                                                            | 5                        | E-commerce skimming code or techniques cannot be added to payment pages as received by the consumer browser without a timely alert being generated. Anti-skimming measures cannot be removed from payment pages without a prompt alert being generated.                                                                          |
| 11.6.1 | N/A      | A change- and tamper-detection mechanism is deployed as follows:<br><ul style="list-style-type: none"> <li>To alert personnel to unauthorized modification (including indicators of compromise, changes, additions, and deletions) to the HTTP headers and the contents of payment pages as received by the consumer browser.</li> <li>The mechanism is configured to evaluate the received HTTP header and payment page.</li> <li>The mechanism functions are performed as follows:<br/> <ul style="list-style-type: none"> <li>At least once every seven days</li> </ul> </li> <li>OR</li> <li>Periodically (at the frequency defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1).</li> </ul> | Functional     | Intersects With   | Endpoint File Integrity Monitoring (FIM)                              | END-06   | Mechanisms exist to utilize File Integrity Monitor (FIM), or similar technologies, to detect and report on unauthorized changes to selected files and configuration settings.                                                                            | 5                        | E-commerce skimming code or techniques cannot be added to payment pages as received by the consumer browser without a timely alert being generated. Anti-skimming measures cannot be removed from payment pages without a prompt alert being generated.                                                                          |
| 11.6.1 | N/A      | A change- and tamper-detection mechanism is deployed as follows:<br><ul style="list-style-type: none"> <li>To alert personnel to unauthorized modification (including indicators of compromise, changes, additions, and deletions) to the HTTP headers and the contents of payment pages as received by the consumer browser.</li> <li>The mechanism is configured to evaluate the received HTTP header and payment page.</li> <li>The mechanism functions are performed as follows:<br/> <ul style="list-style-type: none"> <li>At least once every seven days</li> </ul> </li> <li>OR</li> <li>Periodically (at the frequency defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1).</li> </ul> | Functional     | Intersects With   | File Integrity Monitoring (FIM)                                       | MON-01.7 | Mechanisms exist to utilize a File Integrity Monitor (FIM), or similar change-detection technology, on critical Technology Assets, Applications and/or Services (TAAS) to generate alerts for unauthorized modifications.                                | 5                        | E-commerce skimming code or techniques cannot be added to payment pages as received by the consumer browser without a timely alert being generated. Anti-skimming measures cannot be removed from payment pages without a prompt alert being generated.                                                                          |
| 11.6.1 | N/A      | A change- and tamper-detection mechanism is deployed as follows:<br><ul style="list-style-type: none"> <li>To alert personnel to unauthorized modification (including indicators of compromise, changes, additions, and deletions) to the HTTP headers and the contents of payment pages as received by the consumer browser.</li> <li>The mechanism is configured to evaluate the received HTTP header and payment page.</li> <li>The mechanism functions are performed as follows:<br/> <ul style="list-style-type: none"> <li>At least once every seven days</li> </ul> </li> <li>OR</li> <li>Periodically (at the frequency defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1).</li> </ul> | Functional     | Intersects With   | Website Change Detection                                              | WEB-13   | Mechanisms exist to detect and respond to Indicators of Compromise (IoC) for unauthorized alterations, additions, deletions or changes on websites that store, process and/or transmit sensitive and/or regulated data.                                  | 5                        | E-commerce skimming code or techniques cannot be added to payment pages as received by the consumer browser without a timely alert being generated. Anti-skimming measures cannot be removed from payment pages without a prompt alert being generated.                                                                          |
| 12.1.1 | N/A      | An overall information security policy is:<br><ul style="list-style-type: none"> <li>Established.</li> <li>Published.</li> <li>Maintained.</li> <li>Disseminated to all relevant personnel, as well as to relevant vendors and business partners.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                   | 5                        | The strategic objectives and principles of information security are defined, adopted, and known to all personnel.                                                                                                                                                                                                                |
| 12.1.1 | N/A      | An overall information security policy is:<br><ul style="list-style-type: none"> <li>Established.</li> <li>Published.</li> <li>Maintained.</li> <li>Disseminated to all relevant personnel, as well as to relevant vendors and business partners.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPs), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness. | 5                        | The strategic objectives and principles of information security are defined, adopted, and known to all personnel.                                                                                                                                                                                                                |
| 12.1.2 | N/A      | The information security policy is:<br><ul style="list-style-type: none"> <li>Reviewed at least once every 12 months.</li> <li>Updated as needed to reflect changes to business objectives or risks to the environment.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                   | 5                        | The information security policy continues to reflect the organization's strategic objectives and principles.                                                                                                                                                                                                                     |
| 12.1.2 | N/A      | The information security policy is:<br><ul style="list-style-type: none"> <li>Reviewed at least once every 12 months.</li> <li>Updated as needed to reflect changes to business objectives or risks to the environment.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Periodic Review & Update of Security, Compliance & Resilience Program | GOV-03   | Mechanisms exist to review the Security, Compliance & Resilience Program (SCRPs), including policies, standards and procedures, at planned intervals or if significant changes occur to ensure their continuing suitability, adequacy and effectiveness. | 5                        | The information security policy continues to reflect the organization's strategic objectives and principles.                                                                                                                                                                                                                     |
| 12.1.3 | N/A      | The security policy clearly defines information security roles and responsibilities for all personnel, and all personnel are aware of and acknowledge their information security responsibilities.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Publishing Security, Compliance & Resilience Documentation            | GOV-02   | Mechanisms exist to establish, maintain and disseminate policies, standards and procedures necessary for secure, compliant and resilient capabilities.                                                                                                   | 5                        | Personnel understand their role in protecting the entity's cardholder data.                                                                                                                                                                                                                                                      |
| 12.1.3 | N/A      | The security policy clearly defines information security roles and responsibilities for all personnel, and all personnel are aware of and acknowledge their information security responsibilities.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities           | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPs).                       | 5                        | Personnel understand their role in protecting the entity's cardholder data.                                                                                                                                                                                                                                                      |
| 12.1.3 | N/A      | The security policy clearly defines information security roles and responsibilities for all personnel, and all personnel are aware of and acknowledge their information security responsibilities.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Defined Roles & Responsibilities                                      | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                     | 5                        | Personnel understand their role in protecting the entity's cardholder data.                                                                                                                                                                                                                                                      |
| 12.1.3 | N/A      | The security policy clearly defines information security roles and responsibilities for all personnel, and all personnel are aware of and acknowledge their information security responsibilities.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | User Awareness                                                        | HRS-03.1 | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                     | 5                        | Personnel understand their role in protecting the entity's cardholder data.                                                                                                                                                                                                                                                      |



| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | STRM Rationale | STRM Relationship | SCF Control                                                 | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                   | Strength of Relationship | Notes                                                                                |
|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------|
| 12.1.3 | N/A      | The security policy clearly defines information security roles and responsibilities for all personnel, and all personnel are aware of and acknowledge their information security responsibilities.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Terms of Employment                                         | HRS-05   | Mechanisms exist to require all employees and contractors to apply cybersecurity and data protection principles in their daily work to enable secure, compliant and resilient capabilities.                                                                                           | 5                        | Personnel understand their role in protecting the entity's cardholder data.          |
| 12.1.3 | N/A      | The security policy clearly defines information security roles and responsibilities for all personnel, and all personnel are aware of and acknowledge their information security responsibilities.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Rules of Behavior                                           | HRS-05.1 | Mechanisms exist to define acceptable and unacceptable rules of behavior for the use of technologies, including consequences for unacceptable behavior.                                                                                                                               | 5                        | Personnel understand their role in protecting the entity's cardholder data.          |
| 12.1.4 | N/A      | Responsibility for information security is formally assigned to a Chief Information Security Officer or other information security knowledgeable member of executive management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Assigned Security, Compliance & Resilience Responsibilities | GOV-04   | Mechanisms exist to assign one or more qualified individuals with the mission and resources to centrally-manage, coordinate, develop, implement and maintain an enterprise-wide Security, Compliance & Resilience Program (SCRPI).                                                    | 5                        | A designated member of executive management is responsible for information security. |
| 12.1.4 | N/A      | Responsibility for information security is formally assigned to a Chief Information Security Officer or other information security knowledgeable member of executive management.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Incident Stakeholder Reporting                              | IRO-10   | Mechanisms exist to timely-report incidents to applicable:<br>(1) Internal stakeholders;<br>(2) Affected clients & third-parties; and<br>(3) Regulatory authorities.                                                                                                                  | 5                        | A designated member of executive management is responsible for information security. |
| 12.2.1 | N/A      | Acceptable use policies for end-user technologies are documented and implemented, including:<br>• Explicit approval by authorized parties.<br>• Acceptable uses of the technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Subset Of         | Human Resources Security Management                         | HRS-01   | Mechanisms exist to facilitate the implementation of personnel security controls.                                                                                                                                                                                                     | 10                       | The use of end-user technologies is defined and managed to ensure authorized usage.  |
| 12.2.1 | N/A      | Acceptable use policies for end-user technologies are documented and implemented, including:<br>• Explicit approval by authorized parties.<br>• Acceptable uses of the technology.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Terms of Employment                                         | HRS-05   | Mechanisms exist to require all employees and contractors to apply cybersecurity and data protection principles in their daily work to enable secure, compliant and resilient capabilities.                                                                                           | 5                        | The use of end-user technologies is defined and managed to ensure authorized usage.  |
| 12.2.1 | N/A      | Acceptable use policies for end-user technologies are documented and implemented, including:<br>• Explicit approval by authorized parties.<br>• Acceptable uses of the technology.<br>• List of products approved by the company for employee use, including hardware and software.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Rules of Behavior                                           | HRS-05.1 | Mechanisms exist to define acceptable and unacceptable rules of behavior for the use of technologies, including consequences for unacceptable behavior.                                                                                                                               | 5                        | The use of end-user technologies is defined and managed to ensure authorized usage.  |
| 12.2.1 | N/A      | Acceptable use policies for end-user technologies are documented and implemented, including:<br>• Explicit approval by authorized parties.<br>• Acceptable uses of the technology.<br>• List of products approved by the company for employee use, including hardware and software.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Functional     | Intersects With   | Technology Use Restrictions                                 | HRS-05.3 | Mechanisms exist to establish usage restrictions and implementation guidance for organizational technologies based on the potential to cause damage to Technology Assets, Applications and/or Services (TAAS), if used maliciously.                                                   | 5                        | The use of end-user technologies is defined and managed to ensure authorized usage.  |
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Periodic Review                                             | CFG-03.1 | Mechanisms exist to periodically review system configurations to identify and disable unnecessary and/or non-secure functions, ports, protocols and services.                                                                                                                         | 5                        |                                                                                      |
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Risk Framing                                                | RSK-01.1 | Mechanisms exist to identify:<br>(1) Assumptions affecting risk assessments, risk response and risk monitoring;<br>(2) Constraints affecting risk assessments, risk response and risk monitoring;<br>(3) The organizational risk tolerance; and                                       | 5                        | Up to date knowledge and assessment of risks to the CDE are maintained.              |
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.<br>• Identification of factors that contribute to the likelihood and/or impact of a threat being realized.<br>• Resulting analysis that determines, and includes justification for, how frequently the requirement must be performed to minimize the likelihood of the threat being realized.<br>• Review of each targeted risk analysis at least once every 12 months to determine whether the results are still valid or if an updated risk analysis is needed.<br>• Performance of updated risk analyses when needed, as determined by the annual review. | Functional     | Intersects With   | Risk Identification                                         | RSK-03   | Mechanisms exist to identify and document risks, both internal and external.                                                                                                                                                                                                          | 5                        | Up to date knowledge and assessment of risks to the CDE are maintained.              |
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.<br>• Identification of factors that contribute to the likelihood and/or impact of a threat being realized.<br>• Resulting analysis that determines, and includes justification for, how frequently the requirement must be performed to minimize the likelihood of the threat being realized.<br>• Review of each targeted risk analysis at least once every 12 months to determine whether the results are still valid or if an updated risk analysis is needed.<br>• Performance of updated risk analyses when needed, as determined by the annual review. | Functional     | Intersects With   | Risk Assessment                                             | RSK-04   | Mechanisms exist to conduct recurring assessments of risk that includes the likelihood and magnitude of harm, from unauthorized access, use, disclosure, disruption, modification or destruction of the organization's Technology Assets, Applications, Services and/or Data (TAASD). | 5                        | Up to date knowledge and assessment of risks to the CDE are maintained.              |
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.<br>• Identification of factors that contribute to the likelihood and/or impact of a threat being realized.<br>• Resulting analysis that determines, and includes justification for, how frequently the requirement must be performed to minimize the likelihood of the threat being realized.<br>• Review of each targeted risk analysis at least once every 12 months to determine whether the results are still valid or if an updated risk analysis is needed.<br>• Performance of updated risk analyses when needed, as determined by the annual review. | Functional     | Intersects With   | Risk Register                                               | RSK-04.1 | Mechanisms exist to maintain a risk register that facilitates monitoring and reporting of risks.                                                                                                                                                                                      | 5                        | Up to date knowledge and assessment of risks to the CDE are maintained.              |
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.<br>• Identification of factors that contribute to the likelihood and/or impact of a threat being realized.<br>• Resulting analysis that determines, and includes justification for, how frequently the requirement must be performed to minimize the likelihood of the threat being realized.<br>• Review of each targeted risk analysis at least once every 12 months to determine whether the results are still valid or if an updated risk analysis is needed.<br>• Performance of updated risk analyses when needed, as determined by the annual review. | Functional     | Intersects With   | Risk Ranking                                                | RSK-05   | Mechanisms exist to identify and assign a risk ranking to newly discovered security vulnerabilities that is based on industry-recognized practices.                                                                                                                                   | 5                        | Up to date knowledge and assessment of risks to the CDE are maintained.              |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | STRM Rationale | STRM Relationship | SCF Control                  | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                                          | Strength of Relationship | Notes                                                                                                        |
|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|------------------------------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------|
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.<br>• Identification of factors that contribute to the likelihood and/or impact of a threat being realized.<br>• Resulting analysis that determines, and includes justification for, how frequently the requirement must be performed to minimize the likelihood of the threat being realized.<br>• Review of each targeted risk analysis at least once every 12 months to determine whether the results are still valid or if an updated risk analysis is needed.<br>• Performance of updated risk analyses when needed, as determined by the annual review. | Functional     | Intersects With   | Risk Remediation             | RSK-06   | Mechanisms exist to remediate risks to an acceptable level.                                                                                                                                                                                                                                                                                  | 5                        | Up to date knowledge and assessment of risks to the CDE are maintained.                                      |
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.<br>• Identification of factors that contribute to the likelihood and/or impact of a threat being realized.<br>• Resulting analysis that determines, and includes justification for, how frequently the requirement must be performed to minimize the likelihood of the threat being realized.<br>• Review of each targeted risk analysis at least once every 12 months to determine whether the results are still valid or if an updated risk analysis is needed.<br>• Performance of updated risk analyses when needed, as determined by the annual review. | Functional     | Intersects With   | Compensating Countermeasures | RSK-06.2 | Mechanisms exist to identify and implement compensating countermeasures to reduce risk and exposure to threats.                                                                                                                                                                                                                              | 5                        | Up to date knowledge and assessment of risks to the CDE are maintained.                                      |
| 12.3.1 | N/A      | Each PCI DSS requirement that provides flexibility for how frequently it is performed (for example, requirements to be performed periodically) is supported by a targeted risk analysis that is documented and includes:<br>• Identification of the assets being protected.<br>• Identification of the threat(s) that the requirement is protecting against.<br>• Identification of factors that contribute to the likelihood and/or impact of a threat being realized.<br>• Resulting analysis that determines, and includes justification for, how frequently the requirement must be performed to minimize the likelihood of the threat being realized.<br>• Review of each targeted risk analysis at least once every 12 months to determine whether the results are still valid or if an updated risk analysis is needed.<br>• Performance of updated risk analyses when needed, as determined by the annual review. | Functional     | Intersects With   | Risk Assessment Update       | RSK-07   | Mechanisms exist to routinely update risk assessments and react accordingly upon identifying new security vulnerabilities, including using outside sources for security vulnerability information.                                                                                                                                           | 5                        | Up to date knowledge and assessment of risks to the CDE are maintained.                                      |
| 12.3.2 | N/A      | A targeted risk analysis is performed for each PCI DSS requirement that the entity meets with the customized approach, to include:<br>• Documented evidence detailing each element specified in Appendix D: Customized Approach (including, at a minimum, a controls matrix and risk analysis).<br>• Approval of documented evidence by senior management.<br>• Performance of the targeted analysis of risk at least once every 12 months.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Risk Framing                 | RSK-01.1 | Mechanisms exist to identify:<br>(1) Assumptions affecting risk assessments, risk response and risk monitoring;<br>(2) Constraints affecting risk assessments, risk response and risk monitoring;<br>(3) The organizational risk tolerance; and<br>(4) Priorities, benefits and trade-offs considered by the organization for managing risk. | 5                        | This requirement is part of the customized approach and must be met for those using the customized approach. |
| 12.3.2 | N/A      | A targeted risk analysis is performed for each PCI DSS requirement that the entity meets with the customized approach, to include:<br>• Documented evidence detailing each element specified in Appendix D: Customized Approach (including, at a minimum, a controls matrix and risk analysis).<br>• Approval of documented evidence by senior management.<br>• Performance of the targeted analysis of risk at least once every 12 months.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Risk Identification          | RSK-03   | Mechanisms exist to identify and document risks, both internal and external.                                                                                                                                                                                                                                                                 | 5                        | This requirement is part of the customized approach and must be met for those using the customized approach. |
| 12.3.2 | N/A      | A targeted risk analysis is performed for each PCI DSS requirement that the entity meets with the customized approach, to include:<br>• Documented evidence detailing each element specified in Appendix D: Customized Approach (including, at a minimum, a controls matrix and risk analysis).<br>• Approval of documented evidence by senior management.<br>• Performance of the targeted analysis of risk at least once every 12 months.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Risk Assessment              | RSK-04   | Mechanisms exist to conduct recurring assessments of risk that includes the likelihood and magnitude of harm, from unauthorized access, use, disclosure, disruption, modification or destruction of the organization's Technology Assets, Applications, Services and/or Data (TAASD).                                                        | 5                        | This requirement is part of the customized approach and must be met for those using the customized approach. |
| 12.3.2 | N/A      | A targeted risk analysis is performed for each PCI DSS requirement that the entity meets with the customized approach, to include:<br>• Documented evidence detailing each element specified in Appendix D: Customized Approach (including, at a minimum, a controls matrix and risk analysis).<br>• Approval of documented evidence by senior management.<br>• Performance of the targeted analysis of risk at least once every 12 months.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Risk Register                | RSK-04.1 | Mechanisms exist to maintain a risk register that facilitates monitoring and reporting of risks.                                                                                                                                                                                                                                             | 5                        | This requirement is part of the customized approach and must be met for those using the customized approach. |
| 12.3.2 | N/A      | A targeted risk analysis is performed for each PCI DSS requirement that the entity meets with the customized approach, to include:<br>• Documented evidence detailing each element specified in Appendix D: Customized Approach (including, at a minimum, a controls matrix and risk analysis).<br>• Approval of documented evidence by senior management.<br>• Performance of the targeted analysis of risk at least once every 12 months.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Compensating Countermeasures | RSK-06.2 | Mechanisms exist to identify and implement compensating countermeasures to reduce risk and exposure to threats.                                                                                                                                                                                                                              | 5                        | This requirement is part of the customized approach and must be met for those using the customized approach. |
| 12.3.2 | N/A      | A targeted risk analysis is performed for each PCI DSS requirement that the entity meets with the customized approach, to include:<br>• Documented evidence detailing each element specified in Appendix D: Customized Approach (including, at a minimum, a controls matrix and risk analysis).<br>• Approval of documented evidence by senior management.<br>• Performance of the targeted analysis of risk at least once every 12 months.                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Functional     | Intersects With   | Risk Assessment Update       | RSK-07   | Mechanisms exist to routinely update risk assessments and react accordingly upon identifying new security vulnerabilities, including using outside sources for security vulnerability information.                                                                                                                                           | 5                        | This requirement is part of the customized approach and must be met for those using the customized approach. |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | STRM Rationale | STRM Relationship | SCF Control                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                                                         | Strength of Relationship | Notes                                                                                                                                                                               |
|--------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 12.3.3 | N/A      | Cryptographic cipher suites and protocols in use are documented and reviewed at least once every 12 months, including at least the following:<br>• An up-to-date inventory of all cryptographic cipher suites and protocols in use, including purpose and where used.<br>• Active monitoring of industry trends regarding continued viability of all cryptographic cipher suites and protocols in use.<br>• A documented strategy to respond to anticipated changes in cryptographic vulnerabilities.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Subset Of         | Use of Cryptographic Controls                         | CRY-01   | Mechanisms exist to facilitate the implementation of cryptographic protections controls using known public standards and trusted cryptographic technologies.                                                                                                                                                                | 10                       | The entity is able to respond quickly to any vulnerabilities in cryptographic protocols or algorithms, where those vulnerabilities affect protection of cardholder data.            |
| 12.3.3 | N/A      | Cryptographic cipher suites and protocols in use are documented and reviewed at least once every 12 months, including at least the following:<br>• An up-to-date inventory of all cryptographic cipher suites and protocols in use, including purpose and where used.<br>• Active monitoring of industry trends regarding continued viability of all cryptographic cipher suites and protocols in use.<br>• A documented strategy to respond to anticipated changes in cryptographic vulnerabilities.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Cryptographic Cipher Suites and Protocols Inventory   | CRY-01.5 | Mechanisms exist to identify, document and review deployed cryptographic cipher suites and protocols to proactively respond to industry trends regarding the continued viability of utilized cryptographic cipher suites and protocols.                                                                                     | 5                        | The entity is able to respond quickly to any vulnerabilities in cryptographic protocols or algorithms, where those vulnerabilities affect protection of cardholder data.            |
| 12.3.4 | N/A      | Hardware and software technologies in use are reviewed at least once every 12 months, including at least the following:<br>• Analysis that the technologies continue to receive security fixes from vendors promptly.<br>• Analysis that the technologies continue to support (and do not preclude) the entity's PCI DSS compliance.<br>• Documentation of any industry announcements or trends related to a technology, such as when a vendor has announced "end of life" plans for a technology.<br>• Documentation of a plan, approved by senior management, to                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Periodic Review                                       | CFG-03.1 | Mechanisms exist to periodically review system configurations to identify and disable unnecessary and/or non-secure functions, ports, protocols and services.                                                                                                                                                               | 5                        | The entity's hardware and software technologies are up to date and supported by the vendor. Plans to remove or replace all unsupported system components are reviewed periodically. |
| 12.3.4 | N/A      | Hardware and software technologies in use are reviewed at least once every 12 months, including at least the following:<br>• Analysis that the technologies continue to receive security fixes from vendors promptly.<br>• Analysis that the technologies continue to support (and do not preclude) the entity's PCI DSS compliance.<br>• Documentation of any industry announcements or trends related to a technology, such as when a vendor has announced "end of life" plans for a technology.<br>• Documentation of a plan, approved by senior management, to                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Technical Debt Reviews                                | SEA-02.3 | Mechanisms exist to conduct ongoing "technical debt" reviews of hardware and software technologies to remediate outdated and/or unsupported technologies.                                                                                                                                                                   | 5                        | The entity's hardware and software technologies are up to date and supported by the vendor. Plans to remove or replace all unsupported system components are reviewed periodically. |
| 12.3.4 | N/A      | Hardware and software technologies in use are reviewed at least once every 12 months, including at least the following:<br>• Analysis that the technologies continue to receive security fixes from vendors promptly.<br>• Analysis that the technologies continue to support (and do not preclude) the entity's PCI DSS compliance.<br>• Documentation of any industry announcements or trends related to a technology, such as when a vendor has announced "end of life" plans for a technology.<br>• Documentation of a plan, approved by senior management, to                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Technology Lifecycle Management                       | SEA-07.1 | Mechanisms exist to manage the usable lifecycles of Technology Assets, Applications and/or Services (TAAS).                                                                                                                                                                                                                 | 5                        | The entity's hardware and software technologies are up to date and supported by the vendor. Plans to remove or replace all unsupported system components are reviewed periodically. |
| 12.5.1 | N/A      | An inventory of system components that are in scope for PCI DSS, including a description of function/use, is maintained and kept current.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Compliance-Specific Asset Identification              | AST-04.3 | Mechanisms exist to create and maintain a current inventory of Technology Assets, Applications, Services and/or Data (TAASD) that are in scope for statutory, regulatory and/or contractual compliance obligations that provides sufficient detail to determine control applicability, based on asset scope categorization. | 5                        | All system components in scope for PCI DSS are identified and known.                                                                                                                |
| 12.5.1 | N/A      | An inventory of system components that are in scope for PCI DSS, including a description of function/use, is maintained and kept current.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Compliance Scope                                      | CPL-01.2 | Mechanisms exist to document and validate the scope of security, compliance and resilience controls that are determined to meet statutory, regulatory and/or contractual compliance obligations.                                                                                                                            | 5                        | All system components in scope for PCI DSS are identified and known.                                                                                                                |
| 12.5.1 | N/A      | An inventory of system components that are in scope for PCI DSS, including a description of function/use, is maintained and kept current.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Inventory of Personal Data (PD)                       | PRI-05.5 | Mechanisms exist to establish and maintain a current inventory of all Technology Assets, Applications and/or Services (TAAS) that collect, receive, process, store, transmit, share, update and/or dispose Personal Data (PD).                                                                                              | 5                        | All system components in scope for PCI DSS are identified and known.                                                                                                                |
| 12.5.2 | N/A      | PCI DSS scope is documented and confirmed by the entity at least once every 12 months and upon significant change to the in-scope environment. At a minimum, the scoping validation includes:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Periodic Review                                       | CFG-03.1 | Mechanisms exist to periodically review system configurations to identify and disable unnecessary and/or non-secure functions, ports, protocols and services.                                                                                                                                                               | 5                        | PCI DSS scope is verified periodically, and after significant changes, by comprehensive analysis and appropriate technical measures.                                                |
| 12.5.2 | N/A      | PCI DSS scope is documented and confirmed by the entity at least once every 12 months and upon significant change to the in-scope environment. At a minimum, the scoping validation includes:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Compliance Scope                                      | CPL-01.2 | Mechanisms exist to document and validate the scope of security, compliance and resilience controls that are determined to meet statutory, regulatory and/or contractual compliance obligations.                                                                                                                            | 5                        | PCI DSS scope is verified periodically, and after significant changes, by comprehensive analysis and appropriate technical measures.                                                |
| 12.5.2 | N/A      | PCI DSS scope is documented and confirmed by the entity at least once every 12 months and upon significant change to the in-scope environment. At a minimum, the scoping validation includes:<br>• Identifying all data flows for the various payment stages (for example, authorization, capture settlement, chargebacks, and refunds) and acceptance channels (for example, card-present, card-not-present, and e-commerce).<br>• Updating all data-flow diagrams per Requirement 1.2.4.<br>• Identifying all locations where account data is stored, processed, and transmitted, including but not limited to: 1) any locations outside of the currently defined CDE, 2) applications that process CHO, 3) transmissions between systems and networks, and 4) file backups.<br>• Identifying all system components in the CDE, connected to the CDE, or that could impact security of the CDE.<br>• Identifying all segmentation controls in use and the environment(s) from which the CDE is segmented, including justification for environments being out of scope.<br>• Identifying all connections from third-party entities with access to the CDE.<br>• Confirming that all identified data flows, account data, system components, segmentation controls, and connections from third parties with access to the CDE are included in scope. | Functional     | Intersects With   | Third-Party Processing, Storage and Service Locations | TPM-04.4 | Mechanisms exist to restrict the location of information processing/storage based on business requirements.                                                                                                                                                                                                                 | 5                        | PCI DSS scope is verified periodically, and after significant changes, by comprehensive analysis and appropriate technical measures.                                                |

| FDE #  | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | STRM Rationale | STRM Relationship | SCF Control                                           | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                   | Strength of Relationship | Notes                                                                                                                                                                                          |
|--------|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|-------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 12.5.2 | N/A      | PCI DSS scope is documented and confirmed by the entity at least once every 12 months and upon significant change to the in-scope environment. At a minimum, the scoping validation includes: <ul style="list-style-type: none"> <li>Identifying all data flows for the various payment stages (for example, authorization, capture settlement, chargebacks, and refunds) and acceptance channels (for example, card-present, card-not-present, and e-commerce).</li> <li>Updating all data-flow diagrams per Requirement 1.2.4.</li> <li>Identifying all locations where account data is stored, processed, and transmitted, including but not limited to: 1) any locations outside of the currently defined CDE, 2) applications that process CHB, 3) transmissions between systems and networks, and 4) file backups.</li> <li>Identifying all system components in the CDE, connected to the CDE, or that could impact security of the CDE.</li> <li>Identifying all segmentation controls in use and the environment(s) from which the CDE is segmented, including justification for environments being out of scope.</li> <li>Identifying all connections from third-party entities with access to the CDE.</li> <li>Confirming that all identified data flows, account data, system components, segmentation controls, and connections from third parties with access to the CDE are included in scope.</li> </ul> | Functional     | Intersects With   | Network Segmentation (macrosegmentation)              | NET-06   | Mechanisms exist to implement network segmentation within network architectures to isolate Technology Assets, Applications and/or Services (TAAS) from other network resources.                       | 5                        | PCI DSS scope is verified periodically, and after significant changes, by comprehensive analysis and appropriate technical measures.                                                           |
| 12.5.2 | N/A      | PCI DSS scope is documented and confirmed by the entity at least once every 12 months and upon significant change to the in-scope environment. At a minimum, the scoping validation includes: <ul style="list-style-type: none"> <li>Identifying all data flows for the various payment stages (for example, authorization, capture settlement, chargebacks, and refunds) and acceptance channels (for example, card-present, card-not-present, and e-commerce).</li> <li>Updating all data-flow diagrams per Requirement 1.2.4.</li> <li>Identifying all locations where account data is stored, processed, and transmitted, including but not limited to: 1) any locations outside of the currently defined CDE, 2) applications that process CHB, 3) transmissions between systems and networks, and 4) file backups.</li> <li>Identifying all system components in the CDE, connected to the CDE, or that could impact security of the CDE.</li> <li>Identifying all segmentation controls in use and the environment(s) from which the CDE is segmented, including justification for environments being out of scope.</li> <li>Identifying all connections from third-party entities with access to the CDE.</li> <li>Confirming that all identified data flows, account data, system components, segmentation controls, and connections from third parties with access to the CDE are included in scope.</li> </ul> | Functional     | Intersects With   | DMZ Networks                                          | NET-08.1 | Mechanisms exist to monitor De-Militarized Zone (DMZ) network segments to separate untrusted networks from trusted networks.                                                                          | 5                        | PCI DSS scope is verified periodically, and after significant changes, by comprehensive analysis and appropriate technical measures.                                                           |
| 12.6.1 | N/A      | A formal security awareness program is implemented to make all personnel aware of the entity's information security policy and procedures, and their role in protecting the cardholder data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Subset Of         | Security, Compliance & Resilience-Minded Workforce    | SAT-01   | Mechanisms exist to facilitate the implementation of security workforce development and awareness controls.                                                                                           | 10                       | Personnel are knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.    |
| 12.6.1 | N/A      | A formal security awareness program is implemented to make all personnel aware of the entity's information security policy and procedures, and their role in protecting the cardholder data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Security, Compliance & Resilience Awareness Training  | SAT-02   | Mechanisms exist to provide all employees and contractors appropriate security, compliance and resilience awareness education and training that is relevant for their job function.                   | 5                        | Personnel are knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.    |
| 12.6.1 | N/A      | A formal security awareness program is implemented to make all personnel aware of the entity's information security policy and procedures, and their role in protecting the cardholder data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training: (1) Before authorizing access to the system or performing assigned duties;                               | 5                        | Personnel are knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.    |
| 12.6.1 | N/A      | A formal security awareness program is implemented to make all personnel aware of the entity's information security policy and procedures, and their role in protecting the cardholder data.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Security, Compliance & Resilience Training Records    | SAT-04   | Mechanisms exist to document, retain and monitor individual training activities, including: (1) Initial security, compliance and resilience awareness training; (2) Recurring awareness training; and | 5                        | Personnel are knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.    |
| 12.6.2 | N/A      | The security awareness program is: <ul style="list-style-type: none"> <li>Reviewed at least once every 12 months, and</li> <li>Updated as needed to address any new threats and vulnerabilities that may impact the security of the entity's CDE, or the information provided to personnel about their role in protecting cardholder data.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Functional     | Intersects With   | Periodic Review                                       | CFG-03.1 | Mechanisms exist to periodically review system configurations to identify and disable unnecessary and/or non-secure functions, ports, protocols and services.                                         | 5                        | The content of security awareness material is reviewed and updated periodically.                                                                                                               |
| 12.6.2 | N/A      | The security awareness program is: <ul style="list-style-type: none"> <li>Reviewed at least once every 12 months, and</li> <li>Updated as needed to address any new threats and vulnerabilities that may impact the security of the entity's CDE,</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Subset Of         | Security, Compliance & Resilience-Minded Workforce    | SAT-01   | Mechanisms exist to facilitate the implementation of security workforce development and awareness controls.                                                                                           | 10                       | The content of security awareness material is reviewed and updated periodically.                                                                                                               |
| 12.6.3 | N/A      | Personnel receive security awareness training as follows: <ul style="list-style-type: none"> <li>Upon hire and at least once every 12 months.</li> <li>Multiple methods of communication are used.</li> <li>Personnel acknowledge at least once every 12 months that they have read and understood the information security policy and procedures.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Functional     | Intersects With   | Periodic Review                                       | CFG-03.1 | Mechanisms exist to periodically review system configurations to identify and disable unnecessary and/or non-secure functions, ports, protocols and services.                                         | 5                        | Personnel remain knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required. |

| FDE #    | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                | STRM Rationale | STRM Relationship | SCF Control                                                                | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                             | Strength of Relationship | Notes                                                                                                                                                                                                     |
|----------|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|----------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 12.6.3   | N/A      | Personnel receive security awareness training as follows:<br>• Upon hire and at least once every 12 months.<br>• Multiple methods of communication are used.<br>• Personnel acknowledge at least once every 12 months that they have read and understood the information security policy and procedures. | Functional     | Intersects With   | User Awareness                                                             | HRS-01   | Mechanisms exist to communicate with users about their roles and responsibilities to maintain a safe and secure working environment.                                                                                                                                                            | 5                        | Personnel remain knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.            |
| 12.6.3   | N/A      | Personnel receive security awareness training as follows:<br>• Upon hire and at least once every 12 months.<br>• Multiple methods of communication are used.<br>• Personnel acknowledge at least once every 12 months that they have read and understood the information security policy and procedures. | Functional     | Intersects With   | Policy Familiarization & Acknowledgement                                   | HRS-05.7 | Mechanisms exist to ensure personnel receive recurring familiarization with the organization's security, compliance and resilience policies and provide acknowledgement.                                                                                                                        | 5                        | Personnel remain knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.            |
| 12.6.3   | N/A      | Personnel receive security awareness training as follows:<br>• Upon hire and at least once every 12 months.<br>• Multiple methods of communication are used.<br>• Personnel acknowledge at least once every 12 months that they have read and understood the information security policy and procedures. | Functional     | Subset Of         | Security, Compliance & Resilience-Minded Workforce                         | SAT-01   | Mechanisms exist to facilitate the implementation of security workforce development and awareness controls.                                                                                                                                                                                     | 10                       | Personnel remain knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.            |
| 12.6.3   | N/A      | Personnel receive security awareness training as follows:<br>• Upon hire and at least once every 12 months.<br>• Multiple methods of communication are used.<br>• Personnel acknowledge at least once every 12 months that they have read and understood the information security policy and procedures. | Functional     | Intersects With   | Security, Compliance & Resilience Awareness Training                       | SAT-02   | Personnel exist to provide all employees and contractors appropriate security, compliance and resilience awareness education and training that is relevant for their job function.                                                                                                              | 5                        | Personnel remain knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.            |
| 12.6.3   | N/A      | Personnel receive security awareness training as follows:<br>• Upon hire and at least once every 12 months.<br>• Multiple methods of communication are used.<br>• Personnel acknowledge at least once every 12 months that they have read and understood the information security policy and procedures. | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training                      | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training:<br>(1) Before authorizing access to the system or performing assigned duties;<br>(2) When required by system changes; and<br>(3) Annually thereafter.                                              | 5                        | Personnel remain knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.            |
| 12.6.3   | N/A      | Personnel receive security awareness training as follows:<br>• Upon hire and at least once every 12 months.<br>• Multiple methods of communication are used.<br>• Personnel acknowledge at least once every 12 months that they have read and understood the information security policy and procedures. | Functional     | Intersects With   | Security, Compliance & Resilience Training Records                         | SAT-04   | Mechanisms exist to document, retain and monitor individual training activities, including:<br>(1) Initial security, compliance and resilience awareness training;<br>(2) Recurring awareness training; and<br>(3) Technology Assets, Applications and/or Services (TAAS)-specific training.    | 5                        | Personnel remain knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.            |
| 12.6.3   | N/A      | Personnel receive security awareness training as follows:<br>• Upon hire and at least once every 12 months.<br>• Multiple methods of communication are used.<br>• Personnel acknowledge at least once every 12 months that they have read and understood the information security policy and procedures. | Functional     | Intersects With   | Cyber Threat Environment                                                   | SAT-03.6 | Mechanisms exist to provide role-based security, compliance and resilience awareness training that is current and relevant to the cyber threats that users might encounter in day-to-day business operations.                                                                                   | 5                        | Personnel remain knowledgeable about the threat landscape, their responsibility for the operation of relevant security controls, and are able to access assistance and guidance when required.            |
| 12.6.3.1 | N/A      | Security awareness training includes awareness of threats and vulnerabilities that could impact the security of the CDE, including but not limited to:<br>• Phishing and related attacks.<br>• Social engineering.                                                                                       | Functional     | Intersects With   | Security, Compliance & Resilience Awareness Training                       | SAT-02   | Mechanisms exist to provide all employees and contractors appropriate security, compliance and resilience awareness education and training that is relevant for their job function.                                                                                                             | 5                        | Personnel are knowledgeable about their own human vulnerabilities and how threat actors will attempt to exploit such vulnerabilities. Personnel are able to access assistance and guidance when required. |
| 12.6.3.1 | N/A      | Security awareness training includes awareness of threats and vulnerabilities that could impact the security of the CDE, including but not limited to:<br>• Phishing and related attacks.<br>• Social engineering.                                                                                       | Functional     | Intersects With   | Social Engineering & Mining                                                | SAT-02.2 | Mechanisms exist to include awareness training on recognizing and reporting potential and actual instances of social engineering and social mining.                                                                                                                                             | 5                        | Personnel are knowledgeable about their own human vulnerabilities and how threat actors will attempt to exploit such vulnerabilities. Personnel are able to access assistance and guidance when required. |
| 12.6.3.1 | N/A      | Security awareness training includes awareness of threats and vulnerabilities that could impact the security of the CDE, including but not limited to:<br>• Phishing and related attacks.<br>• Social engineering.                                                                                       | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training                      | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training:<br>(1) Before authorizing access to the system or performing assigned duties;<br>(2) When required by system changes; and                                                                          | 5                        | Personnel are knowledgeable about their own human vulnerabilities and how threat actors will attempt to exploit such vulnerabilities. Personnel are able to access assistance and guidance when required. |
| 12.6.3.1 | N/A      | Security awareness training includes awareness of threats and vulnerabilities that could impact the security of the CDE, including but not limited to:<br>• Phishing and related attacks.<br>• Social engineering.                                                                                       | Functional     | Intersects With   | Sensitive / Regulated Data Storage, Handling & Processing                  | SAT-03.3 | Mechanisms exist to ensure that every user accessing a system processing, storing or transmitting sensitive and/or regulated data is formally trained in data handling requirements.                                                                                                            | 5                        | Personnel are knowledgeable about their own human vulnerabilities and how threat actors will attempt to exploit such vulnerabilities. Personnel are able to access assistance and guidance when required. |
| 12.6.3.1 | N/A      | Security awareness training includes awareness of threats and vulnerabilities that could impact the security of the CDE, including but not limited to:<br>• Phishing and related attacks.<br>• Social engineering.                                                                                       | Functional     | Intersects With   | Cyber Threat Environment                                                   | SAT-03.6 | Mechanisms exist to provide role-based security, compliance and resilience awareness training that is current and relevant to the cyber threats that users might encounter in day-to-day business operations.                                                                                   | 5                        | Personnel are knowledgeable about their own human vulnerabilities and how threat actors will attempt to exploit such vulnerabilities. Personnel are able to access assistance and guidance when required. |
| 12.6.3.2 | N/A      | Security awareness training includes awareness about the acceptable use of end-user technologies in accordance with Requirement 12.2.1.                                                                                                                                                                  | Functional     | Intersects With   | Role-Based Security, Compliance & Resilience Training                      | SAT-03   | Mechanisms exist to provide role-based security, compliance and resilience-related training:<br>(1) Before authorizing access to the system or performing assigned duties;<br>(2) When required by system changes; and                                                                          | 5                        | Personnel are knowledgeable about their responsibility for the security and operation of end-user technologies and are able to access assistance and guidance when required.                              |
| 12.6.3.2 | N/A      | Security awareness training includes awareness about the acceptable use of end-user technologies in accordance with Requirement 12.2.1.                                                                                                                                                                  | Functional     | Intersects With   | Sensitive / Regulated Data Storage, Handling & Processing                  | SAT-03.3 | Mechanisms exist to ensure that every user accessing a system processing, storing or transmitting sensitive and/or regulated data is formally trained in data handling requirements.                                                                                                            | 5                        | Personnel are knowledgeable about their responsibility for the security and operation of end-user technologies and are able to access assistance and guidance when required.                              |
| 12.6.3.2 | N/A      | Security awareness training includes awareness about the acceptable use of end-user technologies in accordance with Requirement 12.2.1.                                                                                                                                                                  | Functional     | Intersects With   | Cyber Threat Environment                                                   | SAT-03.6 | Mechanisms exist to provide role-based security, compliance and resilience awareness training that is current and relevant to the cyber threats that users might encounter in day-to-day business operations.                                                                                   | 5                        | Personnel are knowledgeable about their responsibility for the security and operation of end-user technologies and are able to access assistance and guidance when required.                              |
| 12.7.1   | N/A      | Potential personnel who will have access to the CDE are screened, within the constraints of local laws, prior to hire to minimize the risk of attacks from internal sources.                                                                                                                             | Functional     | Subset Of         | Human Resources Security Management                                        | HRS-01   | Mechanisms exist to facilitate the implementation of personnel security controls.                                                                                                                                                                                                               | 10                       | The risk related to allowing new members of staff access to the CDE is understood and managed.                                                                                                            |
| 12.7.1   | N/A      | Potential personnel who will have access to the CDE are screened, within the constraints of local laws, prior to hire to minimize the risk of attacks from internal sources.                                                                                                                             | Functional     | Intersects With   | Position Categorization                                                    | HRS-02   | Mechanisms exist to manage personnel security risk by assigning a risk designation to all positions and establishing screening criteria for individuals filling those positions.                                                                                                                | 5                        | The risk related to allowing new members of staff access to the CDE is understood and managed.                                                                                                            |
| 12.7.1   | N/A      | Potential personnel who will have access to the CDE are screened, within the constraints of local laws, prior to hire to minimize the risk of attacks from internal sources.                                                                                                                             | Functional     | Intersects With   | Users With Elevated Privileges                                             | HRS-02.1 | Mechanisms exist to ensure that every user accessing Technology Assets, Applications and/or Services (TAAS) that process, store and/or transmit sensitive and/or regulated data is                                                                                                              | 5                        | The risk related to allowing new members of staff access to the CDE is understood and managed.                                                                                                            |
| 12.7.1   | N/A      | Potential personnel who will have access to the CDE are screened, within the constraints of local laws, prior to hire to minimize the risk of attacks from internal sources.                                                                                                                             | Functional     | Intersects With   | Personnel Screening                                                        | HRS-04   | Mechanisms exist to manage personnel security risk by screening individuals prior to authorizing access.                                                                                                                                                                                        | 5                        | The risk related to allowing new members of staff access to the CDE is understood and managed.                                                                                                            |
| 12.7.1   | N/A      | Potential personnel who will have access to the CDE are screened, within the constraints of local laws, prior to hire to minimize the risk of attacks from internal sources.                                                                                                                             | Functional     | Intersects With   | Roles With Special Protection Measures                                     | HRS-04.1 | Mechanisms exist to ensure that individuals accessing a system that stores, transmits or processes information requiring special protection satisfy organization-defined personnel screening criteria.                                                                                          | 5                        | The risk related to allowing new members of staff access to the CDE is understood and managed.                                                                                                            |
| 12.8.1   | N/A      | A list of all third-party service providers (TPSPs) with which account data is shared or that could affect the security of account data is maintained, including a description for each of the services provided.                                                                                        | Functional     | Subset Of         | Cloud Services                                                             | CLD-01   | Mechanisms exist to facilitate the implementation of cloud management controls to ensure cloud instances are secure and in-line with industry practices.                                                                                                                                        | 10                       | Records are maintained of TPSPs and the services provided.                                                                                                                                                |
| 12.8.1   | N/A      | A list of all third-party service providers (TPSPs) with which account data is shared or that could affect the security of account data is maintained, including a description for each of the services provided.                                                                                        | Functional     | Intersects With   | Remote Access                                                              | NET-14   | Mechanisms exist to define, control and review organization-approved, secure remote access methods.                                                                                                                                                                                             | 5                        | Records are maintained of TPSPs and the services provided.                                                                                                                                                |
| 12.8.1   | N/A      | A list of all third-party service providers (TPSPs) with which account data is shared or that could affect the security of account data is maintained, including a description for each of the services provided.                                                                                        | Functional     | Subset Of         | Third-Party Management                                                     | TPM-01   | Mechanisms exist to facilitate the implementation of third-party management controls.                                                                                                                                                                                                           | 10                       | Records are maintained of TPSPs and the services provided.                                                                                                                                                |
| 12.8.1   | N/A      | A list of all third-party service providers (TPSPs) with which account data is shared or that could affect the security of account data is maintained, including a description for each of the services provided.                                                                                        | Functional     | Intersects With   | Third-Party Inventories                                                    | TPM-01.1 | Mechanisms exist to maintain a current, accurate and complete list of External Service Providers (ESPs) that can potentially impact the Confidentiality, Integrity, Availability and/or Safety (CIAS) of the organization's Technology Assets, Applications,                                    | 5                        | Records are maintained of TPSPs and the services provided.                                                                                                                                                |
| 12.8.1   | N/A      | A list of all third-party service providers (TPSPs) with which account data is shared or that could affect the security of account data is maintained, including a description for each of the services provided.                                                                                        | Functional     | Intersects With   | Third-Party Scope Review                                                   | TPM-05.5 | Mechanisms exist to perform recurring validation of the Responsible, Accountable, Supportive, Consulted & Informed (RASCIS) matrix, or similar documentation, to ensure security, compliance and resilience control assignments accurately.                                                     | 5                        | Records are maintained of TPSPs and the services provided.                                                                                                                                                |
| 12.8.2   | N/A      | Written agreements with TPSPs are maintained as follows:<br>• Written agreements are maintained with all TPSPs with which account data is shared or that could affect the security of the CDE.<br>• Written agreements include acknowledgments from TPSPs that                                           | Functional     | Intersects With   | Responsible, Accountable, Supportive, Consulted & Informed (RASCIS) Matrix | TPM-05.4 | Mechanisms exist to document and maintain a Responsible, Accountable, Supportive, Consulted & Informed (RASCIS) matrix, or similar documentation, to delineate assignment for security, compliance and resilience controls between internal stakeholders and External Service Providers (ESPs). | 5                        | Records are maintained of each TPSP's acknowledgment of its responsibility to protect account data.                                                                                                       |

| FDE #   | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | STRM Rationale | STRM Relationship | SCF Control                                                              | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                             | Strength of Relationship | Notes                                                                                                                                                                    |
|---------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 12.8.2  | N/A      | Written agreements with TPSPs are maintained as follows:<br>• Written agreements are maintained with all TPSPs with which account data is shared or that could affect the security of the CDE.<br>• Written agreements include acknowledgments from TPSPs that they are responsible for the security of account data the TPSPs possess or otherwise store, process, or transmit on behalf of the entity, or to the extent that they could impact the security of the entity's CDE.                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Third-Party Contract Requirements                                        | TPM-05   | Mechanisms exist to require contractual requirements for applicable security, compliance and resilience requirements with third-parties, reflecting the organization's needs to protect its Technology Assets, Applications, Services and/or Data (TAASD).                                      | 5                        | Records are maintained of each TPSP's acknowledgment of its responsibility to protect account data.                                                                      |
| 12.8.2  | N/A      | Written agreements with TPSPs are maintained as follows:<br>• Written agreements are maintained with all TPSPs with which account data is shared or that could affect the security of the CDE.<br>• Written agreements include acknowledgments from TPSPs that they are responsible for the security of account data the TPSPs possess or otherwise store, process, or transmit on behalf of the entity, or to the extent that they could impact the security of the entity's CDE.                                                                                                                                                                                                                                                                                                                    | Functional     | Intersects With   | Third-Party Services                                                     | TPM-04   | Mechanisms exist to mitigate the risks associated with third-party access to the organization's Technology Assets, Applications, Services and/or Data (TAASD).                                                                                                                                  | 5                        | Records are maintained of each TPSP's acknowledgment of its responsibility to protect account data.                                                                      |
| 12.8.3  | N/A      | An established process is implemented for engaging TPSPs, including proper due diligence prior to engagement.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Third-Party Risk Assessments & Approvals                                 | TPM-04.1 | Mechanisms exist to conduct a risk assessment prior to the acquisition or outsourcing of technology-related Technology Assets, Applications and/or Services (TAAS).                                                                                                                             | 5                        | The capability, intent, and resources of a prospective TPSP to adequately protect account data are assessed before the TPSP is engaged.                                  |
| 12.8.4  | N/A      | A program is implemented to monitor TPSPs' PCI DSS compliance status at least once every 12 months.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Review of Third-Party Services                                           | TPM-08   | Mechanisms exist to monitor, regularly review and assess External Service Providers (ESPs) for compliance with established contractual requirements for security, compliance and resilience controls.                                                                                           | 5                        | The PCI DSS compliance status of TPSPs is verified periodically.                                                                                                         |
| 12.8.5  | N/A      | Information is maintained about which PCI DSS requirements are managed by each TPSP, which are managed by the entity, and any that are shared between the TPSP and the entity.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Third-Party Contract Requirements                                        | TPM-05   | Mechanisms exist to require contractual requirements for applicable security, compliance and resilience requirements with third parties, reflecting the organization's needs to protect                                                                                                         | 5                        | Records detailing the PCI DSS requirements and related system components for which each TPSP is solely or jointly responsible, are maintained and reviewed periodically. |
| 12.8.5  | N/A      | Information is maintained about which PCI DSS requirements are managed by each TPSP, which are managed by the entity, and any that are shared between the TPSP and the entity.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Functional     | Intersects With   | Responsible, Accountable, Supportive, Consulted & Informed (RASC) Matrix | TPM-05.4 | Mechanisms exist to document and maintain a Responsible, Accountable, Supportive, Consulted & Informed (RASC) matrix, or similar documentation, to delineate assignment for security, compliance and resilience controls between internal                                                       | 5                        | Records detailing the PCI DSS requirements and related system components for which each TPSP is solely or jointly responsible, are maintained and reviewed periodically. |
| 12.10.1 | N/A      | An incident response plan exists and is ready to be activated in the event of a suspected or confirmed security incident. The plan includes, but is not limited to:<br>• Roles, responsibilities, and communication and contact strategies in the event of a suspected or confirmed security incident.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Data Backups                                                             | BCD-11   | Mechanisms exist to create recurring backups of data, software and/or system images, as well as verify the integrity of these backups, to ensure the availability of the data to satisfy Recovery Time Objectives (RTOs) and Recovery Point Objectives (RPOs).                                  | 5                        | A comprehensive incident response plan that meets card brand expectations is maintained.                                                                                 |
| 12.10.1 | N/A      | An incident response plan exists and is ready to be activated in the event of a suspected or confirmed security incident. The plan includes, but is not limited to:<br>• Roles, responsibilities, and communication and contact strategies in the event of a suspected or confirmed security incident.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Functional     | Intersects With   | Defined Roles & Responsibilities                                         | HRS-03   | Mechanisms exist to define cybersecurity roles & responsibilities for all personnel.                                                                                                                                                                                                            | 5                        | A comprehensive incident response plan that meets card brand expectations is maintained.                                                                                 |
| 12.10.1 | N/A      | An incident response plan exists and is ready to be activated in the event of a suspected or confirmed security incident. The plan includes, but is not limited to:<br>• Roles, responsibilities, and communication and contact strategies in the event of a suspected or confirmed security incident, including notification of payment brands and acquirers, at a minimum.<br>• Incident response procedures with specific containment and mitigation activities for different types of incidents.<br>• Business recovery and continuity procedures.<br>• Data backup processes.<br>• Analysis of legal requirements for reporting compromises.<br>• Coverage and responses of all critical system components.<br>• Reference or inclusion of incident response procedures from the payment brands. | Functional     | Intersects With   | Incident Response Plan (IRP)                                             | IRO-04   | Mechanisms exist to maintain and make available a current and visible Incident Response Plan (IRP) to all stakeholders.                                                                                                                                                                         | 5                        | A comprehensive incident response plan that meets card brand expectations is maintained.                                                                                 |
| 12.10.1 | N/A      | An incident response plan exists and is ready to be activated in the event of a suspected or confirmed security incident. The plan includes, but is not limited to:<br>• Roles, responsibilities, and communication and contact strategies in the event of a suspected or confirmed security incident, including notification of payment brands and acquirers, at a minimum.<br>• Incident response procedures with specific containment and mitigation activities for different types of incidents.<br>• Business recovery and continuity procedures.<br>• Data backup processes.<br>• Analysis of legal requirements for reporting compromises.<br>• Coverage and responses of all critical system components.<br>• Reference or inclusion of incident response procedures from the payment brands. | Functional     | Intersects With   | Incident Stakeholder Reporting                                           | IRO-10   | Mechanisms exist to timely-report incidents to applicable:<br>(1) Internal stakeholders;<br>(2) Affected clients & third-parties; and<br>(3) Regulatory authorities.                                                                                                                            | 5                        | A comprehensive incident response plan that meets card brand expectations is maintained.                                                                                 |
| 12.10.1 | N/A      | An incident response plan exists and is ready to be activated in the event of a suspected or confirmed security incident. The plan includes, but is not limited to:<br>• Roles, responsibilities, and communication and contact strategies in the event of a suspected or confirmed security incident, including notification of payment brands and acquirers, at a minimum.<br>• Incident response procedures with specific containment and mitigation activities for different types of incidents.<br>• Business recovery and continuity procedures.<br>• Data backup processes.<br>• Analysis of legal requirements for reporting compromises.<br>• Coverage and responses of all critical system components.<br>• Reference or inclusion of incident response procedures from the payment brands. | Functional     | Intersects With   | Wireless Link Protection                                                 | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for unauthorized wireless access points and taking appropriate action, if an unauthorized connection is discovered. | 5                        | A comprehensive incident response plan that meets card brand expectations is maintained.                                                                                 |
| 12.10.2 | N/A      | At least once every 12 months, the security incident response plan is:<br>• Reviewed and the content is updated as needed.<br>• Tested, including all elements listed in Requirement 12.10.1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | IRP Update                                                               | IRO-04.2 | Mechanisms exist to regularly review and modify incident response practices to incorporate lessons learned, business process changes and industry developments, as necessary.                                                                                                                   | 5                        | The incident response plan is kept current and tested periodically.                                                                                                      |
| 12.10.2 | N/A      | At least once every 12 months, the security incident response plan is:<br>• Reviewed and the content is updated as needed.<br>• Tested, including all elements listed in Requirement 12.10.1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Functional     | Intersects With   | Incident Response Testing                                                | IRO-06   | Mechanisms exist to formally test incident response capabilities through realistic exercises to determine the operational effectiveness of those capabilities.                                                                                                                                  | 5                        | The incident response plan is kept current and tested periodically.                                                                                                      |
| 12.10.3 | N/A      | Specific personnel are designated to be available on a 24/7 basis to respond to suspected or confirmed security incidents.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Integrated Security Incident Response Team (ISIRT)                       | IRO-07   | Mechanisms exist to establish an integrated team of cybersecurity, IT and business function representatives that are capable of addressing cybersecurity and data protection incident response operations.                                                                                      | 5                        | Incidents are responded to immediately where appropriate.                                                                                                                |

| FDE #     | FDE Name | Focal Document Element (FDE) Description*                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | STRM Rationale | STRM Relationship | SCF Control                                      | SCF #    | Secure Controls Framework (SCF) Control Description                                                                                                                                                                                                                                             | Strength of Relationship | Notes                                                                                                                                                |
|-----------|----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------------|--------------------------------------------------|----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| 12.10.4   | N/A      | Personnel responsible for responding to suspected and confirmed security incidents are appropriately and periodically trained on their incident response responsibilities.                                                                                                                                                                                                                                                                                                                                                                                                                                   | Functional     | Intersects With   | Incident Response Training                       | IRO-05   | Mechanisms exist to train personnel in their incident response roles and responsibilities.                                                                                                                                                                                                      | 5                        | Personnel are knowledgeable about their role and responsibilities in incident response and are able to access assistance and guidance when required. |
| 12.10.4.1 | N/A      | The frequency of periodic training for incident response personnel is defined in the entity's targeted risk analysis, which is performed according to all elements specified in Requirement 12.3.1.                                                                                                                                                                                                                                                                                                                                                                                                          | Functional     | Intersects With   | Incident Response Training                       | IRO-05   | Mechanisms exist to train personnel in their incident response roles and responsibilities.                                                                                                                                                                                                      | 5                        | Incident response personnel are trained at a frequency that addresses the entity's risk.                                                             |
| 12.10.5   | N/A      | The security incident response plan includes monitoring and responding to alerts from security monitoring systems, including but not limited to:<br>• Intrusion-detection and intrusion-prevention systems.                                                                                                                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Incident Handling                                | IRO-02   | Mechanisms exist to cover:<br>(1) Preparation;<br>(2) Automated event detection or manual incident report intake;<br>(3) Analysis;                                                                                                                                                              | 5                        | Alerts generated by monitoring and detection technologies are responded to in a structured, repeatable manner.                                       |
| 12.10.5   | N/A      | The security incident response plan includes monitoring and responding to alerts from security monitoring systems, including but not limited to:<br>• Intrusion-detection and intrusion-prevention systems.                                                                                                                                                                                                                                                                                                                                                                                                  | Functional     | Intersects With   | Incident Response Plan (IRP)                     | IRO-04   | Mechanisms exist to maintain and make available a current and visible Incident Response Plan (IRP) to all stakeholders.                                                                                                                                                                         | 5                        | Alerts generated by monitoring and detection technologies are responded to in a structured, repeatable manner.                                       |
| 12.10.5   | N/A      | The security incident response plan includes monitoring and responding to alerts from security monitoring systems, including but not limited to:<br>• Intrusion-detection and intrusion-prevention systems.<br>• Network security controls.<br>• Change-detection mechanisms for critical files.<br>• The change-and tamper-detection mechanism for payment pages. This bullet is a best practice until its effective date; refer to Applicability Notes below for details.<br>• Detection of unauthorized wireless access points.                                                                           | Functional     | Intersects With   | Correlate Monitoring Information                 | MON-02.1 | Automated mechanisms exist to correlate both technical and non-technical information from across the enterprise by a Security Incident Event Manager (SIEM) or similar automated tool, to enhance organization-wide situational awareness.                                                      | 5                        | Alerts generated by monitoring and detection technologies are responded to in a structured, repeatable manner.                                       |
| 12.10.5   | N/A      | The security incident response plan includes monitoring and responding to alerts from security monitoring systems, including but not limited to:<br>• Intrusion-detection and intrusion-prevention systems.<br>• Network security controls.<br>• Change-detection mechanisms for critical files.<br>• The change-and tamper-detection mechanism for payment pages. This bullet is a best practice until its effective date; refer to Applicability Notes below for details.<br>• Detection of unauthorized wireless access points.                                                                           | Functional     | Intersects With   | Wireless Link Protection                         | NET-12.1 | Mechanisms exist to protect external and internal wireless links from signal parameter attacks through monitoring for unauthorized wireless connections, including scanning for unauthorized wireless access points and taking appropriate action, if an unauthorized connection is discovered. | 5                        | Alerts generated by monitoring and detection technologies are responded to in a structured, repeatable manner.                                       |
| 12.10.6   | N/A      | The security incident response plan is modified and evolved according to lessons learned and to incorporate industry developments.                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | Root Cause Analysis (RCA) & Lessons Learned      | IRO-13   | Mechanisms exist to incorporate lessons learned from analyzing and resolving cybersecurity and data protection incidents to reduce the likelihood or impact of future incidents.                                                                                                                | 5                        | The effectiveness and accuracy of the incident response plan is reviewed and updated after each invocation.                                          |
| 12.10.6   | N/A      | The security incident response plan is modified and evolved according to lessons learned and to incorporate industry developments.                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Functional     | Intersects With   | IRP Update                                       | IRO-04.2 | Mechanisms exist to regularly review and modify incident response practices to incorporate lessons learned, business process changes and industry developments, as necessary.                                                                                                                   | 5                        | The effectiveness and accuracy of the incident response plan is reviewed and updated after each invocation.                                          |
| 12.10.7   | N/A      | Incident response procedures are in place, to be initiated upon the detection of stored PAN anywhere it is not expected, and include:<br>• Determining what to do if PAN is discovered outside the CDE.                                                                                                                                                                                                                                                                                                                                                                                                      | Functional     | Intersects With   | Incident Response Plan (IRP)                     | IRO-04   | Mechanisms exist to maintain and make available a current and visible Incident Response Plan (IRP) to all stakeholders.                                                                                                                                                                         | 5                        | Processes are in place to quickly respond, analyze, and address situations in the event that cleartext PAN is detected where it is not expected.     |
| 12.10.7   | N/A      | Incident response procedures are in place, to be initiated upon the detection of stored PAN anywhere it is not expected, and include:<br>• Determining what to do if PAN is discovered outside the CDE, including its retrieval, secure deletion, and/or migration into the currently defined CDE, as applicable.                                                                                                                                                                                                                                                                                            | Functional     | Intersects With   | Sensitive / Regulated Data Spill Response        | IRO-12   | Mechanisms exist to respond to sensitive and/or regulated data spills.                                                                                                                                                                                                                          | 5                        | Processes are in place to quickly respond, analyze, and address situations in the event that cleartext PAN is detected where it is not expected.     |
| 12.10.7   | N/A      | Incident response procedures are in place, to be initiated upon the detection of stored PAN anywhere it is not expected, and include:<br>• Determining what to do if PAN is discovered outside the CDE, including its retrieval, secure deletion, and/or migration into the currently defined CDE, as applicable.<br>• Identifying whether sensitive authentication data is stored with PAN.<br>• Determining where the account data came from and how it ended up where it was not expected.<br>• Remediating data leaks or process gaps that resulted in the account data being where it was not expected. | Functional     | Intersects With   | Post-Sensitive / Regulated Data Spill Operations | IRO-12.3 | Mechanisms exist to ensure that organizational personnel impacted by sensitive and/or regulated data spills can continue to carry out assigned tasks while contaminated Technology Assets, Applications and/or Services (TAAS) are undergoing corrective actions.                               | 5                        | Processes are in place to quickly respond, analyze, and address situations in the event that cleartext PAN is detected where it is not expected.     |
| A2.1.1    | N/A      | Where POS POI terminals at the merchant or payment acceptance location use SSL and/or early TLS, the entity confirms the devices are not susceptible to any known exploits for those protocols.                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Transmission Confidentiality                     | CRY-03   | Cryptographic mechanisms exist to protect the confidentiality of data being transmitted.                                                                                                                                                                                                        | 5                        | This requirement is not eligible for the customized approach.                                                                                        |
| A2.1.1    | N/A      | Where POS POI terminals at the merchant or payment acceptance location use SSL and/or early TLS, the entity confirms the devices are not susceptible to any known exploits for those protocols.                                                                                                                                                                                                                                                                                                                                                                                                              | Functional     | Intersects With   | Secure Web Traffic                               | WEB-10   | Mechanisms exist to ensure all web application content is delivered using cryptographic mechanisms (e.g., TLS).                                                                                                                                                                                 | 5                        | This requirement is not eligible for the customized approach.                                                                                        |