

Dust is Over




$10,000 at 10%, compounded daily on an 18-decimal ruler. docs/benchmarks/ladder.json: compound


One honest transaction



Aave v3 USDC borrow, 1M USDC at 100% utilisation, untouched a day; the deployed code against the formula at 200 digits. docs/benchmarks/accrual-deployed.json: aave-usdc-u100-borrow-1d


Resupply, 26 June 2025






Tx 0xffbbd492…, block 22,785,461: the pinned integers, the same formula on each ruler. scripts/replays/resupply.json; docs/benchmarks/replay-resupply.md

Bunni v2, 2 September 2025




Tx 0x1c27c4d6..., block 23,273,098: the 44 withdrawals replayed from the trace, only the stored idle balance changed. scripts/replays/bunni.json (bunni.py replay); docs/benchmarks/replay-bunni.md

Balancer V2, 3 November 2025




Tx 0x6ed07db1…, block 23,717,397: every call priced on its own on-chain balances; D* solved exactly. scripts/replays/balancer.json (score.osETH); docs/benchmarks/replay-balancer.md

Balancer V1, 31 August 2026




Five pools; from each pool's first join at 3 units, one join/exit cycle re-tuned to each rule at 200 digits. docs/benchmarks/replay-balancer-v1.md: Precision or direction?

Goal one: round once




A year of daily compounding, $10,000 at 10%. docs/benchmarks/ladder.json. WAD = an 18-decimal library; 64.64 and binary128 = the two ABDK formats.

Goal two: never run out of ruler




Exact properties of each format, computed in scripts/talk/deck.py.

Ramanujan




Ramanujan's series through each library's own sqrt, mul and div. docs/benchmarks/pi.md

Balancer's Newton solve, three rulers




StableMath's invariant iteration on each ruler, residual against the exact root at 200 digits. scripts/replays/balancer.json (score.*.convergence); docs/benchmarks/replay-balancer.md: Newton convergence

Converge, or fit




Computed with mpmath at each width: Newton's sqrt(2), and a Taylor polynomial for exp tuned for 60 bits (the shortest within 2^-60 on [0, ln 2]), at x = ln 2. scripts/talk/deck.py: converge_vs_fit

Release one, and now




Worst bits over the committed vectors. Release one: contracts/deployments/FP256.md; now: docs/fp256/precision.json (precision.md) and docs/benchmarks/sweep.json

The format ceiling



A 256-bit word: sign, e exponent bits, 256 − e significand bits with the hidden bit; range 2^±2^(e−1). Computed in scripts/talk/deck.py: plot_format_ceiling


The accuracy ceiling



FP256: share of random inputs that return the correctly rounded word
and 65,273 more forced through the second stage of 12 ops: 0 misrounded


Seeded random inputs against the correctly rounded word (300 digits, ties away from zero). docs/benchmarks/sweep.json (sweep.md)

What it costs




Median gas over each op's input ladder, inline libraries. docs/benchmarks/gas.md (Solady, PRBMath SD59x18, FP127Lib); docs/benchmarks/gas256.md (FP256Lib)

Both goals, met



Exact properties of each format, computed in scripts/talk/deck.py.

Checked on chain



contracts/deployments/RELEASE.json

Use FP127 and FP256

FP127

`0x6cFbCB928Ac068E84Ef793Dd1DFce4f8e9Cac1d1`

FP256

`0x67eFfb11bF93c79a2B12cc7872cBaC12b3eB61be`

blockulator.com · github.com/securedataresearch/blockulator