

# Software Obfuscation with LLVM

(Ab)using the compiler to “protect” code

# Bio

- Carl Svensson
- Head of Security, KRY/LIVI
- CTF: HackingForSoju
- Twitter: @zetatwo
- Email: [calle.svensson@zeta-two.com](mailto:calle.svensson@zeta-two.com)
- Website: <https://zeta-two.com>



# Agenda

- Software obfuscation
- Compilers
  - LLVM
- LLVM for obfuscation
- Testing
- Counter attacks


# Software obfuscation

- Level

- Source
- Intermediate
- Machine code

- Categories

- Control flow flattening
- Self-modifying code
- Dead code
- Packers
- Droppers
- Anti-debugging
- VM



# Compilers





- Transform language
- Human readable to machine
- Example: C to x86
- Example: Rust to ARM

```
1 #include <iostream>
2
3 int main(){
4     std::cout << "Hello, World!" << std::endl;
5     return 0;
6 }
```

```
hello.asm
.MODEL tiny ; all seg regs equal
.CODE
org 100h ; .COM entry
start: jmp short main
.DATA
msg db 'Hello, world!',0dh,0ah,0
.CODE
sout: mov cx,100h
sout1: mov dl,[bx]
      inc bx
      or dl,dl ; set flags
      jz sout2
      mov ah,02h ; chr out
      int 21h
      loop sout1
sout2: ret
main:  mov bx,OFFSET msg
      call sout
      mov ah,4ch ; terminate
      int 21h
      end start
```


# LLVM

- Compiler framework
- L+A instead of L\*A
  - L number of languages
  - A number of architectures
- Single target
- A lot of tools exist
  - Manticore



# Writing an LLVM pass

- Simple
- “Constrained” to LLVM API
- Example: Quarkslab’s



```
#include "llvm/Pass.h"
#include "llvm/IR/Function.h"
#include "llvm/Support/raw_ostream.h"

#include "llvm/IR/LegacyPassManager.h"
#include "llvm/Transforms/IPO/PassManagerBuilder.h"

using namespace llvm;

namespace {
class MyPass : public BasicBlockPass {
public:
    static char ID;

    MyPass() : BasicBlockPass(ID) {}

    bool runOnBasicBlock(BasicBlock &BB) override {
        errs() << "I m running on a block...\n";
        return false;
    }
};
}

char MyPass::ID = 0;
static RegisterPass<MyPass> X("MyPass", "Obfuscates zeroes",
                              false, false);

// register pass for clang use
static void registerMyPassPass(const PassManagerBuilder &,
                               PassManagerBase &PM) {
    PM.add(new MyPass());
}

static RegisterStandardPasses
    RegisterMBAPass(PassManagerBuilder::EP_EarlyAsPossible,
                    registerMyPassPass);
```

# Writing an obfuscating LLVM pass

- Simple
- “Constrained” to LLVM API
- Example: Quarkslab’s

$$(p_1 * ((x \vee a_1)^2) \neq p_2 * ((y \vee a_2)^2))$$

- $(p_1)$  and  $(p_2)$  are *distinct* prime numbers
- $(a_1)$  and  $(a_2)$  are *distinct* strictly positive random numbers
- $(x)$  and  $(y)$  are two variables picked from the program (they have to be reachable from the obfuscation instructions)



# Forking LLVM

- More complicated
- Full control
- Example: Obfuscator-LLVM

“The aim of this project is to provide an open-source fork of the LLVM compilation suite able to provide increased software security through code obfuscation and tamper-proofing.”

# Testing

- Write some unit tests
- Utilize an existing large project
  - Example: OpenSSL

# Antidote?

- Static analysis
  - Build unpacker
- Symbolic execution
  - Generic
  - Specific
- Dynamic analysis
  - Tracing
  - Fuzzing
  - Manual

# Sources

- Obfuscator-LLVM: <https://github.com/obfuscator-llvm/obfuscator/wiki>
- Quarkslab:
  - <https://blog.quarkslab.com/turning-regular-code-into-atrocities-with-llvm.html>
  - <https://blog.quarkslab.com/deobfuscation-recovering-an-llvm-protected-program.html>
- <https://yurichev.com/blog/llvm/>
- <https://github.com/0vercl0k/stuffz/blob/master/llvm-funz/kryptonite/llvm-functionpass-kryptonite-obfuscater.cpp>
- <https://doar-e.github.io/blog/2013/09/16/breaking-kryptonites-obfuscation-with-symbolic-execution/>

# Thanks for listening

Questions?