INTERNATIONAL JOURNAL FOR NUMERICAL METHODS IN FLUIDS Int. J. Numer. Meth. Fluids 29: 605-621 (1999)

DISCRETE NON-LOCAL ABSORBING BOUNDARY CONDITION FOR EXTERIOR PROBLEMS GOVERNED BY HELMHOLTZ EQUATION

RUPERTO P. BONET*1, NORBERTO NIGRO, MARIO A. STORTI AND SERGIO R. IDELSOHN

Mechanic Technology Group, INTEC, Güemes 3450, 3000 Santa Fe, Argentina

SUMMARY

pproximate the solutions of the Helmholtz equation for water wave radiation and scattering in an unbounded domain. A discrete, non-local and non-reflecting boundary condition is specified at an artificial external boundary by the DNL method, yielding an equivalent problem that is solved in a bounded domain. This procedure formulates a boundary value problem in a bounded region by imposing a relation in the discrete medium between the nodal values at the two last layers. For plane geometry, this relation can be found by straightforward eigenvalue decomposition. For circular geometry, the plane candition is applied at the external layer and this condition is condensed through a structured annulary stacle are considered. It is well-known that these kind of problems are well-posed, and have a unipod solution. Numerical studies based on standard annular region width. The DNL condition is companied with local boundary conditions of several orders. Standard conditions. Copyright © 1999 John Wiley answer. Ltd. The finite element method is employed to a

KEY WORDS: absorbing boundary condition; Helmholtz; discrete; non-local radiation; scattering

1. INTRODUCTION

Water waves elliptic propagation models governed by the Helmholtz equation with variable refraction-diffraction index k = k(x, y) [1,2], have received a wide acceptance for performing engineering simulations of water waves propagation over arbitrary bathymetry and in complex coastal domains.

Numerical solutions of the Helmholtz equation in exterior domains have been sought primarily via techniques that are based on the Helmholtz integral representations of the problem, relating quantities on the physical boundary of the problem [1]. Such formulations bathymetry must be constant in the exterior domain. These formulations are obtained by using fundamental solutions as weighting functions and employing Green's theorem, a procedure that typically is restricted to linear, isotropic are based in the consideration that the

Copyright © 1999 John Wiley & Sons, Ltd. CCC 0271-2091/99/050605-17\$17.50

Correspondence to: Mechanic Technology Group, INTEC, Güemes 3450, 3000 Santa Fe, Argentina. E-mail: rbonet@venus.unl.edu.ar
 Tel.: + 54 42 559175; fax: + 54 42 550944.