

[Modules](#)[Chains](#)

Chains

Chains refer to sequences of calls - whether to an LLM, a tool, or a data preprocessing step. The primary supported way to do this is with [LCEL](#).

LCEL is great for constructing your own chains, but it's also nice to have chains that you can use off-the-shelf. There are two types of off-the-shelf chains that LangChain supports:

- Chains that are built with LCEL. In this case, LangChain offers a higher-level constructor method. However, all that is being done under the hood is constructing a chain with LCEL.
- [Legacy] Chains constructed by subclassing from a legacy `Chain` class. These chains do not use LCEL under the hood but are rather standalone classes.

We are working creating methods that create LCEL versions of all chains. We are doing this for a few reasons.

1. Chains constructed in this way are nice because if you want to modify the internals of a chain you can simply

modify the LCEL.

2. These chains natively support streaming, async, and batch out of the box.
3. These chains automatically get observability at each step.

This page contains two lists. First, a list of all LCEL chain constructors. Second, a list of all legacy Chains.

LCEL Chains

Below is a table of all LCEL chain constructors. In addition, we report on:

Chain Constructor

The constructor function for this chain. These are all methods that return LCEL runnables. We also link to the API documentation.

Function Calling

Whether this requires OpenAI function calling.



Other Tools

What other tools (if any) are used in this chain.

When to Use

Our commentary on when to use this chain.

| Chain Constructor | Function Calling | Other Tools |
|---|------------------|-------------|
| <code>create_stuff_documents_chain</code> | | |

| Chain Constructor | Function Calling | Other Tools |
|-----------------------------------|---|-------------|
| | | |
| create_openai_fn_runnable |  | |
| create_structured_output_runnable |  | |

| Chain Constructor | Function Calling | Other Tools |
|---------------------------------|------------------|-------------|
| | | |
| load_query_constructor_runnable | | |

| Chain Constructor | Function Calling | Other Tools |
|---|------------------|--------------|
| | | |
| <code>create_sql_query_chain</code> | | SQL Database |
| <code>create_history_aware_retriever</code> | | Retriever |

| Chain Constructor | Function Calling | Other Tools |
|-------------------------------------|------------------|-------------|
| | | |
| <code>create_retrieval_chain</code> | | Retriever |

| Chain Constructor | Function Calling | Other Tools |
|-------------------|------------------|-------------|
| | | |

Legacy Chains

Below we report on the legacy chain types that exist. We will maintain support for these until we are able to create a LCEL alternative. We report on:

Chain

Name of the chain, or name of the constructor method. If constructor method, this will return a `Chain` subclass.

Function Calling

Whether this requires OpenAI Function Calling.

Other Tools

Other tools used in the chain.

When to Use

Our commentary on when to use.

| Chain | Function Calling | Other Tools |
|------------------------------|------------------|---------------------|
| APIChain | | Requests Wrapper |
| OpenAPIEndpointChain | | OpenAPI Spec |
| ConversationalRetrievalChain | | Retriever |

| Chain | Function Calling | Other Tools |
|----------------------|------------------|-------------|
| | | |
| StuffDocumentsChain | | |
| ReduceDocumentsChain | | |


| Chain | Function Calling | Other Tools |
|-------------------------|------------------|-------------|
| | | |
| MapReduceDocumentsChain | | |
| RefineDocumentsChain | | |






| Chain | Function Calling | Other Tools |
|-------------------------|------------------|-------------|
| | | |
| MapRerankDocumentsChain | | |
| ConstitutionalChain | | |

| Chain | Function Calling | Other Tools |
|----------------------------|------------------|------------------------|
| LLMChain | | |
| ElasticsearchDatabaseChain | | ElasticSearch Instance |
| FlareChain | | |
| ArangoGraphQAChain | | Arango Graph |

| Chain | Function Calling | Other Tools |
|----------------------|------------------|---|
| GraphCypherQAChain | | A graph that works with Cypher query language |
| FalkorDBGraphQAChain | | Falkor Database |
| HugeGraphQAChain | | HugeGraph |
| KuzuQAChain | | Kuzu Graph |

| Chain | Function Calling | Other Tools |
|--------------------------|------------------|------------------------------|
| | | |
| NebulaGraphQAChain | | Nebula Graph |
| NeptuneOpenCypherQAChain | | Neptune Graph |
| GraphSparqlChain | | Graph that works with SparQL |

| Chain | Function Calling | Other Tools |
|-----------------------------------|--|-------------|
| LLMMath | | |
| LLMCheckerChain | | |
| LLMSummarizationChecker | | |
| create_citation_fuzzy_match_chain |  | |

| Chain | Function Calling | Other Tools |
|----------------------------------|--|--------------|
| create_extraction_chain |  | |
| create_extraction_chain_pydantic |  | |
| get_openapi_chain |  | OpenAPI Spec |
| create_qa_with_structure_chain |  | |
| create_qa_with_sources_chain |  | |
| QAGenerationChain | | |

| Chain | Function Calling | Other Tool |
|-----------------------------|------------------|------------|
| | | |
| RetrievalQAWithSourcesChain | | Retriever |
| load_qa_with_sources_chain | | Retriever |

| Chain | Function Calling | Other Tools |
|-----------------------|------------------|-------------|
| | | |
| RetrievalQA | | Retriever |
| MultiPromptChain | | |
| MultiRetrievalQAChain | | Retriever |
| EmbeddingRouterChain | | |

| Chain | Function Calling | Other Tools |
|----------------------|------------------|-------------|
| | | |
| LLMRouterChain | | |
| load_summarize_chain | | |
| LLMRequestsChain | | |