

[Modules](#)[Retrieval](#)[Text Splitters](#)[MarkdownHeaderTextSplitter](#)

MarkdownHeaderTextSplitter

Motivation

Many chat or Q+A applications involve chunking input documents prior to embedding and vector storage.

[These notes](#) from Pinecone provide some useful tips:

When a full paragraph or document is embedded, the embedding process considers both the overall context and the relationships between the sentences and phrases within the text. This can result in a more comprehensive vector representation that captures the broader meaning and themes of the text.

As mentioned, chunking often aims to keep text with common context together. With this in mind, we might want to specifically honor the structure of the document itself. For example, a markdown file is organized by headers. Creating chunks within specific header groups is an intuitive idea. To

address this challenge, we can use

`MarkdownHeaderTextSplitter`. This will split a markdown file by a specified set of headers.

For example, if we want to split this markdown:

```
md = '# Foo\n\n## Bar\n\nHi this is Jim\n\nHi this is Joe\n\n## Baz\n\nHi this is Molly'
```

We can specify the headers to split on:

```
[("#", "Header 1"), ("##", "Header 2")]
```

And content is grouped or split by common headers:

```
{'content': 'Hi this is Jim\n\nHi this is Joe', 'metadata': {'Header 1': 'Foo', 'Header 2': 'Bar'}}  
{'content': 'Hi this is Molly', 'metadata': {'Header 1': 'Foo', 'Header 2': 'Baz'}}
```

Let's have a look at some examples below.

```
from langchain.text_splitter import  
MarkdownHeaderTextSplitter
```

```
markdown_document = "# Foo\n\n    ## Bar\n\nHi  
this is Joe\n\n ### Boo \n\n Hi this is Lance \n  
this is Molly"
```

```
headers_to_split_on = [  
    ("#", "Header 1"),  
    ("##", "Header 2"),  
    ("###", "Header 3"),  
]
```

```
markdown_splitter =  
MarkdownHeaderTextSplitter(headers_to_split_on=  
md_header_splits = markdown_splitter.split_text  
md_header_splits
```

```
[Document(page_content='Hi this is Jim \nHi  
this is Joe', metadata={'Header 1': 'Foo',  
'Header 2': 'Bar'}),  
    Document(page_content='Hi this is Lance',  
metadata={'Header 1': 'Foo', 'Header 2':  
'Bar', 'Header 3': 'Boo'}),  
    Document(page_content='Hi this is Molly',  
metadata={'Header 1': 'Foo', 'Header 2':  
'Baz'})]
```

```
type(md_header_splits[0])
```

```
langchain.schema.document.Document
```

By default, `MarkdownHeaderTextSplitter` strips headers being split on from the output chunk's content. This can be disabled by setting `strip_headers = False`.

```
markdown_splitter = MarkdownHeaderTextSplitter(  
    headers_to_split_on=headers_to_split_on,  
    strip_headers=False  
)  
md_header_splits =  
markdown_splitter.split_text(markdown_document)  
md_header_splits
```

```
[Document(page_content='# Foo \n## Bar \nHi  
this is Jim \nHi this is Joe', metadata=  
{ 'Header 1': 'Foo', 'Header 2': 'Bar' } ),  
 Document(page_content='### Boo \nHi this is  
Lance', metadata={ 'Header 1': 'Foo', 'Header  
2': 'Bar', 'Header 3': 'Boo' } ),  
 Document(page_content='## Baz \nHi this is  
Molly', metadata={ 'Header 1': 'Foo', 'Header  
2': 'Baz' } ) ]
```

Within each markdown group we can then apply any text splitter we want.

```
markdown_document = "# Intro \n\n      ## History \n\n Markdown[9] is a lightweight markup language for creating formatted text using a plain-text editor. John Gruber created Markdown in 2004 as a markup language that is appealing to human readers in its source code form.[9] \n\n Markdown is widely used in blogging, instant messaging, online forums, collaborative software, documentation pages, and readme files. \n\n ## Rise and divergence \n\n As Markdown popularity grew rapidly, many Markdown implementations appeared, driven mostly by the need for \n\n additional features such as tables, footnotes, definition lists,[note 1] and Markdown inside HTML blocks. \n\n #### Standardization \n\n From 2012, a group of people, including Jeff Atwood and John MacFarlane, launched what Atwood characterised as a standardisation effort. \n\n ## Implementations \n\n Implementations of Markdown are available for over a dozen programming languages."
```

```
headers_to_split_on = [  
    ("#", "Header 1"),  
    ("##", "Header 2"),  
]
```

```
# MD splits
markdown_splitter = MarkdownHeaderTextSplitter(
    headers_to_split_on=headers_to_split_on,
    strip_headers=False
)
md_header_splits =
markdown_splitter.split_text(markdown_document)

# Char-level splits
from langchain.text_splitter import
RecursiveCharacterTextSplitter

chunk_size = 250
chunk_overlap = 30
text_splitter = RecursiveCharacterTextSplitter(
    chunk_size=chunk_size,
    chunk_overlap=chunk_overlap
)

# Split
splits =
text_splitter.split_documents(md_header_splits)
splits
```

```
[Document(page_content='# Intro \n## History \nMarkdown[9] is a lightweight markup language for creating formatted text using a plain-text editor. John Gruber created Markdown in 2004 as a markup language that is
```

```
appealing to human readers in its source code
form.[9]', metadata={'Header 1': 'Intro',
'Header 2': 'History'}),
```

```
Document(page_content='Markdown is widely
used in blogging, instant messaging, online
forums, collaborative software, documentation
pages, and readme files.', metadata={'Header
1': 'Intro', 'Header 2': 'History'}),
```

```
Document(page_content='## Rise and
divergence \nAs Markdown popularity grew
rapidly, many Markdown implementations
appeared, driven mostly by the need for
\nadditional features such as tables,
footnotes, definition lists,[note 1] and
Markdown inside HTML blocks.', metadata=
{'Header 1': 'Intro', 'Header 2': 'Rise and
divergence'}),
```

```
Document(page_content='#### Standardization
\nFrom 2012, a group of people, including
Jeff Atwood and John MacFarlane, launched
what Atwood characterised as a
standardisation effort.', metadata={'Header
1': 'Intro', 'Header 2': 'Rise and
divergence'}),
```

```
Document(page_content='## Implementations
\nImplementations of Markdown are available
for over a dozen programming languages.',
metadata={'Header 1': 'Intro', 'Header 2':
'Implementations'})]
```