TECHNICAL DATA SHEET



YIPIN® Green Chrome Green Chrome S5376

Edition of2015-02-18TypePigment GreenDelivery FormPowder


CAS No 1308-38-9

Use RecommendationCoating Construction Plastic

COLOR VALUES AND TINTING STRENGTH				
Reference			Standard: ASTM	
	<u>Min</u>	<u>Max</u>	Test Method	
Binder	Test Paste Based On R-05			
Full Shade			ASTM D 387	
L*	-0.7	+0.7		
a*	-0.7	+0.7		
b*	-0.7	+0.7		
E*ab		1.0		
Reduction with titanium dioxide (1:2)	R-706		ASTM D 387	
L*	-0.7	+0.7		
a*	-0.7	+0.7		
b*	-0.7	+0.7		
E*ab		1.0		
Binder	R-05			
Relative tinting strength [%]	95.0	105.0		

TECHNICAL DATA			
	Min	Max	Test Method
Water-Soluble Content [%]		0.5	ASTM D 1208
Sieve Residue 0.045mm [%]		0.3	ASTM D 185
PH Value	4.0	7.0	ASTM D 1208
Cr ₂ O ₃ [%]	99.0		ASTM D 126
Moisture (After Production) [%]		0.2	ASTM D 280
Particle Shape	Sphe	erical	Electron Micrographs

TECHNICAL DATA SHEET





	<u>Approx.</u>	
Predominant Particle size [µM]	0.4	Electron Micrographs
Oil Absorption [g/100g]	15~25	ASTM D 281
Density [g/ml]	\sim 5.2	ASTM D153
Stability on Heating[]	1000	Muffle Furnace Calcination

STANDARD PACKAGING	25kg/bag 50LB/bag

TRANSPORT AND STORAGE

Protect against weathering. Store in a dry place and avoid extreme fluctuations in temperature. Special conditions for opened packaging: Close bags after use to prevent the absorption of moisture and contamination.

SAFETY

The product is not classified as dangerous under the relevant EC directives and corresponding national regulations valid in the individual EU member states. It is not dangerous according to transport regulations. In countries outside the EU, compliance with the respective national legislation concerning the classification, packaging, labeling and transport of dangerous substances must be ensured.

The information contained in the safety data sheet should be observed.

This contains information on handing, product safety and ecology.

This information is given in good faith, without warranty. It is also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General conditions of sale and delivery.