React

Student: Sajad Dehqhan – 40012358014

Instructor: Narges S. Bathaeian

June of 2024

Main content:

```jsx
import { useState } from "react"
import Card from "./Card"
function MainContent() {
  const data = [
    {id: 1, role: "مربی", edu: "مهندسی کامپیوتر",
pic:"https://intl.basu.ac.ir/web/eng/ce-
profs?p_p_id=ir_sain_university_people_UniversityFacultyListPortlet&p_p_lifecy
cle=2&p_p_state=normal&p_p_mode=view&p_p_resource_id=%2Funiversity_people%2Fpe
rson_image&p_p_cacheability=cacheLevelPage&_ir_sain_university_people_Universi
tyFacultyListPortlet_universityPersonImageId=1031389", name: "نرگس السادات
بطحائیان"},
    {id: 2, role: "مربی", edu: "مهندسی کامپیوتر",
pic:"https://intl.basu.ac.ir/web/eng/ce-
profs?p_p_id=ir_sain_university_people_UniversityFacultyListPortlet&p_p_lifecy
cle=2&p_p_state=normal&p_p_mode=view&p_p_resource_id=%2Funiversity_people%2Fpe
rson_image&p_p_cacheability=cacheLevelPage&_ir_sain_university_people_Universi
tyFacultyListPortlet_universityPersonImageId=1031389", name: "نرگس السادات
بطحائیان"},
    {id: 3, role: "مربی", edu: "مهندسی کامپیوتر",
pic:"https://intl.basu.ac.ir/web/eng/ce-
profs?p_p_id=ir_sain_university_people_UniversityFacultyListPortlet&p_p_lifecy
cle=2&p_p_state=normal&p_p_mode=view&p_p_resource_id=%2Funiversity_people%2Fpe
rson_image&p_p_cacheability=cacheLevelPage&_ir_sain_university_people_Universi
tyFacultyListPortlet_universityPersonImageId=1031389", name: "نرگس السادات
بطحائیان"},
    {id: 4, role: "مربی", edu: "مهندسی کامپیوتر",
pic:"https://intl.basu.ac.ir/web/eng/ce-
profs?p_p_id=ir_sain_university_people_UniversityFacultyListPortlet&p_p_lifecy
cle=2&p_p_state=normal&p_p_mode=view&p_p_resource_id=%2Funiversity_people%2Fpe
rson_image&p_p_cacheability=cacheLevelPage&_ir_sain_university_people_Universi
tyFacultyListPortlet_universityPersonImageId=1031389", name: "نرگس السادات
بطحائیان"},
    {id: 5, role: "مربی", edu: "مهندسی کامپیوتر",
pic:"https://intl.basu.ac.ir/web/eng/ce-
profs?p_p_id=ir_sain_university_people_UniversityFacultyListPortlet&p_p_lifecy
cle=2&p_p_state=normal&p_p_mode=view&p_p_resource_id=%2Funiversity_people%2Fpe
rson_image&p_p_cacheability=cacheLevelPage&_ir_sain_university_people_Universi
tyFacultyListPortlet_universityPersonImageId=1031389", name: "نرگس السادات
بطحائیان"},
    {id: 6, role: "مربی", edu: "مهندسی کامپیوتر",
pic:"https://intl.basu.ac.ir/web/eng/ce-
profs?p_p_id=ir_sain_university_people_UniversityFacultyListPortlet&p_p_lifecy
cle=2&p_p_state=normal&p_p_mode=view&p_p_resource_id=%2Funiversity_people%2Fpe
```

```jsx
rson_image&p_p_cacheability=cacheLevelPage&_ir_sain_university_people_Universi
tyFacultyListPortlet_universityPersonImageId=1031389", name: " نرگس السادات
بطحائیان"},
    {id: 7, role: "مربی", edu: "مهندسی کامپیوتر",
pic:"https://intl.basu.ac.ir/web/eng/ce-
profs?p_p_id=ir_sain_university_people_UniversityFacultyListPortlet&p_p_lifecy
cle=2&p_p_state=normal&p_p_mode=view&p_p_resource_id=%2Funiversity_people%2Fpe
rson_image&p_p_cacheability=cacheLevelPage&_ir_sain_university_people_Universi
tyFacultyListPortlet_universityPersonImageId=1031389", name: " نرگس السادات
بطحائیان"},
  ]

  const [inputValue, setInputValue] = useState("")
console.log(inputValue);

  const handleChangeInput = (e: React.ChangeEvent<HTMLInputElement>) =>
{setInputValue(e.target.value)}

  return (
    <div>
      <div className="flex gap-20 mt-4 md:flex-nowrap flex-wrap">
        <div className="pr-8">
          <h3 className="text-[24px] font-bold>گروه آموزشی مهندسی کامپیوتر
          </h3>
          <ul className="list-disc pr-8 pt-1">
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5] text-sm">درباره گروه</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">مدیر گروه</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">اعضای هیأت علمی</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">کارشناسان گروه</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">زمینه‌های تحقیقاتی گروه</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">اخبار و اطلاعیه ها</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">افتخارات و جوایز</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">ارتباطات ملی و بین‌المللی</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">انجمن‌های علمی دانشجویی</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">دانشجویان دکتری</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]  text-sm">محققان پسادکتری</li>
```

```jsx
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]   text-sm">آزمایشگاه ها و کارگاه ها</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]   text-sm">سمینارها و پایان نامه ها</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]   text-sm">سمینارها و پایان نامه ها
            سرفصل دروس</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]   text-sm">دروس ارائه شده</li>
            <li className="hover:cursor-pointer transition-all duration-300
hover:text-[#007ce5]   text-sm">تقویم آموزشی</li>
          </ul>
        </div>


        <div className=" pr-8">
        <h3 className="text-[24px] font-bold">اعضای هیات‌علمی</h3>
        </h3>
<div className="flex items-center gap-4">
        <input value={inputValue} onChange={handleChangeInput} type="text"
placeholder="جستجو بر اساس نام یا نام خانوادگی"  className="bg-white outline-none shadow-
md w-72 px-4 py-2 rounded placeholder:text-xs" />
        <button className="flex items-start justify-center gap-1 p-2 bg-
[#8b9bb6] hover:bg-[#59769b] text-white text-xs rounded">
                                <svg xmlns="http://www.w3.org/2000/svg"
fill="none" viewBox="0 0 24 24" strokeWidth={1.5} stroke="currentColor"
className="size-5">
                                <path strokeLinecap="round"
strokeLinejoin="round" d="m21 21-5.197-5.197m0 0A7.5 7.5 0 1 0 5.196 5.196a7.5
7.5 0 0 0 10.607 10.607Z" />
                                </svg>
                                <span>جستجو</span>

                        </button>

                        <p className="font-bold text-xs">مجموع نتایج: 7</p>
</div>

<div className="grid grid-cols-3 max-[1240px]:grid-cols-2 max-[840px]:grid-
cols-1 gap-x-8 gap-y-12 my-8 ml-4">
                {data.map(item => <Card key={item.id} name={item.name}
role={item.role} pic={item.pic} edu={item.edu}/>)}
            </div>


        </div>
      </div>
    </div>
  )
}
```

```
export default MainContent
```

Component Structure:

- `MainContent`: A functional React component that serves as the main content of a webpage.

State Management:

- `useState`: A React hook used to create the `inputValue` state variable, which holds the value entered in an input field.
- `inputValue`: The state variable that stores the current value of the input field.
- `setInputValue`: The function provided by `useState` to update the value of `inputValue`.

Data Handling:

- `data`: An array of objects where each object represents a member of the educational staff, containing their id, role, educational background, profile picture URL, and name.

Event Handling:

- `handleChangeInput`: A function that is triggered on input field changes. It takes an event object as an argument and updates `inputValue` with the current value of the input field.

UI Rendering:

- The JSX returned by the component includes:
    - A heading for the computer engineering department.
    - A list of navigational links related to the department.
    - The input field with an `onChange` event listener attached to it, which calls `handleChangeInput` whenever the input value changes.

header:

```jsx
function Header() {
  return (
    <div className="bg-white p-8 relative shadow-2xl">
        <div className="absolute bg-white h-[9.188em] left-1/2 -translate-x-
1/2 top-0 pb-4">
        </div>
        <div className="flex items-center justify-between gap-4 w-full
[&>p]:hover:cursor-pointer border-b border-gray-300 flex-wrap">
            <p className="flex items-center gap-1 border-b-2 border-b-
transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3] group">
                <span className="text-black text-xs font-semibold group-
hover:text-[#0a21b3]">دانشگاه</span>
                <svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0
0 24 24" strokeWidth={1.5} stroke="currentColor" className="size-3">
                    <path strokeLinecap="round" strokeLinejoin="round"
d="m19.5 8.25-7.5 7.5-7.5-7.5" />
                </svg>
            </p>

            <p className="flex items-center gap-1 border-b-2 border-b-
transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3] group">
                <span className="text-black text-xs font-semibold group-
hover:text-[#0a21b3]">آموزش</span>
                <svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0
0 24 24" strokeWidth={1.5} stroke="currentColor" className="size-3">
                    <path strokeLinecap="round" strokeLinejoin="round"
d="m19.5 8.25-7.5 7.5-7.5-7.5" />
                </svg>
            </p>

            <p className="flex items-center gap-1 border-b-2 border-b-
transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3] group">
                <span className="text-black text-xs font-semibold group-
hover:text-[#0a21b3]">پژوهش</span>
                <svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0
0 24 24" strokeWidth={1.5} stroke="currentColor" className="size-3">
                    <path strokeLinecap="round" strokeLinejoin="round"
d="m19.5 8.25-7.5 7.5-7.5-7.5" />
                </svg>
            </p>
```

```jsx
            <p className="flex items-center gap-1 border-b-2 border-b-
transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3] group">
                <span className="text-black text-xs font-semibold group-
hover:text-[#0a21b3]">دانشکده ها</span>
                <svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0
0 24 24" strokeWidth={1.5} stroke="currentColor" className="size-3">
                    <path strokeLinecap="round" strokeLinejoin="round"
d="m19.5 8.25-7.5 7.5-7.5-7.5" />
                </svg>
            </p>

            <p className="flex items-center gap-1 border-b-2 border-b-
transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3] group">
                <span className="text-black text-xs font-semibold group-
hover:text-[#0a21b3]">رفاهی</span>
                <svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0
0 24 24" strokeWidth={1.5} stroke="currentColor" className="size-3">
                    <path strokeLinecap="round" strokeLinejoin="round"
d="m19.5 8.25-7.5 7.5-7.5-7.5" />
                </svg>
            </p>

            <p className="flex items-center gap-1 border-b-2 border-b-
transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3] group">
                <span className="text-black text-xs font-semibold group-
hover:text-[#0a21b3]">فوق برنامه</span>
                <svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0
0 24 24" strokeWidth={1.5} stroke="currentColor" className="size-3">
                    <path strokeLinecap="round" strokeLinejoin="round"
d="m19.5 8.25-7.5 7.5-7.5-7.5" />
                </svg>
            </p>

            <p className="text-black text-xs font-semibold border-b-2 border-
b-transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3]">پایگاه خبری بسنا</p>

            <p className="text-black text-xs font-semibold border-b-2 border-
b-transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3]">پیشخوان</p>

            <p className="text-black text-xs font-semibold border-b-2 border-
b-transparent hover:border-b-[#0a21b3] pb-3 transition-all duration-200
hover:text-[#0a21b3]">اسپاد</p>
```

```
            <p className="flex items-center gap-1 border-b-2 border-b-
transparent hover:border-b-[#0a21b3] pb-1 transition-all duration-200
hover:text-[#0a21b3] group">
                <span className="text-black text-xs font-semibold group-
hover:text-[#0a21b3]">
سامانه های الکترونیک</span>
                <svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0
0 24 24" strokeWidth={1.5} stroke="currentColor" className="size-6">
                    <path strokeLinecap="round" strokeLinejoin="round"
d="M3.75 6A2.25 2.25 0 0 1 6 3.75h2.25A2.25 2.25 0 0 1 10.5 6v2.25a2.25 2.25 0
0 1-2.25 2.25H6a2.25 2.25 0 0 1-2.25-2.25V6ZM3.75 15.75A2.25 2.25 0 0 1 6
13.5h2.25a2.25 2.25 0 0 1 2.25 2.25V18a2.25 2.25 0 0 1-2.25 2.25H6A2.25 2.25 0
0 1 3.75 18v-2.25ZM13.5 6a2.25 2.25 0 0 1 2.25-2.25H18A2.25 2.25 0 0 1 20.25
6v2.25A2.25 2.25 0 0 1 18 10.5h-2.25a2.25 2.25 0 0 1-2.25-2.25V6ZM13.5
15.75a2.25 2.25 0 0 1 2.25-2.25H18a2.25 2.25 0 0 1 2.25 2.25V18A2.25 2.25 0 0
1 18 20.25h-2.25A2.25 2.25 0 0 1 13.5 18v-2.25Z" />
                </svg>

            </p>
        </div>

        <div className="flex items-center justify-between flex-wrap mt-2 gap-
4">

            <p className="text-[#62657e] text-xs hover:cursor-pointer
hover:text-[#4150c5] mr-4">اعضای هیأت علمی</p>
            <p  className="text-[#62657e] text-xs hover:cursor-pointer
hover:text-[#4150c5]">کارکنان
            </p>
            <p  className="text-[#62657e] text-xs hover:cursor-pointer
hover:text-[#4150c5]">دانشجویان</p>
            <p  className="text-[#62657e] text-xs hover:cursor-pointer
hover:text-[#4150c5]">فارغ التحصیلان
            </p>
            <p  className="text-[#62657e] text-xs hover:cursor-pointer
hover:text-[#4150c5]">ارتباط با ما</p>
            <p  className="text-[#62657e] text-xs hover:cursor-pointer
hover:text-[#4150c5]">
روابط بین الملل</p>
            <p  className="text-[#62657e] text-xs hover:cursor-pointer
hover:text-[#4150c5]">وب سایت قدیم</p>

            <div className="flex items-center gap-2 hover:cursor-pointer mr-
8">
            <svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0 0
24 24" strokeWidth={1.5}
            stroke="currentColor" className="size-6 text-[#62657e] ">
  <path strokeLinecap="round" strokeLinejoin="round" d="m21 21-5.197-5.197m0
0A7.5 7.5 0 1 0 5.196 5.196a7.5 7.5 0 0 0 10.607 10.607Z" />
```

```
</svg>

<div className="flex gap-1 ">
<span className="text-[#969aba] text-xs">EN</span>
<svg xmlns="http://www.w3.org/2000/svg" fill="none" viewBox="0 0 24 24"
strokeWidth={1.5} stroke="currentColor" className="size-6 text-[#969aba]">
  <path strokeLinecap="round" strokeLinejoin="round" d="M12 21a9.004 9.004 0 0
0 8.716-6.747M12 21a9.004 9.004 0 0 1-8.716-6.747M12 21c2.485 0 4.5-4.03 4.5-
9S14.485 3 12 3m0 18c-2.485 0-4.5-4.03-4.5-9S9.515 3 12 3m0 0a8.997 8.997 0 0
1 7.843 4.582M12 3a8.997 8.997 0 0 0-7.843 4.582m15.686 0A11.953 11.953 0 0 1
12 10.5c-2.998 0-5.74-1.1-7.843-2.918m15.686 0A8.959 8.959 0 0 1 21 12c0 .778-
.099 1.533-.284 2.253m0 0A17.919 17.919 0 0 1 12 16.5c-3.162 0-6.133-.815-
8.716-2.247m0 0A9.015 9.015 0 0 1 3 12c0-1.605.42-3.113 1.157-4.418" />
</svg>

</div>

            </div>
        </div>
    </div>
  )
}

export default Header
```

Component Overview: The `Header` component is designed to serve as the top navigation section of a web application, specifically tailored for an academic setting. It employs modern web development practices using React and Tailwind CSS to create a responsive and interactive user interface.

Structure and Styling:

- The component is encapsulated within a `div` with a white background, padding, and a shadow effect to create depth and focus on the header.
- An absolutely positioned `div` element is used to create a visual anchor at the top of the header, likely serving as a placeholder or decorative feature.

Navigation Elements:

- The navigation links are structured using paragraph elements, each containing text and an SVG icon. These elements are styled with flexbox properties to align items centrally and distribute space evenly.
- Tailwind CSS classes are utilized to add responsive design features such as wrapping elements when necessary and adding hover effects.

Interactivity:

- The navigation links change appearance on hover, indicating clickable areas. The bottom border and text color transition to a blue shade (#0a21b3), enhancing user experience by providing visual feedback.

Content:

- The text within each navigation link is in Persian, representing various sections of an educational institution's website, such as "University," "Education," "Research," "Faculties," "Welfare," "Extracurricular Activities," and "BASNA News Base."

Purpose:

- The primary purpose of this component is to facilitate easy navigation across different sections of the website while maintaining a clean and modern aesthetic. The use of Tailwind CSS for styling allows for rapid development and easy maintenance.

.

footer:

```jsx
import mapImage from '../assets/image.png';

function Footer() {
  return (
    <div className="flex pt-11 p-[14px] w-full bg-[#05254b] justify-between
flex-wrap">
        <ul className="my-3 px-3 text-white space-y-4 list-disc [&>li]:mr-6
[&>li]:text-xs [&>li]:hover:cursor-pointer">
            <h3 className="font-black text-[1.375rem] text-white mb-5">پیوند
ها</h3>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">دفتر مقام معظم رهبری</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">وزارت علوم، تحقیقات و فناوری</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">صندوق حمایت از پژوهشگران و فناوران کشور</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">مرکز مطالعات راهبردی و آموزش وزارت کشور</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">بنیاد نخبگان استان همدان</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">شبکه آزمایشگاه‌های علمی ایران(شاعا)</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">بنیاد خیرین حامی دانشگاه بوعلی سینا</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">صندوق رفاه دانشجویان</li>
        </ul>

        <ul className="my-3 px-3 text-white space-y-4 list-disc [&>li]:mr-6
[&>li]:text-xs">
            <h3 className="font-black text-[1.375rem] text-white mb-5
invisible">asdasd</h3>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">پورتال امام خمینی (ره)</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">سامانه تدارکات الکترونیکی دولت</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">ریاست جمهوری اسلامی ایران</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">معاونت علمی فناوری ریاست جمهوری</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">پارک علم و فناوری همدان</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">درگاه پرداخت درآمدها</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">مرکز آپا دانشگاه بوعلی سینا</li>
```

```jsx
                <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">پورتال صندوق رفاه دانشجویان</li>
        </ul>

        <ul className="my-3 px-3 text-white space-y-4 list-disc [&>li]:mr-6
[&>li]:text-xs">
            <h3 className="font-black text-[1.375rem] text-white mb-5">واحدها و
مراکز</h3>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">D-۸ دانشگاه بین المللی</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">دبیرستان پسرانه دانشگاه بوعلی سینا</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">سامانه پاسخگوئی به شکایات وزارت علوم، تحقیقات و فناوری</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">دانشگاه ها و موسسات آموزش عالی</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">کانون صنفی استادان</li>
            <li className="hover:text-[#04368f] duration-200 transition-all
hover:cursor-pointer">شورای صنفی کارمندان</li>
        </ul>

        <ul className="my-3 px-3 text-white space-y-4 list-disc [&>li]:mr-6
[&>li]:text-xs">
            <h3 className="font-black text-[1.375rem] text-white mb-5">ارتباط با
ما</h3>
            <div className="grid grid-cols-2 auto-cols-auto gap-4">
                <li className='text-xs'>
                    <p>نشانی</p>
                    <p>دانشگاه بوعلی سینا</p>
                </li>

                <li className="w-min text-xs">
                    <p>کدپستی</p>
                    <p>۶۵۱۷۸ـ۳۸۶۹۵</p>
                </li>

                <li className="w-min text-xs">
                    <p>شماره تماس</p>
                    <p>31400000 - 081</p>
                </li>

                <li className="w-min text-xs">
                    <p>پست الکترونیک
                    </p>
                    <p>info[at]basu.ac.ir</p>
                </li>
        </div>
```

```
            <img src={mapImage} alt="map" className='rounded-xl h-auto
hover:cursor-pointer w-[461px]' />
        </ul>

<div className='w-full h-px bg-white ml-4 mr-6 mt-6'></div>
<div className="mt-6 mb-3 text-center w-full text-[10px] text-white">  حقوق تمام
<div/>مادی و معنوی این وبگاه متعلق به دانشگاه بوعلی سینا همدان است.پیاده سازی توسط سپهر افزار ایرانیان
    </div>
  )
}

export default Footer
```

Component Overview: The `Footer` component is a key part of the web application's layout, designed to provide users with quick access to important links and information. It is implemented using React and styled with Tailwind CSS, ensuring a responsive design that adapts to different screen sizes.

Structure and Styling:

- The component is wrapped in a `div` that uses flexbox properties to arrange child elements in a row or column based on the available width, thanks to the `flex-wrap` class.
- The background color is set to a dark blue (`#05254b`), with padding and space between items for a clean layout.

Navigation Elements:

- Four `ul` elements represent different categories of footer links, each with its own heading (`h3`) and list items (`li`).
- The headings are styled prominently, while the list items have smaller text sizes and are styled to change color on hover, indicating interactivity.

Interactivity:

- The hover state for each list item includes a color change to a lighter blue (`#04368f`) and a smooth transition effect, enhancing the user experience by providing visual feedback.

Content:

- The text within the list items is in Persian, linking to various external organizations and internal university departments, such as "Office of the Supreme Leader," "Ministry of Science, Research and Technology," and "Student Welfare Fund."

Purpose:

- The purpose of this component is to offer organized access to external resources and internal sections of the university's website. It serves as both a navigational tool and an informational resource for users.

Pic of run:

Address in git-hub:

https://github.com/sedwna/react_Faculty_members_Engineering_Faculty