Package 'worldbankmodular'

October 18, 2026

Title World Bank Indicators Explorer

Version 0.0.1

Author Dimitrios Zacharatos [aut, cre]

Maintainer Dimitrios Zacharatos <dzacharatos@yahoo.com>

Description A Shiny application, built as a golem package, for exploring World Bank development indicators through interactive country comparison, indicator comparison, population pyramid, ranked bar chart, correlation scatter, and choropleth map views.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

Imports config, dplyr, DT, golem, pkgload, plotly, shiny

Config/roxygen2/version 8.1.0

Contents

country_code 2
mfi 2
mfi_population 3
plot_bar 4
plot_cor 4
plot_country_comp 5
plot_indicator_comp 6
plot_map 7
plot_pyramid 7
render_index_table 8
run_app 9

Index **10**

`country_code` *Country and region reference table*

Description

Reference metadata mapping each country to its region, income group, and other World Bank classification metadata.

Usage

```
country_code
```

Format

A data frame with 265 rows and 31 columns, including `Country Code`, `Short Name`, `Table Name`, `Long Name`, `Region`, and `Income Group`.

Source

World Bank Open Data (https://data.worldbank.org).

Examples

```
head(country_code)
```

`mfi` *World Bank indicator values*

Description

Long-format World Bank development indicator values, one row per country/indicator/year.

Usage

```
mfi
```

Format

A data frame with 7,478,197 rows and 5 columns:

Country Code ISO country code.

Country Name Country name.

Indicator Name World Bank indicator name.

Year Year of observation (factor).

value Indicator value for that country/year.

Source

World Bank Open Data (https://data.worldbank.org).

Examples

```
head(mfi)
```

`mfi_population` *Population by age, sex, and country*

Description

Long-format population counts by five-year age group and sex, used to drive the population pyramid module.

Usage

```
mfi_population
```

Format

A data frame with 458,304 rows and 7 columns:

Country Name Country name.

Indicator Name World Bank indicator name.

Year Year of observation (factor).

value Population count.

age Age group.

unit Unit of measurement.

sex "Male" or "Female".

Source

World Bank Open Data (https://data.worldbank.org).

Examples

```
head(mfi_population)
```

plot_bar *Build an animated ranked bar chart*

Description

Plots one indicator's value per country as a horizontal bar chart, animated over `Year`, with countries ranked and ordered by their value in the most recent year. Only positive, complete-case rows are kept. Returns `NULL` when fewer than two rows remain after filtering (nothing meaningful to plot/rank).

Usage

```
plot_bar(mfi, indicator, font_style)
```

Arguments

`mfi`	Data frame of World Bank indicator values (long format, with `Country Name`, `Indicator Name`, `Year`, `value` columns).
`indicator`	Character. Indicator name to plot.
`font_style`	A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout.

Value

A `plotly` htmlwidget, or `NULL` if there is not enough data to plot.

Examples

```
plot_bar(mfi, indicator = "GDP (current US$)", font_style = font_style)
```

plot_cor *Build an animated correlation bubble scatter plot*

Description

Reshapes `mfi` from long to wide so `indicator1` and `indicator2` become plottable x/y columns, joins in `Region` from `country_code`, and plots a bubble scatter (bubble size = population, color = region), animated over `Year`, with play/pause controls. Rows with missing values or no region are dropped before plotting.

Usage

```
plot_cor(mfi, country_code, indicator1, indicator2, font_style)
```

Arguments

mfi	Data frame of World Bank indicator values (long format, with `Country Name`, `Indicator Name`, `Year`, `value` columns). Must also contain a `"Population, total"` indicator, used for bubble sizing.
country_code	Data frame mapping countries to region, with columns `Country Code`, `Short Name`, `Region`.
indicator1	Character. Indicator name plotted on the x-axis.
indicator2	Character. Indicator name plotted on the y-axis.
font_style	A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout.

Value

A `plotly` htmlwidget.

Examples

```
plot_cor(
  mfi,
  country_code,
  indicator1 = "Mortality rate, adult, male (per 1,000 male adults)",
  indicator2 = "Mortality rate, infant (per 1,000 live births)",
  font_style = font_style
)
```

---

plot_country_comp *Build a country comparison line chart*

Description

Plots one indicator's value over time as one line per selected country. Rows with missing values for the given filters are dropped before plotting.

Usage

```
plot_country_comp(mfi, countries, indicator, font_style)
```

Arguments

mfi	Data frame of World Bank indicator values (long format, with `Country Name`, `Indicator Name`, `Year`, `value` columns).
countries	Character vector of country names to plot.
indicator	Character. Indicator name to plot.
font_style	A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout.

Value

A `plotly` htmlwidget.

Examples

```
plot_country_comp(
  mfi,
  countries = c("Greece", "Bulgaria"),
  indicator = "Population, total",
  font_style = font_style
)
```

`plot_indicator_comp` *Build an indicator comparison line chart*

Description

Plots several indicators' values over time, for a single country, as one line per indicator. Rows with missing values for the given filters are dropped before plotting.

Usage

```
plot_indicator_comp(mfi, country, indicators, font_style)
```

Arguments

`mfi`	Data frame of World Bank indicator values (long format, with `Country Name`, `Indicator Name`, `Year`, `value` columns).
`country`	Character. Country name to plot.
`indicators`	Character vector of indicator names to plot.
`font_style`	A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout.

Value

A `plotly` htmlwidget.

Examples

```
plot_indicator_comp(
  mfi,
  country = "Greece",
  indicators = c("Population, female", "Population, male"),
  font_style = font_style
)
```

plot_map *Build an animated choropleth map*

Description

Plots one indicator's value per country as a world choropleth, animated over `Year`. Rows with missing values are dropped before plotting.

Usage

```
plot_map(mfi, indicator, font_style)
```

Arguments

`mfi`	Data frame of World Bank indicator values (long format, with `Country Name`, `Country Code`, `Indicator Name`, `Year`, `value` columns).
`indicator`	Character. Indicator name to plot.
`font_style`	A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout.

Value

A `plotly` htmlwidget.

Examples

```
plot_map(mfi, indicator = "Population, total", font_style = font_style)
```

plot_pyramid *Build an animated population pyramid*

Description

Plots male (negative, left) and female (positive, right) population counts by age group as horizontal bars, animated over `Year`. Male values are negated internally so the two sexes render back-to-back, while `display_value` keeps the original (positive) counts for hover/axis text.

Usage

```
plot_pyramid(mfi_population, country, font_style)
```

Arguments

mfi_population	Data frame of population-by-age/sex values (long format, with Country Name, sex, age, Year, value columns).
country	Character. Country name to plot.
font_style	A plotly font list (e.g. list(size = 20, color = "gray25")) applied to the chart's layout.

Value

A plotly htmlwidget.

Examples

```
plot_pyramid(mfi_population, country = "Greece", font_style = font_style)
```

---

render_index_table *Build the indicator index DataTable*

Description

Builds a single-column, non-paginated DT::datatable listing every distinct indicator name present in mfi.

Usage

```
render_index_table(mfi)
```

Arguments

mfi	Data frame of World Bank indicator values, with an Indicator Name column.

Value

A DT::datatable htmlwidget.

Examples

```
render_index_table(mfi)
```

run_app *Run the Shiny Application*

Description

Launches the World Bank indicators explorer app.

Usage

```
run_app(
  onStart = NULL,
  options = list(),
  enableBookmarking = NULL,
  uiPattern = "/",
  ...
)
```

Arguments

onStart	See shiny::shinyApp().
options	See shiny::shinyApp().
enableBookmarking	See shiny::shinyApp().
uiPattern	See shiny::shinyApp().
...	Arguments passed to golem::with_golem_options().

Examples

```
## Not run:
run_app()

# override any shiny::shinyApp() option, e.g. to pick a fixed port:
run_app(options = list(port = 8080))

## End(Not run)
```

Index

∗ **datasets**
country_code, 2
mfi, 2
mfi_population, 3

country_code, 2

golem::with_golem_options(), *9*

mfi, 2
mfi_population, 3

plot_bar, 4
plot_cor, 4
plot_country_comp, 5
plot_indicator_comp, 6
plot_map, 7
plot_pyramid, 7

render_index_table, 8
run_app, 9

shiny::shinyApp(), *9*