# Package 'golemworldbank'

October 25, 2026

**Title** World Bank Indicators Explorer

**Version** 0.0.1

**Author** Dimitrios Zacharatos [aut, cre]

**Maintainer** Dimitrios Zacharatos <dzacharatos@yahoo.com>

**Description** A Shiny application, built as a golem package, for exploring World Bank development indicators through interactive country comparison, indicator comparison, population pyramid, ranked bar chart, correlation scatter, and choropleth map views.

**License** GPL-3

**URL** https://sedzinfo.github.io/golemworldbank/, https://github.com/sedzinfo/golemworldbank

**BugReports** https://github.com/sedzinfo/golemworldbank/issues

**Encoding** UTF-8

**LazyData** true

**LazyDataCompression** xz

**Roxygen** list(markdown = TRUE)

**Imports** config,
dplyr,
DT,
golem,
plotly,
shiny,
stats,
utils

**Config/roxygen2/version** 8.1.1

## Contents

country_code . . . . . 2
mfi . . . . . 3
mfi_population . . . . . 3

plot_bar . . . . . 4
plot_cor . . . . . 5
plot_country_comp . . . . . 6
plot_indicator_comp . . . . . 6
plot_map . . . . . 7
plot_pyramid . . . . . 8
render_index_table . . . . . 8
run_app . . . . . 9

**Index** **10**

---

`country_code` *Country and region reference table*

---

## Description

Reference metadata mapping each country to its region, income group, and other World Bank classification metadata.

## Usage

```
country_code
```

## Format

A data frame with 265 rows and 31 columns, including `Country Code`, `Short Name`, `Table Name`, `Long Name`, `Region`, and `Income Group`.

## Source

World Bank Open Data (https://data.worldbank.org).

## Examples

```
head(country_code)
```

## mfi *World Bank indicator values*

### Description

Long-format World Bank development indicator values, one row per country/indicator/year.

### Usage

```
mfi
```

### Format

A data frame with 7,478,197 rows and 5 columns:

**Country Code** ISO country code.

**Country Name** Country name.

**Indicator Name** World Bank indicator name.

**Year** Year of observation (factor).

**value** Indicator value for that country/year.

### Source

World Bank Open Data (https://data.worldbank.org).

### Examples

```
head(mfi)
```

## mfi_population *Population by age, sex, and country*

### Description

Long-format population counts by five-year age group and sex, used to drive the population pyramid module.

### Usage

```
mfi_population
```

## Format

A data frame with 458,304 rows and 7 columns:

**Country Name** Country name.

**Indicator Name** World Bank indicator name.

**Year** Year of observation (factor).

**value** Population count.

**age** Age group.

**unit** Unit of measurement.

**sex** "Male" or "Female".

## Source

World Bank Open Data (https://data.worldbank.org).

## Examples

```
head(mfi_population)
```

---

# plot_bar *Build an animated ranked bar chart*

---

## Description

Plots one indicator's value per country as a horizontal bar chart, animated over `Year`, with countries ranked and ordered by their value in the most recent year. Only positive, complete-case rows are kept. Returns `NULL` when fewer than two rows remain after filtering (nothing meaningful to plot/rank).

## Usage

```
plot_bar(mfi, indicator, font_style)
```

## Arguments

| | |
|---|---|
| `mfi` | Data frame of World Bank indicator values (long format, with `Country Name`, `Indicator Name`, `Year`, `value` columns). |
| `indicator` | Character. Indicator name to plot. |
| `font_style` | A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout. |

## Value

A `plotly` htmlwidget, or `NULL` if there is not enough data to plot.

## Examples

```
plot_bar(mfi, indicator = "GDP (current US$)", font_style = font_style)
```

---

`plot_cor` *Build an animated correlation bubble scatter plot*

---

## Description

Reshapes `mfi` from long to wide so `indicator1` and `indicator2` become plottable x/y columns, joins in `Region` from `country_code`, and plots a bubble scatter (bubble size = population, color = region), animated over `Year`, with play/pause controls. Rows with missing values or no region are dropped before plotting.

## Usage

```
plot_cor(mfi, country_code, indicator1, indicator2, font_style)
```

## Arguments

| | |
|---|---|
| `mfi` | Data frame of World Bank indicator values (long format, with `Country Name`, `Indicator Name`, `Year`, `value` columns). Must also contain a `"Population, total"` indicator, used for bubble sizing. |
| `country_code` | Data frame mapping countries to region, with columns `Country Code`, `Short Name`, `Region`. |
| `indicator1` | Character. Indicator name plotted on the x-axis. |
| `indicator2` | Character. Indicator name plotted on the y-axis. |
| `font_style` | A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout. |

## Value

A `plotly` htmlwidget.

## Examples

```
plot_cor(
  mfi,
  country_code,
  indicator1 = "Mortality rate, adult, male (per 1,000 male adults)",
  indicator2 = "Mortality rate, infant (per 1,000 live births)",
  font_style = font_style
)
```

## plot_country_comp *Build a country comparison line chart*

### Description

Plots one indicator's value over time as one line per selected country. Rows with missing values for the given filters are dropped before plotting.

### Usage

```
plot_country_comp(mfi, countries, indicator, font_style)
```

### Arguments

| | |
|---|---|
| mfi | Data frame of World Bank indicator values (long format, with `Country Name`, `Indicator Name`, `Year`, `value` columns). |
| countries | Character vector of country names to plot. |
| indicator | Character. Indicator name to plot. |
| font_style | A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout. |

### Value

A `plotly` htmlwidget.

### Examples

```
plot_country_comp(
  mfi,
  countries = c("Greece", "Bulgaria"),
  indicator = "Population, total",
  font_style = font_style
)
```

## plot_indicator_comp *Build an indicator comparison line chart*

### Description

Plots several indicators' values over time, for a single country, as one line per indicator. Rows with missing values for the given filters are dropped before plotting.

### Usage

```
plot_indicator_comp(mfi, country, indicators, font_style)
```

### Arguments

| | |
|---|---|
| mfi | Data frame of World Bank indicator values (long format, with `Country Name`, `Indicator Name`, `Year`, `value` columns). |
| country | Character. Country name to plot. |
| indicators | Character vector of indicator names to plot. |
| font_style | A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout. |

### Value

A `plotly` htmlwidget.

### Examples

```
plot_indicator_comp(
  mfi,
  country = "Greece",
  indicators = c("Population, female", "Population, male"),
  font_style = font_style
)
```

---

## plot_map *Build an animated choropleth map*

---

### Description

Plots one indicator's value per country as a world choropleth, animated over `Year`. Rows with missing values are dropped before plotting.

### Usage

```
plot_map(mfi, indicator, font_style)
```

### Arguments

| | |
|---|---|
| mfi | Data frame of World Bank indicator values (long format, with `Country Name`, `Country Code`, `Indicator Name`, `Year`, `value` columns). |
| indicator | Character. Indicator name to plot. |
| font_style | A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout. |

### Value

A `plotly` htmlwidget.

### Examples

```
plot_map(mfi, indicator = "Population, total", font_style = font_style)
```

## plot_pyramid *Build an animated population pyramid*

### Description

Plots male (negative, left) and female (positive, right) population counts by age group as horizontal bars, animated over `Year`. Male values are negated internally so the two sexes render back-to-back, while `display_value` keeps the original (positive) counts for hover/axis text.

### Usage

```
plot_pyramid(mfi_population, country, font_style)
```

### Arguments

| | |
|---|---|
| `mfi_population` | Data frame of population-by-age/sex values (long format, with `Country Name`, `sex`, `age`, `Year`, `value` columns). |
| `country` | Character. Country name to plot. |
| `font_style` | A `plotly` font list (e.g. `list(size = 20, color = "gray25")`) applied to the chart's layout. |

### Value

A `plotly` htmlwidget.

### Examples

```
plot_pyramid(mfi_population, country = "Greece", font_style = font_style)
```

## render_index_table *Build the indicator index DataTable*

### Description

Builds a single-column, non-paginated `DT::datatable` listing every distinct indicator name present in `mfi`.

### Usage

```
render_index_table(mfi)
```

### Arguments

| | |
|---|---|
| `mfi` | Data frame of World Bank indicator values, with an `Indicator Name` column. |

## Value

A `DT::datatable` htmlwidget.

## Examples

```
render_index_table(mfi)
```

---

`run_app` *Run the Shiny Application*

---

## Description

Launches the World Bank indicators explorer app.

## Usage

```
run_app(
  onStart = NULL,
  options = list(),
  enableBookmarking = NULL,
  uiPattern = "/",
  ...
)
```

## Arguments

| | |
|---|---|
| `onStart` | See `shiny::shinyApp()`. |
| `options` | See `shiny::shinyApp()`. |
| `enableBookmarking` | See `shiny::shinyApp()`. |
| `uiPattern` | See `shiny::shinyApp()`. |
| `...` | Arguments passed to `golem::with_golem_options()`. |

## Examples

```
## Not run:
run_app()

# override any shiny::shinyApp() option, e.g. to pick a fixed port:
run_app(options = list(port = 8080))

## End(Not run)
```

# Index

∗ **datasets**
country_code, 2
mfi, 3
mfi_population, 3

country_code, 2

golem::with_golem_options(), *9*

mfi, 3
mfi_population, 3

plot_bar, 4
plot_cor, 5
plot_country_comp, 6
plot_indicator_comp, 6
plot_map, 7
plot_pyramid, 8

render_index_table, 8
run_app, 9

shiny::shinyApp(), *9*