

Package ‘rwf’

May 23, 2026

Title Statistical reporting and visualization for common methods

Version 0.1.0

Author Dimitrios Zacharatos [aut, cre]

Maintainer Dimitrios Zacharatos <dzacharatos@yahoo.com>

Description Statistical reporting and visualization for common methodology used in psychology. Functions to minimize code and automate procedures using common R packages.

Depends R (>= 3.5), ggplot2

Imports MASS, future, future.apply, gtools, irr, openxlsx, pROC, plyr, psych, reshape2, xgboost, DescTools, Rmisc, ggfortify, ggrepel, car, sjstats, ggpubr, gridExtra, scales, pwr, mirt, nlme, NLP, openNLP, tm, spelling, lavaan, ggExtra, QuantPsyc, purrr, emmeans, ez, htmlwidgets, mixlm, rstatix, rstudioapi, igraph, stopwords, gtable, stringr

Suggests e1071, forecast, lsr, rcompanion

License GPL (>= 2)

Encoding UTF-8

LazyData true

Config/roxygen2/version 8.0.0

RoxygenNote 7.3.3

Contents

alpha_diagnostics	6
call_to_string	6
cdf	7
cdff	9
cfa_icc_index	10
change_data_type	11
clear_stopwords	11
clear_text	12
comparison_combinations	13
compute_ability	13
compute_adjustment	14
compute_aggregate	15

compute_aov_es	15
compute_confidence_interval	16
compute_crosstable	17
compute_descriptives	17
compute_dissatenuation	18
compute_dummy_comparisons	18
compute_frequencies	19
compute_icc_thurstonian	20
compute_info_1pl	20
compute_info_2pl	21
compute_info_3pl	22
compute_kruskal_wallis_test	22
compute_kurtosis	23
compute_map	24
compute_moving_average	24
compute_one_way_test	25
compute_posthoc	25
compute_power_r	26
compute_power_r_matrix	27
compute_residual_stats	27
compute_scores	28
compute_se_theta	28
compute_skewness	29
compute_standard	29
compute_standard_error	30
compute_tversky_index	31
compute_unidimensional_ability	32
compute_unidimensional_theta	33
compute_y_logistic	34
confusion	35
confusion_matrix_percent	35
convert_excel_unix_timestamp	37
c_bind	37
data_frame_index	38
decompose_datetime	38
deg2rad	39
detach_package	40
df_admission	40
df_automotive_data	41
df_blood_pressure	42
df_co2	42
df_crop_yield	43
df_difficile	44
df_insurance	44
df_ocean	45
df_personality	49
df_responses	51
df_responses_state	55

df_sexual_comp	56
df_titanic	57
display_upper_lower_triangle	58
dotnames	58
drop_levels	59
dummy_arrange	59
duplicate_y_axis	60
environment_options	61
excel_confusion_matrix	61
excel_critical_value	62
excel_generic_format	63
excel_matrix	64
extract_components	66
fixed	66
flatten_list	67
generate_comparisons_matrix	67
generate_correlation_matrix	68
generate_data	68
generate_factor	69
generate_matrix_A	70
generate_matrix_lambda_hat	70
generate_missing	71
generate_multiple_responce_vector	71
generate_string	72
generate_unique_comparisons_index	72
getfwp	73
get_script_directory	73
hinvert_title_grob	74
icc_cfa	74
increase_index	75
install_all_packages	75
install_load	76
key_to_cfa_model	76
k_fold	77
k_sample	78
matrix_triangle	79
mean_sd_alpha	79
mgsb	80
min_max_index	80
model_loadings	81
off_diagonal_index	82
outlier_summary	82
output_compare_model_logistic	83
output_separator	83
padNA	84
plot_acf	85
plot_boxplot	85
plot_cfa	86

plot_cfa_gg	86
plot_confusion	88
plot_corrplot	89
plot_crosstable	89
plot_histogram	90
plot_icc_thurstonian	91
plot_interaction	92
plot_irt_onefactor	93
plot_loadings	94
plot_logistic_model	95
plot_mosaic	96
plot_mtm	96
plot_multiplot	97
plot_normality_diagnostics	98
plot_oneway	99
plot_oneway_diagnostics	100
plot_outlier	101
plot_qq	102
plot_response_frequencies	103
plot_roc	103
plot_scatterplot	104
plot_scee	106
plot_separability	106
plot_trees_xgboost	107
plot_ts	108
proper	109
proportion_accurate	109
questions_by_keys	110
questions_dimensions_dataframe	111
rad2deg	111
rank3_to_triplets	112
rank_df_to_binary	112
rank_to_binary	113
raw_alpha	114
rbind_all	114
recode_scale_dummy	115
remove_nc	116
remove_outliers	117
remove_user_packages	117
replace_na_with_previous	118
report_alpha	118
report_cfa	119
report_choric_serial	120
report_correlation	121
report_dataframe	122
report_efa	123
report_factorial_anova	124
report_hlr	126

report_irt	127
report_lda	128
report_logistic	128
report_manova	130
report_normality_tests	131
report_oneway	132
report_pdf	133
report_regression	134
report_ttests	136
report_wtests	137
report_xgboost	139
response_dimension	140
response_frequency	141
result_confusion_performance	142
round_dataframe	143
shrout	143
simulate_cfa_fit	144
simulate_correlation_from_sample	146
split_str	146
split_str_df	147
stat_word_char	148
string_aes	148
str_count	149
str_pad	150
str_replace	151
str_replace_all	152
str_split_fixed	153
str_squish	154
str_wrap	155
sub_str	156
swap	156
symmetric_matrix	157
tag_pos	157
text_similarity	158
trim_df	159
ts_smoothing	159
wrapper	160
write_txt	161

alpha_diagnostics	<i>Item total correlation and r drop</i>
-------------------	--

Description

Item total correlation and r drop

Usage

```
alpha_diagnostics(df)
```

Arguments

df	dataframe with one dimension
----	------------------------------

Examples

```
set.seed(12345)
df<-data.frame(matrix(.5,ncol=6,nrow=6))
correlation_matrix<-as.matrix(df)
diag(correlation_matrix)<-1
df<-round(generate_correlation_matrix(correlation_matrix,nrows=1000),0)+5
psych::alpha(df)
alpha_diagnostics(df=df)
```

call_to_string	<i>Model call to string</i>
----------------	-----------------------------

Description

Takes a call object and convert it to string

Usage

```
call_to_string(model)
```

Arguments

model	Model object
-------	--------------

Examples

```
df<-generate_correlation_matrix()
model<-lm(df$X1~df$X2)
call_to_string(model)
```

cdf	<i>Check dataframe</i>
-----	------------------------

Description

Produces a column-level diagnostic summary of a dataframe, reporting missing values, data types, range statistics, and optionally unique values and factor levels. Returns a named list with a per-column table and a whole-dataframe summary. Can optionally export results to an .xlsx file.

Usage

```
cdf(
  df,
  name_length = (getOption("width")/3),
  digits = 2,
  nunique = 0,
  parallel = FALSE,
  file = NULL
)
```

Arguments

<code>df</code>	A data.frame to inspect. Accepts any column types: numeric, integer, character, factor, logical, Date, POSIXct.
<code>name_length</code>	Integer. Maximum number of characters displayed for column names and MIN/MAX values in the printed output. Longer strings are truncated. Defaults to <code>getOption("width") / 3</code> .
<code>digits</code>	Integer. Number of decimal places used when rounding MEAN, MEDIAN, and SD for numeric columns. Defaults to 2.
<code>nunique</code>	Integer. If > 0, appends UNiques and LEVELS columns to the output. Columns with more distinct entries than nunique are summarised as "N Uniques" / "N Levels". Set to 0 to skip (faster). Defaults to 0.
<code>parallel</code>	Logical. If TRUE, uses <code>future.apply</code> with a multisession plan across all available cores. Recommended for wide dataframes (> 100 columns) or very large n. Defaults to FALSE.
<code>file</code>	Character or NULL. If a string is provided, exports results to <file>.xlsx with two sheets: variables and summary. Any existing file with the same name is overwritten. Defaults to NULL.

Value

A named list with two elements:

`$summary` A single-row data.frame with whole-dataframe counts: COLUMNS, ROWS, TOTAL, EMPTY, null, NAN, na, INF, FIN, FACTOR.

`$check` A per-column data.frame with the following fields:

cdff	<i>Check dataframe (optimised)</i>
------	------------------------------------

Description

A faster equivalent of [cdf](#). Produces an identical column-level diagnostic summary but avoids repeated passes over each column, eliminates row-by-row `rbind` calls, and removes the `gtools` and `plyr` dependencies. Recommended for large dataframes (> 100k rows or > 50 columns).

Usage

```
cdff(
  df,
  name_length = (getOption("width")/3),
  digits = 2,
  nuniqes = 0,
  parralel = FALSE,
  file = NULL
)
```

Arguments

<code>df</code>	A data.frame to inspect. Accepts any column types: numeric, integer, character, factor, logical, Date, POSIXct.
<code>name_length</code>	Integer. Maximum number of characters displayed for column names and MIN/MAX values in the printed output. Longer strings are truncated. Defaults to <code>getOption("width") / 3</code> .
<code>digits</code>	Integer. Number of decimal places used when rounding MEAN, MEDIAN, and SD for numeric columns. Defaults to 2.
<code>nuniqes</code>	Integer. If > 0, appends UNIQES and LEVELS columns to the output. Columns with more distinct entries than nuniqes are summarised as "N Uniques" / "N Levels". Set to 0 to skip (faster). Defaults to 0.
<code>parralel</code>	Logical. If TRUE, uses <code>future.apply</code> with a multisession plan across all available cores. Recommended for wide dataframes (> 100 columns) or very large n. Defaults to FALSE.
<code>file</code>	Character or NULL. If a string is provided, exports results to <file>.xlsx with two sheets: variables and summary. Any existing file with the same name is overwritten. Defaults to NULL.

Value

Identical structure to [cdf](#): a named list with elements `$summary` and `$check`. See [cdf](#) for full field descriptions.

Note

MIN and MAX for non-double columns use base `min()` / `max()` on character representations. Unlike `cdf`, mixed alphanumeric ordering (e.g. "V1" < "V10" < "V2") is *not* guaranteed — lexicographic order is used instead.

See Also

`cdf` for the original with natural sort ordering, [str](#), [summary](#), [skim](#)

Examples

```
cdff(df=mtcars,parralel=TRUE)
cdff(df=change_data_type(mtcars,"factor"),nuniques=3)
cdff(df=data.frame(t(mtcars)),file="mtcars",nuniques=10)
cdff(df=mtcars)
cdff(df=generate_missing(mtcars))
cdff(df=infert,nuniques=10)
cdff(df=infert)
df<-data.frame(infert,
               date=seq(as.Date("2010-1-1"),
                        as.Date("2020-1-1"),
                        length.out=nrow(infert)))
cdff(df=df)
```

cfa_icc_index

index of items to convert from lavaan to thurstonian order for analysis

Description

index of items to convert from lavaan to thurstonian order for analysis

Usage

```
cfa_icc_index(nitems, nfactors = 3)
```

Arguments

nitems	number of items in the questionnaire
nfactors	number of factors

Examples

```
cfa_icc_index(nitems=18,nfactors=3)
```

change_data_type	<i>dataframe data type transformations</i>
------------------	--

Description

dataframe data type transformations

Usage

```
change_data_type(df, type)
```

Arguments

df	dataframe
type	"character" "numeric" "factor" "factor_character" "character_factor" For "factor_character" if factors are found, are converted to characters For "character_factor" if characters are found, are converted to factors

Examples

```
cdf(df=change_data_type(df=mtcars,"character"))
cdf(df=change_data_type(df=mtcars,"numeric"))
cdf(df=change_data_type(df=mtcars,"factor"))
df<-change_data_type(df=mtcars,"factor")
cdf(df=change_data_type(df=df,"factor_character"))
```

clear_stopwords	<i>Remove stopwords</i>
-----------------	-------------------------

Description

Remove stopwords

Usage

```
clear_stopwords(text, stopwords = stopwords::stopwords("english"))
```

Arguments

text	character vector
stopwords	character words to remove

Examples

```
text1<-"word_one word_two word_three"
text2<-"word_three word_four word_six"
text3<-"All the Lorem Ipsum generators on the Internet tend to repeat predefined
chunks as necessary, making this the first true generator on the Internet."
text4<-"It uses a dictionary of over 200 Latin words, combined with a handful of
model sentence structures, to generate Lorem Ipsum which looks reasonable."
text5<-"The generated Lorem Ipsum is therefore always free from repetition,
injected humour, or non-characteristic words etc."
stopwords<-stopwords::stopwords("english")
text<-c(text1,text2,text3,text4,text5)
clear_stopwords(text,stopwords=stopwords)
```

clear_text

Clear text

Description

Clear text

Usage

```
clear_text(text)
```

Arguments

text character vector

Examples

```
text1<-"word_one word_two word_three"
text2<-"word_three word_four word_six"
text3<-"All the Lorem Ipsum generators on the Internet tend to repeat predefined
chunks as necessary, making this the first true generator on the Internet."
text4<-"It uses a dictionary of over 200 Latin words, combined with a handful of
model sentence structures, to generate Lorem Ipsum which looks reasonable."
text5<-"The generated Lorem Ipsum is therefore always free from repetition,
injected humour, or non-characteristic words etc."
text<-c(text1,text2,text3,text4,text5)
clear_text(text)
```

 comparison_combinations

Produce combinations for comparisons from dataframe names

Description

Produce combinations for comparisons from dataframe names

Usage

```
comparison_combinations(df, all_orders = TRUE)
```

Arguments

df	dataframe
all_orders	if TRUE the order of combination is considered i.e. the combination X1 X2 also appears as X2 X1 if FALSE it is assumed that X1 X2 and X2 X1 are the same and only one of them appears

Examples

```
comparison_combinations(generate_correlation_matrix(n=10)[,1:4])
```

 compute_ability

Compute subject ability for thurstonian models

Description

Computes person ability for binary thurstonian coded items for a single dimension

Usage

```
compute_ability(
  response,
  eta,
  gamma,
  lambda,
  psi,
  plot = FALSE,
  map = compute_map(eta = eta, mean = 0, sd = 1)
)
```

Arguments

response	item responses
eta	eta or ability
gamma	gamma or threshold
lambda	lambda or loading
psi	psi or error
plot	if TRUE plots icc curves using the plot_icc_thurstonian function
map	vector from compute_map

Examples

```

gamma<-c(0.556,-1.253,-1.729,0.618,0.937,0.295,-0.672,-1.127,-0.446,0.632,1.147,0.498)
psi<-c(2.172,1.883,2.055,1.869,2.231,2.100,1.762,1.803,1.565,1.892,1.794,1.686)
lambda<-c(1.082,1.082,-1.297,-1.297,0.802,0.802,1.083,1.083)
gamma<-gamma[response_dimension(c(1:12),3,c(1,2))]
psi<-psi[response_dimension(c(1:12),3,c(1,2))]
eta<-seq(-6,6,by=0.1)
response1<-c(0,0,0,0,0,0,0,0,0)
response2<-c(1,1,1,1,1,1,1,1,1)
response3<-c(1,0,1,0,1,0,1,0,1)
response4<-c(0,1,0,1,0,1,0,1,0)
map<-compute_map(eta=eta,mean=0,sd=1)
compute_ability(response1,eta,gamma,lambda,psi,map=map,plot=FALSE)
compute_ability(response2,eta,gamma,lambda,psi,map=map,plot=FALSE)
compute_ability(response3,eta,gamma,lambda,psi,map=map,plot=FALSE)
compute_ability(response4,eta,gamma,lambda,psi,map=map,plot=FALSE)

```

compute_adjustment	<i>Compute adjustments</i>
--------------------	----------------------------

Description

Compute adjustments

Usage

```
compute_adjustment(a, ntests)
```

Arguments

a	alpha criterion
ntests	number of tests

Examples

```
compute_adjustment(0.05,100)
```

compute_aggregate	<i>Descriptive statistics</i>
-------------------	-------------------------------

Description

uses plyr

Usage

```
compute_aggregate(df, iv, file = NULL)
```

Arguments

df	dataframe
iv	index of independent variables
file	output filename

Details

returns xlsx

Examples

```
compute_aggregate(df=mtcars,iv=9)
compute_aggregate(df=mtcars,iv=9:10)
compute_aggregate(df=mtcars,iv=9:11)
compute_aggregate(df=mtcars,iv=9:11,file="descriptives")
```

compute_aov_es	<i>Compute eta and omega</i>
----------------	------------------------------

Description

Computes omega using aov object. Based on <http://stats.stackexchange.com/a/126520>

Usage

```
compute_aov_es(model, ss = "I")
```

Arguments

model	object aov
ss	Character type of sums of squares "I" "II" "III"

Examples

```

form<-formula(uptake~Treatment)
one_way_between<-aov(form,C02)
factorial_between<-aov(uptake~Treatment*Type,C02)
compute_aov_es(model=one_way_between,ss="I")
sjstats::anova_stats(one_way_between,digits=10)
compute_aov_es(model=one_way_between,ss="II")
sjstats::anova_stats(one_way_between,digits=10)
compute_aov_es(model=one_way_between,ss="III")
sjstats::anova_stats(one_way_between,digits=10)
compute_aov_es(model=factorial_between,ss="I")
sjstats::anova_stats(factorial_between,digits=10)
compute_aov_es(model=factorial_between,ss="II")
sjstats::anova_stats(factorial_between,digits=10)
compute_aov_es(model=factorial_between,ss="III")
sjstats::anova_stats(car::Anova(factorial_between,Type=3),digits=10)

```

compute_confidence_interval

Compute confidence interval

Description

Compute confidence interval

Usage

```
compute_confidence_interval(vector)
```

Arguments

vector vector

Examples

```

set.seed(1)
vector<-rnorm(1000)
compute_confidence_interval(vector)

```

compute_crosstable	<i>Compute crosstables</i>
--------------------	----------------------------

Description

Compute crosstables

Usage

```
compute_crosstable(df, factor_index = NULL, combinations = NULL)
```

Arguments

df	dataframe
factor_index	index of factors
combinations	index of comparisons

Examples

```
combinations<-data.frame(index1=c("vs","am","gear"),index2=c("cyl","cyl","cyl"))
compute_crosstable(df=mtcars,combinations=combinations)
combinations<-data.frame(index1=c("vs","am"),index2=c("cyl","cyl"))
compute_crosstable(df=mtcars,combinations=combinations)
compute_crosstable(df=mtcars,factor_index=8:10)
```

compute_descriptives	<i>Descriptive statistics</i>
----------------------	-------------------------------

Description

uses psych

Usage

```
compute_descriptives(df, dv, iv = NULL, file = NULL)
```

Arguments

df	dataframe
dv	index of dependent variables
iv	index of independent variables
file	output filename

Details

returns xlsx

Examples

```
compute_descriptives(df=mtcars,dv=1:5)
compute_descriptives(df=mtcars,dv=1:2,iv=9:10)
compute_descriptives(df=mtcars,dv=1:2,file="descriptives_no_factor")
compute_descriptives(df=mtcars,dv=1:2,iv=9:10,file="descriptives_factor")
```

```
compute_dissatenuation
```

Compute dissatenuation

Description

Compute dissatenuation

Usage

```
compute_dissatenuation(variable1, error1, variable2, error2)
```

Arguments

variable1	vector
error1	vector error measurement for variable1
variable2	vector
error2	vector error measurement for variable2

Examples

```
set.seed(1)
compute_dissatenuation(rnorm(10),rnorm(10),rnorm(10),rnorm(10))
```

```
compute_dummy_comparisons
```

Compute number of dummy comparisons

Description

Compute number of dummy comparisons

Usage

```
compute_dummy_comparisons(items)
```

Arguments

items	number of items per block
-------	---------------------------

Examples

```
compute_dummy_comparisons(1)
compute_dummy_comparisons(2)
compute_dummy_comparisons(3)
compute_dummy_comparisons(4)
compute_dummy_comparisons(5)
compute_dummy_comparisons(6)
```

compute_frequencies	<i>Frequencies by levels</i>
---------------------	------------------------------

Description

returns frequency proportion percent

Usage

```
compute_frequencies(df, ordered = TRUE, file = NULL)
```

Arguments

df	dataframe
ordered	if TRUE it will output frequencies in descending order
file	output filename

Details

returns xlsx

Examples

```
compute_frequencies(df=generate_missing(generate_factor(nrows=10,ncols=10),missing=5))
compute_frequencies(df=generate_factor())
compute_frequencies(df=generate_factor(),file="descriptives")
```

 compute_icc_thurstonian

Compute item characteristic curves for thurstonian models

Description

Computes icc curves for binary thurstonian coded items for a single dimension

Usage

```
compute_icc_thurstonian(eta, gamma, lambda, psi, plot = FALSE)
```

Arguments

eta	eta or ability
gamma	gamma or threshold
lambda	lambda or loading
psi	psi or error
plot	if TRUE plots icc curves using the plot_icc_thurstonian function

Examples

```
gamma<-c(0.556,-1.253,-1.729,0.618,0.937,0.295,-0.672,-1.127,-0.446,0.632,1.147,0.498)
psi<-c(2.172,1.883,2.055,1.869,2.231,2.100,1.762,1.803,1.565,1.892,1.794,1.686)
lambda<-c(1.082,1.082,-1.297,-1.297,0.802,0.802,1.083,1.083)
gamma<-gamma[response_dimension(c(1:12),3,c(1,2))]
```

```
psi<-psi[response_dimension(c(1:12),3,c(1,2))]
```

```
eta<-seq(-6,6,by=0.01)
```

```
compute_icc_thurstonian(eta=eta,gamma=gamma,lambda=lambda,psi=psi,plot=FALSE)
```

 compute_info_1pl

Compute item information for IPL model

Description

Compute item information for 1PL model

Usage

```
compute_info_1pl(b, theta)
```

Arguments

b	numeric difficulty parameter
theta	numeric theta

Examples

```

compute_info_1pl(b=1,theta=-3)
compute_info_1pl(b=1,theta=-2)
compute_info_1pl(b=1,theta=-1)
compute_info_1pl(b=1,theta=0)
compute_info_1pl(b=1,theta=1)
compute_info_1pl(b=1,theta=2)
compute_info_1pl(b=1,theta=3)
ti<-compute_info_1pl(b=1,theta=seq(-6,6,by=.01)) # test information
plot(ti,x=seq(-6,6,by=.01))

```

compute_info_2pl	<i>Compute item information for 2PL model</i>
------------------	---

Description

Compute item information for 2PL model

Usage

```
compute_info_2pl(a, b, theta)
```

Arguments

a	numeric discrimination parameter
b	numeric difficulty parameter
theta	numeric theta

Examples

```

compute_info_2pl(a=1.5,b=1,theta=-3)
compute_info_2pl(a=1.5,b=1,theta=-2)
compute_info_2pl(a=1.5,b=1,theta=-1)
compute_info_2pl(a=1.5,b=1,theta=0)
compute_info_2pl(a=1.5,b=1,theta=1)
compute_info_2pl(a=1.5,b=1,theta=2)
compute_info_2pl(a=1.5,b=1,theta=3)
ti<-compute_info_2pl(a=1,b=-2,theta=seq(-6,6,by=.01)) # test information
plot(ti,x=seq(-6,6,by=.01))
ti<-compute_info_2pl(a=2,b=0,theta=seq(-6,6,by=.01)) # test information
plot(ti,x=seq(-6,6,by=.01))
ti<-compute_info_2pl(a=3,b=2,theta=seq(-6,6,by=.01)) # test information
plot(ti,x=seq(-6,6,by=.01))

```

compute_info_3pl	<i>Compute item information for 3PL model</i>
------------------	---

Description

Compute item information for 3PL model

Usage

```
compute_info_3pl(a, b, g, theta)
```

Arguments

a	numeric discrimination parameter
b	numeric difficulty parameter
g	numeric guessing parameter
theta	numeric theta

Examples

```
compute_info_3pl(a=1.5,b=1,g=.2,theta=-3)
compute_info_3pl(a=1.5,b=1,g=.2,theta=-2)
compute_info_3pl(a=1.5,b=1,g=.2,theta=-1)
compute_info_3pl(a=1.5,b=1,g=.2,theta=0)
compute_info_3pl(a=1.5,b=1,g=.2,theta=1)
compute_info_3pl(a=1.5,b=1,g=.2,theta=2)
compute_info_3pl(a=1.5,b=1,g=.2,theta=3)
ti<-compute_info_3pl(a=1.5,b=1,g=.2,theta=seq(-6,6,by=.01)) # test information
plot(ti,x=seq(-6,6,by=.01))
```

compute_kruskal_wallis_test	<i>Kruskal Wallis test</i>
-----------------------------	----------------------------

Description

Kruskal Wallis test

Usage

```
compute_kruskal_wallis_test(formula, df)
```

Arguments

formula	one way formula in form of y~x. It will ignore more complex formulas
df	dataframe eta squared ranges between 0 and 1 epsilon squared ranges between 0 and 1 eta squared multiplied by 100 indicates the percentage of variance in the dependent variable explained by the independent variable

Examples

```
form<-formula(bp_before~agegrp)
kruskal.test(formula=form,data=df_blood_pressure)
rcompanion::epsilonSquared(x=df_blood_pressure$bp_before,
                           g=df_blood_pressure$agegrp,
                           group="row",
                           ci=TRUE,
                           conf=0.95,
                           type="perc",
                           R=1000,
                           digits=3)
rstatix::kruskal_effsize(df_blood_pressure,form,ci=TRUE,conf.level=0.95,ci.type="perc",nboot=100)
compute_kruskal_wallis_test(formula=form,df=df_blood_pressure)
```

compute_kurtosis	<i>Compute kurtosis</i>
------------------	-------------------------

Description

Compute kurtosis

Usage

```
compute_kurtosis(vector)
```

Arguments

vector	vector
--------	--------

Note

$b_2 = m_4 / s^4 - 3 = (g_2 + 3) (1 - 1/n)^2 - 3$. Used in MINITAB and BMDP.

Examples

```
set.seed(1)
vector<-rnorm(1000)
compute_kurtosis(vector)
e1071::kurtosis(vector)
```

`compute_map`*Simulate prior distribution*

Description

Simulate prior distribution

Usage

```
compute_map(eta, mean = 0, sd = 1)
```

Arguments

<code>eta</code>	vector
<code>mean</code>	numeric
<code>sd</code>	numeric

Examples

```
eta<-seq(-6,6,by=0.1)
compute_map(eta=eta,mean=0,sd=1)
```

`compute_moving_average`*Moving Average*

Description

compute moving average

Usage

```
compute_moving_average(df, w)
```

Arguments

<code>df</code>	dataframe
<code>w</code>	window

Examples

```
compute_moving_average(df=mtcars,w=5)
```

compute_one_way_test	<i>one way test</i>
----------------------	---------------------

Description

one way test

Usage

```
compute_one_way_test(formula, df, var.equal = TRUE)
```

Arguments

formula	one way formula in form of y~x. It will ignore more complex formulas
df	dataframe eta squared ranges between 0 and 1 epsilon squared ranges between 0 and 1 eta squared multiplied by 100 indicates the percentage of variance in the dependent variable explained by the independent variable
var.equal	if TRUE it assumes equal variances

Note

eta and omega for Welch statistics are not adequately tested and they should not be consulted

Examples

```
form<-formula(bp_before~agegrp)
compute_one_way_test(formula=form,df=df_blood_pressure,var.equal=TRUE)
compute_one_way_test(formula=form,df=df_blood_pressure,var.equal=FALSE)
oneway.test(formula=form,data=df_blood_pressure,var.equal=TRUE)
oneway.test(formula=form,data=df_blood_pressure,var.equal=FALSE)
car::Anova(aov(form,data=df_blood_pressure),type=2)
model<-lm(form,data=df_blood_pressure)
lsr::etaSquared(aov(form,data=df_blood_pressure),type=3,anova=TRUE)
sjstats::anova_stats(model,digits=22)
```

compute_posthoc	<i>Games Howell Tukey post hoc tests</i>
-----------------	--

Description

Based on http://www.psych.yorku.ca/cribbie/6130/games_howell.R

Usage

```
compute_posthoc(y, x)
```

Arguments

y	Vector continous variable
x	Vector factor

Examples

```
compute_posthoc(y=df_blood_pressure$bp_before,x=df_blood_pressure$agegrp)
compute_posthoc(y=df_blood_pressure$bp_after,x=df_blood_pressure$agegrp)
```

compute_power_r	<i>Compute r power curve</i>
-----------------	------------------------------

Description

Compute r power curve

Usage

```
compute_power_r(
  n = 100,
  r = NULL,
  sig.level = 0.05,
  alternative = c("two.sided", "less", "greater"),
  title = "",
  base_size = 10
)
```

Arguments

n	number of observations
r	correlation coefficient
sig.level	alpha (type I error probability)
alternative	a character string specifying the alternative hypothesis, must be one of "two.sided" (default), "greater" or "less"
title	plot title
base_size	base font size

Examples

```
compute_power_r(n=100,r=.5,sig.level=.05,alternative=c("two.sided"))
```

`compute_power_r_matrix`*Compute correlation matrix*

Description

Compute correlation matrix

Usage

```
compute_power_r_matrix(m, ...)
```

Arguments

<code>m</code>	correlation matrix
<code>...</code>	arguments passed to <code>compute_power_r</code>

Examples

```
compute_power_r_matrix(m=stats::cor(mtcars,use="pairwise.complete.obs"),n=100)
```

`compute_residual_stats`*Residuals for matrices*

Description

Root Mean Squared Residual Number of absolute residuals > 0.05 Proportion of absolute residuals > 0.05. It can either accept a psych EFA model or it can compare two correlation or covariance matrices

Usage

```
compute_residual_stats(model, data = NULL)
```

Arguments

<code>model</code>	psych EFA model. It has to be a correlation or covariance matrix if data is not NULL
<code>data</code>	correlation or covariance matrix

Examples

```
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="pa",oblique.scores=TRUE)  
compute_residual_stats(model)
```

compute_scores	<i>Compute subject ability for thurstonian models</i>
----------------	---

Description

Computes person ability for binary thurstonian coded items for a single dimension

Usage

```
compute_scores(mydata, ...)
```

Arguments

mydata	item responses
...	arguments passed to compute_ability

Examples

```
gamma<-c(0.556,-1.253,-1.729,0.618,0.937,0.295,-0.672,-1.127,-0.446,0.632,1.147,0.498)
psi<-c(2.172,1.883,2.055,1.869,2.231,2.100,1.762,1.803,1.565,1.892,1.794,1.686)
lambda<-c(1.082,1.082,-1.297,-1.297,0.802,0.802,1.083,1.083)
gamma<-gamma[response_dimension(c(1:12),3,c(1,2))]
```

```
psi<-psi[response_dimension(c(1:12),3,c(1,2))]
```

```
eta<-seq(-6,6,by=0.1)
```

```
map<-compute_map(eta=eta,mean=0,sd=1)
```

```
response_df<-data.frame(matrix(nrow=0,ncol=8))
```

```
response_df[1,]<-c(0,0,0,0,0,0,0,0)
```

```
response_df[2,]<-c(1,1,1,1,1,1,1,1)
```

```
response_df[3,]<-c(1,0,1,0,1,0,1,0)
```

```
response_df[4,]<-c(0,1,0,1,0,1,0,1)
```

```
compute_scores(response_df,eta,gamma,lambda,psi,map=map,plot=FALSE)
```

compute_se_theta	<i>Compute the SE of theta</i>
------------------	--------------------------------

Description

Compute the SE of theta

Usage

```
compute_se_theta(info)
```

Arguments

info	numeric information
------	---------------------

Examples

```
compute_se_theta(1)
ti<-compute_info_2pl(a=10,b=0,theta=seq(-3,3,by=.01)) # test information
plot(compute_se_theta(ti),x=seq(-3,3,by=.01))
```

compute_skewness	<i>Compute skewness</i>
------------------	-------------------------

Description

Compute skewness

Usage

```
compute_skewness(vector)
```

Arguments

vector vector

Note

$b_1 = m_3 / s^3 = g_1 ((n-1)/n)^{3/2}$. Used in MINITAB and BMDP.

Examples

```
set.seed(1)
vector<-rnorm(1000)
compute_skewness(vector)
e1071::skewness(vector)
```

compute_standard	<i>compute standard scores</i>
------------------	--------------------------------

Description

compute standard scores

Usage

```
compute_standard(vector, mean = 0, sd = 1, type = "z", input = "non_standard")
```

Arguments

vector	vector
mean	numeric applicable to "uz"
sd	numeric applicable to "uz"
type	"z" "uz" "sten" "t" "stanine" "center" "center_reversed" "percent" "percentile" "scale_zero_one" "normal_density" "cumulative_density" "all"
input	"standard" "non_standard" standard inputs are z scores and non standard are raw scores

Examples

```
vector<-c(rnorm(10),NA,rnorm(10))
compute_standard(vector,type="z")
compute_standard(vector,mean=0,sd=1,type="uz")
compute_standard(vector,type="sten")
compute_standard(vector,type="t")
compute_standard(vector,type="stanine")
compute_standard(vector,type="center")
compute_standard(vector,type="center_reversed")
compute_standard(vector,type="percent")
compute_standard(vector,type="scale_zero_one")
ndf<-compute_standard(seq(-6,6,.01),mean=0,sd=1,type="normal_density")
plot(ndf)
cdf<-compute_standard(ndf,mean=0,sd=1,type="cumulative_density")
plot(cdf)
compute_standard(vector,type="all")
compute_standard(seq(-6,6,.1),type="all",input="standard")
```

compute_standard_error
<i>Compute standard error</i>

Description

Compute standard error

Usage

```
compute_standard_error(vector)
```

Arguments

vector	vector
--------	--------

Examples

```
set.seed(1)
vector<-rnorm(1000)
compute_standard_error(vector)
```

compute_tversky_index *Compute the Tversky index*

Description

Computes the Tversky index between two sets, a generalisation of the Jaccard and Sørensen–Dice similarity coefficients. The index measures the overlap between x and y relative to their differences, weighted by α and β .

The Tversky index is defined as:

$$T(x, y) = \frac{|x \cap y|}{|x \cap y| + \alpha|x \setminus y| + \beta|y \setminus x|}$$

Special cases:

- $\alpha = \beta = 0.5$ — Sørensen–Dice coefficient
- $\alpha = \beta = 1.0$ — Jaccard index

Usage

```
compute_tversky_index(x, y, alpha = 0.5, beta = 0.5)
```

Arguments

<code>x</code>	A vector. Coerced to character before comparison.
<code>y</code>	A vector. Coerced to character before comparison.
<code>alpha</code>	Non-negative numeric. Weight applied to elements in x but not in y . Defaults to 0.5.
<code>beta</code>	Non-negative numeric. Weight applied to elements in y but not in x . Defaults to 0.5.

Value

A single numeric value in the range $[0, 1]$, where 0 indicates no overlap and 1 indicates identical sets.

Note

Both x and y are treated as *sets* — duplicate elements within each vector are ignored. Inputs are coerced to character before comparison, so 1L and "1" are treated as equal.

See Also

[intersect](#), [setdiff](#), [cdf](#)

Examples

```
x <- c("a", "b", "c", "d")
y <- c("b", "c", "d", "e")

# default (Sorensen-Dice)
compute_tversky_index(x, y)

# Jaccard index
compute_tversky_index(x, y, alpha = 1, beta = 1)

# asymmetric: penalise x-only elements more heavily
compute_tversky_index(x, y, alpha = 0.9, beta = 0.1)

# identical sets → 1
compute_tversky_index(x, x)

# disjoint sets → 0
compute_tversky_index(c("a", "b"), c("c", "d"))
```

```
compute_unidimensional_ability
```

Compute theta for unidimensional models

Description

Compute theta for unidimensional models

Usage

```
compute_unidimensional_ability(
  a,
  b,
  g = NULL,
  d = 1.702,
  u,
  lim_theta = c(-6, 6)
)
```

Arguments

a	numeric vector discrimination parameters
b	numeric vector difficulty parameters
g	numeric vector guessing parameters
d	numeric scaling constant usually it is a value that approximating 1.749
u	numeric vector responses
lim_theta	vector minimum and maximum value of theta

Examples

```

a<-c(0.39,0.45,0.52,0.3,0.35,0.43,0.42,0.44,0.34,0.42)
b<-c(-1.96,-1.9,-1.38,-0.58,0.48,-0.81,-0.35,1.59,1.33,2.93)
u<-c(1,1,1,1,0,0,1,0,1,0)
# SHOULD RETURN 0.48402574251176
compute_unidimensional_ability(a=a,b=b,u=u,d=1.7,g=NULL)
a<-c(1.27,0.9,0.94,0.95,0.55,0.6,0.44,0.4)
b<-c(-0.54,0.18,0.21,1.26,1.73,-0.87,1.72,2.67)
u<-c(1,1,1,1,0,0,0,0)
# SHOULD RETURN 1.04621621510192
compute_unidimensional_ability(a=a,b=b,u=u,d=1.7,g=NULL)
a<-c(0.41,0.32,0.33,1.2,0.63,0.62,0.7,0.61,0.38,0.53,0.6,1.16)
b<-c(-1.4,-1.3,-1.17,0.2,0.71,0.86,-0.12,0.12,2.06,1.38,1.18,-0.33)
u<-c(1,0,1,1,0,0,0,1,1,0,1,0)
# SHOULD RETURN 0.0860506282671103
compute_unidimensional_ability(a=a,b=b,u=u,d=1.7,g=NULL)

```

compute_unidimensional_theta

Compute theta for unidimensional models

Description

Compute theta for unidimensional models

Usage

```
compute_unidimensional_theta(a, b = 0, g = 0, i = 1, d = 1.702, theta = 0)
```

Arguments

a	numeric discrimination parameter
b	numeric difficulty parameter
g	numeric guessing parameter
i	numeric inattentiveness parameter
d	numeric scaling constant usually a value 1.749 or 1.702
theta	numeric or vector theta

Note

when scaling constant=1 it has no effect in equation
 when inattentiveness=1 and guessing=0 function computes a 2PL score
 when inattentiveness=1 and guessing!=0 function computes a 3PL score
 when inattentiveness!=1 and guessing!=0 function computes a 4PL score

Examples

```

compute_unidimensional_theta(a=10,b=0)
x<-seq(-3,3,by=.01)
plot(compute_unidimensional_theta(a=5,b=0,theta=x),x=x)
plot(compute_unidimensional_theta(a=5,b=-1,theta=x),x=x)
plot(compute_unidimensional_theta(a=5,b=1,theta=x),x=x)
plot(compute_unidimensional_theta(a=.1,b=0,theta=x),x=x)
plot(compute_unidimensional_theta(a=1,b=0,theta=x),x=x)
plot(compute_unidimensional_theta(a=10,b=0,theta=x),x=x)
plot(compute_unidimensional_theta(a=10,b=0,g=0,theta=x),x=x)
plot(compute_unidimensional_theta(a=10,b=0,g=.1,theta=x),x=x)
plot(compute_unidimensional_theta(a=10,b=0,g=.5,theta=x),x=x)
plot(compute_unidimensional_theta(a=10,b=0,g=0,i=1,theta=x),x=x)
plot(compute_unidimensional_theta(a=10,b=0,g=0,i=.9,theta=x),x=x)
plot(compute_unidimensional_theta(a=10,b=0,g=0,i=.6,theta=x),x=x)

```

compute_y_logistic	<i>Compute y for logistic function</i>
--------------------	--

Description

This function requires x range to produce a vector with y values

Usage

```
compute_y_logistic(intercept, coefficient, x)
```

Arguments

intercept	Numeric
coefficient	Numeric
x	Numeric

Examples

```

x<--10:10
compute_y_logistic(0,1,x)
compute_y_logistic(0,1,1)
plot(x,compute_y_logistic(0,1,x),type="l");grid();abline(b=0,a=.5)

```

confusion

Create a confusion matrix from observed and predicted vectors

Description

Generates a confusion matrix from observed and predicted values.

Usage

```
confusion(observed, predicted)
```

Arguments

observed	Vector of observed variables. These are the true class labels.
predicted	Vector of predicted variables. These are the predicted class labels.

Details

This function creates a confusion matrix by comparing the observed (true) class labels with the predicted class labels. The confusion matrix is a table that is often used to describe the performance of a classification model. The function performs the following steps: 1. Identifies the unique class labels from both the observed and predicted vectors. 2. Sorts the class labels in a mixed order (if they are character variables) using 'gtools::mixedsort'. 3. Constructs a table to represent the confusion matrix with the sorted class labels as levels. The output is a confusion matrix, where rows represent the predicted class labels and columns represent the observed class labels.

Examples

```
# Example with numeric observed and predicted values
confusion(observed=c(1,2,3,4,5,10),predicted=c(1,2,3,4,5,11))
# Example with repeated observed and predicted values
confusion(observed=c(1,2,2,2,2),predicted=c(1,1,2,2,2))
```

confusion_matrix_percent

Confusion matrix with row and column percent

Description

Generates a confusion matrix from observed and predicted values, including row and column percentages.

Usage

```
confusion_matrix_percent(observed, predicted)
```

Arguments

observed	Vector of observed variables. These are the true class labels.
predicted	Vector of predicted variables. These are the predicted class labels.

Details

This function creates a confusion matrix by comparing the observed (true) class labels with the predicted class labels. Additionally, it calculates row and column percentages to provide a more detailed performance analysis.

The function performs the following steps: 1. Computes the confusion matrix from the observed and predicted values. 2. Calculates the overall accuracy by dividing the sum of diagonal elements by the total number of observations. 3. Appends row and column sums to the confusion matrix. 4. Computes precision and recall for each class and appends these metrics to the matrix. 5. Returns a formatted data frame with the confusion matrix, row and column percentages, and overall accuracy.

Note

Total measures-Accuracy: $(TP+TN)/total$
 Total measures-Prevalence: $(TP+FN)/total$
 Total measures-Proportion Incorrectly Classified: $(FN+FP)/total$
 Horizontal measures-True Positive Rate-Sensitivity: $TP/(TP+FN)$
 Horizontal measures-True Negative Rate-Specificity: $TN/(FP+TN)$
 Horizontal measures-False Negative Rate-Miss Rate: $FN/(TP+FN)$
 Horizontal measures-False Positive Rate-Fall-out: $FP/(FP+TN)$
 Vertical measures-Positive Predictive value-Precision: $TP/(TP+FP)$
 Vertical measures-Negative Predictive value: $TN/(FN+TN)$
 Vertical measures-False Omission Rate: $FN/(FN+TN)$
 Vertical measures-False Discovery Rate: $FP/(TP+FP)$

Examples

```
# Example with numeric observed and predicted values
confusion_matrix_percent(observed=c(1,2,3,4,5,10),predicted=c(1,2,3,4,5,11))

# Example with repeated observed and predicted values
confusion_matrix_percent(observed=c(1,2,2,2,2),predicted=c(1,1,2,2,2))

# Example with random observed and predicted values
observed<-factor(round(rnorm(10000,m=10,sd=1)))
predicted<-factor(round(rnorm(10000,m=10,sd=1)))
confusion_matrix_percent(observed,predicted)
```

convert_excel_unix_timestamp	
	<i>Convert UNIX EXCEL timestamp</i>

Description

Convert UNIX EXCEL timestamp

Usage

```
convert_excel_unix_timestamp(timestamp)
```

Arguments

timestamp	unix or excel timestamp
-----------	-------------------------

Examples

```
convert_excel_unix_timestamp(1)
```

c_bind	<i>cbind dataframes with unequal lengths or row lengths</i>
--------	---

Description

cbind dataframes with unequal lengths or row lengths

Usage

```
c_bind(..., first = TRUE)
```

Arguments

...	dataframes or vectors to bind
first	Logical

Author(s)

Ananda Mahto

Examples

```
c_bind(rnorm(10), rnorm(11), rnorm(12), rnorm(13))
```

data_frame_index	<i>dataframe index</i>
------------------	------------------------

Description

dataframe index

Usage

```
data_frame_index(nrow, ncol)
```

Arguments

nrow	number of rows
ncol	number of columns

Examples

```
data_frame_index(5,5)
```

decompose_datetime	<i>Decompose datetime objects to dataframe columns</i>
--------------------	--

Description

Decompose datetime objects to dataframe columns

Usage

```
decompose_datetime(  
  x,  
  format = "",  
  origin = "1970-01-01",  
  tz = "GMT",  
  extended = FALSE,  
  breaks = c(-1, 5, 13, 16, 20, 23),  
  ...  
)
```

Arguments

x	datetime object
format	date time format
origin	Starting date. The default is the unix time origin "1970-01-01"
tz	Timezone
extended	if TRUE it will display additional day time categories WEEKDAY MONTH JULIAN QUARTER DAY_PERIOD
breaks	Numeric vector Breaks define hour of day for classifying into "Night", "Morning", "Noon", "Afternoon", "Evening".
...	arguments passed to as.POSIXct This argument is used if extended=TRUE

Examples

```
timestamp1<-as.numeric(as.POSIXct(Sys.Date()))
timestamp2<-as.numeric(as.POSIXct(Sys.time()))
d1<-Sys.Date()
d2<-Sys.time()
decompose_datetime(x=d1)
decompose_datetime(x=d2)
decompose_datetime(x=d1,extended=TRUE)
decompose_datetime(x=d2,extended=TRUE)
decompose_datetime(x="01/15/1900",format="%m/%e/%Y")
decompose_datetime(x="01/15/1900",format="%m/%e/%Y",extended=TRUE)
decompose_datetime(x=as.Date(as.POSIXct(10000,origin="1970-01-01")))
decompose_datetime(x=as.Date(as.POSIXct(timestamp1,origin="1970-01-01")),
                    format="%m/%e/%Y")
decompose_datetime(x=as.Date(as.POSIXct(timestamp2,origin="1970-01-01")),
                    format="%m/%e/%Y")
```

deg2rad	<i>Convert degrees to radians</i>
---------	-----------------------------------

Description

Convert degrees to radians

Usage

```
deg2rad(degrees)
```

Arguments

degrees	degrees
---------	---------

Examples

```
deg2rad(180)
```

detach_package	<i>Unload library</i>
----------------	-----------------------

Description

Unload library

Usage

```
detach_package(package)
```

Arguments

package	Package name
---------	--------------

df_admission	<i>Admission Data</i>
--------------	-----------------------

Description

This data set contains information about graduate admission, including GRE scores, GPA, and the ranking of the undergraduate institution.

Usage

```
df_admission
```

Format

A data frame with 8 rows and 4 variables:

admit Binary variable indicating admission (0=No, 1=Yes)

gre GRE (Graduate Record Examination) score

gpa Grade Point Average

rank Ranking of the undergraduate institution (1=highest, 4=lowest)

Source

researchpy repo

df_automotive_data	<i>Automotive Data</i>
--------------------	------------------------

Description

This data set contains various automotive information including engine location, dimensions, weight, engine type, number of cylinders, and other specifications.

Usage

```
df_automotive_data
```

Format

A data frame with 38 rows and 26 variables:

symboling Symboling code for the vehicle
normalized-losses Normalized losses in the vehicle
make Make of the vehicle
fuel-type Type of fuel used (e.g., gas, diesel)
aspiration Aspiration type (e.g., std, turbo)
num-of-doors Number of doors (e.g., two, four)
body-style Body style (e.g., sedan, hatchback, wagon)
drive-wheels Drive wheels (e.g., fwd, rwd, 4wd)
engine-location Location of the engine (e.g., front, rear)
wheel-base Wheelbase of the vehicle in inches
length Length of the vehicle in inches
width Width of the vehicle in inches
height Height of the vehicle in inches
curb-weight Curb weight of the vehicle in pounds
engine-type Type of engine (e.g., dohc, ohcv, ohc, l)
num-of-cylinders Number of cylinders in the engine
engine-size Size of the engine in cubic inches
fuel-system Fuel system used (e.g., mpfi, 2bbl, mfi, 1bbl)
bore Diameter of the cylinders in the engine
stroke Stroke length of the engine
compression-ratio Compression ratio of the engine
horsepower Horsepower generated by the engine
peak-rpm Peak RPM of the engine
city-mpg Miles per gallon in the city
highway-mpg Miles per gallon on the highway
price Price of the vehicle

Source

Downloaded from Kaggle.com by the user Ramakrishnan Srinivasan. see <https://www.kaggle.com/toramky/automobile-dataset>

df_blood_pressure	<i>Blood Pressure Data</i>
-------------------	----------------------------

Description

This data set contains blood pressure readings for patients before and after a certain treatment or intervention.

Usage

df_blood_pressure

Format

A data frame with 30 rows and 5 variables:

patient Unique identifier for each patient

sex Sex of the patient (e.g., Male, Female)

agegrp Age group of the patient (e.g., 30-45, 46-59)

bp_before Blood pressure reading before the intervention

bp_after Blood pressure reading after the intervention

Source

researchpy repo

df_co2	<i>Carbon Dioxide Uptake in Grass Plants</i>
--------	--

Description

The CO2 data frame has 84 rows and 5 columns of data from an experiment on the cold tolerance of the grass species *Echinochloa crus-galli*.

Usage

df_co2

Format

A data frame with 84 rows and 5 variables:

Plant an ordered factor with levels Qn1 < Qn2 < Qn3 < ... < Mc1 giving a unique identifier for each plant). Used as a grouping factor.

Type a factor with levels Quebec Mississippi giving the origin of the plant

Treatment a factor with levels nonchilled chilled

conc a numeric vector of ambient carbon dioxide concentrations (mL/L)

uptake a numeric vector of carbon dioxide uptake rates (in $\mu\text{mol}/\text{m}^2/\text{sec}$)

Details

Grouped formulas like `uptake ~ conc | Plant` are useful in lattice graphics and mixed-effect models. The vertical bar ('|') separates the grouping variable. This allows modeling or plotting the response (uptake) versus the predictor (conc) within each level of Plant.

Source

Potvin, C., Lechowicz, M. J. and Tardif, S. (1990) "The statistical analysis of ecophysiological response curves obtained from experiments involving repeated measures", *Ecology*, 71, 1389–1400.
Pinheiro, J. C. and Bates, D. M. (2000) *Mixed-effects Models in S and S-PLUS*, Springer.

Examples

```
data(df_co2)
head(df_co2)
```

df_crop_yield	<i>Crop Yield Data</i>
---------------	------------------------

Description

This data set contains information about crop yields based on different fertilizer types and water conditions.

Usage

```
df_crop_yield
```

Format

A data frame with 20 rows and 3 variables:

Fert Type of fertilizer used (A or B)

Water Watering condition (High or Low)

Yield Crop yield (in unspecified units)

Source

researchpy repo (simulated data, not real)

df_difficile

Difficile Data

Description

This data set contains information about the impact of different doses on libido.

Usage

df_difficile

Format

A data frame with 15 rows and 3 variables:

person Unique identifier for each person

dose Dose received (e.g., 1, 2, 3)

libido Libido level of the person

Source

researchpy repo

df_insurance

Insurance Data

Description

This data set contains information about insurance charges based on various factors such as age, sex, BMI, number of children, smoking status, and region.

Usage

df_insurance

Format

A data frame with 19 rows and 7 variables:

age Age of the individual

sex Sex of the individual (e.g., male, female)

bmi Body Mass Index of the individual

children Number of children covered by the insurance

smoker Smoking status (yes or no)

region Region where the individual resides (e.g., southwest, southeast, northwest, northeast)

charges Insurance charges

Source

researchpy repo

df_ocean

Big Five Personality Test Dataset

Description

This dataset contains responses to an interactive online Big Five personality test conducted around 2012. Participants rated themselves on 50 personality statements, and also provided demographic and technical metadata. Responses were collected with informed consent, and missing data is coded as 0.

Usage

df_ocean

Format

A data frame with 19719 rows and 57 variables:

race Race/ethnic background (1–13, 0=missing)

age Age (integer; only responses from participants 13 and older included)

engnat Is English your native language? (1=Yes, 2=No, 0=missing)

gender 1=Male, 2=Female, 3=Other, 0=missing

hand Dominant writing hand: 1=Right, 2=Left, 3=Both, 0=missing

source How participant came to the test site: 1=Internal link, 2=Google, 3=Facebook, 4=.edu site, 6=Other/unknown

country Two-letter ISO country code (e.g., "US", "GB")

E1 I am the life of the party.

E2 I don't talk a lot.

- E3** I feel comfortable around people.
- E4** I keep in the background.
- E5** I start conversations.
- E6** I have little to say.
- E7** I talk to a lot of different people at parties.
- E8** I don't like to draw attention to myself.
- E9** I don't mind being the center of attention.
- E10** I am quiet around strangers.
- N1** I get stressed out easily.
- N2** I am relaxed most of the time.
- N3** I worry about things.
- N4** I seldom feel blue.
- N5** I am easily disturbed.
- N6** I get upset easily.
- N7** I change my mood a lot.
- N8** I have frequent mood swings.
- N9** I get irritated easily.
- N10** I often feel blue.
- A1** I feel little concern for others.
- A2** I am interested in people.
- A3** I insult people.
- A4** I sympathize with others' feelings.
- A5** I am not interested in other people's problems.
- A6** I have a soft heart.
- A7** I am not really interested in others.
- A8** I take time out for others.
- A9** I feel others' emotions.
- A10** I make people feel at ease.
- C1** I am always prepared.
- C2** I leave my belongings around.
- C3** I pay attention to details.
- C4** I make a mess of things.
- C5** I get chores done right away.
- C6** I often forget to put things back in their proper place.
- C7** I like order.
- C8** I shirk my duties.
- C9** I follow a schedule.

- C10** I am exacting in my work.
- O1** I have a rich vocabulary.
- O2** I have difficulty understanding abstract ideas.
- O3** I have a vivid imagination.
- O4** I am not interested in abstract ideas.
- O5** I have excellent ideas.
- O6** I do not have a good imagination.
- O7** I am quick to understand things.
- O8** I use difficult words.
- O9** I spend time reflecting on things.
- O10** I am full of ideas.

Details

Personality items were rated on a five-point Likert scale: #’ 1=Disagree, 3=Neutral, 5=Agree. Missed=0.

race Chosen from a drop down menu. 1=Mixed Race, 2=Arctic (Siberian, Eskimo), 3=Caucasian (European), 4=Caucasian (Indian), 5=Caucasian (Middle East), 6=Caucasian (North African, Other), 7=Indigenous Australian, 8=Native American, 9=North East Asian (Mongol, Tibetan, Korean Japanese, etc), 10=Pacific (Polynesian, Micronesian, etc), 11=South East Asian (Chinese, Thai, Malay, Filipino, etc), 12=West African, Bushmen, Ethiopian, 13=Other (0=missed)

age Entered as text (individuals reporting age < 13 were not recorded)

engnat Response to "is English your native language?". 1=Yes, 2=No (0=missed)

gender Chosen from a drop down menu. 1=Male, 2=Female, 3=Other (0=missed)

hand "What hand do you use to write with?". 1=Right, 2=Left, 3=Both (0=missed)

On this page users were also asked to confirm that their answers were accurate and could be used for research. Participants who did not were not recorded). Some values were calculated from technical information.

country The participant’s technical location. ISO country code.

source How the participant came to the test. Based on HTTP Referrer. 1=from another page on the test website, 2=from google, 3=from facebook, 4=from any url with ".edu" in its domain name (e.g. xxx.edu, xxx.edu.au), 6=other source, or HTTP Referer not provided.

In psychological trait theory, the Big Five personality traits, also known as the five-factor model (FFM) and the OCEAN model, is a suggested taxonomy, or grouping, for personality traits, developed from the 1980s onwards. When factor analysis (a statistical technique) is applied to personality survey data, some words used to describe aspects of personality are often applied to the same person. For example, someone described as conscientious is more likely to be described as "always prepared" rather than "messy". This theory is based therefore on semantic associations between words and not on neuropsychological experiments. This theory uses descriptors of common language and suggests five broad dimensions commonly used to describe the human personality and psyche.

The theory identifies five factors:

- **Openness to experience (O)** (inventive/curious vs. consistent/cautious)
- **Conscientiousness (C)** (efficient/organized vs. extravagant/careless)
- **Extraversion (E)** (outgoing/energetic vs. solitary/reserved)
- **Agreeableness (A)** (friendly/compassionate vs. challenging/callous)
- **Neuroticism (N)** (sensitive/nervous vs. resilient/confident)

The five factors are represented using the acronyms OCEAN or CANOE. Beneath each proposed global factor, there are a number of correlated and more specific primary factors. For example, extroversion is typically associated with qualities such as gregariousness, assertiveness, excitement-seeking, warmth, activity, and positive emotions. Family life and the way someone was raised will affect these traits. Twin studies and other research have shown that about half of the variation between individuals results from their genetics and half from their environments. Researchers have found conscientiousness, extroversion, openness to experience, and neuroticism to be relatively stable from childhood through adulthood.

Items are grouped by Big Five traits:

- **Extraversion (E)**: E1 to E10
- **Neuroticism (N)**: N1 to N10
- **Agreeableness (A)**: A1 to A10
- **Conscientiousness (C)**: C1 to C10
- **Openness (O)**: O1 to O10

Negatively keyed items are: E2, E4, E6, E8, E10, N2, N4, A1, A3, A5, A7, C2, C4, C6, C8, O2, O4, O6. These should be reverse-coded prior to scoring.

Source

Collected via an online personality test with informed consent (~2012). Downloaded from Kaggle.com by the user Lucas Greenwell. see <https://www.kaggle.com/datasets/lucasgreenwell/ocean-five-factor-personality-test-responses>

Examples

```
data(df_ocean)
head(df_ocean)

# Compute Big Five average scores (after reverse scoring)
# library(dplyr)
# df_ocean <- df_ocean %>% mutate(E=rowMeans(select(., E1:E10), na.rm=TRUE))
```

df_personality*Big Five Inventory (BFI-44) Personality Dataset*

Description

Responses from 433 participants to the Big Five Inventory (BFI-44), a widely used measure of the five major dimensions of personality: Extraversion (E), Agreeableness (A), Conscientiousness (C), Neuroticism (N), and Openness to Experience (O). Items are rated on a 1-6 Likert scale. Reverse-scored items are marked with (R).

Usage

df_personality

Format

A data frame with 433 rows and 44 variables:

pers01 [E] Is talkative
pers02 [A-R] Tends to find fault with others
pers03 [C] Does a thorough job
pers04 [N] Is depressed, blue
pers05 [O] Is original, comes up with new ideas
pers06 [E-R] Is reserved
pers07 [A] Is helpful and unselfish with others
pers08 [C-R] Can be somewhat careless
pers09 [N-R] Is relaxed, handles stress well
pers10 [O] Is curious about many different things
pers11 [E] Is full of energy
pers12 [A-R] Starts quarrels with others
pers13 [C] Is a reliable worker
pers14 [N] Can be tense
pers15 [O] Is ingenious, a deep thinker
pers16 [E] Generates a lot of enthusiasm
pers17 [A] Has a forgiving nature
pers18 [C-R] Tends to be disorganized
pers19 [N] Worries a lot
pers20 [O] Has an active imagination
pers21 [E-R] Tends to be quiet
pers22 [A] Is generally trusting

pers23 [C-R] Tends to be lazy
pers24 [N-R] Is emotionally stable, not easily upset
pers25 [O] Is inventive
pers26 [E] Has an assertive personality
pers27 [A-R] Can be cold and aloof
pers28 [C] Perseveres until the task is finished
pers29 [N] Can be moody
pers30 [O] Values artistic, aesthetic experiences
pers31 [E-R] Is sometimes shy, inhibited
pers32 [A] Is considerate and kind to almost everyone
pers33 [C] Does things efficiently
pers34 [N-R] Remains calm in tense situations
pers35 [O-R] Prefers work that is routine
pers36 [E] Is outgoing, sociable
pers37 [A-R] Is sometimes rude to others
pers38 [C] Makes plans and follows through with them
pers39 [N] Gets nervous easily
pers40 [O] Likes to reflect, play with ideas
pers41 [O-R] Has few artistic interests
pers42 [A] Likes to cooperate with others
pers43 [C-R] Is easily distracted
pers44 [O] Is sophisticated in art, music, or literature

References

John, O. P., & Srivastava, S. (1999). The Big Five trait taxonomy: History, measurement, and theoretical perspectives. In L. A. Pervin & O. P. John (Eds.), *Handbook of personality: Theory and research* (2nd ed., pp. 102-138). Guilford Press.

Examples

```
data(df_personality)
head(df_personality)
```

df_responses

*Young People Survey Responses***Description**

Survey responses from 1010 young people (15-30 years old) on music preferences, movie preferences, hobbies, phobias, health habits, personality traits, spending habits, and demographics.

Usage

df_responses

Format

A data frame with 1010 rows and 151 variables. All preference and personality items are rated on a 1-5 Likert scale (1=strongly disagree / not interested, 5=strongly agree / very interested) unless otherwise noted.

- **Participant Number:** Unique participant identifier
- **Music:** Interest in music generally
- **Slow songs or fast songs:** Preference for slow vs fast songs
- **Dance:** Interest in dance music
- **Folk:** Interest in folk music
- **Country:** Interest in country music
- **Classical music:** Interest in classical music
- **Musical:** Interest in musicals
- **Pop:** Interest in pop music
- **Rock:** Interest in rock music
- **Metal or Hardrock:** Interest in metal/hardrock
- **Punk:** Interest in punk music
- **Hiphop, Rap:** Interest in hiphop/rap
- **Reggae, Ska:** Interest in reggae/ska
- **Swing, Jazz:** Interest in swing/jazz
- **Rock n roll:** Interest in rock n roll
- **Alternative:** Interest in alternative music
- **Latino:** Interest in Latino music
- **Techno, Trance:** Interest in techno/trance
- **Opera:** Interest in opera
- **Movies:** Interest in movies generally
- **Horror:** Interest in horror films

- **Thriller:** Interest in thrillers
- **Comedy:** Interest in comedy films
- **Romantic:** Interest in romantic films
- **Sci-fi:** Interest in sci-fi films
- **War:** Interest in war films
- **Fantasy/Fairy tales:** Interest in fantasy films
- **Animated:** Interest in animated films
- **Documentary:** Interest in documentaries
- **Western:** Interest in westerns
- **Action:** Interest in action films
- **History:** Interest in history
- **Psychology:** Interest in psychology
- **Politics:** Interest in politics
- **Mathematics:** Interest in mathematics
- **Physics:** Interest in physics
- **Internet:** Interest in internet
- **PC:** Interest in computers
- **Economy Management:** Interest in economy/management
- **Biology:** Interest in biology
- **Chemistry:** Interest in chemistry
- **Reading:** Interest in reading
- **Geography:** Interest in geography
- **Foreign languages:** Interest in foreign languages
- **Medicine:** Interest in medicine
- **Law:** Interest in law
- **Cars:** Interest in cars
- **Art exhibitions:** Interest in art exhibitions
- **Religion:** Interest in religion
- **Countryside, outdoors:** Interest in countryside/outdoors
- **Dancing:** Interest in dancing
- **Musical instruments:** Interest in playing musical instruments
- **Writing:** Interest in writing
- **Passive sport:** Interest in watching sports
- **Active sport:** Interest in playing sports
- **Gardening:** Interest in gardening
- **Celebrities:** Interest in celebrities
- **Shopping:** Interest in shopping

- **Science and technology:** Interest in science and technology
- **Theatre:** Interest in theatre
- **Fun with friends:** Enjoyment of socialising with friends
- **Adrenaline sports:** Interest in adrenaline sports
- **Pets:** Interest in pets
- **Flying:** Fear of flying
- **Storm:** Fear of storms
- **Darkness:** Fear of darkness
- **Heights:** Fear of heights
- **Spiders:** Fear of spiders
- **Snakes:** Fear of snakes
- **Rats:** Fear of rats
- **Ageing:** Fear of ageing
- **Dangerous dogs:** Fear of dangerous dogs
- **Fear of public speaking:** Fear of public speaking
- **Smoking:** Smoking behaviour/attitude
- **Alcohol:** Alcohol consumption/attitude
- **Healthy eating:** Attitude toward healthy eating
- **Daily events:** Attitude toward planning daily events
- **Prioritising workload:** Ability to prioritise workload
- **Writing notes:** Habit of writing notes
- **Workaholism:** Tendency toward workaholism
- **Thinking ahead:** Tendency to think ahead
- **Final judgement:** Tendency to make final judgements
- **Reliability:** Self-rated reliability
- **Keeping promises:** Tendency to keep promises
- **Loss of interest:** Tendency to lose interest
- **Friends versus money:** Attitude toward friends vs money
- **Funniness:** Self-rated funniness
- **Fake:** Tendency to be fake
- **Criminal damage:** Attitude toward criminal damage
- **Decision making:** Decision-making style
- **Elections:** Attitude toward elections
- **Self-criticism:** Tendency toward self-criticism
- **Judgment calls:** Tendency to make judgment calls
- **Hypochondria:** Tendency toward hypochondria
- **Empathy:** Level of empathy

- **Eating to survive:** Attitude toward eating
- **Giving:** Tendency to give to others
- **Compassion to animals:** Compassion toward animals
- **Borrowed stuff:** Attitude toward returning borrowed items
- **Loneliness:** Tendency to feel lonely
- **Cheating in school:** Attitude toward cheating
- **Health:** Self-rated health
- **Changing the past:** Desire to change the past
- **God:** Belief in God
- **Dreams:** Belief in dreams
- **Charity:** Attitude toward charity
- **Number of friends:** Number of friends
- **Punctuality:** Self-rated punctuality
- **Lying:** Tendency to lie
- **Waiting:** Attitude toward waiting
- **New environment:** Comfort in new environments
- **Mood swings:** Tendency to have mood swings
- **Appearance and gestures:** Attention to appearance and gestures
- **Socializing:** Enjoyment of socializing
- **Achievements:** Drive for achievements
- **Responding to a serious letter:** Tendency to respond to serious letters
- **Children:** Attitude toward children
- **Assertiveness:** Level of assertiveness
- **Getting angry:** Tendency to get angry
- **Knowing the right people:** Value placed on knowing the right people
- **Public speaking:** Comfort with public speaking
- **Unpopularity:** Attitude toward unpopularity
- **Life struggles:** Attitude toward life struggles
- **Happiness in life:** Self-rated happiness
- **Energy levels:** Self-rated energy levels
- **Small - big dogs:** Preference for small vs big dogs
- **Personality:** Self-rated personality
- **Finding lost valuables:** Tendency to return lost valuables
- **Getting up:** Ease of getting up in the morning
- **Interests or hobbies:** Number of interests or hobbies
- **Parents' advice:** Attitude toward parents' advice
- **Questionnaires or polls:** Attitude toward questionnaires

- **Internet usage:** Hours of internet usage
- **Finances:** Self-rated financial management
- **Shopping centres:** Attitude toward shopping centres
- **Branded clothing:** Attitude toward branded clothing
- **Entertainment spending:** Spending on entertainment
- **Spending on looks:** Spending on looks
- **Spending on gadgets:** Spending on gadgets
- **Spending on healthy eating:** Spending on healthy eating
- **Age:** Age in years
- **Height:** Height in cm
- **Weight:** Weight in kg
- **Number of siblings:** Number of siblings
- **Gender:** 1=Female, 2=Male
- **Left - right handed:** 1=Right, 2=Left
- **Education:** 1=Primary, 2=Secondary, 3=College/University, 4=Masters, 5=Doctorate
- **Only child:** 1=Yes, 2=No
- **Village - town:** 1=Village, 2=City
- **House - block of flats:** 1=House, 2=Block of flats

Source

Collected from students of Statistics at FSEV UK. Available on Kaggle.

Examples

```
data(df_responses)
head(df_responses)
```

df_responses_state	<i>Responses State Data</i>
--------------------	-----------------------------

Description

This data set contains simulated state information paired with participant numbers from the responses data set.

Usage

```
df_responses_state
```

Format

A data frame with 28 rows and 2 variables:

Participant Number Unique identifier for each participant

State State code where the participant resides (e.g., MI, OH, CO, CA, MA, WA)

Source

researchpy repo (simulated data, not real)

df_sexual_comp	<i>Sexual Compatibility Data</i>
----------------	----------------------------------

Description

This data set contains responses to questions about sexual compatibility, including scores, gender, and age.

Usage

df_sexual_comp

Format

A data frame with 22 rows and 13 variables:

Q1 Response to question 1

Q2 Response to question 2

Q3 Response to question 3

Q4 Response to question 4

Q5 Response to question 5

Q6 Response to question 6

Q7 Response to question 7

Q8 Response to question 8

Q9 Response to question 9

Q10 Response to question 10

score Total score

gender Gender of the respondent (1=Male, 2=Female)

age Age of the respondent

Source

researchpy repo

df_titanicTitanic Dataset

Description

A dataset containing information about passengers on the Titanic.

Usage

```
df_titanic
```

Format

A data frame with the following variables:

PassengerId Unique identifier for each passenger

survived Survival status (0=No, 1=Yes)

pclass Passenger class (1=1st, 2=2nd, 3=3rd)

name Name of the passenger

sex Gender of the passenger

age Age of the passenger

sibsp Number of siblings/spouses aboard the Titanic

parch Number of parents/children aboard the Titanic

ticket Ticket number

fare Passenger fare

cabin Cabin number

embarked Port of embarkation (C=Cherbourg; Q=Queenstown; S=Southampton)

boat Lifeboat number

body Body number

home.dest Home destination

Examples

```
data(df_titanic)
head(df_titanic)
```

`display_upper_lower_triangle`

Return upper diagonal from one matrix and lower diagonal from another matrix

Description

Return upper diagonal from one matrix and lower diagonal from another matrix

Usage

```
display_upper_lower_triangle(m_upper, m_lower, diagonal = NA)
```

Arguments

<code>m_upper</code>	matrix
<code>m_lower</code>	matrix
<code>diagonal</code>	if "upper" it returns upper diagonal if "lower" it returns lower diagonal if NA returns NA in diagonal otherwise it returns any value specified

Examples

```
m1<-matrix(1:9,nrow=3,ncol=3)
m2<-matrix(11:19,nrow=3,ncol=3)
display_upper_lower_triangle(m_upper=m1,m_lower=m2,diagonal="upper")
display_upper_lower_triangle(m_upper=m1,m_lower=m2,diagonal="lower")
display_upper_lower_triangle(m_upper=m1,m_lower=m2,diagonal=NA)
display_upper_lower_triangle(m_upper=m1,m_lower=m2,diagonal=1)
display_upper_lower_triangle(m_upper=m1,m_lower=m2,diagonal=c("X1","X2","X3"))
display_upper_lower_triangle(m_upper=m1,m_lower=m2,diagonal=c(1,2,3))
display_upper_lower_triangle(m_upper=m1,m2)
```

`dotnames`

Get the names of objects in the arguments

Description

Get the names of objects in the arguments

Usage

```
dotnames(...)
```

Arguments

<code>...</code>	objects
------------------	---------

Author(s)

Ananda Mahto

drop_levels	<i>Drops unused factor levels</i>
-------------	-----------------------------------

Description

Drops unused factor levels

Usage

```
drop_levels(df, factor_index = NULL, minimum_frequency = 5)
```

Arguments

df	dataframe
factor_index	numeric index of factors. If NULL the function uses is.factor() to discriminate factors
minimum_frequency	the minimum frequency each factor will have, levels with frequency bellow or equal to the defined frequency will be renamed "Other"

Examples

```
factor1<-factor(c(rep("A",10),rep("B",10)),levels=c("A","B","C","D"))
factor2<-factor(c(rep("A",10),rep("B",10)),levels=c("A","B","C","D"))
numeric1<-c(1:20)
df<-data.frame(numeric1,factor1,factor2)
df$factor1
drop_levels(df=df,minimum_frequency=9)
drop_levels(df=df,minimum_frequency=10)
```

dummy_arrange	<i>Takes a vector with multiple responses and dummy arranges it in a dataframe</i>
---------------	--

Description

Takes a vector with multiple responses and dummy arranges it in a dataframe

Usage

```
dummy_arrange(vector)
```

Arguments

vector Vector

Examples

```
vector1<-gsub(" ", "",
              generate_multiple_responce_vector(responces=c("Agree", "Hi", "All"),
              responded=1:3, length=10), fixed=TRUE)
vector2<-gsub(" ", "",
              generate_multiple_responce_vector(responces=1:4, responded=1:4, length=10),
              fixed=TRUE)
vector3<-sample(1:4, 10, replace=TRUE)
vector4<-sample(LETTERS[1:3], 10, replace=TRUE)
dummy_arrange(vector1)
dummy_arrange(vector2)
dummy_arrange(vector3)
dummy_arrange(vector4)
```

duplicate_y_axis *Duplicate the y axis on the right side of a ggplot*

Description

Takes two ggplot objects and renders p1 with the y axis of p2 mirrored onto the right side. Useful when overlaying two series with different scales or simply to frame the plot with matching axes on both sides.

Usage

```
duplicate_y_axis(p1, p2)
```

Arguments

p1 A ggplot object. This plot is drawn with the duplicated right axis.

p2 A ggplot object whose left y axis is mirrored to the right of p1. Typically the same as p1.

Value

Invisibly returns NULL. The combined plot is drawn to the current graphics device.

Examples

```
p1 <- ggplot(ChickWeight, aes(x=Time, y=weight, colour=Diet, group=Chick)) +
  geom_line() +
  ggtitle("Growth curve for individual chicks")
duplicate_y_axis(p1=p1, p2=p1)
```

environment_options	<i>Load environment options</i>
---------------------	---------------------------------

Description

Load environment options

Usage

```
environment_options()
```

Examples

```
environment_options()
```

excel_confusion_matrix	<i>Write matrix or dataframe to excel sheet</i>
------------------------	---

Description

Usefull for correlation matrices since it uses conditional formatting for matrices

Usage

```
excel_confusion_matrix(
  df,
  workbook,
  title = "Rows: Expected Collumns: Observed"
)
```

Arguments

df	dataframe or matrix
workbook	workbook
title	comment

Examples

```
filename<-"excel_confusion_matrix.xlsx"
if (file.exists(filename)) file.remove(filename)
observed<-factor(round(rnorm(10000,m=10,sd=1)))
predicted<-factor(round(rnorm(10000,m=10,sd=1)))
confusion(observed,predicted)
cm<-confusion_matrix_percent(observed,predicted)
wb<-openxlsx::createWorkbook()
excel_confusion_matrix(cm,wb)
openxlsx::saveWorkbook(wb,invisible(paste(filename)),TRUE)
```

excel_critical_value *Write matrix or dataframe to excel sheet*

Description

Usefull for generic data where conditional formating of a spesific collumn is required

Usage

```
excel_critical_value(
  df,
  workbook,
  sheet = "output",
  title = NULL,
  comment = NULL,
  numFmt = "#0.00",
  critical = NULL
)
```

Arguments

df	dataframe or matrix
workbook	workbook
sheet	sheet
title	title
comment	comment
numFmt	number formatting
critical	list in the form of (collumn1=critical_value1,collumn2=critical_value2...)

Examples

```
comment<-list(mpg="Miles/(US) gallon",
              cyl="Number of cylinders",
              disp="Displacement (cu.in.)",
              hp="Gross horsepower",
              drat="Rear axle ratio",
              wt="Weight (1000 lbs)",
              qsec="1/4 mile time",
              vs="Engine (0=V-shaped,1=straight)",
              am="Transmission (0=automatic,1=manual)",
              gear="Number of forward gears",
              carb="Number of carburetors",
              extra_comment1="test1",
              extra_comment2="test2")
filename<-"excel_critical_value.xlsx"
if (file.exists(filename)) file.remove(filename)
wb<-openxlsx::createWorkbook()
```

```

df<-generate_missing(generate_correlation_matrix())
critical<-list(X1="<0.05",X5="<0")
excel_critical_value(df=df,workbook=wb,sheet="critical",comment=list(X1="test"),
                    numFmt="#0.00",critical=critical)
openxlsx::saveWorkbook(wb,invisible(paste(filename)),TRUE)
filename<-"excel_critical_value_comment.xlsx"
if (file.exists(filename)) file.remove(filename)
wb<-openxlsx::createWorkbook()
df<-generate_missing(mtcars)
critical<-list(mpg=">20",am="=0")
excel_critical_value(df=df,workbook=wb,sheet="critical",comment=comment,
                    numFmt="#0.00",critical=critical)
openxlsx::saveWorkbook(wb,invisible(paste(filename)),TRUE)
filename<-"excel_critical_value_comment_min_max.xlsx"
if (file.exists(filename)) file.remove(filename)
wb<-openxlsx::createWorkbook()
df<-generate_missing(mtcars)
critical<-list(mpg=c(">20","<11"),am="=0")
excel_critical_value(df=df,workbook=wb,sheet="critical",comment=comment,
                    numFmt="#0.00",critical=critical)
openxlsx::saveWorkbook(wb,invisible(paste(filename)),TRUE)

```

excel_generic_format *Generic function for creating workbooks and worksheets*

Description

This function is used by excel_matrix and excel_critical_value functions

Usage

```

excel_generic_format(
  df,
  workbook,
  sheet = "output",
  title = NULL,
  comment = NULL,
  numFmt = "#0.00"
)

```

Arguments

df	dataframe or matrix
workbook	workbook
sheet	sheet
title	title
comment	comment
numFmt	number formatting

Examples

```
comment<-list(mpg="Miles/(US) gallon",
              cyl="Number of cylinders",
              disp="Displacement (cu.in.)",
              hp="Gross horsepower",
              drat="Rear axle ratio",
              wt="Weight (1000 lbs)",
              qsec="1/4 mile time",
              vs="Engine (0=V-shaped,1=straight)",
              am="Transmission (0=automatic,1>manual)",
              gear="Number of forward gears",
              carb="Number of carburetors",
              extra_comment1="test1",
              extra_comment2="test2")
mtcor<-data.frame(cor(mtcars))
filename<-"excel_generic.xlsx"
if (file.exists(filename)) file.remove(filename)
wb<-openxlsx::createWorkbook()
openxlsx::addWorksheet(wb,"sheet")
openxlsx::addWorksheet(wb,"correlation")
openxlsx::writeData(wb,sheet="sheet",x=mtcars,colNames=TRUE,rowNames=TRUE)
openxlsx::writeData(wb,sheet="correlation",x=mtcor,colNames=TRUE,rowNames=TRUE)
excel_generic_format(df=mtcars,workbook=wb,sheet="sheet",title="test",
                    comment=comment,numFmt="#0.00")
excel_generic_format(df=mtcor,workbook=wb,sheet="correlation",title="correlation",
                    comment=comment,numFmt="#0.00")
openxlsx::saveWorkbook(wb,invisible(paste(filename)),TRUE)
```

excel_matrix

Write matrix or dataframe to excel sheet

Description

Usefull for corellation matrices. It uses conditional formatting for matrices,which outlines high and low values using background color

Usage

```
excel_matrix(
  df,
  workbook,
  sheet = "output",
  title = NULL,
  comment = NULL,
  numFmt = "#0.00",
  conditional_formatting = FALSE,
  diagonal = FALSE,
  diagonal_length = nrow(df)
)
```


Arguments

df	dataframe or matrix
workbook	workbook
sheet	sheet
title	title
comment	comment
numFmt	number formatting
conditional_formatting	if TRUE it will use conditional formatting
diagonal	if TRUE it will add background fill to diagonal
diagonal_length	length of diagonal for background fill

Examples

```

comment<-list(mpg="Miles/(US) gallon",
              cyl="Number of cylinders",
              disp="Displacement (cu.in.)",
              hp="Gross horsepower",
              drat="Rear axle ratio",
              wt="Weight (1000 lbs)",
              qsec="1/4 mile time",
              vs="Engine (0=V-shaped,1=straight)",
              am="Transmission (0=automatic,1=manual)",
              gear="Number of forward gears",
              carb="Number of carburetors",
              extra_comment1="test1",
              extra_comment2="test2")

mtcor<-data.frame(cor(mtcars))
filename<-"excel_matrix.xlsx"
if (file.exists(filename)) file.remove(filename)
wb<-openxlsx::createWorkbook()
excel_matrix(mtcars,wb,sheet="matrix",comment=comment,
             conditional_formatting=TRUE,diagonal=FALSE)
excel_matrix(mtcars,wb,sheet="diagonal_non_square",comment=comment,
             conditional_formatting=FALSE,diagonal=TRUE)
excel_matrix(mtcars[1:10,1:10],wb,sheet="diagonal_square",comment=comment[1:10],
             conditional_formatting=FALSE,diagonal=TRUE)
excel_matrix(mtcars,wb,sheet="matrix_diagonal_non_square",comment=comment,
             conditional_formatting=TRUE,diagonal=TRUE)
excel_matrix(mtcars[1:10,1:10],wb,sheet="matrix_diagonal_square",comment=comment[1:10],
             conditional_formatting=TRUE,diagonal=TRUE)
excel_matrix(mtcors,wb,sheet="r",comment=comment,
             conditional_formatting=FALSE,diagonal=FALSE)
excel_matrix(mtcor,wb,sheet="conditional_formatting_r",comment=comment,
             conditional_formatting=TRUE,diagonal=TRUE)
openxlsx::saveWorkbook(wb,invisible(paste(filename)),TRUE)

```

extract_components	<i>Extract variance components from model</i>
--------------------	---

Description

Extract variance components from model

Usage

```
extract_components(model, title = "")
```

Arguments

model	model containing variance components
title	plot title

Examples

```
design<-expand.grid(time=1:3,item=1:3,person=1:10)
design<-change_data_type(design,type="factor")
design$response<-rowSums(change_data_type(design[,1:2],type="numeric"))+rnorm(90,0,0.1)
model<-mixlm::lm(response~r(time)*r(person)+r(item)*r(person),data=design)
extract_components(model)
```

fixed	<i>Mark a pattern as a fixed string</i>
-------	---

Description

Flags a pattern to be interpreted as a literal string rather than a regular expression. Pass the result to `str_replace`, `str_replace_all`, `str_count`, or `str_split_fixed` wherever you want exact character matching instead of regex matching.

Flags a pattern to be interpreted as a literal string rather than a regular expression. Pass the result to `str_replace`, `str_replace_all`, `str_count`, or `str_split_fixed` wherever you want exact character matching instead of regex matching.

Usage

```
fixed(pattern)
```

```
fixed(pattern)
```

Arguments

pattern	A character string to match literally.
---------	--

Value

The same character string with class "fixed_pattern".
The same character string with class "fixed_pattern".

Examples

```
# Without fixed(), "." matches any character (regex)
str_replace_all("a.b.c", ".", "-")

# With fixed(), "." matches only a literal dot
str_replace_all("a.b.c", fixed("."), "-")
# Without fixed(), "." matches any character (regex)
str_replace_all("a.b.c", ".", "-")

# With fixed(), "." matches only a literal dot
str_replace_all("a.b.c", fixed("."), "-")
```

flatten_list	<i>Flatten two dimensional list</i>
--------------	-------------------------------------

Description

Flatten two dimensional list

Usage

```
flatten_list(mydata)
```

Arguments

mydata list with two dimensions

generate_comparisons_matrix	<i>Generate comparisons matrix</i>
-----------------------------	------------------------------------

Description

Generate comparisons matrix

Usage

```
generate_comparisons_matrix(items)
```

Arguments

items number of items

Examples

```
generate_comparisons_matrix(2)
generate_comparisons_matrix(3)
generate_comparisons_matrix(4)
generate_comparisons_matrix(5)
generate_comparisons_matrix(6)
```

```
generate_correlation_matrix
```

Generate dataframe which outputs a predetermined correlation matrix

Description

Generate dataframe which outputs a predetermined correlation matrix

Usage

```
generate_correlation_matrix(correlation_matrix, n_rows = 10)
```

Arguments

correlation_matrix	correlation matrix of resulting dataframe
n_rows	number of rows to generate

Examples

```
df<-data.frame(matrix(.999,ncol=2,nrow=2))
correlation_matrix<-as.matrix(df)
diag(correlation_matrix)<-1
df<-generate_correlation_matrix(correlation_matrix,nrows=100)
stats::cor(df)
```

```
generate_data
```

Generate dataframe with random numbers

Description

Generate dataframe with random numbers

Usage

```
generate_data(
  nrows = 10,
  ncols = 5,
  mean = 0,
  sd = 1,
  min = 1,
  max = 5,
  type = "normal"
)
```

Arguments

nrows	number of rows to generate
ncols	number of columns to generate
mean	mean of generated vectors
sd	standard deviation of generated vectors
min	minimum value in generated vector
max	maximum value in generated vector
type	character "normal" "uniform"

Examples

```
generate_data(nrows=10,ncols=5,mean=0,sd=1,type="normal")
generate_data(nrows=10,ncols=5,min=1,max=5,type="uniform")
```

generate_factor	<i>Generate dataframe of factors</i>
-----------------	--------------------------------------

Description

Generate dataframe of factors

Usage

```
generate_factor(vector = LETTERS[1:5], nrows = 2, ncols = 10, type = "random")
```

Arguments

vector	factor pool
nrows	number of rows to generate
ncols	number of columns to generate
type	"balanced" or "random" "balanced" generates balanced factor vectors, "random" generates random factor vectors

Examples

```
generate_factor(vector=LETTERS[1:5],ncols=5,nrows=10,type="random")
generate_factor(vector=LETTERS[1:5],ncols=5,nrows=10,type="balanced")
generate_factor(vector=LETTERS[1:5],ncols=1,nrows=10,type="balanced")
generate_factor(vector=LETTERS[1:5],ncols=1,nrows=10,type="random")
```

generate_matrix_A	<i>Generate Matrix A</i>
-------------------	--------------------------

Description

Generate Matrix A

Usage

```
generate_matrix_A(blocks = 3, items = 3)
```

Arguments

blocks	number of blocks
items	number of items per block

Examples

```
generate_matrix_A(blocks=3,items=3)
```

generate_matrix_lambda_hat	<i>Generate matrix lambda for spesified number of comparisons</i>
----------------------------	---

Description

Generate matrix lambda for spesified number of comparisons

Usage

```
generate_matrix_lambda_hat(blocks = 3, items = 3)
```

Arguments

blocks	number of blocks
items	number of items per block

Examples

```
generate_matrix_lambda_hat(blocks=3,items=4)
```

generate_missing	<i>Generate missing data</i>
------------------	------------------------------

Description

Generate missing data

Usage

```
generate_missing(df, missing = 5)
```

Arguments

df	vector or dataframe
missing	number of missing data per vector

Examples

```
generate_missing(rnorm(10),missing=5)
generate_missing(generate_data(nrow=10,ncol=2),missing=5)
```

generate_multiple_responce_vector	<i>Generate multiple responce vector</i>
-----------------------------------	--

Description

Generate multiple responce vector

Usage

```
generate_multiple_responce_vector(
  responce = 1:4,
  responded = 1:4,
  length = 10
)
```

Arguments

responce	unique categories allowed
responded	number of categories observed in iteration
length	length of returned vector

Examples

```
generate_multiple_responce_vector(responce=1:4,responded=1:4,length=10)
```

generate_string	<i>Generate random strings</i>
-----------------	--------------------------------

Description

Generate random strings

Usage

```
generate_string(  
  vector = c(LETTERS, letters, 0:9),  
  vector_length = 1,  
  nchar = 5  
)
```

Arguments

vector	character pool
vector_length	number of strings to generate
nchar	Length of generated strings

Examples

```
generate_string(nchar=10)  
generate_string(nchar=10,vector_length=10)
```

generate_unique_comparisons_index	<i>Generate index for unique comparisons</i>
-----------------------------------	--

Description

Generate index for unique comparisons

Usage

```
generate_unique_comparisons_index(items)
```

Arguments

items	number of items
-------	-----------------

Examples

```
generate_unique_comparisons_index(1)
generate_unique_comparisons_index(2)
generate_unique_comparisons_index(3)
generate_unique_comparisons_index(4)
generate_unique_comparisons_index(5)
generate_unique_comparisons_index(6)
```

getfwp	<i>Get working file path</i>
--------	------------------------------

Description

Get working file path

Usage

```
getfwp()
```

Examples

```
#getfwp()
```

get_script_directory	<i>Get script directory</i>
----------------------	-----------------------------

Description

Returns the directory of the currently active script as a string with a trailing slash. Works across multiple environments: RStudio, command line execution, and generic R sessions.

Usage

```
get_script_directory()
```

Details

The function tries three approaches in order:

1. If RStudio is available, uses `rstudioapi` to get the active document path
2. If running from the command line via `Rscript --file=`, parses the file argument
3. Falls back to `getwd()` as a last resort

Value

A character string with the directory path, always ending with "/"

Note

The fallback to `getwd()` may not reflect the script’s actual location if the working directory has been changed during the session.

Examples

```
# Returns the directory of the active script in RStudio
directory <- get_script_directory()
directory
```

hinvert_title_grob	<i>Invert a title grob horizontally</i>
--------------------	---

Description

Helper used by `duplicate_y_axis` to mirror a grob’s width layout and text alignment so it renders correctly on the right-hand side of a plot.

Usage

```
hinvert_title_grob(grob)
```

Arguments

grob A grob object (titleGrob or similar) to invert.

Value

The modified grob.

icc_cfa	<i>Select responses for each dimension</i>
---------	--

Description

Select responses for each dimension

Usage

```
icc_cfa(eta, gamma, lambda, psi)
```

Arguments

eta	eta or ability
gamma	gamma or threshold
lambda	lambda or loading
psi	psi or error

Examples

```
icc_cfa(seq(-6,6,.1),1,1,1)
```

increase_index	<i>index dataframe picks</i>
----------------	------------------------------

Description

index dataframe picks

Usage

```
increase_index(blocks, items)
```

Arguments

blocks	number of blocks
items	number of items per block

Examples

```
increase_index(3,3)
```

install_all_packages	<i>Install all packages available in CRAN</i>
----------------------	---

Description

Install all packages available in CRAN

Usage

```
install_all_packages()
```

Details

Install all packages available in CRAN. Already installed packages are not downloaded or installed

install_load	<i>Install and load multiple packages</i>
--------------	---

Description

Install and load multiple packages. If packages exist, they are loaded, if packages don't exist, they are downloaded installed and loaded

Usage

```
install_load(package)
```

Arguments

package	Vector Package names
---------	----------------------

Author(s)

Steven Worthington

Examples

```
install_load("car")
install_load(c("car", "ggplot2"))
```

key_to_cfa_model	<i>Converts key to cfa model specification</i>
------------------	--

Description

This function uses the key specification used in report_alpha function and converts the key to a cfa model specification

Usage

```
key_to_cfa_model(key)
```

Arguments

key	index of trait names and items constituting a trait
-----	---

Examples

```
population_model<- 't1=~x1+.5*x2+.5*x3
                    t2=~x4+.5*x5+.5*x6
                    t3=~x7+.5*x8+.5*x9'
model_data<-lavaan::simulateData(population_model,sample.nobs=1000)
key<-list(f1=paste0("x",1:3),f2=paste0("x",4:6),f3=paste0("x",7:9))
model<-key_to_cfa_model(key)
fit<-lavaan::cfa(model,model_data)
```

k_fold	<i>K-Fold train test sampling</i>
--------	-----------------------------------

Description

Splits a dataframe into train and test dataframes for model evaluation. Prepared data include data objects for xgboost.

Usage

```
k_fold(df, model_formula, k = 10)
```

Arguments

df	Dataframe containing the dataset to be split.
model_formula	Model formula specifying the predictors and outcome variable.
k	Integer value representing the number of folds. Defaults to 10.

Details

This function performs k-fold cross-validation by splitting the input dataframe into k folds. Each fold serves as a test set once, while the remaining k-1 folds form the training set.

The function prepares data objects for xgboost model training and evaluation, including train/test datasets and xgboost DMatrix objects.

The output is a list containing the following elements: -'f': List of train and test datasets for each fold. -'index': Vector of fold indices. -'model_formula': Model formula used for generating the datasets. -'variables': Names of the variables in the model formula. -'predictors': Names of the predictor variables. -'outcome': Name of the outcome variable. -'xgb': List of xgboost DMatrix objects for training and testing.

Examples

```
# Example with the 'infert' dataset
infert_formula<-formula(case~education+spontaneous+induced)
result<-k_fold(infert,k=10,model_formula=infert_formula)

# Example with the 'mtcars' dataset
model_formula<-as.formula(mpg~cyl+disp+hp+drat+wt+qsec+vs+am+gear+carb)
result<-k_fold(mtcars,k=2,model_formula=model_formula)
```

k_sample

*Train test sampling***Description**

Splits a dataframe into train and test dataframes for model evaluation. Prepared data include data objects for xgboost.

Usage

```
k_sample(df, model_formula, k = 1)
```

Arguments

df	Dataframe containing the dataset to be split.
model_formula	Model formula specifying the predictors and outcome variable.
k	Integer value representing the number of folds. Defaults to 1 (train-test split).

Details

This function performs k-fold cross-validation or a simple train-test split (if k=1) by splitting the input dataframe into k folds. Each fold serves as a test set once, while the remaining k-1 folds form the training set.

The function prepares data objects for xgboost model training and evaluation, including train, test, and validation datasets and xgboost DMatrix objects.

The output is a list containing the following elements: -'f': List of train, test, and validation datasets for each fold. -'index': Vector of fold indices. -'model_formula': Model formula used for generating the datasets. -'variables': Names of the variables in the model formula. -'predictors': Names of the predictor variables. -'outcome': Name of the outcome variable. -'xgb': List of xgboost DMatrix objects for training, testing, and validation.

Examples

```
# Example with the 'infert' dataset
infert_formula<-formula(case~education+spontaneous+induced)
result<-k_sample(df=infert,k=10,model_formula=infert_formula)

# Example with the 'mtcars' dataset
model_formula<-formula(mpg~cyl+disp+hp+drat+wt+qsec+vs+am+gear+carb)
result<-k_sample(df=mtcars,k=10,model_formula=model_formula)
```

matrix_triangle	<i>Return upper or lower matrix triangle</i>
-----------------	--

Description

Return upper or lower matrix triangle

Usage

```
matrix_triangle(m, off_diagonal = NA, diagonal = NULL, type = "lower")
```

Arguments

m	matrix
off_diagonal	off diagonal value
diagonal	diagonal value. If NULL it returns the diagonal of the input matrix
type	"upper" displays upper triangle, "lower" displays lower triangle

Examples

```
m<-matrix(1:9,nrow=3,ncol=3)
matrix_triangle(m=m)
matrix_triangle(m=m,diagonal=NA,type="lower")
matrix_triangle(m=m,diagonal=NULL,type="lower")
matrix_triangle(m=m,diagonal=NA,type="upper")
matrix_triangle(m=m,diagonal=NULL,type="upper")
```

mean_sd_alpha	<i>Mean and SD</i>
---------------	--------------------

Description

Mean and SD

Usage

```
mean_sd_alpha(df, divisor = NULL)
```

Arguments

df	dataframe with one dimension
divisor	number to use for dividing the rowsums

Examples

```
set.seed(12345)
df<-data.frame(matrix(.5,ncol=6,nrow=6))
correlation_martix<-as.matrix(df)
diag(correlation_martix)<-1
df<-round(generate_correlation_matrix(correlation_martix,nrows=1000),0)+5
mean_sd_alpha(df)
mean_sd_alpha(df,divisor=100)
```

mgsub	<i>Sub for multiple patterns</i>
-------	----------------------------------

Description

Sub for multiple patterns

Usage

```
mgsub(mydata, pattern, replacement, ...)
```

Arguments

mydata	Character
pattern	Character to search for
replacement	Replacement character
...	arguments passed to gsub

Examples

```
mgsub(mydata="#$%^&*_"+",pattern=c("%","*"),"REPLACE",fixed=TRUE)
```

min_max_index	<i>Return the minimum and maximum index of a vector</i>
---------------	---

Description

Return the minimum and maximum index of a vector

Usage

```
min_max_index(vector)
```

Arguments

vector	Vector
--------	--------

Examples

```
vector1<-c(1,2,3,4,5,4,3,2,1)
vector2<-c(1,2,3,4,5,5,3,2,1)
vector3<-c(1,2,3,5,5,4,3,2,1)
vector4<-c(1,2,3,4,6,4,3,2,1)
vector5<-c(1,6,3,4,6,4,3,2,1)
vector<-vector1
which(vector==max(vector),arr.ind=TRUE)
which(vector==min(vector),arr.ind=TRUE)
min_max_index(vector1)
min_max_index(vector2)
min_max_index(vector3)
min_max_index(vector4)
min_max_index(vector5)
```

model_loadings	<i>Pattern and structure matrix</i>
----------------	-------------------------------------

Description

Pattern and structure matrix

Usage

```
model_loadings(model, cut = NULL, matrix_type = "pattern", sort = TRUE, ...)
```

Arguments

model	psych EFA model
cut	cut point for loadings
matrix_type	"pattern" "structure" "all"
sort	if TRUE it will sort loadings
...	arguments passed to psych::fa.sort

Note

Check to see if you have multicollinearity values above .8 in the matrix are problematic
Structure matrix represents Loadings after rotation
Pattern matrix represents Loadings before rotation

Examples

```
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="pa",oblique.scores=TRUE)
model_loadings(model=model,cut=NULL,matrix_type="pattern")
model_loadings(model=model,cut=0.4,matrix_type="structure")
model_loadings(model=model,cut=0.4,matrix_type="all",sort=FALSE)
```

off_diagonal_index	<i>index of off diagonal</i>
--------------------	------------------------------

Description

index of off diagonal

Usage

```
off_diagonal_index(length)
```

Arguments

length	length of diagonal
--------	--------------------

Examples

```
off_diagonal_index(length=6)
```

outlier_summary	<i>Percent of outliers in vector</i>
-----------------	--------------------------------------

Description

Percent of outliers in vector

Usage

```
outlier_summary(vector)
```

Arguments

vector	numeric vector
--------	----------------

Details

returns dataframe

Examples

```
vector<-generate_missing(rnorm(1000))
df<-generate_missing(mtcars[,1:2])
outlier_summary(vector)
data.frame(sapply(mtcars,outlier_summary))
```

```
output_compare_model_logistic
      Compare logistic regression models models
```

Description

Compare logistic regression models models

Usage

```
output_compare_model_logistic(model1, model2)
```

Arguments

model1	object glm model
model2	object glm model

Examples

```
modelcategoricalpredictor<-glm(case~education,data=infert,family=binomial)
modelcontinuouspredictor<-glm(case~age,data=infert,family=binomial)
modeltwopredictors<-glm(case~education*age,data=infert,family=binomial)
modelmultiple<-glm(case~education*age*parity,data=infert,family=binomial)
anova(modelcategoricalpredictor,modelcontinuouspredictor)
output_compare_model_logistic(model1=modelcategoricalpredictor,
                              model2=modeltwopredictors)
output_compare_model_logistic(model1=modelcontinuouspredictor,
                              model2=modeltwopredictors)
output_compare_model_logistic(model1=modelcontinuouspredictor,
                              model2=modelcategoricalpredictor)
```

```
output_separator      Output separator
```

Description

Heading, main output, and instructions for output for the console environment

Usage

```
output_separator(
  string,
  output = NULL,
  instruction = NULL,
  length = getOption("width")/2
)
```

Arguments

string	Title of output
output	object to print
instruction	Character provided instructions regarding the output
length	Numeric Length of separator measured in number of characters

Examples

```
output_separator(string="TEST",output="TEST",instruction="TEST",length=100)
output_separator(string="TEST",instruction="TEST",length=100)
output_separator(string="TEST",output="TEST",length=100)
output_separator(string="TEST")
```

padNA	<i>pad NA's to collumns in dataframe</i>
-------	--

Description

pad NA's to collumns in dataframe

Usage

```
padNA(df, rowsneeded, first = TRUE)
```

Arguments

df	dataframe
rowsneeded	Numeric number of rows needed
first	Boolean

Author(s)

Ananda Mahto

plot_acf	<i>Plot autocorrelation function of correlation covariance and partial correlation</i>
----------	--

Description

uses ggplot

Usage

```
plot_acf(df, lag.max = length(df), base_size = 10, title = "")
```

Arguments

df	ts object
lag.max	maximum lags to include
base_size	base font size
title	plot title

Details

returns plot

Examples

```
ts_data<-ts(UKDriverDeaths,start=1969,end=1984,frequency=12)
plot_acf(df=ts_data,base_size=20)
```

plot_boxplot	<i>Boxplot</i>
--------------	----------------

Description

Boxplot

Usage

```
plot_boxplot(df, title = "", base_size = 10)
```

Arguments

df	dataframe or vector with continous or ordinal data
title	Plot title
base_size	numeric base font size

Details

uses ggplot

Examples

```
vector<-generate_missing(rnorm(1000))
df<-generate_missing(mtcars[,1:2])
plot_boxplot(df=vector)
plot_boxplot(df=generate_missing(vector))
plot_boxplot(df=df)
```

plot_cfa	<i>Batch-plot CFA across layouts and display modes</i>
----------	--

Description

Drop-in replacement for plot_cfa() — same signature, returns a named list of ggplot objects instead of base-graphics recordings.

Usage

```
plot_cfa(model, ...)
```

Arguments

- model A fitted lavaan object
- ... Extra arguments forwarded to plot_cfa_gg()

Value

Named list of ggplot objects (same keys as the original plot_cfa)

plot_cfa_gg	<i>Plot CFA model (semPlot-free)</i>
-------------	--------------------------------------

Description

Plot CFA model (semPlot-free)

Usage

```
plot_cfa_gg(
  model,
  what = c("std", "est", "eq"),
  layout = c("tree", "circle", "spring"),
  label_size = 3.2,
  edge_label_size = 2.6,
  color_latent = "#4f8ef7",
  color_observed = "#e8eaf0",
  ...
)
```

Arguments

model	A fitted lavaan object
what	One of "std" (standardized), "est" (unstandardized), or "eq" (parameter labels)
layout	One of "tree", "circle", or "spring"
label_size	Size of node labels
edge_label_size	Size of path coefficient labels
color_latent	Fill colour for latent variable nodes
color_observed	Fill colour for observed variable nodes
...	Ignored (kept for API compatibility with plot_cfa)

Value

A named list of ggplot objects

Examples

```
model='LATENT1=~X1+X2+X3
      LATENT2=~X4+X5+X6'
df<-lavaan::simulateData(model=model,model.type="cfa",
                        return.type="data.frame",sample.nobs=100)
df<-generate_missing(df)
fit<-lavaan::cfa(model,data=df,missing="ML")
plot_cfa_gg(fit,what="std")
plot_cfa_gg(fit,what="std",layout="tree")
plot_cfa_gg(fit,what="std",layout="circle")
plot_cfa_gg(fit,what="std",layout="spring")
```

plot_confusion	<i>Plot confusion matrix</i>
----------------	------------------------------

Description

This function creates a confusion matrix plot with observed and predicted outcomes, including row and column percentages, and various accuracy metrics.

Usage

```
plot_confusion(observed, predicted, base_size = 10, title = "")
```

Arguments

observed	Vector of observed outcomes. This can be numeric or factor values representing the true class labels.
predicted	Vector of predicted outcomes. This should have the same length as the observed vector and represent the predicted class labels.
base_size	Integer value representing the base font size for the plot. Defaults to 10.
title	String representing the title of the plot. Defaults to an empty string.

Details

This function generates a confusion matrix plot using ggplot2. It provides a visual representation of the confusion matrix with observed outcomes on the x-axis and predicted outcomes on the y-axis. The cells of the matrix are filled with the count of observations and annotated with the corresponding values.

The plot also includes various accuracy metrics in the caption, such as: -Overall Accuracy: Proportion of correctly classified observations (diagonal elements). -Off-diagonal Accuracy: Proportion of misclassified observations (off-diagonal elements). -Cohen's Kappa (Unweighted, Linear, and Squared): Measures the agreement between observed and predicted outcomes.

Examples

```
# Example with numeric class labels
plot_confusion(observed=c(1,2,3,1,2,3),predicted=c(1,2,3,1,2,3))

# Example with factor class labels
observed<-c(rep("male",10),rep("female",10),"male","male")
predicted<-c(rep("male",10),rep("female",10),"female","female")
plot_confusion(observed=observed,predicted=predicted)
```

plot_corrplot	<i>Correlation matrix plots</i>
---------------	---------------------------------

Description

Correlation matrix plots

Usage

```
plot_corrplot(mydata, title = "", base_size = 10, fill_limits = c(-1, 0, 1))
```

Arguments

mydata	correlation matrix
title	plot title
base_size	base font size
fill_limits	lower and upper limit for fill

Examples

```
plot_corrplot(stats::cor(mtcars), title="Correlation")
plot_corrplot(stats::cor(mtcars), base_size=20)
```

plot_crosstable	<i>Plot crosstables</i>
-----------------	-------------------------

Description

Plot crosstables

Usage

```
plot_crosstable(
  df,
  factor_index,
  combinations = NULL,
  shape = 16,
  angle = 0,
  base_size = 10,
  title = ""
)
```

Arguments

df	dataframe
factor_index	index of factors
combinations	index of comparisons
shape	shape of points
angle	angle of xaxis labels
base_size	base font size
title	plot title

Examples

```
combinations<-data.frame(index1=c("vs","am","gear"),index2=c("cyl","cyl","cyl"))
plot_crosstable(df=mtcars,factor_index=8:9)
plot_crosstable(df=mtcars,combinations=combinations)
```

plot_histogram	<i>Histograms with density function</i>
----------------	---

Description

Histograms with density function

Usage

```
plot_histogram(
  df,
  bins = 30,
  title = "",
  base_size = 10,
  xlims = NULL,
  fill = "gray25",
  color = "gray50",
  ylab = "Count"
)
```

Arguments

df	dataframe or vector with continous or ordinal data
bins	number of bars to display
title	plot title
base_size	numeric base font size
xlims	x axis limits
fill	color of bar
color	color of bar outline
ylab	y label

Details

uses ggplot

Examples

```
vector<-generate_missing(rnorm(1000))
df<-generate_missing(mtcars[,1:2])
plot_histogram(df=vector)
plot_histogram(df=df,xlims=c(0,50))
plot_histogram(df=df)
plot_mplot(plotlist=plot_histogram(df=mtcars),cols=4)
```

plot_icc_thurstonian	<i>Plot thurstonian icc</i>
----------------------	-----------------------------

Description

Plot icc curves for binary thurstonian coded items for a single dimension using the compute_icc_thurstonian function

Usage

```
plot_icc_thurstonian(mydata, title = "Item Characteristic Curve")
```

Arguments

mydata	dataframe from compute_icc_thurstonian function
title	plot title

Examples

```
gamma<-c(0.556,-1.253,-1.729,0.618,0.937,0.295,-0.672,-1.127,-0.446,0.632,1.147,0.498)
psi<-c(2.172,1.883,2.055,1.869,2.231,2.100,1.762,1.803,1.565,1.892,1.794,1.686)
lambda<-c(1.082,1.082,-1.297,-1.297,0.802,0.802,1.083,1.083)
gamma<-gamma[response_dimension(c(1:12),3,c(1,2))]
psi<-psi[response_dimension(c(1:12),3,c(1,2))]
eta<-seq(-6,6,by=1)
result<-compute_icc_thurstonian(eta=eta,gamma=gamma,lambda=lambda,psi=psi,plot=TRUE)
plot_icc_thurstonian(result$icc)
```

plot_interaction	<i>Plot two-way interaction graphs for all IV pair and DV combinations</i>
------------------	--

Description

For every unique pair of independent variables (IV1 x IV2) and every dependent variable (DV), produces a line-and-point interaction plot with group means on the y-axis. IV1 levels appear on the x-axis (flipped) and IV2 levels are represented by colour and line group. Optional error bars and per-group sample size annotations are included.

When the number of combinations exceeds four times the available CPU cores the plots are produced in parallel via `future.apply`, otherwise sequentially.

Usage

```
plot_interaction(
  df,
  dv,
  iv,
  base_size = 20,
  type = "se",
  order_factor = TRUE,
  title = "",
  note = ""
)
```

Arguments

<code>df</code>	A data frame containing both the independent and dependent variables.
<code>dv</code>	Integer vector of column indices for the continuous dependent variables.
<code>iv</code>	Integer vector of column indices for the categorical independent variables. Columns are coerced to factors automatically.
<code>base_size</code>	Base font size in pt passed to <code>theme_bw</code> . Default 20.
<code>type</code>	Type of error bar to display. One of "se" (standard error), "ci" (95% confidence interval), "sd" (standard deviation), or "" (no error bars). Default "se".
<code>order_factor</code>	Logical. If TRUE factor levels on the x-axis are sorted by the group mean of the DV (descending). Default TRUE.
<code>title</code>	Character. Plot title applied to every panel. Default "".
<code>note</code>	Character. Caption / footnote appended to every panel. Default "".

Value

A named list with three elements:

- `plot_data` — named list of summary data frames (one per IV1-IV2-DV combination) as returned by `Rmisc::summarySE`.

- `plot_data_df` — single data frame combining all summary data frames row-wise.
- `plots` — named list of ggplot objects (one per combination).

All list elements are named "iv1_iv2_dv".

Examples

```
# Single DV, two IVs
plot_interaction(df=mtcars, dv=2, iv=8:9, base_size=20, type="se")

# Multiple DVs, two IVs
plot_interaction(df=mtcars, dv=2:3, iv=8:9, base_size=20, type="se")
plot_interaction(df=mtcars, dv=2:3, iv=8:9, base_size=20, type="ci")
plot_interaction(df=mtcars, dv=2:3, iv=9:10, base_size=20, type="sd")

# No error bars, unordered factor axis
plot_interaction(df=mtcars, dv=2, iv=9:10, base_size=20, type="", order_factor=FALSE)
```

<code>plot_irt_onefactor</code>	<i>Return data for irt plots</i>
---------------------------------	----------------------------------

Description

Return data for irt plots

Usage

```
plot_irt_onefactor(model, theta = seq(-6, 6, 0.1), title = "", base_size = 10)
```

Arguments

<code>model</code>	object mirt
<code>theta</code>	theta
<code>title</code>	plot title
<code>base_size</code>	base size

Examples

```
cormatrix<-psych::sim.rasch(nvar=5,n=50000,low=-4,high=4,d=NULL,a=1,mu=0,sd=1)$items
model<-mirt::mirt(cormatrix,1,empiricalhist=TRUE,calcNull=TRUE)
plot_irt_onefactor(model=model,base_size=10,title="Normal Test")
cormatrix<-psych::sim.rasch(nvar=5,n=50000,low=-6,high=-4,d=NULL,a=1,mu=0,sd=1)$items
model<-mirt::mirt(cormatrix,1,empiricalhist=TRUE,calcNull=TRUE)
plot_irt_onefactor(model=model,base_size=10,title="Easy Items")
cormatrix<-psych::sim.rasch(nvar=5,n=50000,low=4,high=6,d=NULL,a=1,mu=0,sd=1)$items
model<-mirt::mirt(cormatrix,1,empiricalhist=TRUE,calcNull=TRUE)
plot_irt_onefactor(model=model,base_size=10,title="Difficult Items")
cormatrix<-psych::sim.rasch(nvar=5,n=50000,low=-4,high=-4,d=NULL,a=0.01,mu=0,sd=1)$items
```

```
model<-mirt::mirt(cormatrix,1,empiricalhist=TRUE,calcNull=TRUE)
plot_irt_onefactor(model=model,base_size=10,title="Low Discrimination")
cormatrix<-psych::sim.poly(nvar=5,n=50000,low=-4,high=4,a=1,c=0,z=1,d=NULL,
                           mu=0,sd=1,cat=5,mod="logistic",theta=NULL)$items
model<-mirt::mirt(cormatrix,1,itemtype="graded")
plot_irt_onefactor(model=model,base_size=10,title="graded response")
```

plot_loadings	<i>Plot loadings</i>
---------------	----------------------

Description

Plot loadings

Usage

```
plot_loadings(
  model,
  matrix_type = NULL,
  title = "",
  base_size = 10,
  color = c("#5E912C", "white", "#5F2C91"),
  sort = TRUE
)
```

Arguments

model	psych EFA model
matrix_type	"pattern" "structure"
title	plot title
base_size	base font size
color	color ranges for heatmap
sort	TRUE or FALSE sort loadings

Examples

```
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="pa",oblique.scores=TRUE)
plot_loadings(model=model,matrix_type="structure")
plot_loadings(model=model,matrix_type="pattern")
cm<-matrix(c(1,.8,.8,.1,.1,.1,
             .8,1,.8,.1,.1,.1,
             .8,.8,1,.1,.1,.1,
             .1,.1,.1,1,.8,.8,
             .1,.1,.1,.8,1,.8,
             .1,.1,.1,.8,.8,1),
           ncol=6,nrow=6)
df1<-generate_correlation_matrix(cm,nrows=10000)
```

```

model1<-psych::fa(df1,nfactors=2,rotate="oblimin",fm="pa",oblique.scores=TRUE)
plot_loadings(model=model1,matrix_type="pattern",base_size=30)
cm<-matrix(c(1,.1,.1,.1,.1,.1,
             .1,1,.1,.1,.1,.1,
             .1,.1,1,.1,.1,.1,
             .1,.1,.1,1,.8,.8,
             .1,.1,.1,.8,1,.8,
             .1,.1,.1,.8,.8,1),
           ncol=6,nrow=6)
df1<-generate_correlation_matrix(cm,nrows=10000)
model2<-psych::fa(df1,nfactors=2,rotate="oblimin",fm="pa",oblique.scores=TRUE)
plot_loadings(model=model2,matrix_type="pattern",base_size=30)
cm<-matrix(c(1,.01,.01,.01,.01,.01,
             .01,1,.01,.01,.01,.01,
             .01,.01,1,.01,.01,.01,
             .01,.01,.01,1,.01,.01,
             .01,.01,.01,.01,1,.01,
             .01,.01,.01,.01,.01,1),
           ncol=6,nrow=6)
df1<-generate_correlation_matrix(cm,nrows=10000)
model3<-psych::fa(df1,nfactors=2,rotate="oblimin",fm="pa",oblique.scores=TRUE)
plot_loadings(model=model3,matrix_type="pattern",base_size=10)

```

plot_logistic_model *Logistic model plot*

Description

Logistic model plot

Usage

```
plot_logistic_model(df, outcome = "outcome", title = "", base_size = 10)
```

Arguments

df	dataframe with predictor and outcome outcome should be last
outcome	name of outcome variable
title	Character plot title
base_size	base font size

Examples

```

df<-data.frame(outcome=c(rep(1,10),rep(0,10)),
               pd1=c(rep(1,11),rep(0,9)),
               pd2=c(rep(1,9),rep(0,11)),
               pc1=c(rnorm(10,mean=5),rnorm(10,mean=10)),
               pc2=c(rnorm(10,mean=5),rnorm(10,mean=20)))
plot_logistic_model(df=df,base_size=15)

```

plot_mosaic	<i>Plot mosaic plots</i>
-------------	--------------------------

Description

Plot mosaic plots

Usage

```
plot_mosaic(df, factor_index, base_size = 10, title = "")
```

Arguments

df	dataframe
factor_index	index of factors
base_size	base font size
title	plot title

Examples

```
plot_mosaic(df=mtcars,factor_index=8:9)
plot_mosaic(df=mtcars,factor_index=9:10)
```

plot_mtmm	<i>Plot multitrait multimethod matrix</i>
-----------	---

Description

Plot multitrait multimethod matrix

Usage

```
plot_mtmm(df, key, method, subject, title = "")
```

Arguments

df	dataframe
key	List index of trait names and items constituring a trait
method	name of dataframe collumn spesifying the method used for the row observed
subject	name of dataframe collumn spesifying subject id
title	plot title

Examples

```

population_model<- 't1=~x1+.9*x2+.9*x3
                    t2=~x4+.9*x5+.9*x6
                    t3=~x7+.9*x8+.9*x9'

model_data<-lavaan::simulateData(population_model,sample.nobs=1000)
model_data<-model_data[sample(1:1000,1000,TRUE),]
model_data<-rbind(model_data,model_data,model_data)
model_data$method<-c(rep("m1",1000),rep("m2",1000),rep("m3",1000))
model_data$id<-rep(1:1000,3)
key<-list(t1=paste0("x",1:3),t2=paste0("x",4:6),t3=paste0("x",7:9))
plot_mtmm(df=model_data,key=key,method="method",subject="id")

```

plot_multiplot

*Multiple ggplot plots in one graph***Description**

Multiple ggplot plots in one graph

Usage

```
plot_multiplot(..., plotlist = NULL, cols = 2, layout = NULL)
```

Arguments

...	plot objects
plotlist	a list of plots
cols	number of columns in layout
layout	a matrix specifying the layout. If present,'cols' is ignored

Examples

```

p1<-ggplot(ChickWeight,aes(x=Time,y=weight,colour=Diet,group=Chick))+
  geom_line()+
  ggtitle("Growth curve for individual chicks")+
  theme_bw()
p2<-ggplot(ChickWeight,aes(x=Time,y=weight,colour=Diet))+
  geom_point(alpha=.3)+
  geom_smooth(alpha=.2,size=1,method="loess",formula="y~x")+
  ggtitle("Fitted growth curve per diet")+
  theme_bw()
p3<-ggplot(subset(ChickWeight,Time==21),aes(x=weight,colour=Diet))+
  geom_density()+
  ggtitle("Final weight, by diet")+theme_bw()
p4<-ggplot(subset(ChickWeight,Time==21),aes(x=weight,fill=Diet))+
  geom_histogram(colour="black",binwidth=50)+facet_grid(Diet~.)+
  ggtitle("Final weight, by diet")+theme_bw()
cars_plot<-plot_histogram(mtcars)

```

```

plot_multiplot(p1,p2,p3,p4,cols=2)
plot_multiplot(plotlist=plot_histogram(mtcars[,1:4]),cols=2)
plot_multiplot(plotlist=plot_histogram(mtcars),layout=matrix(1:4,ncol=2,byrow=TRUE))
plot_multiplot(plotlist=plot_scatterplot(mtcars[,1:4]),cols=2)
plot_multiplot(plotlist=cars_plot,layout=matrix(1:4,ncol=2,byrow=TRUE))
plot_multiplot(plotlist=cars_plot,cols=3)

```

plot_normality_diagnostics

Normality plots

Description

plot histogram density boxplot qq plot

Usage

```

plot_normality_diagnostics(
  df,
  breaks = NULL,
  title = "",
  file = NULL,
  w = 10,
  h = 10
)

```

Arguments

df	dataframe or vector with continous or ordinal data
breaks	number of bars to display
title	plot title
file	output filename
w	width of pdf file
h	height of pdf file

Details

uses plot base

Examples

```

vector<-generate_missing(rnorm(1000))
df<-generate_missing(mtcars[,1:2])
plot_normality_diagnostics(df=vector,title="",file="rnorm",breaks=30)
plot_normality_diagnostics(df=vector,title="")
plot_normality_diagnostics(df=df,title="mtcars")
plot_normality_diagnostics(df=df,title="mtcars",file="rnorm")

```

plot_oneway

*Plot group means with error bars for all IV-DV combinations***Description**

For every combination of independent variable (IV) and dependent variable (DV) supplied, produces a horizontal dot plot of group means with optional error bars (standard error, confidence interval, or standard deviation). Sample size per group is annotated on each panel.

When the number of IV-DV combinations exceeds four times the available CPU cores the plots are produced in parallel via `future.apply`, otherwise sequentially.

Usage

```
plot_oneway(
  df,
  dv,
  iv,
  base_size = 20,
  type = "se",
  order_factor = TRUE,
  title = "",
  note = "",
  width = 60
)
```

Arguments

<code>df</code>	A data frame containing both the independent and dependent variables.
<code>dv</code>	Integer vector of column indices for the continuous dependent variables.
<code>iv</code>	Integer vector of column indices for the categorical independent variables. Columns are coerced to factors automatically.
<code>base_size</code>	Base font size in pt passed to <code>theme_bw</code> . Default 20.
<code>type</code>	Type of error bar to display. One of "se" (standard error), "ci" (95% confidence interval), "sd" (standard deviation), or "" (no error bars). Default "se".
<code>order_factor</code>	Logical. If TRUE factor levels on the x-axis are sorted by the group mean of the DV (descending). Default TRUE.
<code>title</code>	Character. Plot title applied to every panel. Default "".
<code>note</code>	Character. Caption / footnote appended to every panel. Default "".
<code>width</code>	Integer. Character width at which long axis labels are wrapped. Default 60.

Value

A named list with three elements:

- `plot_data` — named list of summary data frames (one per IV-DV pair) as returned by `Rmisc::summarySE`.
- `plot_data_df` — single data frame combining all summary data frames row-wise.
- `plots` — named list of ggplot objects (one per IV-DV pair).

All list elements are named "iv_dv".

Examples

```
nrows <- 1000
df <- data.frame(generate_factor(vector=LETTERS[1:5], nrows=nrows, ncols=10, type="random"),
                 generate_data(nrows=nrows, ncols=5, type="normal"))
result <- plot_oneway(df=df, dv=11:15, iv=1:10)

# Single IV, single DV
plot_oneway(df=mtcars, dv=2, iv=9)

# Multiple IVs and DVs
plot_oneway(df=mtcars, dv=2:3, iv=9:10)

# Error bar types
plot_oneway(df=mtcars, dv=2:3, iv=9:10, type="se")
plot_oneway(df=mtcars, dv=2:3, iv=9:10, type="ci")
plot_oneway(df=mtcars, dv=2:3, iv=9:10, type="sd")
plot_oneway(df=mtcars, dv=2:3, iv=9:10, type="")

# Factor ordering
plot_oneway(df=mtcars, dv=2:3, iv=9:10, type="", order_factor=FALSE)
plot_oneway(df=mtcars, dv=2:3, iv=9:10, type="", order_factor=TRUE)
```

plot_oneway_diagnostics

Diagnostic plots for one-way ANOVA models

Description

For every combination of independent variable (IV) and dependent variable (DV), fits a linear model and produces a 6-panel diagnostic plot via `ggfortify::autoplot`: Residuals vs Fitted, Normal Q-Q, Scale-Location, Cook's Distance, Residuals vs Leverage, and Cook's Distance vs Leverage.

Interpretation:

- *Residuals vs Fitted* — points should be randomly scattered with no pattern; a funnel shape indicates heteroscedasticity.
- *Normal Q-Q* — points should follow the diagonal; large deviations indicate non-normality.

When the number of IV-DV combinations exceeds four times the available CPU cores the plots are produced in parallel via `future.apply`, otherwise sequentially.

Usage

```
plot_oneway_diagnostics(df, dv, iv, base_size = 10)
```

Arguments

df	A data frame containing both the independent and dependent variables.
dv	Integer vector of column indices for the continuous dependent variables.
iv	Integer vector of column indices for the categorical independent variables.
base_size	Base font size in pt passed to theme_bw. Default 10.

Value

A named list of ggplot objects (one 6-panel plot per IV-DV pair), named "iv_dv".

Examples

```
nrows <- 1000
df <- data.frame(generate_factor(vector=LETTERS[1:5], nrows=nrows, ncols=10, type="random"),
                 generate_data(nrows=nrows, ncols=5, type="normal"))
result <- plot_oneway_diagnostics(df=df, dv=11:15, iv=1:10)

# Single DV, multiple IVs
plot_oneway_diagnostics(df=mtcars, dv=1, iv=9:10)

# Multiple DVs and IVs
plot_oneway_diagnostics(df=mtcars, dv=1:2, iv=9:10)
```

plot_outlier

Outlier graph using mean median and boxplot algorithms

Description

Outlier graph using mean median and boxplot algorithms

Usage

```
plot_outlier(df, method = "mean", title = "", base_size = 10)
```

Arguments

df	dataframe or vector with continous or ordinal data
method	"mean" "median" "boxplot"
title	plot title
base_size	base font size

Author(s)

unknown

Examples

```
vector<-generate_missing(rnorm(1000))
df<-generate_missing(mtcars[,1:2])
plot_outlier(df=vector,method="mean",title="random vector")
plot_outlier(df=vector,method="median")
plot_outlier(df=vector,method="boxplot")
plot_outlier(df=df,method="mean",title="random vector")
plot_outlier(df=df,method="median")
plot_outlier(df=df,method="boxplot")
plot_mplot(plotlist=plot_outlier(df=mtcars[,2:5],method="mean"),cols=2)
```

plot_qq	<i>qq plots</i>
---------	-----------------

Description

qq plots

Usage

```
plot_qq(df, title = "", base_size = 10)
```

Arguments

df	dataframe or vector with continous or ordinal data
title	plot title
base_size	numeric base font size

Details

uses ggplot

Examples

```
vector<-generate_missing(rnorm(1000))
df<-generate_missing(mtcars[,1:2])
plot_qq(df=vector)
plot_qq(df=df)
plot_mplot(plotlist=plot_qq(df=mtcars),cols=4)
```

plot_response_frequencies	<i>Plot response frequencies</i>
---------------------------	----------------------------------

Description

Plot response frequencies

Usage

```
plot_response_frequencies(  
  df,  
  factor_index,  
  base_size = 10,  
  title = "",  
  width = 100,  
  reorder = FALSE  
)
```

Arguments

df	dataframe
factor_index	index of factors
base_size	base font size
title	plot title
width	Numeric, wrap width for x-axis title
reorder	Logical, whether to reorder factors based on frequency

Examples

```
plot_response_frequencies(df=mtcars, factor_index=1:10)
```

plot_roc	<i>Plot Receiver Operating Characteristic (ROC) curve</i>
----------	---

Description

Generates a ROC curve from observed outcomes and predicted probabilities.

Usage

```
plot_roc(observed, predicted, base_size = 10, title = "")
```

Arguments

observed	Vector of observed outcomes. These are the true class labels.
predicted	Vector of predicted outcome probabilities. These are the predicted probabilities for the positive class.
base_size	Integer value representing the base font size for the plot. Defaults to 10.
title	String representing the title of the plot. Defaults to an empty string.

Details

This function generates a ROC curve to evaluate the performance of a binary classification model. The ROC curve is a plot of the true positive rate (TPR) against the false positive rate (FPR) at various threshold settings.

The function performs the following steps: 1. Computes the ROC curve and its confidence interval using `'pROC::roc'`. 2. Generates ROC plots for both reversed and non-reversed order of class levels. 3. Creates a list of ROC plots, each with an AUC value, control level, and direction.

The output is a list of ggplot objects representing the ROC curves for different class level orders.

Examples

```
# Example with random observed and predicted values
observed<-round(abs(rnorm(100,m=0,sd=0.5)))
predicted<-abs(rnorm(100,m=0,sd=0.5))
plot_roc(observed=observed,predicted=predicted)

# Example with generated correlation matrix
df1<-data.frame(matrix(0.999,ncol=2,nrow=2))
correlation_matrix<-as.matrix(df1)
diag(correlation_matrix)<-1
df1<-generate_correlation_matrix(correlation_matrix,nrows=1000)
df1$X1<-ifelse(abs(df1$X1) < 1,0,1)
df1$X2<-abs(df1$X2)
df1$X2<-(df1$X2-min(df1$X2))/(max(df1$X2)-min(df1$X2))
plot_roc(observed=round(abs(df1$X1),0),predicted=abs(df1$X2))
```

plot_scatterplot

Scatter plots for all variable pairs in a data frame

Description

Generates a scatter plot with a smoothing line and marginal histograms for every pair of numeric columns in `df`. Each plot includes Pearson r , explained variance, the regression equation, and the regression angle in its caption (when the default $y \sim x$ formula is used).

When the number of pairs exceeds four times the available CPU cores the plots are produced in parallel via `future.apply`, otherwise sequentially.

Usage

```
plot_scatterplot(
  df,
  method = lm,
  formula = y ~ x,
  base_size = 10,
  coord_equal = FALSE,
  all_orders = FALSE,
  title = "",
  combinations = NULL,
  string_aes = TRUE
)
```

Arguments

df	A data frame of numeric variables. When df has exactly two columns the first is treated as the predictor and the second as the outcome.
method	Smoothing method passed to geom_smooth. Accepts "lm", "glm", "gam", "loess", or a function such as MASS::rlm. Default lm.
formula	Formula passed to geom_smooth. Default y ~ x. When a non-default formula is supplied the caption shows only pairwise n.
base_size	Base font size in pt passed to theme_bw. Default 10.
coord_equal	Logical. If TRUE both axes share the same scale and limits. Default FALSE.
all_orders	Logical. If TRUE both (X, Y) and (Y, X) orderings are plotted for each pair. Default FALSE.
title	Character. Plot title applied to every panel. Default "".
combinations	A two-column data frame specifying which pairs to plot. Column 1 is the x-variable name, column 2 is the y-variable name. When NULL (default) all pairs are derived automatically from df.
string_aes	Logical. If TRUE variable names are passed through string_aes() to clean axis labels. Default TRUE.

Value

A named list of ggplot objects, one per variable pair. Names follow the pattern "x_y".

Examples

```
result <- plot_scatterplot(df=mtcars, title="", coord_equal=TRUE, base_size=10)
plot_multiplot(plotlist=result[1:12], cols=4)

# Two-column data frame: first column = predictor, second = outcome
plot_scatterplot(df=mtcars[,1:2], base_size=10, coord_equal=TRUE, all_orders=FALSE)

# Custom variable pairs
plot_scatterplot(df=mtcars, base_size=10, coord_equal=TRUE,
  combinations=data.frame(x=c("mpg", "mpg", "mpg"),
```

```
y=c("cyl","hp","disp"))))

# Simulated near-perfect correlation
x <- rnorm(1000)
y <- x + rnorm(x, sd=.1)
plot_scatterplot(df=data.frame(x,y), title="Random Simulation", coord_equal=TRUE)
```

plot_scee	<i>Scree plot displaying the Kaiser and Jolife criteria for factor extraction</i>
-----------	---

Description

Scree plot displaying the Kaiser and Jolife criteria for factor extraction

Usage

```
plot_scee(df, base_size = 15, title = "", color = c("#5F2C91", "#5E912C"))
```

Arguments

df	dataframe
base_size	base font size
title	plot title
color	color of line and point outline

Examples

```
plot_scee(df=mtcars,title="",base_size=15)
```

plot_separability	<i>Plot separability</i>
-------------------	--------------------------

Description

This function creates a separability plot showing the density distribution of predicted probabilities for different observed categories.

Usage

```
plot_separability(observed, predicted, base_size = 10, title = "")
```

Arguments

observed	Vector of observed outcomes. This can be numeric or factor values representing the true class labels.
predicted	Vector of predicted outcome probabilities. This should have the same length as the observed vector and represent the predicted probabilities.
base_size	Integer value representing the base font size for the plot. Defaults to 10.
title	String representing the title of the plot. Defaults to an empty string.

Details

This function generates a separability plot using ggplot2. It shows the density distribution of predicted probabilities for different observed categories. The plot helps to visualize how well the predicted probabilities separate the different observed categories.

The plot includes the following components: -Density curves for each observed category, representing the distribution of predicted probabilities. -A legend indicating the observed categories. -The total number of observations is included in the plot caption.

Examples

```
# Example with numeric class labels
df1<-data.frame(matrix(.999,ncol=2,nrow=2))
correlation_matrix<-as.matrix(df1)
diag(correlation_matrix)<-1
df1<-generate_correlation_matrix(correlation_matrix,nrows=1000)
df1$X1<-ifelse(abs(df1$X1) < 1,0,1)
df1$X2<-abs(df1$X2)
df1$X2<-(df1$X2-min(df1$X2))/(max(df1$X2)-min(df1$X2))
plot_separability(observed=round(abs(df1$X1),0),predicted=abs(df1$X2))
```

plot_trees_xgboost	<i>Plot trees for xgboost::xgb.train</i>
--------------------	--

Description

Plot trees for xgboost::xgb.train

Usage

```
plot_trees_xgboost(model, train, file = "xgboost")
```

Arguments

model	object from xgboost::xgb.train
train	Train dataset
file	output filename

Examples

```
infern_formula<-formula(case~education+spontaneous+induced)
boston_formula<-formula(medv~crim+zn+indus+chas+nox+rm+age+dis+rad+tax+ptratio+black+lstat)
train_test_classification<-k_fold(df=infern,model_formula=infern_formula)
train_test_regression<-k_fold(df=MASS::Boston,model_formula=boston_formula)
xgb_classification<-xgboost::xgb.train(
  data=train_test_classification$xgb$f1$train,
  watchlist=train_test_classification$xgb$f1$watchlist,
  eta=.1,
  nthread=8,
  nround=20,
  objective="binary:logistic")
xgb_regression<-xgboost::xgb.train(
  data=train_test_regression$xgb$f1$train,
  watchlist=train_test_regression$xgb$f1$watchlist,
  eta=.3,
  nthread=8,
  nround=20)
# xgboost::xgb.plot.multi.trees(model=xgb_classification,features_keep=2)
# plot_trees_xgboost(model=xgb_classification,
#                     train=train_test_classification$xgb$f1,
#                     file="Classification")
# plot_trees_xgboost(model=xgb_regression,
#                     train=train_test_regression$xgb$f1,
#                     file="Regression")
```

plot_ts	<i>Plot timeseries</i>
---------	------------------------

Description

Plot timeseries

Usage

```
plot_ts(df, base_size = 10, ylab = "Count", title = "")
```

Arguments

df	ts object
base_size	base font size
ylab	y label
title	plot title

Details

returns plot

Examples

```
ts_data<-ts(UKDriverDeaths,start=1969,end=1984,frequency=12)
result<-plot_ts(ts_data,title="UK driver deaths")
for(i in 1969:1984)
  result<-result+geom_vline(xintercept=i,color="blue",size=1,alpha=.5)
result
autoplot(stl(ts_data,s.window='periodic'))+
  theme_bw(base_size=10)+
  labs(title="UK driver deaths")
forecast::gglagplot(data.frame(ts_data),do.lines=FALSE,lags=100)+
  theme_bw(base_size=10)+labs(title="UK driver deaths",y="count")
```

proper

*Capitalize first character and lowercase the rest***Description**

Capitalize first character and lowercase the rest

Usage

```
proper(x)
```

Arguments

x Character

Examples

```
x<-generate_string(nchar=10,vector=LETTERS,vector_length=10)
proper(x)
```

proportion_accurate

*Proportion overall accuracy of a confusion matrix***Description**

Calculates the overall accuracy and Cohen's kappa statistics of a confusion matrix.

Usage

```
proportion_accurate(observed, predicted)
```

Arguments

observed Vector of observed variables. These are the true class labels.
predicted Vector of predicted variables. These are the predicted class labels.

Details

This function evaluates the performance of a confusion matrix by calculating the overall accuracy and Cohen’s kappa statistics.

The function performs the following steps: 1. Computes the confusion matrix from the observed and predicted values. 2. Calculates the diagonal proportion (overall accuracy) and the off-diagonal proportion. 3. Computes Cohen’s kappa statistics (unweighted,linear,and squared weights).

The output is a data.frame containing the following metrics: -‘cm_diagonal’: Proportion of correct classifications (diagonal elements). -‘cm_off_diagonal’: Proportion of misclassified observations (off-diagonal elements). -‘kappa_unweighted’: Cohen’s kappa statistic with no weights. -‘kappa_linear’: Cohen’s kappa statistic with linear weights. -‘kappa_squared’: Cohen’s kappa statistic with squared weights.

Examples

```
# Example with numeric observed and predicted values
proportion_accurate(observed=c(1,2,3,4,5,10),predicted=c(1,2,3,4,5,11))
```

questions_by_keys	<i>Convert key to index list</i>
-------------------	----------------------------------

Description

Convert key to index list

Usage

```
questions_by_keys(key)
```

Arguments

key	a vector indicating the dimension of each question. The order of the elements in the key represents the order of the questions, the numeric values represent the dimension the question belongs to
-----	--

Examples

```
key<-c(1,2,3,4,5,1,2,3,4,5)
questions_by_keys(key)
```

questions_dimensions_dataframe	<i>Question dimension table</i>
--------------------------------	---------------------------------

Description

Return a dataframe with the order of the questions, their respective dimensions, and the description of the dimensions

Usage

```
questions_dimensions_dataframe(  
  key,  
  dimensions,  
  elaborate_dimensions,  
  questions  
)
```

Arguments

- key a vector indicating the dimension of each question. The order of the elements in the key represents the order of the questions, the numeric values represent the dimension the question belongs to
- dimensions dimension names
- elaborate_dimensions full dimension names
- questions question names

Examples

```
key<-c(1,2,3,4,5,1,2,3,4,5)  
dimensions<-paste0("Dimension",1:10)  
elaborate_dimensions<-paste0("Elaborated_Dimension",1:10)  
questions<-paste0("Question",1:65)  
questions_dimensions_dataframe(key,dimensions,elaborate_dimensions,questions)
```

rad2deg	<i>Convert radians to degrees</i>
---------	-----------------------------------

Description

Convert radians to degrees

Usage

```
rad2deg(radians)
```

Arguments

radians radians

Examples

```
rad2deg(pi)
```

rank3_to_triplets	<i>Convert thurstonian binary triplets to scale</i>
-------------------	---

Description

Convert thurstonian binary triplets to scale

Usage

```
rank3_to_triplets(mydata)
```

Arguments

mydata dataframe

Examples

```
set.seed(12345)
mydata<-data.frame(i1=rnorm(10,mean=2,sd=.5),
                   i2=rnorm(10,mean=2,sd=.5),
                   i3=rnorm(10,mean=2,sd=.5),
                   i4=rnorm(10,mean=2,sd=.5),
                   i5=rnorm(10,mean=2,sd=.5),
                   i6=rnorm(10,mean=2,sd=.5))
result<-rank_to_binary(mydata[,1:3])
rank3_to_triplets(result)
```

rank_df_to_binary	<i>Convert scale to thurstonian binary with n items per block and n blocks</i>
-------------------	--

Description

Convert scale to thurstonian binary with n items per block and n blocks

Usage

```
rank_df_to_binary(mydata, items, reverse = TRUE)
```


Arguments

mydata	dataframe
items	number of items in block
reverse	if TRUE assumes that the highest value is first item in rank if FALSE the lowest value is the first item in rank

Examples

```
set.seed(12345)
mydata<-data.frame(i1=rnorm(10,mean=2,sd=.5),
                   i2=rnorm(10,mean=2,sd=.5),
                   i3=rnorm(10,mean=2,sd=.5),
                   i4=rnorm(10,mean=2,sd=.5),
                   i5=rnorm(10,mean=2,sd=.5),
                   i6=rnorm(10,mean=2,sd=.5))
rank_df_to_binary(mydata[,c("i1","i2","i3","i4")],4)
rank_df_to_binary(mydata,3)
```

rank_to_binary	<i>Convert scale to thurstonian binary with n items per ranking block</i>
----------------	---

Description

Convert scale to thurstonian binary with n items per ranking block

Usage

```
rank_to_binary(mydata, items, reverse = TRUE)
```

Arguments

mydata	dataframe
items	number of items in block
reverse	if TRUE assumes that the highest value is first item in rank if FALSE the lowest value is the first item in rank

Examples

```
set.seed(12345)
mydata<-data.frame(i1=round(rnorm(10,mean=2,sd=1),2),
                   i2=round(rnorm(10,mean=2,sd=1),2),
                   i3=round(rnorm(10,mean=2,sd=1),2),
                   i4=round(rnorm(10,mean=2,sd=1),2),
                   i5=round(rnorm(10,mean=2,sd=1),2),
                   i6=round(rnorm(10,mean=2,sd=1),2))
rank_to_binary(mydata[,c("i1","i2","i3")],items=3)
rank_to_binary(mydata[,c("i1","i2","i3")],items=3,reverse=FALSE)
rank_to_binary(mydata,items=3)
```

raw_alpha

*Raw alpha***Description**

Raw alpha

Usage

raw_alpha(df)

Arguments

df dataframe with one dimension

Examples

```
set.seed(12345)
df<-data.frame(matrix(.5,ncol=6,nrow=6))
correlation_matrix<-as.matrix(df)
diag(correlation_matrix)<-1
df<-round(generate_correlation_matrix(correlation_matrix,nrows=1000),0)+5
psych::alpha(df)
raw_alpha(df=df)
```

rbind_all

*rbind dataframes or matrices with different lengths or column names***Description**

rbind dataframes or matrices with different lengths or column names

Usage

rbind_all(df1, df2)

Arguments

df1 dataframe or matrix

df2 dataframe or matrix

Examples

```
df1<-generate_correlation_matrix(n=10)
df2<-generate_correlation_matrix(n=10)
names(df2)[4]<-"X11"
rbind_all(df1=df1,df2=df2)
row.names(df1)<-21:30
rbind_all(df1=df1,df2=df2)
```

recode_scale_dummy	<i>Scale and dummy code</i>
--------------------	-----------------------------

Description

Scales numeric variables between 0 and 1 and creates dummy coding for character and factor variables.

Usage

```
recode_scale_dummy(df, categories = 10)
```

Arguments

df	Dataframe containing the dataset to be scaled and dummy coded.
categories	Numeric value representing the number of unique values a vector must have to perform dummy coding. Defaults to 10.

Details

This function processes a dataframe by scaling numeric variables and creating dummy codes for character and factor variables. The numeric variables are scaled between 0 and 1, while the character and factor variables are converted to dummy variables if they have fewer unique values than the specified 'categories' parameter.

The function performs the following steps: 1. Identifies numeric variables in the dataframe and scales them. 2. Identifies character and factor variables and creates dummy variables if they meet the criteria. 3. Combines the scaled numeric variables and dummy variables into a single dataframe.

The output is a dataframe with scaled numeric variables and dummy-coded character/factor variables.

Examples

```
# Example with the 'infert' dataset
recode_scale_dummy(infert)

# Example with a custom dataframe
df<-data.frame(numeric_var=c(1,2,3,4,5),
               factor_var=factor(c('A','B','A','B','C')))
recode_scale_dummy(df)
```

remove_nc	<i>Replace remove non computable values</i>
-----------	---

Description

Replace remove non computable values

Usage

```
remove_nc(
  df,
  value = NA,
  remove_rows = FALSE,
  aggressive = FALSE,
  remove_cols = FALSE,
  remove_zero_variance = FALSE
)
```

Arguments

df	dataframe
value	replacement
remove_rows	if TRUE it will remove rows with non computable values
aggressive	if TRUE it will remove entire row if a single non computable value exists if FALSE it will remove row if all values are non computable
remove_cols	if TRUE it will remove collumns with non computable values
remove_zero_variance	if TRUE it will remove collumns with no variance

Details

Non computable values are NA, NAN, inf and empty cells.

Note

This function internally replaces non computable values with the value choosen the default value is NA. Then it removes rows and collumns with NA values or zero variance

Examples

```
df<-mtcars
df[1,]<-as.numeric(NaN)
df[2,]<-as.numeric(Inf)
df[3,]<-as.numeric(-Inf)
df[4,]<-as.numeric(NA)
df[5,]<-""
remove_nc(df=df,value=NA)
```

```

cdf(remove_nc(df=df,value=NA))
df<-generate_missing(mtcars,missing=5)
remove_nc(df,remove_rows=TRUE,aggressive=FALSE)
remove_nc(df,remove_rows=TRUE,aggressive=TRUE)
df<-generate_missing(generate_correlation_matrix(nrows=5),missing=2)
df$X2<-NA
df$X3<-1
remove_nc(df,remove_cols=TRUE,remove_zero_variance=FALSE)
remove_nc(df,remove_cols=TRUE,remove_zero_variance=TRUE)

```

remove_outliers	<i>Remove outliers</i>
-----------------	------------------------

Description

Remove outliers

Usage

```
remove_outliers(vector, probs = c(0.25, 0.75), na.rm = TRUE, ...)
```

Arguments

vector	numeric
probs	numeric vector with lowest and highest quantiles
na.rm	if TRUE removes NA values
...	arguments passed to quantile

Examples

```

vector<-generate_missing(rnorm(1000))
df<-generate_missing(mtcars[,1:2])
remove_outliers(vector)
data.frame(sapply(df,remove_outliers))

```

remove_user_packages	<i>Remove all user packages</i>
----------------------	---------------------------------

Description

Remove all user packages

Usage

```
remove_user_packages()
```

```
replace_na_with_previous
```

Replace NA with the previous element in a vector

Description

Replace NA with the previous element in a vector

Usage

```
replace_na_with_previous(vector)
```

Arguments

vector	Vector
--------	--------

Examples

```
df1<-generate_missing(rnorm(10),missing=5)
df2<-generate_missing(rnorm(10),missing=5)
df3<-generate_missing(rnorm(10),missing=5)
df4<-generate_missing(rnorm(10),missing=5)
df5<-generate_missing(rnorm(10),missing=5)
df<-data.frame(df1,df2,df3,df4,df5)
row.names(df)<-paste0("A",row.names(df))
replace_na_with_previous(df1)
df[]<-lapply(df,replace_na_with_previous)
```

```
report_alpha
```

Estimate alpha for several dimensions and export results to xlsx

Description

Uses an arbitrary input

Usage

```
report_alpha(
  df,
  key = NULL,
  questions = NULL,
  reverse = NULL,
  mini = NULL,
  maxi = NULL,
  file = NULL,
  ...
)
```

Arguments

df	dataframe
key	index of trait names and items constituting a trait
questions	trait names and items constituting a trait
reverse	index of trait names and index for reversal
mini	minimum rating in scale if NULL reversal will be performed using the empirical minimum
maxi	maximum rating in scale if NULL reversal will be performed using the empirical maximum
file	output filename
...	arguments passed to psych::alpha

Examples

```
set.seed(12345)
df<-data.frame(matrix(.5,ncol=6,nrow=6))
correlation_martix<-as.matrix(df)
diag(correlation_martix)<-1
df<-round(generate_correlation_matrix(correlation_martix,nrows=1000),0)+5
key<-list(f1=c("X1","X2","X3"),
          f2=c("X4","X5","X6"))
reverse<-list(f1=c(1,1,1),
              f2=c(1,1,1))
report_alpha(df=df,key=key,cumulative=TRUE,n.iter=1)
report_alpha(df=df,key=key,reverse=reverse,check.keys=FALSE,n.iter=2)
report_alpha(df=df,key=key,check.keys=FALSE,n.iter=2,file="alpha")
```

report_cfa	<i>Report</i>
------------	---------------

Description

Report

Usage

```
report_cfa(model, file = NULL, w = 10, h = 10)
```

Arguments

model	lavaan object
file	output filename
w	width of pdf file
h	height of pdf file

Examples

```
model='LATENT=~ITEM1+ITEM2+ITEM3+ITEM4+ITEM5'
df<-lavaan::simulateData(model=model,model.type="cfa",
                          return.type="data.frame",sample.nobs=100)

df<-generate_missing(df)
fit<-lavaan::cfa(model,data=df,missing="ML")
report_cfa(fit)
report_cfa(fit,file="cfa")
```

report_choric_serial *Report polychoric tetrachoric polyserial biserial correlation*

Description

Report polychoric tetrachoric polyserial biserial correlation

Usage

```
report_choric_serial(
  x,
  y = NULL,
  file = NULL,
  w = 10,
  h = 10,
  type = "tetrachoric",
  ...
)
```

Arguments

- | | |
|------|--|
| x | The input may be in one of four forms: <ul style="list-style-type: none"> a) a data frame or matrix of dichotomous data (e.g., the lsat6 from the bock data set) or discrete numerical (i.e., not too many levels, e.g., the big 5 data set, bfi) for polychoric, or continuous for the case of biserial and polyserial b) a 2 x 2 table of cell counts or cell frequencies (for tetrachoric) or an n x m table of cell counts (for both tetrachoric and polychoric) c) a vector with elements corresponding to the four cell frequencies (for tetrachoric) d) a vector with elements of the two marginal frequencies (row and column) and the comorbidity (for tetrachoric) |
| y | matrix or dataframe of discrete scores. In the case of tetrachoric, these should be dichotomous, for polychoric not too many levels, for biserial they should be discrete (e.g., item responses) with not too many (<10?) categories |
| file | output filename |
| w | width of pdf file |

h	height of pdf file
type	"tetrachoric" "polychoric" "polyserial" "biserial"
...	arguments passed to psych::polychoric

Examples

```
report_choric_serial(generate_data(min=0,max=1,type="uniform"),
                     type="tetrachoric",file="tetrachoric")
report_choric_serial(generate_data(min=1,max=5,type="uniform"),
                     type="polychoric")
report_choric_serial(x=psych::lsat6,y=psych::lsat6,
                     type="polyserial",file="polyserial")
report_choric_serial(x=psych::lsat6,y=psych::lsat6,
                     type="biserial",file="biserial")
```

report_correlation	<i>Report correlation matrix</i>
--------------------	----------------------------------

Description

Report correlation matrix

Usage

```
report_correlation(
  x,
  y = NULL,
  use = "pairwise",
  method = "pearson",
  adjust = "holm",
  alpha = 0.05,
  ci = TRUE,
  file = NULL,
  w = 10,
  h = 10,
  base_size = 20,
  scatterplot = TRUE
)
```

Arguments

x	matrix or dataframe
y	a second matrix or dataframe with the same number of rows as x
use	"pairwise" is the default value and will do pairwise deletion of cases. "complete" will select just complete cases
method	"pearson" "spearman" "kendall"

adjust	"holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
alpha	alpha level of confidence intervals
ci	By default, confidence intervals are found. However, this leads to a great slow-down of speed. So, for just the rs, ts and ps, set ci=FALSE
file	output filename
w	width of pdf file
h	height of pdf file
base_size	base font size
scatterplot	if TRUE it will output scatterplots

Examples

```
report_correlation(x=generate_missing(mtcars[,1:3],10))
report_correlation(x=generate_missing(mtcars[,1:3],10),
                    file="correlation",scatterplot=TRUE)
report_correlation(x=mtcars[,1:3],file="correlation")
```

report_dataframe	<i>Write matrix or dataframe to excel sheet</i>
------------------	---

Description

Usefull for generic data where conditional formating of a spesific collumn is required

Usage

```
report_dataframe(df, file = NULL, type = "critical_value", ...)
```

Arguments

df	dataframe or matrix
file	output filename of excel file
type	"critical_value" "matrix"
...	arguments passed to excel_critical_value or to excel_matrix

Examples

```
comment<-list(mpg="Miles/(US) gallon",
              cyl="Number of cylinders",
              disp="Displacement (cu.in.)",
              hp="Gross horsepower",
              drat="Rear axle ratio",
              wt="Weight (1000 lbs)",
              qsec="1/4 mile time",
              vs="Engine (0=V-shaped,1=straight)",
              am="Transmission (0=automatic,1=manual)",
```

```
gear="Number of forward gears",
carb="Number of carburetors")
report_dataframe(mtcars, sheet="report", file="mtcars", comment=comment, numFmt="#0.00",
critical=list(am="<0.05"))
report_dataframe(mtcars, sheet="report", file=NULL, comment=comment, numFmt="#0.00",
critical=list(am="<0.05"))
```

report_efa	<i>Output EFA model</i>
------------	-------------------------

Description

Output EFA model

Usage

```
report_efa(
  model,
  df,
  file = NULL,
  w = 10,
  h = 5,
  cut = 0,
  base_size = 10,
  scores = FALSE
)
```

Arguments

model	psych EFA model
df	dataframe
file	output filename
w	width of pdf file
h	height of pdf file
cut	cut point for loadings
base_size	base font size
scores	if TRUE it will output factor scores in excel file

Note

Orthogonal=varimax, Oblique=oblimin

Examples

```

model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="minres",oblique.scores=TRUE)
report_efa(model=model,df=mtcars,file="efa")
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="uls",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="ols",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="wls",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="gls",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="pa",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="ml",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="minchi",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="minrank",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="old.min",oblique.scores=TRUE)
report_efa(model=model,df=mtcars)
model<-psych::fa(mtcars,nfactors=2,rotate="oblimin",fm="alpha",oblique.scores=TRUE)
#report_efa(model=model,df=mtcars)

```

report_factorial_anova

Plot means with standard error for every level in a dataframe

Description

Plot means with standard error for every level in a dataframe

Usage

```

report_factorial_anova(
  df,
  dv,
  wid,
  within = NULL,
  within_full = NULL,
  between = NULL,
  within_covariates = NULL,
  between_covariates = NULL,
  observed = NULL,
  diff = NULL,
  reverse_diff = FALSE,
  type = 3,
  white.adjust = TRUE,

```

```

detailed = TRUE,
return_aov = TRUE,
file = NULL,
post_hoc_test = TRUE,
base_size = 15
)

```

Arguments

df	dataframe
dv	names of dependent variables
wid	names of
within	names of within factors
within_full	names of within factors after data are collapsed to means per condition
between	names of between factors
within_covariates	names of within covariates
between_covariates	names of between covariates
observed	names in data that are already specified in either within or between that contain predictor variables that are observed variables (not manipulated)
diff	names of variables to collapse in a different score
reverse_diff	If TRUE, triggers reversal of the difference collapse requested by diff
type	sum of squares 1 2 3
white.adjust	if TRUE corrects for heteroscedasticity
detailed	if TRUE returns detailed information
return_aov	if TRUE returns aov object
file	output filename
post_hoc_test	if TRUE outputs post hoc in file
base_size	base font size

Examples

```

set.seed(12345)
df<-data.frame(id=rep(seq(1,80),each=81,1),
               IV1=rep(LETTERS[1:3],each=1,2160),
               IV2=rep(LETTERS[4:6],each=3,720),
               IV3=rep(LETTERS[7:9],each=9,240),
               IV4=rep(LETTERS[10:12],each=27,80),
               stringsAsFactors=FALSE)
cdf<-data.frame(matrix(.01,ncol=4,nrow=4))
correlation_matrix<-as.matrix(cdf)
diag(correlation_matrix)<-1
cdf<-generate_correlation_matrix(correlation_matrix,nrows=nrow(df))+10
names(cdf)<-paste0("DV",1:4)

```

```

df<-data.frame(df,cdf)
df$DV2<-df$DV2+10
df$DV3<-df$DV3+20
df$DV4<-df$DV4+30
df[df$IV1%in%"A",]$DV1<-df[df$IV1%in%"A",]$DV1+1
df[df$IV1%in%"B",]$DV1<-df[df$IV1%in%"B",]$DV1+2
df[df$IV1%in%"C",]$DV1<-df[df$IV1%in%"C",]$DV1+3
cdf(df)
r1<-report_factorial_anova(df=df,wid="id",dv=c("DV1","DV2"),
                           within=c("IV1","IV2"),within_full=c("IV1","IV2"),
                           between=NULL,
                           within_covariates=NULL,between_covariates=NULL,
                           file="anova_within",
                           post_hoc=TRUE)
r2<-report_factorial_anova(df=df,wid="id",dv=c("DV1","DV2"),
                           within=NULL,within_full=NULL,
                           between=c("IV1","IV2"),
                           within_covariates=NULL,between_covariates=NULL,
                           file="anova_between",
                           post_hoc=TRUE)
r3<-report_factorial_anova(df=df,wid="id",dv=c("DV1","DV2"),
                           within=c("IV3","IV4"),within_full=c("IV3","IV4"),
                           between=c("IV1","IV2"),
                           within_covariates=NULL,between_covariates=NULL,
                           file="anova_mixed",
                           post_hoc=FALSE)
r4<-report_factorial_anova(df=df,wid="id",dv=c("DV1","DV2"),
                           within=c("IV1","IV2"),within_full=c("IV1","IV2"),
                           between=NULL,
                           within_covariates=c("DV3","DV4"),between_covariates=NULL,
                           file="anova_within_cov",
                           post_hoc=TRUE)

```

report_hlr

Report HLR

Description

Report HLR

Usage

```

report_hlr(
  df,
  corlist,
  factorlist,
  predictor,
  random_effect,
  file = NULL,
  sheet = "report"
)

```

Arguments

df	dataframe
corlist	Numeric outcome index
factorlist	Numeric predictor index
predictor	Character predictor name
random_effect	Character random effect name
file	Character file
sheet	Character sheet

Examples

```
report_hlr(df=infert,corlist=8,factorlist=1,
           predictor="case",random_effect="case")
```

report_irt	<i>Output for irt model</i>
------------	-----------------------------

Description

Output for irt model

Usage

```
report_irt(model, m2 = TRUE, file = NULL)
```

Arguments

model	object mirt
m2	if TRUE report m2 statistics
file	output filename

Examples

```
set.seed(12345)
cormatrix<-psych::sim.rasch(nvar=5,n=50000,low=-4,high=4,d=NULL,a=1,mu=0,sd=1)$items
irt_onefactor<-mirt::mirt(cormatrix,1,empiricalhist=TRUE,calcNull=TRUE)
irt_twofactor<-mirt::mirt(cormatrix,2,empiricalhist=TRUE,calcNull=TRUE)
irt_threefactor<-mirt::mirt(cormatrix,3,empiricalhist=TRUE,calcNull=TRUE)
report_irt(model=irt_onefactor,file="one_factor")
report_irt(model=irt_twofactor,file="two_factors")
report_irt(model=irt_threefactor,file="three_factors")
```

report_lda	<i>Report for MASS::lda</i>
------------	-----------------------------

Description

Report for MASS::lda

Usage

```
report_lda(model, file = NULL, w = 10, h = 10, base_size = 10, title = "")
```

Arguments

model	object from MASS::lda
file	output filename
w	width of pdf file
h	height of pdf file
base_size	base font size
title	plot title

Examples

```
model<-MASS::lda(case~.,data=infert)
result<-report_lda(model=model)
result<-report_lda(model=model,file="lda")
model<-MASS::lda(Species~.,data=iris)
result<-report_lda(model=model,file="lda")
```

report_logistic	<i>Report logistic regression</i>
-----------------	-----------------------------------

Description

Report logistic regression

Usage

```
report_logistic(
  model,
  validation_data = NULL,
  file = NULL,
  title = "",
  w = 10,
  h = 10,
  base_size = 10,
  fast = FALSE
)
```


Arguments

model	object glm
validation_data	validation data
file	output filename
title	plot title
w	width of pdf file. Relevant only when file string is not empty
h	height of pdf file. Relevant only when file string is not empty
base_size	base font size
fast	if TRUE it will not output individual scores and residuals

Note

(1) Problematic values for standardized residuals $> \pm 1.96$

Standardized residuals are residuals divided by an estimated standard deviation and they can be interpreted as z scores in that:

95 99 99.99 (2) Problematic values for $dfBeta \geq 1$

$dfBeta$ estimates coefficients if the respective case is removed from the dataset

(3) Problematic values for Hat values (leverage) 2 or 3 times the average $(k+1)/n$

Hat values (leverage), gauge the influence of the observed value of the outcome variable over the predicted values

The average leverage value is defined as $(k+1)/n$, k =number of predictors, n =number of participants. Leverage values lie between 0 (no influence) and 1 (complete influence over prediction)

If no cases exert undue influence over the model then all leverage values should be close to $(k+1)/n$ Hoaglin and Welsch (1978) recommends investigating cases with values greater than twice the average $2(k+1)/n$

Stevens (2002) recommends investigating cases with values greater than three times the average $3(k+1)/n$

(4) Problematic values for VIFs > 10

ASSUMPTIONS

(1) Linearity between continous predictors and the logit (test wether the interaction term between the predictor and its log transformation is significant)

(2) Independence of errors

(3) No multicollinearity

Examples

```
modelcategoricalpredictor0<-glm(case~education,data=infert,family=binomial)
modelcategoricalpredictor1<-glm(case~education,data=infert,family=gaussian)
#modelcategoricalpredictor2<-glm(case~education,data=infert,family=Gamma)
#modelcategoricalpredictor3<-glm(case~education,data=infert,family=inverse.gaussian)
modelcategoricalpredictor4<-glm(case~education,data=infert,family=poisson)
modelcategoricalpredictor5<-glm(case~education,data=infert,family=quasi)
modelcategoricalpredictor6<-glm(case~education,data=infert,family=quasibinomial)
modelcategoricalpredictor7<-glm(case~education,data=infert,family=quasipoisson)
modelcontinuouspredictor0<-glm(case~stratum,data=infert,family=binomial)
```

```

modeltwopredictors0<-glm(case~education+stratum,data=infert,family=binomial)
modeltwopredictors1<-glm(case~education+stratum,data=infert,family=gaussian)
#modeltwopredictors2<-glm(case~education+stratum,data=infert,family=Gamma)
#modeltwopredictors3<-glm(case~education+stratum,data=infert,family=inverse.gaussian)
modeltwopredictors4<-glm(case~education+stratum,data=infert,family=poisson)
modeltwopredictors5<-glm(case~education+stratum,data=infert,family=quasi)
modeltwopredictors6<-glm(case~education+stratum,data=infert,family=quasibinomial)
modeltwopredictors7<-glm(case~education+stratum,data=infert,family=quasipoisson)
report_logistic(model=modelcategoricalpredictor0)
report_logistic(model=modelcategoricalpredictor1)
#report_logistic(model=modelcategoricalpredictor2)
#report_logistic(model=modelcategoricalpredictor3)
report_logistic(model=modelcategoricalpredictor4)
report_logistic(model=modelcategoricalpredictor5)
report_logistic(model=modelcategoricalpredictor6)
report_logistic(model=modelcategoricalpredictor7)
report_logistic(model=modelcontinuouspredictor0)
report_logistic(model=modeltwopredictors0)
report_logistic(model=modelcategoricalpredictor0,
                 file="logistic_categorical_predictor",
                 validation_data=infert)
report_logistic(model=modelcontinuouspredictor0,
                 file="logistic_continuous_predictor",
                 validation_data=infert)
report_logistic(model=modeltwopredictors0,
                 file="logistic_two_predictors",
                 validation_data=infert[1:10,])

```

report_manova

Manova result

Description

Manova result

Usage

```
report_manova(model, file = NULL)
```

Arguments

model	object of manova model
file	output filename

Note

Pillai-Bartlett trace (V): Represents the sum of the proportion of explained variance on the discriminant functions. As such, it is similar to the ratio of SS_M / SS_T , which is known as R^2 .

Hottelling-s T^2 : Represents the sum of the eigenvalues for each variate it compares directly to the

F-ratio in ANOVA

Wilks-s lambda (L): Represents the ratio of error variance to total variance (SS_R / SS_T) for each variate.

Roy-s largest root: Represents the proportion of explained variance to unexplained variance (SS_M / SS_R) for the first discriminant function.

ASSUMPTIONS

Independence: Observations should be statistically independent.

Random sampling: Data should be randomly sampled from the population of interest and measured at an interval level.

Multivariate normality: In ANOVA, we assume that our dependent variable is normally distributed within each group. In the case of MANOVA, we assume that the dependent variables (collectively) have multivariate normality within groups.

Homogeneity of covariance matrices: In ANOVA, it is assumed that the variances in each group are roughly equal (homogeneity of variance). In MANOVA we must assume that this is true for each dependent variable, but also that the correlation between any two dependent variables is the same in all groups. This assumption is examined by testing whether the population variance-covariance matrices of the different groups in the analysis are equal.

Examples

```
## Set orthogonal contrasts.
op<-options(contrasts=c("contr.helmert","contr.poly"))
model_mixed<-manova(cbind(yield,foo)~N*P*K,within(npk,foo<-rnorm(24)))
model_between<-manova(cbind(rnorm(24),rnorm(24))~round(rnorm(24),0)*round(rnorm(24),0))
report_manova(model=model_mixed)
report_manova(model=model_between)
```

```
report_normality_tests
```

Normality tests

Description

Shapiro-Wilk Anderson-Darling Cramer-von-Mises Shapiro-Francia
Jarque-Bera Kolmogorov-Smirnov Lilliefors Pearson X2

Usage

```
report_normality_tests(df, file = NULL)
```

Arguments

df	dataframe with continous or ordinal data
file	output filename

Details

returns xlsx file

Examples

```
vector<-generate_missing(rnorm(1000))
df<-generate_missing(mtcars[,1:2])
report_normality_tests(df=df)
report_normality_tests(df=vector,file="normality_tests")
```

report_oneway	One way
---------------	---------

Description

One way

Usage

```
report_oneway(
  df,
  dv,
  iv,
  file = NULL,
  w = 10,
  h = 10,
  base_size = 10,
  note = "",
  title = "",
  type = "ci",
  plot_means = FALSE,
  plot_diagnostics = FALSE
)
```

Arguments

df	A data frame containing both the independent and dependent variables.
dv	Integer vector of column indices for the continuous dependent variables.
iv	Integer vector of column indices for the categorical independent variables.
file	output filename
w	width of pdf file
h	height of pdf file
base_size	base font size
note	text for footnote
title	plot title
type	type of bar to display "se" "ci" "sd" ""
plot_means	if TRUE it will output mean plots and descriptives for plots
plot_diagnostics	if TRUE it will output ANOVA diagnostics plots

Note

- (1) The Fisher procedure assumes heteroscedasticity
- (2) The Welch procedure does not assume heteroscedasticity
- (3) The Kruskal Wallis procedure does not assume normality but it is not an alternative for violations of heteroscedasticity
- (4) Posthoc Tuckey: not good for unequal sample sizes or heteroscedasticity
- (5) Posthoc Games Howell: good for unequal sample sizes and heteroscedasticity

Examples

```
report_oneway(df=df_blood_pressure,
              dv=c(which("bp_before"==names(df_blood_pressure)),
                    which("bp_after"==names(df_blood_pressure))),
              iv=c(which("sex"==names(df_blood_pressure)),
                    which("agegrp"==names(df_blood_pressure))),
              file="anova",
              plot_diagnostics=FALSE,
              plot_means=FALSE)
report_oneway(df=mtcars,dv=2:4,iv=9:10,file="anova_oneway_two_factor")
report_oneway(df=mtcars,dv=2:4,iv=9,file="anova_oneway_one_factor")
report_oneway(df=mtcars,dv=2:4,iv=9,file="anova_oneway_one_factor",
              plot_means=TRUE,plot_diagnostics=TRUE)
```

report_pdf

*Report pdf***Description**

Report pdf

Usage

```
report_pdf(
  ...,
  plotlist = NULL,
  file = NULL,
  title = NULL,
  w = 10,
  h = 10,
  print_plot = TRUE
)
```

Arguments

...	plot objects
plotlist	list of plot objects
file	output filename

title	output filename
w	width of pdf file
h	height of pdf file
print_plot	if TRUE it prints plot on graphics device

Examples

```
p1<-ggplot(ChickWeight,aes(x=Time,y=weight,colour=Diet,group=Chick))+
  geom_line()+
  ggtitle("Growth curve for individual chicks")+
  theme_bw()
p2<-ggplot(ChickWeight,aes(x=Time,y=weight,colour=Diet))+
  geom_point(alpha=.3)+
  geom_smooth(alpha=.2,size=1,method="loess",formula="y~x")+
  ggtitle("Fitted growth curve per diet")+theme_bw()
cars_plot_multiplot<-plot_multiplot(plotlist=plot_histogram(mtcars[,1:4]),cols=2)
cars_plot_base<-plot_normality_diagnostics(mtcars)
report_pdf(p1,p2,print_plot=TRUE)
report_pdf(p1,p2,file="report",print_plot=FALSE)
report_pdf(plotlist=cars_plot_multiplot,print_plot=TRUE)
report_pdf(plotlist=cars_plot_multiplot,file="report",print_plot=FALSE)
report_pdf(plotlist=cars_plot_base,print_plot=TRUE)
report_pdf(plotlist=cars_plot_base,file="report",print_plot=FALSE)
```

report_regression	<i>Regression</i>
-------------------	-------------------

Description

Regression

Usage

```
report_regression(
  model,
  base_size = 10,
  title = "",
  file = NULL,
  w = 10,
  h = 10,
  plot_diagnostics = TRUE
)
```

Arguments

model	object ml
base_size	base font size

title	plot title
file	output filename
w	width of pdf file. Relevant only when file string is not empty
h	height of pdf file. Relevant only when file string is not empty
plot_diagnostics	if TRUE it will output linear model diagnostics plots

Note

(1) Problematic values for standardized residuals $> \pm 1.96$

****Standardized residuals**** are residuals divided by an estimated standard deviation and they can be interpreted as z scores in that:

- 95.00 - 99.00 - 99.99 (2) ****Studentized residuals**** indicate the the ability of the model to predict that case. They follow a t distribution

(3) ****DFFits**** indicate the difference between the adjusted predicted value and the original predicted value. Adjusted predicted value for a case refers to the predicted value of that case, when that case is excluded from model fit.

(4) ****Cook's distance**** indicates leverage. Problematic values for cook's distance > 1 Cook and Weisberg (1982).

(5) ****Hat values**** indicate leverage. Problematic values for Hat values 2 or 3 times the average $(k+1)/n$

The average leverage value is defined as $(k+1)/n$, k =number of predictors, n =number of participants. Leverage values lie between 0 (no influence) and 1 (complete influence over prediction)

- Hoaglin and Welsch (1978) recommends investigating cases with values greater than twice the average $2(k+1)/n$

- Stevens (2002) recommends investigating cases with values greater than three times the average $3(k+1)/n$

****T-tests**** test the hypothesis that b's are different from 0

****Multiple R²****: Variance Explained

****Adjusted R²****: Indicates how much variance in Y would be accounted for if the model is derived from the population from which the sample was taken. Ideally, $R^2 = \text{Adjusted } R^2$

****F-Statistic**** tests the null hypothesis is that the overall model has no effect

****Covariance ratios**** critical values $\text{CVR} > 1 + [3(k+1)/n]$ $\text{CRV} < 1 - [3(k+1)/n]$. In general we should obtain small values or we may have to remove cases

****ASSUMPTIONS****

(1) variable types: All predictors must be quantitative or categorical (with two levels), and the outcome variable must be quantitative (interval data), continuous and unbounded (no constraints on the variability of the outcome) (2) Non-zero variance

(3) No perfect multicollinearity

(4) Predictors are uncorrelated with -external variables-

(5) Homoscedasticity: At each level of the predictor variable(s), the variance of the residual terms should be constant. Residuals at each level of the predictor(s) should have similar variance (homoscedasticity)

(6) Independent errors: For any two observations the residual terms should be uncorrelated (or independent)

This eventuality is sometimes described as a lack of autocorrelation. This assumption can be tested with the Durbin-Watson test, which tests for serial correlations between errors. Specifically, it tests whether adjacent residuals are correlated The size of the Durbin-Watson statistic depends upon the

number of predictors in the model and the number of observations As a very conservative rule of thumb, values less than 1 or greater than 3 are definitely cause for concern; however, values closer to 2 may still be problematic depending on your sample and model R also provides a p-value of the autocorrelation. Be very careful with the Durbin-Watson test, though, as it depends on the order of the data: if you reorder your data, you'll get a different value

(7) Normally distributed errors: It is assumed that the residuals in the model are random, normally distributed variables with a mean of 0

(8) Independence: It is assumed that all of the values of the outcome variable are independent (in other words, each value of the outcome variable comes from a separate entity)

(9) Linearity: The mean values of the outcome variable for each increment of the predictor(s) lie along a straight line

Examples

```
form<-formula(mpg~qsec)
regressionmodel<-lm(form,data=mtcars)
multipleregressionmodel<-lm(mpg~qsec*hp*wt*drat,data=mtcars)
res<-report_regression(model=regressionmodel,plot_diagnostics=TRUE)
res<-report_regression(model=multipleregressionmodel)
res<-report_regression(model=regressionmodel,file="regression")
res<-report_regression(model=multipleregressionmodel,
                        file="regression",
                        plot_diagnostics=TRUE)
```

report_ttests	<i>T test</i>
---------------	---------------

Description

T test

Usage

```
report_ttests(df, dv, iv, file = NULL, ...)
```

Arguments

- df A data frame containing both the independent and dependent variables.
- dv Integer vector of column indices for the continuous dependent variables.
- iv Integer vector of column indices for the categorical independent variables.
- file output filename
- ... Arguments passed on to `stats::t.test`
 - x a (non-empty) numeric vector of data values.
 - y an optional (non-empty) numeric vector of data values.

alternative a character string specifying the alternative hypothesis, must be one of "two.sided" (default), "greater" or "less". You can specify just the initial letter.

mu a number indicating the true value of the mean (or difference in means if you are performing a two sample test).

paired a logical indicating whether you want a paired t-test.

var.equal a logical variable indicating whether to treat the two variances as being equal. If TRUE then the pooled variance is used to estimate the variance otherwise the Welch (or Satterthwaite) approximation to the degrees of freedom is used.

conf.level confidence level of the interval.

formula a formula of the form `lhs ~ rhs` where `lhs` is a numeric variable giving the data values and `rhs` either 1 for a one-sample or paired test or a factor with two levels giving the corresponding groups. If `lhs` is of class "Pair" and `rhs` is 1, a paired test is done, see Examples.

data an optional matrix or data frame (or similar: see [model.frame](#)) containing the variables in the formula `formula`. By default the variables are taken from `environment(formula)`.

subset an optional vector specifying a subset of observations to be used.

na.action a function which indicates what should happen when the data contain NAs.

Examples

```
report_ttests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2))
report_ttests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(4))
report_ttests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4))
report_ttests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4),alternative="two.sided")
report_ttests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4),alternative="less")
report_ttests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4),alternative="greater")
report_ttests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4),var.equal=TRUE)
report_ttests(df=mtcars,dv=1:7,iv=8:10,var.equal=TRUE,file="ttest")
```

report_wtests	<i>Wilcoxon test</i>
---------------	----------------------

Description

Wilcoxon test

Usage

```
report_wtests(df, dv, iv, file = NULL, ...)
```

Arguments

<code>df</code>	A data frame containing both the independent and dependent variables.
<code>dv</code>	Integer vector of column indices for the continuous dependent variables.
<code>iv</code>	Integer vector of column indices for the categorical independent variables.
<code>file</code>	output filename
<code>...</code>	Arguments passed on to <code>stats::wilcox.test</code>
<code>x</code>	numeric vector of data values. Non-finite (e.g., infinite or missing) values will be omitted.
<code>y</code>	an optional numeric vector of data values: as with <code>x</code> non-finite values will be omitted.
<code>alternative</code>	a character string specifying the alternative hypothesis, must be one of "two.sided" (default), "greater" or "less". You can specify just the initial letter.
<code>mu</code>	a number specifying an optional parameter used to form the null hypothesis. See 'Details'.
<code>paired</code>	a logical indicating whether you want a paired test.
<code>exact</code>	a logical indicating whether an exact p-value should be computed.
<code>correct</code>	a logical indicating whether to apply continuity correction in the normal approximation for the p-value, or an integer k between 0 and 3 giving the number of correction terms to use from the Edgeworth series for the normal approximation.
<code>conf.int</code>	a logical indicating whether a confidence interval should be computed.
<code>conf.level</code>	confidence level of the interval.
<code>tol.root</code>	(when <code>conf.int</code> is true:) a positive numeric tolerance, used in <code>uniroot</code> (*, tol=tol.root) calls.
<code>digits.rank</code>	a number; if finite, <code>rank(signif(r, digits.rank))</code> will be used to compute ranks for the test statistic instead of (the default) <code>rank(r)</code> .
<code>formula</code>	a formula of the form <code>lhs ~ rhs</code> where <code>lhs</code> is a numeric variable giving the data values and <code>rhs</code> either 1 for a one-sample or paired test or a factor with two levels giving the corresponding groups. If <code>lhs</code> is of class "Pair" and <code>rhs</code> is 1, a paired test is done, see Examples.
<code>data</code>	an optional matrix or data frame (or similar: see <code>model.frame</code>) containing the variables in the formula <code>formula</code> . By default the variables are taken from <code>environment(formula)</code> .
<code>subset</code>	an optional vector specifying a subset of observations to be used.
<code>na.action</code>	a function which indicates what should happen when the data contain <code>NA</code> s.

Examples

```
report_wtests(df=df_insurance, dv=which("charges"==names(df_insurance)), iv=c(2))
report_wtests(df=df_insurance, dv=which("charges"==names(df_insurance)), iv=c(4))
report_wtests(df=df_insurance, dv=which("charges"==names(df_insurance)), iv=c(2,4))
report_wtests(df=df_insurance, dv=which("charges"==names(df_insurance)), iv=c(2,4), alternative="two.sided")
```

```
report_wtests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4),alternative="less")
report_wtests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4),alternative="greater")
report_wtests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4),var.equal=TRUE)
report_wtests(df=df_insurance,dv=which("charges"==names(df_insurance)),iv=c(2,4),var.equal=TRUE,file="wilcoxon")
```

report_xgboost	<i>Report for xgboost::xgb.train</i>
----------------	--------------------------------------

Description

Report for xgboost::xgb.train

Usage

```
report_xgboost(  
  model,  
  validation_data = NULL,  
  label = NULL,  
  file = "xgboost",  
  w = 10,  
  h = 10,  
  base_size = 10,  
  title = "",  
  fast = FALSE  
)
```

Arguments

model	object from xgboost::xgb.train
validation_data	validation data
label	outcome variable name
file	output filename
w	width of pdf file
h	height of pdf file
base_size	base font size
title	plot title
fast	if TRUE error values are not saved in output

Examples

```

infert_formula<-formula(case~education+spontaneous+induced)
boston_formula<-formula(medv~crim+zn+indus+chas+nox+rm+age+dis+rad+tax+ptratio+black+lstat)
train_test_classification<-k_fold(df=infert,model_formula=infert_formula)
train_test_regression<-k_fold(df=MASS::Boston,model_formula=boston_formula)
xgb_classification<-xgboost::xgb.train(
  params=xgboost::xgb.params(objective="binary:logistic"),
  data=train_test_classification$xgb$f1$train,
  evals=train_test_classification$xgb$f1$watchlist,
  nround=20)
xgb_regression<-xgboost::xgb.train(
  data=train_test_regression$xgb$f1$train,
  evals=train_test_regression$xgb$f1$watchlist,
  nround=20)

## Not run:
report_xgboost(model=xgb_classification,
  validation_data=train_test_classification$f$test$f1,
  label=train_test_classification$outcome,
  file="Classification")
report_xgboost(model=xgb_regression,
  validation_data=train_test_regression$f$test$f1,
  label=train_test_regression$outcome,
  file="Regression")

## End(Not run)

```

response_dimension	<i>index parameter and items relative to their dimensions</i>
--------------------	---

Description

index parameter and items relative to their dimensions

Usage

```
response_dimension(response, dimensions, items)
```

Arguments

response	vector one to number of items
dimensions	number of dimensions
items	item comparisons

Examples

```

response_dimension(c(1:18),3,c(1,2))
response_dimension(c(1:18),3,c(1,3))
response_dimension(c(1:18),3,c(2,3))

```

response_frequency	<i>Response frequencies</i>
--------------------	-----------------------------

Description

returns count proportion percent

Usage

```
response_frequency(  
  df,  
  max = 10,  
  uniqueitems = NULL,  
  type = "percent",  
  file = NULL  
)
```

Arguments

df	dataframe
max	maximum score
uniqueitems	number of unique items
type	"frequency" "proportion" "percent" "all"
file	output filename

Details

returns dataframe

Examples

```
response_frequency(mtcars[,c("gear", "carb")], uniqueitems=1:8, type="frequency")  
response_frequency(mtcars[,c("gear")], uniqueitems=1:8, type="proportion")  
response_frequency(mtcars[,c("gear", "carb")], uniqueitems=1:8, type="percent")  
response_frequency(mtcars[,c("gear", "carb")], uniqueitems=1:8, type="all")  
response_frequency(mtcars[,c("gear", "carb")], uniqueitems=1:8, type="all",  
  file="descriptives")
```

result_confusion_performance

Plot performance of confusion matrix for different cut off points

Description

This function generates a plot to visualize the performance of a confusion matrix at various cut-off points. It evaluates the proportion of correct classifications and identifies the optimal cut-off point.

Usage

```
result_confusion_performance(
  observed,
  predicted,
  step = 0.1,
  base_size = 10,
  title = ""
)
```

Arguments

observed	Vector of observed outcomes. These are the true class labels.
predicted	Vector of predicted outcome probabilities. These are the predicted probabilities for the positive class.
step	Numeric value representing the stepping for tested cut values. Defaults to 0.1.
base_size	Integer value representing the base font size for the plot. Defaults to 10.
title	String representing the title of the plot. Defaults to an empty string.

Details

This function evaluates the performance of a confusion matrix at different cut-off points. It iterates through a range of cut-off points, calculates the confusion matrix, and evaluates the proportion of correct classifications for each cut-off.

The function generates a plot that includes: -The proportion of correct classifications for different cut-off points. -Vertical lines indicating the optimal cut-off point. -A legend representing different performance metrics. -A caption showing the number of observations and the optimal cut-off point.

The function returns a list containing the plot, the data frame with cut-off performance, the optimal cut-off point, and the confusion matrix at the optimal cut-off.

Examples

```
# Example with numeric class labels
df<-data.frame(matrix(.999,ncol=2,nrow=2))
correlation_matrix<-as.matrix(df)
diag(correlation_matrix)<-1
df<-generate_correlation_matrix(correlation_matrix,nrows=1000)
```

```
df$X1<-ifelse(abs(df$X1) < 1,0,1)
df$X2<-abs(df$X2)
df$X2<-(df$X2-min(df$X2))/(max(df$X2)-min(df$X2))
result_confusion_performance(observed=round(abs(df$X1),0),
                             predicted=abs(df$X2),
                             step=0.01)
result_confusion_performance(observed=c(1,2,3,1,2,3),
                             predicted=abs(rnorm(6,0,sd=0.1)))
```

round_dataframe	<i>Round dataframe</i>
-----------------	------------------------

Description

It only processes numeric values in a dataframe

Usage

```
round_dataframe(df, digits = 0, type = "round")
```

Arguments

- df dataframe
- digits decimal points to return. It works only with "round" type
- type "round" "ceiling" "floor" "tenth"

Examples

```
round_dataframe(df=change_data_type(df=mtcars,type="factor"),digits=0)
round_dataframe(df=change_data_type(df=mtcars,type="character"),digits=0)
round_dataframe(df=mtcars,digits=0)
round_dataframe(df=mtcars,digits=0,type="ceiling")
round_dataframe(df=mtcars,digits=0,type="floor")
round_dataframe(df=mtcars*100,digits=2,type="tenth")
```

shrout	<i>Shrout reliability</i>
--------	---------------------------

Description

Shrout reliability

Usage

```
shrout(spersion, spersonitem, stime, spersontime, serror, m, k)
```

Arguments

sperson	variance component of participant
spersonitem	variance component of participant by item interaction
stime	variance component of time
spersontime	variance component of participant by time interaction
serror	variance component of error
m	m item reports
k	k time points

Examples

```

design<-expand.grid(time=1:3,item=1:2,person=1:10)
design<-change_data_type(design,type="factor")
design$response<-rnorm(30,0,0.1)
model<-mixlm::lm(response~r(time)*r(person)+r(item)*r(person),data=design)
result<-extract_components(model)
vc<-result$components
shrout(spersion=vc[2,3],spersonitem=vc[5,3],stime=vc[1,3],
       spersontime=vc[4,3],serror=vc[6,3],3,3)

```

simulate_cfa_fit

*Simulate CFA model fit across sample sizes***Description**

Runs a confirmatory factor analysis (CFA) repeatedly across a range of sample sizes and returns fit indices for each. Useful for power analysis and sample size planning in SEM.

Two workflows are supported:

- **Coefficient-based:** supply `model_sim` with fixed loadings — data are generated from those population parameters at each sample size.
- **Correlation-based:** supply `df` — data are bootstrapped from the observed correlation structure of `df` at each sample size.

Iterations run in parallel via `future.apply`. Results are written to a PDF (scatter plots of fit indices vs. sample size) and an Excel file.

Usage

```

simulate_cfa_fit(
  model_sim = NULL,
  model = NULL,
  df = NULL,
  minnobs = 50,
  maxnobs = 1000,

```



```

stepping = 10,
file = NULL,
w = 10,
h = 10
)

```

Arguments

model_sim	A lavaan model string with fixed coefficients (e.g. "F =~ 1*x1 + 0.8*x2"). Used to generate population data. Mutually exclusive with df; supply one or the other.
model	A lavaan model string with free coefficients specifying the CFA structure to be estimated at each sample size (e.g. "F =~ x1 + x2").
df	A data frame of observed data. When supplied, each iteration simulates data by sampling from the observed correlation structure. Mutually exclusive with model_sim.
minnobs	Integer. Smallest sample size to evaluate. Default 50.
maxnobs	Integer. Largest sample size to evaluate. Default 1000.
stepping	Integer. Increment between sample sizes. Default 10.
file	Character. Base name (without extension) for the output PDF and Excel files. If NULL no files are written.
w	Numeric. Width of the output PDF in inches. Default 10.
h	Numeric. Height of the output PDF in inches. Default 10.

Value

A list of two elements:

- `[[1]]` — a data frame with one row per sample size and one column per lavaan fit index (CFI, RMSEA, SRMR, etc.).
- `[[2]]` — a named list of ggplot scatter plots, one per fit index, showing how the index changes with sample size.

Examples

```

model_sim <- 'LATENT =~ 1*X1 + 0.5*X2 + 1.5*X3 + 1.5*X4 + X5'
model      <- 'LATENT =~ X1 + X2 + X3 + X4 + X5'

# Coefficient-based: generate data from known population parameters
result<-simulate_cfa_fit(model_sim=model_sim, model=model,
                        minnobs=50, maxnobs=1000, stepping=100, file="report")
plot_multiplot(plotlist=result[[2]], cols=4)
# Correlation-based: resample from observed data
df <- lavaan::simulateData(model=model_sim, model.type="cfa",
                          return.type="data.frame", sample.nobs=1000)
result<-simulate_cfa_fit(model=model, df=df,
                        minnobs=50, maxnobs=1000, stepping=100, file="report")
plot_multiplot(plotlist=result[[2]], cols=4)

```

```
simulate_correlation_from_sample
```

Generate a dataframe that produces the same correlation matrix as the input dataframe

Description

Generate a dataframe that produces the same correlation matrix as the input dataframe

Usage

```
simulate_correlation_from_sample(cordata, nrows = 10)
```

Arguments

cordata	dataframe
nrows	number of rows to generate

Examples

```
correlation_matrix<-generate_correlation_matrix()
stats::cor(correlation_matrix)
simulate_correlation_from_sample(correlation_matrix,nrows=1000)
stats::cor(simulate_correlation_from_sample(correlation_matrix,nrows=1000))
```

split_str	<i>Split string to dataframe</i>
-----------	----------------------------------

Description

Split string to dataframe

Usage

```
split_str(vector, split = "/", include_original = FALSE)
```

Arguments

vector	String
split	Separation character
include_original	if TRUE it will return the input on a separate column

Examples

```
string<-paste0(1:10,"/",
               generate_string(nchar=2,vector_length=10),"/",
               generate_string(nchar=2,vector_length=10),"/",
               generate_string(nchar=2,vector_length=10))
split_str(string,split="/")
```

split_str_df	<i>Split string in dataframe</i>
--------------	----------------------------------

Description

Split string in dataframe

Usage

```
split_str_df(df, split = "/", type = "row", index, ...)
```

Arguments

df	dataframe
split	Separation character
type	"row" "column" if "row" it will split the string of row names and it will display it on seperate collumns if "column" it will split the string of a spesified collumn and it will display it on separate collumns
index	Numeric index of collumn to split. This is only relevant if type="collumn"
...	arguments passed to split_str

Examples

```
df<-generate_correlation_matrix()
string<-paste0(1:nrow(df),"/",
               generate_string(nchar=2,vector_length=nrow(df)),"/",
               generate_string(nchar=2,vector_length=nrow(df)),"/",
               generate_string(nchar=2,vector_length=nrow(df)))
row.names(df)<-string
split_str_df(df,split="/",type="row")
df[,1]<-string
split_str_df(df,split="/",type="collumn",index=1)
```

stat_word_char	<i>Text similarity measures</i>
----------------	---------------------------------

Description

Text similarity measures

Usage

```
stat_word_char(text)
```

Arguments

text character vector

Examples

```
text<-"There are many variations of passages of Lorem Ipsum available,
but the majority have suffered alteration in some form, by injected humour,
or randomised words which don't look even slightly believable."
stat_word_char(text)
```

string_aes	<i>Adjust string aesthetics</i>
------------	---------------------------------

Description

Treats spesific characters such as ".", as separating characters and separates strings with space. Trims leading and trailing spaces and capitalizes the first letter of the string and lowers the rest.

Usage

```
string_aes(
  vector,
  characterlist = c(".", "_", "-", ",", "$", "<p>", "</p>", "<br>", "<br/>", "<B>",
    "</B>", "<BR/>", "|", "/", "&nbsp;"),
  proper = TRUE
)
```

Arguments

vector Vector
characterlist List the list of characters to treat as separating characters
proper Logical TRUE capitalizes the first letter in sentence format

Examples

```
vector<-c("TES.T", "TES<p>T", "TES&nbsp;T")
string_aes(vector=vector)
string_aes(vector=vector,proper=FALSE)
string_aes(vector=vector,proper=TRUE)
```

str_count	<i>Count the number of pattern matches in a string</i>
-----------	--

Description

Returns the number of times pattern appears in each element of string. Supports both regular expressions and literal string matching via `fixed()`.

Returns the number of times pattern appears in each element of string. Supports both regular expressions and literal string matching via `fixed()`.

Usage

```
str_count(string, pattern)
```

```
str_count(string, pattern)
```

Arguments

string A character vector.

pattern A regular expression string or a literal string wrapped in `fixed()`.

Value

An integer vector the same length as string.

An integer vector the same length as string.

Examples

```
# Count vowels
str_count(c("banana", "apple", "cherry"), "[aeiou]")

# Count literal semicolons (useful for delimited data)
str_count(c("a;b;c", "x;y", "z"), fixed(";"))

# Count digits
str_count(c("abc123", "99bottles", "none"), "[0-9]")
# Count vowels
str_count(c("banana", "apple", "cherry"), "[aeiou]")

# Count literal semicolons (useful for delimited data)
str_count(c("a;b;c", "x;y", "z"), fixed(";"))
```

```
# Count digits
str_count(c("abc123", "99bottles", "none"), "[0-9]")
```

str_pad	<i>Pad a string to a minimum width</i>
---------	--

Description

Pads string with pad characters on the left, right, or both sides until it reaches at least width characters. Strings already at or exceeding width are returned unchanged.

Pads string with pad characters on the left, right, or both sides until it reaches at least width characters. Strings already at or exceeding width are returned unchanged.

Usage

```
str_pad(string, width, side = "right", pad = " ")
```

```
str_pad(string, width, side = "right", pad = " ")
```

Arguments

string	A character vector.
width	Integer. Minimum total width of the output string.
side	One of "right" (default), "left", or "both".
pad	A single character to use for padding. Default " ".

Value

A character vector the same length as string.

A character vector the same length as string.

Examples

```
# Zero-pad single digit numbers on the left
str_pad(c("1", "10", "100"), width=3, side="left", pad="0")
```

```
# Right-pad to align labels
str_pad(c("Name", "Age", "Score"), width=10)
```

```
# Pad on both sides (centers the string)
str_pad("hello", width=11, side="both")
# Zero-pad single digit numbers on the left
str_pad(c("1", "10", "100"), width=3, side="left", pad="0")
```

```
# Right-pad to align labels
str_pad(c("Name", "Age", "Score"), width=10)
```

```
# Pad on both sides (centers the string)
str_pad("hello", width=11, side="both")
```

str_replace	<i>Replace the first pattern match in a string</i>
-------------	--

Description

Replaces only the first occurrence of pattern in each element of string. For replacing all occurrences use str_replace_all.

Replaces only the first occurrence of pattern in each element of string. For replacing all occurrences use str_replace_all.

Usage

```
str_replace(string, pattern, replacement)
```

```
str_replace(string, pattern, replacement)
```

Arguments

string	A character vector.
pattern	A regular expression string or a literal string wrapped in fixed().
replacement	A character string to replace the first match with.

Value

A character vector the same length as string.

A character vector the same length as string.

Examples

```
# Only the first "o" is replaced
str_replace("hello world", "o", "0")

# Remove leading zero (first match only)
str_replace("007 bond", "^0+", "")

# Fixed match: replace first literal dot
str_replace("a.b.c", fixed("."), "-")
# Only the first "o" is replaced
str_replace("hello world", "o", "0")

# Remove leading zero (first match only)
str_replace("007 bond", "^0+", "")

# Fixed match: replace first literal dot
str_replace("a.b.c", fixed("."), "-")
```

str_replace_all	<i>Replace all pattern matches in a string</i>
-----------------	--

Description

Replaces every occurrence of pattern in string with replacement. Supports both regular expressions and literal string matching via `fixed()`.

Replaces every occurrence of pattern in string with replacement. Supports both regular expressions and literal string matching via `fixed()`.

Usage

```
str_replace_all(string, pattern, replacement)
```

```
str_replace_all(string, pattern, replacement)
```

Arguments

string	A character vector.
pattern	A regular expression string, or a literal string wrapped in <code>fixed()</code> , or a named character vector where names are regex patterns and values are replacements (applied sequentially).
replacement	A character string to replace each match with. Use "" to delete matches.

Value

A character vector the same length as string.

A character vector the same length as string.

Examples

```
# Regex replacement
str_replace_all("hello world", "o", "0")

# Fixed (literal) replacement
str_replace_all("a.b.c", fixed("."), "-")

# Remove all spaces
str_replace_all("remove all spaces", fixed(" "), "")

# Named vector: multiple replacements applied in order
str_replace_all("aabbcc", c("a"="X", "b"="Y"))
# Regex replacement
str_replace_all("hello world", "o", "0")

# Fixed (literal) replacement
str_replace_all("a.b.c", fixed("."), "-")
```



```
# Remove all spaces
str_replace_all("remove all spaces", fixed(" "), "")

# Named vector: multiple replacements applied in order
str_replace_all("aabbcc", c("a"="X", "b"="Y"))
```

str_split_fixed

Split strings into a fixed-width matrix of pieces

Description

Splits each element of string by pattern and returns a character matrix with exactly n columns. If a string produces fewer than n pieces the remaining columns are filled with "".

Splits each element of string by pattern and returns a character matrix with exactly n columns. If a string produces fewer than n pieces the remaining columns are filled with "".

Usage

```
str_split_fixed(string, pattern, n)
```

```
str_split_fixed(string, pattern, n)
```

Arguments

string	A character vector.
pattern	A regular expression string or a literal string wrapped in fixed().
n	Integer. Number of columns in the output matrix.

Value

A character matrix with length(string) rows and n columns.

A character matrix with length(string) rows and n columns.

Examples

```
# Split "trait.method" labels into two columns
str_split_fixed(c("speed.run", "height.jump", "weight.lift"), fixed("."), 2)

# Split on a regex pattern
str_split_fixed(c("a1b", "c2d", "e3f"), "[0-9]", 2)

# Fewer pieces than n: remainder filled with ""
str_split_fixed(c("a.b.c", "x.y"), fixed("."), 3)
# Split "trait.method" labels into two columns
str_split_fixed(c("speed.run", "height.jump", "weight.lift"), fixed("."), 2)

# Split on a regex pattern
```

```
str_split_fixed(c("a1b", "c2d", "e3f"), "[0-9]", 2)

# Fewer pieces than n: remainder filled with ""
str_split_fixed(c("a.b.c", "x.y"), fixed("."), 3)
```

str_squish	<i>Remove leading, trailing, and internal extra whitespace</i>
------------	--

Description

Strips leading and trailing whitespace and collapses any internal sequences of whitespace (spaces, tabs, newlines) down to a single space.

Strips leading and trailing whitespace and collapses any internal sequences of whitespace (spaces, tabs, newlines) down to a single space.

Usage

```
str_squish(string)

str_squish(string)
```

Arguments

string A character vector.

Value

A character vector the same length as string.

A character vector the same length as string.

Examples

```
# Remove extra internal spaces
str_squish(" hello world ")

# Clean up messy column names or labels
str_squish(c(" first name ", "last name", " age"))

# Handles tabs and newlines too
str_squish("line1\n\nline2\t\tword")
# Remove extra internal spaces
str_squish(" hello world ")

# Clean up messy column names or labels
str_squish(c(" first name ", "last name", " age"))

# Handles tabs and newlines too
str_squish("line1\n\nline2\t\tword")
```

`str_wrap`*Wrap long strings to a specified line width*

Description

Breaks a character string into multiple lines so that no line exceeds width characters. Words are kept intact; lines are joined with "\n".

Breaks a character string into multiple lines so that no line exceeds width characters. Words are kept intact; lines are joined with "\n".

Usage

```
str_wrap(string, width = 80)
```

```
str_wrap(string, width = 80)
```

Arguments

string A character vector.

width Maximum number of characters per line. Default 80.

Value

A character vector the same length as string, with embedded newlines inserted at word boundaries.

A character vector the same length as string, with embedded newlines inserted at word boundaries.

Examples

```
# Wrap at 30 characters
cat(str_wrap("The quick brown fox jumped over the lazy dog", width=30))

# Wrap a vector of strings
labels <- c("Short label", "A much longer label that needs wrapping")
str_wrap(labels, width=20)
# Wrap at 30 characters
cat(str_wrap("The quick brown fox jumped over the lazy dog", width=30))

# Wrap a vector of strings
labels <- c("Short label", "A much longer label that needs wrapping")
str_wrap(labels, width=20)
```

sub_str	<i>Return n characters from left or right</i>
---------	---

Description

Return n characters from left or right

Usage

```
sub_str(x, n = 2, type)
```

Arguments

x	Character
n	Number of characters to return
type	"right" "left"

Examples

```
sub_str("12345",n=2,type="right")
sub_str("12345",n=2,type="left")
```

swap	<i>Reverse a numeric vector</i>
------	---------------------------------

Description

Reverse a numeric vector

Usage

```
swap(vector)
```

Arguments

vector	numeric
--------	---------

Examples

```
swap(c(1:10,1,2,3))
```

symmetric_matrix	<i>Symmetric Matrix</i>
------------------	-------------------------

Description

Symmetric Matrix

Usage

```
symmetric_matrix(matrix, duplicate = "lower", diagonal = NULL)
```

Arguments

matrix	matrix
duplicate	"upper" duplicates upper triangle "lower" duplicates lower triangle
diagonal	diagonal values

Examples

```
m_lower<-matrix_triangle(matrix(1:9,nrow=3,ncol=3),type="lower",diagonal=NA)
m_upper<-matrix_triangle(matrix(11:19,nrow=3,ncol=3),type="upper",diagonal=NA)
symmetric_matrix(matrix=m_lower,duplicate="lower",diagonal=NA)
symmetric_matrix(matrix=m_upper,duplicate="upper",diagonal=NA)
```

tag_pos	<i>Part of speech tagging</i>
---------	-------------------------------

Description

Part of speech tagging

Usage

```
tag_pos(text)
```

Arguments

text	character vector
------	------------------

Examples

```

text1<-"word_one word_two word_three"
text2<-"word_three word_four word_six"
text3<-"All the Lorem Ipsum generators on the Internet tend to repeat predefined
chunks as necessary, making this the first true generator on the Internet."
text4<-"It uses a dictionary of over 200 Latin words, combined with a handful of
model sentence structures, to generate Lorem Ipsum which looks reasonable."
text5<-"The generated Lorem Ipsum is therefore always free from repetition,
injected humour, or non-characteristic words etc."
text<-c(text1,text2,text3,text4,text5)
tag_pos(text)

```

text_similarity	<i>Text similarity measures</i>
-----------------	---------------------------------

Description

Text similarity measures

Usage

```
text_similarity(text1, text2)
```

Arguments

text1	character vector
text2	character vector

Examples

```

text1<-"word_one word_two word_three"
text2<-"word_three word_four word_six"
text3<-"All the Lorem Ipsum generators on the Internet tend to repeat predefined
chunks as necessary, making this the first true generator on the Internet."
text4<-"It uses a dictionary of over 200 Latin words, combined with a handful of
model sentence structures, to generate Lorem Ipsum which looks reasonable."
text5<-"The generated Lorem Ipsum is therefore always free from repetition,
injected humour, or non-characteristic words etc."
text<-c(text1,text2,text3,text4,text5)
text<-unlist(strsplit(text,split=" "))
text1<-unlist(strsplit(text1,split=" "))
text2<-unlist(strsplit(text2,split=" "))
text3<-unlist(strsplit(text3,split=" "))
text4<-unlist(strsplit(text4,split=" "))
text5<-unlist(strsplit(text5,split=" "))
text_similarity(text1,text1)
text_similarity(text1,text2)
text_similarity(text1,text3)
text_similarity(text1,text4)

```

trim_df*Trim whitespace in dataframe*

Description

Trim whitespace in dataframe

Usage

```
trim_df(df)
```

Arguments

df dataframe

Examples

```
string<-data.frame(str1=rep(paste0(sample(c(LETTERS,rep(" ",10))),collapse=""),10),
                    str2=rep(paste0(sample(c(LETTERS,rep(" ",10))),collapse=""),10),
                    num1=rnorm(10),
                    stringsAsFactors=FALSE)

trim_df(string)
```

ts_smoothing*Smoothing*

Description

smoothing for timeseries. uses base plot

Usage

```
ts_smoothing(
  df,
  start = 0.01,
  stop = 2,
  step = 0.001,
  title = "",
  type = "kernel"
)
```

Arguments

df	ts object
start	start value
stop	stop value
step	step
title	plot title
type	"default" "kernel" "lowess" "friedman" "splines" "polynomial" "linear"

Details

returns plot

Examples

```
ts_data<-ts(UKDriverDeaths,start=1969,end=1984,frequency=12)
par(mfrow=c(2,2))
ts_smoother(ts_data,start=.01,stop=2,step=.01,title="Driver Deaths in UK",type="default")
ts_smoother(ts_data,start=.01,stop=2,step=.01,title="Driver Deaths in UK",type="polynomial")
ts_smoother(ts_data,start=.01,stop=2,step=.01,title="Driver Deaths in UK",type="linear")
ts_smoother(ts_data,start=.01,stop=2,step=.01,title="Driver Deaths in UK",type="kernel")
ts_smoother(ts_data,start=.01,stop=2,step=.01,title="Driver Deaths in UK",type="lowess")
ts_smoother(ts_data,start=.01,stop=2,step=.01,title="Driver Deaths in UK",type="friedman")
ts_smoother(ts_data,start=.01,stop=2,step=.01,title="Driver Deaths in UK",type="splines")
```

wrapper	<i>Wrap string</i>
---------	--------------------

Description

Wrap string

Usage

```
wrapper(x, ...)
```

Arguments

x	title
...	arguments passed to strwrap

Examples

```
wrapper(rep("sting",50),30)
```

write_txt	<i>Log console in file</i>
-----------	----------------------------

Description

Logs console in file and then displays log in console

Usage

```
write_txt(input, file = NULL)
```

Arguments

input	Script to log in log file
file	Filename of log

Examples

```
write_txt(mtcars)  
write_txt(mtcars,file="mtcars")
```

Index

* ANOVA

- compute_aov_es, [15](#)
- compute_kruskal_wallis_test, [22](#)
- compute_one_way_test, [25](#)
- compute_posthoc, [25](#)
- plot_interaction, [92](#)
- plot_oneway, [99](#)
- plot_oneway_diagnostics, [100](#)
- report_factorial_anova, [124](#)
- report_manova, [130](#)
- report_oneway, [132](#)
- report_ttests, [136](#)
- report_wtests, [137](#)

* EFA

- compute_residual_stats, [27](#)
- model_loadings, [81](#)
- plot_loadings, [94](#)
- plot_scree, [106](#)
- report_efa, [123](#)

* IRT

- cfa_icc_index, [10](#)
- compute_ability, [13](#)
- compute_dummy_comparisons, [18](#)
- compute_icc_thurstonian, [20](#)
- compute_info_1pl, [20](#)
- compute_info_2pl, [21](#)
- compute_info_3pl, [22](#)
- compute_map, [24](#)
- compute_scores, [28](#)
- compute_se_theta, [28](#)
- compute_unidimensional_ability, [32](#)
- compute_unidimensional_theta, [33](#)
- generate_comparisons_matrix, [67](#)
- generate_matrix_A, [70](#)
- generate_matrix_lambda_hat, [70](#)
- generate_unique_comparisons_index, [72](#)
- icc_cfa, [74](#)
- increase_index, [75](#)

- plot_icc_thurstonian, [91](#)
- plot_irt_onefactor, [93](#)
- rank3_to_triplets, [112](#)
- rank_df_to_binary, [112](#)
- rank_to_binary, [113](#)
- report_irt, [127](#)
- response_dimension, [140](#)

* ML

- plot_trees_xgboost, [107](#)
- report_lda, [128](#)
- report_xgboost, [139](#)

* NLP

- clear_stopwords, [11](#)
- clear_text, [12](#)
- stat_word_char, [148](#)
- tag_pos, [157](#)
- text_similarity, [158](#)

* SEM

- report_cfa, [119](#)
- simulate_cfa_fit, [144](#)

* Thurstonian

- cfa_icc_index, [10](#)
- compute_ability, [13](#)
- compute_dummy_comparisons, [18](#)
- compute_icc_thurstonian, [20](#)
- compute_map, [24](#)
- compute_scores, [28](#)
- generate_comparisons_matrix, [67](#)
- generate_matrix_A, [70](#)
- generate_matrix_lambda_hat, [70](#)
- generate_unique_comparisons_index, [72](#)
- icc_cfa, [74](#)
- increase_index, [75](#)
- plot_icc_thurstonian, [91](#)
- rank3_to_triplets, [112](#)
- rank_df_to_binary, [112](#)
- rank_to_binary, [113](#)
- response_dimension, [140](#)

- * **assumptions**
 - outlier_summary, 82
 - plot_boxplot, 85
 - plot_histogram, 90
 - plot_normality_diagnostics, 98
 - plot_outlier, 101
 - plot_qq, 102
 - remove_outliers, 117
 - report_normality_tests, 131
- * **correlation**
 - compute_power_r, 26
 - compute_power_r_matrix, 27
 - deg2rad, 39
 - plot_corrplot, 89
 - rad2deg, 111
 - report_choric_serial, 120
 - report_correlation, 121
- * **dataframe**
 - cdf, 7
 - cdff, 9
- * **datasets**
 - df_admission, 40
 - df_automotive_data, 41
 - df_blood_pressure, 42
 - df_co2, 42
 - df_crop_yield, 43
 - df_difficile, 44
 - df_insurance, 44
 - df_ocean, 45
 - df_personality, 49
 - df_responses, 51
 - df_responses_state, 55
 - df_sexual_comp, 56
 - df_titanic, 57
- * **data**
 - generate_correlation_matrix, 68
 - generate_data, 68
 - generate_factor, 69
 - generate_missing, 71
 - generate_multiple_responce_vector, 71
 - generate_string, 72
 - simulate_correlation_from_sample, 146
- * **descriptives**
 - compute_aggregate, 15
 - compute_crosstable, 17
 - compute_descriptives, 17
 - compute_frequencies, 19
 - plot_crosstable, 89
 - plot_mosaic, 96
 - plot_response_frequencies, 103
 - response_frequency, 141
- * **diagnostics**
 - cdf, 7
 - cdff, 9
- * **dimensions**
 - questions_by_keys, 110
 - questions_dimensions_dataframe, 111
- * **distance**
 - compute_tversky_index, 31
- * **functions**
 - c_bind, 37
 - call_to_string, 6
 - change_data_type, 11
 - comparison_combinations, 13
 - compute_adjustment, 14
 - compute_confidence_inteval, 16
 - compute_dissatenuation, 18
 - compute_kurtosis, 23
 - compute_skewness, 29
 - compute_standard, 29
 - compute_standard_error, 30
 - confusion, 35
 - confusion_matrix_percent, 35
 - data_frame_index, 38
 - detach_package, 40
 - display_upper_lower_triangle, 58
 - dotnames, 58
 - drop_levels, 59
 - dummy_arrange, 59
 - duplicate_y_axis, 60
 - environment_options, 61
 - excel_confusion_matrix, 61
 - excel_critical_value, 62
 - excel_generic_format, 63
 - excel_matrix, 64
 - flatten_list, 67
 - generate_correlation_matrix, 68
 - generate_data, 68
 - generate_factor, 69
 - generate_missing, 71
 - generate_multiple_responce_vector, 71
 - generate_string, 72

- get_script_directory, 73
- getfw, 73
- hinvert_title_grob, 74
- install_all_packages, 75
- install_load, 76
- k_fold, 77
- k_sample, 78
- matrix_triangle, 79
- mgsub, 80
- min_max_index, 80
- off_diagonal_index, 82
- output_separator, 83
- padNA, 84
- plot_confusion, 88
- plot_multiplot, 97
- plot_roc, 103
- plot_separability, 106
- proper, 109
- proportion_accurate, 109
- questions_by_keys, 110
- questions_dimensions_dataframe, 111
- rbind_all, 114
- recode_scale_dummy, 115
- remove_nc, 116
- remove_user_packages, 117
- replace_na_with_previous, 118
- report_dataframe, 122
- report_pdf, 133
- result_confusion_performance, 142
- round_dataframe, 143
- simulate_correlation_from_sample, 146
- split_str, 146
- split_str_df, 147
- string_aes, 148
- sub_str, 156
- swap, 156
- symmetric_matrix, 157
- trim_df, 159
- wrapper, 160
- write_txt, 161
- * generate**
 - generate_correlation_matrix, 68
 - generate_data, 68
 - generate_factor, 69
 - generate_missing, 71
 - generate_multiple_responce_vector, 71
 - generate_string, 72
 - simulate_correlation_from_sample, 146
- * keys**
 - questions_by_keys, 110
 - questions_dimensions_dataframe, 111
- * logistic**
 - compute_y_logistic, 34
 - output_compare_model_logistic, 83
 - plot_logistic_model, 95
 - report_logistic, 128
- * matrix**
 - display_upper_lower_triangle, 58
 - matrix_triangle, 79
 - off_diagonal_index, 82
 - symmetric_matrix, 157
- * missing-values**
 - cdf, 7
 - cdff, 9
- * plot**
 - duplicate_y_axis, 60
 - hinvert_title_grob, 74
 - plot_multiplot, 97
 - report_pdf, 133
 - wrapper, 160
- * regression**
 - compute_y_logistic, 34
 - output_compare_model_logistic, 83
 - plot_logistic_model, 95
 - plot_scatterplot, 104
 - report_logistic, 128
 - report_regression, 134
- * reliability**
 - alpha_diagnostics, 6
 - extract_components, 66
 - key_to_cfa_model, 76
 - mean_sd_alpha, 79
 - plot_mtm, 96
 - raw_alpha, 114
 - report_alpha, 118
 - shrout, 143
- * series**
 - compute_moving_average, 24
 - plot_acf, 85
 - plot_ts, 108
 - ts_smoothing, 159

- * **set**
 - compute_tversky_index, 31
- * **similarity**
 - compute_tversky_index, 31
- * **statistical**
 - compute_adjustment, 14
 - compute_confidence_interval, 16
 - compute_dissatenuation, 18
 - compute_kurtosis, 23
 - compute_skewness, 29
 - compute_standard, 29
 - compute_standard_error, 30
- * **strings**
 - call_to_string, 6
 - fixed, 66
 - mgsub, 80
 - output_separator, 83
 - proper, 109
 - split_str, 146
 - split_str_df, 147
 - str_count, 149
 - str_pad, 150
 - str_replace, 151
 - str_replace_all, 152
 - str_split_fixed, 153
 - str_squish, 154
 - str_wrap, 155
 - string_aes, 148
 - sub_str, 156
 - trim_df, 159
- * **summary**
 - cdf, 7
 - cdff, 9
- * **timestamp**
 - convert_excel_unix_timestamp, 37
 - decompose_datetime, 38
- * **time**
 - compute_moving_average, 24
 - plot_acf, 85
 - plot_ts, 108
 - ts_smoothing, 159
- * **unidimensional**
 - compute_info_1pl, 20
 - compute_info_2pl, 21
 - compute_info_3pl, 22
 - compute_se_theta, 28
 - compute_unidimensional_ability, 32
 - compute_unidimensional_theta, 33
- alpha_diagnostics, 6
- c_bind, 37
- call_to_string, 6
- cdf, 7, 9, 10, 31
- cdff, 9
- cfa_icc_index, 10
- change_data_type, 11
- clear_stopwords, 11
- clear_text, 12
- comparison_combinations, 13
- compute_ability, 13
- compute_adjustment, 14
- compute_aggregate, 15
- compute_aov_es, 15
- compute_confidence_interval, 16
- compute_crosstable, 17
- compute_descriptives, 17
- compute_dissatenuation, 18
- compute_dummy_comparisons, 18
- compute_frequencies, 19
- compute_icc_thurstonian, 20
- compute_info_1pl, 20
- compute_info_2pl, 21
- compute_info_3pl, 22
- compute_kruskal_wallis_test, 22
- compute_kurtosis, 23
- compute_map, 24
- compute_moving_average, 24
- compute_one_way_test, 25
- compute_posthoc, 25
- compute_power_r, 26
- compute_power_r_matrix, 27
- compute_residual_stats, 27
- compute_scores, 28
- compute_se_theta, 28
- compute_skewness, 29
- compute_standard, 29
- compute_standard_error, 30
- compute_tversky_index, 31
- compute_unidimensional_ability, 32
- compute_unidimensional_theta, 33
- compute_y_logistic, 34
- confusion, 35
- confusion_matrix_percent, 35
- convert_excel_unix_timestamp, 37
- data_frame_index, 38
- decompose_datetime, 38

- deg2rad, 39
- detach_package, 40
- df_admission, 40
- df_automotive_data, 41
- df_blood_pressure, 42
- df_co2, 42
- df_crop_yield, 43
- df_difficile, 44
- df_insurance, 44
- df_ocean, 45
- df_personality, 49
- df_responses, 51
- df_responses_state, 55
- df_sexual_comp, 56
- df_titanic, 57
- display_upper_lower_triangle, 58
- dotnames, 58
- drop_levels, 59
- dummy_arrange, 59
- duplicate_y_axis, 60
- environment_options, 61
- excel_confusion_matrix, 61
- excel_critical_value, 62
- excel_generic_format, 63
- excel_matrix, 64
- extract_components, 66
- fixed, 66
- flatten_list, 67
- generate_comparisons_matrix, 67
- generate_correlation_matrix, 68
- generate_data, 68
- generate_factor, 69
- generate_matrix_A, 70
- generate_matrix_lambda_hat, 70
- generate_missing, 71
- generate_multiple_responce_vector, 71
- generate_string, 72
- generate_unique_comparisons_index, 72
- get_script_directory, 73
- getfwp, 73
- hinvert_title_grob, 74
- icc_cfa, 74
- increase_index, 75
- install_all_packages, 75
- install_load, 76
- intersect, 31
- k_fold, 77
- k_sample, 78
- key_to_cfa_model, 76
- matrix_triangle, 79
- mean_sd_alpha, 79
- mgsb, 80
- min_max_index, 80
- model.frame, 137, 138
- model_loadings, 81
- NA, 137, 138
- off_diagonal_index, 82
- outlier_summary, 82
- output_compare_model_logistic, 83
- output_separator, 83
- padNA, 84
- Pair, 137, 138
- plot_acf, 85
- plot_boxplot, 85
- plot_cfa, 86
- plot_cfa_gg, 86
- plot_confusion, 88
- plot_corrplot, 89
- plot_crosstable, 89
- plot_histogram, 90
- plot_icc_thurstonian, 91
- plot_interaction, 92
- plot_irt_onefactor, 93
- plot_loadings, 94
- plot_logistic_model, 95
- plot_mosaic, 96
- plot_mtm, 96
- plot_multiplot, 97
- plot_normality_diagnostics, 98
- plot_oneway, 99
- plot_oneway_diagnostics, 100
- plot_outlier, 101
- plot_qq, 102
- plot_response_frequencies, 103
- plot_roc, 103
- plot_scatterplot, 104
- plot_scee, 106
- plot_separability, 106

plot_trees_xgboost, 107
plot_ts, 108
profile_missing, 8
proper, 109
proportion_accurate, 109

questions_by_keys, 110
questions_dimensions_dataframe, 111

rad2deg, 111
rank, 138
rank3_to_triplets, 112
rank_df_to_binary, 112
rank_to_binary, 113
raw_alpha, 114
rbind_all, 114
recode_scale_dummy, 115
remove_nc, 116
remove_outliers, 117
remove_user_packages, 117
replace_na_with_previous, 118
report_alpha, 118
report_cfa, 119
report_choric_serial, 120
report_correlation, 121
report_dataframe, 122
report_efa, 123
report_factorial_anova, 124
report_hlr, 126
report_irt, 127
report_lda, 128
report_logistic, 128
report_manova, 130
report_normality_tests, 131
report_oneway, 132
report_pdf, 133
report_regression, 134
report_ttests, 136
report_wtests, 137
report_xgboost, 139
response_dimension, 140
response_frequency, 141
result_confusion_performance, 142
round_dataframe, 143

setdiff, 31
shrout, 143
signif, 138
simulate_cfa_fit, 144

simulate_correlation_from_sample, 146
skim, 8, 10
split_str, 146
split_str_df, 147
stat_word_char, 148
stats::t.test, 136
stats::wilcox.test, 138
str, 8, 10
str_count, 149
str_pad, 150
str_replace, 151
str_replace_all, 152
str_split_fixed, 153
str_squish, 154
str_wrap, 155
string_aes, 148
sub_str, 156
summary, 8, 10
swap, 156
symmetric_matrix, 157

tag_pos, 157
text_similarity, 158
trim_df, 159
ts_smoothing, 159

uniroot, 138

wrapper, 160
write_txt, 161