

Ctrl + /

v5.1 ▾

[View on GitHub](#)

Breakpoints

Breakpoints are customizable widths that determine how your responsive layout behaves across device or viewport sizes in Bootstrap.

On this page

[Core concepts](#)[Available breakpoints](#)[Media queries](#)[Min-width](#)[Max-width](#)[Single breakpoint](#)[Between breakpoints](#)

Core concepts

- **Breakpoints are the building blocks of responsive design.** Use them to control when your layout can be adapted at a particular viewport or device size.
- **Use media queries to architect your CSS by breakpoint.** Media queries are a feature of CSS that allow you to conditionally apply styles based on a set of browser and operating system parameters. We most commonly use `min-width` in our media queries.
- **Mobile first, responsive design is the goal.** Bootstrap's CSS aims to apply the bare minimum of styles to make a layout work at the smallest breakpoint, and then layers on styles to adjust that design for larger devices. This optimizes your CSS, improves rendering time, and provides a great experience for your visitors.

Available breakpoints

Bootstrap includes six default breakpoints, sometimes referred to as *grid tiers*, for building responsively. These breakpoints can be customized if you're using our source Sass files.

Breakpoint	Class infix	Dimensions
X-Small	<i>None</i>	<576px
Small	<i>sm</i>	≥576px
Medium	<i>md</i>	≥768px
Large	<i>lg</i>	≥992px
Extra large	<i>xl</i>	≥1200px
Extra extra large	<i>xxl</i>	≥1400px

Each breakpoint was chosen to comfortably hold containers whose widths are multiples of 12. Breakpoints are also representative of a subset of common device sizes and viewport dimensions—they don't specifically target every use case or device. Instead, the ranges provide a strong and consistent foundation to build on for nearly any device.

These breakpoints are customizable via Sass—you'll find them in a Sass map in our `_variables.scss` stylesheet.

```
$grid-breakpoints: (  
  xs: 0,  
  sm: 576px,  
  md: 768px,  
  lg: 992px,  
  xl: 1200px,  
  xxl: 1400px  
);
```

For more information and examples on how to modify our Sass maps and variables, please refer to [the Sass section of the Grid documentation](#).

Media queries

Since Bootstrap is developed to be mobile first, we use a handful of [media queries](#) to create sensible breakpoints for our layouts and interfaces. These breakpoints are mostly based on minimum viewport widths and allow us to scale up elements as the viewport changes.

Min-width


Bootstrap primarily uses the following media query ranges—or breakpoints—in our source Sass files for our layout, grid system, and components.

```
// Source mixins

// No media query necessary for xs breakpoint as it's effectively `@media (min-width: 0)`
@include media-breakpoint-up(sm) { ... }
@include media-breakpoint-up(md) { ... }
@include media-breakpoint-up(lg) { ... }
@include media-breakpoint-up(xl) { ... }
@include media-breakpoint-up(xxl) { ... }

// Usage

// Example: Hide starting at `min-width: 0`, and then show at the `sm` breakpoint
.custom-class {
  display: none;
}
@include media-breakpoint-up(sm) {
  .custom-class {
    display: block;
  }
}
```



These Sass mixins translate in our compiled CSS using the values declared in our Sass variables. For example:

```
// X-Small devices (portrait phones, less than 576px)
// No media query for `xs` since this is the default in Bootstrap

// Small devices (landscape phones, 576px and up)
@media (min-width: 576px) { ... }

// Medium devices (tablets, 768px and up)
@media (min-width: 768px) { ... }

// Large devices (desktops, 992px and up)
@media (min-width: 992px) { ... }

// X-Large devices (large desktops, 1200px and up)
@media (min-width: 1200px) { ... }

// XX-Large devices (larger desktops, 1400px and up)
@media (min-width: 1400px) { ... }
```

Max-width

We occasionally use media queries that go in the other direction (the given screen size *or smaller*):

```
// No media query necessary for xs breakpoint as it's effectively `@media (max-width: 0)`
@include media-breakpoint-down(sm) { ... }
@include media-breakpoint-down(md) { ... }
@include media-breakpoint-down(lg) { ... }
@include media-breakpoint-down(xl) { ... }
@include media-breakpoint-down(xx1) { ... }

// Example: Style from medium breakpoint and down
@include media-breakpoint-down(md) {
  .custom-class {
    display: block;
  }
}
```

These mixins take those declared breakpoints, subtract `.02px` from them, and use them as our `max-width` values. For example:

```
// `xs` returns only a ruleset and no media query
// ... { ... }

// `sm` applies to x-small devices (portrait phones, less than 576px)
@media (max-width: 575.98px) { ... }

// `md` applies to small devices (landscape phones, less than 768px)
@media (max-width: 767.98px) { ... }

// `lg` applies to medium devices (tablets, less than 992px)
@media (max-width: 991.98px) { ... }

// `xl` applies to large devices (desktops, less than 1200px)
@media (max-width: 1199.98px) { ... }

// `xxl` applies to x-large devices (large desktops, less than 1400px)
@media (max-width: 1399.98px) { ... }
```

Why subtract `.02px`? Browsers don't currently support [range context queries](#), so we work around the limitations of [min- and max- prefixes](#) and viewports with fractional widths (which can occur under certain conditions on high-dpi devices, for instance) by using values with higher precision.

Single breakpoint

There are also media queries and mixins for targeting a single segment of screen sizes using the minimum and maximum breakpoint widths.

```
@include media-breakpoint-only(xs) { ... }  
@include media-breakpoint-only(sm) { ... }  
@include media-breakpoint-only(md) { ... }  
@include media-breakpoint-only(lg) { ... }  
@include media-breakpoint-only(xl) { ... }  
@include media-breakpoint-only(xx1) { ... }
```

For example the `@include media-breakpoint-only(md) { ... }` will result in :

```
@media (min-width: 768px) and (max-width: 991.98px) { ... }
```


Between breakpoints

Similarly, media queries may span multiple breakpoint widths:

```
@include media-breakpoint-between(md, xl) { ... }
```

Which results in:

```
// Example  
// Apply styles starting from medium devices and up to extra large devices  
@media (min-width: 768px) and (max-width: 1199.98px) { ... }
```



Designed and built with all the love in the world by the Bootstrap team with the help of our contributors.

Code licensed MIT, docs CC BY 3.0.

Currently v5.1.3.

Links

[Home](#)

[Docs](#)

[Examples](#)

[Themes](#)

[Blog](#)

Projects

[Bootstrap 5](#)

[Bootstrap 4](#)

[Icons](#)

[RFS](#)

[npm starter](#)

Guides

[Getting started](#)

[Starter template](#)

[Webpack](#)

[Parcel](#)

Community

[Issues](#)

[Discussions](#)

[Corporate sponsors](#)

[Open Collective](#)

[Slack](#)

[Stack Overflow](#)