

MealDash

DAX Measures & Calculated Columns Reference

All measures and calculated columns used in **Dashboard/Mealdash_Dashboard.pbix**, built on the **MealDash_Clean** table.

Core Metrics

Total Orders

Total Orders = COUNTROWS(MealDash_Clean)

Base count used across every card and as denominator for percentage measures.

Avg Delivery Time

Avg Delivery Time = AVERAGE(MealDash_Clean[Time_taken _min_])

Headline metric — overall average delivery time in minutes.

Avg Delivery Rating

Avg Delivery Rating = AVERAGE(MealDash_Clean[Delivery_person_Ratings])

Average agent rating across all orders.

Festival Impact

Festival Avg Time

```
Festival Avg Time =  
CALCULATE(  
    AVERAGE(MealDash_Clean[Time_taken _min_]),  
    MealDash_Clean[Festival] = "Yes"  
)
```

Normal Day Avg Time

```
Normal Day Avg Time =  
CALCULATE(  
    AVERAGE(MealDash_Clean[Time_taken _min_]),  
    MealDash_Clean[Festival] = "No"  
)
```

Festival Impact %

Festival Impact % =
DIVIDE([Festival Avg Time] - [Normal Day Avg Time], [Normal Day Avg Time])
Percentage slower on festival days vs. normal days. Drives the "75-80% slower" headline finding.

Slow Delivery Rate

Pct Slow Deliveries

```
Pct Slow Deliveries =  
DIVIDE(  
    CALCULATE(COUNTROWS(MealDash_Clean), MealDash_Clean[Delivery_Flag] = "Slow"),
```

```
COUNTROWS(MealDash_Clean)
)
```

Share of orders flagged as "Slow" via the Delivery_Flag column (built upstream in Power Query).

Trend Over Time

Rolling 7Day Avg

```
Rolling 7Day Avg =
AVERAGEX(
    DATESINPERIOD(MealDash_Clean[Order_Date], MAX(MealDash_Clean[Order_Date]), -7, DAY),
    CALCULATE(AVERAGE(MealDash_Clean[Time_taken _min_]))
)
```

Smooths daily noise to show the underlying trend — confirms delivery time is flat over the period, not drifting.

Day Name

```
Day Name = FORMAT('MealDash_Clean'[Order_Date], "ddd")
```

Day Number

```
Day Number = WEEKDAY('MealDash_Clean'[Order_Date], 2)
```

Used to sort Day Name correctly (Mon to Sun) instead of alphabetically.

City

Slowest City

```
Slowest City =
CALCULATE(
    FIRSTNONBLANK(MealDash_Clean[City], 1),
    TOPN(1,
        SUMMARIZE(MealDash_Clean, MealDash_Clean[City],
            "AvgTime", AVERAGE(MealDash_Clean[Time_taken _min_])),
        [AvgTime], DESC
    )
)
```

Dynamically returns the city with the highest average delivery time, instead of hardcoding "Metropolitan".

Distance Buckets

Distance_Bucket

```
Distance_Bucket =
SWITCH(
    TRUE(),
    MealDash_Clean[Distance_km] <= 5, "0-5 km",
    MealDash_Clean[Distance_km] <= 10, "5-10 km",
    MealDash_Clean[Distance_km] <= 15, "10-15 km",
    "15+ km"
)
```

Distance_Bucket_Sort

```
Distance_Bucket_Sort =
SWITCH(
    TRUE(),
    MealDash_Clean[Distance_km] <= 5, 1,
```

```

MealDash_Clean[Distance_km] <= 10, 2,
MealDash_Clean[Distance_km] <= 15, 3,
4
)

```

Hidden sort-by column so Distance_Bucket displays in logical order instead of alphabetically.

Agent Rating Buckets

Rating_Bucket

```

Rating_Bucket =
IF(
    ISBLANK(MealDash_Clean[Delivery_person_Ratings]),
    BLANK(),
    SWITCH(
        TRUE(),
        MealDash_Clean[Delivery_person_Ratings] >= 4.5, "4.5+",
        MealDash_Clean[Delivery_person_Ratings] >= 4.0, "4.0-4.49",
        MealDash_Clean[Delivery_person_Ratings] >= 3.5, "3.5-3.99",
        "Below 3.5"
    )
)

```

Blank-safe — avoids grouping missing ratings into "Below 3.5" by mistake.

Rating_Bucket_Sort

```

Rating_Bucket_Sort =
SWITCH(
    TRUE(),
    MealDash_Clean[Delivery_person_Ratings] >= 4.5, 4,
    MealDash_Clean[Delivery_person_Ratings] >= 4.0, 3,
    MealDash_Clean[Delivery_person_Ratings] >= 3.5, 2,
    1
)

```

Bundled Deliveries

Multiple_Deliveries_Label

```
Multiple_Deliveries_Label =  
SWITCH(  
    MealDash_Clean[multiple_deliveries],  
    0, "None",  
    1, "1 Additional",  
    2, "2 Additional",  
    3, "3 Additional",  
    "Unknown"  
)
```

Multiple_Deliveries_Sort

```
Multiple_Deliveries_Sort =  
SWITCH(  
    TRUE(),  
    MealDash_Clean[multiple_deliveries] = 0, 1,  
    MealDash_Clean[multiple_deliveries] = 1, 2,  
    MealDash_Clean[multiple_deliveries] = 2, 3,  
    MealDash_Clean[multiple_deliveries] = 3, 4,  
    99  
)
```

Vehicle Condition

Vehicle_Condition_Label

```
Vehicle_Condition_Label =  
SWITCH(  
    MealDash_Clean[Vehicle_condition],  
    0, "Poor",  
    1, "Fair",  
    2, "Good",  
    3, "Excellent",  
    "Unknown"  
)
```

Vehicle_Condition_Sort

```
Vehicle_Condition_Sort =  
SWITCH(  
    MealDash_Clean[Vehicle_condition],  
    0, 1,  
    1, 2,  
    2, 3,  
    3, 4,  
    99  
)
```

Why the *_Sort Columns Exist

Power BI sorts text categories alphabetically by default. Columns like "0-5 km", "5-10 km", "10-15 km" would otherwise sort as 0-5, 10-15, 5-10 — the wrong order. Each *_Sort column is a hidden numeric column, linked to its label column via **Column tool > Sort by Column** in Power BI Desktop, so charts display buckets in the correct

logical order.