

MySQL 8.0 Command Line Client

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

```
mysql> create database anudip;
Query OK, 1 row affected (0.01 sec)

mysql> use anudip;
Database changed
mysql> create table parent(id int primary key,name varchar(20),city varchar(20),age int,income int,occuption varchar(20),email varchar(20));
Query OK, 0 rows affected (0.07 sec)

mysql> insert into parent values(11,"sanjay","mumbai",55,600000,"advocate","sanjay@gmail.com");
Query OK, 1 row affected (0.05 sec)

mysql> insert into parent values(12,"shiv","pune",50,400000,"actor","shiv@gmail.com");
Query OK, 1 row affected (0.01 sec)

mysql> insert into parent values(13,"raghav","delhi",51,400000,"worker","raghav@gmail.com");
Query OK, 1 row affected (0.01 sec)

mysql> insert into paren values(14,"siddharth","pune",53,500000,"techer","siddharth@gmail.com");
ERROR 1146 (42S02): Table 'anudip.paren' doesn't exist
mysql> insert into parent values(14,"siddharth","pune",53,500000,"teacher","siddharth@gmail.com");
Query OK, 1 row affected (0.01 sec)

mysql> insert into parent values(15,"akash","banglore",54,600000,"professor","akash@gmail.com");
Query OK, 1 row affected (0.01 sec)

mysql> select * from parent;
```

| id | name | city | age | income | occuption | email |
|----|-----------|----------|-----|--------|-----------|---------------------|
| 11 | sanjay | mumbai | 55 | 600000 | advocate | sanjay@gmail.com |
| 12 | shiv | pune | 50 | 400000 | actor | shiv@gmail.com |
| 13 | raghav | delhi | 51 | 400000 | worker | raghav@gmail.com |
| 14 | siddharth | pune | 53 | 500000 | teacher | siddharth@gmail.com |
| 15 | akash | banglore | 54 | 600000 | professor | akash@gmail.com |

5 rows in set (0.01 sec)

MySQL 8.0 Command Line Client

5 rows in set (0.01 sec)

```
mysql> update parent set email = "NA";
Query OK, 5 rows affected (0.01 sec)
Rows matched: 5  Changed: 5  Warnings: 0
```

```
mysql> select * from parent;
```

| id | name | city | age | income | occupation | email |
|----|-----------|----------|-----|--------|------------|-------|
| 11 | sanjay | mumbai | 55 | 600000 | advocate | NA |
| 12 | shiv | pune | 50 | 400000 | actor | NA |
| 13 | raghav | delhi | 51 | 400000 | worker | NA |
| 14 | siddharth | pune | 53 | 500000 | teacher | NA |
| 15 | akash | banglore | 54 | 600000 | professor | NA |

5 rows in set (0.00 sec)

```
mysql> update parent set age = 40;
Query OK, 5 rows affected (0.01 sec)
Rows matched: 5  Changed: 5  Warnings: 0
```

```
mysql> select * from parent;
```

| id | name | city | age | income | occupation | email |
|----|-----------|----------|-----|--------|------------|-------|
| 11 | sanjay | mumbai | 40 | 600000 | advocate | NA |
| 12 | shiv | pune | 40 | 400000 | actor | NA |
| 13 | raghav | delhi | 40 | 400000 | worker | NA |
| 14 | siddharth | pune | 40 | 500000 | teacher | NA |
| 15 | akash | banglore | 40 | 600000 | professor | NA |

5 rows in set (0.00 sec)

```
mysql> select count(name) from parent where income > 500000;
```

| count(name) |
|-------------|
| 2 |

1 row in set (0.02 sec)

```
mysql> select * from parent where city="pune" or city="delhi" or city="mumbai";
```

| id | name | city | age | income | occupation | email |
|----|------|------|-----|--------|------------|-------|
|----|------|------|-----|--------|------------|-------|

MySQL 8.0 Command Line Client

```
mysql> select count(name) from parent where income>500000;
```

| count(name) |
|-------------|
| 2 |

1 row in set (0.02 sec)

```
mysql> select * from parent where city="pune" or city="delhi" or city="mumbai";
```

| id | name | city | age | income | occupation | email |
|----|-----------|--------|-----|--------|------------|-------|
| 11 | sanjay | mumbai | 40 | 600000 | advocate | NA |
| 12 | shiv | pune | 40 | 400000 | actor | NA |
| 13 | raghav | delhi | 40 | 400000 | worker | NA |
| 14 | siddharth | pune | 40 | 500000 | teacher | NA |

4 rows in set (0.01 sec)

```
mysql> select * from parent where income<500000 and age>50;  
Empty set (0.00 sec)
```

```
mysql> select * from parent where income<500000 and age>35;
```

| id | name | city | age | income | occupation | email |
|----|--------|-------|-----|--------|------------|-------|
| 12 | shiv | pune | 40 | 400000 | actor | NA |
| 13 | raghav | delhi | 40 | 400000 | worker | NA |

2 rows in set (0.00 sec)

```
mysql> ^C
```

```
mysql> _
```