DATE 29/07/26 (31)

Practical-8

* Aim

□ Using CSS

a. Create a class called income, and make it a background color of #0ff.

b. Create a class called expense, and make it a background color of #f0f.

c. Create a class called profit, and make it a background color of #f00.

d. Throughout the document, any text that mention income, expense, or profit, attach the appropriate class to that price of text.

e. Further create following line of text in the same document: The current price is 50₹ and new price is 40₹

* Theory

- Using CSS with internal CSS, is a method of applying CSS styles with in an HTML document using the <style> tag inside the <head> section.
- In CSS, a class is a reusable attribute used to select and apply specific styling rules to one or multiple HTML elements at the same time.
- CSS classes are created for income, expenses and profit where income is given cyan (#0ff) background, .expenses is given a magenta (#f0f) background and .profit is given red (#f00) background.
- The appropriate class is applied to text using the class attribute.
- Internal CSS helps to style a single webpage without using a seperate CSS file.

DATE 04 08 26 (35)

Practical - 9

* Aim

a. Using CSS

a. Change the tag li to have the following properties:
i. A display status of inline
ii. A medium, doubled-lined, black border
iii. No list style type.
b. Add the following properties to the style for li:
i. Margin of 5px
ii. Padding of 10px to the top, 20px to the right, 10px to the bottom, and 20 px to the left.

* Theory

CSS is used to style and control the appearance of HTML elements.
In this practical, the <li> (list item) element is styled using CSS
display: inline displays list items in a single line
A medium, double-lined black border is applied.
list-style-type: none removes the default bullet points.
A 5px margin is provided around each list items.
Padding is set to 10px top, 20px right, 10px bottom and 20px left.
CSS properties help control the layout, spacing, border and appearance of list elements on a webpage.

DATE 2/9/26 (75)

Practical - 13

* Aim
  - Design a web page demonstrating different core JavaScript references (Array, Boolean, Date, Function, Math, Number, Object, String, regExp.).

* Theory
  - JavaScript provides build-in objects and references that help perform common programming tasks.
  - Array stores multiple values, Boolean represents true or false, and Date is used to work with dates and time.
  - Function contains reusable block of code.
  - Math provides mathematical operations, while Number handles numeric values.
  - Object stores data as properties and methods. String is used for text manipulation and RegExp is used for pattern matching and text validation.
  - Core JavaScript references makes web pages interactive and help perform different data, mathematical and text-processing operations

* Code

```
<!DOCTYPE html>
<html>
<head>
    <title> Practical 13 - Core JavaScript References </t
    <style>
        body {
            font-family: Arial, sans-serif;
            background-color: #f2f2f2;
```

Practical - 14(a)

9 9 26 (81)

* Aim
Write JavaScript code for
a. Finding Pallindrome numbers

* Theory
- A pallindrome number is a number that remains the same when its digits are reversed.
- In JavaScript, the number can be converted into a string or processed using arithmetic operations.
- The original number is compared with its reversed form.
- If both are equal, the number is a pallindrome.

* Code

```
<!DOCTYPE html>
<html>
<head>
    <title>Practical 14(a) - Pallindrome Number </title>
    <style>
        body {
            font-family: Arial, Sans-serif;
            background-color: #f2f2f2;
            padding: 20px;
        }
        section {
            max-width: 600px;
            margin: auto;
            background-color: white;
            padding: 25px;
            border: 2px solid #333;
```

Practical - 14(b)

* Aim
b. Calculating reverse of a number

* Theory
Reversing a number means arranging its digits in the opposite order.
In JavaScript, this can be done by repeatedly taking the last digit using the modulo (%) operator, adding it to the reversed number, and removing the last digit using division.
The process continues until the original number becomes zero.

* Code

```
<!DOCTYPE html>
<html>
<head>
  <title>Practical 14(b) - Reverse of Number </title>
  <style>
    body {
      font-family: Arial, sans-serif;
      background-color : #f2f2f2;
      padding: 20px;
    }
  section {
    max-width: 600px;
    margin: auto;
    background-color: white;
    padding : 25px;
    border: 2 px solid #333;
```

Practical - 14(c)

23/9/26 (87)

* Aim
Write JavaScript code for
c. Displaying the following pattern

```
*
* *
* * *
```

* Theory
JavaScript nested loops are used to display the required star pattern.
The outer loop controls the number of rows, while the inner loop controls the number of stars printed in each row.
Spaces or suitable formatting can be added to obtain the required triguler arrangement

* Code

```
<!DOCTYPE html>
<html>
<head>
    <title> Practical 14(c) - Star Pattern </title>
    <style>
        body {
            font-family : Arial, sans-serif;
            background-color : #f2f2f2;
            padding : 20px
        }
        section {
            max-width : 600px;
```

Practical - 14 (d)

* Aim
Write JavaScript code for
d. Display the following pattern

```
*
* *
* * *
* * * *
```

* Theory
The pattern is generated using nested loops in JavaScript.
The outer loop represents each row and the inner loop prints the required number of stars in that row.
By changing the inner-loop condition for every row, the increasing star pattern shown in the practical can be produced.

* Code

```
<!DOCTYPE html>
<html>
<head>
  <title> Practical 14(d) - Star Pattern </title>
  <style>
    body {
      font-family: Arial, Sans-serif;
      background-color: #f2f2f2;
      padding: 20px;
    }
```

DATE 29 09 26 93

Practical - 15

* Aim:
- Write JavaScript code for Validating the various Form Elements

* Theory:
- Form validation is the process of checking whether the data entered by the user is correct & complete before submitting a form.
- JavaScript is used to validate various form elements such as name, email, password, phone number, gender & course.
- The if-else statement checks the entered values.
- The trim() method removes extra spaces from the beginning & end of the input.
- Email, password, phone number and selection fields are validated as per the give condition
- If the entered data is incorrect, JavaScript displays an appropriate error message.
- If all the entered data is valid, a success message is displayed.
- Thus, Javascript validates various form elements & prevents incomplete or incorrect data from being submitted.