Page No.
Date 23 6 26

Practical No :- 1

Aim : Design a webpage that makes use of
a. Document Structure Tags
b. Various Text Formatting Tags
c. List Tags
d. Image and Image maps

- Theory :

* Document Structure tags are HTML codes in angle brackets that build the foundational skeleton of a web page. They tell the web browser how to organize the document type, metadata, and visible content.

Core HTML Skeleton Tags


- <!DOCTYPE html> : Tells the browser this is an HTML 5 document. It is a declaration, not a true HTML tag.
- <html> : Acts as the root container holding every other elements on the page.
- <head> : Hold hidden metadata, links to style sheets and script.
- <title> : Sets the text shown on the browser tab.
- Text formating Tags like <b>, <i>, <p> & are used to format text.
- List tags such as <ul>, <ol> & display ordered and unordered lists.
- The <img> tag is used to insert images into a webpage. Image map allows different areas of an image to work as clickable links.

Code :-

```
<html>
<head>
<title> Practical No.1 </title>
<body>
  <h1> This is my first code </h1>
  <h2> Welcome to the webpage </h2>
  <P> I'm in FYCS </P>
  <P> SIES </P>
  <b> This is bold tag </b>
  <strong> This is strong tag </strong>
  <i> This is italic tag </i>
  <em> This is emphasis tag </em>
  <small> This is small tag </small>
  <P> Don't forget to buy <mark> milk </mark>
      today </P>
<P> My favourite color is <del> red </del> <ins>
  blue </ins></P>
<u> This tag is underline tag </u>
  <ol>
  <li> Tea </li>
  <li> Coffee </li>
  <li> coke </li>
</ol>
<ul>
  <li> Tea </li>
  <li> Coffee </li>
  <li> coke </li>
  <li> fruit juice </li>
</ul>
```

Page No.
Date

```
<img src = " abc.jpg  alt = "abc" width = "300"
  height = "300" >
<map name = " mapping " >
        <area shape = " rect " coords = " x1 y1 ,
        x2 y2 " alt = "abbc" href = " Link " >
</body>
</html>
```



Page No.
Date 29 6 26

Practical No - 2

Aim :- Design a webpage makes use of
a) Table tags
b) Form tags (forms with various form elements)
c) Navigation across multiple pages
d) Embedded multimedia elements.

Theory :-
(1) HTML table tags such as <table>, <tr>, <th> & <td> are used to organize data in rows and column. Form tags are used to collect information from users through input fields. common form elements include text, boxes, radio, button, checkbox, buttons & dropdowns list.
(2) Navigation links using the <a> tag help users move between multiple webpages.
(3) Multimedia elements such as audio and video can be embedded using <audio> & <video> tags.

Code :-

(a)

```
<HTML>
<head>
<title> Practical 2 </title>
</head>
<body>
<table>
 <tr>
   <th> Name </th>
   <th> Age </th>
 </tr>
 <tr>
   <td> Md A Anusha </td>
   <td> 20 </td>
 </tr>
 <tr>
   <td> Sneha </td>
   <td> 18 </td>
 </tr>
 <tr> Archita <
   <td> Archita </td>
   <td> 20 </td>
 </tr>
</table>
</body>
</html>
```

(b) Form tag
(c) Navigation across multiple pages

```
<html>
<head>
<title> Practical No. 2 (b & c) </title>
</head>
<body>
  <a href = "Table tag.html"> Table tag </a>
  <a href = "Form tag.html"> Form tag </a>
  <a href = "multimedia.html"> multimedia </a>
<Form>
  Name :
<input type = "text" Placeholder = "Enter your name">
<br>
```

Password :
<input type = "text">
Gender :
<input type = "Radio" name = "male">
<input type = "Radio" name = "female">
<input type = "Radio" name = "other">
City :
<select>
<option> Mumbai </option>
<option> Navi Mumbai </option>
<option> Pune </option>

<input type = "submit">
</form>
</body>
</html>

d) Embedded multimedia elements

```
<html>
<head>
<title> Practical No.2 (d) </title> </head>
<body> <video height = "640" width = "640">
    <source src = "xyz.mp4" type = "mp4">
</video>
<audio>
    <source src = "Adc.mp3" type = "mp3">
</audio>
</body>
</html>
```

14/7/26

Practical No. 3

Page No.
Date 14 7 26

Aim :- Create an Html page using tags to accomplish the following.

(a) A paragraph containing text "All the glitters is not gold". Bold face and italicize this text.
(b) Create equation :- $x = 1/3 (y1^2 + z1^2)$
(c) Put a background image to a page and demonstrate all attributes of background image.
(d) Create unordered list of 5 fruits and ordered list of 3 flowers.

Theory :-

(i) Html tag can be used to format text using elements such as <b> for bold and <i> for italic text. To display mathematical equation be can use Html tag such as <sub> & <sup> for powers & subscripts.
(ii) Background image can be added to a webpage using css background properties & can be control position, size, repetition and attachment.
(iii) An unordered list <ul> display items using bullets while an orderedlist <ol> displays number items.

code :-

```
<html>
<head>
<title> Practical No. 3 </title>
</head>
```

```
<body style = " background_image : url ('flower.jpg');
  background -repeat : no-repeat ; >
<p> <em> <strong>
    All the glitters is not gold
  </strong> </em> </p>

<p> x = 1/3 (Y1 <sup> 2 </sup> + Z1 <sup> 2
                </sup> ) </p>
<ul>
<li> mango </li>
<li> Apple </li>
<li> Pineapple </li>
<li> Orange </li>
<li> Kiwi </li>
</ul>
<ol>
<li> Rose </li>
<li> lotus </li>
<li> Sunflower </li>
</ol>
</body>
</html>
```

14/7/26

Page No.
Date 15 7 26

Practical No :- 4

Aim :- Create the following table using HTML tags. Properly align cells, give suitable cell padding and cellspacing and apply background color, bold and emphasis necessary.

Department	Sem 1	Subject A Subject B Subject C
	Sem 2	Subject D Subject E Subject F Subject G
	Sem 3	Subject H Subject I Subject J

Theory :-

i) HTML tables are used to represent information systematically in rows & columns. The <table>, <tr>, <th> & <td> tags are commonly used to create tables.

ii) Rowspan and colspan can be used to merge cells across rows or columns. Cell alignment, padding & spacing help improve the appearance and readability of a table.

Code :-

```
<!DOCTYPE html>
<html>
<head>
<title> Practical 4 </title>
 <style>
    table, td {
            border : 1px solid black;
            border-collapse : collapse ;
     }
  </style>
 </head>
<body>
   <table width = "50%" >
     <tr>
       <td rowspan = "9" align = "centre"
           bgcolor = "yellow" width = "30%" >
 <b> Department </b>
 </td>
<td rowspan = "3" align = "centre" bgcolor = "blue"
          width = "30%" >
<b> Sem 1 </b>
</td>
<td> <b> <i> Subject A </i> </b> </td>
</tr>
<tr>
<td> <b> <i> Subject B </i> </b> </td>
</tr>
<tr>
<td> <b> <i> Subject C </i> </b> </td>
</tr>
<tr>
<td rowspan = "3" align = "centre" bgcolor = "blue"
          width = "30%" >
<b> Sem 2 </b>
</td>
<td> <b> <i> Subject E </i> </b> </td>
</tr>
<tr>
 <td> <b> <i> Subject F </i> </b> </td>
</tr>
<tr>
 <td rowspan = "3" align = "center" bgcolor = "blue"
          width = "30%" >
 <b> Sem 3 </b>
</td>
 <td> <b> <i> Subject H </i> </b> </td>
</tr> <tr>
<td> <b> <i> Subject I </i> </b> </td>
</tr>
<tr>
<td> <b> <i> Subject J </i> </b> </td>
 </tr>
 </table>
 </body>.
 </html> .
```

15/7/26

Practical No 5

Aim: Use HTML 5 for performing following tasks

a. Draw a square using Html 5 SVG. fill the square with green color & make 6px brown stroke width

b. Write the following mathematical expression by using HTML 5 MathML:

$$d = x^2 - y^2$$

c. Redirecting current page to another page after 5 seconds using HTML 5 meta tag.

Theory :-

(i) HTML 5 provides SVG (Scalable vector Graphics) for creating shapes and graphics directly on a webpage.
SVG allows properties such as fill colour, stroke colour and stroke width to be specified for shapes.

(ii) MathML is used to represent mathematical equations and expressions in HTML documents.

(iii) The Html 5 <meta> tag can be used to auto-matically redirect a webpage after a specified time.

(iv) HTML <meta> tag placed in the <head> section, along with alternative paragraph <p> & anchor <a> links.

code :-

```
<html>
<head>
<meta http-eq
<title> Practical 5. a </title>
</head>
<body>
 <svg height = "400" width = "400" viewbox = "0 0 200 200" xmlns = "http://www.w3.org/2000/svg">
 <rect
    x = "10"
    y = "10"
    height = "180"
    width = "180"
    fill = "green"
    stroke = "brown"
    stroke-width = "6"
 />
 </svg>
 </body>
<math xmlns = "http://www.w3.org/1998/Math/MathML">
<mi> d </mi>
<mo> = </mo>
<msup>
<mi> x </mi>
<mn> 2 </mn>
</msup>
<mo> - </mo>
<msup>
 <mi> y </mi>
 <mn> 2 </mn>
</msup> </math>
```

```
<title> Practicle 5_b </title>
 <meta charset = "UTF-8">
<meta name = "viewport" content = " width = device-width,
  initial-scaled = 1.0 ">
<meta http-equiv = "refresh " content* = " 5 ; url =
      Practical 5_a.html " >
</head>
</body>
  <p> Redirecting, for 5 second
  <a href = "Practical 5_a.html "> Click here </a>
   if not redirected </p>
</body>
</html>
```

Page No.
Date 22 | 7 | 26

Practical No. 6

Aim :- Demonstrate the following HTML sematic tags <article> <aside> <details> <figcaption> <figure> <footer> <header> <main> <mark> <section> for a web page that gives information about travel experience.

Theory :-

(i) HTML semantic tags clearly describe the purpose and structure of different parts of a web page content.
Tags such as <header> <main> <section> <article> & <footer> organise webpage content. <aside> is used for related or supplementary information.

(ii) <figure> & <figcaption> are used to display images or other content with caption.

Code :-

```
<html>
<head>
  <title> MY TRAVEL EXPERIENCE </title>
</head>
<body>
  <header>
    <h1> My Travel Experience </h1>
    <p> Exploring beautiful destinations & creating
      unforgettable memories. </p>
```

```
<nav>
  <a href="#about">About</a>
  <a href="#places">Places</a>
  <a href="#gallery">Gallery</a>
  <a href="#contact">Contact</a>
</nav>
<hr>
</header>
<main>
  <section id="about">
  <h2>About My Journey</h2>
    <article>
      <h3>First Solo Trip</h3>
      <p>
Travelling has always been my passion. My first solo trip was to the mountains where I explored nature, local culture, and beautiful landscapes. It taught me confidence and independence.
      </p>
<p>
The most <mark>memorable experience</mark> was watching sunrise from the highest viewpoint.
</p>
<details>
  <summary>Travel Tip</summary>
<p>
Always carry a water bottle, keep important documents safe, and plan your journey before travelling.
</p>
</details></article>
  </section>
```

```
<hr>
<section id="places">
  <h2>Favorite Places Visited</h2>
  <article>
    <h3>Manali</h3>
  <figure>
    <img src="" alt="Manali Mountains">
    <figcaption>
        Snow-covered mountains of Manali.
    </figcaption>
  </figure>
<p>
  Manali is famous for its cool climate, adventure sports, and breathtaking mountain views.
  </p>
</article>
<article>
  <h3>Goa</h3>
<figure>
  <img src="" alt="Goa Beach">
  <figcaption>
        Peaceful sunset at Goa Beach.
  </figcaption>
  </figure>
  <p>
    Goa offers beautiful beaches, seafood, water sports, and a vibrant nightlife.
</p>
</article>
</section>
```

```
<p> Always carry a water bottle, keep
important documents safe and plan your trip
before travelling.
  </p>
 </details>
</article>
</section>
<section id = "places" >
<h2> Favorite Places </h2>
<article>
<h3> Manali </h3>
<figure>
 <img src = "image/manali.jpg" alt = "Manali">
<figcaption> Snow covered mountain of Manali.
</figcaption>
</figure>
<p>
Manali is famous for snowfall, mountain,
adventure sports and scenic beauty.
</p>
</article>
<article>
<h3> Goa </h3>
<figure>
<img src = "image/goa.jpg" alt = "Goa">
<figcaption> Beautiful beaches of Goa.
  </figcaption>
</figure>
<p>
 Goa is famous for beaches, seafood,
churches and water sports. </p>
```

```
</article>
</section>
<section id = "gallery" >
<h2> Travel Gallery </h2>
<figure>
 <img src = "image/travel.jpg" alt = "Travel" >
<figcaption> Memories collected from different
 places. </figcaption>
  </figure>
 </section>
</main>
<footer id = "contact">
 <h3> Contact Me </h3>
 <p> Name : Your name </p>
 <p> Email . yourname@email.com </p>
 <p> Phone : +91 00000 00000 </p>
 <p> &copy; 2025 My Travel Experience </p>
</footer>
</body>
</html>
```

+ Style.css

```
img {
    width: 500px;
    height : 300 px;
    object-fit : cover;
    border-radius : 10 px;
    border : 4 px solid #1565C0;
    display : block;
    margin : auto;
}
```

```
<hr>
<section id="gallery">
<h2> Travel Highlights </h2>
<figure>
<img src="" alt="Travel Memories">
<figcaption>
A collection of unforgettable travel moments.
</figcaption>
</figure>
</section>
<aside>
<h3> Quick facts </h3>
<ul>
<li> Countries Visited : 3 </li>
<li> Cities Explored : 12 </li>
<li> Favourite Destination : Manali </li>
<li> Best Season to Travel : Winter </li>
</ul>
</aside>
</main>
<hr>
<footer id="contact">
<h3> Contact </h3>
<p> Name : Your Name </p>
<p> Email : yourname@email.com </p>
<p> Phone : +91 00000 00000 </p>
<p> &copy ; 2025 My Travel Experience . All
Rights Reserved . </p>
</footer>
</body>
</html>
```

22/7/26

Practical - 7

Aim : Design a webpage that makes use of Cascading Style sheets with
(a) CSS properties to change the background of a page.
(b) CSS properties to change fonts & Text styles.
(c) CSS properties for positioning an element.

Theory :-

(i) CSS (caseading style sheet) is used to control the presentation and appearance of HTML webpage. it can change background of a webpage using color or images.
(ii) Font properties such as font-family, font-size, font-style and font-weight control text appearance.
(iii) Text properties such as color, text-align and text-decoration modify the presentation of text.

Code :-

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<title> My Travel Experience </title>
<link rel="stylesheet" href="style.css">
<style>
{
margin : 0 ;
padding : 0 ;
box-sizing : border-box ;
}
```

```
details {
    margin-top : 15px ;
}
aside {
    float : right ;
    width : 250 px ;
    background : #dbeafe ;
    border : 2 px solid #1565c0 ;
    border-radius : 10px ;
    padding : 15 px ;
    margin : 00 20px 20px ;
}
.hero-content {
    width : 80 % ;
}
</style>
</head>
<body>
 <header>
  <nav>
   <a href ="#about" >About </a>
   <a href ="#places" > Places </a>
   <a href = "#gallery" > Gallery </a>
   <a href = "#contact" > Contact </a>
  </nav>
 <div class = " hero-content ">
  <h1 style =" font-size : 60 px ; letter-spacing
   3px ;" > My Travel Experience </h1>
<p style ="font -size :22px ; font-style : italic ;
 margin-top : 15 px ;" >
```

Exploring beautiful destination and creating unforgettable memories.

```
  </p>
 </div>
</header>
<main>
 <section id = " about " >
  <aside >
   <h3> Quick facts </h3>
  <ul>
  <li> Countries Visited : 3 </li>
  <li> Cities Explored : 12 </li>
  <li> Favourite Places : Manali </li>
  <li> Best Season : Winter </li>
  </ul>
 </aside >
 <h2> About My Journey </h2>
  <article>
  <h3 > First Solo Trip </h3>
   <p>
```

Travelling has always been my passion My first solo trip was to the mountains where I explored nature, local culture and beautiful landscapes.

```
   </p>
   <p>
```

The most <mark > memorable experience </mark> was watching the sunrise from the highest viewpoint.

```
   </p>
   <details>
   <summary > Travel Tip </ summary>
```

```
body {
    font-family : Arial , Helvetica , sans-serif ;
    background : #eef5ff ;
    line-height : 1.6 ;
  }
header {
   height : 100vh ;
  background : linear-gradient (rgba (0,0,0,.5),
  rgba (0,0,0,.5))), url(" images/banner.jpg ");
  background size : cover ;
  background-position : center ;
  colour : white ;
  display : flex ;
  flex-direction : column ;
  justify-content : center ;
  align-items : center ;
  text-align : center ;
}
nav {
   position : fixed ;
   top : 0 ;
   left : 0 ;
   width : 100% ;
   background : rgba (0, 0, 0, .6) ;
   padding : 15px ;
   text-align : center ;
}
nav a {
   colour : white ;
  text-decoration : none ;
```

```
margin : 0 18px ;
font-weight : bold ;
}
nav a : hover {
    color : yellow ;
}
section {
    background : white ;
    margin : 30 px ;
    padding : 25 px ;
    border-radius : 10 px ;
}
article {
    margin-bottom : 25 px ;
}
h2 {
    color : # 1565C0 ;
    margin-bottom : 15 px ;
}
h3 {
    color : # 0d4791 ;
    margin-bottom : 10 px ;
}
p {
  text-align : justify ;
  margin-bottom : 10 px ;
}
mark {
   background : yellow ;
}
```

```
figure {
    text-align : center ;
    margin : 20px 0 ;
}
figcaption {
    margin-top : 10 px ;
    font-style : italic ;
    color : #555 ;
}
ul {
    margin-bottom : 10px ;
}
section-hover {
    box-shadow : 0 5px 15px rgba (0, 0, 0, .2) ;
    transition : .3s ;
}
footer {
    background : #0d47a1 ;
    color : white ;
    text-align : center ;
    padding : 30 px ;
    margin-top : 30px ;
}
footer p {
    text-align : center ;
}
html {
    Scroll-behaviour : Smooth ;
}
```

28/7/26

Page No.
Date 29 7 26

Practical - 8

Aim Using CSS

(a) Create a class called income, and make it a background color of #0ff.

(b) Create a class called experse, and make it a background color of #faf.

(c) Create a class called profit, and make it a background of color of #f00.

(d) Throughout the document, any text that mention income, experses, or profit, attach the appropriate class to that piece of text.

Further create following line of text in the same document: The curruent price is 50 & new price is 40.

Theory :-

Internal CSS (also called embedded CSS) is a method used to style a single HTML document by placing all CSS rules directly inside a <style> tag within the <head> section of the page.

In Cascading Style Sheets (CSS), a class is a reusable attribute used to select and apply specific styling rules to one or multiple HTML elements at the same time.

- tag : The tag stands for "division" and acts as an invisible box or container used to group other elements together.
- A span tag is an empty container used to target & style a specific part of a text without breaking the layout or starting a new line.

```
</head>
<body>
  <div class = "container">
    <h1> Business Report </h1>
  <p>
  Every business aims to increase its
  <span class = "income"> Income </span>
  while reducing
  <span class = "expenses"> Expenses </span>
  When the income is greater than the expenses,
  the company earns a
  <span class = "profit"> Profit </span>
  </p>
  <p> class = "p
  Proper financial planning helps in increasing
  <span class = "income"> Income </span>
  controlling
  <span class = "expenses"> Expenses </span>,
  and maximizing
  <span class = "profit"> Profit </span>
  </p>
  <p class = "price">
  The current price is
  <span class = "oldprice"> 50₹ </span>
  and new price is
  <span class = "newprice"> 40₹ </span>
  </p>
  </div>
  </body>
  </html>
```

Practical - 9

Aim : Using CSS

(a) Change the tag li to have the following properties:
- A display status of inline.
- A medium, double-lined, black border
- No list style type.

(b) Add the following properties to the style for li :-
- Margin of 5px
- Padding of 10 px to the top, 20 px to the right, 10 px to the bottom, and 20 px to the left.

Theory :-

- CSS can be used to control the appearence and layout of list element such as <li>.
- The display property determine how an element is displayed, such as inline.
- The border property control the border style, width and colour of an element.
- The list-style-type property can be remove or change the default list marks.

Code :-

```
<!DOCTYPE HTML>
<html>
<head>
  <title> CSS Classes Example </title>
<style>
    body {
        font-family : Arial , Helvetica , sans-serif ;
        background-color : #f4f4f4 ;
        margin : 40 px ;
        line-height : 1.8 ;
    }
h1 {
    color : # 003366 ;
    text-align : center ;
}
. container {
    background : white ;
    padding & 25 px ;
    border-radius : 10 px ;
    box-shadow : 0 px 0 px 10 px lightgray ;
}
. income {
    background : #0ff ;
    padding : 3 px 8 px ;
    border-radius : 5 px ;
    font-weight : bold ;
}
. expenses {
    background : #f0f ;
    padding : 3 px 8 px ;
    border-radius : 5 px ;
    color : white ;
    font-weight : bold ;
}
. profit {
    background : #f00 ;
    color : white ;
    padding : 3 px 8 px ;
    border-radius : 5 px ;
    font-weight : bold ;
}
. price {
    font-size : 22 px ;
    margin-top : 25 px ;
}
. oldprice {
    color : red ;
    text-decoration : line-through ;
    font-weight : bold ;
}
. newprice {
    color : green ;
    font-size : 28 px ;
    font-weight : bold ;
}
</style>
```

Code :-

```
<!DOCTYPE html>
<html>
<head>
 <title> CSS List Styling </title>
  <style>
    body {
        font-family : Arial;
        background : #f2f2f2;
        margin : 40px;
      }
   . container {
        width : 500px;
        margin : auto;
        background : white;
        padding : 25px;
        border-radius : 10px;
      box-shadows : 0px 0px 10px gray;
    }
h1 {
   text-align : center;
   color : #003366;
  }
ul {
   padding : 0;
  }
li {
   display : inline;
   border : 2px double black;
   list-style-type : none;
   margin : 5px;
   padding : 10px 20px 10px 20px;
   background : #d9f3ff;
   border-radius : 6px;
   font-weight : bold;
   color : #003366;
  }
  .note {
     margin-top : 30 px;
     color : #444;
   }
  </style>
  </head>
  <body>
   <div class = "container">
     <h1> Programming Languages </h1>
      <ul>
       <li> HTML </li>
       <li> CSS </li>
       <li> Javascript </li>
  </ul>
  <p class = "note">
       The list items are displayed inline with
  a  medium double-lined black border,
     no bullet points, custom margin, & padding.
     </p>
     </div>
     </body>
     </html>
```

4 | 8 | 25