Clutta

SHORT WALKTHROUGH / HANDS-ON LAB

Everything is green.
The notification never arrived.

A payment finishes, but its notification scheduler stops doing useful work. The container stays healthy. Clutta watches whether the journey finishes, not just whether the service is alive.

THE JOURNEY YOU WILL WATCH



Same payment ID across all three steps. You approve the expected flow and deadline.

Quick experience: a guided session in a warm lab with the flow already reviewed and activated. Begin at step 2.
Full playground: follow the setup guide and begin at step 1.

THREE MOMENTS. ONE REAL WORKFLOW.

1 Learn what finished looks like

`./lab start`

Generate 600 distinct fake payments through real Node.js services and PostgreSQL. Review the proposed flow and cited runs in Clutta, then approve and activate it yourself.

2 Stop delivery. Keep health green.

`./lab break`

The lab verifies 20 fresh healthy payments before pausing the scheduler loop. A new payment misses its delivery deadline. Open the Case File linked in your terminal.

3 Repair and verify new work

`./lab repair`

The saved notification queue drains. Open a fresh completed run in Clutta and compare all three steps. The earlier missed deadline remains in history.

What to look for in the Case File

Cited accepted and queued records for the same payment; the expected delivery step and missed deadline. A completion violation is established. An unknown root cause is not invented.

TRY IT IN YOUR OWN ACCOUNT

Sign up for Clutta, then follow the guide using a dedicated playground project/environment and a separate workspace key. Never use a production key. The key is workspace-scoped, not project-scoped; use a separate workspace for credential isolation.

Start the step-by-step guide →
github.com/sefastech/clutta-playground

Open in Codespaces →

Local Linux: use Node.js 24 and Docker Compose v2. Before `./lab start`, follow the local setup and install dependencies with `npm ci --ignore-scripts` and `npm --prefix scenarios/scheduler ci --ignore-scripts`.

Repeat the fault, fork the lab, or explore another incident with sanitized evidence in Analyze. Analyze is one-time interpretation, not live monitoring or Case File creation. Finish with `./lab stop`.

Real application activity; synthetic payments. No SDK, Slack, Kubernetes, or production access. Early validation: fresh-account and resume checks remain open. First-time setup and learning take longer than this short read; Codespaces usage depends on your GitHub account.