

## 1.1: Basic Programming Model

**Exercise 1.** Give the value of each of the following expressions:

- (a) `( 0 + 15) / 2`
- (b) `2.0e-6 * 100000000.1`
- (c) `true && false || true && true`

**Solution.**

- (a) 7 because integer division uses truncation.
- (b) 2.000000002E-6
- (c) `true`

**Exercise 2.** Give the type and value of each of the following expressions:

- (a) `(1 + 2.236) / 2`
- (b) `1 + 2 + 3 + 4.0`
- (c) `4.1 >= 4`
- (d) `1 + 2 + "3"`

**Solution.**

- (a) `double` with value 1.6.18
- (b) `double` with value 10.0
- (c) `boolean` with value `true`
- (d) `String` with value "33"

**Exercise 4.** What (if anything) is wrong with each of the following statements?

- (a) `if (a > b) then c = 0;`
- (b) `if a > b { c = 0; }`
- (c) `if (a > b) c = 0;`
- (d) `if (a > b) c = 0 else b = 0;`

**Solution.**

- (a) `then` is not a valid Java keyword. If we remove it, the code snippet will be valid.
- (b) We need parentheses around the boolean condition of the `if` statement, in this case, around `a > b`. If we add this, the snippet will be valid.
- (c) The snippet is valid.
- (d) We need a semicolon to terminate the assignment statement `c = 0`. If we add this, the snippet will be valid.

**Exercise 5.** Write a code snippet that prints `true` if the `double` variables `x` and `y` are both strictly between 0 and 1 and `false` otherwise.

**Solution.**

---

```
System.out.println(x > 0 && x < 1 && y > 0 && y < 1);
```

---

**Exercise 6.** What does the following program print?

---

```
int f = 0;
int g = 1;
for (int i = 0; i <= 15; i++)
{
    StdOut.println(f);
    f = f + g;
    g = f - g;
}
```

---

**Solution.** Note we are given:

$$\begin{aligned}f_0 &= 0, \\g_0 &= 1, \\f_n &= f_{n-1} + g_{n-1}, \quad n \geq 1, \\g_n &= f_n - g_{n-1}, \quad n \geq 1.\end{aligned}$$

Notice the recurrence of  $g_n$  follows because the value just computed in the current iteration of the `for` loop is used to compute the new value for `g`. Note that  $f_0 = 0$ ,  $f_1 = f_0 + g_0 = 0 + 1 = 1$ , and

$$\begin{aligned}f_{n+1} &= f_n + g_n \\&= (f_{n-1} + g_{n-1}) + g_n \\&= f_{n-1} + (g_{n-1} + g_n) \\&= f_{n-1} + f_n\end{aligned}$$

Altogether, we have:

$$\begin{aligned}f_0 &= 0, \\f_1 &= 1, \\f_{n+1} &= f_{n-1} + f_n, \quad n \geq 1.\end{aligned}$$

Hence  $n \mapsto f_n$  is the Fibonacci sequence. The program will print the first 15 Fibonacci numbers:

---

1  
1  
2  
3  
5  
8  
13  
21  
34  
55  
89  
144  
233  
377  
610

---

**Exercise 7.** Give the value printed by each of the following code fragments.

(a) 

---

```
double t = 9.0;
while (Math.abs(t - 9.0/t) > 0.001)
    t = (9.0/t + t) / 2.0;
StdOut.printf("%.5f\n", t);
```

---

```
int sum = 0;
for (int i = 1; i < 1000; i++)
    for (int j = 0; j < i; j++)
        sum++;
StdOut.println(sum);
```

---

(b) 

---

```
int sum = 0;
for (int i = 1; i < 1000; i *= 2)
    for (int j = 0; j < 1000; j++)
        sum++;
StdOut.println(sum);
```

---

**Solution.**

(a) The iterations are computed as:

$$\begin{aligned}
t_0 &= 9.0 \quad ; \quad t_0 - \frac{9.0}{t_0} = 1 \quad ; \quad \rightarrow \quad t_1 = \frac{9.0/t_0 + t_0}{2.0} = 5.0 \\
t_1 &= 5.0 \quad ; \quad t_1 - \frac{9.0}{t_1} = 3.2 \quad ; \quad \rightarrow \quad t_2 = \frac{9.0/t_1 + t_1}{2.0} = 3.4 \\
t_2 &= 3.4 \quad ; \quad t_2 - \frac{9.0}{t_2} \approx 0.75294 \quad ; \quad \rightarrow \quad t_3 = \frac{9.0/t_2 + t_2}{2.0} = 3.023529411764706 \\
t_3 &\approx 3.02352 \quad ; \quad t_3 - \frac{9.0}{t_3} \approx 0.04687 \quad ; \quad \rightarrow \quad t_4 \approx \frac{9.0/t_3 + t_3}{2.0} = 3.00009155413138 \\
t_4 &= 3.00009155413138 \quad ; \quad t_4 - \frac{9.0}{t_4} = 0.00018310546879263256
\end{aligned}$$

The iteration ends once  $t_4$  has been computed because it's below the threshold of 0.004 that controls the **while** loop. Since the format specifier requires 5 places after the decimal, the output will be:

---

3.00009

---

(b) The outer **i** loop runs 999 times. The inner **j** loop runs **i** times, and each time, it increment **sum** by 1. The value of **sum** is given by:

$$\sum_{i=1}^{999} \sum_{j=0}^{i-1} 1 = \sum_{i=1}^{999} i = \frac{999 \cdot (999 + 1)}{2} = 499500$$

Therefore the out will be:

---

499500

---

(c) In this case, we start with 1 and double **i** each time. When **i** reaches  $2^{10} = 1024$ , the **i** loops will end. Hence, the loop will run for  $i = 2^0, i = 2^1, \dots, i = 2^9$ . Since the **j** loops increases **sum** a total of **i** times, we find that **sum** will now be:

$$\begin{aligned}
\sum_k \sum_{i=1}^{1000} [i = 2^k] \sum_{j=0}^{i-1} 1 &= \sum_k \sum_{1 \leq i \leq 1000} [i = 2^k] \cdot i \\
&= \sum_{1 \leq 2^k \leq 1000} 2^k \\
&= \sum_{0 \leq k \leq 9} 2^k \\
&= 2^{10} - 1 \\
&= 1023
\end{aligned}$$

Therefore the output will be:

---

1023

---

**Exercise 8.** What do each of the following print?

- (a) `System.out.println('b');`
- (b) `System.out.println('b' + 'c');`
- (c) `System.out.println((char) ('a' + 4));`

**Solution.**

- (a) Java will display the `char` as the corresponding symbol:

---

`b`

---

- (b) When Java adds two `char` values, it will promote the result to an `int`. In Java, `char` values are 16-bit Unicode characters. Since `'b'` has decimal value 98 in Unicode, and `'c'` has decimal value 99, the result is:

---

`197`

---

- (c) The `char` value `'a'` has decimal value 97, so when it is added to 4, it becomes integer value 101. The effect of `(char)` is to cast the result back to a `char`. The integer 101 fits into a `char`, and it corresponds to `'e'`:

---

`e`

---

**Exercise 9.** Write a code fragment that puts the binary representation of a positive integer `n` into a `String s`.

**Solution.** If we divide `n` by 2, then the remainder of the division is the least significant bit in the binary representation of `n`. If we were to divide by the resulting quotient by 2, then the remainder of that division is the next most significant bit. Continuing this way, the value of `n` falls to 0 as we continue to divide by 2. The solution is actually given in [SW11]:

---

```
String s = "";
for (int k = n; n > 0; n /= 2)
    s = (k % 2) + s;
```

---

We could extend this to handle 0 by changing it to a `do { /*...*/ } while( /*...*/ );` loop.

**Exercise 10.** What is wrong with the following code fragment?

---

```
int[] a;
for (int i = 0; i < 10; i++)
    a[i] = i * i;
```

---

**Solution.** It fails to use `new` to allocate memory for the array before using it in the `for` loop.

**Exercise 11.** Write a code fragment that prints the contents of a two-dimensional boolean array, using `*` to represent `true` and a space to represent `false`. Include row and column numbers.

**Solution.**

---

```
for (int i = 0; i < m; i++) {  
    for(int j = 0; j < n; j++)  
        System.out.printf("(%d,%d): %s ", i, j, (a[i][j]) ? "*" : " ");  
  
    System.out.println();  
}
```

---

**Exercise 12.** What does the following code fragment print?

---

```
int[] a = new int[10];  
for (int i = 0; i < 10; i++)  
    a[i] = 9 - i;  
for (int i = 0; i < 10; i++)  
    a[i] = a[a[i]];  
for (int i = 0; i < 10; i++)  
    System.out.println(a[i]);
```

---

**Solution.** The first loop sets `a` to `{9, 8, 7, 6, 5, 4, 3, 2, 1, 0}`. The second loop `{0, 1, 2, 3, 4, 4, 3, 2, 1, 0}`. Thus the output is:

---

```
0  
1  
2  
3  
4  
4  
3  
2  
1  
0
```

---

**Exercise 13.** Write a code fragment to print the *transposition* (rows and columns changed) of a two-dimensional array with  $m$  rows and  $n$  columns.

**Solution.**

---

```
for (int i = 0; i < m; i++) {  
    for (int j = 0; j < n; j++)  
        System.out.printf("%d ", a[j][i]);  
    System.out.println();  
}
```

---

**Exercise 16.** Give the value of `exR1(6)`:

---

```
public static String exR1(int n)
{
    if (n <= 0) return "";
    return exR1(n-3) + n + exR1(n-2) + n;
}
```

---

**Solution.** The first call is as follows:

---

`exR1(6) -> exR1(3) + 6 + exR1(4) + 6`

---

Now we look at `exR1(3)`:

---

`exR1(3) -> exR1(0) + 3 + exR1(1) + 3`

---

By the base case, `exR1(0)` is `""`. Meanwhile, we keep going for `exR1(1)`:

---

`exR1(1) -> exR1(-2) + 1 + exR1(-1) + 1`

---

Since `exR1(-2)` and `exR1(-1)` evaluate to `""` due to the base case, we get `exR1(1)` is `"11"`. Now `exR1(3)` is `"3113"`. Next we need `exR1(4)`:

---

`exR1(4) -> exR1(1) + 4 + exR1(2) + 4`

---

We already know that `exR1(1)` is `"11"`. For `exR1(2)`:

---

`exR1(2) -> exR1(-1) + 2 + exR1(0) + 2`

---

Hence `exR1(2)` is `"22"`. Altogether, we find that `exR1(4)` is `"114224"`. Finally, the value of `exR1(6)` is:

---

`311361142246`

---

**Exercise 17.** Criticize the following recursive function:

---

```
public static String exR2(int n)
{
    String s = exR2(n-3) + n + n + exR2(n-2) + n;
    if (n <= 0) return "";
    return s;
}
```

---

**Solution.** Because the base case comes after the recursive step, a program that invokes this function will crash with `StackOverflowError`.

**Exercise 18.** Consider the following recursive function:

---

```
public static int mystery(int a, int b)
{
    if (b == 0) return 0;
    if (b % 2 == 0) return mystery(a+a, b/2);
    return mystery(a+a, b/2) + a;
}
```

---

}

What are the values of `mystery(2, 25)` and `mystery(3, 11)`? Given positive integers `a` and `b`, describe what `mystery(a, b)` computes. Answer the same question, but replace the three `+` operators with `*` and replace `return 0` with `return 1`.

**Solution.** Begin with `mystery(2, 25)`:

---

```
mystery(2, 25) -> 2 + mystery(4, 12):  
mystery(4, 12) -> mystery(8, 6):  
mystery(8, 6 ) -> mystery(16, 3):  
mystery(16, 3) -> 16 + mystery(32, 1):  
mystery(32, 1) -> 32 + mystery(64, 0):  
mystery(64, 0) -> 0
```

---

Tracing back the calls, the result is  $2 + 16 + 32 + 0 = 50 = 2 \cdot 25$ . Similarly:

---

```
mystery(3, 11) -> 3 + mystery(6, 5):  
mystery(6, 5 ) -> 6 + mystery(12, 2):  
mystery(12, 2) -> mystery(24, 1):  
mystery(24, 1) -> 24 + mystery(48, 0):  
mystery(48, 0) -> 0
```

---

Tracing back the calls, the result is  $3 + 6 + 24 + 0 = 33 = 3 \cdot 11$ . It appears that the `mystery(a, b)` computes the product  $a \cdot b$ . In essence, we are using the binary representation of `b` decide which weights of the multiples of `a` we should add.

Next, we replace `+` with `*` and `return 0` with `return 1`:

---

```
mystery(2, 25) -> 2 * mystery(4, 12):  
mystery(4, 12) -> mystery(16, 6):  
mystery(16, 6) -> mystery(256, 3):  
mystery(256, 3)-> 256 * mystery(65536, 1):  
mystery(65536, 1) -> 65536 * mystery(4294967296, 0):  
mystery(4294967296, 0) -> 1
```

---

The result is  $2 \cdot 256 \cdot 65536 \cdot 1 = 33554432 = 2^{25}$ . Meanwhile:

---

```
mystery(3, 11) -> 3 * mystery(9, 5):  
mystery(9, 5 ) -> 9 * mystery(81, 2):  
mystery(81, 2) -> mystery(6561, 1):  
mystery(6561, 1) -> 6561 * mystery(43046721, 0):  
mystery(43046721, 0) -> 1
```

---

The result is  $3 \cdot 9 \cdot 6561 \cdot 1 = 177147$ , which is  $3^{11}$ . In this case, `mystery(a, b)` appears to be computing  $a^b$  (meaning  $a$  to the power of  $b$ ).



## References

- [SW11] Robert Sedgewick and Kevin Wayne. *Algorithms*. 4th ed. Addison-Wesley, 2011.  
ISBN: 9780321573513.