

Reinforcement Learning

Niccolò Consigli `n.consigli@studenti.unipi.it`

Luca Seggiani `l.seggiani@studenti.unipi.it`

Università di Pisa

November 23, 2024

A new kind of learning

- ▶ Supervised learning: matching features to labels

A new kind of learning

- ▶ Supervised learning: matching features to labels
- ▶ Unsupervised learning: clustering data

A new kind of learning

- ▶ Supervised learning: matching features to labels
- ▶ Unsupervised learning: clustering data
- ▶ **Reinforcement learning**: learning from rewards

What is reinforcement learning (RL)?

- ▶ We give the agent **rewards** based on its performance

What is reinforcement learning (RL)?


- ▶ We give the agent **rewards** based on its performance
- ▶ Markov property: we can view problems as **Markov decision processes** (MDPs)

A framework: Markov decision processes

- ▶ Actions map states to states with a probability distribution
- ▶ Transition reward: $R(s, a, s')$
- ▶ Transition probability: $P(s' | s, a)$

3	-0.04	-0.04	-0.04	<div>+1</div>
2	-0.04		-0.04	<div>-1</div>
1	START	-0.04	-0.04	-0.04
	1	2	3	4

(a)




(b)

A framework: Markov decision processes

- ▶ Actions map states to states with a probability distribution
- ▶ Transition reward: $R(s, a, s')$
- ▶ Transition probability: $P(s' | s, a)$

3	-0.04	-0.04	-0.04	<div>+1</div>
2	-0.04		-0.04	<div>-1</div>
1	START	-0.04	-0.04	-0.04
	1	2	3	4

(a)



(b)

Bellman's equation

Given a discount factor $\gamma \in [0, 1]$, the utility is given by:

$$U(s) = \max_{a \in A(s)} \sum_{s'} P(s' | s, a) [R(s, a, s') + \gamma U(s')]$$

Model-based reinforcement learning

We maintain a transition model (an **MDP**):

- ▶ Reward function: $R(s, a, s')$
- ▶ Probability function: $P(s' | s, a)$
- ▶ Utility function: $U(s)$, maps states to **utility**

Model-based reinforcement learning

We maintain a transition model (an **MDP**):


- ▶ Reward function: $R(s, a, s')$
- ▶ Probability function: $P(s' | s, a)$
- ▶ Utility function: $U(s)$, maps states to **utility**

Once the model is learned, we can **maximize utility**

3	0.812	0.868	0.918	<div>+ 1</div>
2	0.762		0.660	<div>- 1</div>
1	0.705	0.655	0.611	0.388
	1	2	3	4

Model-free reinforcement learning

- ▶ Action-utility function: $Q(s, a)$ maps **actions** to **utility**
- ▶ Policy search: maps **states** to **actions**, essentially a reflex agent



Passive reinforcement learning

We can't modify the policy, but we can figure out the utilities $U(s)$

- ▶ We use **policy iteration**:

$$U^\pi(s) = E \left[\sum_{t=0}^{+\infty} \gamma^t R(s_t, \pi(s_t), s_{t+1}) \right]$$

Passive reinforcement learning

We can't modify the policy, but we can figure out the utilities $U(s)$

- ▶ We use **policy iteration**:

$$U^\pi(s) = E \left[\sum_{t=0}^{+\infty} \gamma^t R(s_t, \pi(s_t), s_{t+1}) \right]$$

Three approaches for approximation:

- ▶ Direct estimation
- ▶ Adaptive dynamic programming (ADP)
- ▶ Temporal difference learning (TD)

Direct estimation

The goal is to approximate state utility under the given policy

- ▶ Make **trials** and take the **reward-to-go** for each state

Direct estimation

The goal is to approximate state utility under the given policy

- Make **trials** and take the **reward-to-go** for each state

Example

We calculate utilities for $(1, 2)$ given the trial:

$$(1,1) \xrightarrow[\text{Up}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (2,3) \xrightarrow[\text{Right}]{-0.4} (3,3) \xrightarrow[\text{Right}]{+1} (4,3)$$

Direct estimation

The goal is to approximate state utility under the given policy

- Make **trials** and take the **reward-to-go** for each state

Example

We calculate utilities for $(1, 2)$ given the trial:

$$(1,1) \xrightarrow[\text{Up}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (2,3) \xrightarrow[\text{Right}]{-0.4} (3,3) \xrightarrow[\text{Right}]{+1} (4,3)$$

$$U(1, 2) = -0.04 - 0.04 - 0.04 - 0.04 - 0.04 + 1 = 0.8$$

Direct estimation

The goal is to approximate state utility under the given policy

- Make **trials** and take the **reward-to-go** for each state

Example

We calculate utilities for $(1, 2)$ given the trial:

$$(1,1) \xrightarrow[\text{Up}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (2,3) \xrightarrow[\text{Right}]{-0.4} (3,3) \xrightarrow[\text{Right}]{+1} (4,3)$$

$$U(1, 2) = -0.04 - 0.04 - 0.04 - 0.04 - 0.04 + 1 = 0.8$$

$$U(1, 2)' = -0.04 - 0.04 - 0.04 + 1 = 0.88$$

Direct estimation

The goal is to approximate state utility under the given policy

- ▶ Make **trials** and take the **reward-to-go** for each state

Example

We calculate utilities for $(1, 2)$ given the trial:

$$(1,1) \xrightarrow[\text{Up}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (2,3) \xrightarrow[\text{Right}]{-0.4} (3,3) \xrightarrow[\text{Right}]{+1} (4,3)$$

$$U(1, 2) = -0.04 - 0.04 - 0.04 - 0.04 - 0.04 + 1 = 0.8$$

$$U(1, 2)' = -0.04 - 0.04 - 0.04 + 1 = 0.88$$

- ▶ This is inefficient! We can **exploit** the Markov property

Adaptive dynamic programming

We can approximate the transition reward and probability functions (P and R) and apply **simplified Bellman's equation**:

$$U(s) = \sum_{s'} P(s' | s, \pi(s)) [R(s, \pi(s), s') + \gamma U(s')]$$

When the policy is fixed, this gives a **linear equation**

Adaptive dynamic programming

We can approximate the transition reward and probability functions (P and R) and apply **simplified Bellman's equation**:

$$U(s) = \sum_{s'} P(s' | s, \pi(s)) [R(s, \pi(s), s') + \gamma U(s')]$$

When the policy is fixed, this gives a **linear equation**

- ▶ Calculating P and R is easy when the environment is **fully observable**

Temporal difference learning

Still taking trials, but we **update** the utility to match frequently observed transitions

- ▶ We don't need a model!

Temporal difference learning

Still taking trials, but we **update** the utility to match frequently observed transitions

- ▶ We don't need a model!

Example

We calculate utilities for $(1, 3)$ given the trial:

$$(1,1) \xrightarrow[\text{Up}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (2,3) \xrightarrow[\text{Right}]{-0.4} (3,3) \xrightarrow[\text{Right}]{-0.04} (3,2) \xrightarrow[\text{Up}]{-0.04} (3,3) \xrightarrow[\text{Right}]{+1} (4,3)$$

Temporal difference learning

Still taking trials, but we **update** the utility to match frequently observed transitions

- We don't need a model!

Example

We calculate utilities for $(1, 3)$ given the trial:

$$(1,1) \xrightarrow[\text{Up}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (2,3) \xrightarrow[\text{Right}]{-0.4} (3,3) \xrightarrow[\text{Right}]{-0.04} (3,2) \xrightarrow[\text{Up}]{-0.04} (3,3) \xrightarrow[\text{Right}]{+1} (4,3)$$

$$U^\pi(1, 3) = -0.04 + U^\pi(2, 3)$$

Temporal difference learning

Still taking trials, but we **update** the utility to match frequently observed transitions

- ▶ We don't need a model!

Example

We calculate utilities for (1, 3) given the trial:

$$(1,1) \xrightarrow[\text{Up}]{-0.4} (1,2) \xrightarrow[\text{Up}]{-0.4} (1,3) \xrightarrow[\text{Right}]{-0.4} (2,3) \xrightarrow[\text{Right}]{-0.4} (3,3) \xrightarrow[\text{Right}]{-0.04} (3,2) \xrightarrow[\text{Up}]{-0.04} (3,3) \xrightarrow[\text{Right}]{+1} (4,3)$$

$$U^\pi(1, 3) = -0.04 + U^\pi(2, 3)$$

Then we can update with learning rate α :

$$U^\pi(s) \leftarrow U^\pi(s) + \alpha [R(s, \pi(s), s') + \gamma U^\pi(s') - U^\pi(s)]$$

- ▶ From TD's point of view, ADP is TD with *simulated experiences*

Active reinforcement learning

Utility functions give the best (expected) policy

We can decide to improve utility (**explore**) or keep maximizing utility (**exploit**)

- ▶ This is a **bandit problem** (set of Markov reward processes)

Active reinforcement learning


Utility functions give the best (expected) policy

We can decide to improve utility (**explore**) or keep maximizing utility (**exploit**)

- ▶ This is a **bandit problem** (set of Markov reward processes)

Example

Duolingo's recurring notifications use a bandit problem solver:



Template	Eligibility Criteria
You're on fire Continue your 109 day Spanish streak on Duolingo.	<i>Must have a 3+ day streak.¹</i>
Streak wager reminder You're on day 2 of your 7-day streak wager! Now get to day 3!	<i>Must have a streak wager.²</i>
Ready for your trip? Take 5 minutes to practice Italian now	<i>User's profile must indicate travel motivation.</i>

Greedy in the limit of infinite exploration (GLIE)

A greedy algorithm could ignore higher utility actions. We need a GLIE algorithm:

- ▶ Each action in a each state is tried an unbounded amount of times
- ▶ In the limit ($\rightarrow \infty$) the algorithm becomes truly greedy

Greedy in the limit of infinite exploration (GLIE)

A greedy algorithm could ignore higher utility actions. We need a GLIE algorithm:

- ▶ Each action in a each state is tried an unbounded amount of times
- ▶ In the limit ($\rightarrow \infty$) the algorithm becomes truly greedy

We can try different approaches:

- ▶ Random sampling
- ▶ Minimum trials

Random sampling

At step t , do the following:

- ▶ Choose a random action with probability $\frac{1}{t}$
- ▶ Otherwise, follow the greedy policy

This **does** eventually converge, but can be slow: a better approach would use some heuristic on state utility

Minimum trials

Have an **optimistic estimate** of utility ($U^+(s)$):

$$U^+(s) \leftarrow \max_a f \left(\sum_{s'} P(s' | s, a) [R(s, a, s') + \gamma U^+(s')] , N(s, a) \right)$$

- ▶ $N(s, a)$ is the number of times action a was tried from state s
- ▶ f is defined as:

$$f(u, n) = \begin{cases} R^+, & n < N_e \\ u, & n \geq N_e \end{cases}$$

Here, R^+ is an optimistic utility for actions tried less than N_e times

Basically, we are establishing an optimistic **prior** that assigns higher utilities to actions tried less than N_e times

Safe exploration

In the real world, we have to look out for:

- ▶ Large negative rewards
- ▶ Absorbing states
- ▶ Permanent damage (e.g. long-term utility losses)

Neither the greedy nor the exploratory approach are optimal!

Safe exploration

In the real world, we have to look out for:

- ▶ Large negative rewards
- ▶ Absorbing states
- ▶ Permanent damage (e.g. long-term utility losses)

Neither the greedy nor the exploratory approach are optimal! Two ways to solve the problem:

- ▶ Bayesian reinforcement learning
- ▶ Robust control theory approaches

Bayesian reinforcement learning

We take a probabilistic approach, starting with a **prior** probability $P(h)$ on h hypotheses about what the model **is**: the policy is then given by the posterior $P(h|e)$:

$$\pi^* = \operatorname{argmax}_{\pi} \sum_h P(h|e) U_h^{\pi}$$

Bayesian reinforcement learning

We take a probabilistic approach, starting with a **prior** probability $P(h)$ on h hypotheses about what the model **is**: the policy is then given by the posterior $P(h|e)$:

$$\pi^* = \operatorname{argmax}_{\pi} \sum_h P(h|e) U_h^{\pi}$$

- ▶ We turned the problem into an exploration **partially observable Markov decision process** (POMDP)
- ▶ Note that this approach assumes that the prior contains good estimates of reality

The robust control theory approach

We define a set of models \mathcal{H} , and always take the policy that maximizes utility in the **worst case** over \mathcal{H} :

$$\pi^* = \operatorname{argmax}_{\pi} \min_h U_h^{\pi}$$

The robust control theory approach

We define a set of models \mathcal{H} , and always take the policy that maximizes utility in the **worst case** over \mathcal{H} :

$$\pi^* = \operatorname{argmax}_{\pi} \min_h U_h^{\pi}$$

- ▶ This is closely tied to bayesian reinforcement learning: the set \mathcal{H} is the set of models that exceed some likelihood threshold on $P(h|e)$
- ▶ Again, we assume the models to be good estimates of reality

Temporal difference Q-learning

- ▶ With TD learning, we estimated the utility under a given policy

Temporal difference Q-learning

- ▶ With TD learning, we estimated the utility under a given policy
- ▶ Now we can estimate the action-utility functions in order to improve the policy

Temporal difference Q-learning

- ▶ With TD learning, we estimated the utility under a given policy
- ▶ Now we can estimate the action-utility functions in order to improve the policy

We substitute $Q(s, a)$ into Bellman's equation:

$$Q(s, a) = \sum_{s'} P(s'|s, a) \left[R(s, a, s') + \gamma \max_{a'} Q(s', a') \right]$$

Now we can derive an update:

$$Q(s, a) = Q(s, a) + \alpha \left[R(s, a, s') + \gamma \max_{a'} Q(s', a') - Q(s, a) \right]$$

SARSA learning

SARSA is a variation of TD Q-learning: instead of assuming the best possible action under known action-utility functions to be taken (**off-policy**), we wait for the model to actually execute actions (**on-policy**)

- We act after s, a, r, s', a' quintuplets

The update is given by:

$$Q(s, a) \leftarrow Q(s, a) + \alpha [R(s, a, s') + \gamma Q(s', a') - Q(s, a)]$$

SARSA learning

SARSA is a variation of TD Q-learning: instead of assuming the best possible action under known action-utility functions to be taken (**off-policy**), we wait for the model to actually execute actions (**on-policy**)

- ▶ We act after s, a, r, s', a' quintuplets

The update is given by:

$$Q(s, a) \leftarrow Q(s, a) + \alpha [R(s, a, s') + \gamma Q(s', a') - Q(s, a)]$$

TD and SARSA are subtly different:

- ▶ TD learning asks: "What does this action give if i stop using my policy, and take the best action (according to my estimates) from there onwards?"
- ▶ SARSA asks: "What did I get when i followed my policy and took this action?"