
Final Project

The Maximum Edge Weight Clique Problem



Abstract

The Maximum Edge Weight Clique (MEWC) problem is an optimization problem in graph theory that asks for the clique (a subset of vertices, all adjacent to one another) with the maximum total weight in an edge-weighted undirected graph. In the MEWC problem, each edge has a weight, and the weight of a clique is the sum of the weights of its edges. The goal is to find a clique with the maximum possible weight.

Class group:

CIR3 - Team 1

Teacher:

Leandro MONTERO

January 10, 2023

Contents

1	Introduction	3
1.1	Presentation	3
1.2	Configuration	4
1.3	Example of real-life situations	4
2	Exact Algorithm	6
2.1	Presentation	6
2.2	How it works	6
2.3	Pseudo code	11
2.4	Complexity	11
2.5	Bad Instance	11
2.6	Experiments	11
2.7	Analysis	11
3	Constructive Algorithm	12
3.1	Presentation	12
3.2	How it works	13
3.3	Pseudo code	13
3.4	Complexity	14
3.5	Instance	14
3.6	Experiments	14
3.7	Analysis	14
4	Local Search Algorithm	15
4.1	Presentation	15
4.2	How it works	15
4.3	Pseudo code	15
4.4	Complexity	15
4.5	Instance	15
4.6	Experiments	15
4.7	Analysis	15
5	Grasp Algorithm	16
5.1	Presentation	16
5.2	How it works	16
5.3	Pseudo code	16
5.4	Complexity	16
5.5	Instance	16
5.6	Experiments	16
5.7	Analysis	16
6	Conclusion	17
	References	18

1 Introduction

1.1 Presentation

Graph theory is a branch of mathematics that deals with the study of graphs, which are mathematical structures used to model pairwise relationships between objects. Graphs consist of vertices (also called nodes) that are connected by edges. The edges can be either directed (one-way) or undirected (two-way) and can also have a weight.

The Maximum Edge Weight Clique (MEWC) problem is an optimization problem in graph theory that asks for the clique (a subset of vertices, all adjacent to one another) with the maximum total weight in an edge-weighted undirected graph. In the MEWC problem, each edge has a weight, and the weight of a clique is the sum of the weights of its edges. The goal is to find a clique with the maximum possible weight.

Now, the MEWC problem is **NP-hard**, which means that it is not possible to find an efficient algorithm to solve it in polynomial time or that this problem is at least as hard as the hardest problems in NP. It is also the generalization of the Maximum Clique Problem (MCP), which is the special case where all edges have the same weight.

For example, the following graph $G = (V, E)$ has for its set of vertices $V = \{1, 2, 3, 4, 5, 6\}$ and for its set of edges $E = \{(1, 2), (1, 5), (2, 3), (2, 5), (3, 4), (4, 5), (4, 6)\}$. As we can see, the **red** edges $\{(1, 2), (1, 5), (2, 5)\}$ form a clique of size 3 and the other colored edges are each cliques of size 1. We can also easily deduct that the maximum clique of G is the **red** clique of size 3.




Figure 1: Basic graph example

The MEWC problem can be used to model various types of real-world situations where the goal is to find a subset of objects with the maximum total weight, and the objects are connected by weighted edges. Here are a few examples of such situations:

- **Network design:** In a communication network, the MEWC problem can be used to find the optimal subset of devices (vertices) to include in the network, such that the total cost of communication between the devices (edges) is maximum.
- **Protein interaction:** In biology, the MEWC problem can be used to find the optimal subset of proteins (vertices) in a protein-protein interaction network, such that the total interaction strength (edges) between the proteins is maximum.
- **Social network analysis:** In a social network, the MEWC problem can be used to find the optimal subset of individuals (vertices) with the maximum total relationship strength (edges) between them.

1.2 Configuration

- Ajouter les configurations que l'on a utilisé pour les tests du style la config

For this project we used **C++** to develop and implement our algorithms. It is a general-purpose programming language that has been used for a long time and is still widely used today. It is a compiled language, which means that it is translated into machine code before being executed. This allows it to be very fast and efficient. It is also a statically typed language, which means that the type of each variable must be declared before it is used. This allows the compiler to check the type of each variable and to detect errors at compile time.

Though C++ is a very powerful language, it is also very complex and has a lot of features. This can make it difficult to use. That's why we had a debate about which language to use for this project. Our choices were C++ and Python. We eventually chose C++ because it is a language that we are all familiar with and that we have all used before. We also chose it because it is a very powerful language that allows us to implement very efficient algorithms.

To be able to work on the project efficiently and to be able to share the code between us, we used **Github**¹. It is a web-based platform for version control, collaboration, and sharing of code, as well as a community of developers who contribute to open source projects and share their knowledge. It was a tool that was difficult for some to get used to quickly, especially on the configuration of the project at home, but which brought us a significant gain in efficiency once we had understood how to use it. And to share information and communicate between us, we used **Discord**.

1.3 Example of real-life situations

As we said before, the MEWC has many real-world applications in various fields such as social networks, chemistry, bioinformatics. Now, we will give an concrete example of a real-life situation that can be modelled as a MEWC problem.

The team formation process for a project, or for the search for a particular social group, is a situation that can be viewed as a MEWC problem. Let's imagine that the Student Office of ISEN Nantes is looking to reinforce the video games club of its school. Indeed, the latter has no succession for the following year and is thus led to die if no member presents himself. The future members of the office will have to be in contact with each other during a whole year and it is thus important to find people with common interests so that no tension is formed during their studies. The office has access to the Steam profiles of the students within ISEN (Steam is a video game digital distribution service that gives information about the games played by each one) as well as a record made by the gaming club of the different games played by their members. The fact of playing games in common could bring some people closer, and this makes it a good criterion to create a group that could take over the club because it would share common interests.

To model this problem, we can represent each student as a vertex and each the games played in common as an edge. The weight of each edge will be the number of games played in com-

¹<https://github.com/sehnryr/Final-Graph-Project-ISEN-CIR3>

mon. The goal of the office is to find a group of students that will take over the club. To do this, we will use the MEWC algorithm to find a group of students that has the highest affinity.

In the following example, we will restrict ourselves to 9 students of the CIR3 class of ISEN Nantes since it would be too complicated to represent every student of the school. We will also assume that the students have played the game listed in the table below.

Students	Game played
Youn	Minecraft, Civilisations, Lost ARK, Among US
Martin	Minecraft
Valentin	Genshin, Minecraft, Civilisations
Bastien	Genshin, Minecraft, Lost ARK, Among US
Guillaume	CSGO, Genshin, Overwatch, Stardew Valley
Dorian	CSGO, Paladins, Overwatch
Antoine	League of Legends, Stardew Valley
Thomas	League of Legends, The Last of US
Alexandre	League of Legends, Dofus

Which would give us this graph :




Figure 2: Graph representing the games played between the students

The goal of the Maximum Edge Weight Clique problem in this context would be to find a complete subset of individuals such that the sum of the weights of the edges between the individuals is maximized. In this example, the maximum weight clique would be the clique consisting of nodes Youn, Valentin, Martin, Bastien with a total weight of $2+1+1+1+3+2 = 10$.

2 Exact Algorithm

2.1 Presentation

A naive approach to the exact algorithm for solving the MEWC problem works by exploring all potential cliques in the graph and selecting the clique with the maximum weight. To do this, the algorithm uses a recursive function to explore all possible subsets of V . For each subset, the algorithm computes the weight of the clique formed by the vertices in the subset. If the weight is greater than the current maximum weight, the clique is selected as the current maximum. This process is repeated until all possible cliques have been explored, at which point the algorithm returns the clique with the maximum weight.

The time complexity of this approach is $\mathcal{O}(n^2 \times 2^n)$, where n is the number of vertices in the graph. This is due to the fact that there are 2^n possible subsets of V , and the algorithm must compute the weight of the clique, which by itself has a complexity of $\mathcal{O}(n^2)$ because there are at most $\frac{n(n-1)}{2}$ edges in a complete graph, and compare it to the current maximum weight. Therefore, the algorithm is only feasible for small-scale graphs.

However we could only look at the maximal cliques of the graph, which would reduce the number of subsets to explore. A clique is maximal if it is not a subgraph of any other clique. To find all maximal cliques in a graph, we can use the **Bron-Kerbosch** algorithm[1]. This algorithm has a time complexity of $\mathcal{O}(3^{\frac{n}{3}})$, where n is the number of vertices in the graph. This is optimal, as it has been proven by J. W. Moon & L. Moser in 1965[2] that there are at most $3^{\frac{n}{3}}$ maximal cliques in any n -vertex graph.

We can use the Bron-Kerbosch algorithm to find all maximal cliques in the graph, and then compute the weight of each clique. This approach has a time complexity of $\mathcal{O}(n^2 \times 3^{\frac{n}{3}})$, which is much better than the previous approach. However, this algorithm is still not feasible for large-scale graphs.

2.2 How it works

As said before, our algorithm first uses the Bron-Kerbosch algorithm to obtain all the maximal cliques of the input graph. Then, it iterates through those maximal cliques to look for which cliques have the highest weight.

The Bron-Kerbosch pivot algorithm that we use is a more efficient variant of the initial algorithm. The basic form of the algorithm is inefficient in the case of graphs with many non-maximal cliques as it makes a recursive call for every clique, maximal or not. To save time and allow the algorithm to backtrack more quickly in branches of the search that contain no maximal cliques, Bron and Kerbosch introduced a variant of the algorithm involving a "pivot vertex".


At each step, the algorithm keeps track of three groups of vertices: R which is the subset of vertices that must be in a clique, P which is the candidates that could be included in the clique and X which is the excluded vertices that already have been searched. In each call of the algorithm, P and X are disjoint sets whose union consists of vertices that form

cliques when added to R . When P and X are both empty there are no further elements that can be added to R , so R is a maximal clique and the algorithm outputs R .

The recursion is initiated by setting R and X to be the empty set and P to be the vertex set of the graph. Within each recursive call, the algorithm considers the vertices P in turn; if there are no such vertices, it either reports R as a maximal clique if X is also empty, or continue. Then, a pivot vertex u is chosen from $P \cup X$ since any maximal clique must include either u or one of its non-neighbors, for otherwise the clique could be augmented by adding u to it. Only u and its non-neighbors need to be tested as the choices for the vertex v that is added to R in each recursive call to the algorithm. For each vertex v chosen from $P \setminus N(u)$, with $N(u)$ being the neighbor set of u , it makes a recursive call in which v is added to R and in which P and X are restricted to $N(v)$, which finds and reports all cliques extensions of R that contains v . Then, it moves v from P to X to exclude it from consideration in future cliques and continues with the next vertex in $P \setminus N(u)$.

To illustrate the Bron-Kerbosch algorithm, let's use the example in Figure 1 on page 3:

Step 0:




At the initial step, as said before, we will initialize R and X to be the empty set and P to be the set of vertices of the graph.

$$R = \{\} \quad P = \{1, 2, 3, 4, 5, 6\} \quad X = \{\}$$

Figure 3: Graph illustration for the exact algorithm at step 0

Step 1:



In the first call of the function, since P is not empty, we chose a pivot vertex u in $P \cup X$. As it would be more time consuming to search for an appropriate pivot vertex, we simply chose the first one available, which will be represented in red. In this example we will always take the first element of P . The neighboring vertices of u are represented in blue.

After that, we will iterate over the vertices of $P \setminus N(u)$, or in this case, $\{1, 3, 4, 6\}$, and for each vertex v we will make a recursive call to the function with v added to R and P and X restricted to $N(v)$, which will find and report all cliques extensions of R that contains v .

Figure 4: Graph illustration for the exact algorithm at step 1

Step 2:




Figure 5: Graph illustration
for the exact algorithm at
step 2

At this step, since P is not empty, we will choose a pivot vertex u in $P \cup X$. Here $u = 2$ and the algorithm will iterate over the vertices of $P \setminus N(u)$, which is $\{2\}$.

The next recursive call will be made with $P = \{5\}$, the pivot vertex will be $u = 5$ and then the next recursive call will report the clique $\{1, 2, 5\}$, which will be added to the list of cliques.

After that, the algorithm will backtrack to $R = \{\}$ since there will be no more iteration to do, and will add 1 to X as it was visited in its entirety.

The recursive call process looks like this:

$R = \{1\}$	$P = \{2,5\}$	$X = \{\}$
$R = \{1,2\}$	$P = \{5\}$	$X = \{\}$
$R = \{1,2,5\}$	$P = \{\}$	$X = \{\}$

Step 3:




Figure 6: Graph illustration
for the exact algorithm at
step 3

At this step, since P is not empty, we will choose a pivot vertex u in $P \cup X$. Here $u = 2$ and the algorithm will iterate over the vertices of $P \setminus N(u)$, which is $\{2, 4\}$.

The next recursive calls will be made with $P = \{\}$ and $X = \{\}$, so they will report the cliques $\{2, 3\}$ and $\{3, 4\}$, which will be added to the list of cliques.

After that, the algorithm will backtrack to $R = \{\}$ since there will be no more iteration to do, and will add 3 to X as it was visited in its entirety.

The recursive call process looks like this:

$R = \{3\}$	$P = \{2,4\}$	$X = \{\}$
$R = \{2,3\}$	$P = \{\}$	$X = \{\}$
$R = \{3,4\}$	$P = \{\}$	$X = \{\}$

Step 4:




Figure 7: Graph illustration
for the exact algorithm at
step 4

At this step, since P is not empty, we will choose a pivot vertex u in $P \cup X$. Here $u = 3$ and the algorithm will iterate over the vertices of $P \setminus N(u)$, which is $\{5, 6\}$.

The next recursive calls will be made with $P = \{\}$ and $X = \{\}$, so they will report the cliques $\{4, 5\}$ and $\{4, 6\}$, which will be added to the list of cliques.

After that, the algorithm will backtrack to $R = \{\}$ since there will be no more iteration to do, and will add 4 to X as it was visited in its entirety.

The recursive call process looks like this:

$R = \{4\}$	$P = \{5, 6\}$	$X = \{3\}$
$R = \{4, 5\}$	$P = \{\}$	$X = \{\}$
$R = \{4, 6\}$	$P = \{\}$	$X = \{\}$

Step 5:




Figure 8: Graph illustration
for the exact algorithm at
step 5

At this step, since P is empty and X is not, the algorithm will choose a pivot vertex u in X . Here $u = 4$ but the algorithm will not be able to iterate further as $P \setminus N(4) = \{\}$.

The recursive call process looks like this:

$R = \{6\}$	$P = \{\}$	$X = \{4\}$
-------------	------------	-------------

The Bron-Kerbosch algorithm is now finished, and we have obtained the following maximal cliques:

$$\{(1, 2, 5), (2, 3), (3, 4), (4, 5), (4, 6)\}$$

Now that we obtained the maximal cliques of the graph, we can compare them to find the maximal edge-weighted clique.

We will simply iterate over the maximal cliques and sum the weights of the edges that are in the clique. The clique with the highest weight will be the maximal edge-weighted clique.

If we want to explain everything in a more concise way, we can use the call process and tree of the algorithm.

BronKerbosch(\emptyset , $\{1, 2, 3, 4, 5, 6\}$, \emptyset)
BronKerbosch(1, $\{2, 5\}$, \emptyset)
BronKerbosch(1, 2, $\{5\}$, \emptyset)
BronKerbosch(1, 2, 5, \emptyset , \emptyset) : report $\{1, 2, 5\}$
BronKerbosch(3, $\{2, 4\}$, \emptyset)
BronKerbosch(2, 3, \emptyset , \emptyset) : report $\{2, 3\}$
BronKerbosch(2, 4, \emptyset , \emptyset) : report $\{2, 4\}$
BronKerbosch(4, $\{5, 6\}$, 3)
BronKerbosch(4, 5, \emptyset , \emptyset) : report $\{4, 5\}$
BronKerbosch(4, 6, \emptyset , \emptyset) : report $\{4, 6\}$
BronKerbosch(6, \emptyset , 4)

Figure 9: Call process of the Bron-Kerbosch algorithm



Figure 10: Call tree of the Bron-Kerbosch algorithm

2.3 Pseudo code

Algorithm 1 Exact MEWC algorithm

```

1: procedure EXACTMEWC( $G = (V, E)$ )
2:    $maxClique \leftarrow \emptyset$   $\triangleright$  Variable to store the maximum weight clique
3:    $maxCliqueWeight \leftarrow 0$ 
4:    $R \leftarrow \emptyset$ 
5:    $P \leftarrow V$ 
6:    $X \leftarrow \emptyset$ 
7:    $maximalCliques \leftarrow \emptyset$   $\triangleright$  The set of cliques to add the maximal cliques to
8:   BRONKERBOSCH( $R, P, X, maximalCliques$ )  $\triangleright$  Call the BronKerbosch algorithm to get the maximal cliques of the graph
9:   for all  $clique \in maximalCliques$  do
10:     $weight \leftarrow \text{GETCLIQUEWEIGHT}(clique)$   $\triangleright$  Get the weight of the current clique
11:    if  $weight > maxCliqueWeight$  then
12:       $maxClique \leftarrow clique$ 
13:       $maxCliqueWeight \leftarrow maxCliqueWeight + weight$ 

```

Algorithm 2 Bron-Kerbosch algorithm

```

1: procedure BRONKERBOSCH( $R, P, X, maximalCliques$ )
2:   if  $P = \emptyset$  &  $X = \emptyset$  then
3:      $maximalCliques \leftarrow maximalCliques \cup \{R\}$   $\triangleright$  If  $P$  and  $X$  are both empty sets,  $R$  is a maximal clique of the graph
4:    $u \in P \cup X$   $\triangleright$  Chose a pivot vertex from  $P \cup X$ 
5:   for all  $v \in P \setminus N(u)$  do
6:     BRONKERBOSCH( $N \cup \{v\}, P \cap N(v), X \cap N(v)$ )  $\triangleright$  Make recursive call with reduced candidate set
7:      $P \leftarrow P \setminus \{v\}$ 
8:      $X \leftarrow X \cup \{v\}$ 

```

Algorithm 3 Clique weight function

```

1: procedure GETCLIQUEWEIGHT( $clique$ )  $\triangleright$  We assume that the clique is complete
2:    $weight \leftarrow 0$ 
3:   for all  $v_1 \in clique$  do
4:     for all  $v_2 \in clique$  do  $\triangleright$  Iterate over all the vertices in the clique and add the weight of each edge to the weight of the clique
5:       if  $v_1 \neq v_2$  then
6:          $weight \leftarrow weight + w_{v_1, v_2}$ 
7:   return  $\frac{weight}{2}$   $\triangleright$  Divide by 2 because the weight of an edge is counted twice

```

2.4 Complexity

2.5 Bad Instance

The exact algorithm have no bad instance, he will always find the optimal solution each time. However, it will take a fairly long time to do so.

2.6 Experiments

2.7 Analysis

3 Constructive Algorithm

3.1 Presentation

A **heuristic algorithm** is a type of algorithm that uses rules of thumb to try to find an approximate solution to a problem, rather than an exact one. Heuristic algorithms are often used when it is not possible to find an exact solution to a problem, or when an exact solution would be too time-consuming to compute. They are also used when an approximate solution is good enough, or when finding an exact solution is not the primary goal. Heuristic algorithms are commonly used in artificial intelligence, computer science, and other fields. They are often used to solve optimization problems, search problems, and other types of problems where an exact solution is not necessary or practical.

A **constructive heuristic** algorithm is a type of heuristic algorithm that is used to find a solution to a problem by building it incrementally. Constructive heuristics start with a partial solution and gradually add to it until a complete solution is found. They are commonly used to solve optimization problems, where the goal is to find the optimal solution, or the solution that is the best among all possible solutions.

As we said, the use of the constructive heuristic in solving the MEWC start with a partial solution and build it until a complete solution is found. To do this, the latter will be subject to a number of criteria.

1. Add The First Vertex to solution.
2. Seek for his most weighted neighbors. And add it to solution if it's a neighbor of all vertices in solution.
3. Repeat the step 2 until no vertices is available to add

In these choices of criteria, we can notice one that is quite important. The one to choose the First Vertex. Indeed, it is him which will define the quality of our solution. Taking it randomly would be useless and counter productive for the sake of solving MEWC. As it was important, we thought about how to choose it and 2 answers appeared to us and we have a debate on the subject because we could not reach a consensus on it. We hesitated between these two solutions:

- The first idea was to take the highest degree vertex of the graph given as input.
 - One reason to choose the highest degree vertex as the first vertex in the solution is that it may be more likely to be part of a maximum edge weight clique(because it's the case where it's the most likely to have the biggest clique who could be the MEWC). This is because it will allow more edges to be added to the solution, which can increase the overall sum of edge weights in the clique.
 - Another reason is that it may be more likely to be connected to other high degree vertices. This means that by adding the highest degree vertex to the clique first, we may be able to include other high degree vertices in the clique as well, which can further increase the overall sum of edge weights.
- The second one was to take the vertex with the highest sum of weights of the edges.

- One reason to choose the vertex with the highest edge weight as the first vertex in the clique is that it may be more likely to be part of a maximum edge weight clique. This is because adding a vertex with a high edge weight to the clique will contribute more to the overall sum of edge weights in the clique, which is what we are trying to maximize.
- Another reason is that we can potentially reduce the search space for the rest of the algorithm. This is because we know that any clique we find must include this vertex, which means that we can eliminate any vertices that are not connected to it as potential members of the clique. This can help to make the algorithm more efficient by reducing the number of vertices that we need to consider.

We implemented both ideas and performed tests on a number of graph to see which was the most consistent and we concluded that it was the vertex with the highest sum of weights of the edges. Moreover, in most graphs (at least the randomly generated ones), we had, in general, a rather homogeneous weights of edges which worked better with this one.

Constructive heuristic can be contrasted with other types of heuristics, such as local search heuristics, which try to find a solution by making small changes to an existing solution, or random heuristics, which generate solutions randomly and then choose the best one. Constructive heuristics are often used when it is important to find a solution that is complete and comprehensive, rather than just a local improvement.

Examples of some famous problems that are solved using constructive heuristics are the flow shop scheduling, the vehicle routing problem and the open shop problem.

3.2 How it works

3.3 Pseudo code

Algorithm 4 Constructive algorithm

```

1: procedure CONSTRUCTIVE( $G = (V, E)$ )
2:    $S \leftarrow \emptyset$                                 ▷ Variable to store the clique that represents the Solution
3:    $Sweight \leftarrow 0$                              ▷ Variable to store the total weight of S
4:    $P \leftarrow \emptyset$                              ▷ Lists of vertex to store the vertex that could be added to S
5:    $FirstVertex \leftarrow \text{GETFIRSTVERTEX}(G)$         ▷ Call a function to get the vertex of highest degree
6:    $\text{ADDVERTEX}(S, FirstVertex)$                      ▷ add the FirstVertex to S
7:    $LastVertex \leftarrow FirstVertex$                 ▷ Variable to store the last element added to S
8:    $\text{GETPOTENTIELCANDIDATE}(G, FirstVertex, P)$       ▷ add to P all the neighbors of FirstVertex
9:   while  $P.size() \neq 0$  do
10:     $\text{UPDATECLIQUE}(G, LastVertex, P, R)$            ▷ Call the function that update S
11:     $\text{UPDATEPOTENTIELCANDIDATE}(G, LastVertex, P)$    ▷ Call the function that update P

```

Algorithm 5 First Vertex function

```

1: procedure GETFIRSTVERTEX( $G$ )
2:    $BestVertex \leftarrow \emptyset$   $\triangleright$  Variable to store the BestVertex found
3:    $MaxNumNeighbors \leftarrow 0$   $\triangleright$  Variable to store the max number of neighbors found
4:    $vertices \leftarrow GETVERTICES(G)$   $\triangleright$  get the lists of every vertex of  $G$ 
5:   for  $vertex \in vertices$  do  $\triangleright$  Iterate over all the vertices in  $G$ 
6:     if  $||N(vertex)|| > MaxNumNeighbors$  then
7:        $MaxNumNeighbors \leftarrow ||N(vertex)||$   $\triangleright$  replace the maximum size
8:        $BestVertex \leftarrow vertex$   $\triangleright$  replace BestVertex with the vertex
9: return  $BestVertex$ 

```

Algorithm 6 getPotentielCandidate function

```

1: procedure GETPOTENTIELCANDIDATE( $G, LastVertex, P$ )
2:   for  $neighbor \in N(lastVertex)$  do
3:      $P.insert(neighbor)$   $\triangleright$  Add the vertex to  $P$ 

```

Algorithm 7 updateClique function

```

1: procedure UPDATECLIQUE( $G, lastVertex, P, S$ )
2:    $weight \leftarrow 0$   $\triangleright$  Variable to store temporary the weight of each edge of lastVertex
3:    $bestWeight \leftarrow 0$   $\triangleright$  Variable to store the max weight found
4:    $CliqueWeight \leftarrow 0$   $\triangleright$  Variable to store the weight that we will add to the clique
5:    $BestVertex \leftarrow \emptyset$   $\triangleright$  Variable to store the bestVertex found
6:   for  $vertex \in P$  do
7:     if  $vertex = LastVertex$  then
8:       continue
9:     else
10:       $edge \leftarrow G.GETEDGE(lastVertex, vertex)$   $\triangleright$  get the edge between lastVertex and vertex
11:       $weight \leftarrow edge.GETWEIGHT()$   $\triangleright$  get the weight of the edge between lastVertex and vertex
12:      if  $weight > bestWeight$  then  $\triangleright$ 
13:         $bestWeight \leftarrow weight$   $\triangleright$  replace the bestWeight found
14:         $BestVertex \leftarrow vertex$   $\triangleright$  replace the bestVertex found
15:         $weight \leftarrow 0$ 
16:      else
17:         $weight \leftarrow 0$ 
18:    $vertices \leftarrow S.getVertices()$ 
19:   for  $v \in vertices$  do
20:      $edge \leftarrow GRAPH.GETWEIGHT(v, BestVertex)$ 
21:      $CliqueWeight \leftarrow CliqueWeight + edge.GETWEIGHT()$ 
22:    $ADDVERTEX(S, BestVertex)$ 
23:    $LastVertex \leftarrow BestVertex$ 
24:    $ADDWEIGHT(S, CliqueWeight)$ 

```

3.4 Complexity

3.5 Instance

3.6 Experiments

3.7 Analysis

4 Local Search Algorithm

4.1 Presentation

4.2 How it works

4.3 Pseudo code

4.4 Complexity

4.5 Instance

4.6 Experiments

4.7 Analysis

5 Grasp Algorithm

5.1 Presentation

5.2 How it works

5.3 Pseudo code

5.4 Complexity

5.5 Instance

5.6 Experiments

5.7 Analysis

6 Conclusion

References

- [1] C. Bron and J. Kerbosch. Algorithm 457: finding all cliques of an undirected graph. *Communications of the ACM*, September 1973. <https://doi.org/10.1145/362342.362367>.
- [2] J.W. Moon and L. Moser. On cliques in graphs. *Israel J. Math.*, Match 1965. <https://doi.org/10.1007/BF02760024>.