

Assignment 1: E-Purchase Business Process Modeling

BPMN 2.0 and Petri-net models for an Amazon/Souq-like order process

Submission focus

This report models the same business process in two accepted ways: BPMN 2.0 for business readability and Petri nets for formal token-based behavior. It includes the as-is process, a to-be improvement, issue analysis, and exported evidence files.

Team Members

Name	Code
Seif Eldeen Ibrahim	22P0023
Anas Bayoumi	22P0011
Nadine Radwan	22P0214
Jana Sameh	22P0237

Contents

List of Figures	ii
1 Executive Scope	1
2 Prepared Evidence Assets	1
3 Evaluation Criteria Coverage	1
4 Modeling Standard and Core Step Checklist	2
5 Lecture Concepts Applied	3
6 BPMN 2.0 Model	3
6.1 Participants and Responsibilities	3
6.2 As-Is BPMN	3
6.3 To-Be BPMN	5
7 Petri-Net Model	7
7.1 Formal Net Summary	7
7.2 As-Is Petri Net	7
7.3 To-Be Petri Net	9
8 As-Is Analysis	11
9 Enhancements and Comparative Analysis	11
9.1 Expected Outcomes from the To-Be Model	12
10 Case Coverage	12
11 Conclusion	12

List of Figures

1	As-is BPMN 2.0 model exported from the BPMN source as SVG and rendered into the report cache.	4
2	Enhanced to-be BPMN 2.0 model with early validation, parallel checks, tracking, and proactive complaint handling.	6
3	As-is Petri net exported from the DOT/PNML model as SVG and rendered into the report cache.	8
4	Enhanced to-be Petri net showing validation, parallel checks, fulfillment synchronization, and the complaint loop.	10

1 Executive Scope

The modeled process covers an e-purchase from order submission through validation, stock handling, payment, fulfillment, delivery, complaint handling, and final archiving. To maximize assignment coverage, the same process is documented in both required modeling styles:

- BPMN 2.0 models for the as-is and to-be business process.
- Petri-net models for the same as-is and to-be behavior, including choices, synchronization, loops, and final markings.

The to-be design improves early validation, parallelizes independent checks, connects complaints to the same order case, and adds proactive SLA monitoring for delayed goods.

2 Prepared Evidence Assets

File	Purpose
output/assignment1_epurchase_as_is.bpmn	BPMN 2.0 source for the as-is model, importable into bpmn.io or Camunda.
output/assignment1_epurchase_to_be.bpmn	BPMN 2.0 source for the improved to-be model.
output/assignment1_epurchase_as_is_petri.dot and .pnml	Graphviz and PNML versions of the formal as-is Petri net.
output/assignment1_epurchase_to_be_petri.dot and .pnml	Graphviz and PNML versions of the improved to-be Petri net.
screenshots/assignment1/*.svg	Browser/tool exports used as the visual evidence in this report.

3 Evaluation Criteria Coverage

The assignment rubric is used as an explicit checklist. The report covers each marking category as follows:

Criteria category	Marks	How this report covers it
Process model quality	20	BPMN 2.0 models use start/end events, tasks, exclusive gateways, parallel gateways, an event-based gateway, timer/message intermediate events, and logical sequence flows. Petri nets also model the process with places, transitions, arcs, initial marking, final marking, choices, joins, and loops. Core e-purchase steps are shown: order capture, stock check, address validation, payment, invoice, packing, shipping, delivery, complaint, and archive.
Tool proficiency	5	BPMN source files are prepared for bpmn.io/Camunda import. Petri-net DOT/PNML files are prepared for Graphviz, diagrams.net, or PNML tools. The submitted report includes browser/tool SVG exports rendered into the PDF through the verified cache.

Use of intermediate events	10	The as-is BPMN uses an intermediate delivery event and a timer event for delayed goods. The to-be BPMN uses an SLA event and SLA-breach branch. Both models clearly route delayed goods into complaint registration, customer notification/escalation, and return to delivery tracking.
Documentation and clarity	15	Every diagram is labeled, introduced, and followed by text explaining what the model means. Participants, responsibilities, formal Petri-net summary, file evidence, and case coverage are documented.
Analysis before enhancement	10	The as-is issue register identifies reactive complaints, late address correction, weak synchronization, separated complaint ownership, and late archiving. Each issue includes consequence, type, and justification through its proposed fix.
Enhancement suggestions	10	The to-be model moves validation earlier, parallelizes stock/payment checks, standardizes fulfillment, adds tracking, connects complaints to the order case, and makes delay handling proactive.
Comparative analysis	10	The before/after comparison explains what changed and why. Expected outcomes are added for shorter waits, lower rework, clearer customer communication, and stronger auditability.
Report quality and submission	10	The report has a cover page, contents, list of figures, consistent table styling, labeled diagrams, and no LaTeX-drawn diagrams. The repository is cleaned after compilation.
Originality and effort	10	The process is a realistic Amazon/Souq-like scenario with payment service, warehouse, courier, support, complaint escalation, SLA tracking, audit events, and two modeling methods rather than only the minimum model.

4 Modeling Standard and Core Step Checklist

Requirement	Implementation evidence
Correct BPMN start/end behavior	The as-is model starts at <i>Order received</i> and reaches either <i>Order rejected</i> or <i>Order closed</i> . The to-be model starts at <i>Checkout submitted</i> and has the same accepted/rejected closure logic.
Core e-purchase flow	Both versions include order validation, stock decision, payment authorization, invoice emission, warehouse fulfillment, shipment, delivery confirmation, and archiving.
Decision logic	Exclusive gateways model stock availability, address/order validity, and rejection paths. Parallel gateways model independent checks and synchronized branches.
Goods-delay event	The delayed-goods path is not only mentioned in text; it is modeled as an event-driven complaint/escalation branch.
Petri-net formal semantics	The Petri nets include initial/final markings, routing transitions, parallel split/join behavior, and a loop from delay escalation back to delivery waiting/tracking.
Online-tool evidence	SVG exports from BPMN/Petri-net tools are stored in screenshot/assignment1/ , while importable source files remain in output/ .

5 Lecture Concepts Applied

The report follows the lecture definitions of a business process as structured work involving people, systems, data, and resources to deliver value to a customer. The BPMN lecture is used for events, tasks, gateways, sequence flows, and process readability. The Petri-net lecture is used for places, transitions, arcs, markings, reachability, synchronization, and loops. The process-analysis lecture is used for issue registers, customer interfaces, quality risks, cycle-time reduction, and improvement opportunities.

6 BPMN 2.0 Model


6.1 Participants and Responsibilities

Participant or lane	Responsibility
Customer	Places the order, provides address data, receives invoice and delivery, and may complain when goods are delayed.
Marketplace system	Captures the order, checks stock, validates data, emits invoice, tracks status, and archives the order.
Payment service	Authorizes payment and returns payment status to the marketplace process.
Warehouse	Reserves stock, picks, packs, and prepares the physical shipment.
Courier	Ships the product and reports delivery or delay events.
Customer support	Registers complaints, notifies customers, and escalates delayed courier cases.

6.2 As-Is BPMN


The as-is process starts when the order is received. The system captures the order and checks stock. If stock is unavailable, the order is rejected. If stock is available, the item is reserved, address data is checked, and missing address data is requested. Payment authorization and warehouse fulfillment then run in parallel. After invoice emission and shipment, the process waits for a delivery event.

The delayed-goods scenario is represented by an intermediate timer event after shipment. If delivery confirmation is not received within the SLA, the timer branch registers a complaint, escalates the courier, and loops back to the delivery wait state.



6.3 To-Be BPMN

The to-be process moves validation earlier, runs stock and payment checks in parallel, standardizes fulfillment preparation, adds tracking, and makes the complaint path proactive. The SLA breach event opens a complaint automatically, notifies the customer, expedites the courier, and then keeps the order under tracking until delivery confirmation is received.



7 Petri-Net Model

The Petri-net model is the second modeling method. States are represented as places, activities and routing events as transitions, and allowed movement as directed arcs. One token starts in the initial place. Silent transitions are used only for routing choices, parallel splits, and joins.


7.1 Formal Net Summary

Model	Places	Transitions	Arcs	Initial and final markings
As-is	19	20	42	$M_0 = \{p_start\}$ and $M_f = \{p_done\}$
To-be	23	22	48	$M_0 = \{p_start\}$ and $M_f = \{p_done\}$

7.2 As-Is Petri Net

The as-is Petri net has one token in **p_start**. The stock decision place enables either rejection or reservation. The preparation split produces one token for the payment branch and one token for the fulfillment branch; the join requires both invoice completion and shipment before delivery waiting can continue. The goods-delay timer transition creates the complaint token, and the escalation transition loops back to the delivery waiting place.


Assignment 1 As-Is E-Purchase Petri Net



7.3 To-Be Petri Net

The to-be Petri net shows two improvements formally. First, stock check and payment authorization are enabled together after validation, then synchronized before the order validity decision. Second, invoice emission and physical fulfillment are split into parallel branches and joined before tracking. The SLA breach transition sends the case through complaint opening, customer notification, and courier expedition before returning to the SLA wait place.

Assignment 1 To-BE E-Purchase Post Net



8 As-Is Analysis

No.	Issue	Consequence	Type	Proposed fix
1	Complaint is reactive	Customer may discover the delay before the company reacts.	Customer interface	Add proactive shipment tracking and SLA monitoring.
2	Address correction is late	Reserved stock may wait while customer data is fixed.	Data/process	Validate address before reservation.
3	Weak synchronization	Invoice or shipment may wait for manual status checking.	IT/process	Automate parallel checks and clear joins.
4	Complaint path is separate	Support may reconstruct context manually.	Organization	Attach complaint to the same order case and assign ownership.
5	Archiving only at closure	Monitoring data is late and hard to mine.	IT	Record status events throughout execution.

9 Enhancements and Comparative Analysis

Area	As-is process	To-be improvement
Checkout data	Address may be requested after stock reservation.	Validate address and order data before stock is held.
Cycle time	Several checks can wait sequentially.	Run stock and payment checks in parallel.
Delay handling	Complaint begins after a late-delivery event.	SLA monitoring opens the complaint and notification path proactively.
Customer quality	Customer may need to ask for status.	Tracking events and notifications are part of the process.
Cost and rework	Support may manually reconstruct order context.	Complaint is connected to the same order case.
Modeling rigor	BPMN shows business readability.	Petri nets add formal token semantics for choices, joins, and loops.

9.1 Expected Outcomes from the To-Be Model

Improvement target	Change made	Expected outcome
Shorter waiting before fulfillment	Validate order data first and run stock/payment checks in parallel.	Fewer orders reserve inventory while still missing data; independent checks no longer wait unnecessarily.
Faster delay response	Add SLA monitoring and proactive complaint opening.	The company reacts before the customer has to chase the order, improving customer experience.
Lower manual rework	Keep complaint handling attached to the same order case.	Support sees order, shipment, and complaint context together instead of reconstructing the case manually.
Better audit trail	Record status events before final archiving.	Later process mining can identify bottlenecks, courier delays, and repeated failure points.

10 Case Coverage

- Normal order: checkout, validation, stock/payment checks, fulfillment, delivery confirmation, and archive.
- Rejected order: invalid payment, invalid data, or unavailable stock leads to rejection.
- Missing address: handled before stock is blocked in the to-be model.
- On-time delivery: delivery message event continues to archive.
- Goods delayed: timer/SLA event opens complaint, notifies customer, escalates courier, and loops back to delivery tracking.
- Audit trail: status updates and archiving support later monitoring and process mining.

11 Conclusion

The BPMN models provide the business-readable view required for process discussion, while the Petri nets provide the formal execution view required for reasoning about choices, concurrency, synchronization, and loops. The to-be model directly addresses the main weaknesses in the as-is process: late validation, reactive complaint handling, and weak status visibility.