



Clinic API

Reference Documentation

VERSION 1.0

BASE URL <http://localhost:8017>

AUTH TYPE Bearer Token

GENERATED January 2025



Contents

1. Overview

2. Authentication

2.1 Generate Token

2.2 Using the Token

3. Endpoints

3.1 Create Appointment

3.2 Get Doctor

3.3 List Appointments

4. Error Responses

5. State Values

1. Overview

The Clinic API provides programmatic access to a clinic management system built on Odoo. It supports appointment scheduling, doctor lookups, and patient management through a set of REST-style JSON endpoints.

Base URL

```
http://localhost:8017
```

Request Format

Most endpoints accept parameters inside a `params` object in the JSON body. The token generation endpoint is the exception, taking parameters directly in the root JSON object.

Response Format

All responses follow a standard envelope structure:

```
{
  "status": "success" | "error",
  "message": "Human-readable description",
  "data": { ... }
}
```

Note on Route Types

Some endpoints use `type="json"` (Odoo JSON-RPC style), returning JSON directly. Others use `type="http"`, returning a raw HTTP response with JSON body.

2. Authentication

All protected endpoints require a valid Bearer token passed in the `Authorization` header. Tokens are generated via the public `/api/token/generate` endpoint.

Header	Format	Required
<code>Authorization</code>	<code>Bearer <token></code>	Yes (except token generation)
<code>Content-Type</code>	<code>application/json</code>	Recommended for POST

2.1 Generate Token

POST

/api/token/generate

PUBLIC

Generate or regenerate an API token for a user. If a token already exists for the user, it will be renewed with a new expiry date.

Parameters

Field	Type	Required	Description
user_id	integer	Required	Odoo user ID

Request Body

```
{
  "params": {
    "user_id": 2
  }
}
```

Success Response (200 OK)

```
{
  "status": "success",
  "message": "Token generated successfully",
  "data": {
    "name": "Administrator API Token",
    "user_id": 2,
    "token": "a1b2c3d4e5f6789012345678901234567890abcd",
    "is_active": true,
    "expires_on": "2025-02-15 10:30:00",
    "last_used": "null"
  }
}
```

Error Responses

Condition	Response
-----------	----------

6

Missing <code>user_id</code>	User ID is required
User not found	User not found

Token Properties

Property	Description
Expiry	30 days from generation
Reuse	Existing tokens are renewed, not duplicated
Tracking	Last used timestamp and IP are recorded

2.2 Using the Token

Include the token in the `Authorization` header for all protected endpoints:

```
Authorization: Bearer a1b2c3d4e5f6789012345678901234567890abcd
```

The validation middleware will:

1. Check the header is present
2. Verify the token exists and is active
3. Check the expiry date
4. Update last used timestamp and IP address

Token Validation Errors

Error	Status	Description
Missing Authorization Bearer Token	401	No Authorization header present
Invalid or Expired Token	401	Token not found or inactive
Token Expired	401	Token past expiry_date

3.1 Create Appointment

POST /api/clinic/appointments/create**BEARER TOKEN****JSON-RPC**

Create a new appointment between a patient and a doctor.

Parameters

Field	Type	Required	Description
patient_id	integer	Required	Patient record ID
doctor_id	integer	Required	Doctor record ID
date	string	Required	Appointment date (YYYY-MM-DD)

Request Body

```
{
  "params": {
    "patient_id": 1,
    "doctor_id": 3,
    "date": "2025-01-20"
  }
}
```

Success Response (200 OK)

```
{
  "status": "success",
  "message": "Appointment Created Successfully",
  "data": {
    "appointment_id": 15,
    "name": "APT/2025/0015",
    "doctor_name": "Dr. Sarah Johnson",
    "doctor_speciality": "Cardiology",
    "patient_name": "John Doe",
    "patient_email": "john@example.com",
    "patient_age": 35,
    "date": "2025-01-20",
    "state": "draft"
  }
}
```

Error Responses

Condition	Response
Patient not found	Patient not found.
Doctor not found	Doctor not found.
Server exception	Exception message

3.2 Get Doctor

3.2 Get Doctor

GET /api/clinic/doctors/<doctor_id>

BEARER TOKEN

HTTP

Retrieve detailed information about a specific doctor by ID.

URL Parameters

Field	Type	Required	Description
doctor_id	integer	Required	Doctor record ID (URL path)

Request

```
GET /api/clinic/doctors/3
Authorization: Bearer <token>
```

Success Response (200 OK)

```
{
  "status": "success",
  "data": {
    "id": 3,
    "name": "Dr. Sarah Johnson",
    "email": "sarah.j@clinic.com",
    "speciality": "Cardiology",
    "license_number": "MD123456",
    "consultation_fee": 150.00,
    "today_appointment_count": 4
  }
}
```

Error Responses

Condition	Response
Doctor not found	Doctor With id {id} not found

3.3 List Appointments

POST

/api/clinic/appointments/list

BEARER TOKEN

JSON-RPC

Search appointments using dynamic filters. At least one filter parameter is required.

Filter Requirement

Requests with no filter parameters will return an error. Valid filters: `doctor_id` , `date` , `state` , `specialty_id` .

Parameters

Field	Type	Required	Format	Description
<code>doctor_id</code>	<code>integer</code>	Optional	Plain integer	Filter by doctor
<code>date</code>	<code>string</code>	Optional	DD/MM/YYYY	Filter by appointment date
<code>state</code>	<code>string</code>	Optional	See state values	Filter by appointment state
<code>specialty_id</code>	<code>integer</code>	Optional	Plain integer	Filter by medical specialty
<code>limit</code>	<code>integer</code>	Optional	Default: 50	Maximum records to return

Request Body

```
{
  "params": {
    "doctor_id": 3,
    "date": "20/01/2025",
    "state": "confirmed",
    "limit": 50
  }
}
```

Success Response (200 OK)

```
{
  "status": "success",
  "count": 2,
  "data": [
    {
      "id": 12,
      "doctor_id": 3,
      "doctor_name": "Dr. Sarah Johnson",
      "speciality": "Cardiology",
      "patient_id": 5,
      "patient_name": "Alice Brown",
      "date": "2025-01-20",
      "start_time": 9.0,
      "end_time": 10.0,
      "reason": "Regular checkup",
      "state": "confirmed"
    },
    {
      "id": 14,
      "doctor_id": 3,
      "doctor_name": "Dr. Sarah Johnson",
      "speciality": "Cardiology",
      "patient_id": 7,
      "patient_name": "Bob Wilson",
      "date": "2025-01-20",
      "start_time": 14.0,
      "end_time": 15.0,
      "reason": "null",
      "state": "confirmed"
    }
  ]
}
```

Response Fields

Field	Type	Description
id	integer	Appointment ID
doctor_id	integer	Doctor record ID
doctor_name	string	Doctor full name

speciality	string	Doctor specialty name
patient_id	integer	Patient record ID
patient_name	string	Patient full name
date	string	Appointment date
start_time	float	Start hour (24h format)
end_time	float	End hour (24h format)
reason	string	Visit reason or "null"
state	string	Appointment state

Error Responses

Condition	Response
No filters provided	At least one search filter is required.
Invalid date format	time data ... does not match format '%d/%m/%Y'

4. Error Responses

Errors are returned with consistent structure across all endpoints. The format varies slightly between JSON-RPC and HTTP routes.

JSON-RPC Routes

Routes with `type="json"` return errors as a JSON object:

```
{
  "status": "error",
  "message": "Description of what went wrong"
}
```

HTTP Routes

Routes with `type="http"` return a proper HTTP response with JSON body:

```
HTTP/1.1 401 Unauthorized
Content-Type: application/json

{
  "status": "error",
  "message": "Missing Authorization Bearer Token"
}
```

Common Error Codes

HTTP Status	Message	Cause
200 (body error)	User ID is required	Missing parameter in token generation
200 (body error)	User not found	Invalid user_id for token generation
401	Missing Authorization Bearer Token	No Authorization header
401	Invalid or Expired Token	Token not found or inactive
401	Token Expired	Token past expiry date

4. Error Responses

200 (body error)	Patient not found.	Invalid patient_id
200 (body error)	Doctor not found.	Invalid doctor_id
200 (body error)	At least one search filter is required.	Empty search in list endpoint

5. State Values

Appointments progress through defined states. Use these values when filtering by `state` in the list appointments endpoint.

State Value	Description
<code>draft</code>	Appointment created, not yet confirmed
<code>confirmed</code>	Appointment confirmed and scheduled
<code>in_progress</code>	Patient is currently with the doctor
<code>done</code>	Appointment completed
<code>cancelled</code>	Appointment cancelled