PostroniX TX-78

WWW.POSTRONIX.COM

All Purposes Thermal 58mm Receipt Printers

Application of Use :

- ✓ Retail, Grocery, Convenience Store
- ✓ Ticketing, Queueing and Parking
- ✓ Gas Station
- ✓ Café and Restaurant.

© 2012

PHYSICAL CHARACTERISTICS AND INTERFACE	
Dimension (L x W x H)	135 x 215 x 105 mm
Weight (grams)	745 grans
Materials	ABS + PC
Color	Solid Black
Interface	Multi Interface : USB , Serial RS-232 or Centronics Parallel

PRINTING SPECIFICATIONS	
Printing Method	Thermal Line Printing
Printing Width and Resolution	58 milimeters , 20 cpi or 203 dpi
Printing Directions	Bi-directionals Printers
Printing Speed	90 milimeters per-second
Fonts	Font A 12 x 24 dots Font B 9 x 17 dots International Characters 24 x 24 dots
Buffers and NV Images	32Kb data buffer
Barcode Supports	JAN13 / EAN13, JAN 8 / EAN8, CODE39
Colomns	42 or 56 columns for each line
Character Set	Alphanumerics, International Character Sets
Sensors	Paper End Sensor
Cutter	Please use Postronix TX-79C

SUPPLIES	
Paper Type	Thermal Paper Roll (Use Postronix Original Paper)
Paper Dimension	58 milimeters width (57.5 mm ± 0.5 mm)
Paper Maximum Outer Core	53 milimeters outer diameter
Paper Thickness	0.06 – 0.08 mm.

OTHERS GENERAL SPECIFICATIONS	
Compatibility	Microsoft Windows 7, Vista, XP, NT, 2003, 2000, ME, 9X
Power Supply	12 VDC Adaptor 2.5 A
Cash Drawer Output	RJ 11 – 12 VDC 1A
Certifications	CE, ROHS (European Market)
Safety Standards	EN, UL (American Market), CSA (European Market)
Print Head Life	40 Kilometers
Vertical Printing	Yes. Can use printing vertical using optional Vertical Mounting.
Environment	Temperature - 5° C to 50° C Humidity 10 to 80% (Operational) Temperature - 15° C to 65° C Humidity 10 to 90% (Storage)

PostroniX

WWW.POSTRONIX.COM