

Ulsan-Fault earthquake catalog pipeline

Reference manual: detection → association → location → relocation (HypoDD dt.ct + dt.cc)

Long-term (2010–present) catalog for the Ulsan Fault, SE Korea

rev. 2026-07-24 · src/ufpipe

`ufpipe` (`src/ufpipe`) is the **end-to-end pipeline**: six stages, detection → association → augment → PHS → locate → **relocate** (HypoDD dt.ct + dt.cc). The final **relocate** stage produces the double-difference relocated catalog. The heavy `dt.cc/xcorr/HypoDD engine` is external (15.PocketQuake korea-cluster-relocation, HypoDD v2.1beta); `ufpipe` orchestrates it. The relocate stage is **self-fed**: it builds its inputs from `ufpipe`’s OWN detection+association (`ufpipe.reloc_inputs`) and runs the orchestration in `src/ufpipe/reloc_driver/`; working dirs + results go to `outputs/reloc/`. `detection_test/` is a **fully frozen pilot archive** (the 2016 4-picker comparison; `lib/` DEPRECATED, see `detection_test/lib/DEPRECATED.md`). The relocation internals have a dedicated guide: `src/ufpipe/reloc_driver/PIPELINE.md` + the pilot’s `study_guide.pdf`.

Contents

1	What the pipeline does	1
1.1	<code>ufpipe</code> vs <code>detection_test</code>	2
1.2	Two orthogonal “model” dimensions	2
2	Install & environment	2
3	Stages 1–5: detection through location	3
3.1	Source of truth for pick↔event assignment	4
4	Parameters (<code>src/ufpipe/config.py</code> — the single disclosed source)	4
4.1	Detection / DSP	4
4.2	Association (PyOcto) — daily-chunked, <code>ASSOC_GATE</code> (lenient) vs <code>ASSOC_GATE_STRICT</code> .	4
4.3	Velocity model & location	5
5	How to run	5
5.1	Running each stage separately	6
5.2	Relocation — running the last stage (stage 6)	6
6	Outputs & layout	7
7	Stage 6: relocation — HypoDD dt.ct + dt.cc	7
8	Robustness & invariants	8
9	Troubleshooting / provenance checks	9

1 What the pipeline does

Build an **internally consistent, long-term earthquake catalog** for the Ulsan Fault region (SE Korea), 2010–present, from continuous seismic waveforms, using AI phase pickers so small events are detected uniformly even as the recording network grows, and finally **relocate** the catalog with

double-difference (HypoDD `dt.ct + dt.cc`) for sub-100 m relative precision. Every stage is scripted and parameterized; results reproducible.

Detection	Association	Location	QC	Relocation
PhaseNet / PhaseNet+	PyOcto (+augment)	HYPONVERSE	<code>uf_cluster</code>	HypoDD <code>dt.ct + dt.cc</code>
<i>picks</i> →	<i>events+assign</i> →	<i>.sum/.arc</i> →	<i>well-located</i> →	<i>hypoDD.reloc</i>

1.1 ufpipes vs detection_test

`ufpipe` is the production end-to-end pipeline; everything live is under `src/`, including the relocation orchestrator `src/ufpipe/reloc_driver/run_picker_reloc.py` (driven by the relocate stage with `--skip-build`; the HypoDD/xcorr engine itself is external in 15.PocketQuake). `detection_test` is the **frozen pilot archive** of the 2016 4-picker comparison — nothing in it is live (`lib/` DEPRECATED; the `reloc_2016_uf*/` dirs hold the pilot’s manifests and results).

	<code>ufpipe</code> (<code>src/ufpipe</code>)	<code>detection_test</code>
Role	the self-contained end-to-end catalog + relocation pipeline (incl. <code>reloc_driver/</code>)	frozen archive of the 2016 4-picker pilot
Stages	detection → association → augment → PHS → locate → relocate	— (nothing live)
Driver	<code>python -m ufpipes.run_pipeline</code>	—
Ends at	HypoDD <code>dt.cc</code> (§7); results in <code>outputs/reloc/</code>	—

`ufpipe`’s own detection + association cover **KS/KG/GJ/NS** with daily-chunked association (§5), and the `relocate` stage builds its inputs from those outputs (`ufpipe.reloc_inputs`); it no longer consumes `detection_test/lib`. The pipeline is fully self-contained. See §7.

1.2 Two orthogonal “model” dimensions

Dimension	Flag	Values
Picker model	<code>--model</code>	<code>stead</code> , <code>original</code> , <code>phasenet_plus</code> , <code>eqt</code> , ...
Velocity model	<code>--velmodel</code>	<code>kim1983</code> , <code>kim2011</code>

Any picker model can be located with any velocity model. `stead/original` are SeisBench PhaseNet weights; `phasenet_plus` is EQNet PhaseNet+ (needs a local EQNet clone).

2 Install & environment

The pipeline runs in a **two-env split** on this server (there is no single “ulsan” env): detection (PhaseNet+/SeisBench, torch) in `eqnet` (Py 3.9); association (PyOcto) + orchestration in `base` (Py 3.12); the relocate stage’s GPU xcorr shells out to `pq-gpu` internally.

One-time setup

1. `conda run -n eqnet pip install -e . --no-deps` (detection env)
2. `conda run -n base pip install -e . --no-deps` (association/orchestration env)
3. **HYPOINVERSE**: the external `hyp1.40` binary must be on `PATH` (not pip-installable).
4. **PhaseNet+** only: a local EQNet clone at `config.EQNET_DIR`.
5. **Fresh machine**: `conda env create -f environment.yml` (env `uf-catalog`), then install the torch build matching your CUDA (`pip install torch --index-url https://download.pytorch.org/whl/cu128`).

After `pip install -e .`, `import ufpipes.config` and `python -m ufpipes.run_pipeline` work from any directory — no `sys.path` hacks.

3 Stages 1–5: detection through location

`STAGES = [detection, association, augment, phs, locate, relocate]` — run in order. Stages 1–5 (below) are functions in `src/ufpipe/core.py`; the relocate stage (6) is `src/ufpipe/relocate.py` and has its own §7. `run_pipeline.py` chains them per year.

#	Stage	In → Out	What it does
1	detection	continuous mSEED → picks/ (per station-day)	AI picker on each station-day across KS/KG/GJ/NS (per-year multi-network table, <code>stations.py</code>); anti-alias >100 Hz, unify mixed rates, resample to 100 Hz, pick P/S above threshold. GPU. Idempotent (skips done days).
2	association	picks → <code>pyocto_*.csv</code> + assignment	PyOcto octree associator groups picks into events (gate below), daily-chunked (± 150 s/day, in-day origins) so it scales to the dense NS array. Coords from the multi-network table.
3	augment	assignment → augmented assignment	scan daily picks for orphans PyOcto missed, add to each event so HYPOINVERSE sees the full pick set. Backs up + overwrites in place; idempotent.
4	phs	assignment → <code>UF{year}.phs</code>	write the HYPOINVERSE phase file from the (augmented) assignment.
5	locate	<code>.phs</code> → <code>UF{year}.{sum,arc}</code>	run HYPOINVERSE (<code>hyp1.40</code>) with the chosen velocity model → located catalog + errors.

Pipeline order matters

`augment` runs *between* `association` and `phs`, so HYPOINVERSE sees the full augmented pick set and computes correct `GAP/DMIN/ERZ/RMS`. Do not reorder.

3.1 Source of truth for pick↔event assignment

The **PyOcto assignment (after augmentation)** is authoritative for which `(station, phase)` tuples belong to each event. Do NOT use a legacy time-window pick dump — when two events fall <60 s apart at the same station the earliest pick “wins” and leaks into the wrong event. Downstream (SAC-header writers, magnitude/QC notebooks) must read `pyocto_assignment_{velmodel}_{year}.csv`.

4 Parameters (src/ufpipe/config.py — the single disclosed source)

Change defaults here. Everything is one file.

4.1 Detection / DSP

Parameter	Value	Meaning
<code>SAMPLING_RATE</code>	100.0 Hz	the pickers’ trained rate; all data resampled to it
<code>ANTIALIAS</code>	lowpass 45 Hz, 8 corners, zerophase	applied BEFORE down-sampling (>100 Hz KG/NS)
<code>BANDPASS</code>	1–40 Hz, 4 corners, causal	legacy detection path; PhaseNet+ runs raw
<code>P_THRESHOLD</code> , <code>S_THRESHOLD</code>	0.2	SeisBench pick probability threshold
<code>PNPLUS_MIN_PROB</code>	0.3	EQNet PhaseNet+ pick threshold
<code>PNPLUS_NT</code>	1024×36	PhaseNet+ patch length (whole-day, <code>cut_patch</code>)
<code>MAX_CORES</code>	24	CPU cap (respects <code>taskset</code> affinity)

4.2 Association (PyOcto) — daily-chunked, ASSOC_GATE (lenient) vs ASSOC_GATE_STRICT

Association runs **one calendar day at a time**: a $\pm$ `ASSOC_OVERLAP_S` (150 s) window per day is associated and only events whose *origin* falls in-day are kept (dedup). This is physically equivalent to a single pass (local events are seconds long) but keeps each PyOcto solve to seconds — a whole-year single pass is intractable on the dense ~200-station NS array ($\gg$ 1 h, 12 GB). Station coordinates come from the multi-network year table (`stations.py`), so KS/KG/GJ/NS all associate.

Parameter (config)	lenient	_STRICT	Meaning
REGION_CENTER $\pm$ pad	(35.856,129.224) $\pm$ (1.0,1.2)		search area (deg)
ASSOC_ZLIM	(0, 30)		depth range (km)
ASSOC_TIME_BEFORE	300		origin-search window (s)
ASSOC_OVERLAP_S	150		daily-chunk overlap (s)
n_picks	4	6	min total picks
n_p / n_s	2 / 2	3 / 3	min P / S picks
n_ps	1	2	min stations with both P+S (depth)
ASSOC_PICK_MATCH_TOL		1.5	residual cap (s)

Pass `--strict` to use `ASSOC_GATE_STRICT` (fewer, cleaner events). `--workers N` parallelises the independent daily chunks. Velocity for association = `ASSOC_VELMODEL` (kim2011 1-D), matching the reloc feeder. Output schema (events `idx,time,x,y,z,picks,latitude,longitude,depth`; assignment event `idx,pick_idx,residual,station,phase,time`) is unchanged, so `phs/locate/relocate` consume it as before.

4.3 Velocity model & location

DEFAULT_VELMODEL = kim2011; kim1983 also available (`data/metadata/velocity/kim1983.csv`, a layered V_p/V_s model; HYPOINVERSE *.crh tables live in `data/hypoinv/{kim1983,kim2011}/`). PHASE_CHANNELS = {P: HHZ, S: HHN}.

5 How to run

Standard runs (from the repo root)

```
python -m ufpipes.run_pipeline --model original --years 2024          one year, all 5 stages
python -m ufpipes.run_pipeline --model original --years 2010-2024    the whole record
python -m ufpipes.run_pipeline --model original --years 2015,2016 --velmodel kim1983    specific years, kim1983
python -m ufpipes.run_pipeline --model original --years 2024 --stage-from association    resume (picks already done)
python -m ufpipes.run_pipeline --model original --years 2024 --days 1-3    detection on a few days (testing)
python -m ufpipes.run_pipeline --model original --years 2024 --strict    strict association gate
python -m ufpipes.run_pipeline --model original --years 2016 --stage-from relocate --through dtcc    relocation only (dt.cc; needs feeder)
```

CLI flags: `--model` · `--years` ('2010-2024' or '2015,2016') · `--velmodel` · `--days` · `--device` {cuda,cpu} · `--workers` · `--strict` · `--force` (allow writing to `stead`) ·

`--stage-from {detection,association,augment,phs,locate}` (start mid-chain).

Shared 64-core server — always pin cores

Detection sizes its preprocessing pool and `torch` threads from the process CPU *affinity*, capped by `MAX_CORES=24`. Launch under `taskset` so the whole job stays within budget:

```
OMP_NUM_THREADS=1 taskset -c 0-7 python -m ufpipes.run_pipeline --model original
--years 2010-2024
```

Without pinning, PhaseNet+ grabbed ~49 cores / 193 threads and starved everything. Inference is **GPU-preferred** (warns loudly, never silently falls back to CPU).

Detection is **idempotent** — it skips station-days whose picks already exist, so runs resume safely after an interruption.

5.1 Running each stage separately

Every `ufpipe` stage is also a standalone CLI (`--model --year`), so you can run detection alone, then association alone, etc. Order is `detection` → `association` → `augment` → `phs` → `locate`. Each reads the previous stage's output from disk.

Stage	standalone command
Detection	<code>python -m ufpipes.detection --model original --year 2024</code> <code>[--networks KS,KG,GJ,NS] [--days 1-5] [--workers 8]</code>
Association	<code>python -m ufpipes.association --model original --year 2024</code> <code>[--networks KS,KG,GJ,NS] [--workers 8] [--strict]</code>
Augment	(runs inside <code>run_pipeline</code> ; or call <code>core.run_augment_year</code> from Python)
PHS	<code>python -m ufpipes.make_phs --model original --year 2024</code>
Location	<code>python -m ufpipes.run_hypoinverse --model original --year 2024</code> <code>--velmodel kim2011</code>

Or drive the same stage functions from Python / a notebook:

```
from ufpipes import core, config
core.run_detection_year("original", 2024, days=range(1,6))
events, assign = core.run_association_year("original", 2024)
core.write_phs("original", 2024); core.run_hypoinverse_year("original", 2024,
velmodel="kim2011")
```

5.2 Relocation — running the last stage (stage 6)

The relocate stage is **self-fed**: it needs only `ufpipe`'s own per-year detection + association (`pyocto_kim2011_<year>.csv` + assignment). It builds the reloc input store (event-idx SAC + station table) from those via `ufpipes.reloc_inputs`, then hands off to the driver `run_picker_reloc.py` `--skip-build` (scaffold → HYPOINVERSE → QC → rereference → GPU xcorr → HypoDD dt.cc). If a year's association is missing, the stage preflights and prints exactly what to run.

Step	command
Detection	<code>conda run -n eqnet python -m ufpipes.detection --model original --year 2016</code>
Association	<code>conda run -n base python -m ufpipes.association --model original --year 2016</code>
Reloc (to QC)	<code>python -m ufpipes.run_pipeline --model original --years 2016 --stage-from relocate --through hypoinverse (fast)</code>
Reloc (full)	<code>python -m ufpipes.run_pipeline --model original --years 2016 --stage-from relocate --through dtcc (+ xcorr→HypoDD dt.cc; ~6 h dense)</code>

`--through hypoinverse` stops at the QC'd absolute-location subset; `--through dtcc` continues to the double-difference relocation. `--clean-cache` deletes the ~tens-of-GB interp cache after dt.cc (essential for multi-year runs). `detection_test/lib/` is DEPRECATED (see `lib/DEPRECATED.md`); the relocation internals are documented in `src/ufpipe/reloc_driver/PIPELINE.md + study_guide.pdf`.

6 Outputs & layout

All pipeline products go under `outputs/models/<model>/` (regenerable; gitignored):

Path	Contents
<code>.../detection_location/<year>/picks/</code>	per-station-day picks (stage 1)
<code>.../pyocto/pyocto_{vm}_{year}.csv</code>	associated events (stage 2)
<code>.../pyocto/pyocto_assignment_{vm}_{year}.csv</code>	pick→event assignment (authoritative)
<code>.../station_table/stations_{year}.csv</code>	per-year station roster (discovered from metadata)
<code>.../HypoInv/PHS/UF{year}.phs</code>	HYPOINVERSE phase file (stage 4)
<code>.../HypoInv/{vm}/UF{year}.{sum,arc,prt}</code>	located catalog + errors (stage 5)
<code>outputs/reloc/reloc_{year}_uf[_{model}]/results/</code>	dt.cc-relocated catalog + links (stage 6)

`{vm}` = `config.PYOCTO_VELMODEL` = `kim2011` for current daily-chunked runs; legacy pre-2026-07 whole-year artifacts on disk are named `kim1983`.

Inputs (metadata by kind, 2026-07): waveforms in `KS_KG/ GJ/ NS/ NS_100hz/` (station dirs at each root); station tables in `data/metadata/stations/{ks_kg,gj,ns,kigam}/` (+ the per-year derived cache `stations/derived/`); instrument responses in `data/metadata/responses/`; velocity model in `data/metadata/velocity/`; HYPOINVERSE control inputs (STA/kim*) in `data/hypoinv/`.

7 Stage 6: relocation — HypoDD dt.ct + dt.cc

The 6th ufpipes stage: turn the QC'd absolute-location catalog into a **double-difference relocated** catalog for sub-100 m relative precision.

```
python -m ufpipes.run_pipeline --model original --years 2016 --stage-from relocate
--through dtcc --clean-cache
```

`ufpipes.relocate` (`src/ufpipes/relocate.py`) is *self-fed*: it preflights ufpipes's OWN per-year association, builds the reloc inputs from it (`ufpipes.reloc_inputs` — SAC store, pyocto tables, station table, merged archive), then invokes the validated orchestrator `src/ufpipes/reloc_driver/run_picker_reloc.py --skip-build`, which drives the external HypoDD/xcorr engine. Internal stages (all KS/KG/GJ/NS):

#	Stage	What it does
1	SAC store	event-idx-keyed native-rate SAC waveforms from the associated picks (<code>event_sac/</code>)
2	HYPOINVERSE	absolute location of all UF-box events (kim2011) → <code>.sum</code>
3	QC	<code>uf_cluster.QC</code> : keep <code>erh<5</code> , <code>erz<5</code> , <code>gap<270</code> , <code>num>5</code> , <code>rms<1.0</code>
4	re-reference	stamp each SAC's origin from the (full-run) HYPOINVERSE <code>.sum</code>
5	ph2dt	build <code>event.dat</code> + catalog differential times <code>dt.ct</code>
6	xcorr (GPU)	cross-correlation differential times <code>dt.cc</code> (band 5–20 Hz, interp 1000 Hz, <code>cc≥0.7</code>)
7	HypoDD	kim2011, ISTART=2, ISOLV=2 (LSQR), adaptive damping (CND 40–80), HypoDD v2.1beta (MAXDATA=15M) → <code>hypoDD.reloc</code>

Relocation outputs (symlinked into the working dir)

Each run publishes `outputs/reloc/reloc_<year>_uf[_<p>]/results/` with symlinks to the external run tree: `hypoDD.reloc.dtcc` (`dt.ct+dt.cc`), `hypoDD.reloc.dtct` (`dt.ct-only`), `HypoInv.full.sum`, ...“`dt.cc-resolved`” = events keeping ≥ 1 surviving cross-correlation link — the highest-precision subset.

The invariant that matters (see PIPELINE.md)

Origins flow into `dt.cc`: `rereference` stamps SAC origins from a `.sum`, and `xcorr` stores $dt = (t_1 + \text{shift} - ot_1) - (t_2 - ot_2)$ — subtracting those origins. Use the *full-run* HYPOINVERSE solution QC gated on (never a redundant re-run), or the `dt.cc` values are corrupted. This is enforced by `run_picker_reloc.py::inject_full_hypoinverse`.

8 Robustness & invariants

- **Network growth is automatic.** Stations are *discovered from StationXML + on-disk coverage* each month; the deployed network for that period is what enters the run. No hard-coded station lists.
- **Mixed sampling rates handled.** >100 Hz stations (KG/NS at 200 Hz) are anti-alias-lowpassed then resampled to the pickers' 100 Hz. The anti-alias filter is applied BEFORE down-sampling (never after).
- **Velocity model, thresholds, and gates are epoch-invariant by choice** $\Rightarrow$ the catalog stays internally comparable across years.
- **Idempotent & resumable** at every stage; `--stage-from` restarts mid-chain.
- **Do not edit the stead reference run** (it is the baseline). Scripts refuse `--model stead` writes unless `--force`.

9 Troubleshooting / provenance checks

Symptom	Check
Detection finds no waveforms	<code>python -c "import ufpipes.stations as s; print(s.build_year_table(YEAR).net.value_counts())"</code> — the per-year multi-network table must list stations, and each row's <code>archive</code> dir must exist.
<code>ImportError: ufpipes / uflib</code>	<code>pip install -e . --no-deps</code> in both <code>eqnet</code> and <code>base</code> ; <code>import ufpipes.config; print(__file__)</code> must be <code>src/ufpipes</code> .
<code>ModuleNotFoundError: pyocto</code>	you ran association in <code>eqnet</code> — <code>PyOcto</code> lives in <code>base</code> . Detection → <code>eqnet</code> ; association → <code>base</code> .
<code>InternalMSEEDWarning: ...Steim2 failed</code>	corrupt <code>Steim2</code> record(s) in the archive (e.g. <code>KG.MKL 2010</code>): the samples still decode; the reader collapses the per-record spam into one summary line per station-day and reads anyway. Informational — the named station-days are the QC signal.
GJ/NS station silently yields no picks	mid-day sampling-rate changes (100/200/1000 Hz) and <code>int32/float64</code> records refuse to merge — handled since 2026-07 (rate + dtype unified <i>before</i> merge in both readers).
<code>relocate</code> aborts at preflight	<code>ufpipes</code> 's own per-year association is missing for that (model, year) — run <code>ufpipes.detection</code> (<code>eqnet</code>) then <code>ufpipes.association</code> (<code>base</code>); the preflight prints the exact commands.
Wrong pipeline imported	<code>ufpipes</code> is renamed precisely to avoid the collision with the external korea-cluster-relocation <code>pipeline</code> . Verify <code>ufpipes.config.__file__</code> is under <code>src/</code> .
Events look over/under-associated	<code>ASSOC_GATE</code> vs <code>--strict</code> (<code>ASSOC_GATE_STRICT</code>); <code>ASSOC_PICK_MATCH_TOL</code> is the primary knob.
GPU not used	inference is GPU-preferred and warns loudly; check the torch/CUDA install (never silently CPU).
Sparse early years, few events	expected — KS/KG-only network (2010–2015) has larger azimuthal gaps; GJ joins 2016, the dense NS array 2017+; the QC gate honestly reflects what the network resolves.

Companion docs: docs/overview.md, docs/pipeline.md, docs/how-to-run.md,
docs/directory-structure.md · src/ufpipes/README.md · relocation pipeline:
src/ufpipes/reloc_driver/PIPELINE.md + study_guide.pdf.