



Calango

Packaging Guide

Building the macOS `.dmg`
and Linux `.deb` installers

Leandro Seixas

Calango 26.8.36

Abstract

Calango ships as two native installers built with CMake/CPack: a drag-and-drop disk image (`.dmg`) for macOS and a Debian package (`.deb`) for Ubuntu/Debian. This guide covers the prerequisites, the exact commands, what the packaging pipeline does under the hood, how to verify the artifacts, and the failure modes we have already hit — with their fixes. Everything described here lives in `CMakeLists.txt` (install and CPack sections) and in the `packaging/` directory of the repository.

Contents

1 Overview	1
2 BLAS/LAPACK backend	2
2.1 The incident this exists to prevent	2
2.2 The startup crash Accelerate alone didn't catch	3
2.3 Dependency audit	3
3 macOS: building the <code>.dmg</code>	4
3.1 Prerequisites	4
3.2 Commands	4
3.3 The resulting image	5
3.4 Cleaning up afterwards	5
3.5 What the install step does	6
3.6 File associations	6
3.7 Verification	7
4 Linux: building the <code>.deb</code>	7
4.1 Prerequisites (Ubuntu/Debian)	7
4.2 Commands	8
4.3 Package contents and desktop integration	8
4.4 Verification	9
5 The embedded Python environment	9
6 Known limitations and next steps	10

1 Overview

Both installers come out of the standard CMake flow: `configure` → `build` → `cpack`. The platform decides the generator:

Platform	CPack generator	Artifact
macOS (<code>-DCALANGO_MACOS_BUNDLE=ON</code>)	DragNDrop	<code>calango-26.8.36-macos-arm64.dmg</code>
Linux	DEB	<code>calango_26.8.36_amd64.deb</code>

Each artifact is accompanied by a `.sha256` checksum file. The package version comes from `project(calango VERSION ...)` in `CMakeLists.txt` — the single source of truth for the version, baked into the binary as `CALANGO_VERSION` (About dialog, project files) and reused by CPack for the installer file names.

The supporting files are:

- `packaging/macos/make_icns.sh` — renders `calango.icns` from the master PNG icon in `assets/calango/` (used when no committed `.icns` exists).
- `packaging/macos/embed_python_framework.sh` — makes the `.app` independent of the build machine's Python (Section 5).
- `packaging/linux/calango.desktop` — application launcher entry.
- `packaging/linux/calango-mime.xml` — registers `application/x-calango-project` for `.calproj` project files, plus MIME types for the 12 other structure / trajectory / volumetric formats Calango reads (Section 3.6).
- `packaging/linux/postinst`, `postrm` — refresh the desktop/MIME/icon caches on install and removal.
- `packaging/linux/audit_elf_deps.py`, `packaging/macos/audit_macho_deps.py` — fail the packaging step if a shipped binary needs a library the installer does not declare (Section 2).

2 BLAS/LAPACK backend

Status: there is no BLAS/LAPACK backend anymore. The native DFT engine's generalised eigenproblem (`src/dft/LinearAlgebra.cpp`) and the native DFTB engine that shared it were LAPACK's only consumers in this codebase — both were removed entirely (substantially implemented but narrowly exposed, with no downstream feature wiring; see git history). The packaged `calango` binary now links no BLAS/LAPACK implementation at all. This section is kept as history: it explains an incident that shaped the packaging pipeline's dependency audit (Section 2.3), which remains active and still matters for every OTHER shipped library.

The fix at the time was a CMake option, `CALANGO_BLAS`, offering a choice of vendors (Accelerate, OpenBLAS, Generic, MKL, or the old unconstrained behaviour) and pinning `BLA_VENDOR` explicitly instead of letting `find_package(LAPACK)` guess. **That option no longer exists** — removed along with its only two consumers.

2.1 The incident this exists to prevent

`calango 26.8.36`'s shipped `.deb` needed `libmkl_intel_lp64.so.3`, `libmkl_intel_thread.so.3`, `libmkl_core.so.3` and `libiomp5.so` at runtime — present on the build machine (an unconstrained `find_package(LAPACK)` picked up MKL there), completely absent from a clean `apt install ./calango_*.deb`, and **not declared as a Depends::** `dpkg-shlibdeps` could not attribute those `.so` files to any installed package, so it silently omitted them from the control file rather than failing the build. The package installed cleanly and crashed on first launch with a missing-library error, on any machine without that exact MKL install.

The same build round's `.dmg` had the identical disease, through a different vendor. The DFTB helper binary linked directly against Homebrew's `libopenblas.0.dylib` under `/opt/homebrew`, preferred over Apple's Accelerate framework simply because it was discoverable on that build machine's CMake search path. Nothing downstream rewrites its load commands the way `macdeployqt` rewrites `calango` itself (Section 3.5), so it stayed absent on any Mac without `brew install openblas`.

Pinning `BLA_VENDOR` explicitly used to fix both: with a vendor set, `find_package(LAPACK)` only looks for that vendor’s own library name patterns, so it could no longer silently substitute whatever else happened to sit on a build machine’s search path. Removing the only two things that ever called `find_package(LAPACK)` is the more complete version of the same fix — there is no vendor left to substitute.

2.2 The startup crash Accelerate alone didn’t catch

A user’s Mac never got past launch: a crash report (2026-08-21) showed a dyld “Library not loaded” error for `@rpath/libgcc_s.1.1.dylib`, referenced from the bundled `libgfortran.5.dylib` — same 26.8.36 .dmg, a SECOND defect past what pinning `BLA_VENDOR` alone fixes. `calango`’s bundled `libopenblas.0.dylib` had its own dependencies correctly rewritten to be bundle-relative by `macdeployqt`, but kept three of its original absolute Homebrew GCC rpaths on its `LC_RPATH` list; on the build machine dyld’s chained rpath search silently found `libgcc_s.1.1.dylib` through one of them, while the file itself was never actually copied into `Contents/Frameworks`. A clean Mac without that exact Homebrew install misses every one of those paths and aborts before `main()` runs. A bundle-relative load path is proof of *form*, not of *resolution* — the first version of `audit_macho_deps.py` (path-form only) would have passed this bundle.

Two fixes at the time: `CALANGO_BLAS` defaulting to `Accelerate` removed the whole `openblas/gfortran/gcc_s` chain outright (verified by rebuilding: a fresh .dmg linked `calango` and `calango-dftb-run` against `Accelerate.framework` only) — since superseded by removing the native DFT/DFTB engines entirely (Section 2), so there is now no BLAS chain to link on any platform; and `packaging/macos/strip_leftover_rpaths.sh`, run after `macdeployqt`’s two passes and before the final `codesign`, deletes any non-relocatable `LC_RPATH` entry from every bundled Mach-O — the same .dmg carried this on three OTHER, unrelated libraries too (`libdbus-1.3.dylib`, `libjasper.7.dylib`, `libjpeg.8.dylib`), so this one is **still active**: defense in depth for every future bundled library, not the BLAS vendor that is now gone. `audit_macho_deps.py` was extended to match: it now checks every `LC_RPATH` entry for the same relocatability rule, and resolves every relative dependency against the bundle’s own pooled rpath set rather than trusting the load-path string’s shape alone.

2.3 Dependency audit

`packaging/linux/audit_elf_deps.py` and `packaging/macos/audit_macho_deps.py` run automatically at the end of `build_deb.sh/build_dmg.sh`, after `cpack` produces the artifact and before it is published, and fail the packaging step — not just warn — if any shipped ELF/Mach-O needs a library that is not declared in the installer’s own dependency metadata, bundled in the package itself, or part of the base OS. Intel MKL and the Intel OpenMP runtime (`libmkl_*`, `libiomp5`, `libimf`, `libirc`, `libsvml`, `libintlc`) are hard-banned in the Linux audit regardless of `Depends`: — a packaged build must never need them.

```
python3 packaging/linux/audit_elf_deps.py installers/calango_<ver>_<arch>.deb
python3 packaging/macos/audit_macho_deps.py installers/calango_<ver>_macOS.dmg
```

The Linux script needs `dpkg` for an authoritative package-ownership check (the real gate, run on the Linux packaging machine); without it, it falls back to a soname-family heuristic — useful for exercising the script’s own logic elsewhere, not a substitute for the real gate. The macOS script needs no such fallback: `otool`, always present, is enough to tell a relative/system load path from a build-machine one.

Known gap, not silently swept under the audit. `build_dmg.sh` passes the audit script two `-exclude` flags that skip the embedded Python framework and its payload directory entirely — not because that tree is clean. Auditing the 26.8.36 .dmg found it has the *same* disease: six `stdlib`

extension modules (`_ssl`, `_hashlib`, `_decimal`, `_lzma`, `_sqlite3`, `_zstd`) plus the framework’s own Python binaries loaded Homebrew’s OpenSSL, sqlite, zstd, mpdecimal and xz directly, meaning that particular artifact was built against a Homebrew-linked interpreter rather than the relocatable `python-build-standalone` tree this pipeline is documented to download by default (Section 5). That is a separate, pre-existing bug in Python provisioning, not the BLAS/MKL issue this audit was built for, and fixing it is out of scope here — the existing `-probe-python` launch check catches “ASE won’t import” but not “every dylib is relocatable”. Rebuild via the documented default flow and re-run the audit script with no `-exclude` flags to confirm a given build is actually clean there before treating this as closed.

3 macOS: building the .dmg

3.1 Prerequisites

- Xcode command-line tools (provides `sips`, `iconutil`, `codesign`, `hdiutil`).
- Qt 6 with the Svg module; Homebrew’s `brew install qt` puts it at `/opt/homebrew/opt/qt`.
- CMake $\geq$ 3.21.
- A Python virtualenv with ASE installed, e.g. the project `.venv` (`python3 -m venv .venv` $\hookrightarrow$ `&& .venv/bin/pip install ase`).

3.2 Commands

The supported one-shot route is the driver script, which provisions the relocatable Python payload, builds, packages, and mounts the finished image to prove the shipped app can import ASE:

```
packaging/macos/build_dmg.sh
```

It also picks the build directory for you, which matters — see the warning below. To drive the steps by hand instead, from the repository root:

```
BUILD=~/.Library/Caches/calango/build-dmg

cmake -S . -B $BUILD \
  -DCMAKE_BUILD_TYPE=Release \
  -DPython3_EXECUTABLE=$PWD/.venv/bin/python \
  -DCMAKE_PREFIX_PATH=/opt/homebrew/opt/qt \
  -DCALANGO_MACOS_BUNDLE=ON

cmake --build $BUILD -j 8

cd $BUILD && cpack
```

The staging tree must not be cloud-synced. A file provider (Dropbox, iCloud Drive, OneDrive, Google Drive) stamps its own extended attributes on every file it manages, and re-applies them faster than they can be cleared. `codesign` rejects those as “*resource fork, Finder information, or similar detritus*”. Since the checkout itself lives in Dropbox on this machine, a build directory named relative to it (`build-dmg`) puts `_CPack_Packages/` inside the synced tree, and the run fails at the very last step — after the full build, `macdeployqt` and the Python embed — with

```
calango.app: resource fork, Finder information, or similar detritus not allowed
error: calango.app fails strict signature validation
```

The fix is to stage outside the synced folder, as above. `build_dmg.sh` does this automatically: a `BUILD_DIR` you set yourself is refused with an explanation, and the default is relocated to `~/Library/Caches/calango/` with a notice. An already built tree does not need reconfiguring — `cpack -B` moves only the staging directory and the output:

```
cd build-dmg && cpack -G DragNDrop -B ~/Library/Caches/calango/cpack-stage
```

A finished `.dmg` is a single signed file that syncing cannot spoil, so only the staging tree has to move.

3.3 The resulting image

The result is `calango-<version>-macos-arm64.dmg`. Mounting it shows `calango.app` next to an `/Applications` symlink — the standard drag-to-install layout. There is deliberately no click-through license sheet (`CPACK_DMG_SL_A_USE_RESOURCE_FILE_LICENSE OFF`): a license SLA blocks scripted `hdiutil attach` and adds friction for an MIT-licensed application.

3.4 Cleaning up afterwards

The scratch tree is several GB — a Release build of the application, the CPack staging copy of the bundle, and the provisioned Python payload — and every byte of it is reproducible. `build_dmg.sh` therefore deletes it as its last step, once the image has been built, mounted and probed:

```
==> SUCCESS
Artifact : /path/to/repo/installers/calango_<version>_macOS.dmg
Checksum : /path/to/repo/installers/calango_<version>_macOS.dmg.sha256
Size      : 65M
Verified  : valid macOS disk image (hdiutil imageinfo)
Probe     : python: 3.14.6 ase: 3.29.0
Cleaned   : ~/Library/Caches/calango/macos-bundle-a1b2c3d4 (freed 3.4G)
           next run re-provisions the embedded Python; --keep-cache avoids that
```

Three properties of that step are deliberate:

- **It runs last, and only on success.** A run that failed anywhere keeps its tree, because that tree is exactly what is needed to diagnose the failure.
- **It deletes the per-checkout subdirectory, not the root.** The scratch directory is keyed by the repository's path (`macos-bundle-<hash>`) so that several checkouts can coexist; removing `~/Library/Caches/calango` wholesale would take another checkout's cache with it. The root itself is then removed only if it is left empty.
- **It only ever deletes inside that root.** A `BUILD_DIR` pointing anywhere else is reported and kept — it may be a working build directory that predates the packaging run.

Pass `-keep-cache` while iterating on packaging itself. The tree caches the ~500 MB embedded-Python payload, so a kept tree makes the following run skip the download and reuse the compiled objects as well. Cleaning up by hand after a manual `cpack` is the same idea:

```
rm -rf ~/Library/Caches/calango/cpack-stage
```

3.5 What the install step does

cpack internally runs the CMake install rules into a staging directory (`_CPack_Packages/`) and then wraps the result in a disk image. The install rules perform, in order:

1. **Stage the bundle.** `calango.app` is installed with the Finder icon (`calango.icns`, committed or rendered at build time by `make_icns.sh`) and the `Info.plist` metadata (bundle id `org.seixasresearch.calango`).
2. **Optionally embed a Python environment** into `Contents/Resources/python`, when the cache variable `CALANGO_EMBEDDED_PYTHON_DIR` is set (Section 5).
3. **Deploy Qt with `macdeployqt` — twice.** The tool copies the Qt frameworks and plugins into the bundle and rewrites their load paths to `@executable_path`. Two passes with `-libpath=/opt/homebrew/opt/qt/lib` are required: frameworks copied into the bundle lose the `@loader_path` context their `@rpath` dependencies resolve against, so transitive dependencies (e.g. `QtGui` → `QtDBus`, plugin dependencies) are only found when the second pass re-scans the already-copied frameworks. The first pass prints a wall of `ERROR: Cannot resolve rpath` lines — this is expected noise; judge success by the verification steps below.
4. **Embed the linked Python.framework.** `embed_python_framework.sh` copies the framework version the binary links against (typically Homebrew’s) into `Contents/Frameworks`, replaces Homebrew’s dangling `site-packages` symlink with a real directory, recreates the canonical framework symlinks, retargets the load command with `install_name_tool`, and finally re-signs the whole bundle ad hoc (`codesign --force --deep --sign -`). Without the re-sign, Apple-silicon macOS refuses to load the modified binaries.

3.6 File associations

`packaging/macos/Info.plist.in` declares document types for every format Calango reads that has a real, associable filename extension: a `CFBundleDocumentTypes` entry and a matching `UTExportedTypeDeclarations` entry each — 13 pairs, split across two tiers:

Tier	LSHandlerRank	What
Owner	Owner	<code>.calproj</code> — Calango’s own project format
Alternate	Default / Alternate	<code>.extxyz</code> (Default), <code>.xyz</code> , <code>.cif</code> , <code>.vasp</code> , <code>.traj</code> , <code>.pwi</code> , <code>.lammstrj</code> , <code>.gjf</code> , <code>.res</code> , <code>.cube</code> , <code>.xsf</code> , <code>.h5/.hdf5</code> (all Alternate)

Alternate adds Calango to Finder’s “Open With” menu for a format without taking over the user’s existing default handler — every one of these is a community/scientific format other applications (VESTA, OVITO, Avogadro, Mercury, ...) also read. `.calproj` is the only format Calango defines, so it alone claims **Owner**.

Two things are deliberately *not* declared. **Extension-less filenames** — Launch Services associates by extension or UTI, never by exact basename, so `POSCAR/CONTCAR` and the VASP volumetric family (`CHGCAR/LOCPOT/PARCHG/ELFCAR`) cannot be double-click-associated at all; `.vasp` and `.cube` cover the extension case of the same two formats, and these still open fine through the Open dialog, a CLI argument, or drag-and-drop. **Extensions too generic to claim system-wide** — `.in`, `.out`, `.data`, `.dump`, `.cell`, `.com`, `.json`, `.dat`, `.top` — even though `src/gui/FileOpenRouting.hpp` still maps several of them to an explicit ASE format hint when Calango opens them itself; declaring them in `LSItemContentTypes` would put Calango in “Open With” for large numbers of files that are not its concern.

No established system or community UTI was found to *import* for any of these formats (checked specifically for HDF5, since `.h5/.hdf5` are generic containers Calango does not own), so every UTI

is Calango’s own `org.seixasresearch.calango.*`, declared via `UTExportedTypeDeclarations`. Four reuse a real chemical-MIME-type convention for `public.mime-type` — `chemical/x-xyz`, `chemical/x-cif`, `chemical/x-gaussian-input` and `chemical/x-gaussian-cube`; the rest get an `application/x-*` string of Calango’s own.

Installing by dragging the `.app` out of the `.dmg` registers the bundle with Launch Services automatically, no separate step needed. Verified directly against exactly this ad-hoc-signed, unnotarized build:

```
LSREGISTER=/System/Library/Frameworks/CoreServices.framework/Versions/A/\
Frameworks/LaunchServices.framework/Versions/A/Support/lsregister

codesign --force --deep --sign - calango.app
"$LSREGISTER" -f calango.app
"$LSREGISTER" -dump | grep -A2 'claimed UTIs'
```

All 13 UTIs came back in `claimed UTIs:`, each with the right extension/MIME tag. **Caveat:** a freshly registered, unnotarized bundle carries a `launch-disabled` flag until Gatekeeper approves it — the document *associations* appear in “Open With” immediately, but Finder may still need the one-time right-click → Open approval (or an ordinary first launch of the app) before it will actually run Calango for a double-clicked document.

On the application side, `calango::CalangoApplication` (`src/CalangoApplication.hpp`) intercepts `QFileOpenEvent` — the Apple Event Qt surfaces for a double-click, “Open With”, a Dock drop, or (one event per file) several files opened together — and routes each path to `MainWindow::loadFile`, exactly like a CLI argument, so each file opens in its own tab. An event arriving before `MainWindow` exists (the normal case on a cold Finder launch) is queued (`src/FileOpenQueue.hpp`) and replayed once the window is attached. `loadFile` itself decides project vs. structure and picks the ASE format hint (`src/gui/FileOpenRouting.hpp`) — the same routing used for the Open dialog, so format detection, error dialogs and recent-files behave identically regardless of how the file arrived.

3.7 Verification

```
APP=_CPack_Packages/Darwin/DragNDrop/calango-<version>-macos-arm64/calango.app

# 1. Signature must verify strictly, including nested code
codesign --verify --deep --strict "$APP"

# 2. The packaged binary must start and find a Python with ASE
"$APP/Contents/MacOS/calango" --probe-python

# 3. The image must mount without an SLA prompt
hdiutil attach -readonly -nobrowse calango-<version>-macos-arm64.dmg
```

To rebuild the package from a clean state, clear the staging area first with `cmake -E rm -rf ↪ _CPack_Packages` — stale staging can mask deployment bugs. `build_dmg.sh` additionally runs `audit_macho_deps.py` over the finished image and fails the build on a build-machine load path (Section 2).

4 Linux: building the .deb

4.1 Prerequisites (Ubuntu/Debian)


```
sudo apt install build-essential cmake ninja-build \
  qt6-base-dev libqt6svg6-dev libqt6opengl6-dev \
  libgl1-mesa-dev python3-dev python3-venv \
  dpkg-dev file
```

`dpkg-dev` provides `dpkg-shlibdeps`, which `CPack` uses to compute the runtime `Depends:` line automatically (`CPACK_DEBIAN_PACKAGE_SHLIBDEPS ON`).

Build against the system Python, not Conda/Homebrew. The `.deb` must link the distribution's `libpython` (`/usr/lib/.../libpython3.x.so.1.0`, owned by the `libpython3.x` package) so that `dpkg-shlibdeps` can resolve it into a proper `Depends:` line. If `CMake` is pointed at a Conda or Homebrew interpreter, the binary links a `libpython` under `$HOME` that `dpkg-shlibdeps` cannot find — packaging fails with `dpkg-shlibdeps: error: cannot find library` — and the resulting package would not be installable on other machines anyway. `python3-dev` installs the system interpreter and its `libpython`; configure against `/usr/bin/python3` (Section 4.2). `ASE` is only a runtime `Recommends` (`apt install python3-ase`); it is not needed to build the package.

4.2 Commands

Configure a *fresh*, Linux-native build directory — never reuse a tree configured on another machine or OS (see the note below) — and point `CMake` at the system interpreter:

```
cmake -S . -B build-deb \
  -DCMAKE_BUILD_TYPE=Release \
  -DPython3_EXECUTABLE=/usr/bin/python3

cmake --build build-deb -j$(nproc)

cd build-deb && cpack
```

Do not run `cpack` in a build directory copied from another host. Cloud-synced check-outs (Dropbox) carry the macOS `build/` tree along with the source. Its `CMakeCache.txt` and `CPackConfig.cmake` bake in absolute macOS tool paths, so a Linux `cpack` there fails with `CPack Error: Cannot find description file name: [/opt/homebrew/share/cmake/Templates/...]`. A separate `build-deb` directory, configured by the Linux `cmake`, avoids this entirely.

The result is `calango_26.8.36_<arch>.deb`. Install it via `apt` rather than `dpkg -i`, so the dependencies are resolved:

```
sudo apt install ./calango_<version>_amd64.deb
```

4.3 Package contents and desktop integration

Path in package	Purpose
<code>/usr/bin/calango</code>	The application binary
<code>/usr/share/applications/calango.desktop</code>	Launcher entry (<code>Exec=calango %F</code>)
<code>/usr/share/mime/packages/calango-mime.xml</code>	MIME types for <code>.calproj</code> and 12 other readable formats
<code>/usr/share/pixmaps/calango.png</code>	Application icon (resolves the <code>.desktop Icon=calango</code> lookup)
<code>/usr/lib/calango/python/</code>	Embedded Python (optional, see Section 5)

The MIME registration means double-clicking a `.calproj` workspace, or one of the 12 other associated formats (the same Alternate-tier list as the macOS `Info.plist`, Section 3.6), in the file manager opens it in Calango; `MainWindow::loadFile` routes `.calproj` arguments to the project loader and everything else through the ASE structure reader, picking a format hint (`src/gui/FileOpenRouting.hpp`) when the extension alone is ambiguous. The declarations in `calango-mime.xml` are self-contained rather than assuming the optional `chemical-mime-data` package is installed, so the association resolves even on a system that never installed it. The `postinst/postrm` maintainer scripts refresh `update-mime-database`, `update-desktop-database` and `gtk-update-icon-cache` so the association is live immediately after install (modern `dpkg` triggers usually do this anyway; the scripts make it robust on minimal systems).

Unless an embedded Python is bundled, the package declares `Depends: python3 (>= 3.9)` and `Recommends: python3-ase`. Without ASE the GUI starts but structure I/O and job submission are disabled; users can also point Calango at any interpreter via `CALANGO_PYTHON`.

4.4 Verification

```
dpkg-deb --info calango_<version>_amd64.deb # control fields, Depends
dpkg-deb --contents calango_<version>_amd64.deb

# after installing:
calango --probe-python
xdg-mime query default application/x-calango-project
```

Status note: the DEB pipeline has been built and verified end-to-end on Ubuntu (`dpkg-deb -info` shows the auto-computed `Depends:`, including `libpython3.12t64` and the Qt 6 runtime libraries). Running it in CI on a clean Ubuntu 22.04/24.04 image remains worthwhile to catch host-specific assumptions. `build_deb.sh` additionally runs `audit_elf_deps.py` over the finished `.deb` and fails the build if any shipped ELF needs a library the control file does not declare (Section 2) — the check that would have caught calango 26.8.36’s undeclared MKL link before it shipped.

5 The embedded Python environment

Calango embeds CPython at runtime. The interpreter is resolved in this order (documented in `src/python_bridge/PythonEngine.hpp`):

1. `$CALANGO_PYTHON` — explicit interpreter path;
2. `$VIRTUAL_ENV/bin/python` — active virtualenv;
3. a Python bundled by the installers: `Contents/Resources/python/bin/python3` (macOS) or `<prefix>/lib/calango/python/bin/python3` (Linux);
4. the interpreter CMake was configured against (`CALANGO_DEFAULT_PYTHON`, meaningful only on the build machine).

To ship a fully self-contained installer, pass a *relocatable* Python distribution that has ASE installed:

```
cmake -S . -B $BUILD ... \
  -DCALANGO_EMBEDDED_PYTHON_DIR=/path/to/standalone-python
```

A distribution from the `python-build-standalone` project is the recommended source. A plain project `.venv` is *not* relocatable — its `bin/python` and `pyvenv.cfg` refer back to the build machine's base interpreter.

`build_dmg.sh` does all of this for you when the variable is unset. It downloads a matching `python-build-standalone` tree, pip-installs `CALANGO_EMBEDDED_PACKAGES` into it, and caches the result in the build directory. Skipping this is what separates a `.dmg` that only runs on the build machine from a shippable one — the app still launches either way, it just cannot import ASE — and the mount-and-probe check at the end of the script is what tells the two apart.

Independent of this option, the macOS pipeline always embeds the `Python.framework` that the binary itself links against (`libpython` via `Development.Embed`), so the packaged app launches on machines without Homebrew. For the interpreter to also find ASE there, either bundle an environment as above or let users install ASE and set `CALANGO_PYTHON`.

6 Known limitations and next steps

- **Code signing:** the `.app` is signed ad hoc. Distribution outside a lab requires a Developer ID certificate and notarization (`codesign -sign "Developer ID..."`, `notarytool submit`, `stapler`); the ad-hoc step in `embed_python_framework.sh` is the place to swap the identity in.
- **DEB validation:** run the Linux pipeline once in CI (Ubuntu 22.04/24.04) and consider `lintian` for policy checks.
- **Full ASE bundling:** wiring a `python-build-standalone` + ASE tree into both installers (and building against its `libpython`) would remove the last runtime dependency on a user-provided Python.