In an operating system three CPU-intensive processes are ready for execution, which require 10ns, 20ns and 30ns and arrival at times 0ns, 2ns and 6ns, respectively. Write a Program to calculate the total number of context switches needed if the operating system implements a shortest job first (preemptive) scheduling algorithm. Also calculate the average time for which the processes have to wait before getting the CPU.

/c/Users/nehaa/OneDrive/Documents/Desktop/OS_CD24047

GNU nano 8.7 sjf_prim.c Modified

```c
#include <stdio.h>

int main() {
    int n = 3;
    int at[3] = {0, 2, 6};      // Arrival times
    int bt[3] = {10, 20, 30};  // Burst times
    int rt[3];                 // Remaining times
    int wt[3] = {0};
    int ct[3];

    int time = 0, completed = 0;
    int prev = -1;
    int context_switch = 0;

    for (int i = 0; i < n; i++)
        rt[i] = bt[i];

    while (completed < n) {
        int shortest = -1;
        int min_rt = 9999;

        for (int i = 0; i < n; i++) {
            if (at[i] <= time && rt[i] > 0 && rt[i] < min_rt) {
                min_rt = rt[i];
                shortest = i;
            }
        }

        if (shortest == -1) {
            time++;
            continue;
        }

        if (prev != shortest && prev != -1)
            context_switch++;

        prev = shortest;
        rt[shortest]--;
        time++;

        if (rt[shortest] == 0) {
            completed++;
            ct[shortest] = time;
            wt[shortest] = ct[shortest] - at[shortest] - bt[shortest];
        }
    }

    float avg_wt = 0;
    printf("\nProcess\tAT\tBT\tWT\n");
    for (int i = 0; i < n; i++) {
        avg_wt += wt[i];
        printf("P%d\t%d\t%d\t%d\n", i + 1, at[i], bt[i], wt[i]);
    }

    printf("\nTotal Context Switches = %d", context_switch);
    printf("\nAverage Waiting Time = %.2f ns\n", avg_wt / n);

    return 0;
}
```

^G Help ^O Write Out ^F Where Is ^K Cut ^T Execute ^C Location M-U Undo M-A Set Mark M-] To Bracket M-B Previous ^B Back ^A Prev Word ^A Home
^X Exit ^R Read File ^\ Replace ^U Paste ^J Justify ^/ Go To Line M-E Redo M-6 Copy ^Q Where Was M-F Next ^F Forward ^W Next Word ^E End

Trending videos The Muppet Sho... Search ENG IN 18:19 31-01-2026

/c/Users/nehaa/OneDrive/Documents/Desktop/OS_CD24047

```
nehaa@NEHA MSYS /c/Users/nehaa/OneDrive/Documents/Desktop/OS_CD24047
$ nano sjf_prim.c

nehaa@NEHA MSYS /c/Users/nehaa/OneDrive/Documents/Desktop/OS_CD24047
$ gcc sjf_prim.c -o sjf_prim

nehaa@NEHA MSYS /c/Users/nehaa/OneDrive/Documents/Desktop/OS_CD24047
$ ./sjf
-bash: ./sjf: No such file or directory

nehaa@NEHA MSYS /c/Users/nehaa/OneDrive/Documents/Desktop/OS_CD24047
$ ./sjf_prim

Process AT      BT      WT
P1      0       10      0
P2      2       20      8
P3      6       30      24

Total Context Switches = 2
Average Waiting Time = 10.67 ns

nehaa@NEHA MSYS /c/Users/nehaa/OneDrive/Documents/Desktop/OS_CD24047
$ |
```