

JQUERY

- Add-on library written in Javascript
- Go to www.jquery.com to download or use CDN (better)
- Reference the library as an *external Javascript* source file
- JQuery
 - Uses `$()` notation
 - Object oriented
 - Alternate way to
 - Attach events
 - Update content
 - Special F/X

37

SELECTING PAGE ELEMENTS

- id `$('#name')`
- Tag `$('tag')`
`$('tag:even')` also `('tag:odd')`
- Class name `$('.className')`
- Tag with class `$('span.error')`
- Child of tag `$('ul>li')` only `` within ``
- Child of id `$($('#navbar a'))` only links within navbar
- Adjacent tags `$('h2 + p')` only `<p>` after `<h2>`
- Attributes `$('p[align]')`
`$('p[align=center]')` match attr value
`$('a[href=http://]')` starts with `http://`
`$('a[href=.pdf]')` ends with `.pdf`
`$('a[href*=sitetx]')` sitex is anywhere

38

ATTACHING EVENTS

- Assign event handlers using the selector notation along with the event name
 - `$('#menu1').mouseover(func);`
 - `$('#menu1').bind('mouseover',func);`
 - `$('#menu1').mouseover(function() { });`
- Example:


```
$('#menu1').mouseover(function() {
  $('#submenu').show();
});
```

39

FREQUENTLY USED EVENTS

- click `dblclick`
- mouseenter `mouseleave`
- keypress `keyup`
- focus `blur`
- hover `toggle`
- submit
- load
- resize

40

PAGE LOAD EVENT

- Replace `window.onload` with `$(document).ready`

```
$(document).ready (function()
{
})
```

41

EXAMPLE

Problem: Detect when a button is pressed and display a message on the page

- The HTML

```
<body>
<div id="button1">Press Me</div>
<div id="message1">&nbsp;</div>
</body>
```

42

EXAMPLE JQUERY, CONTINUED

- The CSS:

```
#button1 {
font-family:Arial, Helvetica, sans-serif; font-size: 36px; font-weight: bold;
text-align: center; line-height: 220px; color: #777777;
width: 210px; height: 220px; margin-bottom: 20px;
background-color: #2A00FF;
}
#button1:hover { opacity:.5; }
#message1 {font-size: 20px;}
#message1.showme {
background-color: #ECEA34; padding: 6px 8px; display:inline-block;
}
```

43

EXAMPLE JQUERY, CONTINUED

- jQuery code:

```
<script language="javascript">
$(document).ready (
function ()
{
$("#button1").click(function(e) {
$("#message1").html("That tickles!");
$("#message1").addClass("showme");
});
});
</script>
```

44

CHANGING PAGE CONTENT

- .html
 - \$('#err_name').html ("Must provide your name");
- .append .prepend
- .after .before
- .attr
 - \$('#slides img').attr('src','slide2.jpg');
- .removeAttr

45

CHANGING STYLING

- .addClass
 - \$('img').addClass('myborder');
- .removeClass
- .toggleClass
- .css
 - \$('body').css('font-size','24pt');
 - \$('body').css(
 {
 'font-size': '24pt',
 'color': '#00ff00'
 }
);

46

“LOOPING”

- Lists of objects with .each
 - \$('a').each will apply to all <a> tags
- Example:


```

$('a').each ( function() {
  theLink = $(this).attr('href');
  alert("Found a link! " + theLink);
});
      
```

47

VISIBILITY & ANIMATION

- | | |
|---|-----------------------------------|
| ■ .hide | ■ .slideDown |
| ■ \$(selector).hide(speed,callback) | ■ .slideUp |
| ■ .show | ■ .slideToggle |
| ■ \$(selector).show(speed,callback) | (down if hidden, up if displayed) |
| ■ .fadeIn | |
| ■ .fadeOut | |
| ■ fadeTo | |
| ■ \$(selector).fadeTo(speed,opacity,callback) | |

48