

Platform Veteran Badge API

Deployed Edge Function:

1. platform-veteran

Authentication Flow:

1. Call your login/client-auth flow and copy the access_token.
2. Pass that token to platform-veteran in the Authorization header as Bearer <access_token>.
3. Keep [apikey](#) in the headers for the request.
4. The function also requires [Content-Type: application/json](#).

platform-veteran Request:

Method: POST

Endpoint:

<https://oycqlrxnmlwxkpcfwehx.functions.supabase.co/platform-veteran>

Headers:

- Content-Type: application/json
- apikey: <SUPABASE_ANON_KEY>
- Authorization: Bearer <access_token>

Body example:

```
{
  "mode": "sync",
  "worker_ids": ["1a44e832-1984-4bf5-91bb-6afd3262ded7"]
}
```

Expected Success Response:

```
{
  "success": true,
  "mode": "preview",
  "processed_workers": 1,
  "eligible_workers": 1,
  "results": [
    {
      "worker_id": "1a44e832-1984-4bf5-91bb-6afd3262ded7",
      "worker_name": "aanya.sharma@dataalchemy.ai",
      "active_months": 6,
      "total_jobs_completed": 10,
      "badge_name": "Silver Veteran",
      "badge_tier": "Silver Veteran",
      "badge_slug": "platform-veteran-silver",
      "eligible": true
    }
  ]
}
```

Expected Ineligible Response:

```
{
  "success": true,
  "mode": "preview",
  "processed_workers": 1,
  "eligible_workers": 0,
  "results": [
    {
      "worker_id": "1a44e832-1984-4bf5-91bb-6afd3262ded7",
      "worker_name": "aanya.sharma@dataalchemy.ai",
      "active_months": 0,

```

```
        "total_jobs_completed": 10,
"badge_name": null,
        "badge_tier": null,
        "badge_slug": null,
        "eligible": false,
        "reason": "Account age below veteran threshold"
    }
]
}
```