```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ docker --version
Docker version 29.8.0, build 88096ef
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl version --client
Client Version: v1.36.1
Kustomize Version: v5.8.1
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ minikube version
minikube version: v1.39.0
commit: 7a9f6a841470a207de8cf4bafcccee0969d8ba10
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ minikube status
minikube
type: Control Plane
host: Running
kubelet: Running
apiserver: Running
kubeconfig: Configured

sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl get nodes
NAME       STATUS   ROLES           AGE   VERSION
minikube   Ready    control-plane   18m   v1.37.0
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl get podes
error: the server doesn't have a resource type "podes"
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl get pods
No resources found in default namespace.
```

```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar$ git clone https://github.com/sejalshinkar904/student-task-manager.git
Cloning into 'student-task-manager'...
remote: Enumerating objects: 23, done.
remote: Counting objects: 100% (23/23), done.
remote: Compressing objects: 100% (19/19), done.
remote: Total 23 (delta 6), reused 18 (delta 3), pack-reused 0 (from 0)
Receiving objects: 100% (23/23), 5.53 KiB | 472.00 KiB/s, done.
Resolving deltas: 100% (6/6), done.
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar$ cd student-task-manager
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ nano .dockerignore
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ nano dockerfile
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ cat .dockerignore
.git
.gitignore
node_modules
README.md

sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ cat dockerfile
FROM nginx:alpine
COPY index.html usr/share/nginx/html
COPY script.js usr/share/nginx/html
COPY style.css usr/share/nginx/html
EXPOSE 80
```

```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ docker build -t task-manager:1.0 .
[+] Building 11.0s (10/10) FINISHED                                                
```

```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ minikube image load task-manager:1.0
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ minikube image ls | grep task-manager
docker.io/library/task-manager:1.0
```

```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ nano deployment.yaml
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ cat deployment.yaml
apiVersion: apps/v1
kind: Deployment
metadata:
  name: task-manager
spec:
  replicas: 2
  selector:
    matchLabels:
      app: task-manager
  template:
    metadata:
      labels:
        app: task-manager
    spec:
      containers:
        - name: task-manager
          image: task-manager:1.0
          imagePullPolicy: IfNotPresent
          ports:
            - containerPort: 80
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl apply -f deployment.yaml
deployment.apps/task-manager created
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl get deployments
NAME           READY   UP-TO-DATE   AVAILABLE   AGE
task-manager   2/2     2            2           16s
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl get pods
NAME                           READY   STATUS    RESTARTS   AGE
task-manager-77c55fc459-m9kfs   1/1     Running   0          27s
task-manager-77c55fc459-ngmqp   1/1     Running   0          27s
```


```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ nano service.yaml
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ cat service.yaml
apiVersion: v1
kind: Service
metadata:
  name: task-manager-service
spec:
  type: NodePort
  selector:
    app: task-manager
  ports:
    - port: 80
      targetPort: 80
      nodePort: 30080
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl apply -f service.yaml
service/task-manager-service created
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ kubectl get services
NAME                   TYPE        CLUSTER-IP      EXTERNAL-IP   PORT(S)        AGE
kubernetes             ClusterIP   10.96.0.1       <none>        443/TCP        26m
task-manager-service   NodePort    10.107.15.83    <none>        80:30080/TCP   14s
```

```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar/student-task-manager$ minikube service task-manager-service
```

NAMESPACE	NAME	TARGET PORT	URL
default	task-manager-service	80	http://192.168.49.2:30080

```
🔗  Starting tunnel for service task-manager-service.
```

NAMESPACE	NAME	TARGET PORT	URL
default	task-manager-service		http://127.0.0.1:37895




```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar$ kubectl get all
NAME                                    READY   STATUS    RESTARTS   AGE
pod/task-manager-77c55fc459-m9kfs       1/1     Running   0          9m24s
pod/task-manager-77c55fc459-ngmqp       1/1     Running   0          9m24s

NAME                              TYPE        CLUSTER-IP      EXTERNAL-IP   PORT(S)        AGE
service/kubernetes                ClusterIP   10.96.0.1       <none>        443/TCP        33m
service/task-manager-service      NodePort    10.107.15.83    <none>        80:30080/TCP   6m45s

NAME                              READY   UP-TO-DATE   AVAILABLE   AGE
deployment.apps/task-manager      2/2     2            2           9m25s

NAME                                         DESIRED   CURRENT   READY   AGE
replicaset.apps/task-manager-77c55fc459      2         2         2       9m25s
```

```
sejalshinkar@SEJAL25:/mnt/c/Users/Sejal Anil Shinkar$ minikube status
minikube
type: Control Plane
host: Running
kubelet: Running
apiserver: Running
kubeconfig: Configured
```