

How to open a file from a terminal emulator

Katsutoshi Seki | Published: May 5, 2017 | Source: <https://sekika.github.io/2017/05/05/open-command/>

This article describes how to open a file from a [terminal emulator](#) in Mac , Linux, and Windows.

1. Mac (macOS)

Use `open` command in [Terminal](#). By running

```
open Readme.txt
```

`Readme.txt` opens with an application associated with `Readme.txt`. URL can be specified. For example,

```
open http://google.com
```

opens Google website with your default web browser. A directory can also be specified. For example,

```
open .
```

opens current directly in Finder.

Sometimes you may want to open a file with a program which is different from the associated one, for example, when you want to edit html file with a text editor. By using `-t` option, you can open a file with a default text editor.

```
open -t filename
```

You can also open a file with a specified application by using `-a` option.

You can make a shell script to open a file with your favorite text editor. For example, to open a file with [Brackets](#), make a text file `br` like this,

```
#!/bin/sh
open $1 -a /Applications/Brackets.app
```

make it executable (`chmod +x br`) and put in your path (check it by `echo $PATH`). Then you can use the `br` command as

```
br filename
```

Following help is shown by `open --help`.

Usage: `open [-e] [-t] [-f] [-W] [-R] [-n] [-g] [-h] [-s <partial SDK name>] [-b <bundle identifier>] [-a <application>] [filenames] [--args arguments]`

Help: `Open` opens files from a shell.

By default, opens each file using the default application for that file.

If the file is in the form of a URL, the file will be opened as a URL.

Options:

- `-a` Opens with the specified application.
- `-b` Opens with the specified application bundle identifier.
- `-e` Opens with TextEdit.
- `-t` Opens with default text editor.
- `-f` Reads input from standard input and opens with TextEdit.
- `-F --fresh` Launches the app fresh, that is, without restoring windows.

Saved persistent state is lost, excluding Untitled documents.

- `-R, --reveal` Selects in the Finder instead of opening.
- `-W, --wait-apps` Blocks until the used applications are closed (even if they were already running).
- `--args` All remaining arguments are passed in `argv` to the application's `main()` function instead of opened.

- `-n, --new` Open a new instance of the application even if one is already running.
- `-j, --hide` Launches the app hidden.
- `-g, --background` Does not bring the application to the foreground.
- `-h, --header` Searches header file locations for headers matching the given filenames, and opens them.
- `-s` For `-h`, the SDK to use; if supplied, only SDKs whose names contain the argument value are searched. Otherwise the highest versioned SDK in each platform is used.

With `cdto` you can add a toolbar in the Finder to open the current directory in the Terminal.

2. Linux

`xdg-open` can be used to open a file with default applications. `xdg-open` is a part of [xdg-utils](#).

- [xdg-open\(1\) - Linux man page](#)

This command is a little bit too long to type, and therefore you may want to create alias such as

```
alias open=xdg-open
```

in `.bashrc`. In Gnome, `gnome-open` is also available.

- [gnome-open](#) - manual page at Ubuntu xenial

3. Windows

`start` command can be executed from [command prompt](#), and `Invoke-Item` command is used for [PowerShell](#). See following documents by Microsoft for detail.

- [start](#)

- [Invoke-Item](#)