Bahir Dar universty

Faculty of computing

Department of software engineering

OSSP_ Indivisual Assignment

Title_ Alpine Linux Os

Name:Selam Agegn
Section:B
Id:1702581

Submitted to Mr.Wendmu

Submission date April 20, 2018 Ec

Table of Contents

1. **Introduction**
2. **Objective**
3. **Requirement**
   - 3.1 Hardware Requirements
   - 3.2 Software Requirements
4. **Installation of Alpine Linux on** Oracle VirtualBox
   - Step 1: Install VirtualBox
   - Step 2: Download Alpine Linux
   - Step 3: Create Virtual Machine
   - Step 4: Configure Hardware Resources
   - Step 5: Start Virtual Machine
   - Step 6: Boot Alpine Linux
   - Step 7: Login & Start Installation
   - Step 8: Configure Basic Settings
   - Step 9: Security & Localization
   - Step 10: Additional Features
   - Step 11: Install to Disk
   - Step 12: Reboot System
   - Step 13: Verify Installation
5. **Issues Faced**
6. **Solutions**
7. **Filesystem Support**
8. **Advantages and Disadvantages**
9. **Conclusion**
10. **Future Outlook / Recommendations**
11. **Virtualization in Modern Operating Systems**
    - 11.1 What is Virtualization
    - 11.2 Why Virtualization
    - 11.3 How Virtualization Works
12. **System Call Implementation (**clock_gettime()**)**
    - 12.1 Description
    - 12.2 Purpose
    - 12.3 Alpine Linux Environment
13. **Final Conclusion**
14. **Acknowledgement**
15. **References**

1. Introduction

Alpine Linux is a lightweight, secure, and efficient Linux distribution designed to use minimal system resources while maintaining high performance. It is commonly used in virtual environments, servers, and container-based systems due to its small size and strong focus on security.

The purpose of this project is to install Alpine Linux in a virtual machine and gain practical experience in operating system setup and management. The process includes configuring system settings, managing packages, and working with the command-line interface. Unlike graphical operating systems, Alpine Linux provides a deeper understanding of how systems operate at a lower level.

Through this hands-on practice, I was able to develop skills in installation, system configuration, and basic administration tasks. This project also helps in understanding the real-world application of operating system concepts, improving both technical knowledge and problem-solving ability.

2. Objective

The main objective of this project is to install and configure Alpine Linux in a virtual environment and gain practical knowledge of operating system concepts.

It aims to develop hands-on skills in system installation, basic configuration, and command-line usage. Additionally, the project helps in understanding how a lightweight Linux system operates, how resources are managed, and how system administration tasks are performed.

Another objective is to build problem-solving ability by identifying and resolving issues encountered during the installation and setup process.

3.Requirement

A **requirement** is something that is **needed or necessary** for a particular purpose.

3.1 Hardware Requirements

To successfully install and run Alpine Linux in a virtual environment, the following hardware components are required:

- **Computer or Laptop:**
  A system capable of running virtualization software smoothly.
- **Processor (CPU):**
  A modern processor with virtualization support (such as Intel VT-x or AMD-V) is recommended to ensure efficient performance of the virtual machine.
- **Memory (RAM):**
  Minimum of **2 GB RAM** is required, but **4 GB or more is recommended** for better multitasking and smoother operation of both the host and virtual machine.

- **Storage (Hard Disk):**
  At least **10 GB of free disk space** is needed to install Alpine Linux and store additional packages and files.
- **Display and Input Devices:**
  A monitor, keyboard, and mouse are necessary for interacting with the system during installation and usage.

3.2 Software Requirements

The following software components are required to install and operate Alpine Linux:

- **Virtualization Software:**
  Tools such as VirtualBox or VMware are used to create and run a virtual machine where Alpine Linux will be installed.
- **Alpine Linux ISO File:**
  The official installation image of Alpine Linux, which is used to boot and install the operating system.
- **Host Operating System:**
  A working operating system (such as Windows, Linux, or macOS) is required to run the virtualization software.
- **Internet Connection:**
  Needed to download the ISO file, install additional packages, and update the system after installation.

Command-Line Interface Tools:

Since Alpine Linux is primarily command-line based, basic familiarity with terminal commands is important for system configuration and management.

Installation of Alpine Linux on Virtual-box (Detailed Explanation)

Step1:install oracle virtual box

Oracle Virtual_Box is a tool that lets me run different operating systems on one computer.
First, I downloaded it from the official website and ran the installer file.
I followed the setup wizard by clicking “Next” and keeping the default settings.
I allowed all required permissions and completed the installation process.
After installation, I opened Virtual_Box and created a virtual machine.
Then, I selected the operating system type and allocated memory and storage.
I attached an ISO file of the operating system I wanted to install.
Next, I started the virtual machine to begin the installation process.
Finally, I completed the OS installation inside Virtual_Box and started using it



Figure1.instillation of virtual box

Step 2:download alpine linux

Alpine Linux is a lightweight and efficient operating system suitable for virtual environments.
First, I visited the official Alpine Linux website to download the ISO file.
I selected the latest stable release to ensure better performance and security.
Then, I chose the **Standard ISO (x86_64)** version for installation.
I clicked the download link and saved the ISO file on my computer.
Since Alpine Linux is small in size, the download completed quickly.

After downloading, I checked that the file was properly saved.
This ISO file acts as a boot-able installation image.
Next, I opened Oracle Virtual-box to use this file.
I created a new virtual machine and selected Linux as the OS type.
Then, I attached the downloaded ISO file in the storage settings.
Finally, I started the virtual machine to begin installing Alpine Linux.



Figure2.downloading of alpine linux

Step 3: Create a Virtual Machine

To begin the installation, I created a new virtual machine using Virtual-box. I clicked on the “New” option and entered a suitable name such as *Alpine Linux OS*. Then, I selected Linux as the operating system type and chose the 64-bit version.

During this step, I also selected the Alpine Linux ISO file. This ISO file acts as the installation media, similar to a boot-able disk used to install an operating system on a physical computer



Figure3: Creating a virtual machine and attaching the Alpine Linux ISO file

Step 2: Configure Hardware Resources

After creating the virtual machine, I configured the hardware resources. I allocated memory (RAM), selected the number of processors, and created a virtual hard disk with sufficient storage space (around 8 GB).

This step is important because the performance of the virtual machine depends on how much memory and storage are assigned. Allocating too little may cause slow performance, while sufficient resources ensure smooth operation during installation.



Figure4*: Configuring memory, processor, and storage for the virtual machine.*

Step 3: Start the Virtual Machine

Once all configurations were completed, I started the virtual machine. The system began running and booted from the attached ISO file. At this stage, the virtual machine behaves like a real computer starting up.



Figure 5*: Starting the virtual machine and launching Alpine Linux.*

Step 4: Boot Alpine Linux

After starting the virtual machine, Alpine Linux began its boot process. The screen displayed several system initialization messages as the operating system loaded necessary services. After the boot process was complete, the system displayed the login prompt:

“localhost login”

This indicates that the system is ready for user interaction.



Figure6: Booting Alpine Linux and displaying the login prompt.

Step 5: Log in and Start Installation

At the login prompt, I entered the root user to gain administrative access. After logging in, I started the installation process by running the setup command. This command opens the Alpine Linux installation script, which guides the user through the configuration process step by step.

This step is important because it transitions the system from a temporary live environment into an actual installation process.



Figure7: Logging in as root and starting the installation process.

Step 6: Configure Basic System Settings

During this step, I configured essential system settings. The installer prompted me to select a keyboard layout, set a hostname for the system, and configure the network interface. The network was set up automatically using DHCP, which assigned an IP address.

These settings are important because they define how the system communicates and identifies itself on a network.



Figure8*: Configuring keyboard layout, hostname, and network settings.*

Step 7: Set Security and Localization Options

Next, I set a root password to secure the system. I also selected the appropriate time zone to ensure the system displays the correct date and time. Additionally, I configured the package repository by allowing the system to choose the fastest mirror for downloading software.

This step is important for both system security and proper functionality.





Figure9*: Setting root password, timezone, and package repository.*

Step 8: Configure Additional Features

The installer then prompted for additional configurations such as creating a user account and enabling SSH services. These options allow better system management and remote access if needed.

Although optional, these settings improve system usability and flexibility.





Figure10*: Configuring additional system features such as user accounts and SSH.*

Step 9: Install Alpine Linux to Disk

After completing all configurations, I proceeded to install Alpine Linux onto the virtual disk. I selected the available disk (sda), chose the installation type, and confirmed disk formatting.

The system then created file systems and copied necessary files to the disk. Once completed, it displayed a message indicating that the installation was successful.

```
Disk & Install
--------------
Available disks are:
  sda   (8.6 GB ATA      VBOX HARDDISK   )

Which disk(s) would you like to use? (or '?' for help or 'none') [none]
Enter where to store configs ('floppy', 'usb' or 'none') [none]
Enter apk cache directory (or '?' or 'none') [/var/cache/apk]
alpine-selam:~# root
-sh: root: not found
alpine-selam:~# sda
-sh: sda: not found
alpine-selam:~# setup-disk
Available disks are:
  sda   (8.6 GB ATA      VBOX HARDDISK   )

Which disk(s) would you like to use? (or '?' for help or 'none') [sda] sda

The following disk is selected:
  sda   (8.6 GB ATA      VBOX HARDDISK   )

How would you like to use it? ('sys', 'data', 'crypt', 'lvm' or '?' for help) [?] sys

WARNING: The following disk(s) will be erased:
  sda   (8.6 GB ATA      VBOX HARDDISK   )

WARNING: Erase the above disk(s) and continue? (y/n) [n] y
Creating file systems...
Installing system on /dev/sda3:
/mnt/boot is device /dev/sda1
* creating /boot/initramfs-lts for 6.18.22-0-lts
* /boot is device /dev/sda1

Installation is complete. Please reboot.
alpine-selam:~#
```

Figure11: Installing Alpine Linux onto the virtual disk.

Step 10: Reboot the System

After installation, I rebooted the system. This step is necessary for the system to start from the installed disk instead of the ISO file.

Upon reboot, the system again displayed the login prompt, confirming that the operating system was installed correctly.

```
boot:
[    0.124624] RDRAND is not reliable on this platform; disabling.


  OpenRC 0.63 is starting up Linux 6.18.7-0-lts (x86_64)

 * /proc is already mounted
 * Mounting /run ...                                                [ ok ]
 * /run/openrc: creating directory
 * /run/lock: creating directory
 * /run/lock: correcting owner
 * Caching service dependencies ...                                 [ ok ]
 * Remounting devtmpfs on /dev ...                                  [ ok ]
 * Mounting /dev/mqueue ...                                         [ ok ]
 * Mounting modloop  ...
 * Verifying modloop                                                [ ok ]
 * Mounting security filesystem ...                                 [ ok ]
 * Mounting debug filesystem ...                                    [ ok ]
 * Mounting trace filesystem ...                                    [ ok ]
 * Mounting persistent storage (pstore) filesystem ...              [ ok ]
 * Mounting bpf filesystem ...                                      [ ok ]
 * Starting busybox mdev ...                                        [ ok ]
 * Scanning hardware for mdev ...                                   [ ok ]
 * Loading hardware drivers ...                                                [ ok ]
 * Loading modules ...                                                         [ ok ]
 * Setting system clock using the hardware clock [UTC] ...                     [ ok ]
 * Checking local filesystems  ...                                             [ ok ]
 * Remounting filesystems ...                                                  [ ok ]
 * Mounting local filesystems ...                                              [ ok ]
 * Configuring kernel parameters ...                                           [ ok ]
 * Creating user login records ...                                             [ ok ]
 * Cleaning /tmp directory ...                                                 [ ok ]
 * Setting hostname to localhost from /etc/hostname ...                        [ ok ]
 * Starting busybox syslog ...                                                 [ ok ]
 * Starting firstboot ...                                                      [ ok ]

Welcome to Alpine Linux 3.23
Kernel 6.18.7-0-lts on x86_64 (/dev/tty1)

localhost login: _
```

figure12*: Rebooting the system after installation.*

Step 11: Verify Installation and System Functionality

Finally, I logged into the system again and performed basic checks. I updated the system packages and tested the network connection to ensure that everything was working correctly.

This step confirms that the installation process was successful and that the system is ready for

```
The Alpine Wiki contains a large amount of how-to guides and general
information about administrating Alpine systems.
See <https://wiki.alpinelinux.org/>.

You can setup the system with the command: setup-alpine

You may change this message by editing /etc/motd.

localhost:~# alpine-selam
-sh: alpine-selam: not found
localhost:~# apk update
3.23.3 [/media/cdrom/apks]
OK: 489 distinct packages available
localhost:~# selamagegn
-sh: selamagegn: not found
localhost:~# setup-apkrepos-f
-sh: setup-apkrepos-f: not found
localhost:~# setup-apkrepos -f
wget: bad address 'mirrors.alpinelinux.org'
Finding fastest mirror...
Warning! No mirror found
localhost:~# apk update
3.23.3 [/media/cdrom/apks]
OK: 489 distinct packages available
localhost:~# setup-interfaces
Available interfaces are: eth0.
Enter '?' for help on bridges, bonding and vlans.
Which one do you want to initialize? (or '?' or 'done') [eth0]
Ip address for eth0? (or 'dhcp', 'none', '?') [dhcp] dhcp
Do you want to do any manual network configuration? (y/n) [n] setup-apkrepos -1
Do you want to do any manual network configuration? (y/n) [n] setup--apkrepos -1
Do you want to do any manual network configuration? (y/n) [n]
localhost:~#
localhost:~# re-service networking start
-sh: re-service: not found
localhost:~# rc-service networking start
 * Starting networking ...
 *   lo ...
 *   eth0 ...
udhcpc: started, v1.37.0
udhcpc: broadcasting discover
udhcpc: broadcasting select for 10.0.2.15, server 10.0.2.2
udhcpc: lease of 10.0.2.15 obtained from 10.0.2.2, lease time 86400
localhost:~# ping -c 3 google.com
PING google.com (142.250.180.14): 56 data bytes

--- google.com ping statistics ---
3 packets transmitted, 0 packets received, 100% packet loss
localhost:~#
```

Network Configuration and System Setup in Linux Terminal

```
(100/376) Installing gtk-update-icon-cache (3.24.51-r0)
(101/376) Installing libxcursor (1.2.3-r0)
(102/376) Installing libxi (1.8.2-r0)
(103/376) Installing libxinerama (1.1.5-r4)
(104/376) Installing at-spi2-core-libs (2.58.3-r0)
(105/376) Installing gdbm (1.26-r0)
(106/376) Installing mpdecimal (4.0.1-r0)
(107/376) Installing libpanelw (6.5_p20251123-r0)
(108/376) Installing readline (8.3.1-r0)
(109/376) Installing sqlite-libs (3.51.2-r0)
(110/376) Installing python3 (3.12.13-r0)
(111/376) Installing python3-pycache-pyc0 (3.12.13-r0)
(112/376) Installing pyc (3.12.13-r0)
(113/376) Installing python3-pyc (3.12.13-r0)
(114/376) Installing libxtst (1.2.5-r0)
(115/376) Installing at-spi2-core (2.58.3-r0)
(116/376) Installing libatk-bridge-2.0 (2.58.3-r0)
(117/376) Installing avahi-libs (0.8-r23)
(118/376) Installing gmp (6.3.0-r4)
(119/376) Installing nettle (3.10.2-r0)
(120/376) Installing libunistring (1.4.1-r0)
(121/376) Installing libidn2 (2.3.8-r0)
(122/376) Installing libtasn1 (4.21.0-r0)
(123/376) Installing p11-kit (0.25.5-r2)
(124/376) Installing gnutls (3.8.12-r0)
(125/376) Installing cups-libs (2.4.16-r0)
(126/376) Installing libepoxy (1.5.10-r1)
(127/376) Installing fribidi (1.0.16-r2)
(128/376) Installing graphite2 (1.3.14-r6)
(129/376) Installing harfbuzz (12.2.0-r0)
(130/376) Installing libxft (2.3.9-r0)
(131/376) Installing pango (1.56.4-r0)
(132/376) Installing wayland-libs-cursor (1.24.0-r0)
(133/376) Installing wayland-libs-egl (1.24.0-r0)
(134/376) Installing xkeyboard-config (2.46-r0)
(135/376) Installing libxkbcommon (1.12.2-r0)
(136/376) Installing gtk+3.0 (3.24.51-r0)
(137/376) Installing icu-data-en (76.1-r1)
  Executing icu-data-en-76.1-r1.post-install
  *
  * If you need ICU with non-English locales and legacy charset support, install
  * package icu-data-full.
  *
(138/376) Installing icu-libs (76.1-r1)
(139/376) Installing nspr (4.36-r0)
(140/376) Installing nss (3.118.1-r0)
(141/376) Installing scudo-malloc (21.1.2-r0)
(142/376) Installing libwebpdemux (1.6.0-r0)
(143/376) Installing firefox (145.0-r0)
 53%
```

```
(348/376) Installing dbus-x11 (1.16.2-r1)
(349/376) Installing libproc2 (4.0.5-r0)
(350/376) Installing procps-ng (4.0.5-r0)
(351/376) Installing xfce4-session (4.20.2-r0)
(352/376) Installing xfce4-settings (4.20.1-r0)
(353/376) Installing yaml (0.2.5-r2)
(354/376) Installing xfdesktop (4.20.1-r0)
(355/376) Installing libxpresent (1.0.2-r0)
(356/376) Installing xfwm4 (4.20.0-r1)
(357/376) Installing xfce4 (4.20-r0)
(358/376) Installing libxscrnsaver (1.2.5-r0)
(359/376) Installing dbus-glib (0.114-r0)
(360/376) Installing xfce4-screensaver (4.18.4-r0)
(361/376) Installing py3-gobject3 (3.54.5-r0)
(362/376) Installing py3-gobject3-pyc (3.54.5-r0)
(363/376) Installing xfce4-screensaver-configure (4.18.4-r0)
(364/376) Installing vte3-profile (0.82.3-r1)
(365/376) Installing simdutf (7.5.0-r1)
(366/376) Installing vte3 (0.82.3-r1)
(367/376) Installing xfce4-terminal (1.1.3-r0)
(368/376) Installing font-alias (1.0.5-r0)
(369/376) Installing util-macros (1.20.2-r0)
(370/376) Installing font-cursor-misc (1.0.4-r1)
(371/376) Installing font-misc-misc (1.1.3-r1)
(372/376) Installing xkbcomp (1.5.0-r0)
(373/376) Installing xorg-server-common (21.1.22-r0)
(374/376) Installing libxfont2 (2.0.7-r0)
(375/376) Installing libxcvt (0.1.3-r0)
(376/376) Installing xorg-server (21.1.22-r0)
Executing busybox-1.37.0-r30.trigger
Executing dbus-1.16.2-r1.trigger
Executing eudev-3.2.14-r6.trigger
Executing glib-2.86.3-r0.trigger
Executing fontconfig-2.17.1-r0.trigger
Executing shared-mime-info-2.4-r6.trigger
Executing gdk-pixbuf-2.44.4-r0.trigger
Executing gtk-update-icon-cache-3.24.51-r0.trigger
Executing gtk+3.0-3.24.51-r0.trigger
Executing mkfontscale-1.2.3-r1.trigger
Executing ca-certificates-20260413-r0.trigger
Executing gvfs-1.58.2-r0.trigger
Executing desktop-file-utils-0.28-r0.trigger
1 error; 1009.2 MiB in 435 packages
 * Starting udev ...
 * Generating a rule to create a /dev/root symlink ...
 * Populating /dev with existing devices through uevents ...
 * Waiting for uevents to be processed ...
 * service lightdm added to runlevel default
 * service acpid deleted from runlevel default
/home/selamagegn # _
```

Package Installation Process in Linux Terminal



User Login Screen Interface

Linux Desktop Environment (Initial View)

Linux Desktop with Application Menu Open



Terminal Window in Desktop Environment

figure 13*: Verifying system functionality and testing network connectivity.*

Generally In this process, I successfully installed Alpine Linux on a virtual machine using VirtualBox. Each step, from creating the virtual machine to verifying the system, played an important role in ensuring a complete and successful installation. The system is now fully functional and ready for further use.

6. Issues Faced

During the installation of Alpine Linux, I encountered several challenges while setting up the system in a virtual environment. These issues helped me understand the process more deeply.

- **Confusion during first boot:**
  At the beginning, I was confused when the system started because I did not know what username or password to use.
- **Login misunderstanding:**
  I did not initially understand that the default username is root and that no password is required at the first login.
- **Login failure after reboot:**
  After rebooting, the system asked for a username and password. I entered the credentials I used earlier, but it showed errors multiple times. Because of this, I restarted the installation process several times.
- **Black screen or boot delay:**
  At one point, the system showed a blank screen for a few seconds, which caused confusion during startup.
- **Timezone configuration difficulty:**
  I had difficulty selecting the correct timezone because I was not familiar with the available options.
- **Reboot process challenge:**
  Restarting the system was difficult at first, and I did not know that I needed to remove the ISO file before rebooting.
- **Typing errors during installation (e.g.,** sys**):**
  While selecting the installation type, I made mistakes when typing options like sys, which caused confusion.
- **Command sensitivity issue:**
  The system is very sensitive to commands. Even a small typing mistake caused errors, which made the process slower.
- **Long installation time:**
  The installation process took more time than expected, especially when repeating steps after errors.
- **Network connection loss:**
  The internet connection was unstable, and when it disconnected during the process, it caused errors.
- **Network configuration issue:**
  The system did not connect properly due to incorrect or incomplete network setup.
- **Slow virtual machine performance:**
  The system sometimes responded slowly due to limited RAM allocation.
- **ISO boot problem:**
  The virtual machine failed to boot correctly when the ISO file was not properly attached.
- **Disk selection confusion:**
  It was difficult to identify the correct disk (such as sda) for installation.

- **Command-line difficulty:**
  Since Alpine Linux uses a command-line interface, working without a graphical interface required extra attention and practice.

- **Forgetting to remove ISO after installation:**
  After installation, the system booted again into the setup screen because the ISO file was still attached.
- **Understanding installation options:**
  Some setup options were not clearly understood at first, which made the process confusing.

7. Solutions

To overcome the challenges faced during the installation of Alpine Linux, I applied the following solutions:

- **Solution for first boot confusion:**
  I learned that the default username is root, which should be used to log in when the system starts.
- **Solution for login misunderstanding:**
  I understood that no password is required during the first login before installation begins.
- **Solution for login failure after reboot:**
  I carefully set and remembered the root password during setup. After reboot, I used the correct username (root) and the password I created during installation.
- **Solution for timezone difficulty:**
  I selected the correct timezone by carefully reading the available options and choosing the one that matches my location.
- **Solution for reboot issue:**
  I learned to properly reboot the system using the reboot command and removed the ISO file from the virtual machine settings before restarting.
- **Solution for typing errors (e.g.,** sys**):**
  I paid close attention while typing commands and rechecked inputs before pressing Enter.
- **Solution for command sensitivity:**
  I became more careful with command-line inputs, ensuring there were no small mistakes such as missing letters or spaces.
- **Solution for long installation time:**
  I followed each step carefully to avoid repeating the process, which helped reduce time.
- **Solution for network connection loss:**
  I ensured a stable internet connection before starting the installation process.
- **Solution for network configuration issue:**
  I selected automatic configuration (DHCP), which allowed the system to connect to the network successfully.

- **Solution for slow performance:**
  I increased the allocated RAM in the virtual machine settings to improve performance.
- **Solution for ISO boot problem:**
  I correctly attached the Alpine Linux ISO file and ensured it was selected as the boot device.
- **Solution for disk selection confusion:**
  I carefully checked the disk name (sda) and confirmed before proceeding with installation.
- **Solution for command-line difficulty:**
  I followed the instructions step by step and practiced basic commands to improve my confidence.
- **Solution for understanding installation options:**
  I read each option carefully during setup and selected the recommended choices.

8. Filesystem Support

A file-system is a method used by an operating system to store, organize, and manage data on a storage device. It determines how files are created, accessed, and protected. Different operating systems use different file-systems depending on their design and purpose.

In the case of Alpine Linux, the most commonly used and recommended file-system is **ext4**. This file-system is widely used in Linux systems because it provides a good balance between performance, reliability, and stability. One of its important features is journaling, which helps protect data and reduces the risk of data loss during system crashes.

Ext4 also supports large file sizes and efficient disk management, making it suitable for both small and large systems. In addition, it is simple to use and does not require complex configuration, which makes it ideal for users working with Alpine Linux. For these reasons, ext4 is considered the best choice when installing Alpine Linux.

Even though Alpine Linux can *support* many file-systems, it does not use most of them as the main file system because they are not designed for Linux or not optimal for it because Every operating system has a file-system that fits it best.

Even though Alpine Linux can *support* many file-systems, it does **not use most of them as the main file-system** because they are **not designed for Linux or not optimal for it**.

Other File-systems

- **NTFS:**
  Used mainly in Windows systems. It supports large files and security features but is not ideal for installing Alpine Linux.
- **FAT32:**
  A simple and widely supported file-system used for USB drives. It has a limitation of 4GB file size.
- **exFAT:**
  An improved version of FAT32 that supports larger files and is commonly used for external storage.
- **Btrfs:**
  A Linux filesystem with advanced features like snapshots and backup, but more complex than ext4.
- **ZFS:**
  A powerful file-system used in servers for data protection and management, but not commonly used in Alpine Linux.
- **HFS+ and APFS:**
  These are file-systems used by mac-OS systems and are not suitable for Alpine Linux installations

9. Advantage and Disadvantage

the strengths and weaknesses of Alpine Linux based on practical experience.

Advantages of Alpine Linux

- **Lightweight and Fast:**
  Alpine Linux uses very few system resources, which makes it run smoothly even on low-performance systems.
- **Small Installation Size:**
  It has a very small base size, making it quick to install and saving storage space.
- **High Security:**
  The system is designed with security in mind by including only necessary components and reducing vulnerabilities.
- **Efficient Resource Usage:**
  It uses less CPU and RAM, which makes it suitable for virtual machines and servers.
- **Simple and Minimal Design:**
  Users can install only the packages they need, avoiding unnecessary software.
- **Good for Containers and Cloud:**
  It is widely used in container environments like Docker due to its efficiency.
- **Fast Boot Time:**
  The system starts quickly because it is lightweight.
- **Stable Performance:**
  It runs consistently without unnecessary background processes.
- **Easy to Maintain:**
  The system is simple, which makes updates and maintenance easier.

Disadvantages of Alpine Linux

- **Command-Line Based:**
  It does not include a graphical interface by default, which can be difficult for beginners.
- **Steep Learning Curve:**
  Users need knowledge of Linux commands to operate the system effectively.
- **Limited Software Availability:**
  Some applications are not easily available or require extra configuration.
- **Compatibility Issues:**
  It uses musl libc instead of glibc, which may cause compatibility problems with some software.
- **More Manual Configuration:**
  Many tasks must be done manually, which can take more time.
- **Not Beginner-Friendly:**
  It may be difficult for users who are new to Linux.
- **Troubleshooting Difficulty:**
  Errors may be harder to solve without prior experience.
- **Less Community Support Compared to Larger Distros:**
  Compared to bigger Linux distributions, it has fewer tutorials and community resources.

10. Conclusion

In this project, I successfully installed and configured Alpine Linux in a virtual environment. Through this process, I learned how to create and manage a virtual machine, attach an ISO file, and carry out the installation using command-line instructions.

I also gained practical experience in configuring important system settings such as network setup, disk selection, timezone configuration, and user login. During the installation, I faced several challenges, including login errors after reboot, command typing sensitivity, network connection problems, and confusion with some setup options. By carefully repeating the steps and understanding each part of the process, I was able to overcome these issues successfully.

Furthermore, I developed a better understanding of filesystem support. I learned why ext4 is the most suitable filesystem for Alpine Linux and how other filesystems like NTFS, FAT32, and APFS are used in different operating systems based on their design and purpose.

This project also improved my ability to work in a command-line environment, which is an important skill in Linux systems. It taught me the importance of accuracy, patience, and careful attention when entering commands and configuring systems.

Overall, this assignment provided valuable hands-on experience and helped me build confidence in installing and managing a lightweight operating system. It also strengthened my problem-solving skills and gave me a deeper understanding of how operating systems function in real-world scenarios.

11. Future Outlook / Recommendations

Based on my experience working with Alpine Linux, there are several improvements and future possibilities that can enhance its usability and learning experience.

One important recommendation is to improve **user guidance for beginners**. Since Alpine Linux mainly uses a command-line interface, new users may find it difficult to understand the installation process. Providing more beginner-friendly documentation or guided steps could make it easier to use.

Another suggestion is to include an **optional graphical user interface (GUI)** during installation. This would help users who are not familiar with command-line operations and make the system more accessible.

In the future, improving **software compatibility** would also be beneficial. Since Alpine Linux uses musl libc instead of glibc, some applications may not work properly. Enhancing compatibility can make the system more flexible.

Additionally, better **network stability and automatic configuration** features could reduce common issues faced during installation, especially for beginners.

From a learning perspective, this project can be extended by exploring advanced topics such as server configuration, container usage (e.g., Docker), and system security. These areas represent the future potential of Alpine Linux in real-world applications.

Virtualization in Modern Operating Systems

What is Virtualization?

Virtualization is a technology that allows a single physical computer to run multiple virtual systems at the same time. Each virtual system behaves like a real computer with its own operating system, applications, and settings.

For example, using virtualization, I was able to install Alpine Linux on my computer without affecting my main operating system.

Why is Virtualization Important?

Virtualization is important for several reasons:

- **Efficient Resource Usage:**
  It allows one computer to run multiple systems, making better use of hardware resources.
- **Safe Testing Environment:**
  Users can test new operating systems or software without risking damage to the main system.
- **Cost Reduction:**
  It reduces the need for multiple physical machines.
- **Flexibility and Convenience:**
  Different operating systems can run on the same device at the same time.
- **Learning and Development:**
  It is very useful for students and developers to practice and experiment safely.

How Virtualization Works?

Virtualization works through a software called a **hypervisor** (such as VirtualBox or VM_ware).

The hypervisor creates a **virtual machine (VM)**, which acts like a real computer. It allocates resources such as CPU, memory (RAM), and storage from the physical computer to the virtual machine.

When the virtual machine is started, it runs its own operating system independently. This is how I was able to install and run Alpine Linux inside a virtual environment.

System Call Implementation in Alpine Linux

clock_gettime()

In Alpine Linux, the system call **clock_gettime()** is used to retrieve the current time from a specified system clock. Since Alpine Linux is a minimal distribution, it relies directly on the Linux kernel and uses a lightweight C library (musl) instead of glibc.

This makes the implementation simpler and more efficient.

. Purpose of clock_gettime()

The system call is used to:

- Retrieve current system time
- Measure execution time of programs
- Support high-resolution timing (nanoseconds)



Alpine Linux Environment (Important Difference)

Unlike many Linux distributions:

- Alpine uses **musl libc** instead of glibc
- musl is smaller and simpler
- Fewer layers → more direct interaction with kernel

This means:
clock_gettime() in Alpine is **closer to the actual kernel system call**

Conclusion

This assignment provided a comprehensive understanding of operating system concepts through both theoretical and practical approaches. By using Oracle VirtualBox, I was able to create a virtual environment and successfully install Alpine Linux. This process helped me understand how virtualization works, including how system resources such as memory, storage, and processors are allocated and managed within a virtual machine.

During the installation process, I learned step-by-step procedures such as creating a virtual machine, configuring system settings, attaching an ISO image, and completing the operating system setup. This gave me practical experience in system installation and configuration, which is an important skill in operating systems.

In addition, working with the **clock_gettime()** system call allowed me to understand how user-level programs interact with the operating system kernel. I learned that system calls act as an interface between user applications and the

hardware, enabling safe and controlled access to system resources. Specifically, **clock_gettime()** demonstrated how the system retrieves time information from the kernel and returns it to the user program with high precision.

Overall, this assignment enhanced my knowledge of virtualization, system installation, and system calls. It also improved my practical skills in using Linux-based systems and strengthened my understanding of how operating systems function internally. The experience gained from this assignment will be useful for further studies and real-world applications in computing.

Acknowledgement

I would like to express my sincere gratitude to you, Mr. Wondmu, for giving me this assignment. This assignment helped me understand the practical process of installing an operating system using virtualization and working with system calls such as clock_get-time(). Through this task, I was able to learn how to use Virtual-box, install Alpine Linux, and perform basic system operations. Your instruction and guidance made it possible for me to complete this work successfully and gain valuable knowledge related to operating systems.

References

Oracle VirtualBox. *Official Website*. Available at: https://www.virtualbox.org/

Alpine Linux. *Official Website*. Available at: https://alpinelinux.org/

Linux Manual Page. *clock_gettime() System Call*. Available at: https://man7.org/linux/man-pages/man2/clock_gettime.2.html

Operating System Concepts. Abraham Silberschatz, Peter B. Galvin, Greg Gagne.

Modern Operating Systems. Andrew S. Tanenbaum and Herbert Bos.

The Linux Foundation. *Linux Documentation*. Available at: https://www.linuxfoundation.org/

GCC. *Official Website*. Available at: https://gcc.gnu.org/

musl libc. *Official Website*. Available at: https://musl.libc.org/

Linux kernel. *Official Documentation*. Available at: https://www.kernel.org/

Instructor Guidance – Mr. Wondmu (Class notes and assignment instructions).