Response to the Referees

Manuscript ZV10235: "Accessing the symmetric component of quadrupole misalignment through counter-rotating closed orbits in EDM storage rings"
I. Abedrabbo and S. Hacıömeroğlu

We thank both referees for their careful reading and constructive comments. The comments led us to test the method against the error sources raised by Referee A and to rewrite the presentation along the lines requested by Referee B. The main changes are:

1. A new section "Domain of validity" (Sec. V) quantifies the scheme against monitor motion, electrostatic deflector field errors and rolls, corrector type and correlated misalignment.
2. A new section "Operating scenario" (Sec. VI) follows the machine for one week with ground motion, BPM drift and periodic BBA.
3. The two-beam scheme is now stated as an explicit algorithm (Sec. IV.C), including the treatment of BPM offsets and the choice of the regularization.
4. The symmetric and antisymmetric components are defined in the introduction (Sec. I.C), and the claim of a 100-fold orbit suppression of the symmetric component has been corrected: the measured suppression is four- to sevenfold at low harmonics, explained by the different beta functions at the focusing and defocusing quadrupoles (Sec. III.A, Fig. 2).
5. The false EDM is now evaluated at the frozen-spin energy (Sec. II.C, Appendix A). With a launch at fixed momentum, the result depended on the launch point in a misaligned lattice; this affected the uncorrected and single-beam results by factors of 1.1–35, but not the two-beam results, which were and remain at the numerical floor. The false-EDM values in the paper were recomputed accordingly. [Authors: BBA convergence and channel figure are being re-run with the new evaluation; update this item and the figure numbers once they are included.]
6. To keep the length under control, the main text was streamlined, the BBA section shortened, and technical material moved to appendices.

Referee A

First, the paper assumes that the orbit perturbation is mainly driven by misalignment of quadrupoles with alignment accuracy of about 50–100 μm. [...] there are other sources of orbit perturbation. They are errors of bending power of electrostatic bends and their roles. Optimistically one can put the relative accuracy of about 10^{-4} and the roll of 0.1 mrad. Then for the suggested optics, the orbit perturbation from just one of 48 bends is about 400 μm.

Reply. We agree that this is essential, and we have added Sec. V.B. We confirm the estimate: a relative field error of 10^{-4} (roll of 0.1 mrad) in one deflector produces a closed-orbit distortion of 418 μm (525 μm) peak. Such static errors are removed in the initial calibration; the relevant question for our scheme is the *drift* of the deflectors between calibrations, because the electric force does not reverse with the beam direction and the deflector-induced orbit therefore appears in the same (sum) channel as the symmetric quadrupole misalignment. We find:

- A fit containing only quadrupole columns mistakes a deflector drift for a symmetric misalignment (about 1 μm per 10^{-7} field drift or 0.1 μrad roll drift). Adding the deflector columns to the fit removes this leakage, at the price of a larger noise amplification [Fig. 6(a)].
- A deflector roll produces a first-order false EDM through the magnetic kicks that close the orbit. It has the same sign for the two beam directions and cancels in the CW−CCW observable; its size sets a requirement on the CW/CCW symmetry of the ring, as in Ref. [2].
- Field errors and rolls together produce a geometric phase of their own. It is removed by trimming the deflectors at the source (field by the deflector voltage, roll by an up–down

electrode voltage difference), using the deflector part of the fit. The tolerable deflector drift between trims is set by the accuracy of the response model: with an exact model the false EDM stays at the numerical floor up to 10^{-5}; with a 0.2% gradient error the target is reached at 3–5 $\times 10^{-6}$ [Fig. 6(b)].

The second problem is that the authors assume that accuracy of quad positioning is independent on their location in the ring. [. . .] A more accurate model should account that an error in relative positions of two quads is proportional to the square root of distance between quads. [. . .] The problem is complicated by suppression of beam orbit deviation from BPM centers for long wave perturbations, but it is not obvious that spin precession out of plane has similar suppression.

Reply. We have added Sec. V.D with a random-walk (ATL-type) model in which the relative displacement grows as the square root of the distance. Because neighboring quadrupoles move together, the symmetric component dominates (84% of the variance after removal of the rigid translation and tilt, against about 50% for uncorrelated errors). The two-beam correction is linear and its residual does not depend on the pattern statistics. The time-dependent version of this model is used in the one-week scenario of Sec. VI.

On the second point—whether the spin shares the suppression of long-wavelength perturbations—our answer is yes, for the components that the beam actually follows. A uniform translation or tilt of the lattice moves the closed orbit with it, so the beam still passes through the quadrupole centers and the spin is not affected. More generally, the spin is most sensitive near the betatron tune ($m = 2$–3) and weakly sensitive at $m = 0$. We also found that the more important consequence of long-wavelength motion is that the BPMs move together with the quadrupoles. Section V.A treats this explicitly: an estimator that assumes fixed BPMs then recovers only about a third of the symmetric drift, but the remaining part lies at harmonics to which the spin is weakly sensitive and the false EDM stays below target with a margin of three to five. Monitors rigidly attached to the quadrupoles, with an estimator that accounts for the mounting, recover it fully and are robust against BPM–quadrupole drifts up to at least 1 μm.

It also should be spelled out the difference between usage of electrostatic and magnetic correctors.

Reply. Added as Sec. V.C. Only dipole correctors mounted in the quadrupoles (or quadrupole movers) cancel the misalignment where it occurs and keep the false EDM at the floor. Magnetic correctors at the deflectors act only on the difference channel and cannot correct a symmetric drift. Electrostatic correctors act on both beams alike and can steer them through the quadrupole centers, but the electric kicks they need generate first- and second-order deflector effects ($C = 1.3$–7.6 times the target, plus same-sign signals that rely on CW/CCW symmetry).

Overall impression is that the paper is too long for the reported context.

Reply. We have tightened the introduction and the BBA section, removed repetitions and moved technical material (frozen-spin evaluation, breathing, orbit-difference inversion, two-dimensional illustration) to appendices. Some length was added to address the substantive points above and those of Referee B; we kept these additions as concise as possible.

1. Excessive use of acronyms greatly complicates reading of the text.

Reply. We removed most acronyms. The remaining ones (EDM, BPM, BBA, SVD, CW/CCW) are defined at first use. [Authors: final pass on acronyms.]

2. Section 1.A, line 1: "A permanent electric dipole moment violates" → "A permanent electric dipole moment of an elementary particle violates".

Reply. Changed as suggested.

3. Section 1C, line 6: "Subtracting the" → "Subtraction of the".

Reply. The sentence has been rewritten.

4. Section 1D: An explanation of symmetric and antisymmetric quad displacement comes late in the text.

Reply. The definitions now appear in Sec. I.C, before they are first used.

5. Section II.A, line 3: "the lattice as described in Sec. IB" → "the lattice described in Sec. IB".

Reply. Changed.

6. Line before Eq. (9): ΔR does not look as a matrix.

7. Equation after (9) has problem with dimension.

Reply. (6, 7) The orbit-difference discussion was moved to Appendix C and rewritten: ΔR is the difference of the response matrices for two gradient settings, $\Delta R \approx \epsilon_g \, \partial R/\partial g$, and the relation now reads $\|\Delta R^{-1}\| \approx \|R^{-1}\|/\epsilon_g$, with ϵ_g the dimensionless relative gradient change.

8. Section V.A, Line 3: In the phrase "beams pass through the quadrupoles in the opposite order," state that these are two nearby quads.

Reply. Clarified: "the reversed order of the two quadrupoles of a cell" (Sec. IV.C).

Referee B

A hypothetical ring is described in Section 1.B. But no corresponding lattice layout or optics plot is provided.

Reply. Added as Fig. 1 (cell layout and beta functions), together with the beta functions at the quadrupoles in Table I.

The manuscript introduces the symmetric and antisymmetric quadrupole modes near the beginning of the article, but their mathematical definitions do not appear until Section III.A, in Equation (4). In addition, Equation (5) uses n as an index, whereas k is not defined. [. . .]

Reply. The definitions now appear in Sec. I.C, Eq. (3), with the indices defined (quadrupole $n = 0, \ldots, 47$, cell $k = 0, \ldots, 23$, QF $n = 2k$, QD $n = 2k{+}1$), the decomposition $v[n] = v^s[n]{+}v^a[n]$, and the statement that the two projections are orthogonal and span 24-dimensional subspaces.

The authors state that the low-order singular-value-decomposition (SVD) modes correspond to the symmetric mode, but they provide no explanation or supporting evidence for this correspondence.

Reply. Figure 2(b) now shows the singular values of the tracked response matrix colored by the symmetric content of the corresponding right singular vectors: the directions with the smallest singular values are predominantly symmetric. Section III.A explains why: the symmetric pattern kicks the beam in opposite directions at the two quadrupoles of a cell, and these kicks cancel up to the difference of $\sqrt{\beta}$ between the two quadrupoles; the net kick is about 0.15 of that of an antisymmetric pattern, in agreement with the measured orbit gains [Fig. 2(a)]. In revising this point we found that the statement of a 100-fold suppression in the original manuscript, based on a smooth-focusing estimate, was incorrect; the suppression is four- to sevenfold at low harmonics.

The central purpose of the paper is to present a method for keeping false EDM signals arising from quadrupole misalignments below the sub-target threshold by monitoring the sum of the BPM readings from the two beams. However, the implementation of this method is described only verbally in a single paragraph in Section V.B. [. . .] a PRAB article requires a more rigorous presentation demonstrating how the method works and how its performance is evaluated.

Reply. We agree. Section IV.C now states the scheme as an explicit five-step algorithm: reference readings after BBA, differences of both beams relative to the reference, the two-beam least-squares estimate [Eq. (6)] with the regularization chosen by the discrepancy principle (no knowledge of the true misalignment is needed), the correction by quadrupole-mounted dipole correctors, and the BBA trigger. The performance is evaluated in three steps: (i) static correction of random misalignments (Fig. 4); (ii) the validity domain against monitor motion, deflector errors, corrector type and correlated misalignment (Sec. V, Figs. 5 and 6); (iii) a one-week time-dependent scenario with ground motion, BPM drift, BPM noise and periodic BBA, in which two-beam monitoring keeps the false EDM at the level set by the BBA residual (median 0.05–0.09 of the target, maximum 0.18), whereas periodic BBA alone rises to about 45 times the target between calibrations (Sec. VI, Fig. 7). The detection limit of the monitor is given in the same section.

Recommendation: the manuscript undergo major revision before it can be considered further for publication.

Reply. We hope that the revised manuscript addresses the referees' concerns.

Additional change not requested by the referees. While revising, we found that our false-EDM estimator launched the particle on the closed orbit at fixed momentum. With hard-edge deflectors the momentum varies along a distorted closed orbit, so the result depended on the launch point. Since the experiment keeps the horizontal spin frozen by feedback, we now evaluate the false EDM at the frozen-spin energy (Sec. II.C, Appendix A), where the result is independent of the launch point to 0.2%. The two-beam results of the original manuscript are unaffected (both at the numerical floor); the uncorrected and single-beam values decreased by factors of 1.1–35. All values in the revised manuscript use the new evaluation.