

CONSTRUCTION MATERIAL KEY

- 1. RUBBER WATERPROOFING MEMBRANE
- 2. 0.75" EXTERIOR GRADE PLYWOOD
- 3. 5.5" CLOSED CELL INSULATION
- 4. 0.75" EXTERIOR GRADE PLYWOOD
- 5. WATERPROOF MEMBRANE
- 6. 1.5"x0.75" LARCH SLAT
- 7. 7.25"x1.5" TRUSS CHORDS AND WEB
- 8. 0.5" OSB GUSSET
- 9. 3.5"x1.5" CEILING FRAME
- 10. PARAPET FLASHING
- 11. WOOD CAP
- 12. 5.5"x1.5" TOP PLATE
- 13. 5.5"x1.5" STUD (16" O.C.)
- 14. 11.25"x1.5" HEADER
- 15. 0.75" EXTERIOR GRADE PLYWOOD
- 16. 5.5"x1.5" BRIDGING
- 17. 5.5"x1.5" SILL PLATE
- 18. 5.5"x1.5" SOLE PLATE
- 19. 3.5"x1.5" STUD (16" O.C.)
- 20. 3.5"x1.5" SOLE PLATE
- 21. 0.5" THK. CAPILLARY PAD
- 22. 1'1" ~ 2'8.5" BOARD FORMED CONCRETE PIER
- 23. 18"x3.5" PSL
- 24. 0.75" PLYWOOD
- 25. I-JOIST: PLYWOOD AND LVL
- 26. JOIST HANGAR
- 27. 3.5"x1.5" SLEEPER STUD AND VENTILATION GAP
- 28. 0.75" PLYWOOD FLOOR
- 29. 6" POURED CONCRETE FLOOR SLAB
- 30. 6" COMPACTED GRAVEL
- 31. EARTH/GROUND
- 32. 0.75" HARDWOOD FLOOR
- 33. 1.5" THK STAIR TREAD
- 34. 5.5"x1.5" TIMBER STRINGER
- 35. 3.5"x1.5"X STUD (16" O.C)
- 36. TRUSS HANGAR

WOOD FRAMING

ASSIGNMENT 3 PAGE: 2 OF 3

48-215 MATERIALS & ASSEMBLY SPRING 2017

INSTRUCTOR: DAMIANI

SELENA ZHEN