

SAILING

Dimmable LED Driver

Triac Dimmable Driver
0-10V Dimmable Driver
Waterproof LED Driver



珠海市新霖科技有限公司
zhuhai sailing technology co.,ltd

公司简介

珠海市新霖科技有限公司是一家专业从事 LED 智能调光技术产品的研发，生产，销售及售后服务的高新技术企业。公司主要生产，可控硅 /Triac 调光电源，0-10V 调光电源，DALI 调光驱动及无线控制产品等。产品兼容路创、邦奇、飞利浦、欧司朗、奇胜、施耐德、等系统。广泛运用于多家五星级酒店工程、LED 亮化工程、广告灯箱、城市景观照明工程、商业照明、室内外照明工程、酒吧、KTV 等各个大领域。公司拥有先进的生产设备，完善的生产流程、专业的技术工程师及一流的销售团队，始终坚持以优质的产品和至上的服务为立足之本，以客户需求为发展源泉，秉承“信誉第一，质量至上”的经验理念，生产出一流的产品，满足客户各种需求。珠海市新霖科技有限公司产品齐全，价格合理，产品畅销国内外，出口多个国家和地区。

我们的产品系列包括：

LED 可控硅调光：12V 24V 灯带恒压调光电源、筒灯、天花灯恒流调光电源

LED 三合一调光 (0/1-10V, PWM, 电阻调光)：12V 24V 灯带恒压调光电源、0-10V 调光开关

LED 防水电源 (洗墙灯，泛光灯，投光灯，水底灯，灯条灯带)

LED 室内电源

Company profile:

Zhuhai sailing Technology Co., Ltd. is a high-tech enterprises engaged in LED intelligent dimming technology products research and development, production, sales and after-sales . The company mainly produces Triac dimming power supply, 0-10V/1-10 dimming driver, DALI dimming driver and wireless control products. Products are compatible with Lutron, Dynalite, Philips, Osram, Clipsal, Schneider and other brand systems. Widely used in hotel engineering, LED lighting engineering, advertising lighting, landscape lighting engineering, commercial lighting, indoor and outdoor lighting engineering, bars, KTV etc.. The company has advanced production equipment, perfect production process, professional technical engineers and first-class sales team, always adhere to high-quality products and supreme service as the basis, customer demand as the source of development, adhering to the "reputation first, quality first" experience concept, to provide globally competitive products to meet the needs of customers. Zhuhai sailing Technology Co., Ltd. has a full range of products, reasonable prices, best-selling products sales all over the world.

目 录

CONTENTS

- 01 可控硅防水调光电源 (IP67)
Waterproof Triac dimmable driver (IP67)
- 02 可控硅调光电源 (IP20)
Triac dimmable driver (IP20)
- 04 0/1-10V PWM 防水调光电源 (IP67)
0/1-10V PWM Waterproof dimmable driver
- 05 0/1-10V PWM 调光电源 (IP20)
0/1-10V PWM dimmable driver (IP20)
- 07 防水电源 (IP67)
Waterproof LED driver

可控硅防水调光电源 (IP67)

Waterproof Triac dimmable driver (IP67)



可控硅恒压电源 (IP67)

产品特点:

- ◆调光方式: 可控硅调光, 满足前沿 (Triac) 调光、后沿 (ELV) 调光
- ◆高质量, 体积小、寿命长
- ◆兼容性强, 调光无闪烁, 无抖动, 调光曲线平滑
- ◆具备短路、过载、过压及保护
- ◆100% 满负载老化
- ◆使用环境温度: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆电磁兼容符合 EN55015、EN61000、EN61547
- ◆安规标准符合 EN61347-1

Triac dimmable Constant Voltage driver(IP67)

Features:

- ◆ Dimming type: Triac dimmable
- ◆ High quality, small volume and long life
- ◆ Strong compatibility, no flicker, no jitter, smooth dimming curve
- ◆ Open circuit and short circuit protection
- ◆ Output Protections: OLP/OVP/OTP
- ◆ 100% Full Load Aging Test
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ EMC approval according to: EN55015, EN61000 and EN61547
- ◆ Conform to general and safety requirements IEC/EN 61347-1

产品型号	输出功率 (W)	输入电压 (AC-V)	输出电压 (DC-V)	输出电流 (mA)	效率 (EFF)	防护等级	产品尺寸 (L*W*H) mm	重量 Kg/pcs
LTD-WM-030	30W	AC100-130V	12V	2.5A	85%	IP67	185*52*38mm	0.7Kg
	30W	AC200-240V	24V	1.25A	85%	IP67	185*52*38mm	0.7Kg
LTD-WM-036	36W	AC100-130V	12V	3A	85%	IP67	185*52*38mm	0.7Kg
	36W	AC200-240V	24V	1.5A	85%	IP67	185*52*38mm	0.7Kg
LTD-WM-045	45W	AC100-130V	12V	3.75A	85%	IP67	185*52*38mm	0.7Kg
	45W	AC200-240V	24V	1.87A	85%	IP67	185*52*38mm	0.7Kg
LTD-WM-060	60W	AC100-130V	12V	5A	85%	IP67	185*52*38mm	0.7Kg
	60W	AC200-240V	24V	2.5A	85%	IP67	185*52*38mm	0.7Kg
LTD-WM-080	80W	AC100-130V	12V	6.66A	85%	IP67	300*52*38mm	1.1Kg
	80W	AC200-240V	24V	3.33A	85%	IP67	300*52*38mm	1.1Kg
LTD-WM-100	100W	AC100-130V	12V	8.3A	85%	IP67	300*52*38mm	1.1Kg
	100W	AC200-240V	24V	4.15A	85%	IP67	300*52*38mm	1.1Kg
LTD-WM-150	150W	AC100-130V	12V	12.5A	85%	IP67	245*75*45mm	1.8Kg
	150W	AC200-240V	24V	6.25A	85%	IP67	245*75*45mm	1.8Kg
LTD-WM-200	200W	AC100-130V	12V	16.6A	85%	IP67	245*75*45mm	1.8Kg
	200W	AC200-240V	24V	8.33A	85%	IP67	245*75*45mm	1.8Kg

可控硅调光电源 (IP20)

Triac dimmable driver(IP20)



可控硅恒压电源 (IP20)

产品特点:

- ◆调光方式: 可控硅调光, 满足前沿 (Triac) 调光、后沿 (ELV) 调光
- ◆高质量, 体积小、寿命长
- ◆兼容性强, 调光无闪烁, 无抖动, 调光曲线平滑
- ◆具备短路、过载、过压及保护
- ◆100% 满负载老化
- ◆使用环境温度: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆电磁兼容符合 EN55015、EN61000、EN61547
- ◆安规标准符合 EN61347-1

Triac dimmable Constant Voltage driver(IP20)

Features:

- ◆ Dimming type: Triac dimmable
- ◆ High quality, small volume and long life
- ◆ Strong compatibility, no flicker, no jitter, smooth dimming curve
- ◆ Open circuit and short circuit protection
- ◆ Output Protections: OLP/OVP/OTP
- ◆ 100% Full Load Aging Test
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ EMC approval according to: EN55015, EN61000 and EN61547
- ◆ Conform to general and safety requirements IEC/EN 61347-1

产品型号	输出功率 (W)	输入电压 (AC-V)	输出电压 (DC-V)	输出电流 (mA)	效率 (EFF)	防护等级	产品尺寸 (L*W*H) mm	重量 Kg/pcs
LTD-P-030	30W	AC100-130V	12V	2.5A	85%	IP20	160*50*34mm	0.5Kg
	30W	AC200-240V	24V	1.25A	85%	IP20	160*50*34mm	0.5Kg
LTD-P-036	36W	AC100-130V	12V	3A	85%	IP20	160*50*34mm	0.5Kg
	36W	AC200-240V	24V	1.5A	85%	IP20	160*50*34mm	0.5Kg
LTD-P-045	45W	AC100-130V	12V	3.75A	85%	IP20	160*50*34mm	0.5Kg
	45W	AC200-240V	24V	1.87A	85%	IP20	160*50*34mm	0.5Kg
LTD-M-060	60W	AC100-130V	12V	5A	85%	IP20	255*49*30mm	0.7Kg
	60W	AC200-240V	24V	2.5A	85%	IP20	255*49*30mm	0.7Kg
LTD-M-080	80W	AC100-130V	12V	6.66A	85%	IP20	255*49*30mm	0.7Kg
	80W	AC200-240V	24V	3.33A	85%	IP20	255*49*30mm	0.7Kg
LTD-M-100	100W	AC100-130V	12V	8.3A	85%	IP20	255*49*30mm	0.7Kg
	100W	AC200-240V	24V	4.15A	85%	IP20	255*49*30mm	0.7Kg
LTD-F-150	150W	AC100-130V	12V	12.5A	85%	IP20	198*98*42mm	0.8Kg
	150W	AC200-240V	24V	6.25A	85%	IP20	198*98*42mm	0.8Kg
LTD-M-150	150W	AC100-130V	12V	12.5A	85%	IP20	198*98*42mm	0.8Kg
	150W	AC200-240V	24V	6.25A	85%	IP20	198*98*42mm	0.8Kg
LTD-M-200-12	200W	AC100-130V	12V	16.6A	85%	IP20	198*98*42mm	0.8Kg
	200W	AC200-240V	24V	8.33A	85%	IP20	198*98*42mm	0.8Kg

可控硅调光电源 (IP20)

Triac dimmable driver(IP20)



可控硅恒压电源 (IP20)

产品特点:

- ◆调光方式: 可控硅调光, 满足前沿 (Triac) 调光、后沿 (ELV) 调光
- ◆高质量, 体积小、寿命长
- ◆兼容性强, 调光无闪烁, 无抖动, 调光曲线平滑
- ◆具备短路、过载、过压及保护
- ◆100% 满负载老化
- ◆使用环境温度: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆电磁兼容符合 EN55015、EN61000、EN61547
- ◆安规标准符合 EN61347-1

Triac dimmable Constant Current driver(IP20)

Features:

- ◆ Dimming type: Triac dimmable
- ◆ High quality, small volume and long life
- ◆ Strong compatibility, no flicker, no jitter, smooth dimming curve
- ◆ Open circuit and short circuit protection
- ◆ Output Protections: OLP/OVP/OTP
- ◆ 100% Full Load Aging Test
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ EMC approval according to: EN55015, EN61000 and EN61547
- ◆ Conform to general and safety requirements IEC/EN 61347-1

产品型号	输出功率 (W)	输入电压 (AC-V)	输出电压 (DC-V)	输出电流 (mA)	效率 (EFF)	防护等级	产品尺寸 (L*W*H) mm	重量 Kg/pcs
LTD-P-12-300	3-12W	AC100-130V AC200-240V	DC 3-42V	150-300mA	85%	IP20	185*52*38mm	0.1Kg
LTD-P-10-150	5-10W	AC100-130V AC200-240V	DC50-72V	100-150mA	85%	IP20	185*52*38mm	0.1Kg
LTD-P-24-550	12-24W	AC100-130V AC200-240V	DC25-42V	420-550mA	85%	IP20	185*52*38mm	0.15Kg
LTD-P-31-800	24-31W	AC100-130V AC200-240V	DC25-42V	600-800mA	85%	IP20	240*52*38mm	0.15Kg
LTD-P-50-900	30-50W	AC100-130V AC200-240V	DC50-56V	600-900mA	85%	IP20	240*52*38mm	0.15Kg

0/1-10V PWM 防水调光电源 (IP67)

0/1-10V PWM Waterproof dimmable driver (IP67)



0/1-10V PWM 恒压调光电源 (IP67)

产品特点:

- ◆支持 3 合一模拟调光 0-10V/1-10V/PWM 信号和电阻调光
- ◆高质量, 体积小、寿命长
- ◆兼容性强, 调光无闪烁, 无抖动, 调光曲线平滑
- ◆具备短路、过载、过压及保护
- ◆100% 满负载老化
- ◆使用环境温度: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆电磁兼容符合 EN55015、EN61000、EN61547
- ◆安规标准符合 EN61347-1

0/1-10V Constant Voltage dimmable driver (IP67)

Features:

- ◆ Support 3-in-1 dimming mode(1-10V active signal, adjustable resistance and PWM signal)
- ◆ High quality, small volume and long life
- ◆ Strong compatibility, no flicker, smooth dimming
- ◆ Short circuit, over load, over voltage protection
- ◆ IP Rated: IP67
- ◆ 100% Full Load Aging Test
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ EMC approval according to: EN55015, EN61000 and EN61547
- ◆ Conform to general and safety requirements IEC/EN 61347-1

产品型号	输出功率 (W)	输入电压 (AC-V)	输出电压 (DC-V)	输出电流 (mA)	效率 (EFF)	防护等级	产品尺寸 (L*W*H) mm	重量 Kg/pcs
LPD-060	60W	AC90-130V AC170-265V	12V	5A	85%	IP67	240*53*40mm	1Kg
	60W		24V	2.5A	85%	IP67	240*53*40mm	1Kg
LPD-080	80W	AC90-130V AC170-265V	12V	6.66A	85%	IP67	240*70*42mm	1.2Kg
	80W		24V	3.33A	85%	IP67	240*70*42mm	1.2Kg
LPD-100	100W	AC90-130V AC170-265V	12V	8.3A	85%	IP67	240*70*42mm	1.2Kg
	100W		24V	4.15A	85%	IP67	240*70*42mm	1.2Kg
LPD-120	120W	AC90-130V AC170-265V	12V	10A	85%	IP67	240*70*42mm	1.2Kg
	120W		24V	5A	85%	IP67	240*70*42mm	1.2Kg
LPD-150	150W	AC90-130V AC170-265V	12V	12.5A	85%	IP67	250*75*45mm	1.8Kg
	150W		24V	6.25A	85%	IP67	250*75*45mm	1.8Kg
LPD-200	200W	AC90-130V AC170-265V	12V	16.6A	85%	IP67	250*75*45mm	1.8Kg
	200W		24V	8.33A	85%	IP67	250*75*45mm	1.8Kg

0/1-10V PWM 调光电源 (IP20)

0/1-10V PWM dimmable driver(IP20)



0/1-10V PWM 恒压调光电源 (IP20)

产品特点:

- ◆支持 3 合一模拟调光 0-10V/1-10V/PWM 信号和电阻调光
- ◆高质量, 体积小、寿命长
- ◆兼容性强, 调光无闪烁, 无抖动, 调光曲线平滑
- ◆具备短路、过载、过压及保护
- ◆100% 满负载老化
- ◆使用环境温度: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆电磁兼容符合 EN55015、EN61000、EN61547
- ◆安规标准符合 EN61347-1

0/1-10V Constant Voltage (IP20)

Features:

- ◆ Support 3-in-1 dimming mode(1-10V active signal, adjustable resistance and PWM signal)
- ◆ High quality, small volume and long life
- ◆ Strong compatibility, no flicker, smooth dimming
- ◆ Short circuit, over load, over voltage protection
- ◆ IP Rated: IP67
- ◆ 100% Full Load Aging Test
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ EMC approval according to: EN55015, EN61000 and EN61547
- ◆ Conform to general and safety requirements IEC/EN 61347-1

产品型号	输出功率 (W)	输入电压 (AC-V)	输出电压 (DC-V)	输出电流 (mA)	效率 (EFF)	防护等级	产品尺寸 (L*W*H) mm	重量 Kg/pcs
LND-060	60W	AC90-130V AC170-265V	12V	5A	85%	IP20	200*55*38mm	0.7Kg
	60W		24V	2.5A	85%	IP20	200*55*38mm	0.7Kg
LND-080	80W	AC90-130V AC170-265V	12V	6.66A	85%	IP20	200*55*38mm	0.7Kg
	80W		24V	3.33A	85%	IP20	200*55*38mm	0.7Kg
LND-100	100W	AC90-130V AC170-265V	12V	8.3A	85%	IP20	200*55*38mm	0.7Kg
	100W		24V	4.15A	85%	IP20	200*55*38mm	0.7Kg
LND-120	120W	AC90-130V AC170-265V	12V	10A	85%	IP20	200*55*38mm	0.7Kg
	120W		24V	5A	85%	IP20	200*55*38mm	0.7Kg
LND-150	150W	AC90-130V AC170-265V	12V	12.5A	85%	IP20	223*65*40mm	600g
	150W		24V	6.25A	85%	IP20	223*65*40mm	0.7Kg
LND-200	200W	AC90-130V AC170-265V	12V	16.6A	85%	IP20	223*65*40mm	0.7Kg
	200W		24V	8.33A	85%	IP20	223*65*40mm	0.7Kg
LND-300	300W	AC90-130V AC170-265V	12V	25A	85%	IP20	215*110*50mm	1KG
	300W		24V	12.5A	85%	IP20	215*110*50mm	1KG
LND-350	350W	AC90-130V AC170-265V	12V	29A	85%	IP20	215*110*50mm	1KG
	350W		24V	14.5A	85%	IP20	215*110*50mm	1KG

0/1-10V PWM 调光电源 (IP20)

0/1-10V PWM dimmable driver (IP20)



0/1-10V PWM 恒流调光电源 (IP20)

产品特点:

- ◆支持 3 合一模拟调光 0-10V/1-10V/PWM 信号和电阻调光
- ◆高质量, 体积小、寿命长
- ◆兼容性强, 调光无闪烁, 无抖动, 调光曲线平滑
- ◆具备短路、过载、过压及保护
- ◆100% 满负载老化
- ◆使用环境温度: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆电磁兼容符合 EN55015、EN61000、EN61547
- ◆安规标准符合 EN61347-1

0/1-10V Constant Current dimmable driver (IP20)

Features:

- ◆ Support 3-in-1 dimming mode(1-10V active signal, adjustable resistance and PWM signal)
- ◆ High quality, small volume and long life
- ◆ Strong compatibility, no flicker, smooth dimming
- ◆ Short circuit, over load, over voltage protection
- ◆ IP Rated: IP67
- ◆ 100% Full Load Aging Test
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ EMC approval according to: EN55015, EN61000 and EN61547
- ◆ Conform to general and safety requirements IEC/ EN 61347-1

产品型号	输出功率 (W)	输入电压 (AC-V)	输出电压 (DC-V)	输出电流 (mA)	效率 (EFF)	防护等级	产品尺寸 (L*W*H) mm	重量 Kg/pcs
LND-12-300	6-12W	AC100-240V	DC25-42V	300MA	85%	IP20	240*53*40mm	0.1Kg
LND-15-600	15W	AC100-240V	DC12-25V	600MA	85%	IP20	240*53*40mm	0.1Kg
LND-30-300	24W	AC100-240V	DC36-80V	800MA	85%	IP20	240*70*42mm	0.15Kg
LND-30-700	32W	AC100-240V	DC25-45V	700MA	85%	IP20	240*70*42mm	0.15Kg
LND-30-900	32W	AC100-240V	DC20-36V	900MA	85%	IP20	240*70*42mm	0.15Kg

防水电源 (IP67)

Waterproof LED driver



恒压防水电源 (IP67)

产品特点:

- ◆ 高质量, 小体积、长寿命
- ◆ 具备开路及短路保护
- ◆ 具备输出过载、过压及过温保护
- ◆ 100% 满负载老化
- ◆ 使用环境温度: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ 符合 IP67 防护等级, RoHS 环保标准
- ◆ 电磁兼容符合 EN55015、EN61000、EN61547
- ◆ 安规标准符合 EN61347-1

Constant voltage Waterproof LED driver (IP67)

Features:

- ◆ High quality, small volume and long life
- ◆ Open circuit and short circuit protection
- ◆ Output Protections: OLP/OVP/OTP
- ◆ 100% Full Load Aging Test
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ Comply with IP67&RoHS standards
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ EMC approval according to: EN55015, EN61000 and EN61547
- ◆ Conform to general and safety requirements IEC/ EN 61347-1

产品型号	输出功率 (W)	输入电压 (AC-V)	输出电压 (DC-V)	输出电流 (mA)	效率 (EFF)	防护等级	产品尺寸 (L*W*H) mm	重量 Kg/pcs
LFV-010	10W	AC90-265V	12V	0.83A	85%	IP67	110*30*20mm	0.15Kg
	10W		24V	0.42A	85%	IP67	110*30*20mm	0.15Kg
LFV-015	15W	AC90-265V	12V	1.25A	85%	IP67	110*30*20mm	0.15Kg
	15W		24V	0.625A	85%	IP67	110*30*20mm	0.15Kg
LFV-020	20W	AC90-130V AC170-250V	12V	1.67A	85%	IP67	110*30*20mm	0.15Kg
	20W		24V	0.83A	85%	IP67	110*30*20mm	0.15Kg
LFV-030	30W	AC90-265V	12V	2.5A	85%	IP67	172*30*20mm	0.2Kg
	30W		24V	1.25A	85%	IP67	172*30*20mm	0.2Kg
LFV-0306	36W	AC90-130V AC170-250V	12V	3A	85%	IP67	217*30*20mm	0.25Kg
	36W		24V	1.5A	85%	IP67	217*30*20mm	0.25Kg
LFV-045	45W	AC90-130V AC170-250V	12V	3.75A	85%	IP67	217*30*20mm	0.25Kg
	45W		24V	1.87A	85%	IP67	217*30*20mm	0.25Kg
LFV-060	60W	AC90-265V	12V	5A	85%	IP67	165*52*38mm	0.65Kg
	60W		24V	2.5A	85%	IP67	165*52*38mm	0.65Kg
LFV-080	80W	AC90-265V	12V	6.67A	85%	IP67	165*52*38mm	0.65Kg
	80W		24V	3.33A	85%	IP67	165*52*38mm	0.65Kg
LFV-100	100W	AC90-130V AC170-250V	12V	8.33A	85%	IP67	180*70*42mm	1.1Kg
	100W		24V	4.17A	85%	IP67	180*70*42mm	1.1Kg
LFV-150	150W	AC90-130V AC170-250V	12V	12.5A	85%	IP67	180*70*42mm	1.1Kg
	150W		24V	6.7A	85%	IP67	180*70*42mm	1.1Kg
LFV-200	200W	AC90-130V AC170-250V	12V	16.7A	85%	IP67	240*70*42mm	1.25Kg
	200W		24V	8.33A	85%	IP67	240*70*42mm	1.25Kg

防水电源 (IP67)

Waterproof LED driver



恒流防水电源 (IP67)

产品特点:

- ◆ 高质量, 小体积、长寿命
- ◆ 具备开路及短路保护
- ◆ 具备输出过载、过压及过温保护
- ◆ 100% 满负载老化
- ◆ 使用环境温度: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ 符合 IP67 防护等级, RoHS 环保标准
- ◆ 电磁兼容符合 EN55015、EN61000、EN61547
- ◆ 安规标准符合 EN61347-1

Constant current waterproof LED driver

Features:

- ◆ High quality, small volume and long life
- ◆ Open circuit and short circuit protection
- ◆ Output Protections: OLP/OVP/OTP
- ◆ 100% Full Load Aging Test
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ Comply with IP67&RoHS standards
- ◆ Work Temperature: $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$
- ◆ EMC approval according to: EN55015, EN61000 and EN61547
- ◆ Conform to general and safety requirements IEC/EN 61347-1

产品型号	输出功率 (W)	输入电压 (AC-V)	输出电压 (DC-V)	输出电流 (mA)	效率 (EFF)	防护等级	产品尺寸 (L*W*H) mm	重量 Kg/pcs
LFC-10-300	10W	AC90-265V	DC12-20V	300mA	85%	IP67	110*30*20mm	0.15Kg
			DC15-25V	300mA	85%	IP67	110*30*20mm	0.15Kg
			DC20-36V	300mA	85%	IP67	110*30*20mm	0.15Kg
LFC-18-600	18W	AC90-265V	DC18-30V	300mA-600mA	85%	IP67	160*30*20mm	0.2Kg
			DC30-60V	300mA-600mA	85%	IP67	160*30*20mm	0.2Kg
LFC-30-900	30W	AC90-265V	20-60V	300mA-600mA	85%	IP67	160*30*20mm	0.2Kg
			60-90V	300mA-600mA	85%	IP67	160*30*20mm	0.2Kg
FLC-36-1200	36W	AC90-265V	25-50V	450mA-900mA	85%	IP67	160*30*20mm	0.2Kg
			50-80V	450mA-900mA	85%	IP67	160*30*20mm	0.2Kg
FLC-48-1500	48W	AC90-265V	20-50V	600mA-1200mA	85%	IP67	165*52*38mm	0.65Kg
			50-90V	600mA-1200mA	85%	IP67	165*52*38mm	0.65Kg



珠海市新霖科技有限公司
zhuhai sailing technology co.,ltd



广东省珠海市香洲区屏东 2 路路 20 号 1 栋 2 楼

1st Building, No.20, Pingdong 2th Road, Nanping Technical Industrial Park, Zhuhai, uangdong



0756-8305964



0756-8305964



info@ledsailing.com



www.ledsailing.com

