

Reproducible Documents with `{ rmarkdown }`

Day 2

Instructor: **Selina Baldauf**

Freie Universität Berlin - Theoretical Ecology



2022-22-03 (updated: 2022-03-30)

Topics today

- Citations
- Make tables look nice
- Some more tips and good practice

html_document


Interactive graphs e.g. with `plotly`

```
library(ggplot2)
scatter <- ggplot(
  data = penguins,
  aes(
    x = bill_length_mm,
    y = bill_depth_mm,
    color = species,
    shape = species
  )
) +
  geom_point(size = 2, alpha = 0.8) +
  geom_smooth(method = "lm", se = FALSE) +
  scale_color_manual(values = c("darkorange", "purple", "cyan4")) +
  theme_minimal()
```

html_document


Interactive graphs e.g. with `plotly`

```
library(plotly)
ggplotly(scatter)
```



The visual editor in RStudio

- WYSIWYG editor (*What you see is what you get*)
 - More similar to Word etc. but with less functionality
- Click on the button on the top right



- Very helpful in the beginning until you remember how everything works in markdown
- Especially helpful for markdown tables and citations
- But careful: Can reformat the `.Rmd` file a bit, so sometimes if you switch back it can look different than before.

Adding citations - The classic way

Bibliographies can be included via a BibTeX data base.

- Create a `.bib` file that consists of bibliography entries

```
@Book{cookbook,  
  title = {R Markdown Cookbook},  
  author = {Yihui Xie and Christophe Dervieux and Emily Riederer},  
  publisher = {Chapman and Hall/CRC},  
  address = {Boca Raton, Florida},  
  year = {2020},  
  note = {ISBN 9780367563837},  
  url = {https://bookdown.org/yihui/rmarkdown-cookbook},  
}
```

Adding citations - The classic way

Bibliographies can be included via a BibTeX data base.

- Create a `.bib` file that consists of bibliography entries
- Add name and location of your `.bib` file as a metadata field in YAML header

```
---  
output: html_document  
bibliography: references.bib  
---
```

- Cite an article from the database with `@bib_item_name` for in text citations or `[@bib_item_name]` for citation in brackets
 - Here, I cite `@cookbook` because it's a good book `[@cookbook]`
 - Here, I cite Xie, Dervieux, and Riederer (2020) because it's a good book (Xie, Dervieux, and Riederer 2020)
- List of references used will be added to the end of the document
 - Just add a heading `# References` to end of the doc

Adding citations - The classic way

- Add a custom citation style file with:


```
---  
output: html_document  
bibliography: references.bib  
csl: myrefstyle.csl  
---
```

- Most (all?) reference managers can export your citations as a `.bib` file
- Problem: RStudio does not auto-fill citations
 - You have to know the name of the citation in order to cite it

Adding citations - Visual editor

Citations can also be added using the **visual editor** in RStudio.

- Visual editor creates and extends `.bib` file automatically
- Search and add citations from
 - The bibliography file
 - Zotero
 - DOI
 - ...
- Just click on the @ symbol in the visual editor to add a citation



- You can also start typing @ and the editor will suggest you a list of citations that fit

Adding citations - Visual editor

Using Zotero

- If you use Zotero on your machine, RStudio should automatically detect the installation
- If not, go to `Tools->Global Options->R Markdown -> Citations` and enter the location of your Zotero data directory and the library that you would like to use
 - In General this should be recognized automatically

Now you

Task 1: Add some citations (20 mins)

Find the task description [here](#)

Nice looking tables in R Markdown

Nice looking tables with R Markdown

- The default for printing tables looks the same as printing it in the console:

```
iris_sum
```

```
## # A tibble: 3 x 5
##   Species      Sepal.Length Sepal.Width Petal.Length Petal.Width
##   <fct>         <dbl>         <dbl>         <dbl>         <dbl>
## 1 setosa         5.01           3.43           1.46           0.246
## 2 versicolor    5.94           2.77           4.26           1.33
## 3 virginica     6.59           2.97           5.55           2.03
```

- This is not really nice for documents

knitr::kable()

Simple to use table generator from the `knitr` package.

```
knitr::kable(iris_sum) # or iris_sum %>% knitr::kable()
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

- Chose `kable` as default table printing in YAML header:

```
df_print: "kable"
```

- `kable` works for PDF, HTML and Word output

knitr::kable()

Add arguments for additional formatting:

```
kable(x,  
  format,  
  digits = getOption("digits"),  
  row.names = NA,  
  col.names = NA,  
  align, caption = NULL,  
  label = NULL,  
  format.args = list(),  
  escape = TRUE, ...  
)
```

- See [here](#) for many examples many different use cases

knitr::kable()

Example:

```
knitr::kable(  
  iris_sum,  
  digits = 1,  
  col.names = c("Species", "Sepal Length", "Sepal Width", "Petal Length", "Petal Width"),  
  caption = "Summary of the Iris data",  
  align = "l"  
)
```

Summary of the Iris data				
Species	Sepal Length	Sepal Width	Petal Length	Petal Width
setosa	5.0	3.4	1.5	0.2
versicolor	5.9	2.8	4.3	1.3
virginica	6.6	3.0	5.6	2.0

The {kableExtra} package

- Provides options for table styling for HTML and PDF tables
- Most of the features work for both HTML and PDF tables
- Find the full documentation [here](#)
 - If you use tables a lot, I recommend looking through the documentation to see all possibilities
- Load the packages in the setup chunk before using them

```
library(knitr)  
library(kableExtra)
```

- **Careful:** Don't load `kableExtra` for `word_document` output. This will break the tables made with `kable`

The {kableExtra} package

kable_styling() is the basic styling function

- Use the pipe operator (`%>%`) to pipe `kable()` output to styling function `kable_styling()`

```
iris_sum %>%  
  kable() %>%  
  kable_styling(  
    full_width = FALSE, # display table on full page width?  
    position = "center", # if not full width -> where  
    font_size = 15  
  )
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

The {kableExtra} package

`kable_styling()` provides styling options

- Additional styling options for HTML output are passed via `bootstrap_options`

```
iris_sum %>%  
  kable() %>%  
  kable_styling(  
    full_width = FALSE, # display table on full page width?  
    position = "center", # if not full width -> where  
    font_size = 15,  
    bootstrap_options = c("striped", "hover")  
  )
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

The {kableExtra} package

`kable_styling()` provides styling options

- Additional styling options for PDF output are passed via `latex_options`

```
iris_sum %>%  
  kable(booktabs = TRUE) %>%  
  kable_styling(  
    full_width = FALSE, # display table on full page width?  
    position = "center", # if not full width -> where  
    font_size = 15,  
    bootstrap_options = c("striped", "hover"),  
    latex_options = c("striped", "hold_position", "scale_down")  
  )
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

- Depending on the output format you chose, `bootstrap_options` or `latex_options` will be ignored

The {kableExtra} package

`kable_styling()` provides styling options

- Additional styling options for PDF output are passed via `latex_options`

```
iris_sum %>%  
  kable(booktabs = TRUE) %>%  
  kable_styling(  
    full_width = FALSE, # display table on full page width?  
    position = "center", # if not full width -> where  
    font_size = 15,  
    bootstrap_options = c("striped", "hover"),  
    latex_options = c("striped", "hold_position", "scale_down")  
  )
```

- `booktabs = TRUE` will use the `booktabs` LaTeX package to create nice horizontal lines and removes vertical lines
- `hold_position` places the table where it is created in the document (no floating)
- `striped` creates striped tables

The {kableExtra} package

Packing rows and columns

```
iris_sum %>%  
  kable() %>%  
  kable_styling(font_size = 15) %>%  
  add_header_above(c("", "Sepals" = 2, "Petals" = 2)) %>%  
  pack_rows("Group 1", 1, 1) %>%  
  pack_rows("Group 2", 2, 3)
```

	Sepals		Petals	
Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
Group 1				
setosa	5.006	3.428	1.462	0.246
Group 2				
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

The {kableExtra} package

Adding footnotes

```
iris_sum %>%  
  kable() %>%  
  footnote(general = "Here is a general comments of the table. ",  
           number = c("Footnote 1; ", "Footnote 2; "),  
           alphabet = c("Footnote A; ", "Footnote B; "),  
           symbol = c("Footnote Symbol 1; ", "Footnote Symbol 2")  
  )
```

virginica	6.588	2.974	5.552	2.026
<i>Note:</i>				
Here is a general comments of the table.				
¹ Footnote 1;				
² Footnote 2;				
^a Footnote A;				
^b Footnote B;				
[*] Footnote Symbol 1;				
[†] Footnote Symbol 2				

The {kableExtra} package

Some predefined html themes

- `kableExtra` offers some themes for HTML tables
 - `kable_paper`, `kable_classic`, `kable_classic_2`, `kable_minimal`, `kable_material` and `kable_material_dark`
 - Use them alternative to `kable_styling()`

```
iris_sum %>%  
  kable() %>%  
  kable_classic(  
    font_size = 15  
  )
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

- This only works with HTML output! It will give you an error for PDF output.

The {flextable} package

- Works with PDF, HTML and Word output
 - Can be used as an option to style tables in Word
- Alternative to `kable` and `kableExtra`
- Set options for all tables in beginning (e.g. in setup chunk)

```
library(flextable)
set_flextable_defaults(
  font.size = 10,
  theme_fun = theme_booktabs,
  padding = 6,
  digits = 1
)
```

- See all options with `?flextable::set_flextable_defaults`

The {flextable} package

- An example table that looks decent in all 3 outputs

```
iris_sum %>%  
  flextable() %>%  
  set_caption("Summary of the iris data") %>%  
  set_header_labels(  
    Sepal.Length = "Sepal Length",  
    Sepal.Width = "Sepal Width",  
    Petal.Length = "Petal Length",  
    Petal.Width = "Petal Width"  
  ) %>%  
  colformat_double()
```

Summary of the iris data

Species	Sepal Length	Sepal Width	Petal Length	Petal Width
setosa	5.0	3.4	1.5	0.2
versicolor	5.9	2.8	4.3	1.3
virginica	6.6	3.0	5.6	2.0

Now you

Task 3: Create a nice table (25 mins)

Find the task description [here](#)