Reproducible Documents with {rmarkdown}

Day 2

Instructor: Selina Baldauf

Freie Universität Berlin - Theoretical Ecology



2022-22-03 (updated: 2022-09-13)

Topics today

- Visual editor in RStudio
- Citations
- Make tables look nice
- Some more tips and good practice

The visual editor in RStudio

- WYSIWYG editor (What you see is what you get)
 - More similar to Word etc. but with less functionality
- Click on the button on the top left



- Very helpful in the beginning until you remember how everything works in markdown
- Especially helpful for markdown tables and citations
- But careful: Can reformat the .Rmd file a bit, so sometimes if you switch back it can look different than before.
 - Best to choose the editor you like most and stick with it

Adding citations - The classic way

Bibliographies can be included via a BibTeX data base.

• Create a .bib file that consists of bibliography entries

```
@Book{cookbook,
  title = {R Markdown Cookbook},
  author = {Yihui Xie and Christophe Dervieux and Emily Riederer},
  publisher = {Chapman and Hall/CRC},
  address = {Boca Raton, Florida},
  year = {2020},
  note = {ISBN 9780367563837},
  url = {https://bookdown.org/yihui/rmarkdown-cookbook},
  }
```

Adding citations - The classic way

Bibliographies can be included via a BibTeX data base.

- Create a .bib file that consists of bibliography entries
- Add name and location of your .bib file as a medatada field in YAML header

```
---
output: html_document
bibliography: references.bib
---
```

- Cite an article from the database with <code>@bib_item_name</code> for in text citations or <code>[@bib_item_name]</code> for citation in brackets
 - Here, I cite @cookbook because it's a good book [@cookbook]
 - Here, I cite Xie, Dervieux, and Riederer (2020) because it's a good book (Xie, Dervieux, and Riederer 2020)
- List of references used will be added to the end of the document
 - Just add a heading # References to end of the doc

Adding citations - The classic way

Add a custom citation style file with:

```
output: html_document
bibliography: references.bib
csl: myrefstyle.csl
---
```


- Most (all?) reference managers can export your citations as a .bib file
- Problem: RStudio does not auto-fill citations.
 - You have to know the name of the citation in order to cite it

Citations can also be added using the visual editor in RStudio.


- Visual editor creates and updates .bib file automatically
- Search and add citations from
 - The bibliography file
 - Zotero
 - o DOI
 - 0 ...

• Just click on the Insert -> citation

- Select source of citation on the left (e.g. DOI, Zotero, ...)
- Click Insert to add citation to bibliography.bib



• You can also start typing @ and the editor will suggest you a list of citations that fit



Using Zotero

- If you use Zotero on your machine, RStudio should automatically detect the installation
- If not, go to Tools->Global Options->R Markdown -> Citations and enter the location of your Zotero data directory and the library that you would like to use
 - In General this should be recognized automatically

Now you

Task 1: Add some citations (20 mins)

Find the task description here

Nice looking tables in R Markdown

Nice looking tables with R Markdown

• The default for printing tables looks the same as printing it in the console:

```
iris sum
## # A tibble: 3 \times 5
  Species Sepal.Length Sepal.Width Petal.Length Petal.Width
  <fct>
           <dbl>
                         <dbl>
                                   <dbl> <dbl>
## 1 setosa
                     3.43 1.46 0.246
                 5.01
                 5.94 2.77 4.26 1.33
## 2 versicolor
                          2.97 5.55
                                           2.03
## 3 virginica
                 6.59
```

• This is not really nice for documents

knitr::kable()

Simple to use table generator from the knitr package.

```
knitr::kable(iris_sum) # or iris_sum %>% knitr::kable()
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

• Chose kable as default table printing in YAML header:

```
df_print: "kable"
```

• kable works for PDF, HTML and Word output

knitr::kable()

Add arguments for additional formatting:

```
kable(x,
  format,
  digits = getOption("digits"),
  row.names = NA,
  col.names = NA,
  align, caption = NULL,
  label = NULL,
  format.args = list(),
  escape = TRUE, ...
)
```

• See here for many examples many different use cases

knitr::kable()

Example:

```
knitr::kable(
  iris_sum,
  digits = 1,
  col.names = c("Species", "Sepal Length", "Sepal Width", "Petal Length", "Petal Width"),
  caption = "Summary of the Iris data",
  align = "1"
)
```

Summary of the Iris data

Species	Sepal Length	Sepal Width	Petal Length	Petal Width
setosa	5.0	3.4	1.5	0.2
versicolor	5.9	2.8	4.3	1.3
virginica	6.6	3.0	5.6	2.0

- Provides options for table styling for HTML and PDF tables
- Most of the features work for both HTML and PDF tables
- Find the full documentation here
 - If you use tables a lot, I recommend looking through the documentation to see all possibilities
- Load the packages in the setup chunk before using them

```
library(knitr)
library(kableExtra)
```

• Careful: Don't load kableExtra for word_document output. This will break the tables made with kable

kable styling() is the basic styling function

Use the pipe operator (%>%) to pipe kable() output to styling function kable_styling()
 Use the keyboard shortcut Ctrl/Cmd + Shift + M to insert %>%

```
iris_sum %>%
  kable() %>%
  kable_styling(
  full_width = FALSE, # display table on full page width?
  position = "center", # if not full width -> where to put table
  font_size = 15
)
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

kable styling() provides styling options

• Additional styling options for HTML output are passed via bootstrap options

```
iris_sum %>%
  kable() %>%
  kable_styling(
  full_width = FALSE, # display table on full page width?
  position = "center", # if not full width -> where
  font_size = 15,
  bootstrap_options = c("striped", "hover")
)
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

kable styling() provides styling options

Additional styling options for PDF output are passed via latex options

```
iris_sum %>%
  kable(booktabs = TRUE) %>%
  kable_styling(
    full_width = FALSE,
    position = "center",
    font_size = 15,
    bootstrap_options = c("striped", "hover"),
    latex_options = c("striped", "hold_position", "scale_down")
)
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

• booktabs = TRUE will use the booktabs LaTeX package to create nice horizontal lines and removes vertical lines

kable_styling() provides styling options

Additional styling options for PDF output are passed via latex options

```
iris_sum %>%
  kable(booktabs = TRUE) %>%

kable_styling(
  full_width = FALSE,
  position = "center",
  font_size = 15,
  bootstrap_options = c("striped", "hover"),
  latex_options = c("striped", "hold_position", "scale_down")
)
```

• Depending on the output format you chose, bootstrap_options or latex_options will be ignored

Packing rows and columns

```
iris_sum %>%
  kable() %>%
  kable_styling(font_size = 15) %>%
  add_header_above(c("", "Sepals" = 2, "Petals" = 2)) %>%
  pack_rows("Group 1", 1, 1) %>%
  pack_rows("Group 2", 2, 3)
```

	Sepals		Petals	
Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
Group 1				
setosa	5.006	3.428	1.462	0.246
Group 2				
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

Some predefined html themes

- kableExtra offers some themes for HTML tables
 - o kable_paper, kable_classic, kable_classic_2, kable_minimal, kable_material and kable_material_dark
 - Use them alternative to kable styling()

```
iris_sum %>%
  kable() %>%
  kable_classic(
    font_size = 15
)
```

Species	Sepal.Length	Sepal.Width	Petal.Length	Petal.Width
setosa	5.006	3.428	1.462	0.246
versicolor	5.936	2.770	4.260	1.326
virginica	6.588	2.974	5.552	2.026

• This only works with HTML output! It will give you an error for PDF output.

The {flextable} package

- Works with PDF, HTML and Word output
 - o Can be used as an option to style tables in Word
- Alternative to kable and kableExtra
- See here for an extensive documentation of the flextable package

Now you

Task 3: Create a nice table (25 mins)

Find the task description here