

**DT/NT : DT**

**LESSON : DevOps**

**SUBJECT: Kubernetes-4**  
**(Kubernetes Volumes)**

**BATCH: 149**  
**31.10.2023**



**TECHPRO**  
EDUCATION



techproeducation.com



+1 (585) 304 29 59





# Table of Contents


- ❖ Volumes
- ❖ Volume Types
- ❖ PersistentVolumes
- ❖ PersistentVolumeClaims
- ❖ The interaction between PVs and PVCs

# Volumes

- on-disk files in a Container are ephemeral.
- All data stored inside a container is deleted if the container crashes.
- When a Container crashes, kubelet will restart it, but the files will be lost which means that it will not have any of the old data.
- To overcome this problem, Kubernetes uses **Volumes**. A Volume is essentially a directory backed by a storage medium. The storage medium, content and access mode are determined by the Volume Type.


# Volumes

A **volume** can be thought of as a directory which is accessible to the containers in a pod.



# Volume Types

**hostPath:** A hostPath volume mounts a file or directory from the host node's filesystem into your Pod.



# Volume Types


- **emptyDir:** An emptyDir volume is first created when a Pod is assigned to a Node and exists as long as that Pod is running on that node.

Some uses for an emptyDir are:

- checkpointing a long computation for recovery from crashes
- as a cache

# Volume Types

## □ **hostPath vs emptyDir**



# Volume Types

- **awsElasticBlockStore:** An awsElasticBlockStore volume mounts an Amazon Web Services (AWS) EBS Volume into your Pod.
- **azureDisk:** An azureDisk is used to mount a Microsoft Azure Data Disk into a Pod.
- **gcePersistentDisk:** A gcePersistentDisk volume mounts a Google Compute Engine (GCE) persistent disk (PD) into your Pod.




# Volume Types

- **Secret:** A secret volume is used to pass sensitive information, such as passwords, to Pods.
- **configMap:** The configMap resource provides a way to inject configuration data, or shell commands and arguments into a Pod.

# PersistentVolumes

A **PersistentVolume (PV)** is a piece of storage in the cluster that has been provisioned by an administrator or dynamically provisioned using Storage Classes.




# PersistentVolumeClaims

A **PersistentVolumeClaim (PVC)** is a request for storage by a user. Users request for PersistentVolume resources based on type, access mode, and size. There are four access modes:

- **ReadWriteOnce** (read-write by a single node)
- **ReadOnlyMany** (read-only by many nodes)
- **ReadWriteMany** (read-write by many nodes).
- **ReadWriteOncePod** (read-write only one pod in the cluster)

Once a suitable **PersistentVolume** is found, it is bound to a **PersistentVolumeClaim**.


# PersistentVolumeClaims




# The interaction between PVs and PVCs


Static

Dynamic









# Do you have any questions?

Send it to us! We hope you learned something new.