DT/NT :

DT

LESSON:

DevOps

SUBJECT:

Docker-5 **Docker-compose**

BATCH: 149 20.10.2023





















Table of Contents

- •What is Docker Compose?
- Using Compose
- Docker Compose File
- Docker Compose Commands



What is Docker Compose?

- •Compose is a tool for defining and running multi-container Docker applications.
- •With Compose, you use a **YAML file** to configure your application's services.
- •Then, with a single command, you create and start all the services based on your configuration.
- •Compose works in all environments: production, staging, development, testing, as well as workflows.





Using Compose

Using Compose is basically three-step process:

- •Define your app's environment with a **Dockerfile** so it can be reproduced anywhere.
- •Define the services that make up your app in docker-compose.yml so they can be run together in an isolated environment.
- •Run docker-compose up and Compose starts and runs your entire app.



Docker Compose File

- •The Compose file is a YAML file defining:
- -services
- -networks
- -volumes
- The default path for a Compose file is
 ./docker-compose.yml


```
version: "3.8"
services:
   web:
     build: .
     depends_on:
        -db
        -redis
   redis:
     image: redis
   db:
     image: postgres
```

```
version: '3.0'
services:
 web:
  build: .
  ports:
   - "5000:5000"
  volumes:
   - ./code
logvolume01:/var/log
  depends_on:
   - redis
 redis:
  image: redis
volumes:
 logvolume01: {}
networks:
```



Docker Compose File

• There are several versions of the Compose file format -1,2,2.x, and 3.x.



EDUCATION

Docker-compose Commands

| Command | Description |
|---------|---|
| build | Build or rebuild services |
| config | Validate and view the Compose file |
| down | Stop and remove containers, networks, images, and volumes |
| events | Receive real time events from containers |
| exec | Execute a command in a running container |
| images | List images |
| kill | Kill containers |
| logs | View output from containers |
| pause | Pause services |



Docker-compose Commands


| Command | Description |
|---------|--|
| port | Print the public port for a port binding |
| ps | List containers |
| pull | Pull service images |
| push | Push service images |
| restart | Restart services |
| rm | Remove stopped containers |
| run | Run a one-off command |
| start | Start services |
| stop | Stop services |



Docker-compose Commands

| Command | Description |
|---------|---|
| top | Display the running processes |
| unpause | Unpause services |
| up | Create and start containers |
| version | Show the Docker-Compose version information |





Do you have any questions?

Send it to us! We hope you learned something new.