Peradheep Y

Rathinam College

Submitted on 1/22/2026, 9:51:52 AM

Powered by DoSelect

29 scored out of **145**

Failed in the assessment

(Cut-off score >= 50%)

3 problems attempted out of **5**

Test Time Analysis

1:15:41.521000

time taken for completion

21/01/2026 10:00 AM

test invite time

21/01/2026 05:09 AM

test start time

21/01/2026 05:29 AM

test end time

Solutions

Problem Name	Problem Type	Status	Score
Write a function that rev	Coding Test	Accepted	6/20
You are given a string s	Coding Test	Accepted	5/25
Given a string s containi	Coding Test	Rejected	null/30
Given a string s, count t	Coding Test	Accepted	18/30
A pangram is a sentence w	Coding Test	Rejected	null/40

All Languages

Problem 1: Write a function that reverses a string given as an array of c

Input Format:

Character Array

Output Format:

null

Sample Code:

Code: c

```
#include <stdio.h>

#include <string.h>


void reverseString(char s[]) {

    int i = 0, j = strlen(s) - 1;

    if (s[j] == '\n') j--;   // remove newline from fgets

    while(i < j) {

        char temp = s[i];

        s[i] = s[j];

        s[j] = temp;

        i++; j--;

    }

}
```

```
int main() {
    char s[100];
    fgets(s, sizeof(s), stdin);
    reverseString(s);
    printf("%s", s);
    return 0;
}
```

Code: cpp

```
#include <iostream>
#include <string>
using namespace std;

void reverseString(string &s) {
    int i = 0, j = s.length() - 1;
    while(i < j) {
        swap(s[i], s[j]);
        i++; j--;
    }
}

int main() {
```

```
    string s;
    getline(cin, s);
    reverseString(s);
    cout << s << endl;
    return 0;
}
```

Code: java

```
import java.util.Scanner;


public class ReverseString {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        String s = sc.nextLine();
        char[] arr = s.toCharArray();
        int i = 0, j = arr.length - 1;
        while(i < j) {
            char temp = arr[i];
            arr[i] = arr[j];
            arr[j] = temp;
            i++; j--;
        }
        System.out.println(new String(arr));
    }
}
```

Code: python

```python
def reverse_string(s: list) -> None:

    i, j = 0, len(s)-1

    while i < j:

        s[i], s[j] = s[j], s[i]

        i += 1

        j -= 1



# Input from user

text = input().strip()

arr = list(text)



reverse_string(arr)

print(''.join(arr))
```

Solution:

Score: 6/20

Submitted Code:

```java
public static string reversed(string name){

    for(int i = name.lenth-1; i > 0; i--){

        char ch = name.charAt(i);

    }
```

```
}


public static void main(String args[]){

    Scanner sc = new Scanner(System.in);

    System.out.println("Enter the string");

    String demo = sc.nextLine;



    reversed(demo);

}
```

Problem 2: You are given a string s consisting only of characters '1' an

Input Format:

String

Output Format:

null

Sample Code:

Code: c

```
#include <stdio.h>

#include <string.h>


int main() {

    char s[101];
```

```
    fgets(s, sizeof(s), stdin);


    // remove newline if present
    int len = strlen(s);
    if(len > 0 && s[len-1] == '\n') s[len-1] = '\0';


    int last = -1;
    for (int i = 0; s[i]; i++) {
        if (s[i] == '2') last = i;
    }


    if (last == -1) {
        printf("empty\n");
    } else {
        for (int i = 0; i <= last; i++) {
            printf("%c", s[i]);
        }
        printf("\n");
    }
    return 0;
}
```

Code: cpp

```
#include <iostream>

#include <string>

using namespace std;


int main() {

    string s;

    getline(cin, s);


    size_t pos = s.rfind('2');

    if (pos == string::npos)

        cout << "empty" << endl;

    else

        cout << s.substr(0, pos + 1) << endl;


    return 0;

}
```

Code: java

```
import java.util.Scanner;


public class LargestEvenString {

    public static void main(String[] args) {

        Scanner sc = new Scanner(System.in);

        String s = sc.nextLine();
```

```
        int pos = s.lastIndexOf('2');
        if (pos == -1) {
            System.out.println("empty");
        } else {
            System.out.println(s.substring(0, pos + 1));
        }
    }
}
```

Code: python

```
s = input().strip()
i = s.rfind('2')
if i == -1:
    print("empty")
else:
    print(s[:i+1])
```

Solution:

Score: 5/25

Submitted Code:

```
class Solution{
 public string isInt(string s){
    string isEmpty = 0;
```

```
    for(int i = 0; i < s.lenght(); i++){
        if (s == isEmpty){
            return s[i];
        } else {
            return string {};
        }
    }
}
}
```

Problem 3: Given a string s, count the number of vowels (a, e, i, o, u) pr

Input Format:

Output Format:

null

Sample Code:

Code: c

```
#include <stdio.h>
#include <string.h>

int isVowel(char ch) {
    return (ch=='a'||ch=='e'||ch=='i'||ch=='o'||ch=='u'||
```

```
        ch=='A'||ch=='E'||ch=='I'||ch=='O'||ch=='U');
}

int main() {
    char s[1000];
    fgets(s, sizeof(s), stdin);

    int count = 0;
    for (int i = 0; s[i] != '\0'; i++) {
        if (isVowel(s[i])) {
            count++;
        }
    }

    printf("%d", count);
    return 0;
}
```

Code: cpp

```
#include <iostream>
#include <string>
using namespace std;

bool isVowel(char ch) {
```

```
    return ch=='a'||ch=='e'||ch=='i'||ch=='o'||ch=='u'||
           ch=='A'||ch=='E'||ch=='I'||ch=='O'||ch=='U';
}

int main() {
    string s;
    getline(cin, s);

    int count = 0;
    for (char ch : s) {
        if (isVowel(ch)) {
            count++;
        }
    }

    cout << count;
    return 0;
}
```

Code: java

```
import java.util.*;

public class Main {
    public static void main(String[] args) {
```

```
        Scanner sc = new Scanner(System.in);
        String s = sc.nextLine();

        int count = 0;
        for (int i = 0; i < s.length(); i++) {
            char ch = s.charAt(i);
            if ("aeiouAEIOU".indexOf(ch) != -1) {
                count++;
            }
        }

        System.out.println(count);
    }
}
```

Code: python

```
def count_vowels(s):
    vowels = set("aeiouAEIOU")
    count = 0
    for ch in s:
        if ch in vowels:
            count += 1
    return count
```

```
s = input().strip()

print(count_vowels(s))
```

Solution:

Score: 18/30

Submitted Code:

```
def vowel():

  s = input("Enter the string")

  v = ['a', 'e', 'i', 'o', 'u', 'A', 'E', 'I', 'O', 'U']



  count = 0



  for i in s:

   for j in v:

       if i in j:

           count += 1

   print(count)
```