

```
\set ON_ERROR_STOP 1
```

```
BEGIN;
```

```
CREATE TABLE alternative_release ( -- replicate
```

```
  id          SERIAL, -- PK
```

```
  gid         UUID NOT NULL,
```

```
  release     INTEGER NOT NULL, -- references release.id
```

```
  name        VARCHAR,
```

```
  artist_credit INTEGER, -- references artist_credit.id
```

```
  type        INTEGER NOT NULL, -- references
```

```
alternative_release_type.id
```

```
  language    INTEGER NOT NULL, -- references language.id
```

```
  script      INTEGER NOT NULL, -- references script.id
```

```
  comment     VARCHAR(255) NOT NULL DEFAULT ''
```

```
  CHECK (name != '')
```

```
);
```

```
CREATE TABLE alternative_release_type ( -- replicate
```

```
  id          SERIAL, -- PK
```

```
  name        TEXT NOT NULL,
```

```
  parent      INTEGER, -- references alternative_release_type.id
```

```
  child_order INTEGER NOT NULL DEFAULT 0,
```

```
  description TEXT,
```

```
  gid         UUID NOT NULL
```

```
);
```

```
CREATE TABLE alternative_medium ( -- replicate
```

```
  id          SERIAL, -- PK
```

```
  medium      INTEGER NOT NULL, -- FK, references medium.id
```

```
  alternative_release INTEGER NOT NULL, -- references
```

```
alternative_release.id
```

```
  name        VARCHAR
```

```
  CHECK (name != '')
```

```
);
```

```
CREATE TABLE alternative_track ( -- replicate
```

```
  id          SERIAL, -- PK
```

```
  name        VARCHAR,
```

```
  artist_credit INTEGER, -- references artist_credit.id
```

```
  ref_count   INTEGER NOT NULL DEFAULT 0
```

```
  CHECK (name != '' AND (name IS NOT NULL OR artist_credit IS NOT  
NULL))
```

```
);
```

```

CREATE TABLE alternative_medium_track ( -- replicate
    alternative_medium      INTEGER NOT NULL, -- PK, references
alternative_medium.id
    track                    INTEGER NOT NULL, -- PK, references track.id
    alternative_track        INTEGER NOT NULL -- references
alternative_track.id
);

```

```

CREATE TABLE annotation ( -- replicate (verbose)
    id          SERIAL,
    editor       INTEGER NOT NULL, -- references editor.id
    text         TEXT,
    changelog    VARCHAR(255),
    created      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE application
(
    id          SERIAL,
    owner       INTEGER NOT NULL, -- references editor.id
    name        TEXT NOT NULL,
    oauth_id    TEXT NOT NULL,
    oauth_secret TEXT NOT NULL,
    oauth_redirect_uri TEXT
);

```

```

CREATE TABLE area_type ( -- replicate
    id          SERIAL, -- PK
    name        VARCHAR(255) NOT NULL,
    parent      INTEGER, -- references area_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid         uuid NOT NULL
);

```

```

CREATE TABLE area ( -- replicate (verbose)
    id          SERIAL, -- PK
    gid         uuid NOT NULL,
    name        VARCHAR NOT NULL,
    type        INTEGER, -- references area_type.id
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>=0),

```

```

last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
begin_date_year  SMALLINT,
begin_date_month SMALLINT,
begin_date_day   SMALLINT,
end_date_year    SMALLINT,
end_date_month   SMALLINT,
end_date_day     SMALLINT,
ended            BOOLEAN NOT NULL DEFAULT FALSE
CHECK (
  (
    -- If any end date fields are not null, then ended must be true
    (end_date_year IS NOT NULL OR
     end_date_month IS NOT NULL OR
     end_date_day IS NOT NULL) AND
    ended = TRUE
  ) OR (
    -- Otherwise, all end date fields must be null
    (end_date_year IS NULL AND
     end_date_month IS NULL AND
     end_date_day IS NULL)
  )
),
comment         VARCHAR(255) NOT NULL DEFAULT ''
);

```

```

CREATE TABLE area_gid_redirect ( -- replicate (verbose)
  gid          UUID NOT NULL, -- PK
  new_id       INTEGER NOT NULL, -- references area.id
  created      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE area_alias_type ( -- replicate
  id          SERIAL, -- PK,
  name        TEXT NOT NULL,
  parent      INTEGER, -- references area_alias_type.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);

```

```

CREATE TABLE area_alias ( -- replicate (verbose)
  id          SERIAL, --PK
  area        INTEGER NOT NULL, -- references area.id

```

```

name          VARCHAR NOT NULL,
locale        TEXT,
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>=0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
type          INTEGER, -- references area_alias_type.id
sort_name     VARCHAR NOT NULL,
begin_date_year  SMALLINT,
begin_date_month SMALLINT,
begin_date_day   SMALLINT,
end_date_year    SMALLINT,
end_date_month   SMALLINT,
end_date_day     SMALLINT,
primary_for_locale BOOLEAN NOT NULL DEFAULT false,
ended          BOOLEAN NOT NULL DEFAULT FALSE
CHECK (
  (
    -- If any end date fields are not null, then ended must be true
    (end_date_year IS NOT NULL OR
     end_date_month IS NOT NULL OR
     end_date_day IS NOT NULL) AND
    ended = TRUE
  ) OR (
    -- Otherwise, all end date fields must be null
    (end_date_year IS NULL AND
     end_date_month IS NULL AND
     end_date_day IS NULL)
  )
),
  CONSTRAINT primary_check
    CHECK ((locale IS NULL AND primary_for_locale IS FALSE) OR
(locale IS NOT NULL)));

```

```

CREATE TABLE area_annotation ( -- replicate (verbose)
  area      INTEGER NOT NULL, -- PK, references area.id
  annotation INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE area_attribute_type ( -- replicate (verbose)
  id          SERIAL, -- PK
  name        VARCHAR(255) NOT NULL,
  comment     VARCHAR(255) NOT NULL DEFAULT "",
  free_text   BOOLEAN NOT NULL,

```

```

    parent      INTEGER, -- references area_attribute_type.id
    child_order  INTEGER NOT NULL DEFAULT 0,
    description  TEXT,
    gid          uuid NOT NULL
);

```

```

CREATE TABLE area_attribute_type_allowed_value ( -- replicate (verbose)
    id          SERIAL, -- PK
              area_attribute_type  INTEGER NOT NULL, -- references
area_attribute_type.id
    value       TEXT,
              parent              INTEGER, -- references
area_attribute_type_allowed_value.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid         uuid NOT NULL
);

```

```

CREATE TABLE area_attribute ( -- replicate (verbose)
    id          SERIAL, -- PK
    area        INTEGER NOT NULL, -- references area.id
    area_attribute_type      INTEGER NOT NULL, -- references
area_attribute_type.id
    area_attribute_type_allowed_value  INTEGER, -- references
area_attribute_type_allowed_value.id
    area_attribute_text      TEXT
    CHECK (
        (area_attribute_type_allowed_value IS NULL AND area_attribute_text IS
NOT NULL)
        OR
        (area_attribute_type_allowed_value IS NOT NULL AND
area_attribute_text IS NULL)
    )
);

```

```

CREATE TABLE area_containment (
    descendant  INTEGER NOT NULL, -- PK, references area.id
    parent      INTEGER NOT NULL, -- PK, references area.id
    depth       SMALLINT NOT NULL
);

```

```

CREATE TABLE area_tag ( -- replicate (verbose)
    area        INTEGER NOT NULL, -- PK, references area.id

```

```

tag          INTEGER NOT NULL, -- PK, references tag.id
count        INTEGER NOT NULL,
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE area_tag_raw (
  area        INTEGER NOT NULL, -- PK, references area.id
  editor       INTEGER NOT NULL, -- PK, references editor.id
  tag         INTEGER NOT NULL, -- PK, references tag.id
  is_upvote    BOOLEAN NOT NULL DEFAULT TRUE
);

CREATE TABLE artist ( -- replicate (verbose)
  id           SERIAL,
  gid          UUID NOT NULL,
  name         VARCHAR NOT NULL,
  sort_name    VARCHAR NOT NULL,
  begin_date_year  SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day   SMALLINT,
  end_date_year    SMALLINT,
  end_date_month   SMALLINT,
  end_date_day     SMALLINT,
  type            INTEGER, -- references artist_type.id
  area            INTEGER, -- references area.id
  gender          INTEGER, -- references gender.id
  comment         VARCHAR(255) NOT NULL DEFAULT "",
  edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  ended           BOOLEAN NOT NULL DEFAULT FALSE
  CONSTRAINT artist_ended_check CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
       end_date_month IS NOT NULL OR
       end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND
       end_date_month IS NULL AND
       end_date_day IS NULL)
    )
  )
);

```

```

    )
  ),
  begin_area      INTEGER, -- references area.id
  end_area        INTEGER -- references area.id
);

```

```

CREATE TABLE artist_alias_type ( -- replicate
  id          SERIAL,
  name        TEXT NOT NULL,
  parent       INTEGER, -- references artist_alias_type.id
  child_order  INTEGER NOT NULL DEFAULT 0,
  description   TEXT,
  gid          uuid NOT NULL
);

```

```

CREATE TABLE artist_alias ( -- replicate (verbose)
  id          SERIAL,
  artist       INTEGER NOT NULL, -- references artist.id
  name         VARCHAR NOT NULL,
  locale       TEXT,
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type          INTEGER, -- references artist_alias_type.id
  sort_name     VARCHAR NOT NULL,
  begin_date_year  SMALLINT,
  begin_date_month  SMALLINT,
  begin_date_day   SMALLINT,
  end_date_year    SMALLINT,
  end_date_month   SMALLINT,
  end_date_day     SMALLINT,
  primary_for_locale BOOLEAN NOT NULL DEFAULT false,
  ended           BOOLEAN NOT NULL DEFAULT FALSE
  CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
        end_date_month IS NOT NULL OR
        end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND

```

```

        end_date_month IS NULL AND
        end_date_day IS NULL)
    ),
    CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
    CONSTRAINT search_hints_are_empty
    CHECK (
        (type <> 3) OR (
            type = 3 AND sort_name = name AND
            begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
            end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
            primary_for_locale IS FALSE AND locale IS NULL
        )
    )
);

```

```

CREATE TABLE artist_annotation ( -- replicate (verbose)
    artist      INTEGER NOT NULL, -- PK, references artist.id
    annotation   INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE artist_attribute_type ( -- replicate (verbose)
    id          SERIAL, -- PK
    name        VARCHAR(255) NOT NULL,
    comment     VARCHAR(255) NOT NULL DEFAULT "",
    free_text   BOOLEAN NOT NULL,
    parent      INTEGER, -- references artist_attribute_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid         uuid NOT NULL
);

```

```

CREATE TABLE artist_attribute_type_allowed_value ( -- replicate (verbose)
    id          SERIAL, -- PK
    artist_attribute_type INTEGER NOT NULL, -- references
artist_attribute_type.id
    value       TEXT,
    parent      INTEGER, -- references
artist_attribute_type_allowed_value.id
    child_order INTEGER NOT NULL DEFAULT 0,

```



```

description      TEXT,
gid              uuid NOT NULL
);

CREATE TABLE artist_attribute ( -- replicate (verbose)
  id              SERIAL, -- PK
  artist          INTEGER NOT NULL, -- references artist.id
  artist_attribute_type      INTEGER NOT NULL, -- references
artist_attribute_type.id
  artist_attribute_type_allowed_value  INTEGER, -- references
artist_attribute_type_allowed_value.id
  artist_attribute_text      TEXT
  CHECK (
    (artist_attribute_type_allowed_value IS NULL AND artist_attribute_text
IS NOT NULL)
    OR
    (artist_attribute_type_allowed_value IS NOT NULL AND
artist_attribute_text IS NULL)
  )
);

CREATE TABLE artist_ipi ( -- replicate (verbose)
  artist          INTEGER NOT NULL, -- PK, references artist.id
  ipi             CHAR(11) NOT NULL CHECK (ipi ~ E'^\\d{11}$'), -- PK
  edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  created         TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE artist_isni ( -- replicate (verbose)
  artist          INTEGER NOT NULL, -- PK, references artist.id
  isni            CHAR(16) NOT NULL CHECK (isni ~ E'^\\d{15}[\\dX]$'), -- PK
  edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  created         TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE artist_meta ( -- replicate
  id              INTEGER NOT NULL, -- PK, references artist.id CASCADE
  rating          SMALLINT CHECK (rating >= 0 AND rating <= 100),
  rating_count    INTEGER
);

```

```
CREATE TABLE artist_tag ( -- replicate (verbose)
  artist      INTEGER NOT NULL, -- PK, references artist.id
  tag         INTEGER NOT NULL, -- PK, references tag.id
  count       INTEGER NOT NULL,
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE artist_rating_raw
(
  artist      INTEGER NOT NULL, -- PK, references artist.id
  editor      INTEGER NOT NULL, -- PK, references editor.id
  rating      SMALLINT NOT NULL CHECK (rating >= 0 AND rating <= 100)
);
```

```
CREATE TABLE artist_tag_raw
(
  artist      INTEGER NOT NULL, -- PK, references artist.id
  editor      INTEGER NOT NULL, -- PK, references editor.id
  tag         INTEGER NOT NULL, -- PK, references tag.id
  is_upvote   BOOLEAN NOT NULL DEFAULT TRUE
);
```

```
CREATE TABLE artist_credit ( -- replicate
  id          SERIAL,
  name        VARCHAR NOT NULL,
  artist_count SMALLINT NOT NULL,
  ref_count   INTEGER DEFAULT 0,
  created     TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  gid         UUID NOT NULL
);
```

```
CREATE TABLE artist_credit_gid_redirect ( -- replicate (verbose)
  gid         UUID NOT NULL, -- PK
  new_id      INTEGER NOT NULL, -- references artist_credit.id
  created     TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE artist_credit_name ( -- replicate (verbose)
  artist_credit INTEGER NOT NULL, -- PK, references artist_credit.id
  CASCADE
  position      SMALLINT NOT NULL, -- PK
```

```

    artist      INTEGER NOT NULL, -- references artist.id CASCADE
    name        VARCHAR NOT NULL,
    join_phrase  TEXT NOT NULL DEFAULT ''
);

CREATE TABLE artist_gid_redirect ( -- replicate (verbose)
    gid         UUID NOT NULL, -- PK
    new_id      INTEGER NOT NULL, -- references artist.id
    created     TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE artist_type ( -- replicate
    id          SERIAL,
    name        VARCHAR(255) NOT NULL,
    parent      INTEGER, -- references artist_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description  TEXT,
    gid         uuid NOT NULL
);

CREATE TABLE artist_release (
    -- is_track_artist is TRUE only if the artist came from a track
    -- AC and does not also appear in the release AC. Track artists
    -- that appear in the release AC are not stored.
    is_track_artist    BOOLEAN NOT NULL,
    artist             INTEGER NOT NULL, -- references artist.id,
    CASCADE
    first_release_date    INTEGER,
    catalog_numbers       TEXT[],
    country_code          CHAR(2),
    barcode               BIGINT,
    -- Prior to adding these materialized tables, we'd order releases
    -- by name only if all other attributes were equal. It's not too
    -- common that an artist will have tons of releases with no dates,
    -- catalog numbers, countries, or barcodes (though it can be seen
    -- on some big composers). As a compromise between dropping the
    -- name sorting and having to store the entire name here (which,
    -- as a reminder, is duplicated for every artist on the release),
    -- we only store the first character of the name for sorting.
    sort_character        CHAR(1) COLLATE musicbrainz NOT NULL,
    release               INTEGER NOT NULL -- references release.id,
    CASCADE
) PARTITION BY LIST (is_track_artist);

```

```
CREATE TABLE artist_release_nonva
PARTITION OF artist_release FOR VALUES IN (FALSE);
```

```
CREATE TABLE artist_release_va
PARTITION OF artist_release FOR VALUES IN (TRUE);
```

```
-- The set of triggers keeping the artist_release table up-to-date
-- don't update the table directly. The query to do that for a particular
-- release can be moderately heavy if there are a lot of tracks, so it
-- would degrade performance if identical updates to the same release
-- were triggered many times in the same transaction (which is very
-- easy to trigger when adding, editing, or removing tracks). The
-- strategy we use is to instead push release IDs that need updating
-- to the artist_release_pending_update table, and perform the
-- actual updates in a DEFERRED trigger at the end of the transaction.
-- (For where this happens, see the apply_*_pending_updates functions.)
```

```
CREATE TABLE artist_release_pending_update (
    release INTEGER NOT NULL
);
```

```
CREATE TABLE artist_release_group (
    -- See comment for artist_release.is_track_artist.
    is_track_artist          BOOLEAN NOT NULL,
    artist                   INTEGER NOT NULL, -- references artist.id,
    CASCADE
    unofficial               BOOLEAN NOT NULL,
    primary_type             SMALLINT,
    secondary_types          SMALLINT[],
    first_release_date       INTEGER,
    -- See comment for artist_release.sort_character.
    sort_character           CHAR(1) COLLATE musicbrainz NOT NULL,
    release_group            INTEGER NOT NULL -- references
    release_group.id, CASCADE
) PARTITION BY LIST (is_track_artist);
```

```
CREATE TABLE artist_release_group_nonva
PARTITION OF artist_release_group FOR VALUES IN (FALSE);
```

```
CREATE TABLE artist_release_group_va
PARTITION OF artist_release_group FOR VALUES IN (TRUE);
```

```
-- Please see the comment above artist_release_pending_update
```

-- (the same idea applies).

```
CREATE TABLE artist_release_group_pending_update (  
  release_group INTEGER NOT NULL  
);
```

```
CREATE TABLE autoeditor_election
```

```
(  
  id          SERIAL,  
  candidate   INTEGER NOT NULL, -- references editor.id  
  proposer    INTEGER NOT NULL, -- references editor.id  
  seconder_1  INTEGER, -- references editor.id  
  seconder_2  INTEGER, -- references editor.id  
  status      INTEGER NOT NULL DEFAULT 1  
              CHECK (status IN (1,2,3,4,5,6)),  
              -- 1 : has proposer  
              -- 2 : has seconder_1  
              -- 3 : has seconder_2 (voting open)  
              -- 4 : accepted!  
              -- 5 : rejected  
              -- 6 : cancelled (by proposer)  
  yes_votes   INTEGER NOT NULL DEFAULT 0,  
  no_votes    INTEGER NOT NULL DEFAULT 0,  
  propose_time  TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT  
NOW(),  
  open_time    TIMESTAMP WITH TIME ZONE,  
  close_time   TIMESTAMP WITH TIME ZONE  
);
```

```
CREATE TABLE autoeditor_election_vote
```

```
(  
  id          SERIAL,  
              autoeditor_election  INTEGER  NOT  NULL,  --  references  
autoeditor_election.id  
  voter       INTEGER NOT NULL, -- references editor.id  
  vote        INTEGER NOT NULL CHECK (vote IN (-1,0,1)),  
  vote_time   TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT  
NOW()  
);
```

```
CREATE TABLE cdtoc ( -- replicate
```

```
  id          SERIAL,  
  discid      CHAR(28) NOT NULL,  
  freedb_id   CHAR(8) NOT NULL,
```

```

    track_count    INTEGER NOT NULL,
    leadout_offset INTEGER NOT NULL,
    track_offset   INTEGER[] NOT NULL,
    created        TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE cdtoc_raw ( -- replicate
    id          SERIAL, -- PK
    release     INTEGER NOT NULL, -- references release_raw.id
    discid      CHAR(28) NOT NULL,
    track_count INTEGER NOT NULL,
    leadout_offset INTEGER NOT NULL,
    track_offset INTEGER[] NOT NULL
);

```

```

CREATE TABLE country_area ( -- replicate (verbose)
    area        INTEGER -- PK, references area.id
);

```

```

CREATE TABLE deleted_entity (
    gid UUID NOT NULL, -- PK
    data JSONB NOT NULL,
    deleted_at timestamptz NOT NULL DEFAULT now()
);

```

```

CREATE TABLE edit
(
    id          SERIAL,
    editor      INTEGER NOT NULL, -- references editor.id
    type       SMALLINT NOT NULL,
    status     SMALLINT NOT NULL,
    autoedit   SMALLINT NOT NULL DEFAULT 0,
    open_time  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    close_time TIMESTAMP WITH TIME ZONE,
    expire_time TIMESTAMP WITH TIME ZONE NOT NULL,
    language   INTEGER, -- references language.id
    quality    SMALLINT NOT NULL DEFAULT 1
);

```

```

CREATE TABLE edit_data
(
    edit      INTEGER NOT NULL, -- PK, references edit.id
    data      JSONB NOT NULL
);

```

```
);
```

```
CREATE TABLE edit_note
```

```
(  
  id          SERIAL,  
  editor      INTEGER NOT NULL, -- references editor.id  
  edit        INTEGER NOT NULL, -- references edit.id  
  text        TEXT NOT NULL,  
  post_time   TIMESTAMP WITH TIME ZONE DEFAULT NOW()  
);
```

```
CREATE TABLE edit_note_change
```

```
(  
  id          SERIAL, -- PK  
  status      edit_note_status,  
  edit_note   INTEGER NOT NULL, -- references edit_note.id  
  change_editor INTEGER NOT NULL, -- references editor.id  
  change_time TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  old_note    TEXT NOT NULL,  
  new_note    TEXT NOT NULL,  
  reason      TEXT NOT NULL DEFAULT ''  
);
```

```
CREATE TABLE edit_note_recipient (
```

```
  recipient   INTEGER NOT NULL, -- PK, references editor.id  
  edit_note   INTEGER NOT NULL -- PK, references edit_note.id  
);
```

```
CREATE TABLE edit_area
```

```
(  
  edit        INTEGER NOT NULL, -- PK, references edit.id  
  area        INTEGER NOT NULL -- PK, references area.id CASCADE  
);
```

```
CREATE TABLE edit_artist
```

```
(  
  edit        INTEGER NOT NULL, -- PK, references edit.id  
  artist      INTEGER NOT NULL, -- PK, references artist.id CASCADE  
  status      SMALLINT NOT NULL -- materialized from edit.status  
);
```

```
CREATE TABLE edit_event
```

```
(
```

```
    edit          INTEGER NOT NULL, -- PK, references edit.id
    event          INTEGER NOT NULL -- PK, references event.id CASCADE
);
```

```
CREATE TABLE edit_genre
(
    edit          INTEGER NOT NULL, -- PK, references edit.id
    genre          INTEGER NOT NULL -- PK, references genre.id CASCADE
);
```

```
CREATE TABLE edit_instrument
(
    edit          INTEGER NOT NULL, -- PK, references edit.id
    instrument      INTEGER NOT NULL -- PK, references instrument.id
    CASCADE
);
```

```
CREATE TABLE edit_label
(
    edit          INTEGER NOT NULL, -- PK, references edit.id
    label          INTEGER NOT NULL, -- PK, references label.id CASCADE
    status          SMALLINT NOT NULL -- materialized from edit.status
);
```

```
CREATE TABLE edit_mood
(
    edit          INTEGER NOT NULL, -- PK, references edit.id
    mood          INTEGER NOT NULL -- PK, references mood.id CASCADE
);
```

```
CREATE TABLE edit_place
(
    edit          INTEGER NOT NULL, -- PK, references edit.id
    place          INTEGER NOT NULL -- PK, references place.id CASCADE
);
```

```
CREATE TABLE edit_release
(
    edit          INTEGER NOT NULL, -- PK, references edit.id
    release          INTEGER NOT NULL -- PK, references release.id CASCADE
);
```

```
CREATE TABLE edit_release_group
```



```
(
  edit          INTEGER NOT NULL, -- PK, references edit.id
  release_group  INTEGER NOT NULL -- PK, references release_group.id
  CASCADE
);
```

```
CREATE TABLE edit_recording
(
  edit          INTEGER NOT NULL, -- PK, references edit.id
  recording      INTEGER NOT NULL -- PK, references recording.id
  CASCADE
);
```

```
CREATE TABLE edit_series
(
  edit          INTEGER NOT NULL, -- PK, references edit.id
  series        INTEGER NOT NULL -- PK, references series.id CASCADE
);
```

```
CREATE TABLE edit_work
(
  edit          INTEGER NOT NULL, -- PK, references edit.id
  work          INTEGER NOT NULL -- PK, references work.id CASCADE
);
```

```
CREATE TABLE edit_url
(
  edit          INTEGER NOT NULL, -- PK, references edit.id
  url           INTEGER NOT NULL -- PK, references url.id CASCADE
);
```

```
CREATE TABLE editor
(
  id            SERIAL,
  name          VARCHAR(64) NOT NULL,
  privs         INTEGER DEFAULT 0,
  email         VARCHAR(64) DEFAULT NULL,
  website       VARCHAR(255) DEFAULT NULL,
  bio           TEXT DEFAULT NULL,
  member_since  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  email_confirm_date  TIMESTAMP WITH TIME ZONE,
  last_login_date  TIMESTAMP WITH TIME ZONE DEFAULT now(),
  last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
```

```
birth_date    DATE,
gender        INTEGER, -- references gender.id
area          INTEGER, -- references area.id
password      VARCHAR(128) NOT NULL,
ha1           CHAR(32) NOT NULL,
deleted       BOOLEAN NOT NULL DEFAULT FALSE
);
```

```
CREATE TABLE old_editor_name (
  name  VARCHAR(64) NOT NULL
);
```

```
CREATE TABLE editor_language (
  editor  INTEGER NOT NULL, -- PK, references editor.id
  language INTEGER NOT NULL, -- PK, references language.id
  fluency FLUENCY NOT NULL
);
```

```
CREATE TABLE editor_preference
(
  id          SERIAL,
  editor      INTEGER NOT NULL, -- references editor.id
  name        VARCHAR(50) NOT NULL,
  value       VARCHAR(100) NOT NULL
);
```

```
CREATE TABLE editor_subscribe_artist
(
  id          SERIAL,
  editor      INTEGER NOT NULL, -- references editor.id
  artist      INTEGER NOT NULL, -- references artist.id
  last_edit_sent INTEGER NOT NULL -- references edit.id
);
```

```
CREATE TABLE editor_subscribe_artist_deleted
(
  editor INTEGER NOT NULL, -- PK, references editor.id
  gid    UUID NOT NULL, -- PK, references deleted_entity.gid
  deleted_by INTEGER NOT NULL -- references edit.id
);
```

```
CREATE TABLE editor_subscribe_collection
(
```

```

    id          SERIAL,
    editor       INTEGER NOT NULL,          -- references editor.id
    collection   INTEGER NOT NULL,          -- weakly references
editor_collection.id
    last_edit_sent  INTEGER NOT NULL,        -- weakly references edit.id
    available      BOOLEAN NOT NULL DEFAULT TRUE,
    last_seen_name  VARCHAR(255)
);

```

```

CREATE TABLE editor_subscribe_label
(
    id          SERIAL,
    editor       INTEGER NOT NULL, -- references editor.id
    label        INTEGER NOT NULL, -- references label.id
    last_edit_sent  INTEGER NOT NULL -- references edit.id
);

```

```

CREATE TABLE editor_subscribe_label_deleted
(
    editor INTEGER NOT NULL, -- PK, references editor.id
    gid UUID NOT NULL, -- PK, references deleted_entity.gid
    deleted_by INTEGER NOT NULL -- references edit.id
);

```

```

CREATE TABLE editor_subscribe_editor
(
    id          SERIAL,
    editor       INTEGER NOT NULL, -- references editor.id (the one who
has subscribed)
    subscribed_editor  INTEGER NOT NULL, -- references editor.id (the one
being subscribed)
    last_edit_sent  INTEGER NOT NULL -- weakly references edit.id
);

```

```

CREATE TABLE editor_subscribe_series
(
    id          SERIAL,
    editor       INTEGER NOT NULL, -- references editor.id
    series        INTEGER NOT NULL, -- references series.id
    last_edit_sent  INTEGER NOT NULL -- references edit.id
);

```

```

CREATE TABLE editor_subscribe_series_deleted

```

```

(
  editor      INTEGER NOT NULL, -- PK, references editor.id
  gid         UUID NOT NULL, -- PK, references deleted_entity.gid
  deleted_by  INTEGER NOT NULL -- references edit.id
);

CREATE TABLE event ( -- replicate (verbose)
  id          SERIAL,
  gid         UUID NOT NULL,
  name        VARCHAR NOT NULL,
  begin_date_year  SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day   SMALLINT,
  end_date_year    SMALLINT,
  end_date_month   SMALLINT,
  end_date_day     SMALLINT,
  time           TIME WITHOUT TIME ZONE,
  type           INTEGER, -- references event_type.id
  cancelled      BOOLEAN NOT NULL DEFAULT FALSE,
  setlist        TEXT,
  comment        VARCHAR(255) NOT NULL DEFAULT "",
  edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  ended          BOOLEAN NOT NULL DEFAULT FALSE
  CONSTRAINT event_ended_check CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
       end_date_month IS NOT NULL OR
       end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND
       end_date_month IS NULL AND
       end_date_day IS NULL)
    )
  )
);

```

```

CREATE TABLE event_meta ( -- replicate
  id          INTEGER NOT NULL, -- PK, references event.id CASCADE

```

```

rating          SMALLINT CHECK (rating >= 0 AND rating <= 100),
rating_count    INTEGER,
event_art_presence event_art_presence NOT NULL DEFAULT 'absent'
);

```

```

CREATE TABLE event_rating_raw (
  event          INTEGER NOT NULL, -- PK, references event.id
  editor         INTEGER NOT NULL, -- PK, references editor.id
  rating         SMALLINT NOT NULL CHECK (rating >= 0 AND rating <= 100)
);

```

```

CREATE TABLE event_tag_raw (
  event          INTEGER NOT NULL, -- PK, references event.id
  editor         INTEGER NOT NULL, -- PK, references editor.id
  tag            INTEGER NOT NULL, -- PK, references tag.id
  is_upvote      BOOLEAN NOT NULL DEFAULT TRUE
);

```

```

CREATE TABLE event_alias_type ( -- replicate
  id             SERIAL,
  name           TEXT NOT NULL,
  parent         INTEGER, -- references event_alias_type.id
  child_order    INTEGER NOT NULL DEFAULT 0,
  description     TEXT,
  gid            uuid NOT NULL
);

```

```

CREATE TABLE event_alias ( -- replicate (verbose)
  id             SERIAL,
  event          INTEGER NOT NULL, -- references event.id
  name           VARCHAR NOT NULL,
  locale         TEXT,
  edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type           INTEGER, -- references event_alias_type.id
  sort_name      VARCHAR NOT NULL,
  begin_date_year SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day  SMALLINT,
  end_date_year   SMALLINT,
  end_date_month  SMALLINT,
  end_date_day    SMALLINT,

```

```

primary_for_locale BOOLEAN NOT NULL DEFAULT false,
ended              BOOLEAN NOT NULL DEFAULT FALSE
CHECK (
    (
        -- If any end date fields are not null, then ended must be true
        (end_date_year IS NOT NULL OR
         end_date_month IS NOT NULL OR
         end_date_day IS NOT NULL) AND
        ended = TRUE
    ) OR (
        -- Otherwise, all end date fields must be null
        (end_date_year IS NULL AND
         end_date_month IS NULL AND
         end_date_day IS NULL)
    )
),
    CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
    CONSTRAINT search_hints_are_empty
    CHECK (
        (type <> 2) OR (
            type = 2 AND sort_name = name AND
                begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
                end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
                primary_for_locale IS FALSE AND locale IS NULL
        )
    )
);

```

```

CREATE TABLE event_annotation ( -- replicate (verbose)
    event          INTEGER NOT NULL, -- PK, references event.id
    annotation      INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE event_attribute_type ( -- replicate (verbose)
    id             SERIAL, -- PK
    name           VARCHAR(255) NOT NULL,
    comment        VARCHAR(255) NOT NULL DEFAULT "",
    free_text      BOOLEAN NOT NULL,
    parent         INTEGER, -- references event_attribute_type.id
    child_order    INTEGER NOT NULL DEFAULT 0,

```

```

        description    TEXT,
        gid            uuid NOT NULL
    );

```

```

CREATE TABLE event_attribute_type_allowed_value ( -- replicate (verbose)
    id                SERIAL, -- PK
        event_attribute_type            INTEGER NOT NULL, -- references
event_attribute_type.id
    value            TEXT,
        parent                            INTEGER, -- references
event_attribute_type_allowed_value.id
    child_order        INTEGER NOT NULL DEFAULT 0,
    description        TEXT,
    gid                uuid NOT NULL
);

```

```

CREATE TABLE event_attribute ( -- replicate (verbose)
    id                SERIAL, -- PK
    event            INTEGER NOT NULL, -- references event.id
        event_attribute_type            INTEGER NOT NULL, -- references
event_attribute_type.id
        event_attribute_type_allowed_value    INTEGER, -- references
event_attribute_type_allowed_value.id
    event_attribute_text    TEXT
    CHECK (
        (event_attribute_type_allowed_value IS NULL AND event_attribute_text
IS NOT NULL)
        OR
            (event_attribute_type_allowed_value IS NOT NULL AND
event_attribute_text IS NULL)
    )
);

```

```

CREATE TABLE event_gid_redirect ( -- replicate (verbose)
    gid            UUID NOT NULL, -- PK
    new_id        INTEGER NOT NULL, -- references event.id
    created        TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE event_tag ( -- replicate (verbose)
    event        INTEGER NOT NULL, -- PK, references event.id
    tag        INTEGER NOT NULL, -- PK, references tag.id
    count        INTEGER NOT NULL,

```

```
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE event_type ( -- replicate
    id              SERIAL,
    name            VARCHAR(255) NOT NULL,
    parent          INTEGER, -- references event_type.id
    child_order     INTEGER NOT NULL DEFAULT 0,
    description     TEXT,
    gid             uuid NOT NULL
);
```

```
CREATE TABLE release_first_release_date (
    release    INTEGER NOT NULL, -- PK, references release.id CASCADE
    year       SMALLINT,
    month      SMALLINT,
    day        SMALLINT
);
```

```
CREATE TABLE recording_first_release_date (
    recording    INTEGER NOT NULL, -- PK, references recording.id CASCADE
    year         SMALLINT,
    month        SMALLINT,
    day          SMALLINT
);
```

```
CREATE TABLE gender ( -- replicate
    id          SERIAL,
    name        VARCHAR(255) NOT NULL,
    parent      INTEGER, -- references gender.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid         uuid NOT NULL
);
```

```
CREATE TABLE genre ( -- replicate (verbose)
    id          SERIAL, -- PK
    gid         UUID NOT NULL,
    name        VARCHAR NOT NULL,
    comment     VARCHAR(255) NOT NULL DEFAULT "",
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >=0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW()
```


);

```
CREATE TABLE genre_alias_type ( -- replicate
  id          SERIAL, -- PK,
  name        TEXT NOT NULL,
  parent      INTEGER, -- references genre_alias_type.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);
```

```
CREATE TABLE genre_alias ( -- replicate (verbose)
  id          SERIAL, --PK
  genre       INTEGER NOT NULL, -- references genre.id
  name        VARCHAR NOT NULL,
  locale      TEXT,
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type         INTEGER, -- references genre_alias_type.id
  sort_name     VARCHAR NOT NULL,
  begin_date_year  SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day   SMALLINT,
  end_date_year    SMALLINT,
  end_date_month   SMALLINT,
  end_date_day     SMALLINT,
  primary_for_locale BOOLEAN NOT NULL DEFAULT false,
  ended          BOOLEAN NOT NULL DEFAULT FALSE
  CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
      end_date_month IS NOT NULL OR
      end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND
      end_date_month IS NULL AND
      end_date_day IS NULL)
    )
  ),
```

```

        CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
        CONSTRAINT search_hints_are_empty
        CHECK (
            (type <> 2) OR (
                type = 2 AND sort_name = name AND
                begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
                end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
                primary_for_locale IS FALSE AND locale IS NULL
            )
        )
    );

```

```

CREATE TABLE genre_annotation ( -- replicate (verbose)
    genre    INTEGER NOT NULL, -- PK, references genre.id
    annotation INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE instrument_type ( -- replicate
    id        SERIAL, -- PK
    name      VARCHAR(255) NOT NULL,
    parent    INTEGER, -- references instrument_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid       uuid NOT NULL
);

```

```

CREATE TABLE instrument ( -- replicate (verbose)
    id        SERIAL, -- PK
    gid       uuid NOT NULL,
    name      VARCHAR NOT NULL,
    type      INTEGER, -- references instrument_type.id
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>=0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    comment         VARCHAR(255) NOT NULL DEFAULT "",
    description     TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE instrument_gid_redirect ( -- replicate (verbose)
    gid       UUID NOT NULL, -- PK

```

```

    new_id          INTEGER NOT NULL, -- references instrument.id
    created         TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE instrument_alias_type ( -- replicate
    id              SERIAL, -- PK,
    name            TEXT NOT NULL,
    parent          INTEGER, -- references instrument_alias_type.id
    child_order     INTEGER NOT NULL DEFAULT 0,
    description      TEXT,
    gid             uuid NOT NULL
);

```

```

CREATE TABLE instrument_alias ( -- replicate (verbose)
    id              SERIAL, --PK
    instrument       INTEGER NOT NULL, -- references instrument.id
    name            VARCHAR NOT NULL,
    locale          TEXT,
    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>=0),
    last_updated     TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    type            INTEGER, -- references instrument_alias_type.id
    sort_name        VARCHAR NOT NULL,
    begin_date_year  SMALLINT,
    begin_date_month SMALLINT,
    begin_date_day   SMALLINT,
    end_date_year    SMALLINT,
    end_date_month   SMALLINT,
    end_date_day     SMALLINT,
    primary_for_locale BOOLEAN NOT NULL DEFAULT false,
    ended            BOOLEAN NOT NULL DEFAULT FALSE
    CHECK (
        (
            -- If any end date fields are not null, then ended must be true
            (end_date_year IS NOT NULL OR
            end_date_month IS NOT NULL OR
            end_date_day IS NOT NULL) AND
            ended = TRUE
        ) OR (
            -- Otherwise, all end date fields must be null
            (end_date_year IS NULL AND
            end_date_month IS NULL AND
            end_date_day IS NULL)

```

```

    )
),
    CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
    CONSTRAINT search_hints_are_empty
    CHECK (
        (type <> 2) OR (
            type = 2 AND sort_name = name AND
            begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
            end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
            primary_for_locale IS FALSE AND locale IS NULL
        )
    )
);

```

```

CREATE TABLE instrument_annotation ( -- replicate (verbose)
    instrument INTEGER NOT NULL, -- PK, references instrument.id
    annotation INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE instrument_attribute_type ( -- replicate (verbose)
    id          SERIAL, -- PK
    name        VARCHAR(255) NOT NULL,
    comment     VARCHAR(255) NOT NULL DEFAULT "",
    free_text    BOOLEAN NOT NULL,
    parent      INTEGER, -- references instrument_attribute_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description  TEXT,
    gid         uuid NOT NULL
);

```

```

CREATE TABLE instrument_attribute_type_allowed_value ( -- replicate
(verbose)
    id          SERIAL, -- PK
    instrument_attribute_type INTEGER NOT NULL, -- references
instrument_attribute_type.id
    value       TEXT,
    parent      INTEGER, -- references
instrument_attribute_type_allowed_value.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description  TEXT,

```

```

    gid                uuid NOT NULL
);

CREATE TABLE instrument_attribute ( -- replicate (verbose)
    id                SERIAL, -- PK
    instrument        INTEGER NOT NULL, -- references
instrument.id
    instrument_attribute_type    INTEGER NOT NULL, -- references
instrument_attribute_type.id
    instrument_attribute_type_allowed_value    INTEGER, -- references
instrument_attribute_type_allowed_value.id
    instrument_attribute_text    TEXT
    CHECK (
        (instrument_attribute_type_allowed_value IS NULL AND
instrument_attribute_text IS NOT NULL)
        OR
        (instrument_attribute_type_allowed_value IS NOT NULL AND
instrument_attribute_text IS NULL)
    )
);

```

```

CREATE TABLE instrument_tag ( -- replicate (verbose)
    instrument        INTEGER NOT NULL, -- PK, references instrument.id
    tag                INTEGER NOT NULL, -- PK, references tag.id
    count            INTEGER NOT NULL,
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE instrument_tag_raw (
    instrument        INTEGER NOT NULL, -- PK, references instrument.id
    editor            INTEGER NOT NULL, -- PK, references editor.id
    tag                INTEGER NOT NULL, -- PK, references tag.id
    is_upvote         BOOLEAN NOT NULL DEFAULT TRUE
);

```

```

CREATE TABLE iso_3166_1 ( -- replicate
    area    INTEGER NOT NULL, -- references area.id
    code    CHAR(2) -- PK
);

```

```

CREATE TABLE iso_3166_2 ( -- replicate
    area    INTEGER NOT NULL, -- references area.id
    code    VARCHAR(10) -- PK
);

```

```
CREATE TABLE iso_3166_3 ( -- replicate
  area    INTEGER NOT NULL, -- references area.id
  code    CHAR(4) -- PK
);
```

```
CREATE TABLE isrc ( -- replicate (verbose)
  id          SERIAL,
  recording    INTEGER NOT NULL, -- references recording.id
  isrc        CHAR(12) NOT NULL CHECK (isrc ~
E'^[A-Z]{2}[A-Z0-9]{3}[0-9]{7}$'),
  source      SMALLINT,
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  created     TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE iswc ( -- replicate (verbose)
  id SERIAL NOT NULL,
  work INTEGER NOT NULL, -- references work.id
  iswc CHARACTER(15) CHECK (iswc ~
E'^T-?\\d{3}.?\\d{3}.?\\d{3}[-.]?\\d$'),
  source SMALLINT,
  edits_pending INTEGER NOT NULL DEFAULT 0,
  created TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT now()
);
```

```
CREATE TABLE l_area_area ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references area.id
  entity1     INTEGER NOT NULL, -- references area.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order  INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_area_artist ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references area.id
```

```

    entity1          INTEGER NOT NULL, -- references artist.id
    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated     TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order       INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_event ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references area.id
    entity1         INTEGER NOT NULL, -- references event.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit  TEXT NOT NULL DEFAULT "",
    entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_genre ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references area.id
    entity1         INTEGER NOT NULL, -- references genre.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit  TEXT NOT NULL DEFAULT "",
    entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_instrument ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references area.id
    entity1         INTEGER NOT NULL, -- references instrument.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),

```

```

    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_label ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references area.id
    entity1         INTEGER NOT NULL, -- references label.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_mood ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references area.id
    entity1         INTEGER NOT NULL, -- references mood.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_place ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references area.id
    entity1         INTEGER NOT NULL, -- references place.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```



```

CREATE TABLE l_area_recording ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references area.id
  entity1     INTEGER NOT NULL, -- references recording.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_release ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references area.id
  entity1     INTEGER NOT NULL, -- references release.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_release_group ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references area.id
  entity1     INTEGER NOT NULL, -- references release_group.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_series ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id

```

```

entity0      INTEGER NOT NULL, -- references area.id
entity1      INTEGER NOT NULL, -- references series.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_url ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references area.id
entity1     INTEGER NOT NULL, -- references url.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_area_work ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references area.id
entity1     INTEGER NOT NULL, -- references work.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_artist ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references artist.id
entity1     INTEGER NOT NULL, -- references artist.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),

```

```

last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit  TEXT NOT NULL DEFAULT "",
entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_event ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references artist.id
  entity1     INTEGER NOT NULL, -- references event.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_genre ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references artist.id
  entity1     INTEGER NOT NULL, -- references genre.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_instrument ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references artist.id
  entity1     INTEGER NOT NULL, -- references instrument.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

);

```
CREATE TABLE l_artist_label ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references artist.id
  entity1     INTEGER NOT NULL, -- references label.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_artist_mood ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references artist.id
  entity1     INTEGER NOT NULL, -- references mood.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_artist_place ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references artist.id
  entity1     INTEGER NOT NULL, -- references place.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_artist_recording ( -- replicate
  id          SERIAL,
```

```

link          INTEGER NOT NULL, -- references link.id
entity0       INTEGER NOT NULL, -- references artist.id
entity1       INTEGER NOT NULL, -- references recording.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_release ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references artist.id
entity1     INTEGER NOT NULL, -- references release.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_release_group ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references artist.id
entity1     INTEGER NOT NULL, -- references release_group.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_series ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references artist.id
entity1     INTEGER NOT NULL, -- references series.id

```

```

    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated     TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order       INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_url ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references artist.id
    entity1         INTEGER NOT NULL, -- references url.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit  TEXT NOT NULL DEFAULT "",
    entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_artist_work ( -- replicate (verbose)
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references artist.id
    entity1         INTEGER NOT NULL, -- references work.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit  TEXT NOT NULL DEFAULT "",
    entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_event_event ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references event.id
    entity1         INTEGER NOT NULL, -- references event.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),

```

```
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_event_genre ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0            INTEGER NOT NULL, -- references event.id
    entity1            INTEGER NOT NULL, -- references genre.id
    edits_pending      INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated       TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order         INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit     TEXT NOT NULL DEFAULT "",
    entity1_credit     TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_event_instrument ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0            INTEGER NOT NULL, -- references event.id
    entity1            INTEGER NOT NULL, -- references instrument.id
    edits_pending      INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated       TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order         INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit     TEXT NOT NULL DEFAULT "",
    entity1_credit     TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_event_label ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0            INTEGER NOT NULL, -- references event.id
    entity1            INTEGER NOT NULL, -- references label.id
    edits_pending      INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated       TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order         INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit     TEXT NOT NULL DEFAULT "",
    entity1_credit     TEXT NOT NULL DEFAULT ""
);
```

```

CREATE TABLE l_event_mood ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references event.id
  entity1     INTEGER NOT NULL, -- references mood.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_event_place ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references event.id
  entity1     INTEGER NOT NULL, -- references place.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_event_recording ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references event.id
  entity1     INTEGER NOT NULL, -- references recording.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_event_release ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references event.id

```



```

entity1      INTEGER NOT NULL, -- references release.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order     INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_event_release_group ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references event.id
entity1     INTEGER NOT NULL, -- references release_group.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order     INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_event_series ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references event.id
entity1     INTEGER NOT NULL, -- references series.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order     INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_event_url ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references event.id
entity1     INTEGER NOT NULL, -- references url.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),

```

```

    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_event_work ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references event.id
    entity1         INTEGER NOT NULL, -- references work.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_label_label ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references label.id
    entity1         INTEGER NOT NULL, -- references label.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_genre ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references genre.id
    entity1         INTEGER NOT NULL, -- references genre.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_instrument ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references genre.id
  entity1     INTEGER NOT NULL, -- references instrument.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_label ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references genre.id
  entity1     INTEGER NOT NULL, -- references label.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_mood ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references genre.id
  entity1     INTEGER NOT NULL, -- references mood.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_place ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id

```

```

    entity0      INTEGER NOT NULL, -- references genre.id
    entity1      INTEGER NOT NULL, -- references place.id
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit TEXT NOT NULL DEFAULT "",
    entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_recording ( -- replicate
    id          SERIAL,
    link         INTEGER NOT NULL, -- references link.id
    entity0      INTEGER NOT NULL, -- references genre.id
    entity1      INTEGER NOT NULL, -- references recording.id
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit TEXT NOT NULL DEFAULT "",
    entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_release ( -- replicate
    id          SERIAL,
    link         INTEGER NOT NULL, -- references link.id
    entity0      INTEGER NOT NULL, -- references genre.id
    entity1      INTEGER NOT NULL, -- references release.id
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit TEXT NOT NULL DEFAULT "",
    entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_release_group ( -- replicate
    id          SERIAL,
    link         INTEGER NOT NULL, -- references link.id
    entity0      INTEGER NOT NULL, -- references genre.id
    entity1      INTEGER NOT NULL, -- references release_group.id
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),

```

```

last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit  TEXT NOT NULL DEFAULT "",
entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_series ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references genre.id
  entity1     INTEGER NOT NULL, -- references series.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_url ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references genre.id
  entity1     INTEGER NOT NULL, -- references url.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_genre_work ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references genre.id
  entity1     INTEGER NOT NULL, -- references work.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

);

```
CREATE TABLE l_instrument_instrument ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references instrument.id
  entity1     INTEGER NOT NULL, -- references instrument.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_instrument_label ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references instrument.id
  entity1     INTEGER NOT NULL, -- references label.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_instrument_mood ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references instrument.id
  entity1     INTEGER NOT NULL, -- references mood.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_instrument_place ( -- replicate
  id          SERIAL,
```

```

link          INTEGER NOT NULL, -- references link.id
entity0       INTEGER NOT NULL, -- references instrument.id
entity1       INTEGER NOT NULL, -- references place.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_instrument_recording ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references instrument.id
entity1     INTEGER NOT NULL, -- references recording.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_instrument_release ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references instrument.id
entity1     INTEGER NOT NULL, -- references release.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_instrument_release_group ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references instrument.id
entity1     INTEGER NOT NULL, -- references release_group.id

```

```

    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated     TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order       INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_instrument_series ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references instrument.id
    entity1         INTEGER NOT NULL, -- references series.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_instrument_url ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references instrument.id
    entity1         INTEGER NOT NULL, -- references url.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_instrument_work ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references instrument.id
    entity1         INTEGER NOT NULL, -- references work.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),

```



```
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_label_mood ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0           INTEGER NOT NULL, -- references label.id
    entity1           INTEGER NOT NULL, -- references mood.id
    edits_pending     INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order        INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_label_place ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0           INTEGER NOT NULL, -- references label.id
    entity1           INTEGER NOT NULL, -- references place.id
    edits_pending     INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order        INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_label_recording ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0           INTEGER NOT NULL, -- references label.id
    entity1           INTEGER NOT NULL, -- references recording.id
    edits_pending     INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order        INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);
```

```

CREATE TABLE l_label_release ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references label.id
  entity1     INTEGER NOT NULL, -- references release.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_label_release_group ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references label.id
  entity1     INTEGER NOT NULL, -- references release_group.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_label_series ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references label.id
  entity1     INTEGER NOT NULL, -- references series.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_label_url ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references label.id

```

```

entity1      INTEGER NOT NULL, -- references url.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_label_work ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references label.id
entity1     INTEGER NOT NULL, -- references work.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_mood_mood ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references mood.id
entity1     INTEGER NOT NULL, -- references mood.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_mood_place ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references mood.id
entity1     INTEGER NOT NULL, -- references place.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),

```

```

    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_mood_recording ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references mood.id
    entity1         INTEGER NOT NULL, -- references recording.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_mood_release ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references mood.id
    entity1         INTEGER NOT NULL, -- references release.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_mood_release_group ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references mood.id
    entity1         INTEGER NOT NULL, -- references release_group.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_mood_series ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references mood.id
  entity1     INTEGER NOT NULL, -- references series.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_mood_url ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references mood.id
  entity1     INTEGER NOT NULL, -- references url.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_mood_work ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references mood.id
  entity1     INTEGER NOT NULL, -- references work.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_place_place ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id

```

```

entity0      INTEGER NOT NULL, -- references place.id
entity1      INTEGER NOT NULL, -- references place.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_place_recording ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references place.id
entity1     INTEGER NOT NULL, -- references recording.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_place_release ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references place.id
entity1     INTEGER NOT NULL, -- references release.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_place_release_group ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references place.id
entity1     INTEGER NOT NULL, -- references release_group.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),

```

```

last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit  TEXT NOT NULL DEFAULT "",
entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_place_series ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references place.id
  entity1     INTEGER NOT NULL, -- references series.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_place_url ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references place.id
  entity1     INTEGER NOT NULL, -- references url.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_place_work ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references place.id
  entity1     INTEGER NOT NULL, -- references work.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit  TEXT NOT NULL DEFAULT "",
  entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

);

```
CREATE TABLE l_recording_recording ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references recording.id
  entity1     INTEGER NOT NULL, -- references recording.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_recording_release ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references recording.id
  entity1     INTEGER NOT NULL, -- references release.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_recording_release_group ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references recording.id
  entity1     INTEGER NOT NULL, -- references release_group.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);
```

```
CREATE TABLE l_recording_series ( -- replicate
  id          SERIAL,
```



```

link          INTEGER NOT NULL, -- references link.id
entity0       INTEGER NOT NULL, -- references recording.id
entity1       INTEGER NOT NULL, -- references series.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_recording_url ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references recording.id
entity1     INTEGER NOT NULL, -- references url.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_recording_work ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references recording.id
entity1     INTEGER NOT NULL, -- references work.id
edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_release ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references release.id
entity1     INTEGER NOT NULL, -- references release.id

```

```

    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated     TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order       INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_release_group ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references release.id
    entity1         INTEGER NOT NULL, -- references release_group.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit  TEXT NOT NULL DEFAULT "",
    entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_series ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references release.id
    entity1         INTEGER NOT NULL, -- references series.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit  TEXT NOT NULL DEFAULT "",
    entity1_credit  TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_url ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references release.id
    entity1         INTEGER NOT NULL, -- references url.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),

```

```

    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_work ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0           INTEGER NOT NULL, -- references release.id
    entity1           INTEGER NOT NULL, -- references work.id
    edits_pending     INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order        INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_group_release_group ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0           INTEGER NOT NULL, -- references release_group.id
    entity1           INTEGER NOT NULL, -- references release_group.id
    edits_pending     INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order        INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_group_series ( -- replicate
    id                SERIAL,
    link              INTEGER NOT NULL, -- references link.id
    entity0           INTEGER NOT NULL, -- references release_group.id
    entity1           INTEGER NOT NULL, -- references series.id
    edits_pending     INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order        INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit    TEXT NOT NULL DEFAULT "",
    entity1_credit    TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_group_url ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references release_group.id
  entity1     INTEGER NOT NULL, -- references url.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_release_group_work ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references release_group.id
  entity1     INTEGER NOT NULL, -- references work.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_series_series ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references series.id
  entity1     INTEGER NOT NULL, -- references series.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  link_order    INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
  entity0_credit TEXT NOT NULL DEFAULT "",
  entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_series_url ( -- replicate
  id          SERIAL,
  link        INTEGER NOT NULL, -- references link.id
  entity0     INTEGER NOT NULL, -- references series.id

```

```

entity1      INTEGER NOT NULL, -- references url.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order     INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_series_work ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references series.id
entity1     INTEGER NOT NULL, -- references work.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order     INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_url_url ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references url.id
entity1     INTEGER NOT NULL, -- references url.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
link_order     INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
entity0_credit TEXT NOT NULL DEFAULT "",
entity1_credit TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_url_work ( -- replicate
id          SERIAL,
link        INTEGER NOT NULL, -- references link.id
entity0     INTEGER NOT NULL, -- references url.id
entity1     INTEGER NOT NULL, -- references work.id
edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),

```

```

    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE l_work_work ( -- replicate
    id              SERIAL,
    link            INTEGER NOT NULL, -- references link.id
    entity0         INTEGER NOT NULL, -- references work.id
    entity1         INTEGER NOT NULL, -- references work.id
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    link_order      INTEGER NOT NULL DEFAULT 0 CHECK (link_order >= 0),
    entity0_credit   TEXT NOT NULL DEFAULT "",
    entity1_credit   TEXT NOT NULL DEFAULT ""
);

```

```

CREATE TABLE label ( -- replicate (verbose)
    id              SERIAL,
    gid            UUID NOT NULL,
    name           VARCHAR NOT NULL,
    begin_date_year SMALLINT,
    begin_date_month SMALLINT,
    begin_date_day  SMALLINT,
    end_date_year   SMALLINT,
    end_date_month  SMALLINT,
    end_date_day    SMALLINT,
    label_code      INTEGER,
    type            INTEGER, -- references label_type.id
    area           INTEGER, -- references area.id
    comment         VARCHAR(255) NOT NULL DEFAULT "",
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    ended          BOOLEAN NOT NULL DEFAULT FALSE
    CONSTRAINT label_ended_check CHECK (
        (
            -- If any end date fields are not null, then ended must be true
            (end_date_year IS NOT NULL OR
            end_date_month IS NOT NULL OR
            end_date_day IS NOT NULL) AND
            ended = TRUE

```

```

    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND
       end_date_month IS NULL AND
       end_date_day IS NULL)
    )
  )
);

```

```

CREATE TABLE label_rating_raw
(
  label      INTEGER NOT NULL, -- PK, references label.id
  editor     INTEGER NOT NULL, -- PK, references editor.id
  rating     SMALLINT NOT NULL CHECK (rating >= 0 AND rating <= 100)
);

```

```

CREATE TABLE label_tag_raw
(
  label      INTEGER NOT NULL, -- PK, references label.id
  editor     INTEGER NOT NULL, -- PK, references editor.id
  tag        INTEGER NOT NULL, -- PK, references tag.id
  is_upvote  BOOLEAN NOT NULL DEFAULT TRUE
);

```

```

CREATE TABLE label_alias_type ( -- replicate
  id         SERIAL,
  name       TEXT NOT NULL,
  parent     INTEGER, -- references label_alias_type.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid        uuid NOT NULL
);

```

```

CREATE TABLE label_alias ( -- replicate (verbose)
  id         SERIAL,
  label      INTEGER NOT NULL, -- references label.id
  name       VARCHAR NOT NULL,
  locale     TEXT,
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type          INTEGER, -- references label_alias_type.id
  sort_name     VARCHAR NOT NULL,

```

```

begin_date_year  SMALLINT,
begin_date_month SMALLINT,
begin_date_day   SMALLINT,
end_date_year    SMALLINT,
end_date_month   SMALLINT,
end_date_day     SMALLINT,
primary_for_locale BOOLEAN NOT NULL DEFAULT false,
ended            BOOLEAN NOT NULL DEFAULT FALSE
CHECK (
  (
    -- If any end date fields are not null, then ended must be true
    (end_date_year IS NOT NULL OR
     end_date_month IS NOT NULL OR
     end_date_day IS NOT NULL) AND
    ended = TRUE
  ) OR (
    -- Otherwise, all end date fields must be null
    (end_date_year IS NULL AND
     end_date_month IS NULL AND
     end_date_day IS NULL)
  )
),
    CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
    CONSTRAINT search_hints_are_empty
    CHECK (
      (type <> 2) OR (
        type = 2 AND sort_name = name AND
        begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
        end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
        primary_for_locale IS FALSE AND locale IS NULL
      )
    )
);

```

```

CREATE TABLE label_annotation ( -- replicate (verbose)
  label      INTEGER NOT NULL, -- PK, references label.id
  annotation  INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE label_attribute_type ( -- replicate (verbose)

```



```

id          SERIAL, -- PK
name        VARCHAR(255) NOT NULL,
comment     VARCHAR(255) NOT NULL DEFAULT "",
free_text   BOOLEAN NOT NULL,
parent      INTEGER, -- references label_attribute_type.id
child_order INTEGER NOT NULL DEFAULT 0,
description TEXT,
gid         uuid NOT NULL
);

CREATE TABLE label_attribute_type_allowed_value ( -- replicate (verbose)
id          SERIAL, -- PK
label_attribute_type      INTEGER NOT NULL, -- references
label_attribute_type.id
value            TEXT,
parent          INTEGER, -- references
label_attribute_type_allowed_value.id
child_order     INTEGER NOT NULL DEFAULT 0,
description     TEXT,
gid            uuid NOT NULL
);

CREATE TABLE label_attribute ( -- replicate (verbose)
id          SERIAL, -- PK
label       INTEGER NOT NULL, -- references label.id
label_attribute_type      INTEGER NOT NULL, -- references
label_attribute_type.id
label_attribute_type_allowed_value      INTEGER, -- references
label_attribute_type_allowed_value.id
label_attribute_text      TEXT
CHECK (
    (label_attribute_type_allowed_value IS NULL AND label_attribute_text
IS NOT NULL)
    OR
    (label_attribute_type_allowed_value IS NOT NULL AND
label_attribute_text IS NULL)
)
);

CREATE TABLE label_ipi ( -- replicate (verbose)
label       INTEGER NOT NULL, -- PK, references label.id
ipi         CHAR(11) NOT NULL CHECK (ipi ~ E'^\\d{11}$'), -- PK

```

```
    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    created          TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE label_isni ( -- replicate (verbose)
    label            INTEGER NOT NULL, -- PK, references label.id
    isni             CHAR(16) NOT NULL CHECK (isni ~ E'^\\d{15}[\\dX]$'), -- PK
    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    created          TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE label_meta ( -- replicate
    id              INTEGER NOT NULL, -- PK, references label.id CASCADE
    rating          SMALLINT CHECK (rating >= 0 AND rating <= 100),
    rating_count     INTEGER
);
```

```
CREATE TABLE label_gid_redirect ( -- replicate (verbose)
    gid             UUID NOT NULL, -- PK
    new_id          INTEGER NOT NULL, -- references label.id
    created          TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE label_tag ( -- replicate (verbose)
    label           INTEGER NOT NULL, -- PK, references label.id
    tag             INTEGER NOT NULL, -- PK, references tag.id
    count           INTEGER NOT NULL,
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE label_type ( -- replicate
    id              SERIAL,
    name            VARCHAR(255) NOT NULL,
    parent          INTEGER, -- references label_type.id
    child_order     INTEGER NOT NULL DEFAULT 0,
    description      TEXT,
    gid             uuid NOT NULL
);
```

```
CREATE TABLE language ( -- replicate
    id              SERIAL,
```

```

iso_code_2t    CHAR(3), -- ISO 639-2 (T)
iso_code_2b    CHAR(3), -- ISO 639-2 (B)
iso_code_1     CHAR(2), -- ISO 639
name          VARCHAR(100) NOT NULL,
frequency     SMALLINT NOT NULL DEFAULT 0,
iso_code_3     CHAR(3) -- ISO 639-3
);

```

```

ALTER TABLE language
  ADD CONSTRAINT iso_code_check
  CHECK (iso_code_2t IS NOT NULL OR iso_code_3 IS NOT NULL);

```

```

CREATE TABLE link ( -- replicate
  id          SERIAL,
  link_type   INTEGER NOT NULL, -- references link_type.id
  begin_date_year  SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day   SMALLINT,
  end_date_year    SMALLINT,
  end_date_month   SMALLINT,
  end_date_day     SMALLINT,
  attribute_count  INTEGER NOT NULL DEFAULT 0,
  created         TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  ended          BOOLEAN NOT NULL DEFAULT FALSE
  CONSTRAINT link_ended_check CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
       end_date_month IS NOT NULL OR
       end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND
       end_date_month IS NULL AND
       end_date_day IS NULL)
    )
  );

```

```

CREATE TABLE link_attribute ( -- replicate
  link        INTEGER NOT NULL, -- PK, references link.id

```

```

        attribute_type          INTEGER NOT NULL, -- PK, references
link_attribute_type.id
    created          TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE link_attribute_type ( -- replicate
    id          SERIAL,
    parent      INTEGER, -- references link_attribute_type.id
    root        INTEGER NOT NULL, -- references link_attribute_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    gid         UUID NOT NULL,
    name        VARCHAR(255) NOT NULL,
    description  TEXT,
    last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE link_creditable_attribute_type ( -- replicate
    attribute_type INT NOT NULL -- PK, references link_attribute_type.id
CASCADE
);

```

```

CREATE TABLE link_attribute_credit ( -- replicate
    link INT NOT NULL, -- PK, references link.id
        attribute_type INT NOT NULL, -- PK, references
link_creditable_attribute_type.attribute_type
    credited_as TEXT NOT NULL
);

```

```

CREATE TABLE link_text_attribute_type ( -- replicate
    attribute_type INT NOT NULL -- PK, references link_attribute_type.id
CASCADE
);

```

```

CREATE TABLE link_attribute_text_value ( -- replicate
    link          INT NOT NULL, -- PK, references link.id
        attribute_type          INT NOT NULL, -- PK, references
link_text_attribute_type.attribute_type
    text_value    TEXT NOT NULL
);

```

```

CREATE TABLE link_type ( -- replicate
    id          SERIAL,
    parent      INTEGER, -- references link_type.id

```

```

child_order    INTEGER NOT NULL DEFAULT 0,
gid            UUID NOT NULL,
entity_type0   VARCHAR(50) NOT NULL,
entity_type1   VARCHAR(50) NOT NULL,
name           VARCHAR(255) NOT NULL,
description    TEXT,
link_phrase    VARCHAR(255) NOT NULL,
reverse_link_phrase VARCHAR(255) NOT NULL,
long_link_phrase VARCHAR(255) NOT NULL,
last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
is_deprecated  BOOLEAN NOT NULL DEFAULT false,
has_dates      BOOLEAN NOT NULL DEFAULT true,
entity0_cardinality SMALLINT NOT NULL DEFAULT 0,
entity1_cardinality SMALLINT NOT NULL DEFAULT 0
);

CREATE TABLE link_type_attribute_type ( -- replicate
    link_type    INTEGER NOT NULL, -- PK, references link_type.id
    attribute_type    INTEGER NOT NULL, -- PK, references
link_attribute_type.id
    min          SMALLINT,
    max          SMALLINT,
    last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE editor_collection
(
    id            SERIAL,
    gid          UUID NOT NULL,
    editor        INTEGER NOT NULL, -- references editor.id
    name          VARCHAR NOT NULL,
    public        BOOLEAN NOT NULL DEFAULT FALSE,
    description    TEXT DEFAULT '' NOT NULL,
    type          INTEGER NOT NULL -- references editor_collection_type.id
);

CREATE TABLE editor_collection_gid_redirect (
    gid          UUID NOT NULL, -- PK
    new_id        INTEGER NOT NULL, -- references editor_collection.id
    created       TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE editor_collection_type ( -- replicate

```

```
id          SERIAL,
name        VARCHAR(255) NOT NULL,
entity_type VARCHAR(50) NOT NULL,
parent      INTEGER, -- references editor_collection_type.id
child_order INTEGER NOT NULL DEFAULT 0,
description TEXT,
gid         uuid NOT NULL
);
```

```
CREATE TABLE editor_collection_collaborator (
  collection INTEGER NOT NULL, -- PK, references editor_collection.id
  editor INTEGER NOT NULL -- PK, references editor.id
);
```

```
CREATE TABLE editor_collection_area (
  collection INTEGER NOT NULL, -- PK, references editor_collection.id
  area INTEGER NOT NULL, -- PK, references area.id
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),
  comment TEXT DEFAULT '' NOT NULL
);
```

```
CREATE TABLE editor_collection_artist (
  collection INTEGER NOT NULL, -- PK, references editor_collection.id
  artist INTEGER NOT NULL, -- PK, references artist.id
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),
  comment TEXT DEFAULT '' NOT NULL
);
```

```
CREATE TABLE editor_collection_event (
  collection INTEGER NOT NULL, -- PK, references editor_collection.id
  event INTEGER NOT NULL, -- PK, references event.id
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),
  comment TEXT DEFAULT '' NOT NULL
);
```

```
CREATE TABLE editor_collection_genre (
  collection INTEGER NOT NULL, -- PK, references editor_collection.id
  genre INTEGER NOT NULL, -- PK, references genre.id
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),
```

```
comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_instrument (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  instrument INTEGER NOT NULL, -- PK, references instrument.id  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_label (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  label INTEGER NOT NULL, -- PK, references label.id  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_place (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  place INTEGER NOT NULL, -- PK, references place.id  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_recording (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  recording INTEGER NOT NULL, -- PK, references recording.id  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_release (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  release INTEGER NOT NULL, -- PK, references release.id  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_release_group (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  release_group INTEGER NOT NULL, -- PK, references release_group.id  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_series (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  series INTEGER NOT NULL, -- PK, references series.id  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_work (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  work INTEGER NOT NULL, -- PK, references work.id  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_collection_deleted_entity (  
  collection INTEGER NOT NULL, -- PK, references editor_collection.id  
  gid UUID NOT NULL, -- PK, references deleted_entity.gid  
  added TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  position INTEGER NOT NULL DEFAULT 0 CHECK (position >= 0),  
  comment TEXT DEFAULT " NOT NULL  
);
```

```
CREATE TABLE editor_oauth_token  
(  
  id SERIAL,  
  editor INTEGER NOT NULL, -- references editor.id  
  application INTEGER NOT NULL, -- references application.id  
  authorization_code TEXT,  
  refresh_token TEXT,  
  access_token TEXT,  
  expire_time TIMESTAMP WITH TIME ZONE NOT NULL,  
  scope INTEGER NOT NULL DEFAULT 0,
```



```

    granted          TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT
NOW(),
    code_challenge    TEXT,
    code_challenge_method oauth_code_challenge_method,
    CONSTRAINT valid_code_challenge CHECK (
        (code_challenge IS NULL) = (code_challenge_method IS NULL) AND
        (code_challenge IS NULL OR code_challenge ~
E'^[A-Za-z0-9._-]{43,128}$')
    )
);

```

```

CREATE TABLE medium ( -- replicate (verbose)
    id          SERIAL,
    release     INTEGER NOT NULL, -- references release.id
    position    INTEGER NOT NULL,
    format      INTEGER, -- references medium_format.id
    name        VARCHAR NOT NULL DEFAULT "",
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    track_count   INTEGER NOT NULL DEFAULT 0
);

```

```

CREATE TABLE medium_attribute_type ( -- replicate (verbose)
    id          SERIAL, -- PK
    name        VARCHAR(255) NOT NULL,
    comment     VARCHAR(255) NOT NULL DEFAULT "",
    free_text    BOOLEAN NOT NULL,
    parent      INTEGER, -- references medium_attribute_type.id
    child_order  INTEGER NOT NULL DEFAULT 0,
    description  TEXT,
    gid         uuid NOT NULL
);

```

```

CREATE TABLE medium_attribute_type_allowed_format ( -- replicate
(verbose)
    medium_format INTEGER NOT NULL, -- PK, references
medium_format.id,
    medium_attribute_type INTEGER NOT NULL -- PK, references
medium_attribute_type.id
);

```

```

CREATE TABLE medium_attribute_type_allowed_value ( -- replicate
(verbose)
  id SERIAL, -- PK
  medium_attribute_type INTEGER NOT NULL, -- references
medium_attribute_type.id
  value TEXT,
  parent INTEGER, -- references
medium_attribute_type_allowed_value.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid uuid NOT NULL
);

```

```

CREATE TABLE medium_attribute_type_allowed_value_allowed_format ( --
replicate (verbose)
  medium_format INTEGER NOT NULL, -- PK, references
medium_format.id,
  medium_attribute_type_allowed_value INTEGER NOT NULL -- PK,
references medium_attribute_type_allowed_value.id
);

```

```

CREATE TABLE medium_attribute ( -- replicate (verbose)
  id SERIAL, -- PK
  medium INTEGER NOT NULL, -- references medium.id
  medium_attribute_type INTEGER NOT NULL, -- references
medium_attribute_type.id
  medium_attribute_type_allowed_value INTEGER, -- references
medium_attribute_type_allowed_value.id
  medium_attribute_text TEXT
  CHECK (
    (medium_attribute_type_allowed_value IS NULL AND
medium_attribute_text IS NOT NULL)
    OR
    (medium_attribute_type_allowed_value IS NOT NULL AND
medium_attribute_text IS NULL)
  )
);

```

```

CREATE TABLE medium_cdtoc ( -- replicate (verbose)
  id SERIAL,
  medium INTEGER NOT NULL, -- references medium.id
  cdtoc INTEGER NOT NULL, -- references cdtoc.id

```

```
    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated     TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE medium_format ( -- replicate
    id                SERIAL,
    name              VARCHAR(100) NOT NULL,
    parent            INTEGER, -- references medium_format.id
    child_order       INTEGER NOT NULL DEFAULT 0,
    year              SMALLINT,
    has_discids       BOOLEAN NOT NULL DEFAULT FALSE,
    description        TEXT,
    gid               uuid NOT NULL
);
```

```
CREATE TABLE mood ( -- replicate (verbose)
    id                SERIAL, -- PK
    gid               UUID NOT NULL,
    name              VARCHAR NOT NULL,
    comment           VARCHAR(255) NOT NULL DEFAULT "",
    edits_pending     INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>=0),
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE mood_alias_type ( -- replicate
    id                SERIAL, -- PK,
    name              TEXT NOT NULL,
    parent            INTEGER, -- references mood_alias_type.id
    child_order       INTEGER NOT NULL DEFAULT 0,
    description        TEXT,
    gid               uuid NOT NULL
);
```

```
CREATE TABLE mood_alias ( -- replicate (verbose)
    id                SERIAL, --PK
    mood              INTEGER NOT NULL, -- references mood.id
    name              VARCHAR NOT NULL,
    locale            TEXT,
    edits_pending     INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated      TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
```

```

type          INTEGER, -- references mood_alias_type.id
sort_name     VARCHAR NOT NULL,
begin_date_year  SMALLINT,
begin_date_month SMALLINT,
begin_date_day   SMALLINT,
end_date_year    SMALLINT,
end_date_month   SMALLINT,
end_date_day     SMALLINT,
primary_for_locale BOOLEAN NOT NULL DEFAULT false,
ended          BOOLEAN NOT NULL DEFAULT FALSE
CHECK (
  (
    -- If any end date fields are not null, then ended must be true
    (end_date_year IS NOT NULL OR
     end_date_month IS NOT NULL OR
     end_date_day IS NOT NULL) AND
    ended = TRUE
  ) OR (
    -- Otherwise, all end date fields must be null
    (end_date_year IS NULL AND
     end_date_month IS NULL AND
     end_date_day IS NULL)
  )
),
CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
CONSTRAINT search_hints_are_empty
CHECK (
  (type <> 2) OR (
    type = 2 AND sort_name = name AND
    begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
    end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
    primary_for_locale IS FALSE AND locale IS NULL
  )
);

CREATE TABLE mood_annotation ( -- replicate (verbose)
  mood      INTEGER NOT NULL, -- PK, references mood.id
  annotation INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE orderable_link_type ( -- replicate
  link_type      INTEGER NOT NULL, -- PK, references link_type.id
  direction      SMALLINT NOT NULL DEFAULT 1 CHECK (direction = 1 OR
direction = 2)
);

```

```

CREATE TABLE place ( -- replicate (verbose)
  id              SERIAL, -- PK
  gid             uuid NOT NULL,
  name            VARCHAR NOT NULL,
  type            INTEGER, -- references place_type.id
  address         VARCHAR NOT NULL DEFAULT "",
  area            INTEGER, -- references area.id
  coordinates     POINT,
  comment         VARCHAR(255) NOT NULL DEFAULT "",
  edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>=0),
  last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  begin_date_year SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day  SMALLINT,
  end_date_year   SMALLINT,
  end_date_month  SMALLINT,
  end_date_day    SMALLINT,
  ended           BOOLEAN NOT NULL DEFAULT FALSE
  CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
      end_date_month IS NOT NULL OR
      end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND
      end_date_month IS NULL AND
      end_date_day IS NULL)
    )
  )
);

```

```

CREATE TABLE place_alias ( -- replicate (verbose)

```

```

id          SERIAL,
place       INTEGER NOT NULL, -- references place.id
name        VARCHAR NOT NULL,
locale      TEXT,
  edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type           INTEGER, -- references place_alias_type.id
  sort_name      VARCHAR NOT NULL,
  begin_date_year  SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day   SMALLINT,
  end_date_year    SMALLINT,
  end_date_month   SMALLINT,
  end_date_day     SMALLINT,
  primary_for_locale  BOOLEAN NOT NULL DEFAULT false,
  ended           BOOLEAN NOT NULL DEFAULT FALSE
  CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
      end_date_month IS NOT NULL OR
      end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND
      end_date_month IS NULL AND
      end_date_day IS NULL)
    )
  ),
  CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
  CONSTRAINT search_hints_are_empty
  CHECK (
    (type <> 2) OR (
      type = 2 AND sort_name = name AND
      begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
      end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
      primary_for_locale IS FALSE AND locale IS NULL
    )
  )

```

```
)  
);
```

```
CREATE TABLE place_alias_type ( -- replicate  
  id          SERIAL,  
  name        TEXT NOT NULL,  
  parent      INTEGER, -- references place_alias_type.id  
  child_order INTEGER NOT NULL DEFAULT 0,  
  description  TEXT,  
  gid         uuid NOT NULL  
);
```

```
CREATE TABLE place_annotation ( -- replicate (verbose)  
  place      INTEGER NOT NULL, -- PK, references place.id  
  annotation  INTEGER NOT NULL -- PK, references annotation.id  
);
```

```
CREATE TABLE place_attribute_type ( -- replicate (verbose)  
  id          SERIAL, -- PK  
  name        VARCHAR(255) NOT NULL,  
  comment     VARCHAR(255) NOT NULL DEFAULT "",  
  free_text   BOOLEAN NOT NULL,  
  parent      INTEGER, -- references place_attribute_type.id  
  child_order INTEGER NOT NULL DEFAULT 0,  
  description  TEXT,  
  gid         uuid NOT NULL  
);
```

```
CREATE TABLE place_attribute_type_allowed_value ( -- replicate (verbose)  
  id          SERIAL, -- PK  
  place_attribute_type      INTEGER NOT NULL, -- references  
place_attribute_type.id  
  value        TEXT,  
  parent      INTEGER, -- references  
place_attribute_type_allowed_value.id  
  child_order INTEGER NOT NULL DEFAULT 0,  
  description  TEXT,  
  gid         uuid NOT NULL  
);
```

```
CREATE TABLE place_attribute ( -- replicate (verbose)  
  id          SERIAL, -- PK  
  place      INTEGER NOT NULL, -- references place.id
```

```

        place_attribute_type          INTEGER NOT NULL, -- references
place_attribute_type.id
        place_attribute_type_allowed_value    INTEGER, -- references
place_attribute_type_allowed_value.id
        place_attribute_text          TEXT
CHECK (
    (place_attribute_type_allowed_value IS NULL AND place_attribute_text
IS NOT NULL)
    OR
    (place_attribute_type_allowed_value IS NOT NULL AND
place_attribute_text IS NULL)
)
);

```

```

CREATE TABLE place_gid_redirect ( -- replicate (verbose)
    gid          UUID NOT NULL, -- PK
    new_id       INTEGER NOT NULL, -- references place.id
    created      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE place_meta ( -- replicate
    id          INTEGER NOT NULL, -- PK, references place.id CASCADE
    rating      SMALLINT CHECK (rating >= 0 AND rating <= 100),
    rating_count INTEGER
);

```

```

CREATE TABLE place_rating_raw
(
    place      INTEGER NOT NULL, -- PK, references place.id
    editor     INTEGER NOT NULL, -- PK, references editor.id
    rating     SMALLINT NOT NULL CHECK (rating >= 0 AND rating <= 100)
);

```

```

CREATE TABLE place_tag ( -- replicate (verbose)
    place      INTEGER NOT NULL, -- PK, references place.id
    tag        INTEGER NOT NULL, -- PK, references tag.id
    count      INTEGER NOT NULL,
    last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE place_tag_raw
(
    place      INTEGER NOT NULL, -- PK, references place.id

```



```

    editor      INTEGER NOT NULL, -- PK, references editor.id
    tag         INTEGER NOT NULL, -- PK, references tag.id
    is_upvote   BOOLEAN NOT NULL DEFAULT TRUE
);

```

```

CREATE TABLE place_type ( -- replicate
    id          SERIAL, -- PK
    name        VARCHAR(255) NOT NULL,
    parent      INTEGER, -- references place_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid         uuid NOT NULL
);

```

```

CREATE TABLE replication_control ( -- replicate
    id              SERIAL,
    current_schema_sequence INTEGER NOT NULL,
    current_replication_sequence INTEGER,
    last_replication_date   TIMESTAMP WITH TIME ZONE
);

```

```

CREATE TABLE recording ( -- replicate (verbose)
    id          SERIAL,
    gid         UUID NOT NULL,
    name        VARCHAR NOT NULL,
    artist_credit INTEGER NOT NULL, -- references artist_credit.id
    length      INTEGER CHECK (length IS NULL OR length > 0),
    comment     VARCHAR(255) NOT NULL DEFAULT "",
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    last_updated   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    video          BOOLEAN NOT NULL DEFAULT FALSE
);

```

```

CREATE TABLE recording_alias_type ( -- replicate
    id          SERIAL, -- PK,
    name        TEXT NOT NULL,
    parent      INTEGER, -- references recording_alias_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid         uuid NOT NULL
);

```

```

CREATE TABLE recording_alias ( -- replicate (verbose)
  id          SERIAL, --PK
  recording   INTEGER NOT NULL, -- references recording.id
  name        VARCHAR NOT NULL,
  locale      TEXT,
  edits_pending  INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>=0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type         INTEGER, -- references recording_alias_type.id
  sort_name    VARCHAR NOT NULL,
  begin_date_year  SMALLINT,
  begin_date_month  SMALLINT,
  begin_date_day   SMALLINT,
  end_date_year    SMALLINT,
  end_date_month   SMALLINT,
  end_date_day     SMALLINT,
  primary_for_locale  BOOLEAN NOT NULL DEFAULT false,
  ended            BOOLEAN NOT NULL DEFAULT FALSE
  CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
      end_date_month IS NOT NULL OR
      end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
      -- Otherwise, all end date fields must be null
      (end_date_year IS NULL AND
      end_date_month IS NULL AND
      end_date_day IS NULL)
    )
  ),
  CONSTRAINT primary_check
      CHECK ((locale IS NULL AND primary_for_locale IS FALSE) OR
(locale IS NOT NULL)));

```

```

CREATE TABLE recording_rating_raw
(
  recording   INTEGER NOT NULL, -- PK, references recording.id
  editor      INTEGER NOT NULL, -- PK, references editor.id
  rating      SMALLINT NOT NULL CHECK (rating >= 0 AND rating <= 100)
);

```

```
CREATE TABLE recording_tag_raw
```

```
(
  recording      INTEGER NOT NULL, -- PK, references recording.id
  editor         INTEGER NOT NULL, -- PK, references editor.id
  tag            INTEGER NOT NULL, -- PK, references tag.id
  is_upvote      BOOLEAN NOT NULL DEFAULT TRUE
);
```

```
CREATE TABLE recording_annotation ( -- replicate (verbose)
```

```
  recording      INTEGER NOT NULL, -- PK, references recording.id
  annotation      INTEGER NOT NULL -- PK, references annotation.id
);
```

```
CREATE TABLE recording_attribute_type ( -- replicate (verbose)
```

```
  id             SERIAL, -- PK
  name           VARCHAR(255) NOT NULL,
  comment        VARCHAR(255) NOT NULL DEFAULT "",
  free_text      BOOLEAN NOT NULL,
  parent         INTEGER, -- references recording_attribute_type.id
  child_order    INTEGER NOT NULL DEFAULT 0,
  description     TEXT,
  gid            uuid NOT NULL
);
```

```
CREATE TABLE recording_attribute_type_allowed_value ( -- replicate
(verbose)
```

```
  id             SERIAL, -- PK
  recording_attribute_type    INTEGER NOT NULL, -- references
recording_attribute_type.id
  value          TEXT,
  parent         INTEGER, -- references
recording_attribute_type_allowed_value.id
  child_order    INTEGER NOT NULL DEFAULT 0,
  description     TEXT,
  gid            uuid NOT NULL
);
```

```
CREATE TABLE recording_attribute ( -- replicate (verbose)
```

```
  id             SERIAL, -- PK
  recording      INTEGER NOT NULL, -- references
recording.id
  recording_attribute_type    INTEGER NOT NULL, -- references
recording_attribute_type.id
```

```

        recording_attribute_type_allowed_value    INTEGER, -- references
recording_attribute_type_allowed_value.id
        recording_attribute_text                  TEXT
CHECK (
        (recording_attribute_type_allowed_value IS NULL AND
recording_attribute_text IS NOT NULL)
        OR
        (recording_attribute_type_allowed_value IS NOT NULL AND
recording_attribute_text IS NULL)
)
);

```

```

CREATE TABLE recording_meta ( -- replicate
    id          INTEGER NOT NULL, -- PK, references recording.id CASCADE
    rating       SMALLINT CHECK (rating >= 0 AND rating <= 100),
    rating_count INTEGER
);

```

```

CREATE TABLE recording_gid_redirect ( -- replicate (verbose)
    gid          UUID NOT NULL, -- PK
    new_id       INTEGER NOT NULL, -- references recording.id
    created      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE recording_tag ( -- replicate (verbose)
    recording    INTEGER NOT NULL, -- PK, references recording.id
    tag          INTEGER NOT NULL, -- PK, references tag.id
    count        INTEGER NOT NULL,
    last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE release ( -- replicate (verbose)
    id          SERIAL,
    gid         UUID NOT NULL,
    name        VARCHAR NOT NULL,
    artist_credit INTEGER NOT NULL, -- references artist_credit.id
    release_group INTEGER NOT NULL, -- references release_group.id
    status      INTEGER, -- references release_status.id
    packaging   INTEGER, -- references release_packaging.id
    language    INTEGER, -- references language.id
    script      INTEGER, -- references script.id
    barcode     VARCHAR(255),
    comment     VARCHAR(255) NOT NULL DEFAULT "",

```

```

    edits_pending    INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >= 0),
    quality          SMALLINT NOT NULL DEFAULT -1,
    last_updated     TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE release_alias_type ( -- replicate
    id              SERIAL, -- PK,
    name            TEXT NOT NULL,
    parent          INTEGER, -- references release_alias_type.id
    child_order     INTEGER NOT NULL DEFAULT 0,
    description     TEXT,
    gid             uuid NOT NULL
);

```

```

CREATE TABLE release_alias ( -- replicate (verbose)
    id              SERIAL, --PK
    release         INTEGER NOT NULL, -- references release.id
    name            VARCHAR NOT NULL,
    locale          TEXT,
    edits_pending   INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
    >=0),
    last_updated    TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    type            INTEGER, -- references release_alias_type.id
    sort_name       VARCHAR NOT NULL,
    begin_date_year SMALLINT,
    begin_date_month SMALLINT,
    begin_date_day  SMALLINT,
    end_date_year   SMALLINT,
    end_date_month  SMALLINT,
    end_date_day    SMALLINT,
    primary_for_locale BOOLEAN NOT NULL DEFAULT false,
    ended           BOOLEAN NOT NULL DEFAULT FALSE
    CHECK (
        (
            -- If any end date fields are not null, then ended must be true
            (end_date_year IS NOT NULL OR
            end_date_month IS NOT NULL OR
            end_date_day IS NOT NULL) AND
            ended = TRUE
        ) OR (
            -- Otherwise, all end date fields must be null
            (end_date_year IS NULL AND

```

```

        end_date_month IS NULL AND
        end_date_day IS NULL)
    ),
    CONSTRAINT primary_check
        CHECK ((locale IS NULL AND primary_for_locale IS FALSE) OR
(locale IS NOT NULL)));

```

```

CREATE TABLE release_country ( -- replicate (verbose)
    release INTEGER NOT NULL, -- PK, references release.id
    country INTEGER NOT NULL, -- PK, references country_area.area
    date_year SMALLINT,
    date_month SMALLINT,
    date_day SMALLINT
);

```

```

CREATE TABLE release_unknown_country ( -- replicate (verbose)
    release INTEGER NOT NULL, -- PK, references release.id
    date_year SMALLINT,
    date_month SMALLINT,
    date_day SMALLINT
);

```

```

CREATE TABLE release_raw ( -- replicate
    id          SERIAL, -- PK
    title       VARCHAR(255) NOT NULL,
    artist      VARCHAR(255),
    added       TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    last_modified  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    lookup_count  INTEGER DEFAULT 0,
    modify_count  INTEGER DEFAULT 0,
    source       INTEGER DEFAULT 0,
    barcode     VARCHAR(255),
    comment     VARCHAR(255) NOT NULL DEFAULT ''
);

```

```

CREATE TABLE release_tag_raw
(
    release     INTEGER NOT NULL, -- PK, references release.id
    editor      INTEGER NOT NULL, -- PK, references editor.id
    tag         INTEGER NOT NULL, -- PK, references tag.id
    is_upvote   BOOLEAN NOT NULL DEFAULT TRUE
);

```

```

CREATE TABLE release_annotation ( -- replicate (verbose)
  release      INTEGER NOT NULL, -- PK, references release.id
  annotation    INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE release_attribute_type ( -- replicate (verbose)
  id          SERIAL, -- PK
  name        VARCHAR(255) NOT NULL,
  comment     VARCHAR(255) NOT NULL DEFAULT "",
  free_text   BOOLEAN NOT NULL,
  parent      INTEGER, -- references release_attribute_type.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);

```

```

CREATE TABLE release_attribute_type_allowed_value ( -- replicate
(verbose)
  id          SERIAL, -- PK
  release_attribute_type INTEGER NOT NULL, -- references
release_attribute_type.id
  value       TEXT,
  parent      INTEGER, -- references
release_attribute_type_allowed_value.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);

```

```

CREATE TABLE release_attribute ( -- replicate (verbose)
  id          SERIAL, -- PK
  release     INTEGER NOT NULL, -- references release.id
  release_attribute_type INTEGER NOT NULL, -- references
release_attribute_type.id
  release_attribute_type_allowed_value INTEGER, -- references
release_attribute_type_allowed_value.id
  release_attribute_text TEXT
  CHECK (
    (release_attribute_type_allowed_value IS NULL AND
release_attribute_text IS NOT NULL)
    OR

```

```
        (release_attribute_type_allowed_value IS NOT NULL AND
release_attribute_text IS NULL)
    )
);
```

```
CREATE TABLE release_gid_redirect ( -- replicate (verbose)
gid          UUID NOT NULL, -- PK
new_id       INTEGER NOT NULL, -- references release.id
created      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE release_meta ( -- replicate (verbose)
id           INTEGER NOT NULL, -- PK, references release.id CASCADE
date_added   TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
info_url     VARCHAR(255),
amazon_asin  VARCHAR(10),
cover_art_presence cover_art_presence NOT NULL DEFAULT 'absent'
);
```

```
CREATE TABLE release_label ( -- replicate (verbose)
id           SERIAL,
release      INTEGER NOT NULL, -- references release.id
label        INTEGER, -- references label.id
catalog_number VARCHAR(255),
last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE release_packaging ( -- replicate
id          SERIAL,
name        VARCHAR(255) NOT NULL,
parent      INTEGER, -- references release_packaging.id
child_order INTEGER NOT NULL DEFAULT 0,
description TEXT,
gid         uuid NOT NULL
);
```

```
CREATE TABLE release_status ( -- replicate
id          SERIAL,
name        VARCHAR(255) NOT NULL,
parent      INTEGER, -- references release_status.id
child_order INTEGER NOT NULL DEFAULT 0,
description TEXT,
gid         uuid NOT NULL
```


);

```
CREATE TABLE release_tag ( -- replicate (verbose)
  release      INTEGER NOT NULL, -- PK, references release.id
  tag          INTEGER NOT NULL, -- PK, references tag.id
  count        INTEGER NOT NULL,
  last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE release_group ( -- replicate (verbose)
  id           SERIAL,
  gid          UUID NOT NULL,
  name         VARCHAR NOT NULL,
  artist_credit INTEGER NOT NULL, -- references artist_credit.id
  type         INTEGER, -- references release_group_primary_type.id
  comment      VARCHAR(255) NOT NULL DEFAULT "",
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
  >= 0),
  last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE release_group_alias_type ( -- replicate
  id          SERIAL, -- PK,
  name        TEXT NOT NULL,
  parent      INTEGER, -- references release_group_alias_type.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);
```

```
CREATE TABLE release_group_alias ( -- replicate (verbose)
  id          SERIAL, --PK
  release_group INTEGER NOT NULL, -- references release_group.id
  name        VARCHAR NOT NULL,
  locale      TEXT,
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
  >=0),
  last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type        INTEGER, -- references release_group_alias_type.id
  sort_name   VARCHAR NOT NULL,
  begin_date_year  SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day   SMALLINT,
```

```

end_date_year    SMALLINT,
end_date_month   SMALLINT,
end_date_day     SMALLINT,
primary_for_locale BOOLEAN NOT NULL DEFAULT false,
ended            BOOLEAN NOT NULL DEFAULT FALSE
CHECK (
    (
        -- If any end date fields are not null, then ended must be true
        (end_date_year IS NOT NULL OR
         end_date_month IS NOT NULL OR
         end_date_day IS NOT NULL) AND
        ended = TRUE
    ) OR (
        -- Otherwise, all end date fields must be null
        (end_date_year IS NULL AND
         end_date_month IS NULL AND
         end_date_day IS NULL)
    )
),
    CONSTRAINT primary_check
        CHECK ((locale IS NULL AND primary_for_locale IS FALSE) OR
(locale IS NOT NULL));

```

```

CREATE TABLE release_group_rating_raw
(
    release_group    INTEGER NOT NULL, -- PK, references release_group.id
    editor           INTEGER NOT NULL, -- PK, references editor.id
    rating           SMALLINT NOT NULL CHECK (rating >= 0 AND rating <= 100)
);

```

```

CREATE TABLE release_group_tag_raw
(
    release_group    INTEGER NOT NULL, -- PK, references release_group.id
    editor           INTEGER NOT NULL, -- PK, references editor.id
    tag              INTEGER NOT NULL, -- PK, references tag.id
    is_upvote        BOOLEAN NOT NULL DEFAULT TRUE
);

```

```

CREATE TABLE release_group_annotation ( -- replicate (verbose)
    release_group    INTEGER NOT NULL, -- PK, references release_group.id
    annotation       INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE release_group_attribute_type ( -- replicate (verbose)
  id          SERIAL, -- PK
  name        VARCHAR(255) NOT NULL,
  comment     VARCHAR(255) NOT NULL DEFAULT "",
  free_text   BOOLEAN NOT NULL,
  parent      INTEGER, -- references release_group_attribute_type.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);

```

```

CREATE TABLE release_group_attribute_type_allowed_value ( -- replicate
(verbose)
  id          SERIAL, -- PK
  release_group_attribute_type INTEGER NOT NULL, -- references
release_group_attribute_type.id
  value       TEXT,
  parent      INTEGER, -- references
release_group_attribute_type_allowed_value.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);

```

```

CREATE TABLE release_group_attribute ( -- replicate (verbose)
  id          SERIAL, -- PK
  release_group INTEGER NOT NULL, -- references
release_group.id
  release_group_attribute_type INTEGER NOT NULL, -- references
release_group_attribute_type.id
  release_group_attribute_type_allowed_value INTEGER, -- references
release_group_attribute_type_allowed_value.id
  release_group_attribute_text TEXT
  CHECK (
    (release_group_attribute_type_allowed_value IS NULL AND
release_group_attribute_text IS NOT NULL)
    OR
    (release_group_attribute_type_allowed_value IS NOT NULL AND
release_group_attribute_text IS NULL)
  )
);

```

```

CREATE TABLE release_group_gid_redirect ( -- replicate (verbose)

```

```

gid          UUID NOT NULL, -- PK
new_id       INTEGER NOT NULL, -- references release_group.id
created      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE release_group_meta ( -- replicate
  id          INTEGER NOT NULL, -- PK, references release_group.id
  CASCADE
  release_count  INTEGER NOT NULL DEFAULT 0,
  first_release_date_year  SMALLINT,
  first_release_date_month SMALLINT,
  first_release_date_day   SMALLINT,
  rating         SMALLINT CHECK (rating >= 0 AND rating <= 100),
  rating_count   INTEGER
);

CREATE TABLE release_group_tag ( -- replicate (verbose)
  release_group  INTEGER NOT NULL, -- PK, references release_group.id
  tag           INTEGER NOT NULL, -- PK, references tag.id
  count         INTEGER NOT NULL,
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE release_group_primary_type ( -- replicate
  id            SERIAL,
  name          VARCHAR(255) NOT NULL,
  parent        INTEGER, -- references release_group_primary_type.id
  child_order   INTEGER NOT NULL DEFAULT 0,
  description    TEXT,
  gid           uuid NOT NULL
);

CREATE TABLE release_group_secondary_type ( -- replicate
  id            SERIAL NOT NULL, -- PK
  name          TEXT NOT NULL,
  parent        INTEGER, -- references release_group_secondary_type.id
  child_order   INTEGER NOT NULL DEFAULT 0,
  description    TEXT,
  gid           uuid NOT NULL
);

CREATE TABLE release_group_secondary_type_join ( -- replicate (verbose)
  release_group INTEGER NOT NULL, -- PK, references release_group.id,

```

```

        secondary_type INTEGER NOT NULL, -- PK, references
release_group_secondary_type.id
    created TIMESTAMP WITH TIME ZONE NOT NULL DEFAULT now()
);

```

```

CREATE TABLE script ( -- replicate
    id SERIAL,
    iso_code CHAR(4) NOT NULL, -- ISO 15924
    iso_number CHAR(3) NOT NULL, -- ISO 15924
    name VARCHAR(100) NOT NULL,
    frequency SMALLINT NOT NULL DEFAULT 0
);

```

```

CREATE TABLE series ( -- replicate (verbose)
    id SERIAL,
    gid UUID NOT NULL,
    name VARCHAR NOT NULL,
    comment VARCHAR(255) NOT NULL DEFAULT "",
    type INTEGER NOT NULL, -- references series_type.id
    ordering_type INTEGER NOT NULL, -- references
series_ordering_type.id
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE series_type ( -- replicate (verbose)
    id SERIAL,
    name VARCHAR(255) NOT NULL,
    entity_type VARCHAR(50) NOT NULL,
    parent INTEGER, -- references series_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid uuid NOT NULL
);

```

```

CREATE TABLE series_ordering_type ( -- replicate (verbose)
    id SERIAL,
    name VARCHAR(255) NOT NULL,
    parent INTEGER, -- references series_ordering_type.id
    child_order INTEGER NOT NULL DEFAULT 0,
    description TEXT,
    gid uuid NOT NULL

```

);

```
CREATE TABLE series_gid_redirect ( -- replicate (verbose)
  gid          UUID NOT NULL, -- PK
  new_id       INTEGER NOT NULL, -- references series.id
  created      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);
```

```
CREATE TABLE series_alias_type ( -- replicate (verbose)
  id           SERIAL, -- PK
  name         TEXT NOT NULL,
  parent       INTEGER, -- references series_alias_type.id
  child_order  INTEGER NOT NULL DEFAULT 0,
  description  TEXT,
  gid          uuid NOT NULL
);
```

```
CREATE TABLE series_alias ( -- replicate (verbose)
  id           SERIAL, -- PK
  series       INTEGER NOT NULL, -- references series.id
  name         VARCHAR NOT NULL,
  locale       TEXT,
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type         INTEGER, -- references series_alias_type.id
  sort_name    VARCHAR NOT NULL,
  begin_date_year  SMALLINT,
  begin_date_month SMALLINT,
  begin_date_day   SMALLINT,
  end_date_year    SMALLINT,
  end_date_month   SMALLINT,
  end_date_day     SMALLINT,
  primary_for_locale BOOLEAN NOT NULL DEFAULT FALSE,
  ended           BOOLEAN NOT NULL DEFAULT FALSE
  CHECK (
    (
      -- If any end date fields are not null, then ended must be true
      (end_date_year IS NOT NULL OR
       end_date_month IS NOT NULL OR
       end_date_day IS NOT NULL) AND
      ended = TRUE
    ) OR (
```

```

        -- Otherwise, all end date fields must be null
        (end_date_year IS NULL AND
        end_date_month IS NULL AND
        end_date_day IS NULL)
    )
),
    CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
    CONSTRAINT search_hints_are_empty
    CHECK (
        (type <> 2) OR (
            type = 2 AND sort_name = name AND
            begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
            end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
            primary_for_locale IS FALSE AND locale IS NULL
        )
    )
);

```

```

CREATE TABLE series_annotation ( -- replicate (verbose)
    series          INTEGER NOT NULL, -- PK, references series.id
    annotation      INTEGER NOT NULL -- PK, references annotation.id
);

```

```

CREATE TABLE series_attribute_type ( -- replicate (verbose)
    id              SERIAL, -- PK
    name            VARCHAR(255) NOT NULL,
    comment         VARCHAR(255) NOT NULL DEFAULT "",
    free_text       BOOLEAN NOT NULL,
    parent          INTEGER, -- references series_attribute_type.id
    child_order     INTEGER NOT NULL DEFAULT 0,
    description     TEXT,
    gid             uuid NOT NULL
);

```

```

CREATE TABLE series_attribute_type_allowed_value ( -- replicate (verbose)
    id              SERIAL, -- PK
    series_attribute_type      INTEGER NOT NULL, -- references
series_attribute_type.id
    value           TEXT,

```

```

        parent                INTEGER, -- references
series_attribute_type_allowed_value.id
    child_order                INTEGER NOT NULL DEFAULT 0,
    description                 TEXT,
    gid                         uuid NOT NULL
);

```

```

CREATE TABLE series_attribute ( -- replicate (verbose)
    id                          SERIAL, -- PK
    series                      INTEGER NOT NULL, -- references series.id
    series_attribute_type       INTEGER NOT NULL, -- references
series_attribute_type.id
        series_attribute_type_allowed_value INTEGER, -- references
series_attribute_type_allowed_value.id
    series_attribute_text       TEXT
    CHECK (
        (series_attribute_type_allowed_value IS NULL AND
series_attribute_text IS NOT NULL)
        OR
        (series_attribute_type_allowed_value IS NOT NULL AND
series_attribute_text IS NULL)
    )
);

```

```

CREATE TABLE series_tag ( -- replicate (verbose)
    series                      INTEGER NOT NULL, -- PK, references series.id
    tag                         INTEGER NOT NULL, -- PK, references tag.id
    count                       INTEGER NOT NULL,
    last_updated                TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE series_tag_raw (
    series                      INTEGER NOT NULL, -- PK, references series.id
    editor                      INTEGER NOT NULL, -- PK, references editor.id
    tag                         INTEGER NOT NULL, -- PK, references tag.id
    is_upvote                   BOOLEAN NOT NULL DEFAULT TRUE
);

```

```

CREATE TABLE tag ( -- replicate (verbose)
    id                          SERIAL,
    name                        VARCHAR(255) NOT NULL,
    ref_count                   INTEGER NOT NULL DEFAULT 0
);

```



```

CREATE TABLE tag_relation
(
    tag1          INTEGER NOT NULL, -- PK, references tag.id
    tag2          INTEGER NOT NULL, -- PK, references tag.id
    weight        INTEGER NOT NULL,
    last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    CHECK (tag1 < tag2)
);

CREATE TABLE track ( -- replicate (verbose)
    id            SERIAL,
    gid           UUID NOT NULL,
    recording     INTEGER NOT NULL, -- references recording.id
    medium        INTEGER NOT NULL, -- references medium.id
    position      INTEGER NOT NULL,
    number        TEXT NOT NULL,
    name          VARCHAR NOT NULL,
    artist_credit INTEGER NOT NULL, -- references artist_credit.id
    length        INTEGER CHECK (length IS NULL OR length > 0),
    edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
    last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
    is_data_track BOOLEAN NOT NULL DEFAULT FALSE
);

CREATE TABLE track_gid_redirect ( -- replicate (verbose)
    gid           UUID NOT NULL, -- PK
    new_id        INTEGER NOT NULL, -- references track.id
    created       TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

CREATE TABLE track_raw ( -- replicate
    id            SERIAL, -- PK
    release       INTEGER NOT NULL, -- references release_raw.id
    title         VARCHAR(255) NOT NULL,
    artist        VARCHAR(255), -- For VA albums, otherwise empty
    sequence      INTEGER NOT NULL
);

CREATE TABLE medium_index ( -- replicate
    medium        INTEGER, -- PK, references medium.id CASCADE
    toc           CUBE

```

```
);
```

```
CREATE TABLE unreferenced_row_log (  
  table_name    VARCHAR NOT NULL, -- PK  
  row_id        INTEGER NOT NULL, -- PK  
  inserted      TIMESTAMP WITH TIME ZONE DEFAULT NOW()  
);
```

```
CREATE TABLE url ( -- replicate  
  id            SERIAL,  
  gid           UUID NOT NULL,  
  url           TEXT NOT NULL,  
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending  
>= 0),  
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW()  
);
```

```
CREATE TABLE url_gid_redirect ( -- replicate  
  gid           UUID NOT NULL, -- PK  
  new_id        INTEGER NOT NULL, -- references url.id  
  created       TIMESTAMP WITH TIME ZONE DEFAULT NOW()  
);
```

```
CREATE TABLE vote  
(  
  id            SERIAL,  
  editor        INTEGER NOT NULL, -- references editor.id  
  edit          INTEGER NOT NULL, -- references edit.id  
  vote          SMALLINT NOT NULL,  
  vote_time     TIMESTAMP WITH TIME ZONE DEFAULT NOW(),  
  superseded    BOOLEAN NOT NULL DEFAULT FALSE  
);
```

```
CREATE TABLE work ( -- replicate (verbose)  
  id            SERIAL,  
  gid           UUID NOT NULL,  
  name          VARCHAR NOT NULL,  
  type          INTEGER, -- references work_type.id  
  comment       VARCHAR(255) NOT NULL DEFAULT "",  
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending  
>= 0),  
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW()  
);
```

```

CREATE TABLE work_language ( -- replicate (verbose)
  work          INTEGER NOT NULL, -- PK, references work.id
  language      INTEGER NOT NULL, -- PK, references language.id
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  created       TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE work_rating_raw
(
  work          INTEGER NOT NULL, -- PK, references work.id
  editor        INTEGER NOT NULL, -- PK, references editor.id
  rating        SMALLINT NOT NULL CHECK (rating >= 0 AND rating <= 100)
);

```

```

CREATE TABLE work_tag_raw
(
  work          INTEGER NOT NULL, -- PK, references work.id
  editor        INTEGER NOT NULL, -- PK, references editor.id
  tag           INTEGER NOT NULL, -- PK, references tag.id
  is_upvote     BOOLEAN NOT NULL DEFAULT TRUE
);

```

```

CREATE TABLE work_alias_type ( -- replicate
  id            SERIAL,
  name          TEXT NOT NULL,
  parent        INTEGER, -- references work_alias_type.id
  child_order   INTEGER NOT NULL DEFAULT 0,
  description   TEXT,
  gid           uuid NOT NULL
);

```

```

CREATE TABLE work_alias ( -- replicate (verbose)
  id            SERIAL,
  work          INTEGER NOT NULL, -- references work.id
  name          VARCHAR NOT NULL,
  locale        TEXT,
  edits_pending INTEGER NOT NULL DEFAULT 0 CHECK (edits_pending
>= 0),
  last_updated  TIMESTAMP WITH TIME ZONE DEFAULT NOW(),
  type          INTEGER, -- references work_alias_type.id
  sort_name     VARCHAR NOT NULL,

```

```

begin_date_year  SMALLINT,
begin_date_month SMALLINT,
begin_date_day   SMALLINT,
end_date_year    SMALLINT,
end_date_month   SMALLINT,
end_date_day     SMALLINT,
primary_for_locale BOOLEAN NOT NULL DEFAULT false,
ended            BOOLEAN NOT NULL DEFAULT FALSE
CHECK (
  (
    -- If any end date fields are not null, then ended must be true
    (end_date_year IS NOT NULL OR
     end_date_month IS NOT NULL OR
     end_date_day IS NOT NULL) AND
    ended = TRUE
  ) OR (
    -- Otherwise, all end date fields must be null
    (end_date_year IS NULL AND
     end_date_month IS NULL AND
     end_date_day IS NULL)
  )
),
CONSTRAINT primary_check CHECK ((locale IS NULL AND
primary_for_locale IS FALSE) OR (locale IS NOT NULL)),
CONSTRAINT search_hints_are_empty
CHECK (
  (type <> 2) OR (
    type = 2 AND sort_name = name AND
    begin_date_year IS NULL AND begin_date_month IS NULL AND
begin_date_day IS NULL AND
    end_date_year IS NULL AND end_date_month IS NULL AND
end_date_day IS NULL AND
    primary_for_locale IS FALSE AND locale IS NULL
  )
)
);

CREATE TABLE work_annotation ( -- replicate (verbose)
  work          INTEGER NOT NULL, -- PK, references work.id
  annotation     INTEGER NOT NULL -- PK, references annotation.id
);

CREATE TABLE work_gid_redirect ( -- replicate (verbose)

```

```

gid          UUID NOT NULL, -- PK
new_id       INTEGER NOT NULL, -- references work.id
created      TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE work_meta ( -- replicate
  id          INTEGER NOT NULL, -- PK, references work.id CASCADE
  rating      SMALLINT CHECK (rating >= 0 AND rating <= 100),
  rating_count INTEGER
);

```

```

CREATE TABLE work_tag ( -- replicate (verbose)
  work        INTEGER NOT NULL, -- PK, references work.id
  tag         INTEGER NOT NULL, -- PK, references tag.id
  count       INTEGER NOT NULL,
  last_updated TIMESTAMP WITH TIME ZONE DEFAULT NOW()
);

```

```

CREATE TABLE work_type ( -- replicate
  id          SERIAL,
  name        VARCHAR(255) NOT NULL,
  parent      INTEGER, -- references work_type.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);

```

```

CREATE TABLE work_attribute_type ( -- replicate (verbose)
  id          SERIAL, -- PK
  name        VARCHAR(255) NOT NULL,
  comment     VARCHAR(255) NOT NULL DEFAULT "",
  free_text   BOOLEAN NOT NULL,
  parent      INTEGER, -- references work_attribute_type.id
  child_order INTEGER NOT NULL DEFAULT 0,
  description TEXT,
  gid         uuid NOT NULL
);

```

```

CREATE TABLE work_attribute_type_allowed_value ( -- replicate (verbose)
  id          SERIAL, -- PK
  work_attribute_type INTEGER NOT NULL, -- references
work_attribute_type.id
  value       TEXT,

```

```

        parent                                INTEGER, -- references
work_attribute_type_allowed_value.id
    child_order    INTEGER NOT NULL DEFAULT 0,
    description    TEXT,
    gid            uuid NOT NULL
);

```

```

CREATE TABLE work_attribute ( -- replicate (verbose)
    id                SERIAL, -- PK
    work              INTEGER NOT NULL, -- references work.id
    work_attribute_type    INTEGER NOT NULL, -- references
work_attribute_type.id
        work_attribute_type_allowed_value    INTEGER, -- references
work_attribute_type_allowed_value.id
    work_attribute_text    TEXT
    CHECK (
        (work_attribute_type_allowed_value IS NULL AND work_attribute_text
IS NOT NULL)
        OR
        (work_attribute_type_allowed_value IS NOT NULL AND
work_attribute_text IS NULL)
    )
);

```

```

COMMIT;

```

```

-- vi: set ts=4 sw=4 et :

```

```

-- Automatically generated, do not edit.

```

```

\set ON_ERROR_STOP 1

```

```

ALTER TABLE alternative_medium
    ADD CONSTRAINT alternative_medium_fk_medium
    FOREIGN KEY (medium)
    REFERENCES medium(id);

```

```

ALTER TABLE alternative_medium
    ADD CONSTRAINT alternative_medium_fk_alternative_release
    FOREIGN KEY (alternative_release)
    REFERENCES alternative_release(id);

```

```
ALTER TABLE alternative_medium_track
  ADD CONSTRAINT alternative_medium_track_fk_alternative_medium
  FOREIGN KEY (alternative_medium)
  REFERENCES alternative_medium(id);
```

```
ALTER TABLE alternative_medium_track
  ADD CONSTRAINT alternative_medium_track_fk_track
  FOREIGN KEY (track)
  REFERENCES track(id);
```

```
ALTER TABLE alternative_medium_track
  ADD CONSTRAINT alternative_medium_track_fk_alternative_track
  FOREIGN KEY (alternative_track)
  REFERENCES alternative_track(id);
```

```
ALTER TABLE alternative_release
  ADD CONSTRAINT alternative_release_fk_release
  FOREIGN KEY (release)
  REFERENCES release(id);
```

```
ALTER TABLE alternative_release
  ADD CONSTRAINT alternative_release_fk_artist_credit
  FOREIGN KEY (artist_credit)
  REFERENCES artist_credit(id);
```

```
ALTER TABLE alternative_release
  ADD CONSTRAINT alternative_release_fk_type
  FOREIGN KEY (type)
  REFERENCES alternative_release_type(id);
```

```
ALTER TABLE alternative_release
  ADD CONSTRAINT alternative_release_fk_language
  FOREIGN KEY (language)
  REFERENCES language(id);
```

```
ALTER TABLE alternative_release
  ADD CONSTRAINT alternative_release_fk_script
  FOREIGN KEY (script)
  REFERENCES script(id);
```

```
ALTER TABLE alternative_release_type
  ADD CONSTRAINT alternative_release_type_fk_parent
```

```
FOREIGN KEY (parent)
REFERENCES alternative_release_type(id);
```

```
ALTER TABLE alternative_track
ADD CONSTRAINT alternative_track_fk_artist_credit
FOREIGN KEY (artist_credit)
REFERENCES artist_credit(id);
```

```
ALTER TABLE annotation
ADD CONSTRAINT annotation_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE application
ADD CONSTRAINT application_fk_owner
FOREIGN KEY (owner)
REFERENCES editor(id);
```

```
ALTER TABLE area
ADD CONSTRAINT area_fk_type
FOREIGN KEY (type)
REFERENCES area_type(id);
```

```
ALTER TABLE area_alias
ADD CONSTRAINT area_alias_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE area_alias
ADD CONSTRAINT area_alias_fk_type
FOREIGN KEY (type)
REFERENCES area_alias_type(id);
```

```
ALTER TABLE area_alias_type
ADD CONSTRAINT area_alias_type_fk_parent
FOREIGN KEY (parent)
REFERENCES area_alias_type(id);
```

```
ALTER TABLE area_annotation
ADD CONSTRAINT area_annotation_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```



```
ALTER TABLE area_annotation
  ADD CONSTRAINT area_annotation_fk_annotation
  FOREIGN KEY (annotation)
  REFERENCES annotation(id);
```

```
ALTER TABLE area_attribute
  ADD CONSTRAINT area_attribute_fk_area
  FOREIGN KEY (area)
  REFERENCES area(id);
```

```
ALTER TABLE area_attribute
  ADD CONSTRAINT area_attribute_fk_area_attribute_type
  FOREIGN KEY (area_attribute_type)
  REFERENCES area_attribute_type(id);
```

```
ALTER TABLE area_attribute
  ADD CONSTRAINT area_attribute_fk_area_attribute_type_allowed_value
  FOREIGN KEY (area_attribute_type_allowed_value)
  REFERENCES area_attribute_type_allowed_value(id);
```

```
ALTER TABLE area_attribute_type
  ADD CONSTRAINT area_attribute_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES area_attribute_type(id);
```

```
ALTER TABLE area_attribute_type_allowed_value
  ADD CONSTRAINT
area_attribute_type_allowed_value_fk_area_attribute_type
  FOREIGN KEY (area_attribute_type)
  REFERENCES area_attribute_type(id);
```

```
ALTER TABLE area_attribute_type_allowed_value
  ADD CONSTRAINT area_attribute_type_allowed_value_fk_parent
  FOREIGN KEY (parent)
  REFERENCES area_attribute_type_allowed_value(id);
```

```
ALTER TABLE area_containment
  ADD CONSTRAINT area_containment_fk_descendant
  FOREIGN KEY (descendant)
  REFERENCES area(id);
```

```
ALTER TABLE area_containment
  ADD CONSTRAINT area_containment_fk_parent
```

```
FOREIGN KEY (parent)
REFERENCES area(id);
```

```
ALTER TABLE area_gid_redirect
ADD CONSTRAINT area_gid_redirect_fk_new_id
FOREIGN KEY (new_id)
REFERENCES area(id);
```

```
ALTER TABLE area_tag
ADD CONSTRAINT area_tag_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE area_tag
ADD CONSTRAINT area_tag_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE area_tag_raw
ADD CONSTRAINT area_tag_raw_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE area_tag_raw
ADD CONSTRAINT area_tag_raw_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE area_tag_raw
ADD CONSTRAINT area_tag_raw_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE area_type
ADD CONSTRAINT area_type_fk_parent
FOREIGN KEY (parent)
REFERENCES area_type(id);
```

```
ALTER TABLE artist
ADD CONSTRAINT artist_fk_type
FOREIGN KEY (type)
REFERENCES artist_type(id);
```

```
ALTER TABLE artist
  ADD CONSTRAINT artist_fk_area
  FOREIGN KEY (area)
  REFERENCES area(id);
```

```
ALTER TABLE artist
  ADD CONSTRAINT artist_fk_gender
  FOREIGN KEY (gender)
  REFERENCES gender(id);
```

```
ALTER TABLE artist
  ADD CONSTRAINT artist_fk_begin_area
  FOREIGN KEY (begin_area)
  REFERENCES area(id);
```

```
ALTER TABLE artist
  ADD CONSTRAINT artist_fk_end_area
  FOREIGN KEY (end_area)
  REFERENCES area(id);
```

```
ALTER TABLE artist_alias
  ADD CONSTRAINT artist_alias_fk_artist
  FOREIGN KEY (artist)
  REFERENCES artist(id);
```

```
ALTER TABLE artist_alias
  ADD CONSTRAINT artist_alias_fk_type
  FOREIGN KEY (type)
  REFERENCES artist_alias_type(id);
```

```
ALTER TABLE artist_alias_type
  ADD CONSTRAINT artist_alias_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES artist_alias_type(id);
```

```
ALTER TABLE artist_annotation
  ADD CONSTRAINT artist_annotation_fk_artist
  FOREIGN KEY (artist)
  REFERENCES artist(id);
```

```
ALTER TABLE artist_annotation
  ADD CONSTRAINT artist_annotation_fk_annotation
  FOREIGN KEY (annotation)
```

```
REFERENCES annotation(id);
```

```
ALTER TABLE artist_attribute  
  ADD CONSTRAINT artist_attribute_fk_artist  
  FOREIGN KEY (artist)  
  REFERENCES artist(id);
```

```
ALTER TABLE artist_attribute  
  ADD CONSTRAINT artist_attribute_fk_artist_attribute_type  
  FOREIGN KEY (artist_attribute_type)  
  REFERENCES artist_attribute_type(id);
```

```
ALTER TABLE artist_attribute  
  ADD CONSTRAINT  
  artist_attribute_fk_artist_attribute_type_allowed_value  
  FOREIGN KEY (artist_attribute_type_allowed_value)  
  REFERENCES artist_attribute_type_allowed_value(id);
```

```
ALTER TABLE artist_attribute_type  
  ADD CONSTRAINT artist_attribute_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES artist_attribute_type(id);
```

```
ALTER TABLE artist_attribute_type_allowed_value  
  ADD CONSTRAINT  
  artist_attribute_type_allowed_value_fk_artist_attribute_type  
  FOREIGN KEY (artist_attribute_type)  
  REFERENCES artist_attribute_type(id);
```

```
ALTER TABLE artist_attribute_type_allowed_value  
  ADD CONSTRAINT artist_attribute_type_allowed_value_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES artist_attribute_type_allowed_value(id);
```

```
ALTER TABLE artist_credit_gid_redirect  
  ADD CONSTRAINT artist_credit_gid_redirect_fk_new_id  
  FOREIGN KEY (new_id)  
  REFERENCES artist_credit(id);
```

```
ALTER TABLE artist_credit_name  
  ADD CONSTRAINT artist_credit_name_fk_artist_credit  
  FOREIGN KEY (artist_credit)  
  REFERENCES artist_credit(id)
```

```
ON DELETE CASCADE;
```

```
ALTER TABLE artist_credit_name  
  ADD CONSTRAINT artist_credit_name_fk_artist  
  FOREIGN KEY (artist)  
  REFERENCES artist(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE artist_gid_redirect  
  ADD CONSTRAINT artist_gid_redirect_fk_new_id  
  FOREIGN KEY (new_id)  
  REFERENCES artist(id);
```

```
ALTER TABLE artist_ipi  
  ADD CONSTRAINT artist_ipi_fk_artist  
  FOREIGN KEY (artist)  
  REFERENCES artist(id);
```

```
ALTER TABLE artist_isni  
  ADD CONSTRAINT artist_isni_fk_artist  
  FOREIGN KEY (artist)  
  REFERENCES artist(id);
```

```
ALTER TABLE artist_meta  
  ADD CONSTRAINT artist_meta_fk_id  
  FOREIGN KEY (id)  
  REFERENCES artist(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE artist_rating_raw  
  ADD CONSTRAINT artist_rating_raw_fk_artist  
  FOREIGN KEY (artist)  
  REFERENCES artist(id);
```

```
ALTER TABLE artist_rating_raw  
  ADD CONSTRAINT artist_rating_raw_fk_editor  
  FOREIGN KEY (editor)  
  REFERENCES editor(id);
```

```
ALTER TABLE artist_release  
  ADD CONSTRAINT artist_release_fk_artist  
  FOREIGN KEY (artist)  
  REFERENCES artist(id)
```

ON DELETE CASCADE;

```
ALTER TABLE artist_release
  ADD CONSTRAINT artist_release_fk_release
  FOREIGN KEY (release)
  REFERENCES release(id)
  ON DELETE CASCADE;
```

```
ALTER TABLE artist_release_group
  ADD CONSTRAINT artist_release_group_fk_artist
  FOREIGN KEY (artist)
  REFERENCES artist(id)
  ON DELETE CASCADE;
```

```
ALTER TABLE artist_release_group
  ADD CONSTRAINT artist_release_group_fk_release_group
  FOREIGN KEY (release_group)
  REFERENCES release_group(id)
  ON DELETE CASCADE;
```

```
ALTER TABLE artist_tag
  ADD CONSTRAINT artist_tag_fk_artist
  FOREIGN KEY (artist)
  REFERENCES artist(id);
```

```
ALTER TABLE artist_tag
  ADD CONSTRAINT artist_tag_fk_tag
  FOREIGN KEY (tag)
  REFERENCES tag(id);
```

```
ALTER TABLE artist_tag_raw
  ADD CONSTRAINT artist_tag_raw_fk_artist
  FOREIGN KEY (artist)
  REFERENCES artist(id);
```

```
ALTER TABLE artist_tag_raw
  ADD CONSTRAINT artist_tag_raw_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE artist_tag_raw
  ADD CONSTRAINT artist_tag_raw_fk_tag
  FOREIGN KEY (tag)
```

```
REFERENCES tag(id);
```

```
ALTER TABLE artist_type  
  ADD CONSTRAINT artist_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES artist_type(id);
```

```
ALTER TABLE autoeditor_election  
  ADD CONSTRAINT autoeditor_election_fk_candidate  
  FOREIGN KEY (candidate)  
  REFERENCES editor(id);
```

```
ALTER TABLE autoeditor_election  
  ADD CONSTRAINT autoeditor_election_fk_proposer  
  FOREIGN KEY (proposer)  
  REFERENCES editor(id);
```

```
ALTER TABLE autoeditor_election  
  ADD CONSTRAINT autoeditor_election_fk_seconder_1  
  FOREIGN KEY (seconder_1)  
  REFERENCES editor(id);
```

```
ALTER TABLE autoeditor_election  
  ADD CONSTRAINT autoeditor_election_fk_seconder_2  
  FOREIGN KEY (seconder_2)  
  REFERENCES editor(id);
```

```
ALTER TABLE autoeditor_election_vote  
  ADD CONSTRAINT autoeditor_election_vote_fk_autoeditor_election  
  FOREIGN KEY (autoeditor_election)  
  REFERENCES autoeditor_election(id);
```

```
ALTER TABLE autoeditor_election_vote  
  ADD CONSTRAINT autoeditor_election_vote_fk_voter  
  FOREIGN KEY (voter)  
  REFERENCES editor(id);
```

```
ALTER TABLE cdtoc_raw  
  ADD CONSTRAINT cdtoc_raw_fk_release  
  FOREIGN KEY (release)  
  REFERENCES release_raw(id);
```

```
ALTER TABLE country_area
```

```
ADD CONSTRAINT country_area_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE edit
ADD CONSTRAINT edit_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE edit
ADD CONSTRAINT edit_fk_language
FOREIGN KEY (language)
REFERENCES language(id);
```

```
ALTER TABLE edit_area
ADD CONSTRAINT edit_area_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_area
ADD CONSTRAINT edit_area_fk_area
FOREIGN KEY (area)
REFERENCES area(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_artist
ADD CONSTRAINT edit_artist_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_artist
ADD CONSTRAINT edit_artist_fk_artist
FOREIGN KEY (artist)
REFERENCES artist(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_data
ADD CONSTRAINT edit_data_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_event
ADD CONSTRAINT edit_event_fk_edit
```



```
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_event
ADD CONSTRAINT edit_event_fk_event
FOREIGN KEY (event)
REFERENCES event(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_genre
ADD CONSTRAINT edit_genre_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_genre
ADD CONSTRAINT edit_genre_fk_genre
FOREIGN KEY (genre)
REFERENCES genre(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_instrument
ADD CONSTRAINT edit_instrument_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_instrument
ADD CONSTRAINT edit_instrument_fk_instrument
FOREIGN KEY (instrument)
REFERENCES instrument(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_label
ADD CONSTRAINT edit_label_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_label
ADD CONSTRAINT edit_label_fk_label
FOREIGN KEY (label)
REFERENCES label(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_mood
```

```
ADD CONSTRAINT edit_mood_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_mood
ADD CONSTRAINT edit_mood_fk_mood
FOREIGN KEY (mood)
REFERENCES mood(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_note
ADD CONSTRAINT edit_note_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE edit_note
ADD CONSTRAINT edit_note_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_note_change
ADD CONSTRAINT edit_note_change_fk_edit_note
FOREIGN KEY (edit_note)
REFERENCES edit_note(id);
```

```
ALTER TABLE edit_note_change
ADD CONSTRAINT edit_note_change_fk_change_editor
FOREIGN KEY (change_editor)
REFERENCES editor(id);
```

```
ALTER TABLE edit_note_recipient
ADD CONSTRAINT edit_note_recipient_fk_recipient
FOREIGN KEY (recipient)
REFERENCES editor(id);
```

```
ALTER TABLE edit_note_recipient
ADD CONSTRAINT edit_note_recipient_fk_edit_note
FOREIGN KEY (edit_note)
REFERENCES edit_note(id);
```

```
ALTER TABLE edit_place
ADD CONSTRAINT edit_place_fk_edit
FOREIGN KEY (edit)
```

```
REFERENCES edit(id);
```

```
ALTER TABLE edit_place  
  ADD CONSTRAINT edit_place_fk_place  
  FOREIGN KEY (place)  
  REFERENCES place(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE edit_recording  
  ADD CONSTRAINT edit_recording_fk_edit  
  FOREIGN KEY (edit)  
  REFERENCES edit(id);
```

```
ALTER TABLE edit_recording  
  ADD CONSTRAINT edit_recording_fk_recording  
  FOREIGN KEY (recording)  
  REFERENCES recording(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE edit_release  
  ADD CONSTRAINT edit_release_fk_edit  
  FOREIGN KEY (edit)  
  REFERENCES edit(id);
```

```
ALTER TABLE edit_release  
  ADD CONSTRAINT edit_release_fk_release  
  FOREIGN KEY (release)  
  REFERENCES release(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE edit_release_group  
  ADD CONSTRAINT edit_release_group_fk_edit  
  FOREIGN KEY (edit)  
  REFERENCES edit(id);
```

```
ALTER TABLE edit_release_group  
  ADD CONSTRAINT edit_release_group_fk_release_group  
  FOREIGN KEY (release_group)  
  REFERENCES release_group(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE edit_series  
  ADD CONSTRAINT edit_series_fk_edit
```

```
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_series
ADD CONSTRAINT edit_series_fk_series
FOREIGN KEY (series)
REFERENCES series(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_url
ADD CONSTRAINT edit_url_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_url
ADD CONSTRAINT edit_url_fk_url
FOREIGN KEY (url)
REFERENCES url(id)
ON DELETE CASCADE;
```

```
ALTER TABLE edit_work
ADD CONSTRAINT edit_work_fk_edit
FOREIGN KEY (edit)
REFERENCES edit(id);
```

```
ALTER TABLE edit_work
ADD CONSTRAINT edit_work_fk_work
FOREIGN KEY (work)
REFERENCES work(id)
ON DELETE CASCADE;
```

```
ALTER TABLE editor
ADD CONSTRAINT editor_fk_gender
FOREIGN KEY (gender)
REFERENCES gender(id);
```

```
ALTER TABLE editor
ADD CONSTRAINT editor_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE editor_collection
ADD CONSTRAINT editor_collection_fk_editor
```

```
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE editor_collection
ADD CONSTRAINT editor_collection_fk_type
FOREIGN KEY (type)
REFERENCES editor_collection_type(id);
```

```
ALTER TABLE editor_collection_area
ADD CONSTRAINT editor_collection_area_fk_collection
FOREIGN KEY (collection)
REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_area
ADD CONSTRAINT editor_collection_area_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE editor_collection_artist
ADD CONSTRAINT editor_collection_artist_fk_collection
FOREIGN KEY (collection)
REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_artist
ADD CONSTRAINT editor_collection_artist_fk_artist
FOREIGN KEY (artist)
REFERENCES artist(id);
```

```
ALTER TABLE editor_collection_collaborator
ADD CONSTRAINT editor_collection_collaborator_fk_collection
FOREIGN KEY (collection)
REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_collaborator
ADD CONSTRAINT editor_collection_collaborator_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE editor_collection_deleted_entity
ADD CONSTRAINT editor_collection_deleted_entity_fk_collection
FOREIGN KEY (collection)
REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_deleted_entity
  ADD CONSTRAINT editor_collection_deleted_entity_fk_gid
  FOREIGN KEY (gid)
  REFERENCES deleted_entity(gid);
```

```
ALTER TABLE editor_collection_event
  ADD CONSTRAINT editor_collection_event_fk_collection
  FOREIGN KEY (collection)
  REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_event
  ADD CONSTRAINT editor_collection_event_fk_event
  FOREIGN KEY (event)
  REFERENCES event(id);
```

```
ALTER TABLE editor_collection_genre
  ADD CONSTRAINT editor_collection_genre_fk_collection
  FOREIGN KEY (collection)
  REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_genre
  ADD CONSTRAINT editor_collection_genre_fk_genre
  FOREIGN KEY (genre)
  REFERENCES genre(id);
```

```
ALTER TABLE editor_collection_gid_redirect
  ADD CONSTRAINT editor_collection_gid_redirect_fk_new_id
  FOREIGN KEY (new_id)
  REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_instrument
  ADD CONSTRAINT editor_collection_instrument_fk_collection
  FOREIGN KEY (collection)
  REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_instrument
  ADD CONSTRAINT editor_collection_instrument_fk_instrument
  FOREIGN KEY (instrument)
  REFERENCES instrument(id);
```

```
ALTER TABLE editor_collection_label
  ADD CONSTRAINT editor_collection_label_fk_collection
  FOREIGN KEY (collection)
```

```
REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_label  
  ADD CONSTRAINT editor_collection_label_fk_label  
  FOREIGN KEY (label)  
  REFERENCES label(id);
```

```
ALTER TABLE editor_collection_place  
  ADD CONSTRAINT editor_collection_place_fk_collection  
  FOREIGN KEY (collection)  
  REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_place  
  ADD CONSTRAINT editor_collection_place_fk_place  
  FOREIGN KEY (place)  
  REFERENCES place(id);
```

```
ALTER TABLE editor_collection_recording  
  ADD CONSTRAINT editor_collection_recording_fk_collection  
  FOREIGN KEY (collection)  
  REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_recording  
  ADD CONSTRAINT editor_collection_recording_fk_recording  
  FOREIGN KEY (recording)  
  REFERENCES recording(id);
```

```
ALTER TABLE editor_collection_release  
  ADD CONSTRAINT editor_collection_release_fk_collection  
  FOREIGN KEY (collection)  
  REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_release  
  ADD CONSTRAINT editor_collection_release_fk_release  
  FOREIGN KEY (release)  
  REFERENCES release(id);
```

```
ALTER TABLE editor_collection_release_group  
  ADD CONSTRAINT editor_collection_release_group_fk_collection  
  FOREIGN KEY (collection)  
  REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_release_group
```

```
ADD CONSTRAINT editor_collection_release_group_fk_release_group
FOREIGN KEY (release_group)
REFERENCES release_group(id);
```

```
ALTER TABLE editor_collection_series
ADD CONSTRAINT editor_collection_series_fk_collection
FOREIGN KEY (collection)
REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_series
ADD CONSTRAINT editor_collection_series_fk_series
FOREIGN KEY (series)
REFERENCES series(id);
```

```
ALTER TABLE editor_collection_type
ADD CONSTRAINT editor_collection_type_fk_parent
FOREIGN KEY (parent)
REFERENCES editor_collection_type(id);
```

```
ALTER TABLE editor_collection_work
ADD CONSTRAINT editor_collection_work_fk_collection
FOREIGN KEY (collection)
REFERENCES editor_collection(id);
```

```
ALTER TABLE editor_collection_work
ADD CONSTRAINT editor_collection_work_fk_work
FOREIGN KEY (work)
REFERENCES work(id);
```

```
ALTER TABLE editor_language
ADD CONSTRAINT editor_language_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE editor_language
ADD CONSTRAINT editor_language_fk_language
FOREIGN KEY (language)
REFERENCES language(id);
```

```
ALTER TABLE editor_oauth_token
ADD CONSTRAINT editor_oauth_token_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```



```
ALTER TABLE editor_oauth_token
  ADD CONSTRAINT editor_oauth_token_fk_application
  FOREIGN KEY (application)
  REFERENCES application(id);
```

```
ALTER TABLE editor_preference
  ADD CONSTRAINT editor_preference_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_artist
  ADD CONSTRAINT editor_subscribe_artist_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_artist
  ADD CONSTRAINT editor_subscribe_artist_fk_artist
  FOREIGN KEY (artist)
  REFERENCES artist(id);
```

```
ALTER TABLE editor_subscribe_artist
  ADD CONSTRAINT editor_subscribe_artist_fk_last_edit_sent
  FOREIGN KEY (last_edit_sent)
  REFERENCES edit(id);
```

```
ALTER TABLE editor_subscribe_artist_deleted
  ADD CONSTRAINT editor_subscribe_artist_deleted_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_artist_deleted
  ADD CONSTRAINT editor_subscribe_artist_deleted_fk_gid
  FOREIGN KEY (gid)
  REFERENCES deleted_entity(gid);
```

```
ALTER TABLE editor_subscribe_artist_deleted
  ADD CONSTRAINT editor_subscribe_artist_deleted_fk_deleted_by
  FOREIGN KEY (deleted_by)
  REFERENCES edit(id);
```

```
ALTER TABLE editor_subscribe_collection
  ADD CONSTRAINT editor_subscribe_collection_fk_editor
```

```
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_editor
ADD CONSTRAINT editor_subscribe_editor_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_editor
ADD CONSTRAINT editor_subscribe_editor_fk_subscribed_editor
FOREIGN KEY (subscribed_editor)
REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_label
ADD CONSTRAINT editor_subscribe_label_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_label
ADD CONSTRAINT editor_subscribe_label_fk_label
FOREIGN KEY (label)
REFERENCES label(id);
```

```
ALTER TABLE editor_subscribe_label
ADD CONSTRAINT editor_subscribe_label_fk_last_edit_sent
FOREIGN KEY (last_edit_sent)
REFERENCES edit(id);
```

```
ALTER TABLE editor_subscribe_label_deleted
ADD CONSTRAINT editor_subscribe_label_deleted_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_label_deleted
ADD CONSTRAINT editor_subscribe_label_deleted_fk_gid
FOREIGN KEY (gid)
REFERENCES deleted_entity(gid);
```

```
ALTER TABLE editor_subscribe_label_deleted
ADD CONSTRAINT editor_subscribe_label_deleted_fk_deleted_by
FOREIGN KEY (deleted_by)
REFERENCES edit(id);
```

```
ALTER TABLE editor_subscribe_series
  ADD CONSTRAINT editor_subscribe_series_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_series
  ADD CONSTRAINT editor_subscribe_series_fk_series
  FOREIGN KEY (series)
  REFERENCES series(id);
```

```
ALTER TABLE editor_subscribe_series
  ADD CONSTRAINT editor_subscribe_series_fk_last_edit_sent
  FOREIGN KEY (last_edit_sent)
  REFERENCES edit(id);
```

```
ALTER TABLE editor_subscribe_series_deleted
  ADD CONSTRAINT editor_subscribe_series_deleted_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE editor_subscribe_series_deleted
  ADD CONSTRAINT editor_subscribe_series_deleted_fk_gid
  FOREIGN KEY (gid)
  REFERENCES deleted_entity(gid);
```

```
ALTER TABLE editor_subscribe_series_deleted
  ADD CONSTRAINT editor_subscribe_series_deleted_fk_deleted_by
  FOREIGN KEY (deleted_by)
  REFERENCES edit(id);
```

```
ALTER TABLE event
  ADD CONSTRAINT event_fk_type
  FOREIGN KEY (type)
  REFERENCES event_type(id);
```

```
ALTER TABLE event_alias
  ADD CONSTRAINT event_alias_fk_event
  FOREIGN KEY (event)
  REFERENCES event(id);
```

```
ALTER TABLE event_alias
  ADD CONSTRAINT event_alias_fk_type
  FOREIGN KEY (type)
```

```
REFERENCES event_alias_type(id);
```

```
ALTER TABLE event_alias_type  
  ADD CONSTRAINT event_alias_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES event_alias_type(id);
```

```
ALTER TABLE event_annotation  
  ADD CONSTRAINT event_annotation_fk_event  
  FOREIGN KEY (event)  
  REFERENCES event(id);
```

```
ALTER TABLE event_annotation  
  ADD CONSTRAINT event_annotation_fk_annotation  
  FOREIGN KEY (annotation)  
  REFERENCES annotation(id);
```

```
ALTER TABLE event_attribute  
  ADD CONSTRAINT event_attribute_fk_event  
  FOREIGN KEY (event)  
  REFERENCES event(id);
```

```
ALTER TABLE event_attribute  
  ADD CONSTRAINT event_attribute_fk_event_attribute_type  
  FOREIGN KEY (event_attribute_type)  
  REFERENCES event_attribute_type(id);
```

```
ALTER TABLE event_attribute  
                                     ADD CONSTRAINT  
event_attribute_fk_event_attribute_type_allowed_value  
  FOREIGN KEY (event_attribute_type_allowed_value)  
  REFERENCES event_attribute_type_allowed_value(id);
```

```
ALTER TABLE event_attribute_type  
  ADD CONSTRAINT event_attribute_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES event_attribute_type(id);
```

```
ALTER TABLE event_attribute_type_allowed_value  
                                     ADD CONSTRAINT  
event_attribute_type_allowed_value_fk_event_attribute_type  
  FOREIGN KEY (event_attribute_type)  
  REFERENCES event_attribute_type(id);
```

```
ALTER TABLE event_attribute_type_allowed_value
  ADD CONSTRAINT event_attribute_type_allowed_value_fk_parent
  FOREIGN KEY (parent)
  REFERENCES event_attribute_type_allowed_value(id);
```

```
ALTER TABLE event_gid_redirect
  ADD CONSTRAINT event_gid_redirect_fk_new_id
  FOREIGN KEY (new_id)
  REFERENCES event(id);
```

```
ALTER TABLE event_meta
  ADD CONSTRAINT event_meta_fk_id
  FOREIGN KEY (id)
  REFERENCES event(id)
  ON DELETE CASCADE;
```

```
ALTER TABLE event_rating_raw
  ADD CONSTRAINT event_rating_raw_fk_event
  FOREIGN KEY (event)
  REFERENCES event(id);
```

```
ALTER TABLE event_rating_raw
  ADD CONSTRAINT event_rating_raw_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE event_tag
  ADD CONSTRAINT event_tag_fk_event
  FOREIGN KEY (event)
  REFERENCES event(id);
```

```
ALTER TABLE event_tag
  ADD CONSTRAINT event_tag_fk_tag
  FOREIGN KEY (tag)
  REFERENCES tag(id);
```

```
ALTER TABLE event_tag_raw
  ADD CONSTRAINT event_tag_raw_fk_event
  FOREIGN KEY (event)
  REFERENCES event(id);
```

```
ALTER TABLE event_tag_raw
```

```
ADD CONSTRAINT event_tag_raw_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE event_tag_raw
ADD CONSTRAINT event_tag_raw_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE event_type
ADD CONSTRAINT event_type_fk_parent
FOREIGN KEY (parent)
REFERENCES event_type(id);
```

```
ALTER TABLE gender
ADD CONSTRAINT gender_fk_parent
FOREIGN KEY (parent)
REFERENCES gender(id);
```

```
ALTER TABLE genre_alias
ADD CONSTRAINT genre_alias_fk_genre
FOREIGN KEY (genre)
REFERENCES genre(id);
```

```
ALTER TABLE genre_alias
ADD CONSTRAINT genre_alias_fk_type
FOREIGN KEY (type)
REFERENCES genre_alias_type(id);
```

```
ALTER TABLE genre_alias_type
ADD CONSTRAINT genre_alias_type_fk_parent
FOREIGN KEY (parent)
REFERENCES genre_alias_type(id);
```

```
ALTER TABLE genre_annotation
ADD CONSTRAINT genre_annotation_fk_genre
FOREIGN KEY (genre)
REFERENCES genre(id);
```

```
ALTER TABLE genre_annotation
ADD CONSTRAINT genre_annotation_fk_annotation
FOREIGN KEY (annotation)
REFERENCES annotation(id);
```

```
ALTER TABLE instrument
  ADD CONSTRAINT instrument_fk_type
  FOREIGN KEY (type)
  REFERENCES instrument_type(id);
```

```
ALTER TABLE instrument_alias
  ADD CONSTRAINT instrument_alias_fk_instrument
  FOREIGN KEY (instrument)
  REFERENCES instrument(id);
```

```
ALTER TABLE instrument_alias
  ADD CONSTRAINT instrument_alias_fk_type
  FOREIGN KEY (type)
  REFERENCES instrument_alias_type(id);
```

```
ALTER TABLE instrument_alias_type
  ADD CONSTRAINT instrument_alias_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES instrument_alias_type(id);
```

```
ALTER TABLE instrument_annotation
  ADD CONSTRAINT instrument_annotation_fk_instrument
  FOREIGN KEY (instrument)
  REFERENCES instrument(id);
```

```
ALTER TABLE instrument_annotation
  ADD CONSTRAINT instrument_annotation_fk_annotation
  FOREIGN KEY (annotation)
  REFERENCES annotation(id);
```

```
ALTER TABLE instrument_attribute
  ADD CONSTRAINT instrument_attribute_fk_instrument
  FOREIGN KEY (instrument)
  REFERENCES instrument(id);
```

```
ALTER TABLE instrument_attribute
  ADD CONSTRAINT instrument_attribute_fk_instrument_attribute_type
  FOREIGN KEY (instrument_attribute_type)
  REFERENCES instrument_attribute_type(id);
```

```
ALTER TABLE instrument_attribute
```

```
                                ADD                                CONSTRAINT
instrument_attribute_fk_instrument_attribute_type_allowed_value
    FOREIGN KEY (instrument_attribute_type_allowed_value)
    REFERENCES instrument_attribute_type_allowed_value(id);
```

```
ALTER TABLE instrument_attribute_type
    ADD CONSTRAINT instrument_attribute_type_fk_parent
    FOREIGN KEY (parent)
    REFERENCES instrument_attribute_type(id);
```

```
ALTER TABLE instrument_attribute_type_allowed_value
                                ADD                                CONSTRAINT
instrument_attribute_type_allowed_value_fk_instrument_attribute_type
    FOREIGN KEY (instrument_attribute_type)
    REFERENCES instrument_attribute_type(id);
```

```
ALTER TABLE instrument_attribute_type_allowed_value
    ADD CONSTRAINT instrument_attribute_type_allowed_value_fk_parent
    FOREIGN KEY (parent)
    REFERENCES instrument_attribute_type_allowed_value(id);
```

```
ALTER TABLE instrument_gid_redirect
    ADD CONSTRAINT instrument_gid_redirect_fk_new_id
    FOREIGN KEY (new_id)
    REFERENCES instrument(id);
```

```
ALTER TABLE instrument_tag
    ADD CONSTRAINT instrument_tag_fk_instrument
    FOREIGN KEY (instrument)
    REFERENCES instrument(id);
```

```
ALTER TABLE instrument_tag
    ADD CONSTRAINT instrument_tag_fk_tag
    FOREIGN KEY (tag)
    REFERENCES tag(id);
```

```
ALTER TABLE instrument_tag_raw
    ADD CONSTRAINT instrument_tag_raw_fk_instrument
    FOREIGN KEY (instrument)
    REFERENCES instrument(id);
```

```
ALTER TABLE instrument_tag_raw
    ADD CONSTRAINT instrument_tag_raw_fk_editor
```



```
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE instrument_tag_raw
ADD CONSTRAINT instrument_tag_raw_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE instrument_type
ADD CONSTRAINT instrument_type_fk_parent
FOREIGN KEY (parent)
REFERENCES instrument_type(id);
```

```
ALTER TABLE iso_3166_1
ADD CONSTRAINT iso_3166_1_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE iso_3166_2
ADD CONSTRAINT iso_3166_2_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE iso_3166_3
ADD CONSTRAINT iso_3166_3_fk_area
FOREIGN KEY (area)
REFERENCES area(id);
```

```
ALTER TABLE isrc
ADD CONSTRAINT isrc_fk_recording
FOREIGN KEY (recording)
REFERENCES recording(id);
```

```
ALTER TABLE iswc
ADD CONSTRAINT iswc_fk_work
FOREIGN KEY (work)
REFERENCES work(id);
```

```
ALTER TABLE l_area_area
ADD CONSTRAINT l_area_area_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_area_area
  ADD CONSTRAINT l_area_area_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES area(id);
```

```
ALTER TABLE l_area_area
  ADD CONSTRAINT l_area_area_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES area(id);
```

```
ALTER TABLE l_area_artist
  ADD CONSTRAINT l_area_artist_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_area_artist
  ADD CONSTRAINT l_area_artist_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES area(id);
```

```
ALTER TABLE l_area_artist
  ADD CONSTRAINT l_area_artist_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES artist(id);
```

```
ALTER TABLE l_area_event
  ADD CONSTRAINT l_area_event_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_area_event
  ADD CONSTRAINT l_area_event_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES area(id);
```

```
ALTER TABLE l_area_event
  ADD CONSTRAINT l_area_event_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES event(id);
```

```
ALTER TABLE l_area_genre
  ADD CONSTRAINT l_area_genre_fk_link
  FOREIGN KEY (link)
```

```
REFERENCES link(id);
```

```
ALTER TABLE l_area_genre  
  ADD CONSTRAINT l_area_genre_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES area(id);
```

```
ALTER TABLE l_area_genre  
  ADD CONSTRAINT l_area_genre_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES genre(id);
```

```
ALTER TABLE l_area_instrument  
  ADD CONSTRAINT l_area_instrument_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_area_instrument  
  ADD CONSTRAINT l_area_instrument_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES area(id);
```

```
ALTER TABLE l_area_instrument  
  ADD CONSTRAINT l_area_instrument_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES instrument(id);
```

```
ALTER TABLE l_area_label  
  ADD CONSTRAINT l_area_label_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_area_label  
  ADD CONSTRAINT l_area_label_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES area(id);
```

```
ALTER TABLE l_area_label  
  ADD CONSTRAINT l_area_label_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES label(id);
```

```
ALTER TABLE l_area_mood
```

```
ADD CONSTRAINT l_area_mood_fk_link  
FOREIGN KEY (link)  
REFERENCES link(id);
```

```
ALTER TABLE l_area_mood  
ADD CONSTRAINT l_area_mood_fk_entity0  
FOREIGN KEY (entity0)  
REFERENCES area(id);
```

```
ALTER TABLE l_area_mood  
ADD CONSTRAINT l_area_mood_fk_entity1  
FOREIGN KEY (entity1)  
REFERENCES mood(id);
```

```
ALTER TABLE l_area_place  
ADD CONSTRAINT l_area_place_fk_link  
FOREIGN KEY (link)  
REFERENCES link(id);
```

```
ALTER TABLE l_area_place  
ADD CONSTRAINT l_area_place_fk_entity0  
FOREIGN KEY (entity0)  
REFERENCES area(id);
```

```
ALTER TABLE l_area_place  
ADD CONSTRAINT l_area_place_fk_entity1  
FOREIGN KEY (entity1)  
REFERENCES place(id);
```

```
ALTER TABLE l_area_recording  
ADD CONSTRAINT l_area_recording_fk_link  
FOREIGN KEY (link)  
REFERENCES link(id);
```

```
ALTER TABLE l_area_recording  
ADD CONSTRAINT l_area_recording_fk_entity0  
FOREIGN KEY (entity0)  
REFERENCES area(id);
```

```
ALTER TABLE l_area_recording  
ADD CONSTRAINT l_area_recording_fk_entity1  
FOREIGN KEY (entity1)  
REFERENCES recording(id);
```

```
ALTER TABLE l_area_release
  ADD CONSTRAINT l_area_release_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_area_release
  ADD CONSTRAINT l_area_release_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES area(id);
```

```
ALTER TABLE l_area_release
  ADD CONSTRAINT l_area_release_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release(id);
```

```
ALTER TABLE l_area_release_group
  ADD CONSTRAINT l_area_release_group_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_area_release_group
  ADD CONSTRAINT l_area_release_group_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES area(id);
```

```
ALTER TABLE l_area_release_group
  ADD CONSTRAINT l_area_release_group_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release_group(id);
```

```
ALTER TABLE l_area_series
  ADD CONSTRAINT l_area_series_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_area_series
  ADD CONSTRAINT l_area_series_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES area(id);
```

```
ALTER TABLE l_area_series
  ADD CONSTRAINT l_area_series_fk_entity1
```

```
FOREIGN KEY (entity1)
REFERENCES series(id);
```

```
ALTER TABLE l_area_url
ADD CONSTRAINT l_area_url_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_area_url
ADD CONSTRAINT l_area_url_fk_entity0
FOREIGN KEY (entity0)
REFERENCES area(id);
```

```
ALTER TABLE l_area_url
ADD CONSTRAINT l_area_url_fk_entity1
FOREIGN KEY (entity1)
REFERENCES url(id);
```

```
ALTER TABLE l_area_work
ADD CONSTRAINT l_area_work_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_area_work
ADD CONSTRAINT l_area_work_fk_entity0
FOREIGN KEY (entity0)
REFERENCES area(id);
```

```
ALTER TABLE l_area_work
ADD CONSTRAINT l_area_work_fk_entity1
FOREIGN KEY (entity1)
REFERENCES work(id);
```

```
ALTER TABLE l_artist_artist
ADD CONSTRAINT l_artist_artist_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_artist_artist
ADD CONSTRAINT l_artist_artist_fk_entity0
FOREIGN KEY (entity0)
REFERENCES artist(id);
```

```
ALTER TABLE l_artist_artist
  ADD CONSTRAINT l_artist_artist_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES artist(id);
```

```
ALTER TABLE l_artist_event
  ADD CONSTRAINT l_artist_event_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_artist_event
  ADD CONSTRAINT l_artist_event_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES artist(id);
```

```
ALTER TABLE l_artist_event
  ADD CONSTRAINT l_artist_event_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES event(id);
```

```
ALTER TABLE l_artist_genre
  ADD CONSTRAINT l_artist_genre_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_artist_genre
  ADD CONSTRAINT l_artist_genre_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES artist(id);
```

```
ALTER TABLE l_artist_genre
  ADD CONSTRAINT l_artist_genre_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES genre(id);
```

```
ALTER TABLE l_artist_instrument
  ADD CONSTRAINT l_artist_instrument_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_artist_instrument
  ADD CONSTRAINT l_artist_instrument_fk_entity0
  FOREIGN KEY (entity0)
```

```
REFERENCES artist(id);
```

```
ALTER TABLE l_artist_instrument  
  ADD CONSTRAINT l_artist_instrument_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES instrument(id);
```

```
ALTER TABLE l_artist_label  
  ADD CONSTRAINT l_artist_label_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_artist_label  
  ADD CONSTRAINT l_artist_label_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES artist(id);
```

```
ALTER TABLE l_artist_label  
  ADD CONSTRAINT l_artist_label_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES label(id);
```

```
ALTER TABLE l_artist_mood  
  ADD CONSTRAINT l_artist_mood_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_artist_mood  
  ADD CONSTRAINT l_artist_mood_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES artist(id);
```

```
ALTER TABLE l_artist_mood  
  ADD CONSTRAINT l_artist_mood_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES mood(id);
```

```
ALTER TABLE l_artist_place  
  ADD CONSTRAINT l_artist_place_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_artist_place
```



```
ADD CONSTRAINT l_artist_place_fk_entity0
FOREIGN KEY (entity0)
REFERENCES artist(id);
```

```
ALTER TABLE l_artist_place
ADD CONSTRAINT l_artist_place_fk_entity1
FOREIGN KEY (entity1)
REFERENCES place(id);
```

```
ALTER TABLE l_artist_recording
ADD CONSTRAINT l_artist_recording_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_artist_recording
ADD CONSTRAINT l_artist_recording_fk_entity0
FOREIGN KEY (entity0)
REFERENCES artist(id);
```

```
ALTER TABLE l_artist_recording
ADD CONSTRAINT l_artist_recording_fk_entity1
FOREIGN KEY (entity1)
REFERENCES recording(id);
```

```
ALTER TABLE l_artist_release
ADD CONSTRAINT l_artist_release_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_artist_release
ADD CONSTRAINT l_artist_release_fk_entity0
FOREIGN KEY (entity0)
REFERENCES artist(id);
```

```
ALTER TABLE l_artist_release
ADD CONSTRAINT l_artist_release_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release(id);
```

```
ALTER TABLE l_artist_release_group
ADD CONSTRAINT l_artist_release_group_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_artist_release_group
  ADD CONSTRAINT l_artist_release_group_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES artist(id);
```

```
ALTER TABLE l_artist_release_group
  ADD CONSTRAINT l_artist_release_group_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release_group(id);
```

```
ALTER TABLE l_artist_series
  ADD CONSTRAINT l_artist_series_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_artist_series
  ADD CONSTRAINT l_artist_series_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES artist(id);
```

```
ALTER TABLE l_artist_series
  ADD CONSTRAINT l_artist_series_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES series(id);
```

```
ALTER TABLE l_artist_url
  ADD CONSTRAINT l_artist_url_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_artist_url
  ADD CONSTRAINT l_artist_url_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES artist(id);
```

```
ALTER TABLE l_artist_url
  ADD CONSTRAINT l_artist_url_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES url(id);
```

```
ALTER TABLE l_artist_work
  ADD CONSTRAINT l_artist_work_fk_link
```

```
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_artist_work
ADD CONSTRAINT l_artist_work_fk_entity0
FOREIGN KEY (entity0)
REFERENCES artist(id);
```

```
ALTER TABLE l_artist_work
ADD CONSTRAINT l_artist_work_fk_entity1
FOREIGN KEY (entity1)
REFERENCES work(id);
```

```
ALTER TABLE l_event_event
ADD CONSTRAINT l_event_event_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_event_event
ADD CONSTRAINT l_event_event_fk_entity0
FOREIGN KEY (entity0)
REFERENCES event(id);
```

```
ALTER TABLE l_event_event
ADD CONSTRAINT l_event_event_fk_entity1
FOREIGN KEY (entity1)
REFERENCES event(id);
```

```
ALTER TABLE l_event_genre
ADD CONSTRAINT l_event_genre_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_event_genre
ADD CONSTRAINT l_event_genre_fk_entity0
FOREIGN KEY (entity0)
REFERENCES event(id);
```

```
ALTER TABLE l_event_genre
ADD CONSTRAINT l_event_genre_fk_entity1
FOREIGN KEY (entity1)
REFERENCES genre(id);
```

```
ALTER TABLE l_event_instrument
  ADD CONSTRAINT l_event_instrument_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_event_instrument
  ADD CONSTRAINT l_event_instrument_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES event(id);
```

```
ALTER TABLE l_event_instrument
  ADD CONSTRAINT l_event_instrument_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES instrument(id);
```

```
ALTER TABLE l_event_label
  ADD CONSTRAINT l_event_label_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_event_label
  ADD CONSTRAINT l_event_label_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES event(id);
```

```
ALTER TABLE l_event_label
  ADD CONSTRAINT l_event_label_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES label(id);
```

```
ALTER TABLE l_event_mood
  ADD CONSTRAINT l_event_mood_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_event_mood
  ADD CONSTRAINT l_event_mood_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES event(id);
```

```
ALTER TABLE l_event_mood
  ADD CONSTRAINT l_event_mood_fk_entity1
  FOREIGN KEY (entity1)
```

```
REFERENCES mood(id);
```

```
ALTER TABLE l_event_place  
  ADD CONSTRAINT l_event_place_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_event_place  
  ADD CONSTRAINT l_event_place_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES event(id);
```

```
ALTER TABLE l_event_place  
  ADD CONSTRAINT l_event_place_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES place(id);
```

```
ALTER TABLE l_event_recording  
  ADD CONSTRAINT l_event_recording_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_event_recording  
  ADD CONSTRAINT l_event_recording_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES event(id);
```

```
ALTER TABLE l_event_recording  
  ADD CONSTRAINT l_event_recording_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES recording(id);
```

```
ALTER TABLE l_event_release  
  ADD CONSTRAINT l_event_release_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_event_release  
  ADD CONSTRAINT l_event_release_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES event(id);
```

```
ALTER TABLE l_event_release
```

```
ADD CONSTRAINT l_event_release_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release(id);
```

```
ALTER TABLE l_event_release_group
ADD CONSTRAINT l_event_release_group_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_event_release_group
ADD CONSTRAINT l_event_release_group_fk_entity0
FOREIGN KEY (entity0)
REFERENCES event(id);
```

```
ALTER TABLE l_event_release_group
ADD CONSTRAINT l_event_release_group_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release_group(id);
```

```
ALTER TABLE l_event_series
ADD CONSTRAINT l_event_series_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_event_series
ADD CONSTRAINT l_event_series_fk_entity0
FOREIGN KEY (entity0)
REFERENCES event(id);
```

```
ALTER TABLE l_event_series
ADD CONSTRAINT l_event_series_fk_entity1
FOREIGN KEY (entity1)
REFERENCES series(id);
```

```
ALTER TABLE l_event_url
ADD CONSTRAINT l_event_url_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_event_url
ADD CONSTRAINT l_event_url_fk_entity0
FOREIGN KEY (entity0)
REFERENCES event(id);
```

```
ALTER TABLE l_event_url
  ADD CONSTRAINT l_event_url_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES url(id);
```

```
ALTER TABLE l_event_work
  ADD CONSTRAINT l_event_work_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_event_work
  ADD CONSTRAINT l_event_work_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES event(id);
```

```
ALTER TABLE l_event_work
  ADD CONSTRAINT l_event_work_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES work(id);
```

```
ALTER TABLE l_genre_genre
  ADD CONSTRAINT l_genre_genre_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_genre_genre
  ADD CONSTRAINT l_genre_genre_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES genre(id);
```

```
ALTER TABLE l_genre_genre
  ADD CONSTRAINT l_genre_genre_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES genre(id);
```

```
ALTER TABLE l_genre_instrument
  ADD CONSTRAINT l_genre_instrument_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_genre_instrument
  ADD CONSTRAINT l_genre_instrument_fk_entity0
```

```
FOREIGN KEY (entity0)
REFERENCES genre(id);
```

```
ALTER TABLE l_genre_instrument
ADD CONSTRAINT l_genre_instrument_fk_entity1
FOREIGN KEY (entity1)
REFERENCES instrument(id);
```

```
ALTER TABLE l_genre_label
ADD CONSTRAINT l_genre_label_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_genre_label
ADD CONSTRAINT l_genre_label_fk_entity0
FOREIGN KEY (entity0)
REFERENCES genre(id);
```

```
ALTER TABLE l_genre_label
ADD CONSTRAINT l_genre_label_fk_entity1
FOREIGN KEY (entity1)
REFERENCES label(id);
```

```
ALTER TABLE l_genre_mood
ADD CONSTRAINT l_genre_mood_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_genre_mood
ADD CONSTRAINT l_genre_mood_fk_entity0
FOREIGN KEY (entity0)
REFERENCES genre(id);
```

```
ALTER TABLE l_genre_mood
ADD CONSTRAINT l_genre_mood_fk_entity1
FOREIGN KEY (entity1)
REFERENCES mood(id);
```

```
ALTER TABLE l_genre_place
ADD CONSTRAINT l_genre_place_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```



```
ALTER TABLE l_genre_place
  ADD CONSTRAINT l_genre_place_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES genre(id);
```

```
ALTER TABLE l_genre_place
  ADD CONSTRAINT l_genre_place_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES place(id);
```

```
ALTER TABLE l_genre_recording
  ADD CONSTRAINT l_genre_recording_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_genre_recording
  ADD CONSTRAINT l_genre_recording_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES genre(id);
```

```
ALTER TABLE l_genre_recording
  ADD CONSTRAINT l_genre_recording_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES recording(id);
```

```
ALTER TABLE l_genre_release
  ADD CONSTRAINT l_genre_release_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_genre_release
  ADD CONSTRAINT l_genre_release_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES genre(id);
```

```
ALTER TABLE l_genre_release
  ADD CONSTRAINT l_genre_release_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release(id);
```

```
ALTER TABLE l_genre_release_group
  ADD CONSTRAINT l_genre_release_group_fk_link
  FOREIGN KEY (link)
```

```
REFERENCES link(id);
```

```
ALTER TABLE l_genre_release_group  
  ADD CONSTRAINT l_genre_release_group_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES genre(id);
```

```
ALTER TABLE l_genre_release_group  
  ADD CONSTRAINT l_genre_release_group_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES release_group(id);
```

```
ALTER TABLE l_genre_series  
  ADD CONSTRAINT l_genre_series_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_genre_series  
  ADD CONSTRAINT l_genre_series_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES genre(id);
```

```
ALTER TABLE l_genre_series  
  ADD CONSTRAINT l_genre_series_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES series(id);
```

```
ALTER TABLE l_genre_url  
  ADD CONSTRAINT l_genre_url_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_genre_url  
  ADD CONSTRAINT l_genre_url_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES genre(id);
```

```
ALTER TABLE l_genre_url  
  ADD CONSTRAINT l_genre_url_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES url(id);
```

```
ALTER TABLE l_genre_work
```

```
ADD CONSTRAINT l_genre_work_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_genre_work
ADD CONSTRAINT l_genre_work_fk_entity0
FOREIGN KEY (entity0)
REFERENCES genre(id);
```

```
ALTER TABLE l_genre_work
ADD CONSTRAINT l_genre_work_fk_entity1
FOREIGN KEY (entity1)
REFERENCES work(id);
```

```
ALTER TABLE l_instrument_instrument
ADD CONSTRAINT l_instrument_instrument_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_instrument_instrument
ADD CONSTRAINT l_instrument_instrument_fk_entity0
FOREIGN KEY (entity0)
REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_instrument
ADD CONSTRAINT l_instrument_instrument_fk_entity1
FOREIGN KEY (entity1)
REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_label
ADD CONSTRAINT l_instrument_label_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_instrument_label
ADD CONSTRAINT l_instrument_label_fk_entity0
FOREIGN KEY (entity0)
REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_label
ADD CONSTRAINT l_instrument_label_fk_entity1
FOREIGN KEY (entity1)
REFERENCES label(id);
```

```
ALTER TABLE l_instrument_mood
  ADD CONSTRAINT l_instrument_mood_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_instrument_mood
  ADD CONSTRAINT l_instrument_mood_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_mood
  ADD CONSTRAINT l_instrument_mood_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES mood(id);
```

```
ALTER TABLE l_instrument_place
  ADD CONSTRAINT l_instrument_place_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_instrument_place
  ADD CONSTRAINT l_instrument_place_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_place
  ADD CONSTRAINT l_instrument_place_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES place(id);
```

```
ALTER TABLE l_instrument_recording
  ADD CONSTRAINT l_instrument_recording_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_instrument_recording
  ADD CONSTRAINT l_instrument_recording_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_recording
  ADD CONSTRAINT l_instrument_recording_fk_entity1
```

```
FOREIGN KEY (entity1)
REFERENCES recording(id);
```

```
ALTER TABLE l_instrument_release
ADD CONSTRAINT l_instrument_release_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_instrument_release
ADD CONSTRAINT l_instrument_release_fk_entity0
FOREIGN KEY (entity0)
REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_release
ADD CONSTRAINT l_instrument_release_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release(id);
```

```
ALTER TABLE l_instrument_release_group
ADD CONSTRAINT l_instrument_release_group_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_instrument_release_group
ADD CONSTRAINT l_instrument_release_group_fk_entity0
FOREIGN KEY (entity0)
REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_release_group
ADD CONSTRAINT l_instrument_release_group_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release_group(id);
```

```
ALTER TABLE l_instrument_series
ADD CONSTRAINT l_instrument_series_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_instrument_series
ADD CONSTRAINT l_instrument_series_fk_entity0
FOREIGN KEY (entity0)
REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_series
  ADD CONSTRAINT l_instrument_series_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES series(id);
```

```
ALTER TABLE l_instrument_url
  ADD CONSTRAINT l_instrument_url_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_instrument_url
  ADD CONSTRAINT l_instrument_url_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_url
  ADD CONSTRAINT l_instrument_url_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES url(id);
```

```
ALTER TABLE l_instrument_work
  ADD CONSTRAINT l_instrument_work_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_instrument_work
  ADD CONSTRAINT l_instrument_work_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES instrument(id);
```

```
ALTER TABLE l_instrument_work
  ADD CONSTRAINT l_instrument_work_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES work(id);
```

```
ALTER TABLE l_label_label
  ADD CONSTRAINT l_label_label_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_label_label
  ADD CONSTRAINT l_label_label_fk_entity0
  FOREIGN KEY (entity0)
```

```
REFERENCES label(id);
```

```
ALTER TABLE l_label_label  
  ADD CONSTRAINT l_label_label_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES label(id);
```

```
ALTER TABLE l_label_mood  
  ADD CONSTRAINT l_label_mood_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_label_mood  
  ADD CONSTRAINT l_label_mood_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES label(id);
```

```
ALTER TABLE l_label_mood  
  ADD CONSTRAINT l_label_mood_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES mood(id);
```

```
ALTER TABLE l_label_place  
  ADD CONSTRAINT l_label_place_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_label_place  
  ADD CONSTRAINT l_label_place_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES label(id);
```

```
ALTER TABLE l_label_place  
  ADD CONSTRAINT l_label_place_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES place(id);
```

```
ALTER TABLE l_label_recording  
  ADD CONSTRAINT l_label_recording_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_label_recording
```

```
ADD CONSTRAINT l_label_recording_fk_entity0
FOREIGN KEY (entity0)
REFERENCES label(id);
```

```
ALTER TABLE l_label_recording
ADD CONSTRAINT l_label_recording_fk_entity1
FOREIGN KEY (entity1)
REFERENCES recording(id);
```

```
ALTER TABLE l_label_release
ADD CONSTRAINT l_label_release_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_label_release
ADD CONSTRAINT l_label_release_fk_entity0
FOREIGN KEY (entity0)
REFERENCES label(id);
```

```
ALTER TABLE l_label_release
ADD CONSTRAINT l_label_release_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release(id);
```

```
ALTER TABLE l_label_release_group
ADD CONSTRAINT l_label_release_group_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_label_release_group
ADD CONSTRAINT l_label_release_group_fk_entity0
FOREIGN KEY (entity0)
REFERENCES label(id);
```

```
ALTER TABLE l_label_release_group
ADD CONSTRAINT l_label_release_group_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release_group(id);
```

```
ALTER TABLE l_label_series
ADD CONSTRAINT l_label_series_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```



```
ALTER TABLE l_label_series
  ADD CONSTRAINT l_label_series_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES label(id);
```

```
ALTER TABLE l_label_series
  ADD CONSTRAINT l_label_series_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES series(id);
```

```
ALTER TABLE l_label_url
  ADD CONSTRAINT l_label_url_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_label_url
  ADD CONSTRAINT l_label_url_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES label(id);
```

```
ALTER TABLE l_label_url
  ADD CONSTRAINT l_label_url_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES url(id);
```

```
ALTER TABLE l_label_work
  ADD CONSTRAINT l_label_work_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_label_work
  ADD CONSTRAINT l_label_work_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES label(id);
```

```
ALTER TABLE l_label_work
  ADD CONSTRAINT l_label_work_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES work(id);
```

```
ALTER TABLE l_mood_mood
  ADD CONSTRAINT l_mood_mood_fk_link
```

```
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_mood_mood
ADD CONSTRAINT l_mood_mood_fk_entity0
FOREIGN KEY (entity0)
REFERENCES mood(id);
```

```
ALTER TABLE l_mood_mood
ADD CONSTRAINT l_mood_mood_fk_entity1
FOREIGN KEY (entity1)
REFERENCES mood(id);
```

```
ALTER TABLE l_mood_place
ADD CONSTRAINT l_mood_place_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_mood_place
ADD CONSTRAINT l_mood_place_fk_entity0
FOREIGN KEY (entity0)
REFERENCES mood(id);
```

```
ALTER TABLE l_mood_place
ADD CONSTRAINT l_mood_place_fk_entity1
FOREIGN KEY (entity1)
REFERENCES place(id);
```

```
ALTER TABLE l_mood_recording
ADD CONSTRAINT l_mood_recording_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_mood_recording
ADD CONSTRAINT l_mood_recording_fk_entity0
FOREIGN KEY (entity0)
REFERENCES mood(id);
```

```
ALTER TABLE l_mood_recording
ADD CONSTRAINT l_mood_recording_fk_entity1
FOREIGN KEY (entity1)
REFERENCES recording(id);
```

```
ALTER TABLE l_mood_release
  ADD CONSTRAINT l_mood_release_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_mood_release
  ADD CONSTRAINT l_mood_release_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES mood(id);
```

```
ALTER TABLE l_mood_release
  ADD CONSTRAINT l_mood_release_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release(id);
```

```
ALTER TABLE l_mood_release_group
  ADD CONSTRAINT l_mood_release_group_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_mood_release_group
  ADD CONSTRAINT l_mood_release_group_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES mood(id);
```

```
ALTER TABLE l_mood_release_group
  ADD CONSTRAINT l_mood_release_group_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release_group(id);
```

```
ALTER TABLE l_mood_series
  ADD CONSTRAINT l_mood_series_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_mood_series
  ADD CONSTRAINT l_mood_series_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES mood(id);
```

```
ALTER TABLE l_mood_series
  ADD CONSTRAINT l_mood_series_fk_entity1
  FOREIGN KEY (entity1)
```

```
REFERENCES series(id);
```

```
ALTER TABLE l_mood_url  
  ADD CONSTRAINT l_mood_url_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_mood_url  
  ADD CONSTRAINT l_mood_url_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES mood(id);
```

```
ALTER TABLE l_mood_url  
  ADD CONSTRAINT l_mood_url_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES url(id);
```

```
ALTER TABLE l_mood_work  
  ADD CONSTRAINT l_mood_work_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_mood_work  
  ADD CONSTRAINT l_mood_work_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES mood(id);
```

```
ALTER TABLE l_mood_work  
  ADD CONSTRAINT l_mood_work_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES work(id);
```

```
ALTER TABLE l_place_place  
  ADD CONSTRAINT l_place_place_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_place_place  
  ADD CONSTRAINT l_place_place_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES place(id);
```

```
ALTER TABLE l_place_place
```

```
ADD CONSTRAINT l_place_place_fk_entity1
FOREIGN KEY (entity1)
REFERENCES place(id);
```

```
ALTER TABLE l_place_recording
ADD CONSTRAINT l_place_recording_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_place_recording
ADD CONSTRAINT l_place_recording_fk_entity0
FOREIGN KEY (entity0)
REFERENCES place(id);
```

```
ALTER TABLE l_place_recording
ADD CONSTRAINT l_place_recording_fk_entity1
FOREIGN KEY (entity1)
REFERENCES recording(id);
```

```
ALTER TABLE l_place_release
ADD CONSTRAINT l_place_release_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_place_release
ADD CONSTRAINT l_place_release_fk_entity0
FOREIGN KEY (entity0)
REFERENCES place(id);
```

```
ALTER TABLE l_place_release
ADD CONSTRAINT l_place_release_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release(id);
```

```
ALTER TABLE l_place_release_group
ADD CONSTRAINT l_place_release_group_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_place_release_group
ADD CONSTRAINT l_place_release_group_fk_entity0
FOREIGN KEY (entity0)
REFERENCES place(id);
```

```
ALTER TABLE l_place_release_group
  ADD CONSTRAINT l_place_release_group_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release_group(id);
```

```
ALTER TABLE l_place_series
  ADD CONSTRAINT l_place_series_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_place_series
  ADD CONSTRAINT l_place_series_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES place(id);
```

```
ALTER TABLE l_place_series
  ADD CONSTRAINT l_place_series_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES series(id);
```

```
ALTER TABLE l_place_url
  ADD CONSTRAINT l_place_url_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_place_url
  ADD CONSTRAINT l_place_url_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES place(id);
```

```
ALTER TABLE l_place_url
  ADD CONSTRAINT l_place_url_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES url(id);
```

```
ALTER TABLE l_place_work
  ADD CONSTRAINT l_place_work_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_place_work
  ADD CONSTRAINT l_place_work_fk_entity0
```

```
FOREIGN KEY (entity0)
REFERENCES place(id);
```

```
ALTER TABLE l_place_work
ADD CONSTRAINT l_place_work_fk_entity1
FOREIGN KEY (entity1)
REFERENCES work(id);
```

```
ALTER TABLE l_recording_recording
ADD CONSTRAINT l_recording_recording_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_recording_recording
ADD CONSTRAINT l_recording_recording_fk_entity0
FOREIGN KEY (entity0)
REFERENCES recording(id);
```

```
ALTER TABLE l_recording_recording
ADD CONSTRAINT l_recording_recording_fk_entity1
FOREIGN KEY (entity1)
REFERENCES recording(id);
```

```
ALTER TABLE l_recording_release
ADD CONSTRAINT l_recording_release_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_recording_release
ADD CONSTRAINT l_recording_release_fk_entity0
FOREIGN KEY (entity0)
REFERENCES recording(id);
```

```
ALTER TABLE l_recording_release
ADD CONSTRAINT l_recording_release_fk_entity1
FOREIGN KEY (entity1)
REFERENCES release(id);
```

```
ALTER TABLE l_recording_release_group
ADD CONSTRAINT l_recording_release_group_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_recording_release_group
  ADD CONSTRAINT l_recording_release_group_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES recording(id);
```

```
ALTER TABLE l_recording_release_group
  ADD CONSTRAINT l_recording_release_group_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release_group(id);
```

```
ALTER TABLE l_recording_series
  ADD CONSTRAINT l_recording_series_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_recording_series
  ADD CONSTRAINT l_recording_series_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES recording(id);
```

```
ALTER TABLE l_recording_series
  ADD CONSTRAINT l_recording_series_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES series(id);
```

```
ALTER TABLE l_recording_url
  ADD CONSTRAINT l_recording_url_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_recording_url
  ADD CONSTRAINT l_recording_url_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES recording(id);
```

```
ALTER TABLE l_recording_url
  ADD CONSTRAINT l_recording_url_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES url(id);
```

```
ALTER TABLE l_recording_work
  ADD CONSTRAINT l_recording_work_fk_link
  FOREIGN KEY (link)
```



```
REFERENCES link(id);
```

```
ALTER TABLE l_recording_work  
  ADD CONSTRAINT l_recording_work_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES recording(id);
```

```
ALTER TABLE l_recording_work  
  ADD CONSTRAINT l_recording_work_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES work(id);
```

```
ALTER TABLE l_release_group_release_group  
  ADD CONSTRAINT l_release_group_release_group_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_release_group_release_group  
  ADD CONSTRAINT l_release_group_release_group_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES release_group(id);
```

```
ALTER TABLE l_release_group_release_group  
  ADD CONSTRAINT l_release_group_release_group_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES release_group(id);
```

```
ALTER TABLE l_release_group_series  
  ADD CONSTRAINT l_release_group_series_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_release_group_series  
  ADD CONSTRAINT l_release_group_series_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES release_group(id);
```

```
ALTER TABLE l_release_group_series  
  ADD CONSTRAINT l_release_group_series_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES series(id);
```

```
ALTER TABLE l_release_group_url
```

```
ADD CONSTRAINT l_release_group_url_fk_link  
FOREIGN KEY (link)  
REFERENCES link(id);
```

```
ALTER TABLE l_release_group_url  
ADD CONSTRAINT l_release_group_url_fk_entity0  
FOREIGN KEY (entity0)  
REFERENCES release_group(id);
```

```
ALTER TABLE l_release_group_url  
ADD CONSTRAINT l_release_group_url_fk_entity1  
FOREIGN KEY (entity1)  
REFERENCES url(id);
```

```
ALTER TABLE l_release_group_work  
ADD CONSTRAINT l_release_group_work_fk_link  
FOREIGN KEY (link)  
REFERENCES link(id);
```

```
ALTER TABLE l_release_group_work  
ADD CONSTRAINT l_release_group_work_fk_entity0  
FOREIGN KEY (entity0)  
REFERENCES release_group(id);
```

```
ALTER TABLE l_release_group_work  
ADD CONSTRAINT l_release_group_work_fk_entity1  
FOREIGN KEY (entity1)  
REFERENCES work(id);
```

```
ALTER TABLE l_release_release  
ADD CONSTRAINT l_release_release_fk_link  
FOREIGN KEY (link)  
REFERENCES link(id);
```

```
ALTER TABLE l_release_release  
ADD CONSTRAINT l_release_release_fk_entity0  
FOREIGN KEY (entity0)  
REFERENCES release(id);
```

```
ALTER TABLE l_release_release  
ADD CONSTRAINT l_release_release_fk_entity1  
FOREIGN KEY (entity1)  
REFERENCES release(id);
```

```
ALTER TABLE l_release_release_group
  ADD CONSTRAINT l_release_release_group_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_release_release_group
  ADD CONSTRAINT l_release_release_group_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES release(id);
```

```
ALTER TABLE l_release_release_group
  ADD CONSTRAINT l_release_release_group_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES release_group(id);
```

```
ALTER TABLE l_release_series
  ADD CONSTRAINT l_release_series_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_release_series
  ADD CONSTRAINT l_release_series_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES release(id);
```

```
ALTER TABLE l_release_series
  ADD CONSTRAINT l_release_series_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES series(id);
```

```
ALTER TABLE l_release_url
  ADD CONSTRAINT l_release_url_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_release_url
  ADD CONSTRAINT l_release_url_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES release(id);
```

```
ALTER TABLE l_release_url
  ADD CONSTRAINT l_release_url_fk_entity1
```

```
FOREIGN KEY (entity1)
REFERENCES url(id);
```

```
ALTER TABLE l_release_work
ADD CONSTRAINT l_release_work_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_release_work
ADD CONSTRAINT l_release_work_fk_entity0
FOREIGN KEY (entity0)
REFERENCES release(id);
```

```
ALTER TABLE l_release_work
ADD CONSTRAINT l_release_work_fk_entity1
FOREIGN KEY (entity1)
REFERENCES work(id);
```

```
ALTER TABLE l_series_series
ADD CONSTRAINT l_series_series_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_series_series
ADD CONSTRAINT l_series_series_fk_entity0
FOREIGN KEY (entity0)
REFERENCES series(id);
```

```
ALTER TABLE l_series_series
ADD CONSTRAINT l_series_series_fk_entity1
FOREIGN KEY (entity1)
REFERENCES series(id);
```

```
ALTER TABLE l_series_url
ADD CONSTRAINT l_series_url_fk_link
FOREIGN KEY (link)
REFERENCES link(id);
```

```
ALTER TABLE l_series_url
ADD CONSTRAINT l_series_url_fk_entity0
FOREIGN KEY (entity0)
REFERENCES series(id);
```

```
ALTER TABLE l_series_url
  ADD CONSTRAINT l_series_url_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES url(id);
```

```
ALTER TABLE l_series_work
  ADD CONSTRAINT l_series_work_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_series_work
  ADD CONSTRAINT l_series_work_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES series(id);
```

```
ALTER TABLE l_series_work
  ADD CONSTRAINT l_series_work_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES work(id);
```

```
ALTER TABLE l_url_url
  ADD CONSTRAINT l_url_url_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_url_url
  ADD CONSTRAINT l_url_url_fk_entity0
  FOREIGN KEY (entity0)
  REFERENCES url(id);
```

```
ALTER TABLE l_url_url
  ADD CONSTRAINT l_url_url_fk_entity1
  FOREIGN KEY (entity1)
  REFERENCES url(id);
```

```
ALTER TABLE l_url_work
  ADD CONSTRAINT l_url_work_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE l_url_work
  ADD CONSTRAINT l_url_work_fk_entity0
  FOREIGN KEY (entity0)
```

```
REFERENCES url(id);
```

```
ALTER TABLE l_url_work  
  ADD CONSTRAINT l_url_work_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES work(id);
```

```
ALTER TABLE l_work_work  
  ADD CONSTRAINT l_work_work_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE l_work_work  
  ADD CONSTRAINT l_work_work_fk_entity0  
  FOREIGN KEY (entity0)  
  REFERENCES work(id);
```

```
ALTER TABLE l_work_work  
  ADD CONSTRAINT l_work_work_fk_entity1  
  FOREIGN KEY (entity1)  
  REFERENCES work(id);
```

```
ALTER TABLE label  
  ADD CONSTRAINT label_fk_type  
  FOREIGN KEY (type)  
  REFERENCES label_type(id);
```

```
ALTER TABLE label  
  ADD CONSTRAINT label_fk_area  
  FOREIGN KEY (area)  
  REFERENCES area(id);
```

```
ALTER TABLE label_alias  
  ADD CONSTRAINT label_alias_fk_label  
  FOREIGN KEY (label)  
  REFERENCES label(id);
```

```
ALTER TABLE label_alias  
  ADD CONSTRAINT label_alias_fk_type  
  FOREIGN KEY (type)  
  REFERENCES label_alias_type(id);
```

```
ALTER TABLE label_alias_type
```

```
ADD CONSTRAINT label_alias_type_fk_parent
FOREIGN KEY (parent)
REFERENCES label_alias_type(id);
```

```
ALTER TABLE label_annotation
ADD CONSTRAINT label_annotation_fk_label
FOREIGN KEY (label)
REFERENCES label(id);
```

```
ALTER TABLE label_annotation
ADD CONSTRAINT label_annotation_fk_annotation
FOREIGN KEY (annotation)
REFERENCES annotation(id);
```

```
ALTER TABLE label_attribute
ADD CONSTRAINT label_attribute_fk_label
FOREIGN KEY (label)
REFERENCES label(id);
```

```
ALTER TABLE label_attribute
ADD CONSTRAINT label_attribute_fk_label_attribute_type
FOREIGN KEY (label_attribute_type)
REFERENCES label_attribute_type(id);
```

```
ALTER TABLE label_attribute
ADD CONSTRAINT label_attribute_fk_label_attribute_type_allowed_value
FOREIGN KEY (label_attribute_type_allowed_value)
REFERENCES label_attribute_type_allowed_value(id);
```

```
ALTER TABLE label_attribute_type
ADD CONSTRAINT label_attribute_type_fk_parent
FOREIGN KEY (parent)
REFERENCES label_attribute_type(id);
```

```
ALTER TABLE label_attribute_type_allowed_value
ADD CONSTRAINT
label_attribute_type_allowed_value_fk_label_attribute_type
FOREIGN KEY (label_attribute_type)
REFERENCES label_attribute_type(id);
```

```
ALTER TABLE label_attribute_type_allowed_value
ADD CONSTRAINT label_attribute_type_allowed_value_fk_parent
FOREIGN KEY (parent)
```

```
REFERENCES label_attribute_type_allowed_value(id);
```

```
ALTER TABLE label_gid_redirect  
  ADD CONSTRAINT label_gid_redirect_fk_new_id  
  FOREIGN KEY (new_id)  
  REFERENCES label(id);
```

```
ALTER TABLE label_ipi  
  ADD CONSTRAINT label_ipi_fk_label  
  FOREIGN KEY (label)  
  REFERENCES label(id);
```

```
ALTER TABLE label_isni  
  ADD CONSTRAINT label_isni_fk_label  
  FOREIGN KEY (label)  
  REFERENCES label(id);
```

```
ALTER TABLE label_meta  
  ADD CONSTRAINT label_meta_fk_id  
  FOREIGN KEY (id)  
  REFERENCES label(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE label_rating_raw  
  ADD CONSTRAINT label_rating_raw_fk_label  
  FOREIGN KEY (label)  
  REFERENCES label(id);
```

```
ALTER TABLE label_rating_raw  
  ADD CONSTRAINT label_rating_raw_fk_editor  
  FOREIGN KEY (editor)  
  REFERENCES editor(id);
```

```
ALTER TABLE label_tag  
  ADD CONSTRAINT label_tag_fk_label  
  FOREIGN KEY (label)  
  REFERENCES label(id);
```

```
ALTER TABLE label_tag  
  ADD CONSTRAINT label_tag_fk_tag  
  FOREIGN KEY (tag)  
  REFERENCES tag(id);
```



```
ALTER TABLE label_tag_raw
  ADD CONSTRAINT label_tag_raw_fk_label
  FOREIGN KEY (label)
  REFERENCES label(id);
```

```
ALTER TABLE label_tag_raw
  ADD CONSTRAINT label_tag_raw_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE label_tag_raw
  ADD CONSTRAINT label_tag_raw_fk_tag
  FOREIGN KEY (tag)
  REFERENCES tag(id);
```

```
ALTER TABLE label_type
  ADD CONSTRAINT label_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES label_type(id);
```

```
ALTER TABLE link
  ADD CONSTRAINT link_fk_link_type
  FOREIGN KEY (link_type)
  REFERENCES link_type(id);
```

```
ALTER TABLE link_attribute
  ADD CONSTRAINT link_attribute_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE link_attribute
  ADD CONSTRAINT link_attribute_fk_attribute_type
  FOREIGN KEY (attribute_type)
  REFERENCES link_attribute_type(id);
```

```
ALTER TABLE link_attribute_credit
  ADD CONSTRAINT link_attribute_credit_fk_link
  FOREIGN KEY (link)
  REFERENCES link(id);
```

```
ALTER TABLE link_attribute_credit
  ADD CONSTRAINT link_attribute_credit_fk_attribute_type
  FOREIGN KEY (attribute_type)
```

```
REFERENCES link_creditable_attribute_type(attribute_type);
```

```
ALTER TABLE link_attribute_text_value  
  ADD CONSTRAINT link_attribute_text_value_fk_link  
  FOREIGN KEY (link)  
  REFERENCES link(id);
```

```
ALTER TABLE link_attribute_text_value  
  ADD CONSTRAINT link_attribute_text_value_fk_attribute_type  
  FOREIGN KEY (attribute_type)  
  REFERENCES link_text_attribute_type(attribute_type);
```

```
ALTER TABLE link_attribute_type  
  ADD CONSTRAINT link_attribute_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES link_attribute_type(id);
```

```
ALTER TABLE link_attribute_type  
  ADD CONSTRAINT link_attribute_type_fk_root  
  FOREIGN KEY (root)  
  REFERENCES link_attribute_type(id);
```

```
ALTER TABLE link_creditable_attribute_type  
  ADD CONSTRAINT link_creditable_attribute_type_fk_attribute_type  
  FOREIGN KEY (attribute_type)  
  REFERENCES link_attribute_type(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE link_text_attribute_type  
  ADD CONSTRAINT link_text_attribute_type_fk_attribute_type  
  FOREIGN KEY (attribute_type)  
  REFERENCES link_attribute_type(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE link_type  
  ADD CONSTRAINT link_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES link_type(id);
```

```
ALTER TABLE link_type_attribute_type  
  ADD CONSTRAINT link_type_attribute_type_fk_link_type  
  FOREIGN KEY (link_type)  
  REFERENCES link_type(id);
```

```
ALTER TABLE link_type_attribute_type
  ADD CONSTRAINT link_type_attribute_type_fk_attribute_type
  FOREIGN KEY (attribute_type)
  REFERENCES link_attribute_type(id);
```

```
ALTER TABLE medium
  ADD CONSTRAINT medium_fk_release
  FOREIGN KEY (release)
  REFERENCES release(id);
```

```
ALTER TABLE medium
  ADD CONSTRAINT medium_fk_format
  FOREIGN KEY (format)
  REFERENCES medium_format(id);
```

```
ALTER TABLE medium_attribute
  ADD CONSTRAINT medium_attribute_fk_medium
  FOREIGN KEY (medium)
  REFERENCES medium(id);
```

```
ALTER TABLE medium_attribute
  ADD CONSTRAINT medium_attribute_fk_medium_attribute_type
  FOREIGN KEY (medium_attribute_type)
  REFERENCES medium_attribute_type(id);
```

```
ALTER TABLE medium_attribute
  ADD CONSTRAINT
medium_attribute_fk_medium_attribute_type_allowed_value
  FOREIGN KEY (medium_attribute_type_allowed_value)
  REFERENCES medium_attribute_type_allowed_value(id);
```

```
ALTER TABLE medium_attribute_type
  ADD CONSTRAINT medium_attribute_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES medium_attribute_type(id);
```

```
ALTER TABLE medium_attribute_type_allowed_format
  ADD CONSTRAINT
medium_attribute_type_allowed_format_fk_medium_format
  FOREIGN KEY (medium_format)
  REFERENCES medium_format(id);
```

```
ALTER TABLE medium_attribute_type_allowed_format
                        ADD                        CONSTRAINT
medium_attribute_type_allowed_format_fk_medium_attribute_type
FOREIGN KEY (medium_attribute_type)
REFERENCES medium_attribute_type(id);
```

```
ALTER TABLE medium_attribute_type_allowed_value
                        ADD                        CONSTRAINT
medium_attribute_type_allowed_value_fk_medium_attribute_type
FOREIGN KEY (medium_attribute_type)
REFERENCES medium_attribute_type(id);
```

```
ALTER TABLE medium_attribute_type_allowed_value
ADD CONSTRAINT medium_attribute_type_allowed_value_fk_parent
FOREIGN KEY (parent)
REFERENCES medium_attribute_type_allowed_value(id);
```

```
ALTER TABLE medium_attribute_type_allowed_value_allowed_format
                        ADD                        CONSTRAINT
medium_attribute_type_allowed_value_allowed_format_fk_medium_format
FOREIGN KEY (medium_format)
REFERENCES medium_format(id);
```

```
ALTER TABLE medium_attribute_type_allowed_value_allowed_format
                        ADD                        CONSTRAINT
medium_attribute_type_allowed_value_allowed_format_fk_medium_attri-
bute_type_allowed_value
FOREIGN KEY (medium_attribute_type_allowed_value)
REFERENCES medium_attribute_type_allowed_value(id);
```

```
ALTER TABLE medium_cdtoc
ADD CONSTRAINT medium_cdtoc_fk_medium
FOREIGN KEY (medium)
REFERENCES medium(id);
```

```
ALTER TABLE medium_cdtoc
ADD CONSTRAINT medium_cdtoc_fk_cdtoc
FOREIGN KEY (cdtoc)
REFERENCES cdtoc(id);
```

```
ALTER TABLE medium_format
ADD CONSTRAINT medium_format_fk_parent
FOREIGN KEY (parent)
```

```
REFERENCES medium_format(id);
```

```
ALTER TABLE medium_index  
  ADD CONSTRAINT medium_index_fk_medium  
  FOREIGN KEY (medium)  
  REFERENCES medium(id)  
  ON DELETE CASCADE;
```

```
ALTER TABLE mood_alias  
  ADD CONSTRAINT mood_alias_fk_mood  
  FOREIGN KEY (mood)  
  REFERENCES mood(id);
```

```
ALTER TABLE mood_alias  
  ADD CONSTRAINT mood_alias_fk_type  
  FOREIGN KEY (type)  
  REFERENCES mood_alias_type(id);
```

```
ALTER TABLE mood_alias_type  
  ADD CONSTRAINT mood_alias_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES mood_alias_type(id);
```

```
ALTER TABLE mood_annotation  
  ADD CONSTRAINT mood_annotation_fk_mood  
  FOREIGN KEY (mood)  
  REFERENCES mood(id);
```

```
ALTER TABLE mood_annotation  
  ADD CONSTRAINT mood_annotation_fk_annotation  
  FOREIGN KEY (annotation)  
  REFERENCES annotation(id);
```

```
ALTER TABLE orderable_link_type  
  ADD CONSTRAINT orderable_link_type_fk_link_type  
  FOREIGN KEY (link_type)  
  REFERENCES link_type(id);
```

```
ALTER TABLE place  
  ADD CONSTRAINT place_fk_type  
  FOREIGN KEY (type)  
  REFERENCES place_type(id);
```

```
ALTER TABLE place
  ADD CONSTRAINT place_fk_area
  FOREIGN KEY (area)
  REFERENCES area(id);
```

```
ALTER TABLE place_alias
  ADD CONSTRAINT place_alias_fk_place
  FOREIGN KEY (place)
  REFERENCES place(id);
```

```
ALTER TABLE place_alias
  ADD CONSTRAINT place_alias_fk_type
  FOREIGN KEY (type)
  REFERENCES place_alias_type(id);
```

```
ALTER TABLE place_alias_type
  ADD CONSTRAINT place_alias_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES place_alias_type(id);
```

```
ALTER TABLE place_annotation
  ADD CONSTRAINT place_annotation_fk_place
  FOREIGN KEY (place)
  REFERENCES place(id);
```

```
ALTER TABLE place_annotation
  ADD CONSTRAINT place_annotation_fk_annotation
  FOREIGN KEY (annotation)
  REFERENCES annotation(id);
```

```
ALTER TABLE place_attribute
  ADD CONSTRAINT place_attribute_fk_place
  FOREIGN KEY (place)
  REFERENCES place(id);
```

```
ALTER TABLE place_attribute
  ADD CONSTRAINT place_attribute_fk_place_attribute_type
  FOREIGN KEY (place_attribute_type)
  REFERENCES place_attribute_type(id);
```

```
ALTER TABLE place_attribute
                                ADD CONSTRAINT
place_attribute_fk_place_attribute_type_allowed_value
```

```
FOREIGN KEY (place_attribute_type_allowed_value)
REFERENCES place_attribute_type_allowed_value(id);
```

```
ALTER TABLE place_attribute_type
ADD CONSTRAINT place_attribute_type_fk_parent
FOREIGN KEY (parent)
REFERENCES place_attribute_type(id);
```

```
ALTER TABLE place_attribute_type_allowed_value
ADD CONSTRAINT
place_attribute_type_allowed_value_fk_place_attribute_type
FOREIGN KEY (place_attribute_type)
REFERENCES place_attribute_type(id);
```

```
ALTER TABLE place_attribute_type_allowed_value
ADD CONSTRAINT place_attribute_type_allowed_value_fk_parent
FOREIGN KEY (parent)
REFERENCES place_attribute_type_allowed_value(id);
```

```
ALTER TABLE place_gid_redirect
ADD CONSTRAINT place_gid_redirect_fk_new_id
FOREIGN KEY (new_id)
REFERENCES place(id);
```

```
ALTER TABLE place_meta
ADD CONSTRAINT place_meta_fk_id
FOREIGN KEY (id)
REFERENCES place(id)
ON DELETE CASCADE;
```

```
ALTER TABLE place_rating_raw
ADD CONSTRAINT place_rating_raw_fk_place
FOREIGN KEY (place)
REFERENCES place(id);
```

```
ALTER TABLE place_rating_raw
ADD CONSTRAINT place_rating_raw_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE place_tag
ADD CONSTRAINT place_tag_fk_place
FOREIGN KEY (place)
```

```
REFERENCES place(id);
```

```
ALTER TABLE place_tag  
  ADD CONSTRAINT place_tag_fk_tag  
  FOREIGN KEY (tag)  
  REFERENCES tag(id);
```

```
ALTER TABLE place_tag_raw  
  ADD CONSTRAINT place_tag_raw_fk_place  
  FOREIGN KEY (place)  
  REFERENCES place(id);
```

```
ALTER TABLE place_tag_raw  
  ADD CONSTRAINT place_tag_raw_fk_editor  
  FOREIGN KEY (editor)  
  REFERENCES editor(id);
```

```
ALTER TABLE place_tag_raw  
  ADD CONSTRAINT place_tag_raw_fk_tag  
  FOREIGN KEY (tag)  
  REFERENCES tag(id);
```

```
ALTER TABLE place_type  
  ADD CONSTRAINT place_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES place_type(id);
```

```
ALTER TABLE recording  
  ADD CONSTRAINT recording_fk_artist_credit  
  FOREIGN KEY (artist_credit)  
  REFERENCES artist_credit(id);
```

```
ALTER TABLE recording_alias  
  ADD CONSTRAINT recording_alias_fk_recording  
  FOREIGN KEY (recording)  
  REFERENCES recording(id);
```

```
ALTER TABLE recording_alias  
  ADD CONSTRAINT recording_alias_fk_type  
  FOREIGN KEY (type)  
  REFERENCES recording_alias_type(id);
```

```
ALTER TABLE recording_alias_type
```



```
ADD CONSTRAINT recording_alias_type_fk_parent
FOREIGN KEY (parent)
REFERENCES recording_alias_type(id);
```

```
ALTER TABLE recording_annotation
ADD CONSTRAINT recording_annotation_fk_recording
FOREIGN KEY (recording)
REFERENCES recording(id);
```

```
ALTER TABLE recording_annotation
ADD CONSTRAINT recording_annotation_fk_annotation
FOREIGN KEY (annotation)
REFERENCES annotation(id);
```

```
ALTER TABLE recording_attribute
ADD CONSTRAINT recording_attribute_fk_recording
FOREIGN KEY (recording)
REFERENCES recording(id);
```

```
ALTER TABLE recording_attribute
ADD CONSTRAINT recording_attribute_fk_recording_attribute_type
FOREIGN KEY (recording_attribute_type)
REFERENCES recording_attribute_type(id);
```

```
ALTER TABLE recording_attribute
ADD CONSTRAINT
recording_attribute_fk_recording_attribute_type_allowed_value
FOREIGN KEY (recording_attribute_type_allowed_value)
REFERENCES recording_attribute_type_allowed_value(id);
```

```
ALTER TABLE recording_attribute_type
ADD CONSTRAINT recording_attribute_type_fk_parent
FOREIGN KEY (parent)
REFERENCES recording_attribute_type(id);
```

```
ALTER TABLE recording_attribute_type_allowed_value
ADD CONSTRAINT
recording_attribute_type_allowed_value_fk_recording_attribute_type
FOREIGN KEY (recording_attribute_type)
REFERENCES recording_attribute_type(id);
```

```
ALTER TABLE recording_attribute_type_allowed_value
ADD CONSTRAINT recording_attribute_type_allowed_value_fk_parent
```

```
FOREIGN KEY (parent)
REFERENCES recording_attribute_type_allowed_value(id);
```

```
ALTER TABLE recording_first_release_date
ADD CONSTRAINT recording_first_release_date_fk_recording
FOREIGN KEY (recording)
REFERENCES recording(id)
ON DELETE CASCADE;
```

```
ALTER TABLE recording_gid_redirect
ADD CONSTRAINT recording_gid_redirect_fk_new_id
FOREIGN KEY (new_id)
REFERENCES recording(id);
```

```
ALTER TABLE recording_meta
ADD CONSTRAINT recording_meta_fk_id
FOREIGN KEY (id)
REFERENCES recording(id)
ON DELETE CASCADE;
```

```
ALTER TABLE recording_rating_raw
ADD CONSTRAINT recording_rating_raw_fk_recording
FOREIGN KEY (recording)
REFERENCES recording(id);
```

```
ALTER TABLE recording_rating_raw
ADD CONSTRAINT recording_rating_raw_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE recording_tag
ADD CONSTRAINT recording_tag_fk_recording
FOREIGN KEY (recording)
REFERENCES recording(id);
```

```
ALTER TABLE recording_tag
ADD CONSTRAINT recording_tag_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE recording_tag_raw
ADD CONSTRAINT recording_tag_raw_fk_recording
FOREIGN KEY (recording)
```

```
REFERENCES recording(id);
```

```
ALTER TABLE recording_tag_raw  
  ADD CONSTRAINT recording_tag_raw_fk_editor  
  FOREIGN KEY (editor)  
  REFERENCES editor(id);
```

```
ALTER TABLE recording_tag_raw  
  ADD CONSTRAINT recording_tag_raw_fk_tag  
  FOREIGN KEY (tag)  
  REFERENCES tag(id);
```

```
ALTER TABLE release  
  ADD CONSTRAINT release_fk_artist_credit  
  FOREIGN KEY (artist_credit)  
  REFERENCES artist_credit(id);
```

```
ALTER TABLE release  
  ADD CONSTRAINT release_fk_release_group  
  FOREIGN KEY (release_group)  
  REFERENCES release_group(id);
```

```
ALTER TABLE release  
  ADD CONSTRAINT release_fk_status  
  FOREIGN KEY (status)  
  REFERENCES release_status(id);
```

```
ALTER TABLE release  
  ADD CONSTRAINT release_fk_packaging  
  FOREIGN KEY (packaging)  
  REFERENCES release_packaging(id);
```

```
ALTER TABLE release  
  ADD CONSTRAINT release_fk_language  
  FOREIGN KEY (language)  
  REFERENCES language(id);
```

```
ALTER TABLE release  
  ADD CONSTRAINT release_fk_script  
  FOREIGN KEY (script)  
  REFERENCES script(id);
```

```
ALTER TABLE release_alias
```

```
ADD CONSTRAINT release_alias_fk_release
FOREIGN KEY (release)
REFERENCES release(id);
```

```
ALTER TABLE release_alias
ADD CONSTRAINT release_alias_fk_type
FOREIGN KEY (type)
REFERENCES release_alias_type(id);
```

```
ALTER TABLE release_alias_type
ADD CONSTRAINT release_alias_type_fk_parent
FOREIGN KEY (parent)
REFERENCES release_alias_type(id);
```

```
ALTER TABLE release_annotation
ADD CONSTRAINT release_annotation_fk_release
FOREIGN KEY (release)
REFERENCES release(id);
```

```
ALTER TABLE release_annotation
ADD CONSTRAINT release_annotation_fk_annotation
FOREIGN KEY (annotation)
REFERENCES annotation(id);
```

```
ALTER TABLE release_attribute
ADD CONSTRAINT release_attribute_fk_release
FOREIGN KEY (release)
REFERENCES release(id);
```

```
ALTER TABLE release_attribute
ADD CONSTRAINT release_attribute_fk_release_attribute_type
FOREIGN KEY (release_attribute_type)
REFERENCES release_attribute_type(id);
```

```
ALTER TABLE release_attribute
ADD CONSTRAINT
release_attribute_fk_release_attribute_type_allowed_value
FOREIGN KEY (release_attribute_type_allowed_value)
REFERENCES release_attribute_type_allowed_value(id);
```

```
ALTER TABLE release_attribute_type
ADD CONSTRAINT release_attribute_type_fk_parent
FOREIGN KEY (parent)
```

```
REFERENCES release_attribute_type(id);
```

```
ALTER TABLE release_attribute_type_allowed_value  
ADD CONSTRAINT  
release_attribute_type_allowed_value_fk_release_attribute_type  
FOREIGN KEY (release_attribute_type)  
REFERENCES release_attribute_type(id);
```

```
ALTER TABLE release_attribute_type_allowed_value  
ADD CONSTRAINT release_attribute_type_allowed_value_fk_parent  
FOREIGN KEY (parent)  
REFERENCES release_attribute_type_allowed_value(id);
```

```
ALTER TABLE release_country  
ADD CONSTRAINT release_country_fk_release  
FOREIGN KEY (release)  
REFERENCES release(id);
```

```
ALTER TABLE release_country  
ADD CONSTRAINT release_country_fk_country  
FOREIGN KEY (country)  
REFERENCES country_area(area);
```

```
ALTER TABLE release_first_release_date  
ADD CONSTRAINT release_first_release_date_fk_release  
FOREIGN KEY (release)  
REFERENCES release(id)  
ON DELETE CASCADE;
```

```
ALTER TABLE release_gid_redirect  
ADD CONSTRAINT release_gid_redirect_fk_new_id  
FOREIGN KEY (new_id)  
REFERENCES release(id);
```

```
ALTER TABLE release_group  
ADD CONSTRAINT release_group_fk_artist_credit  
FOREIGN KEY (artist_credit)  
REFERENCES artist_credit(id);
```

```
ALTER TABLE release_group  
ADD CONSTRAINT release_group_fk_type  
FOREIGN KEY (type)  
REFERENCES release_group_primary_type(id);
```

```
ALTER TABLE release_group_alias
  ADD CONSTRAINT release_group_alias_fk_release_group
  FOREIGN KEY (release_group)
  REFERENCES release_group(id);
```

```
ALTER TABLE release_group_alias
  ADD CONSTRAINT release_group_alias_fk_type
  FOREIGN KEY (type)
  REFERENCES release_group_alias_type(id);
```

```
ALTER TABLE release_group_alias_type
  ADD CONSTRAINT release_group_alias_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES release_group_alias_type(id);
```

```
ALTER TABLE release_group_annotation
  ADD CONSTRAINT release_group_annotation_fk_release_group
  FOREIGN KEY (release_group)
  REFERENCES release_group(id);
```

```
ALTER TABLE release_group_annotation
  ADD CONSTRAINT release_group_annotation_fk_annotation
  FOREIGN KEY (annotation)
  REFERENCES annotation(id);
```

```
ALTER TABLE release_group_attribute
  ADD CONSTRAINT release_group_attribute_fk_release_group
  FOREIGN KEY (release_group)
  REFERENCES release_group(id);
```

```
ALTER TABLE release_group_attribute
  ADD CONSTRAINT
release_group_attribute_fk_release_group_attribute_type
  FOREIGN KEY (release_group_attribute_type)
  REFERENCES release_group_attribute_type(id);
```

```
ALTER TABLE release_group_attribute
  ADD CONSTRAINT
release_group_attribute_fk_release_group_attribute_type_allowed_value
  FOREIGN KEY (release_group_attribute_type_allowed_value)
  REFERENCES release_group_attribute_type_allowed_value(id);
```

```
ALTER TABLE release_group_attribute_type
  ADD CONSTRAINT release_group_attribute_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES release_group_attribute_type(id);
```

```
ALTER TABLE release_group_attribute_type_allowed_value
  ADD CONSTRAINT
release_group_attribute_type_allowed_value_fk_release_group_attribute_ty
pe
  FOREIGN KEY (release_group_attribute_type)
  REFERENCES release_group_attribute_type(id);
```

```
ALTER TABLE release_group_attribute_type_allowed_value
  ADD CONSTRAINT
release_group_attribute_type_allowed_value_fk_parent
  FOREIGN KEY (parent)
  REFERENCES release_group_attribute_type_allowed_value(id);
```

```
ALTER TABLE release_group_gid_redirect
  ADD CONSTRAINT release_group_gid_redirect_fk_new_id
  FOREIGN KEY (new_id)
  REFERENCES release_group(id);
```

```
ALTER TABLE release_group_meta
  ADD CONSTRAINT release_group_meta_fk_id
  FOREIGN KEY (id)
  REFERENCES release_group(id)
  ON DELETE CASCADE;
```

```
ALTER TABLE release_group_primary_type
  ADD CONSTRAINT release_group_primary_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES release_group_primary_type(id);
```

```
ALTER TABLE release_group_rating_raw
  ADD CONSTRAINT release_group_rating_raw_fk_release_group
  FOREIGN KEY (release_group)
  REFERENCES release_group(id);
```

```
ALTER TABLE release_group_rating_raw
  ADD CONSTRAINT release_group_rating_raw_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE release_group_secondary_type
  ADD CONSTRAINT release_group_secondary_type_fk_parent
  FOREIGN KEY (parent)
  REFERENCES release_group_secondary_type(id);
```

```
ALTER TABLE release_group_secondary_type_join
  ADD CONSTRAINT release_group_secondary_type_join_fk_release_group
  FOREIGN KEY (release_group)
  REFERENCES release_group(id);
```

```
ALTER TABLE release_group_secondary_type_join
  ADD CONSTRAINT
release_group_secondary_type_join_fk_secondary_type
  FOREIGN KEY (secondary_type)
  REFERENCES release_group_secondary_type(id);
```

```
ALTER TABLE release_group_tag
  ADD CONSTRAINT release_group_tag_fk_release_group
  FOREIGN KEY (release_group)
  REFERENCES release_group(id);
```

```
ALTER TABLE release_group_tag
  ADD CONSTRAINT release_group_tag_fk_tag
  FOREIGN KEY (tag)
  REFERENCES tag(id);
```

```
ALTER TABLE release_group_tag_raw
  ADD CONSTRAINT release_group_tag_raw_fk_release_group
  FOREIGN KEY (release_group)
  REFERENCES release_group(id);
```

```
ALTER TABLE release_group_tag_raw
  ADD CONSTRAINT release_group_tag_raw_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE release_group_tag_raw
  ADD CONSTRAINT release_group_tag_raw_fk_tag
  FOREIGN KEY (tag)
  REFERENCES tag(id);
```

```
ALTER TABLE release_label
```



```
ADD CONSTRAINT release_label_fk_release
FOREIGN KEY (release)
REFERENCES release(id);
```

```
ALTER TABLE release_label
ADD CONSTRAINT release_label_fk_label
FOREIGN KEY (label)
REFERENCES label(id);
```

```
ALTER TABLE release_meta
ADD CONSTRAINT release_meta_fk_id
FOREIGN KEY (id)
REFERENCES release(id)
ON DELETE CASCADE;
```

```
ALTER TABLE release_packaging
ADD CONSTRAINT release_packaging_fk_parent
FOREIGN KEY (parent)
REFERENCES release_packaging(id);
```

```
ALTER TABLE release_status
ADD CONSTRAINT release_status_fk_parent
FOREIGN KEY (parent)
REFERENCES release_status(id);
```

```
ALTER TABLE release_tag
ADD CONSTRAINT release_tag_fk_release
FOREIGN KEY (release)
REFERENCES release(id);
```

```
ALTER TABLE release_tag
ADD CONSTRAINT release_tag_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE release_tag_raw
ADD CONSTRAINT release_tag_raw_fk_release
FOREIGN KEY (release)
REFERENCES release(id);
```

```
ALTER TABLE release_tag_raw
ADD CONSTRAINT release_tag_raw_fk_editor
FOREIGN KEY (editor)
```

```
REFERENCES editor(id);
```

```
ALTER TABLE release_tag_raw  
  ADD CONSTRAINT release_tag_raw_fk_tag  
  FOREIGN KEY (tag)  
  REFERENCES tag(id);
```

```
ALTER TABLE release_unknown_country  
  ADD CONSTRAINT release_unknown_country_fk_release  
  FOREIGN KEY (release)  
  REFERENCES release(id);
```

```
ALTER TABLE series  
  ADD CONSTRAINT series_fk_type  
  FOREIGN KEY (type)  
  REFERENCES series_type(id);
```

```
ALTER TABLE series  
  ADD CONSTRAINT series_fk_ordering_type  
  FOREIGN KEY (ordering_type)  
  REFERENCES series_ordering_type(id);
```

```
ALTER TABLE series_alias  
  ADD CONSTRAINT series_alias_fk_series  
  FOREIGN KEY (series)  
  REFERENCES series(id);
```

```
ALTER TABLE series_alias  
  ADD CONSTRAINT series_alias_fk_type  
  FOREIGN KEY (type)  
  REFERENCES series_alias_type(id);
```

```
ALTER TABLE series_alias_type  
  ADD CONSTRAINT series_alias_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES series_alias_type(id);
```

```
ALTER TABLE series_annotation  
  ADD CONSTRAINT series_annotation_fk_series  
  FOREIGN KEY (series)  
  REFERENCES series(id);
```

```
ALTER TABLE series_annotation
```

```
ADD CONSTRAINT series_annotation_fk_annotation
FOREIGN KEY (annotation)
REFERENCES annotation(id);
```

```
ALTER TABLE series_attribute
ADD CONSTRAINT series_attribute_fk_series
FOREIGN KEY (series)
REFERENCES series(id);
```

```
ALTER TABLE series_attribute
ADD CONSTRAINT series_attribute_fk_series_attribute_type
FOREIGN KEY (series_attribute_type)
REFERENCES series_attribute_type(id);
```

```
ALTER TABLE series_attribute
ADD CONSTRAINT
series_attribute_fk_series_attribute_type_allowed_value
FOREIGN KEY (series_attribute_type_allowed_value)
REFERENCES series_attribute_type_allowed_value(id);
```

```
ALTER TABLE series_attribute_type
ADD CONSTRAINT series_attribute_type_fk_parent
FOREIGN KEY (parent)
REFERENCES series_attribute_type(id);
```

```
ALTER TABLE series_attribute_type_allowed_value
ADD CONSTRAINT
series_attribute_type_allowed_value_fk_series_attribute_type
FOREIGN KEY (series_attribute_type)
REFERENCES series_attribute_type(id);
```

```
ALTER TABLE series_attribute_type_allowed_value
ADD CONSTRAINT series_attribute_type_allowed_value_fk_parent
FOREIGN KEY (parent)
REFERENCES series_attribute_type_allowed_value(id);
```

```
ALTER TABLE series_gid_redirect
ADD CONSTRAINT series_gid_redirect_fk_new_id
FOREIGN KEY (new_id)
REFERENCES series(id);
```

```
ALTER TABLE series_ordering_type
ADD CONSTRAINT series_ordering_type_fk_parent
```

```
FOREIGN KEY (parent)
REFERENCES series_ordering_type(id);
```

```
ALTER TABLE series_tag
ADD CONSTRAINT series_tag_fk_series
FOREIGN KEY (series)
REFERENCES series(id);
```

```
ALTER TABLE series_tag
ADD CONSTRAINT series_tag_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE series_tag_raw
ADD CONSTRAINT series_tag_raw_fk_series
FOREIGN KEY (series)
REFERENCES series(id);
```

```
ALTER TABLE series_tag_raw
ADD CONSTRAINT series_tag_raw_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE series_tag_raw
ADD CONSTRAINT series_tag_raw_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE series_type
ADD CONSTRAINT series_type_fk_parent
FOREIGN KEY (parent)
REFERENCES series_type(id);
```

```
ALTER TABLE tag_relation
ADD CONSTRAINT tag_relation_fk_tag1
FOREIGN KEY (tag1)
REFERENCES tag(id);
```

```
ALTER TABLE tag_relation
ADD CONSTRAINT tag_relation_fk_tag2
FOREIGN KEY (tag2)
REFERENCES tag(id);
```

```
ALTER TABLE track
  ADD CONSTRAINT track_fk_recording
  FOREIGN KEY (recording)
  REFERENCES recording(id);
```

```
ALTER TABLE track
  ADD CONSTRAINT track_fk_medium
  FOREIGN KEY (medium)
  REFERENCES medium(id);
```

```
ALTER TABLE track
  ADD CONSTRAINT track_fk_artist_credit
  FOREIGN KEY (artist_credit)
  REFERENCES artist_credit(id);
```

```
ALTER TABLE track_gid_redirect
  ADD CONSTRAINT track_gid_redirect_fk_new_id
  FOREIGN KEY (new_id)
  REFERENCES track(id);
```

```
ALTER TABLE track_raw
  ADD CONSTRAINT track_raw_fk_release
  FOREIGN KEY (release)
  REFERENCES release_raw(id);
```

```
ALTER TABLE url_gid_redirect
  ADD CONSTRAINT url_gid_redirect_fk_new_id
  FOREIGN KEY (new_id)
  REFERENCES url(id);
```

```
ALTER TABLE vote
  ADD CONSTRAINT vote_fk_editor
  FOREIGN KEY (editor)
  REFERENCES editor(id);
```

```
ALTER TABLE vote
  ADD CONSTRAINT vote_fk_edit
  FOREIGN KEY (edit)
  REFERENCES edit(id);
```

```
ALTER TABLE work
  ADD CONSTRAINT work_fk_type
  FOREIGN KEY (type)
```

```
REFERENCES work_type(id);
```

```
ALTER TABLE work_alias  
  ADD CONSTRAINT work_alias_fk_work  
  FOREIGN KEY (work)  
  REFERENCES work(id);
```

```
ALTER TABLE work_alias  
  ADD CONSTRAINT work_alias_fk_type  
  FOREIGN KEY (type)  
  REFERENCES work_alias_type(id);
```

```
ALTER TABLE work_alias_type  
  ADD CONSTRAINT work_alias_type_fk_parent  
  FOREIGN KEY (parent)  
  REFERENCES work_alias_type(id);
```

```
ALTER TABLE work_annotation  
  ADD CONSTRAINT work_annotation_fk_work  
  FOREIGN KEY (work)  
  REFERENCES work(id);
```

```
ALTER TABLE work_annotation  
  ADD CONSTRAINT work_annotation_fk_annotation  
  FOREIGN KEY (annotation)  
  REFERENCES annotation(id);
```

```
ALTER TABLE work_attribute  
  ADD CONSTRAINT work_attribute_fk_work  
  FOREIGN KEY (work)  
  REFERENCES work(id);
```

```
ALTER TABLE work_attribute  
  ADD CONSTRAINT work_attribute_fk_work_attribute_type  
  FOREIGN KEY (work_attribute_type)  
  REFERENCES work_attribute_type(id);
```

```
ALTER TABLE work_attribute  
  ADD CONSTRAINT work_attribute_fk_work_attribute_type_allowed_value  
  FOREIGN KEY (work_attribute_type_allowed_value)  
  REFERENCES work_attribute_type_allowed_value(id);
```

```
ALTER TABLE work_attribute_type
```

```
ADD CONSTRAINT work_attribute_type_fk_parent
FOREIGN KEY (parent)
REFERENCES work_attribute_type(id);
```

```
ALTER TABLE work_attribute_type_allowed_value
ADD CONSTRAINT
work_attribute_type_allowed_value_fk_work_attribute_type
FOREIGN KEY (work_attribute_type)
REFERENCES work_attribute_type(id);
```

```
ALTER TABLE work_attribute_type_allowed_value
ADD CONSTRAINT work_attribute_type_allowed_value_fk_parent
FOREIGN KEY (parent)
REFERENCES work_attribute_type_allowed_value(id);
```

```
ALTER TABLE work_gid_redirect
ADD CONSTRAINT work_gid_redirect_fk_new_id
FOREIGN KEY (new_id)
REFERENCES work(id);
```

```
ALTER TABLE work_language
ADD CONSTRAINT work_language_fk_work
FOREIGN KEY (work)
REFERENCES work(id);
```

```
ALTER TABLE work_language
ADD CONSTRAINT work_language_fk_language
FOREIGN KEY (language)
REFERENCES language(id);
```

```
ALTER TABLE work_meta
ADD CONSTRAINT work_meta_fk_id
FOREIGN KEY (id)
REFERENCES work(id)
ON DELETE CASCADE;
```

```
ALTER TABLE work_rating_raw
ADD CONSTRAINT work_rating_raw_fk_work
FOREIGN KEY (work)
REFERENCES work(id);
```

```
ALTER TABLE work_rating_raw
ADD CONSTRAINT work_rating_raw_fk_editor
```

```
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE work_tag
ADD CONSTRAINT work_tag_fk_work
FOREIGN KEY (work)
REFERENCES work(id);
```

```
ALTER TABLE work_tag
ADD CONSTRAINT work_tag_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE work_tag_raw
ADD CONSTRAINT work_tag_raw_fk_work
FOREIGN KEY (work)
REFERENCES work(id);
```

```
ALTER TABLE work_tag_raw
ADD CONSTRAINT work_tag_raw_fk_editor
FOREIGN KEY (editor)
REFERENCES editor(id);
```

```
ALTER TABLE work_tag_raw
ADD CONSTRAINT work_tag_raw_fk_tag
FOREIGN KEY (tag)
REFERENCES tag(id);
```

```
ALTER TABLE work_type
ADD CONSTRAINT work_type_fk_parent
FOREIGN KEY (parent)
REFERENCES work_type(id);
```

```
\set ON_ERROR_STOP 1
BEGIN;
```

```
ALTER TABLE area ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE artist ADD CHECK
(controlled_for_whitespace(comment));
```



```

ALTER TABLE event ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE instrument ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE label ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE medium ADD CHECK (controlled_for_whitespace(name));
ALTER TABLE place ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE recording ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE release ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE release_group ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE release_label ADD CHECK
(controlled_for_whitespace(catalog_number));
ALTER TABLE series ADD CHECK
(controlled_for_whitespace(comment));
ALTER TABLE track ADD CHECK (controlled_for_whitespace(number));
ALTER TABLE work ADD CHECK
(controlled_for_whitespace(comment));

ALTER TABLE area
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name)),
    ADD CONSTRAINT only_non_empty CHECK (name != "");

ALTER TABLE area_alias
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name)),
    ADD CONSTRAINT only_non_empty CHECK (name != ""),
    ADD CONSTRAINT control_for_whitespace_sort_name CHECK
(controlled_for_whitespace(sort_name)),
    ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != "");

ALTER TABLE artist
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name)),
    ADD CONSTRAINT only_non_empty CHECK (name != ""),
    ADD CONSTRAINT control_for_whitespace_sort_name CHECK
(controlled_for_whitespace(sort_name)),
    ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != "");

```

```

ALTER TABLE artist_alias
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name)),
    ADD CONSTRAINT only_non_empty CHECK (name != ''),
    ADD CONSTRAINT control_for_whitespace_sort_name CHECK
(controlled_for_whitespace(sort_name)),
    ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != '');

```

```

ALTER TABLE editor_collection_type
    ADD CONSTRAINT allowed_collection_entity_type CHECK (
        entity_type IN (
            'area', 'artist', 'event', 'genre', 'instrument', 'label',
            'place', 'recording', 'release', 'release_group',
            'series', 'work'
        )
    );

```

```

ALTER TABLE event
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name));

```

```

ALTER TABLE event_alias
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name)),
    ADD CONSTRAINT only_non_empty CHECK (name != ''),
    ADD CONSTRAINT control_for_whitespace_sort_name CHECK
(controlled_for_whitespace(sort_name)),
    ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != '');

```

```

ALTER TABLE artist_credit
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name)),
    ADD CONSTRAINT only_non_empty CHECK (name != '');

```

```

ALTER TABLE artist_credit_name
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name)),
    ADD CONSTRAINT only_non_empty CHECK (name != '');

```

```

ALTER TABLE instrument
    ADD CONSTRAINT control_for_whitespace CHECK
(controlled_for_whitespace(name)),

```

```
ADD CONSTRAINT only_non_empty CHECK (name != "");
```

```
ALTER TABLE instrument_alias
```

```
    ADD CONSTRAINT control_for_whitespace CHECK  
(controlled_for_whitespace(name)),
```

```
    ADD CONSTRAINT only_non_empty CHECK (name != ""),
```

```
    ADD CONSTRAINT control_for_whitespace_sort_name CHECK  
(controlled_for_whitespace(sort_name)),
```

```
    ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != "");
```

```
ALTER TABLE label
```

```
    ADD CONSTRAINT control_for_whitespace CHECK  
(controlled_for_whitespace(name)),
```

```
    ADD CONSTRAINT only_non_empty CHECK (name != ""),
```

```
    ADD CONSTRAINT label_code_length CHECK (label_code > 0 AND  
label_code < 1000000);
```

```
ALTER TABLE label_alias
```

```
    ADD CONSTRAINT control_for_whitespace CHECK  
(controlled_for_whitespace(name)),
```

```
    ADD CONSTRAINT only_non_empty CHECK (name != ""),
```

```
    ADD CONSTRAINT control_for_whitespace_sort_name CHECK  
(controlled_for_whitespace(sort_name)),
```

```
    ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != "");
```

```
ALTER TABLE link_attribute_text_value
```

```
    ADD CONSTRAINT control_for_whitespace CHECK  
(controlled_for_whitespace(text_value)),
```

```
    ADD CONSTRAINT only_non_empty CHECK (text_value != "");
```

```
ALTER TABLE place
```

```
    ADD CONSTRAINT control_for_whitespace CHECK  
(controlled_for_whitespace(name)),
```

```
    ADD CONSTRAINT only_non_empty CHECK (name != "");
```

```
ALTER TABLE place_alias
```

```
    ADD CONSTRAINT control_for_whitespace CHECK  
(controlled_for_whitespace(name)),
```

```
    ADD CONSTRAINT only_non_empty CHECK (name != ""),
```

```
    ADD CONSTRAINT control_for_whitespace_sort_name CHECK  
(controlled_for_whitespace(sort_name)),
```

```
    ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != "");
```

```
ALTER TABLE release
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != '');
```

```
ALTER TABLE release_alias
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != ''),
      ADD  CONSTRAINT  control_for_whitespace_sort_name  CHECK
(controlled_for_whitespace(sort_name)),
      ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != '');
```

```
ALTER TABLE release_group
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != '');
```

```
ALTER TABLE release_group_alias
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != ''),
      ADD  CONSTRAINT  control_for_whitespace_sort_name  CHECK
(controlled_for_whitespace(sort_name)),
      ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != '');
```

```
ALTER TABLE track
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != '');
```

```
ALTER TABLE recording
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != '');
```

```
ALTER TABLE recording_alias
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != ''),
      ADD  CONSTRAINT  control_for_whitespace_sort_name  CHECK
(controlled_for_whitespace(sort_name)),
      ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != '');
```

```

ALTER TABLE series
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != "");

```

```

ALTER TABLE series_type ADD CONSTRAINT allowed_series_entity_type
CHECK (
  entity_type IN (
    'artist',
    'event',
    'recording',
    'release',
    'release_group',
    'work'
  )
);

```

```

ALTER TABLE tag
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != "");

```

```

ALTER TABLE work
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != "");

```

```

ALTER TABLE work_alias
      ADD      CONSTRAINT      control_for_whitespace      CHECK
(controlled_for_whitespace(name)),
      ADD CONSTRAINT only_non_empty CHECK (name != ""),
      ADD  CONSTRAINT  control_for_whitespace_sort_name  CHECK
(controlled_for_whitespace(sort_name)),
      ADD CONSTRAINT only_non_empty_sort_name CHECK (sort_name != "");

```

```

ALTER TABLE artist
ADD CONSTRAINT group_type_implies_null_gender CHECK (
  (gender IS NULL AND type IN (2, 5, 6))
  OR type NOT IN (2, 5, 6)
  OR type IS NULL
);

```

```
ALTER TABLE release_label
ADD CHECK (catalog_number IS NOT NULL OR label IS NOT NULL);
```

```
ALTER TABLE artist ADD CONSTRAINT artist_va_check
CHECK (id <> 1 OR
      (type = 3 AND
       gender IS NULL AND
       area IS NULL AND
       begin_area IS NULL AND
       end_area IS NULL AND
       begin_date_year IS NULL AND
       begin_date_month IS NULL AND
       begin_date_day IS NULL AND
       end_date_year IS NULL AND
       end_date_month IS NULL AND
       end_date_day IS NULL));
```

```
ALTER TABLE release_unknown_country ADD CONSTRAINT
non_empty_date
CHECK (date_year IS NOT NULL OR date_month IS NOT NULL OR
date_day IS NOT NULL);
```

```
ALTER TABLE medium ADD CONSTRAINT medium_uniq
UNIQUE (release, position) DEFERRABLE INITIALLY IMMEDIATE;
```

```
ALTER TABLE track ADD CONSTRAINT track_uniq_medium_position
UNIQUE (medium, position) DEFERRABLE INITIALLY IMMEDIATE;
```

```
ALTER TABLE l_area_area ADD CONSTRAINT
control_for_whitespace_entity0_credit CHECK
(controlled_for_whitespace(entity0_credit));
```

```
ALTER TABLE l_area_area ADD CONSTRAINT
control_for_whitespace_entity1_credit CHECK
(controlled_for_whitespace(entity1_credit));
```

```
ALTER TABLE l_area_area ADD CONSTRAINT non_loop_relationship CHECK
(entity0 != entity1);
```

```
ALTER TABLE l_area_artist ADD CONSTRAINT
control_for_whitespace_entity0_credit CHECK
(controlled_for_whitespace(entity0_credit));
```

```
ALTER TABLE l_area_artist ADD CONSTRAINT
control_for_whitespace_entity1_credit CHECK
(controlled_for_whitespace(entity1_credit));
```

ALTER TABLE l_area_event control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_event control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_genre control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_genre control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_instrument control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_instrument control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_label control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_label control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_mood control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_mood control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_place control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_place control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK

ALTER TABLE l_area_recording control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_recording control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_release control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_release control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_release_group control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_release_group control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_series control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_series control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_url control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_url control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_work control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_area_work control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK

ALTER	TABLE	l_artist_artist	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_artist	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER TABLE l_artist_artist ADD CONSTRAINT non_loop_relationship				
CHECK (entity0 != entity1);				
ALTER	TABLE	l_artist_event	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_event	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_genre	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_genre	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_instrument	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_instrument	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_label	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_label	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_mood	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_mood	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				

ALTER	TABLE	l_artist_place	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_place	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_recording	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_recording	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_release	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_release	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_release_group	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_release_group	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_series	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_series	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_artist_url	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_url	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				

ALTER	TABLE	l_artist_work	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_artist_work	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_event	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_event	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_event	ADD	CONSTRAINT
non_loop_relationship				
CHECK (entity0 != entity1);				
ALTER	TABLE	l_event_genre	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_genre	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_instrument	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_instrument	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_label	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_label	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_mood	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_mood	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				

ALTER	TABLE	l_event_place	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_place	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_recording	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_recording	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_release	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_release	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_release_group	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_release_group	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_series	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_series	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_event_url	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_url	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				

ALTER	TABLE	l_event_work	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_event_work	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_genre_genre	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_genre_genre	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER TABLE l_genre_genre ADD CONSTRAINT non_loop_relationship				
CHECK (entity0 != entity1);				
ALTER	TABLE	l_genre_instrument	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_genre_instrument	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_genre_label	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_genre_label	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_genre_mood	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_genre_mood	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_genre_place	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_genre_place	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				

ALTER TABLE l_genre_recording control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_recording control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_release control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_release control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_release_group control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_release_group control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_series control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_series control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_url control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_url control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_work control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_genre_work control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK

ALTER TABLE l_instrument_instrument control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_instrument control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_instrument non_loop_relationship CHECK (entity0 != entity1);	ADD	CONSTRAINT
ALTER TABLE l_instrument_label control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_label control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_mood control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_mood control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_place control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_place control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_recording control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_recording control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_release control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_instrument_release control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK

ALTER TABLE l_instrument_release_group	ADD	CONSTRAINT
control_for_whitespace_entity0_credit		CHECK
(controlled_for_whitespace(entity0_credit));		
ALTER TABLE l_instrument_release_group	ADD	CONSTRAINT
control_for_whitespace_entity1_credit		CHECK
(controlled_for_whitespace(entity1_credit));		
ALTER TABLE l_instrument_series	ADD	CONSTRAINT
control_for_whitespace_entity0_credit		CHECK
(controlled_for_whitespace(entity0_credit));		
ALTER TABLE l_instrument_series	ADD	CONSTRAINT
control_for_whitespace_entity1_credit		CHECK
(controlled_for_whitespace(entity1_credit));		
ALTER TABLE l_instrument_url	ADD	CONSTRAINT
control_for_whitespace_entity0_credit		CHECK
(controlled_for_whitespace(entity0_credit));		
ALTER TABLE l_instrument_url	ADD	CONSTRAINT
control_for_whitespace_entity1_credit		CHECK
(controlled_for_whitespace(entity1_credit));		
ALTER TABLE l_instrument_work	ADD	CONSTRAINT
control_for_whitespace_entity0_credit		CHECK
(controlled_for_whitespace(entity0_credit));		
ALTER TABLE l_instrument_work	ADD	CONSTRAINT
control_for_whitespace_entity1_credit		CHECK
(controlled_for_whitespace(entity1_credit));		
ALTER TABLE l_label_label	ADD	CONSTRAINT
control_for_whitespace_entity0_credit		CHECK
(controlled_for_whitespace(entity0_credit));		
ALTER TABLE l_label_label	ADD	CONSTRAINT
control_for_whitespace_entity1_credit		CHECK
(controlled_for_whitespace(entity1_credit));		
ALTER TABLE l_label_label	ADD CONSTRAINT	non_loop_relationship
CHECK (entity0 != entity1);		
ALTER TABLE l_label_mood	ADD	CONSTRAINT
control_for_whitespace_entity0_credit		CHECK
(controlled_for_whitespace(entity0_credit));		

ALTER	TABLE	l_label_mood	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_label_place	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_label_place	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_label_recording	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_label_recording	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_label_release	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_label_release	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_label_release_group	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_label_release_group	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_label_series	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_label_series	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_label_url	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				

ALTER	TABLE	l_label_url	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_label_work	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_label_work	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_mood_mood	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_mood_mood	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER TABLE l_mood_mood ADD CONSTRAINT non_loop_relationship				
CHECK (entity0 != entity1);				
ALTER	TABLE	l_mood_place	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_mood_place	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_mood_recording	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_mood_recording	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_mood_release	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_mood_release	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				

ALTER TABLE l_mood_release_group control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_mood_release_group control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_mood_series control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_mood_series control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_mood_url control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_mood_url control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_mood_work control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_mood_work control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_place_place control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_place_place control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_place_place ADD CONSTRAINT non_loop_relationship CHECK (entity0 != entity1);		
ALTER TABLE l_place_recording control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_place_recording control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK

ALTER	TABLE	l_place_release	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_place_release	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_place_release_group	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_place_release_group	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_place_series	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_place_series	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_place_url	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_place_url	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_place_work	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_place_work	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_recording_recording	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_recording_recording	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				

ALTER TABLE l_recording_recording non_loop_relationship CHECK (entity0 != entity1);	ADD	CONSTRAINT
ALTER TABLE l_recording_release control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_release control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_release_group control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_release_group control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_series control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_series control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_url control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_url control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_work control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_recording_work control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_release_release control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK

ALTER	TABLE	l_release_release	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_release_release	ADD	CONSTRAINT
non_loop_relationship				CHECK (entity0 != entity1);
ALTER	TABLE	l_release_release_group	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_release_release_group	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_release_series	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_release_series	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_release_url	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_release_url	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_release_work	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_release_work	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_release_group_release_group	ADD	CONSTRAINT
control_for_whitespace_entity0_credit				CHECK
(controlled_for_whitespace(entity0_credit));				
ALTER	TABLE	l_release_group_release_group	ADD	CONSTRAINT
control_for_whitespace_entity1_credit				CHECK
(controlled_for_whitespace(entity1_credit));				
ALTER	TABLE	l_release_group_release_group	ADD	CONSTRAINT
non_loop_relationship				CHECK (entity0 != entity1);

ALTER TABLE l_release_group_series control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_release_group_series control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_release_group_url control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_release_group_url control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_release_group_work control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_release_group_work control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_series_series control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_series_series control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_series_series ADD CONSTRAINT non_loop_relationship CHECK (entity0 != entity1);		
ALTER TABLE l_series_url control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_series_url control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_series_work control_for_whitespace_entity0_credit (controlled_for_whitespace(entity0_credit));	ADD	CONSTRAINT CHECK
ALTER TABLE l_series_work control_for_whitespace_entity1_credit (controlled_for_whitespace(entity1_credit));	ADD	CONSTRAINT CHECK

```

ALTER      TABLE      l_url_url      ADD      CONSTRAINT
control_for_whitespace_entity0_credit      CHECK
(controlled_for_whitespace(entity0_credit));
ALTER      TABLE      l_url_url      ADD      CONSTRAINT
control_for_whitespace_entity1_credit      CHECK
(controlled_for_whitespace(entity1_credit));
ALTER TABLE l_url_url ADD CONSTRAINT non_loop_relationship CHECK
(entity0 != entity1);

```

```

ALTER      TABLE      l_url_work      ADD      CONSTRAINT
control_for_whitespace_entity0_credit      CHECK
(controlled_for_whitespace(entity0_credit));
ALTER      TABLE      l_url_work      ADD      CONSTRAINT
control_for_whitespace_entity1_credit      CHECK
(controlled_for_whitespace(entity1_credit));

```

```

ALTER      TABLE      l_work_work      ADD      CONSTRAINT
control_for_whitespace_entity0_credit      CHECK
(controlled_for_whitespace(entity0_credit));
ALTER      TABLE      l_work_work      ADD      CONSTRAINT
control_for_whitespace_entity1_credit      CHECK
(controlled_for_whitespace(entity1_credit));
ALTER TABLE l_work_work ADD CONSTRAINT non_loop_relationship
CHECK (entity0 != entity1);

```

```

COMMIT;

```

```

-- Automatically generated, do not edit.
\set ON_ERROR_STOP 1

```

```

ALTER      TABLE      alternative_medium      ADD      CONSTRAINT
alternative_medium_pkey PRIMARY KEY (id);
ALTER      TABLE      alternative_medium_track      ADD      CONSTRAINT
alternative_medium_track_pkey PRIMARY KEY (alternative_medium, track);
ALTER      TABLE      alternative_release      ADD      CONSTRAINT
alternative_release_pkey PRIMARY KEY (id);
ALTER      TABLE      alternative_release_type      ADD      CONSTRAINT
alternative_release_type_pkey PRIMARY KEY (id);
ALTER TABLE alternative_track ADD CONSTRAINT alternative_track_pkey
PRIMARY KEY (id);

```



```

ALTER TABLE annotation ADD CONSTRAINT annotation_pkey PRIMARY
KEY (id);
ALTER TABLE application ADD CONSTRAINT application_pkey PRIMARY
KEY (id);
ALTER TABLE area ADD CONSTRAINT area_pkey PRIMARY KEY (id);
ALTER TABLE area_alias ADD CONSTRAINT area_alias_pkey PRIMARY KEY
(id);
ALTER TABLE area_alias_type ADD CONSTRAINT area_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE area_annotation ADD CONSTRAINT area_annotation_pkey
PRIMARY KEY (area, annotation);
ALTER TABLE area_attribute ADD CONSTRAINT area_attribute_pkey
PRIMARY KEY (id);
ALTER TABLE area_attribute_type ADD CONSTRAINT
area_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE area_attribute_type_allowed_value ADD CONSTRAINT
area_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE area_containment ADD CONSTRAINT
area_containment_pkey PRIMARY KEY (descendant, parent);
ALTER TABLE area_gid_redirect ADD CONSTRAINT area_gid_redirect_pkey
PRIMARY KEY (gid);
ALTER TABLE area_tag ADD CONSTRAINT area_tag_pkey PRIMARY KEY
(area, tag);
ALTER TABLE area_tag_raw ADD CONSTRAINT area_tag_raw_pkey
PRIMARY KEY (area, editor, tag);
ALTER TABLE area_type ADD CONSTRAINT area_type_pkey PRIMARY KEY
(id);
ALTER TABLE artist ADD CONSTRAINT artist_pkey PRIMARY KEY (id);
ALTER TABLE artist_alias ADD CONSTRAINT artist_alias_pkey PRIMARY
KEY (id);
ALTER TABLE artist_alias_type ADD CONSTRAINT artist_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE artist_annotation ADD CONSTRAINT artist_annotation_pkey
PRIMARY KEY (artist, annotation);
ALTER TABLE artist_attribute ADD CONSTRAINT artist_attribute_pkey
PRIMARY KEY (id);
ALTER TABLE artist_attribute_type ADD CONSTRAINT
artist_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE artist_attribute_type_allowed_value ADD CONSTRAINT
artist_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE artist_credit ADD CONSTRAINT artist_credit_pkey PRIMARY
KEY (id);

```

```

ALTER      TABLE      artist_credit_gid_redirect      ADD      CONSTRAINT
artist_credit_gid_redirect_pkey PRIMARY KEY (gid);
ALTER      TABLE      artist_credit_name      ADD      CONSTRAINT
artist_credit_name_pkey PRIMARY KEY (artist_credit, position);
ALTER      TABLE      artist_gid_redirect      ADD      CONSTRAINT
artist_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE artist_ipi ADD CONSTRAINT artist_ipi_pkey PRIMARY KEY
(artist, ipi);
ALTER TABLE artist_isni ADD CONSTRAINT artist_isni_pkey PRIMARY KEY
(artist, isni);
ALTER TABLE artist_meta ADD CONSTRAINT artist_meta_pkey PRIMARY
KEY (id);
ALTER TABLE artist_rating_raw ADD CONSTRAINT artist_rating_raw_pkey
PRIMARY KEY (artist, editor);
ALTER TABLE artist_tag ADD CONSTRAINT artist_tag_pkey PRIMARY KEY
(artist, tag);
ALTER TABLE artist_tag_raw ADD CONSTRAINT artist_tag_raw_pkey
PRIMARY KEY (artist, editor, tag);
ALTER TABLE artist_type ADD CONSTRAINT artist_type_pkey PRIMARY
KEY (id);
ALTER      TABLE      autoeditor_election      ADD      CONSTRAINT
autoeditor_election_pkey PRIMARY KEY (id);
ALTER      TABLE      autoeditor_election_vote      ADD      CONSTRAINT
autoeditor_election_vote_pkey PRIMARY KEY (id);
ALTER TABLE cdtoc ADD CONSTRAINT cdtoc_pkey PRIMARY KEY (id);
ALTER TABLE cdtoc_raw ADD CONSTRAINT cdtoc_raw_pkey PRIMARY KEY
(id);
ALTER TABLE country_area ADD CONSTRAINT country_area_pkey
PRIMARY KEY (area);
ALTER TABLE deleted_entity ADD CONSTRAINT deleted_entity_pkey
PRIMARY KEY (gid);
ALTER TABLE edit ADD CONSTRAINT edit_pkey PRIMARY KEY (id);
ALTER TABLE edit_area ADD CONSTRAINT edit_area_pkey PRIMARY KEY
(edit, area);
ALTER TABLE edit_artist ADD CONSTRAINT edit_artist_pkey PRIMARY KEY
(edit, artist);
ALTER TABLE edit_data ADD CONSTRAINT edit_data_pkey PRIMARY KEY
(edit);
ALTER TABLE edit_event ADD CONSTRAINT edit_event_pkey PRIMARY KEY
(edit, event);
ALTER TABLE edit_genre ADD CONSTRAINT edit_genre_pkey PRIMARY KEY
(edit, genre);

```

```

ALTER TABLE edit_instrument ADD CONSTRAINT edit_instrument_pkey
PRIMARY KEY (edit, instrument);
ALTER TABLE edit_label ADD CONSTRAINT edit_label_pkey PRIMARY KEY
(edit, label);
ALTER TABLE edit_mood ADD CONSTRAINT edit_mood_pkey PRIMARY
KEY (edit, mood);
ALTER TABLE edit_note ADD CONSTRAINT edit_note_pkey PRIMARY KEY
(id);
ALTER TABLE edit_note_change ADD CONSTRAINT edit_note_change_pkey
PRIMARY KEY (id);
ALTER TABLE edit_note_recipient ADD CONSTRAINT
edit_note_recipient_pkey PRIMARY KEY (recipient, edit_note);
ALTER TABLE edit_place ADD CONSTRAINT edit_place_pkey PRIMARY KEY
(edit, place);
ALTER TABLE edit_recording ADD CONSTRAINT edit_recording_pkey
PRIMARY KEY (edit, recording);
ALTER TABLE edit_release ADD CONSTRAINT edit_release_pkey PRIMARY
KEY (edit, release);
ALTER TABLE edit_release_group ADD CONSTRAINT
edit_release_group_pkey PRIMARY KEY (edit, release_group);
ALTER TABLE edit_series ADD CONSTRAINT edit_series_pkey PRIMARY
KEY (edit, series);
ALTER TABLE edit_url ADD CONSTRAINT edit_url_pkey PRIMARY KEY
(edit, url);
ALTER TABLE edit_work ADD CONSTRAINT edit_work_pkey PRIMARY KEY
(edit, work);
ALTER TABLE editor ADD CONSTRAINT editor_pkey PRIMARY KEY (id);
ALTER TABLE editor_collection ADD CONSTRAINT editor_collection_pkey
PRIMARY KEY (id);
ALTER TABLE editor_collection_area ADD CONSTRAINT
editor_collection_area_pkey PRIMARY KEY (collection, area);
ALTER TABLE editor_collection_artist ADD CONSTRAINT
editor_collection_artist_pkey PRIMARY KEY (collection, artist);
ALTER TABLE editor_collection_collaborator ADD CONSTRAINT
editor_collection_collaborator_pkey PRIMARY KEY (collection, editor);
ALTER TABLE editor_collection_deleted_entity ADD CONSTRAINT
editor_collection_deleted_entity_pkey PRIMARY KEY (collection, gid);
ALTER TABLE editor_collection_event ADD CONSTRAINT
editor_collection_event_pkey PRIMARY KEY (collection, event);
ALTER TABLE editor_collection_genre ADD CONSTRAINT
editor_collection_genre_pkey PRIMARY KEY (collection, genre);
ALTER TABLE editor_collection_gid_redirect ADD CONSTRAINT
editor_collection_gid_redirect_pkey PRIMARY KEY (gid);

```

```

ALTER TABLE editor_collection_instrument ADD CONSTRAINT
editor_collection_instrument_pkey PRIMARY KEY (collection, instrument);
ALTER TABLE editor_collection_label ADD CONSTRAINT
editor_collection_label_pkey PRIMARY KEY (collection, label);
ALTER TABLE editor_collection_place ADD CONSTRAINT
editor_collection_place_pkey PRIMARY KEY (collection, place);
ALTER TABLE editor_collection_recording ADD CONSTRAINT
editor_collection_recording_pkey PRIMARY KEY (collection, recording);
ALTER TABLE editor_collection_release ADD CONSTRAINT
editor_collection_release_pkey PRIMARY KEY (collection, release);
ALTER TABLE editor_collection_release_group ADD CONSTRAINT
editor_collection_release_group_pkey PRIMARY KEY (collection,
release_group);
ALTER TABLE editor_collection_series ADD CONSTRAINT
editor_collection_series_pkey PRIMARY KEY (collection, series);
ALTER TABLE editor_collection_type ADD CONSTRAINT
editor_collection_type_pkey PRIMARY KEY (id);
ALTER TABLE editor_collection_work ADD CONSTRAINT
editor_collection_work_pkey PRIMARY KEY (collection, work);
ALTER TABLE editor_language ADD CONSTRAINT editor_language_pkey
PRIMARY KEY (editor, language);
ALTER TABLE editor_oauth_token ADD CONSTRAINT
editor_oauth_token_pkey PRIMARY KEY (id);
ALTER TABLE editor_preference ADD CONSTRAINT editor_preference_pkey
PRIMARY KEY (id);
ALTER TABLE editor_subscribe_artist ADD CONSTRAINT
editor_subscribe_artist_pkey PRIMARY KEY (id);
ALTER TABLE editor_subscribe_artist_deleted ADD CONSTRAINT
editor_subscribe_artist_deleted_pkey PRIMARY KEY (editor, gid);
ALTER TABLE editor_subscribe_collection ADD CONSTRAINT
editor_subscribe_collection_pkey PRIMARY KEY (id);
ALTER TABLE editor_subscribe_editor ADD CONSTRAINT
editor_subscribe_editor_pkey PRIMARY KEY (id);
ALTER TABLE editor_subscribe_label ADD CONSTRAINT
editor_subscribe_label_pkey PRIMARY KEY (id);
ALTER TABLE editor_subscribe_label_deleted ADD CONSTRAINT
editor_subscribe_label_deleted_pkey PRIMARY KEY (editor, gid);
ALTER TABLE editor_subscribe_series ADD CONSTRAINT
editor_subscribe_series_pkey PRIMARY KEY (id);
ALTER TABLE editor_subscribe_series_deleted ADD CONSTRAINT
editor_subscribe_series_deleted_pkey PRIMARY KEY (editor, gid);
ALTER TABLE event ADD CONSTRAINT event_pkey PRIMARY KEY (id);

```

```

ALTER TABLE event_alias ADD CONSTRAINT event_alias_pkey PRIMARY
KEY (id);
ALTER TABLE event_alias_type ADD CONSTRAINT event_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE event_annotation ADD CONSTRAINT event_annotation_pkey
PRIMARY KEY (event, annotation);
ALTER TABLE event_attribute ADD CONSTRAINT event_attribute_pkey
PRIMARY KEY (id);
ALTER TABLE event_attribute_type ADD CONSTRAINT
event_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE event_attribute_type_allowed_value ADD CONSTRAINT
event_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE event_gid_redirect ADD CONSTRAINT
event_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE event_meta ADD CONSTRAINT event_meta_pkey PRIMARY
KEY (id);
ALTER TABLE event_rating_raw ADD CONSTRAINT event_rating_raw_pkey
PRIMARY KEY (event, editor);
ALTER TABLE event_tag ADD CONSTRAINT event_tag_pkey PRIMARY KEY
(event, tag);
ALTER TABLE event_tag_raw ADD CONSTRAINT event_tag_raw_pkey
PRIMARY KEY (event, editor, tag);
ALTER TABLE event_type ADD CONSTRAINT event_type_pkey PRIMARY
KEY (id);
ALTER TABLE gender ADD CONSTRAINT gender_pkey PRIMARY KEY (id);
ALTER TABLE genre ADD CONSTRAINT genre_pkey PRIMARY KEY (id);
ALTER TABLE genre_alias ADD CONSTRAINT genre_alias_pkey PRIMARY
KEY (id);
ALTER TABLE genre_alias_type ADD CONSTRAINT genre_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE genre_annotation ADD CONSTRAINT genre_annotation_pkey
PRIMARY KEY (genre, annotation);
ALTER TABLE instrument ADD CONSTRAINT instrument_pkey PRIMARY
KEY (id);
ALTER TABLE instrument_alias ADD CONSTRAINT instrument_alias_pkey
PRIMARY KEY (id);
ALTER TABLE instrument_alias_type ADD CONSTRAINT
instrument_alias_type_pkey PRIMARY KEY (id);
ALTER TABLE instrument_annotation ADD CONSTRAINT
instrument_annotation_pkey PRIMARY KEY (instrument, annotation);
ALTER TABLE instrument_attribute ADD CONSTRAINT
instrument_attribute_pkey PRIMARY KEY (id);

```

```

ALTER TABLE instrument_attribute_type ADD CONSTRAINT
instrument_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE instrument_attribute_type_allowed_value ADD CONSTRAINT
instrument_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE instrument_gid_redirect ADD CONSTRAINT
instrument_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE instrument_tag ADD CONSTRAINT instrument_tag_pkey
PRIMARY KEY (instrument, tag);
ALTER TABLE instrument_tag_raw ADD CONSTRAINT
instrument_tag_raw_pkey PRIMARY KEY (instrument, editor, tag);
ALTER TABLE instrument_type ADD CONSTRAINT instrument_type_pkey
PRIMARY KEY (id);
ALTER TABLE iso_3166_1 ADD CONSTRAINT iso_3166_1_pkey PRIMARY KEY
(code);
ALTER TABLE iso_3166_2 ADD CONSTRAINT iso_3166_2_pkey PRIMARY KEY
(code);
ALTER TABLE iso_3166_3 ADD CONSTRAINT iso_3166_3_pkey PRIMARY KEY
(code);
ALTER TABLE isrc ADD CONSTRAINT isrc_pkey PRIMARY KEY (id);
ALTER TABLE iswc ADD CONSTRAINT iswc_pkey PRIMARY KEY (id);
ALTER TABLE l_area_area ADD CONSTRAINT l_area_area_pkey PRIMARY
KEY (id);
ALTER TABLE l_area_artist ADD CONSTRAINT l_area_artist_pkey PRIMARY
KEY (id);
ALTER TABLE l_area_event ADD CONSTRAINT l_area_event_pkey PRIMARY
KEY (id);
ALTER TABLE l_area_genre ADD CONSTRAINT l_area_genre_pkey PRIMARY
KEY (id);
ALTER TABLE l_area_instrument ADD CONSTRAINT
l_area_instrument_pkey PRIMARY KEY (id);
ALTER TABLE l_area_label ADD CONSTRAINT l_area_label_pkey PRIMARY
KEY (id);
ALTER TABLE l_area_mood ADD CONSTRAINT l_area_mood_pkey PRIMARY
KEY (id);
ALTER TABLE l_area_place ADD CONSTRAINT l_area_place_pkey PRIMARY
KEY (id);
ALTER TABLE l_area_recording ADD CONSTRAINT l_area_recording_pkey
PRIMARY KEY (id);
ALTER TABLE l_area_release ADD CONSTRAINT l_area_release_pkey
PRIMARY KEY (id);
ALTER TABLE l_area_release_group ADD CONSTRAINT
l_area_release_group_pkey PRIMARY KEY (id);

```

```
ALTER TABLE l_area_series ADD CONSTRAINT l_area_series_pkey PRIMARY
KEY (id);
ALTER TABLE l_area_url ADD CONSTRAINT l_area_url_pkey PRIMARY KEY
(id);
ALTER TABLE l_area_work ADD CONSTRAINT l_area_work_pkey PRIMARY
KEY (id);
ALTER TABLE l_artist_artist ADD CONSTRAINT l_artist_artist_pkey
PRIMARY KEY (id);
ALTER TABLE l_artist_event ADD CONSTRAINT l_artist_event_pkey
PRIMARY KEY (id);
ALTER TABLE l_artist_genre ADD CONSTRAINT l_artist_genre_pkey
PRIMARY KEY (id);
ALTER TABLE l_artist_instrument ADD CONSTRAINT
l_artist_instrument_pkey PRIMARY KEY (id);
ALTER TABLE l_artist_label ADD CONSTRAINT l_artist_label_pkey PRIMARY
KEY (id);
ALTER TABLE l_artist_mood ADD CONSTRAINT l_artist_mood_pkey
PRIMARY KEY (id);
ALTER TABLE l_artist_place ADD CONSTRAINT l_artist_place_pkey
PRIMARY KEY (id);
ALTER TABLE l_artist_recording ADD CONSTRAINT l_artist_recording_pkey
PRIMARY KEY (id);
ALTER TABLE l_artist_release ADD CONSTRAINT l_artist_release_pkey
PRIMARY KEY (id);
ALTER TABLE l_artist_release_group ADD CONSTRAINT
l_artist_release_group_pkey PRIMARY KEY (id);
ALTER TABLE l_artist_series ADD CONSTRAINT l_artist_series_pkey
PRIMARY KEY (id);
ALTER TABLE l_artist_url ADD CONSTRAINT l_artist_url_pkey PRIMARY
KEY (id);
ALTER TABLE l_artist_work ADD CONSTRAINT l_artist_work_pkey
PRIMARY KEY (id);
ALTER TABLE l_event_event ADD CONSTRAINT l_event_event_pkey
PRIMARY KEY (id);
ALTER TABLE l_event_genre ADD CONSTRAINT l_event_genre_pkey
PRIMARY KEY (id);
ALTER TABLE l_event_instrument ADD CONSTRAINT
l_event_instrument_pkey PRIMARY KEY (id);
ALTER TABLE l_event_label ADD CONSTRAINT l_event_label_pkey
PRIMARY KEY (id);
ALTER TABLE l_event_mood ADD CONSTRAINT l_event_mood_pkey
PRIMARY KEY (id);
```

```

ALTER TABLE l_event_place ADD CONSTRAINT l_event_place_pkey
PRIMARY KEY (id);
ALTER TABLE l_event_recording ADD CONSTRAINT
l_event_recording_pkey PRIMARY KEY (id);
ALTER TABLE l_event_release ADD CONSTRAINT l_event_release_pkey
PRIMARY KEY (id);
ALTER TABLE l_event_release_group ADD CONSTRAINT
l_event_release_group_pkey PRIMARY KEY (id);
ALTER TABLE l_event_series ADD CONSTRAINT l_event_series_pkey
PRIMARY KEY (id);
ALTER TABLE l_event_url ADD CONSTRAINT l_event_url_pkey PRIMARY
KEY (id);
ALTER TABLE l_event_work ADD CONSTRAINT l_event_work_pkey
PRIMARY KEY (id);
ALTER TABLE l_genre_genre ADD CONSTRAINT l_genre_genre_pkey
PRIMARY KEY (id);
ALTER TABLE l_genre_instrument ADD CONSTRAINT
l_genre_instrument_pkey PRIMARY KEY (id);
ALTER TABLE l_genre_label ADD CONSTRAINT l_genre_label_pkey
PRIMARY KEY (id);
ALTER TABLE l_genre_mood ADD CONSTRAINT l_genre_mood_pkey
PRIMARY KEY (id);
ALTER TABLE l_genre_place ADD CONSTRAINT l_genre_place_pkey
PRIMARY KEY (id);
ALTER TABLE l_genre_recording ADD CONSTRAINT
l_genre_recording_pkey PRIMARY KEY (id);
ALTER TABLE l_genre_release ADD CONSTRAINT l_genre_release_pkey
PRIMARY KEY (id);
ALTER TABLE l_genre_release_group ADD CONSTRAINT
l_genre_release_group_pkey PRIMARY KEY (id);
ALTER TABLE l_genre_series ADD CONSTRAINT l_genre_series_pkey
PRIMARY KEY (id);
ALTER TABLE l_genre_url ADD CONSTRAINT l_genre_url_pkey PRIMARY
KEY (id);
ALTER TABLE l_genre_work ADD CONSTRAINT l_genre_work_pkey
PRIMARY KEY (id);
ALTER TABLE l_instrument_instrument ADD CONSTRAINT
l_instrument_instrument_pkey PRIMARY KEY (id);
ALTER TABLE l_instrument_label ADD CONSTRAINT
l_instrument_label_pkey PRIMARY KEY (id);
ALTER TABLE l_instrument_mood ADD CONSTRAINT
l_instrument_mood_pkey PRIMARY KEY (id);

```



```

ALTER      TABLE      l_instrument_place      ADD      CONSTRAINT
l_instrument_place_pkey PRIMARY KEY (id);
ALTER      TABLE      l_instrument_recording  ADD      CONSTRAINT
l_instrument_recording_pkey PRIMARY KEY (id);
ALTER      TABLE      l_instrument_release    ADD      CONSTRAINT
l_instrument_release_pkey PRIMARY KEY (id);
ALTER      TABLE      l_instrument_release_group  ADD      CONSTRAINT
l_instrument_release_group_pkey PRIMARY KEY (id);
ALTER      TABLE      l_instrument_series      ADD      CONSTRAINT
l_instrument_series_pkey PRIMARY KEY (id);
ALTER TABLE l_instrument_url ADD CONSTRAINT l_instrument_url_pkey
PRIMARY KEY (id);
ALTER      TABLE      l_instrument_work      ADD      CONSTRAINT
l_instrument_work_pkey PRIMARY KEY (id);
ALTER TABLE l_label_label ADD CONSTRAINT l_label_label_pkey PRIMARY
KEY (id);
ALTER TABLE l_label_mood  ADD  CONSTRAINT  l_label_mood_pkey
PRIMARY KEY (id);
ALTER TABLE l_label_place ADD CONSTRAINT l_label_place_pkey PRIMARY
KEY (id);
ALTER TABLE l_label_recording ADD CONSTRAINT l_label_recording_pkey
PRIMARY KEY (id);
ALTER TABLE l_label_release ADD CONSTRAINT l_label_release_pkey
PRIMARY KEY (id);
ALTER      TABLE      l_label_release_group    ADD      CONSTRAINT
l_label_release_group_pkey PRIMARY KEY (id);
ALTER TABLE l_label_series ADD CONSTRAINT l_label_series_pkey
PRIMARY KEY (id);
ALTER TABLE l_label_url ADD CONSTRAINT l_label_url_pkey PRIMARY KEY
(id);
ALTER TABLE l_label_work ADD CONSTRAINT l_label_work_pkey PRIMARY
KEY (id);
ALTER TABLE l_mood_mood  ADD  CONSTRAINT  l_mood_mood_pkey
PRIMARY KEY (id);
ALTER TABLE l_mood_place ADD CONSTRAINT l_mood_place_pkey
PRIMARY KEY (id);
ALTER      TABLE      l_mood_recording      ADD      CONSTRAINT
l_mood_recording_pkey PRIMARY KEY (id);
ALTER TABLE l_mood_release ADD CONSTRAINT l_mood_release_pkey
PRIMARY KEY (id);
ALTER      TABLE      l_mood_release_group    ADD      CONSTRAINT
l_mood_release_group_pkey PRIMARY KEY (id);

```

```

ALTER TABLE l_mood_series ADD CONSTRAINT l_mood_series_pkey
PRIMARY KEY (id);
ALTER TABLE l_mood_url ADD CONSTRAINT l_mood_url_pkey PRIMARY
KEY (id);
ALTER TABLE l_mood_work ADD CONSTRAINT l_mood_work_pkey
PRIMARY KEY (id);
ALTER TABLE l_place_place ADD CONSTRAINT l_place_place_pkey
PRIMARY KEY (id);
ALTER TABLE l_place_recording ADD CONSTRAINT l_place_recording_pkey
PRIMARY KEY (id);
ALTER TABLE l_place_release ADD CONSTRAINT l_place_release_pkey
PRIMARY KEY (id);
ALTER TABLE l_place_release_group ADD CONSTRAINT
l_place_release_group_pkey PRIMARY KEY (id);
ALTER TABLE l_place_series ADD CONSTRAINT l_place_series_pkey
PRIMARY KEY (id);
ALTER TABLE l_place_url ADD CONSTRAINT l_place_url_pkey PRIMARY
KEY (id);
ALTER TABLE l_place_work ADD CONSTRAINT l_place_work_pkey
PRIMARY KEY (id);
ALTER TABLE l_recording_recording ADD CONSTRAINT
l_recording_recording_pkey PRIMARY KEY (id);
ALTER TABLE l_recording_release ADD CONSTRAINT
l_recording_release_pkey PRIMARY KEY (id);
ALTER TABLE l_recording_release_group ADD CONSTRAINT
l_recording_release_group_pkey PRIMARY KEY (id);
ALTER TABLE l_recording_series ADD CONSTRAINT
l_recording_series_pkey PRIMARY KEY (id);
ALTER TABLE l_recording_url ADD CONSTRAINT l_recording_url_pkey
PRIMARY KEY (id);
ALTER TABLE l_recording_work ADD CONSTRAINT l_recording_work_pkey
PRIMARY KEY (id);
ALTER TABLE l_release_group_release_group ADD CONSTRAINT
l_release_group_release_group_pkey PRIMARY KEY (id);
ALTER TABLE l_release_group_series ADD CONSTRAINT
l_release_group_series_pkey PRIMARY KEY (id);
ALTER TABLE l_release_group_url ADD CONSTRAINT
l_release_group_url_pkey PRIMARY KEY (id);
ALTER TABLE l_release_group_work ADD CONSTRAINT
l_release_group_work_pkey PRIMARY KEY (id);
ALTER TABLE l_release_release ADD CONSTRAINT l_release_release_pkey
PRIMARY KEY (id);

```

```

ALTER TABLE l_release_release_group ADD CONSTRAINT
l_release_release_group_pkey PRIMARY KEY (id);
ALTER TABLE l_release_series ADD CONSTRAINT l_release_series_pkey
PRIMARY KEY (id);
ALTER TABLE l_release_url ADD CONSTRAINT l_release_url_pkey PRIMARY
KEY (id);
ALTER TABLE l_release_work ADD CONSTRAINT l_release_work_pkey
PRIMARY KEY (id);
ALTER TABLE l_series_series ADD CONSTRAINT l_series_series_pkey
PRIMARY KEY (id);
ALTER TABLE l_series_url ADD CONSTRAINT l_series_url_pkey PRIMARY
KEY (id);
ALTER TABLE l_series_work ADD CONSTRAINT l_series_work_pkey
PRIMARY KEY (id);
ALTER TABLE l_url_url ADD CONSTRAINT l_url_url_pkey PRIMARY KEY (id);
ALTER TABLE l_url_work ADD CONSTRAINT l_url_work_pkey PRIMARY KEY
(id);
ALTER TABLE l_work_work ADD CONSTRAINT l_work_work_pkey PRIMARY
KEY (id);
ALTER TABLE label ADD CONSTRAINT label_pkey PRIMARY KEY (id);
ALTER TABLE label_alias ADD CONSTRAINT label_alias_pkey PRIMARY KEY
(id);
ALTER TABLE label_alias_type ADD CONSTRAINT label_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE label_annotation ADD CONSTRAINT label_annotation_pkey
PRIMARY KEY (label, annotation);
ALTER TABLE label_attribute ADD CONSTRAINT label_attribute_pkey
PRIMARY KEY (id);
ALTER TABLE label_attribute_type ADD CONSTRAINT
label_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE label_attribute_type_allowed_value ADD CONSTRAINT
label_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE label_gid_redirect ADD CONSTRAINT
label_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE label_ipi ADD CONSTRAINT label_ipi_pkey PRIMARY KEY
(label, ipi);
ALTER TABLE label_isni ADD CONSTRAINT label_isni_pkey PRIMARY KEY
(label, isni);
ALTER TABLE label_meta ADD CONSTRAINT label_meta_pkey PRIMARY
KEY (id);
ALTER TABLE label_rating_raw ADD CONSTRAINT label_rating_raw_pkey
PRIMARY KEY (label, editor);

```

```

ALTER TABLE label_tag ADD CONSTRAINT label_tag_pkey PRIMARY KEY
(label, tag);
ALTER TABLE label_tag_raw ADD CONSTRAINT label_tag_raw_pkey
PRIMARY KEY (label, editor, tag);
ALTER TABLE label_type ADD CONSTRAINT label_type_pkey PRIMARY KEY
(id);
ALTER TABLE language ADD CONSTRAINT language_pkey PRIMARY KEY
(id);
ALTER TABLE link ADD CONSTRAINT link_pkey PRIMARY KEY (id);
ALTER TABLE link_attribute ADD CONSTRAINT link_attribute_pkey
PRIMARY KEY (link, attribute_type);
ALTER TABLE link_attribute_credit ADD CONSTRAINT
link_attribute_credit_pkey PRIMARY KEY (link, attribute_type);
ALTER TABLE link_attribute_text_value ADD CONSTRAINT
link_attribute_text_value_pkey PRIMARY KEY (link, attribute_type);
ALTER TABLE link_attribute_type ADD CONSTRAINT
link_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE link_creditable_attribute_type ADD CONSTRAINT
link_creditable_attribute_type_pkey PRIMARY KEY (attribute_type);
ALTER TABLE link_text_attribute_type ADD CONSTRAINT
link_text_attribute_type_pkey PRIMARY KEY (attribute_type);
ALTER TABLE link_type ADD CONSTRAINT link_type_pkey PRIMARY KEY
(id);
ALTER TABLE link_type_attribute_type ADD CONSTRAINT
link_type_attribute_type_pkey PRIMARY KEY (link_type, attribute_type);
ALTER TABLE medium ADD CONSTRAINT medium_pkey PRIMARY KEY (id);
ALTER TABLE medium_attribute ADD CONSTRAINT
medium_attribute_pkey PRIMARY KEY (id);
ALTER TABLE medium_attribute_type ADD CONSTRAINT
medium_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE medium_attribute_type_allowed_format ADD CONSTRAINT
medium_attribute_type_allowed_format_pkey PRIMARY KEY
(medium_format, medium_attribute_type);
ALTER TABLE medium_attribute_type_allowed_value ADD CONSTRAINT
medium_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE medium_attribute_type_allowed_value_allowed_format ADD
CONSTRAINT medium_attribute_type_allowed_value_allowed_format_pkey
PRIMARY KEY (medium_format, medium_attribute_type_allowed_value);
ALTER TABLE medium_cdtoc ADD CONSTRAINT medium_cdtoc_pkey
PRIMARY KEY (id);
ALTER TABLE medium_format ADD CONSTRAINT medium_format_pkey
PRIMARY KEY (id);

```

```

ALTER TABLE medium_index ADD CONSTRAINT medium_index_pkey
PRIMARY KEY (medium);
ALTER TABLE mood ADD CONSTRAINT mood_pkey PRIMARY KEY (id);
ALTER TABLE mood_alias ADD CONSTRAINT mood_alias_pkey PRIMARY
KEY (id);
ALTER TABLE mood_alias_type ADD CONSTRAINT mood_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE mood_annotation ADD CONSTRAINT mood_annotation_pkey
PRIMARY KEY (mood, annotation);
ALTER TABLE orderable_link_type ADD CONSTRAINT
orderable_link_type_pkey PRIMARY KEY (link_type);
ALTER TABLE place ADD CONSTRAINT place_pkey PRIMARY KEY (id);
ALTER TABLE place_alias ADD CONSTRAINT place_alias_pkey PRIMARY
KEY (id);
ALTER TABLE place_alias_type ADD CONSTRAINT place_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE place_annotation ADD CONSTRAINT place_annotation_pkey
PRIMARY KEY (place, annotation);
ALTER TABLE place_attribute ADD CONSTRAINT place_attribute_pkey
PRIMARY KEY (id);
ALTER TABLE place_attribute_type ADD CONSTRAINT
place_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE place_attribute_type_allowed_value ADD CONSTRAINT
place_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE place_gid_redirect ADD CONSTRAINT
place_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE place_meta ADD CONSTRAINT place_meta_pkey PRIMARY
KEY (id);
ALTER TABLE place_rating_raw ADD CONSTRAINT place_rating_raw_pkey
PRIMARY KEY (place, editor);
ALTER TABLE place_tag ADD CONSTRAINT place_tag_pkey PRIMARY KEY
(place, tag);
ALTER TABLE place_tag_raw ADD CONSTRAINT place_tag_raw_pkey
PRIMARY KEY (place, editor, tag);
ALTER TABLE place_type ADD CONSTRAINT place_type_pkey PRIMARY
KEY (id);
ALTER TABLE recording ADD CONSTRAINT recording_pkey PRIMARY KEY
(id);
ALTER TABLE recording_alias ADD CONSTRAINT recording_alias_pkey
PRIMARY KEY (id);
ALTER TABLE recording_alias_type ADD CONSTRAINT
recording_alias_type_pkey PRIMARY KEY (id);

```

```

ALTER      TABLE      recording_annotation      ADD      CONSTRAINT
recording_annotation_pkey PRIMARY KEY (recording, annotation);
ALTER      TABLE      recording_attribute      ADD      CONSTRAINT
recording_attribute_pkey PRIMARY KEY (id);
ALTER      TABLE      recording_attribute_type      ADD      CONSTRAINT
recording_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE recording_attribute_type_allowed_value ADD CONSTRAINT
recording_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER      TABLE      recording_first_release_date      ADD      CONSTRAINT
recording_first_release_date_pkey PRIMARY KEY (recording);
ALTER      TABLE      recording_gid_redirect      ADD      CONSTRAINT
recording_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE recording_meta ADD CONSTRAINT recording_meta_pkey
PRIMARY KEY (id);
ALTER      TABLE      recording_rating_raw      ADD      CONSTRAINT
recording_rating_raw_pkey PRIMARY KEY (recording, editor);
ALTER TABLE recording_tag ADD CONSTRAINT recording_tag_pkey
PRIMARY KEY (recording, tag);
ALTER      TABLE      recording_tag_raw      ADD      CONSTRAINT
recording_tag_raw_pkey PRIMARY KEY (recording, editor, tag);
ALTER TABLE release ADD CONSTRAINT release_pkey PRIMARY KEY (id);
ALTER TABLE release_alias ADD CONSTRAINT release_alias_pkey PRIMARY
KEY (id);
ALTER      TABLE      release_alias_type      ADD      CONSTRAINT
release_alias_type_pkey PRIMARY KEY (id);
ALTER      TABLE      release_annotation      ADD      CONSTRAINT
release_annotation_pkey PRIMARY KEY (release, annotation);
ALTER TABLE release_attribute ADD CONSTRAINT release_attribute_pkey
PRIMARY KEY (id);
ALTER      TABLE      release_attribute_type      ADD      CONSTRAINT
release_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE release_attribute_type_allowed_value ADD CONSTRAINT
release_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE release_country ADD CONSTRAINT release_country_pkey
PRIMARY KEY (release, country);
ALTER      TABLE      release_first_release_date      ADD      CONSTRAINT
release_first_release_date_pkey PRIMARY KEY (release);
ALTER      TABLE      release_gid_redirect      ADD      CONSTRAINT
release_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE release_group ADD CONSTRAINT release_group_pkey
PRIMARY KEY (id);
ALTER      TABLE      release_group_alias      ADD      CONSTRAINT
release_group_alias_pkey PRIMARY KEY (id);

```

```

ALTER TABLE release_group_alias_type ADD CONSTRAINT
release_group_alias_type_pkey PRIMARY KEY (id);
ALTER TABLE release_group_annotation ADD CONSTRAINT
release_group_annotation_pkey PRIMARY KEY (release_group, annotation);
ALTER TABLE release_group_attribute ADD CONSTRAINT
release_group_attribute_pkey PRIMARY KEY (id);
ALTER TABLE release_group_attribute_type ADD CONSTRAINT
release_group_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE release_group_attribute_type_allowed_value ADD
CONSTRAINT release_group_attribute_type_allowed_value_pkey PRIMARY
KEY (id);
ALTER TABLE release_group_gid_redirect ADD CONSTRAINT
release_group_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE release_group_meta ADD CONSTRAINT
release_group_meta_pkey PRIMARY KEY (id);
ALTER TABLE release_group_primary_type ADD CONSTRAINT
release_group_primary_type_pkey PRIMARY KEY (id);
ALTER TABLE release_group_rating_raw ADD CONSTRAINT
release_group_rating_raw_pkey PRIMARY KEY (release_group, editor);
ALTER TABLE release_group_secondary_type ADD CONSTRAINT
release_group_secondary_type_pkey PRIMARY KEY (id);
ALTER TABLE release_group_secondary_type_join ADD CONSTRAINT
release_group_secondary_type_join_pkey PRIMARY KEY (release_group,
secondary_type);
ALTER TABLE release_group_tag ADD CONSTRAINT
release_group_tag_pkey PRIMARY KEY (release_group, tag);
ALTER TABLE release_group_tag_raw ADD CONSTRAINT
release_group_tag_raw_pkey PRIMARY KEY (release_group, editor, tag);
ALTER TABLE release_label ADD CONSTRAINT release_label_pkey PRIMARY
KEY (id);
ALTER TABLE release_meta ADD CONSTRAINT release_meta_pkey
PRIMARY KEY (id);
ALTER TABLE release_packaging ADD CONSTRAINT
release_packaging_pkey PRIMARY KEY (id);
ALTER TABLE release_raw ADD CONSTRAINT release_raw_pkey PRIMARY
KEY (id);
ALTER TABLE release_status ADD CONSTRAINT release_status_pkey
PRIMARY KEY (id);
ALTER TABLE release_tag ADD CONSTRAINT release_tag_pkey PRIMARY
KEY (release, tag);
ALTER TABLE release_tag_raw ADD CONSTRAINT release_tag_raw_pkey
PRIMARY KEY (release, editor, tag);

```

```

ALTER TABLE release_unknown_country ADD CONSTRAINT
release_unknown_country_pkey PRIMARY KEY (release);
ALTER TABLE replication_control ADD CONSTRAINT
replication_control_pkey PRIMARY KEY (id);
ALTER TABLE script ADD CONSTRAINT script_pkey PRIMARY KEY (id);
ALTER TABLE series ADD CONSTRAINT series_pkey PRIMARY KEY (id);
ALTER TABLE series_alias ADD CONSTRAINT series_alias_pkey PRIMARY
KEY (id);
ALTER TABLE series_alias_type ADD CONSTRAINT series_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE series_annotation ADD CONSTRAINT series_annotation_pkey
PRIMARY KEY (series, annotation);
ALTER TABLE series_attribute ADD CONSTRAINT series_attribute_pkey
PRIMARY KEY (id);
ALTER TABLE series_attribute_type ADD CONSTRAINT
series_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE series_attribute_type_allowed_value ADD CONSTRAINT
series_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE series_gid_redirect ADD CONSTRAINT
series_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE series_ordering_type ADD CONSTRAINT
series_ordering_type_pkey PRIMARY KEY (id);
ALTER TABLE series_tag ADD CONSTRAINT series_tag_pkey PRIMARY KEY
(series, tag);
ALTER TABLE series_tag_raw ADD CONSTRAINT series_tag_raw_pkey
PRIMARY KEY (series, editor, tag);
ALTER TABLE series_type ADD CONSTRAINT series_type_pkey PRIMARY
KEY (id);
ALTER TABLE tag ADD CONSTRAINT tag_pkey PRIMARY KEY (id);
ALTER TABLE tag_relation ADD CONSTRAINT tag_relation_pkey PRIMARY
KEY (tag1, tag2);
ALTER TABLE track ADD CONSTRAINT track_pkey PRIMARY KEY (id);
ALTER TABLE track_gid_redirect ADD CONSTRAINT
track_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE track_raw ADD CONSTRAINT track_raw_pkey PRIMARY KEY
(id);
ALTER TABLE unreferenced_row_log ADD CONSTRAINT
unreferenced_row_log_pkey PRIMARY KEY (table_name, row_id);
ALTER TABLE url ADD CONSTRAINT url_pkey PRIMARY KEY (id);
ALTER TABLE url_gid_redirect ADD CONSTRAINT url_gid_redirect_pkey
PRIMARY KEY (gid);
ALTER TABLE vote ADD CONSTRAINT vote_pkey PRIMARY KEY (id);
ALTER TABLE work ADD CONSTRAINT work_pkey PRIMARY KEY (id);

```



```
ALTER TABLE work_alias ADD CONSTRAINT work_alias_pkey PRIMARY
KEY (id);
ALTER TABLE work_alias_type ADD CONSTRAINT work_alias_type_pkey
PRIMARY KEY (id);
ALTER TABLE work_annotation ADD CONSTRAINT work_annotation_pkey
PRIMARY KEY (work, annotation);
ALTER TABLE work_attribute ADD CONSTRAINT work_attribute_pkey
PRIMARY KEY (id);
ALTER TABLE work_attribute_type ADD CONSTRAINT
work_attribute_type_pkey PRIMARY KEY (id);
ALTER TABLE work_attribute_type_allowed_value ADD CONSTRAINT
work_attribute_type_allowed_value_pkey PRIMARY KEY (id);
ALTER TABLE work_gid_redirect ADD CONSTRAINT
work_gid_redirect_pkey PRIMARY KEY (gid);
ALTER TABLE work_language ADD CONSTRAINT work_language_pkey
PRIMARY KEY (work, language);
ALTER TABLE work_meta ADD CONSTRAINT work_meta_pkey PRIMARY
KEY (id);
ALTER TABLE work_rating_raw ADD CONSTRAINT work_rating_raw_pkey
PRIMARY KEY (work, editor);
ALTER TABLE work_tag ADD CONSTRAINT work_tag_pkey PRIMARY KEY
(work, tag);
ALTER TABLE work_tag_raw ADD CONSTRAINT work_tag_raw_pkey
PRIMARY KEY (work, editor, tag);
ALTER TABLE work_type ADD CONSTRAINT work_type_pkey PRIMARY
KEY (id);
```