# MOTH: A 19.7 MB ITALIAN–ENGLISH CODE-SWITCHING SPEECH RECOGNIZER BUILT ON A PRETRAINED WHISPER-TINY ENCODER

A PREPRINT

**Tancredi Bosi**
Semantique
tancredi.bosi@gmail.com

November 2026

**ABSTRACT**

Speech recognizers for Italian technical speech must handle English words embedded mid-sentence, but compact open models often force a single language token per clip and degrade at switches. We present Moth, a record-then-transcribe Italian–English code-switching ASR system that fits a hard 20 MB artifact budget. Moth initializes a Whisper-tiny encoder, adds two transformer blocks and a linear CTC head over a shared 1,024-piece Italian+English SentencePiece vocabulary, and drops the autoregressive decoder and the language token. The released 0.8.1 system has 11.58 M acoustic parameters and occupies 19.71 MB: an 11.91 MB int8 ONNX graph, a 5.38 MB trigram language model and a 2.33 MB Silero VAD. It is trained on 437.7 h of open human-transcribed speech, 110 h of spliced Italian–English exposure and 50.2 min of recorded mixed speech oversampled $50\times$, on one 16 GB laptop with no external compute. On a 600-utterance scripted mixed test set it reaches 24.08% WER and 55.23% English-term accuracy; on filtered FLEURS-IT it reaches 20.16% WER; the browser path decodes at a median $42\times$ real time in headless Chromium on a desktop. We report the 41-experiment development record, including rejected quantization-aware training, intermediate CTC, contextual bias, larger language models and conservative fine-tunes. Decode-side calibration and language-model data weighting produced the largest measured gains on the mixed test and the rare-term readout, respectively. We also quantify costs hidden by a single headline number: INT8 adds 0.16 pp WER on dev and the browser path 0.72 pp on the mixed test set; the three voices span 5.34 pp WER; four seeds of a rejected recipe span 0.46 pp. All code-switching quality evidence is scripted read speech from three known voices; the public FLEURS results are read speech from other speakers. The paper makes no claim of spontaneous code-switching or unseen-speaker generalization on the mixed task.

***Keywords*** speech recognition · code-switching · Italian · CTC · Whisper · quantization · on-device inference

## 1 Introduction

Italian technical speech is routinely bilingual: "ho spostato il *meeting* a domani", "mandami il *feedback* sul *deploy*", "facciamo un *quick sync* dopo la *call*". The English material is not a foreign-language sentence; it is a short, often domain-specific insertion inside an Italian utterance. A recognizer for this setting must transcribe both languages with one output stream, must not decide a single language for the whole clip, and must keep short technical terms intact.

Large multilingual systems handle such input well when they are allowed to be large. The design constraint here is the opposite: the complete set of required model assets must fit in 20 MB, the model must run on a CPU and in a browser tab, and the work must be reproducible on a single 16 GB laptop with no paid compute. Under that constraint, the standard Whisper recipe is a poor fit. Its decoder is autoregressive, its checkpoint is 39 M parameters for the tiny variant, and its language token is chosen once per 30 s window—exactly the granularity at which code-switching happens.

This paper describes Moth, a system built around a different decomposition. A pretrained Whisper-tiny encoder supplies acoustic representations learned from a large, weakly supervised corpus. Two additional transformer blocks and a linear CTC head map those representations to a single shared Italian+English SentencePiece vocabulary. There is no decoder and no language token: every frame emits either a subword or a blank. A small trigram language model is used only during beam-search decoding, and a voice-activity detector gates silence. The resulting artifact has 11.58 M acoustic parameters and occupies 19.71 MB in its shipped form.

The scientific interest is not the architecture, which is deliberately conventional. It is the measured development record under a hard byte budget, and the gap between what looks like progress on a development set and what survives on the deployed artifact. We report 41 experiments, including twelve rejected interventions. Several plausible improvements—more English data, a larger vocabulary, intermediate CTC, quantization-aware training, contextual bias, a larger language model, a conservative knowledge-distilled fine-tune—did not produce a deployable gain. The largest single improvement on the mixed test came from recalibrating the decoder; the largest rare-term improvement came from rebuilding the language model from a frozen training-side corpus with different pruning and term weighting. We quantify both, and we quantify what they cost.

**What the paper reports.**

- A complete, open-weight Italian–English code-switching system at 19.71 MB: 11.58 M acoustic parameters, an 11.91 MB int8 ONNX graph, a 5.38 MB trigram LM and a 2.33 MB VAD. It runs record-then-transcribe on CPU and in the browser via ONNX Runtime Web.
- Main results on a scripted mixed test set (24.08% WER, 55.23% ETA on 600 utterances), a never-acoustically-trained voice (24.96% / 51.27% on 200 utterances), filtered FLEURS-IT (20.16%), and a comparison against Whisper-tiny, Whistle and Parakeet at their measured artifact sizes.
- A measured account of decode-side gains, rare-term gains, noise robustness, quantization cost and browser cost, each with paired confidence intervals and the conditions under which the number was produced.
- A negative-results section that separates recipe properties from seed artifacts: the rare-term shortfall of the conservative fine-tune reproduces across eight runs, while its silence hallucination does not.
- An explicit validity boundary. Every code-switching quality number comes from scripted read speech and three known voices; the public FLEURS numbers are read speech from other speakers. There is no spontaneous code-switching test and no unseen speaker in the mixed test.

**What the paper does not claim.** It does not claim a new architecture, state-of-the-art accuracy, or general code-switching competence. It does not claim that the reported comparisons are matched in pretraining data, compute or decoding budget. It does not treat a confidence interval that includes zero as proof of equivalence. The system is a small, working artifact and the paper is a case study of how it was measured.

## 2 Related Work

**Code-switching ASR.** Code-switching has been studied with language-specific acoustic models, language identification, unified multilingual vocabularies and end-to-end models; Sitaram et al. [2019] survey the area. The SEAME [Lyu et al., 2010] and ASCEND [Lovenia et al., 2022] speech corpora made Chinese–English switching measurable, and LinCE [Aguilar et al., 2020] centralized text benchmarks across several language pairs, but Italian–English technical speech remains comparatively under-resourced. A recurring finding is that a single language token or a monolingual decoder forces an unnatural decision at the utterance level, while a shared subword vocabulary with a frame-synchronous objective avoids that decision. Moth follows the second route: one vocabulary, one CTC output stream, no language token.

**Small and on-device ASR.** Whisper [Radford et al., 2023] established robust multilingual ASR from weak supervision, and its tiny variant is a common starting point for edge systems. Distillation reduces it further [Gandhi et al., 2023]; Moonshine [Jeffries et al., 2024] targets live transcription with a compact encoder–decoder; on-device engines such as Whistle [Cactus Compute, 2024] and transducer models in NeMo [NVIDIA, 2024] provide strong engineering baselines. Quantization [Jacob et al., 2018] and integer-only inference are what make a sub-20 MB package practical. Most of these systems are optimized for English or for broad multilingual coverage; the Italian–English mixed-term case is usually a secondary condition. Moth is intentionally narrower.





Figure 1: The Moth acoustic graph. A log-mel front end feeds a stride-two convolutional stem and the four pretrained Whisper-tiny encoder blocks. Two additional pre-LayerNorm transformer blocks and a linear projection produce 1,025 CTC classes (blank plus 1,024 BPE pieces). There is no autoregressive decoder and no language token. The graph runs at 50 frames per second; the 30 s limit corresponds to 1,500 encoder frames. At inference a separate 2.33 MB Silero VAD gates silence and optionally segments multi-utterance audio, and a 5.38 MB trigram LM is used only inside beam search.

**CTC and decoding.** CTC [Graves et al., 2006] removes the need for frame-level alignment and supports a non-autoregressive, frame-synchronous encoder. Prefix beam search with an external language model [Graves, 2012, Hannun et al., 2014] remains an effective decoder for small CTC models, and intermediate CTC losses [Lee and Watanabe, 2021] are a standard regularizer. Our architecture is a plain CTC model; the interesting result is how much of the final quality is decided by decoder calibration and LM data rather than by the acoustic network.

**Evaluation validity.** Code-switching evaluation is sensitive to the test population: read scripted sentences, spontaneous conversation and elicited term lists measure different things. LinCE [Aguilar et al., 2020] makes this explicit by separating tasks and languages. We therefore report the test population, the reuse history and the per-voice range, and we do not describe the mixed test set as an untouched natural benchmark.

## 3 System

### 3.1 Task and text normalization

The input is 16 kHz mono audio, at most 30 s per request. The output is lowercase text without punctuation or case restoration. This is a record-then-transcribe system: it is not streaming, it does not produce word timestamps, and it does not perform diarization.

All training text, LM text and scoring pass through one normalizer. It applies NFKC and lowercase, folds apostrophes and joins whitespace after them, spells digit sequences with `num2words` using the language hint, separates hyphens, dashes and slashes, keeps Latin letters, Italian accented vowels and apostrophes, folds other Latin diacritics, drops other symbols and collapses whitespace. Mixed or unknown language falls back to Italian rules. Using one rule for training and scoring avoids a class of silent mismatch between the acoustic targets and the reported WER. It also means that punctuation and capitalization are outside the task, not merely unmeasured.

### 3.2 Acoustic model

Figure 1 shows the model. The front end is the Whisper log-mel representation: 80 bins, 25 ms window, 10 ms hop, per-clip dynamic-range normalization. A two-layer convolutional stem (kernel 3, stride 1 then stride 2, GELU) maps 80 bins to width 384 and halves the frame rate to 50 Hz. Four pre-LayerNorm transformer blocks follow, each with six 64-dimensional attention heads, a 1,536-wide GELU feed-forward network and a final LayerNorm. Attention is bidirectional and masked by real-frame key padding; it is not causal or streaming. Positions are fixed sinusoids generated as a non-persistent buffer, not learned parameters.

The released configuration adds two full transformer blocks after the encoder's final LayerNorm, then a linear projection to 1,025 classes and a float32 log-softmax at inference. This detail matters: early project notes describe "a linear CTC head on the Whisper encoder", which would be 8.03 M parameters. The shipped model is 11.58 M, because the two extra blocks are part of the trained and exported network. Table 1 gives the exact accounting.

The blank label is index 0; BPE piece $i$ maps to CTC index $i+1$, including the unknown piece. The model therefore has no explicit word boundary, no language tag and no punctuation class. The inductive bias is that mixed Italian–English text is one sequence over one vocabulary.

Table 1: Parameter accounting of the released acoustic network. Counts include weights and biases, exclude buffers, optimizer state, the language model and the separate VAD network.

| Component | Parameters |
|---|---|
| Convolutional stem and four pretrained encoder blocks (with final LayerNorm) | 7,632,384 |
| Two post-encoder transformer blocks ($2 \times 1{,}774{,}080$) | 3,548,160 |
| CTC linear projection ($384 \times 1025 + 1025$) | 394,625 |
| **Total acoustic network** | **11,575,169** |

### 3.3 Tokenizer

The vocabulary is a 1,024-piece SentencePiece BPE model [Kudo and Richardson, 2018] trained on normalized MLS-IT and LibriSpeech-EN training transcripts, the mixed training pool and a curated list of 580 English technical terms. Italian is oversampled to 70% of transcript words (not audio hours), and the curated terms are weighted to about 5% of corpus lines. The resulting model tokenizes at 1.945 tokens per word and 4.70 tokens per second; 48.8% of the curated English terms fit in at most three pieces. These are historical build statistics: the serialized tokenizer is not committed to the repository, and the builder does not promise byte-identical SentencePiece output across runs. The vocabulary used by the release is pinned through the exported `vocab.json`, not through the original SentencePiece model.

### 3.4 CTC decoding

The default decoder is a CTC prefix beam search [Graves, 2012] with beam width 12 and the top 10 non-blank labels per frame. A trigram BPE language model is combined in shallow fusion,

$$\log p(\mathbf{y} \mid \mathbf{x}) \;\approx\; \log p_{\mathrm{CTC}}(\mathbf{y} \mid \mathbf{x}) + \alpha \log p_{\mathrm{LM}}(\mathbf{y}) + \beta\,|\mathbf{y}|, \tag{1}$$

with LM weight $\alpha = 0.55$ and per-token bonus $\beta = 2.7$. The bonus is not cosmetic. Without it, an LM trained on text shorter than the acoustic hypothesis penalizes each emitted token, and the decoder deletes about 12% of reference words to avoid that penalty. The recalibration that introduced the bonus moved mass from deletions to insertions and lowered WER by 6–9 points on every set without changing a single weight (Section 7.2).

A greedy CTC decoder is available as a fast path. It uses no LM and no bonus; it is the mode in which the acoustic model alone is measured. Greedy and beam results are therefore not interchangeable and are labeled separately throughout.

The LM is a BPE trigram with stupid backoff 0.4, stored as a sparse CSR binary of int16-quantized log-probabilities. The shipped 0.8.1 LM (arm A3 in E-031) was built from a frozen training-side corpus, keeps all bigrams while requiring count at least two for trigrams, and repeats term-containing sentences three times. Section 7.3 isolates what that change did and what it cost.

### 3.5 Runtime, VAD and packaging

At inference a Silero VAD [Silero Team, 2021] runs first. The no-speech gate uses the fraction of VAD windows above a 0.1 speech-probability threshold; the fraction must exceed 0.10. If at least two speech runs are found, the runtime transcribes each span separately; a single run is left intact. Spans shorter than 560 samples or longer than 30 s are rejected rather than silently cropped. Segmentation is not diarization.

The acoustic graph is exported to ONNX opset 17 and dynamically quantized to int8. The Python runtime loads ONNX Runtime sessions, the binary LM and the mel filters once; the browser runtime loads the same files through ONNX Runtime Web with WASM SIMD. The browser path implements its own log-mel front end and beam decoder. Audio is processed in the tab and is not uploaded by the demo.

The released package contains seven files. The 20 MB ceiling is on the sum of these required assets, not on the browser's JavaScript, the Python environment, or a download-compressed archive. The shipped 0.8.1 package is 19,706,289 bytes, leaving 293,711 bytes of headroom. A 25 MB tier exists in the release validator but was not used.

Table 2: Data used by the released system. "Unique" counts distinct audio; "exposure" counts epoch-weighted repetitions. Spliced material reuses natural clips by construction; gold data are 50.2 unique minutes repeated $50\times$. Total training exposure is 589.55 h, of which 41.87 h is repeated gold. Test sets are never trained on, but T and S3 have informed development repeatedly (Section 9).

| Source | License | Unique | Clips | Role |
|---|---|---|---|---|
| Common Voice IT 27 | CC0 | 167.79 h | 113,118 | train |
| MLS Italian | CC-BY 4.0 | 169.89 h | 40,953 | train |
| LibriSpeech EN | CC-BY 4.0 | 100.00 h | 28,370 | train |
| Spliced IT+EN | derived | 110.00 h | — | train |
| R-S1 + R-S2 gold | recorded, consent | 50.2 min | 1,263 | train ($50\times$) |
| MUSAN + room tone | CC-BY 4.0 / own | 217 clips | 217 | noise aug. |
| MLS-IT + LS-EN dev | CC-BY 4.0 | 10.48 h | 3,939 | selection |
| T-600 (S1–S3) | recorded, consent | 23.2 min | 600 | test (reused) |
| T-S3 | recorded, consent | 7.7 min | 200 | test (reused) |
| FLEURS-IT test | CC-BY 4.0 | 2.74 h | 697 | test |
| FLEURS-EN test | CC-BY 4.0 | 1.39 h | 525 | test |
| CV-IT test | CC0 | 25.81 h | 14,643 | test |
| Silence/noise/music | mixed | 76.2 min | 457 | non-speech |

# 4 Data

## 4.1 Open corpora

Training uses three open human-transcribed sources, summarized with the evaluation sets in Table 2. Common Voice IT 27 [Ardila et al., 2020] contributes 167.79 manifest hours (113,118 clips), MLS Italian [Pratap et al., 2020] 169.89 h (40,953 clips), and LibriSpeech train-clean-100 English [Panayotov et al., 2015] 100.00 h (28,370 clips). The natural mixture is 437.68 unique hours, 77/23 Italian/English by audio duration. It is not the design's shorthand 70/30: reaching 70/30 would either discard more than 100 h of Italian or repeat English.

The manifest builder applies deterministic duration sampling (1–30 s), duration and character filters, a digit-transcript filter, and a speaking-rate filter. Evaluation manifests and their normalized-text hashes are built before training, so the overlap check is not retrofitted. The filtering is why the reported FLEURS populations (697 Italian, 525 English) are smaller than the upstream test splits.

## 4.2 Recorded mixed speech

The only source of genuinely mixed Italian–English audio is a small recorded corpus made for this project. A generator produced a pool of 3,137 sentences in eight categories (control Italian, control English, single-word insertions, phrases, brands, acronyms, Italianized verbs and switch-point sentences). A scripted test set T contains 800 sentences, 200 per speaker; 600 were recorded by S1, S2 and S3 (23.2 minutes total) and the fourth block remains unrecorded. A separate training script R was recorded by S1 (641 takes) and S2 (622 valid takes), 50.2 unique minutes in total. An anchor set A has each recorded speaker read 60 T sentences; it is a script/channel control, not an independent test.

All recordings are 48 kHz mono, converted to 16 kHz for training and evaluation. Every take is bound to a manifest row with text, speaker, category, duration and file hash. The scripts were reviewed by hand: 1,464 lines were read, 24 lines in the unrecorded S4 block were corrected, and 13 recorded R lines with article errors were left untouched because the audio contains the error and rewriting the text would desynchronize audio and transcript. No recorded row was modified. There are no category violations, no duplicates and no near-duplicates above trigram Jaccard 0.8 within the scripts.

## 4.3 Splicing and noise augmentation

Two augmentation strategies expand the effective training signal without new recordings. Utterance-level splicing concatenates an Italian clip and an English clip into one training example, producing 110 h of exposure; this teaches the model to switch inside a sequence without inventing new speech. Splicing reuses the same source sentences, so it is a training-signal choice, not new data.

Noise augmentation replaces about half of the Common Voice Italian material (83.6 h) with noisy versions. The clean/noisy split is derived from a hash of the clip ID, and each noisy clip has a fixed SNR drawn once in the 10–

30 dB range. Noise comes from a pool of 217 clips: MUSAN noise and music [Snyder et al., 2015] plus a room-tone recording. Because the SNR is fixed per clip, the augmentation is deterministic across epochs and does not silently change the difficulty of the training set between runs. The pool is used in training; the separate held-out room in Section 7.4 is not.

### 4.4 Development and test sets

Checkpoint selection uses a 3,939-clip dev set: 1,248 MLS-IT utterances and 2,691 LibriSpeech-EN utterances, 10.48 h in total. The selection metric is the unweighted mean of the two corpus WERs, not a pooled WER. This choice is deliberate—it prevents the larger English partition from dominating—but it also means that a dev improvement need not correspond to a mixed-set improvement. The released model's dev number is slightly worse than its predecessor's (Section 5.3); the product readout, not the dev number, decided adoption.

The product readouts use T-600 (600 scripted mixed utterances, 3,488 reference words and 1,043 annotated English positions), its S3 subset (200 utterances, 1,174 words, 355 English positions), filtered FLEURS-IT and FLEURS-EN test sets, the full 14,643-clip Common Voice IT test set where historical numbers exist, and a 457-clip non-speech set. T is the only mixed test set; it is scripted read speech, not spontaneous conversation.

### 4.5 Leakage controls and term provenance

The project treats leakage as a property to be audited rather than asserted. Test and dev manifests were hashed before training. T, R and the sentence pool are disjoint beyond exact script reuse; the anchor A repeats 60 T sentences by design. A source-level audit hashed 2,209 recorded wav files: no hash appears in two sets, every manifest path resolves, and the train/dev/test ID sets inside Common Voice, MLS and LibriSpeech are disjoint.

A text near-duplicate audit over 247,510 documents found 8,205 pairs above trigram Jaccard 0.8 after correcting the MinHash implementation. All are explained: spliced training data reusing LibriSpeech and MLS sentences by construction, Common Voice prompt reuse across speakers, or the project's own script/manifest pairs. Zero pairs involve T or FLEURS. A raw-audio pass over 287,429 loose files (12.8 GB) found no cross-source byte collisions; the only repeated hashes are 120 byte-identical silence clips (one signal repeated, relevant when interpreting a silence probe) and one room-tone recording stored under two names. The held-out room tone used in Section 7.4 is absent from the training noise pool.

Term provenance required a correction that matters for how the rare-term result is read. T contains 655 English terms. Against the acoustic source text including LibriSpeech train-clean-100 and the term addenda, they split into 475 natural, 145 gold and 35 terms that were absent from the 0.7.0 training text. The historical rare-term readout is defined on a fixed set of 47 utterances and 81 annotated span tokens so that earlier experiments remain comparable. It is a fixed metric, not a claim that the shipped 0.8.1 has never seen the vocabulary: all 35 terms were introduced by the E-015/E-028 addenda, so 0.8.1 has seen them. The earlier "44 never-seen terms" label was too wide because it omitted LibriSpeech; nine of those terms are in LibriSpeech train-clean-100.

## 5 Training

Experiments are referred to by their retained repository IDs (E-000–E-041); Appendix B indexes all of them.

### 5.1 Hardware, budget and cost

All training ran on an Apple M5 MacBook Pro with 16 GB of unified memory, using PyTorch 2.14.1 with MPS and bf16 autocast; CTC loss is computed in fp32. Long runs used AC power and `caffeinate -i`. The external monetary cost was 0 USD. This is not a claim that the work was free: it consumed author time and a laptop, and the largest runs took most of a working day. A feasibility probe (E-000) measured 394 ms per synthetic step with bf16 on MPS, 812 audio seconds per wall second, which made the project viable before any real data were trained.

### 5.2 Recipe

The shared recipe is AdamW with betas $(0.9, 0.98)$, $\epsilon = 10^{-8}$ and weight decay 0.01, a 500-step warm-up, cosine decay to 5% of peak, gradient clipping at 1.0, and batches capped at 192 audio-seconds or 32 clips. Inputs are truncated to 30 s. Augmentation is SpecAugment [Park et al., 2019] plus tempo stretch; the first full fine-tune (E-005) had an epoch counter bug that repeated the same augmentation view across epochs, which was fixed afterwards. Checkpoints are written every 10–20 minutes and selected by dev macro WER. Seed 0 is used for the released lineage.

Table 3: Training lineage. Dev macro WER is the checkpoint-selection metric on 3,939 MLS-IT/LS-EN clips. "Release" marks the first shipped version whose acoustic weights come from that arm. The E-024 dev minimum conflicts with the release label (see Appendix C).

| Arm | Initialization | Steps | Change | Dev | Release |
|---|---|---|---|---|---|
| E-004 | converted Whisper | 5,871 | frozen encoder, linear head | 75.77 | — |
| E-005 | E-004 | 72,592 | full fine-tune, 437.7 h | 33.77 | — |
| E-006 | E-005 | 36,296 | +2 transformer blocks | 31.27 | — |
| E-014 | E-006 | 22,494 | +110 h spliced IT/EN | 30.86 | — |
| E-017 | E-014 | 26,442 | +S1+S2 gold, 50× | 30.98 | 0.5.0 |
| E-024 | E-014 | 26,442 | +noise augmentation | 30.84 | 0.7.0 |
| E-028 | E-024 | 13,283 | +S2 term addendum; gentler LRs | 31.01 | 0.8.0/0.8.1 |





Figure 2: Dev macro WER from the retained training logs. (a) The from-scratch full fine-tune E-005: the first dev point is 57.3% at step 2,000; the curve reaches 33.77% at 72,592 steps. (b) Continuation arms. E-028 starts at the 0.7.0 dev level (30.81%), rises to 31.53% under the initial optimization shock, and returns to 31.01%—slightly worse than its parent. It was adopted on product readouts, not on dev.

### 5.3 Lineage

Table 3 and Figure 2 summarize the acoustic lineage. The frozen-encoder probe (E-004) established that the pretrained representation was useful but insufficient: a linear head on frozen features reached 75.77% dev WER. Full fine-tuning (E-005) dropped dev WER to 33.77% and beat Whisper-tiny on Common Voice dev by 10.9 points, but missed the pre-registered FLEURS-IT bar by 5.3 points. Adding two transformer blocks (E-006) took dev WER to 31.27%; adding spliced Italian–English material (E-014) took it to 30.86%.

The gold-data arms are the product story. E-017 added S1 and S2's recorded mixed speech, oversampled 50×, and improved T-S3—a speaker with no training audio—by an amount comparable to the trained speakers (6.1 points, against 4.5 and 6.6), which argued against pure speaker adaptation. E-024 reran the recipe from E-014 with the same gold data and noise augmentation, released as 0.7.0. E-028 then added the S2 term addendum and lowered the learning rates (encoder $10^{-5}$, head $10^{-4}$) for one epoch, 13,283 steps; it is the acoustic model in 0.8.0 and 0.8.1.

### 5.4 Selection, gates and the dev/product gap

Adoption decisions were made against written plans; the later arms used pre-registered gates. The E-028 arm, for example, had six gates: rare aligned ETA at least 30%, T-600 ETA at least 53.7%, T-600 WER at most 25.7%, at least 431 of 817 natural-term occurrences, FLEURS-IT/EN not worse by more than 0.5 points with a CI excluding zero, and a checkpoint selected by dev rather than the step-20 baseline. The fp32 candidate passed all six; the first int8

Table 4: Main comparison. Moth numbers are the shipped 0.8.1 int8 graph with the A3 LM and decoder 12/10/0.55/2.7. Whisper uses forced-Italian beam 5 on T and automatic-language beam 5 on FLEURS (its best FLEURS variant); Whistle is forced Italian; Parakeet is int8 greedy. T-S3 baselines were not measured for Parakeet. Artifact sizes are declared bytes and are not like-for-like (Section 6).

| System | T-600 WER | T-600 ETA | T-S3 WER | T-S3 ETA | FLEURS-IT | Size |
|---|---|---|---|---|---|---|
| Whisper-tiny | 50.72 | 36.05 | 46.51 | 38.03 | 27.42 | 148.7 MB |
| Whistle | 29.42 | 49.28 | 28.36 | 52.11 | 11.85 | 16.9 MB |
| Parakeet TDT 0.6B | 10.98 | 83.60 | — | — | 3.65 | 670.5 MB |
| **Moth 0.8.1** | 24.08 | 55.23 | 24.96 | 51.27 | 20.16 | 19.7 MB |

export missed the rare gate by one aligned occurrence, and the published 0.8.0 decoder arm by two (23/81 against the required 25/81). That exception was documented at publication rather than redefined after the fact.

The dev metric and the product metric are not the same quantity. E-028's dev WER is 0.20 points worse than 0.7.0, while its T-600 and T-S3 results are better. The project kept the dev set as a selection tool and treated the product readout as the decision, but this is a real weakness: a model that improves the target behavior can look worse on a proxy that weights pure Italian and pure English read speech. Section 9 returns to this point.

## 6 Evaluation Protocol

**Word error rate.** WER is computed after normalization, by minimum edit distance over words, from summed substitutions, deletions and insertions divided by reference words. Corpus WER is not the mean of per-utterance WERs. The T-600 reference has 3,488 words; a one-word change moves corpus WER by about 0.03 pp, so small point differences should not be read as precise.

**English-term accuracy (ETA).** ETA is the fraction of annotated English-origin reference positions reproduced exactly after alignment. It is a strict exact-match metric, not semantic equivalence. On T-600 there are 1,043 annotated positions. The rare-term readout uses 81 annotated span tokens in the 47 rare-bearing utterances (47 target tokens plus 34 co-occurring annotated tokens), and a separate presence count over the 47 utterances. Presence and aligned ETA answer different questions and are reported separately. The 81 tokens are not 81 independent terms.

**Confidence intervals.** Unless stated otherwise, intervals are 95% percentile intervals from 1,000 paired utterance-level bootstrap resamples with seed 0 [Efron and Tibshirani, 1993]. The resampling unit is the utterance, not the speaker, seed or recording session. A CI that includes zero is called a *tie*; this means no detected difference at this sample size, not equivalence and not non-inferiority. Intervals for per-speaker results are within-speaker intervals and do not estimate between-speaker variance. The multi-seed result in Section 7.6 is a descriptive range over four replicates, not a variance estimate.

**Baselines.** Whisper-tiny [Radford et al., 2023] is evaluated in fp32 on CPU, padded to 30 s, with no hotwords. We report forced-Italian beam-5 on T (the better language setting for mixed speech) and automatic-language beam-5 on FLEURS (the best measured variant). Whistle [Cactus Compute, 2024] is evaluated with its native engine, forced Italian, no hotwords; the engine's exact kernel precision and beam are not recorded in the baseline metadata. Parakeet TDT 0.6B v3 is evaluated as an int8 transducer through NeMo/sherpa-onnx with greedy search and four threads [NVIDIA, 2024]. These are engine comparisons, not matched-compute or matched-pretraining experiments.

**Artifact sizes.** Sizes are declared artifact bytes, not parameter counts and not full runtime footprints. For Moth the number is the sum of the seven required release files. For the baselines it is the serialized model artifact recorded in the baseline metadata: 148.7 MB of fp32 parameter storage for Whisper-tiny, 16.9 MB for Whistle's compressed engine file and 670.5 MB for Parakeet's serialized export. These quantities exclude different things (tokenizer, VAD, runtime libraries, compression), so Figure 3 is a size–accuracy sketch, not a controlled efficiency benchmark.





Figure 3: WER against declared artifact size, on a logarithmic axis. Left: the scripted mixed test T-600. Right: filtered FLEURS-IT. The dashed line marks the 20 MB ceiling. At 19.7 MB Moth has the best mixed-set WER in this comparison: Whisper and Parakeet are 7.5× and 34× larger, and Whistle is 2.8 MB smaller but 5.3 pp worse on the mixed set. The FLEURS panel shows the cost of specialization: Moth beats Whisper-tiny on Italian read speech but is far behind Whistle and Parakeet, and its pure-English FLEURS WER is 49.81% (not shown).

## 7 Results

### 7.1 Main results

Table 4 and Figure 3 give the headline comparison. On the mixed scripted set, Moth reaches 24.08% WER and 55.23% ETA. It beats Whisper-tiny by 26.6 pp WER and 19.2 pp ETA, and Whistle by 5.3 pp WER and 6.0 pp ETA. Parakeet remains far better (10.98% WER, 83.60% ETA) at roughly 34 times the artifact size. On FLEURS-IT, Moth beats Whisper-tiny (20.16 vs 27.42) but is worse than Whistle (11.85) and Parakeet (3.65). On FLEURS-EN it is poor (49.81%) because the acoustic mixture is Italian-dominant and the English training material is audiobook speech, not the read FLEURS domain.

Two cautions apply to every row. First, the baselines may have seen FLEURS or its source material during pretraining; we cannot audit upstream contamination. Second, the T-600 aggregate is not a speaker-independent estimate. S1 and S2 contributed acoustic training audio (400 of 600 clips); S3 contributed none but shares S1's microphone family and has been inspected repeatedly. The per-voice breakdown in Section 7.6 is part of the result, not an appendix.

### 7.2 Decoder calibration

The largest single measured improvement on the mixed test came from decoding, not training. Figure 4 shows E-022: on unchanged E-017 weights, a wider beam, a stronger LM weight and a per-token bonus reduced T-600 WER from 32.77% to 25.92% and raised T-S3 from 35.43% to 26.66%. FLEURS-IT fell from 26.52% to 20.46%, crossing the Whisper-tiny bar that had blocked the project. All six sets improved with paired CIs excluding zero. The ETA gain was 9.8 points on T-600 and 12.1 on T-S3.

The mechanism was a length bias. The LM had been trained on text shorter than the acoustic hypotheses, so its per-token log-probability penalized every extra token. The decoder responded by deleting words. Adding a constant bonus per emitted token compensates the bias without changing the acoustic model or the LM. Deletions fell by about a third and insertions rose slightly; total errors fell. This is a calibration fix, not a modeling insight, and it cost zero bytes.

A second recalibration (E-030) moved the shipped decoder to LM weight 0.55 and bonus 2.7, selected on a 1,277-clip dev set, and recovered most of the int8 gap of the E-028 acoustic arm. The shipped 0.8.1 decoder is 12/10/0.55/2.7. The fact that two rounds of decoder tuning produced more than any single acoustic arm is a statement about this model at this scale, not a general claim that decoding is more important than acoustics.





Figure 4: Decoder recalibration on unchanged acoustic weights (E-022). The shipped decode used beam 5, top-8, LM weight 0.2 and no token bonus; the recalibrated decode uses beam 12, top-10, LM weight 0.5 and a per-token bonus of 2.4. (a) WER drops on all six sets; every paired CI excludes zero. (b) ETA rises on all three T subsets. The mechanism is visible in the error mix: deletions fall from 12.2% to 8.3% of reference words and insertions rise from 0.8% to 1.3%. The artifact and the int8 graph are byte-identical between the two decodes.





Figure 5: (a) Aligned rare-term ETA over the fixed 47-utterance / 81-token readout. (b) Exact-match accuracy by term group on T-600. Natural and gold are occurrence-level exact-match rates; rare is utterance-level presence. The 0.8.1 LM rebuild raises rare-term presence from 23.4% to 51.1% while giving back 9 natural-term occurrences; the gold group is essentially unchanged. The rare group is 47 utterance-level checks, not 47 independent terms.

### 7.3 Rare English terms

The intended use case includes short English terms that are rare in the training text. The project therefore tracks a fixed rare-term readout: 47 T utterances that contain at least one of the terms absent from the 0.7.0 acoustic training text. Table 5 and Figure 5 show the progression across releases.

The 0.8.1 gain is decode-side. The acoustic graph is byte-identical to 0.8.0. The LM was rebuilt from a frozen training-side corpus with three simultaneous changes: all bigrams were kept, trigrams still required count at least two,

Table 5: Rare-term readout and term groups for the three published releases. Aligned ETA and presence use the fixed historical definition; provenance was corrected after the 0.8.1 release (Section 4.5). "16-term" is a separate regression set.

| Release | Aligned ETA | Presence | Rare WER | Natural | Gold | 16-term |
|---|---|---|---|---|---|---|
| 0.7.0 | 22.2% (18/81) | 8/47 | 40.2% | 441/817 | 130/179 | 22/27 |
| 0.8.0 | 28.4% (23/81) | 11/47 | 35.9% | 436/817 | 126/179 | 19/27 |
| 0.8.1 | **46.9% (38/81)** | **24/47** | **28.2%** | 432/817 | 127/179 | 19/27 |

Table 6: Noise WER (%) for the 0.6.0→0.7.0 comparison. Each condition uses the same 100 S3 clips and 589 reference words. The shared-pool estimate is potentially optimistic because all pool clips were used in training; the held-out room is one 38 s take, not a room population.

| | Shared pool | | | Held-out room | | |
|---|---|---|---|---|---|---|
| SNR | 0.6.0 | 0.7.0 | Δ | 0.6.0 | 0.7.0 | Δ |
| clean | 22.24 | 23.94 | +1.70 | 22.24 | 23.94 | +1.70 |
| 30 dB | 25.98 | 23.26 | −2.72 | 28.52 | 24.62 | −3.90 |
| 20 dB | 27.50 | 26.83 | −0.68 | 38.71 | 31.92 | −6.79 |
| 15 dB | 33.62 | 27.33 | −6.28 | 47.71 | 36.50 | −11.21 |
| 10 dB | 44.82 | 33.28 | −11.54 | 63.33 | 44.99 | −18.34 |
| 5 dB | 50.93 | 41.26 | −9.68 | 81.32 | 66.72 | −14.60 |

and term-containing sentences were repeated three times. The binary grew to 5,381,992 bytes, still inside the package budget. Aligned rare ETA rose from 28.4% to 46.9% (23/81 to 38/81, +18.5 pp, CI $[+9.6, +31.0]$), presence from 11/47 to 24/47, and rare WER from 35.9% to 28.2%. T-600 as a whole improved by 0.63 pp WER and 1.06 pp ETA, both with CIs excluding zero; T-S3 and FLEURS were ties.

The cost is visible in the same table: natural-term occurrences fell from 436 to 432 (and from 441 at 0.7.0), and the 16-term regression set stayed at 19/27 after dropping from 22/27 at 0.7.0. The LM change is therefore not a free win; it trades a small amount of broad vocabulary coverage for a large gain on the targeted terms. The three build changes are confounded: the experiment does not isolate corpus refresh, pruning and term weighting. A later attempt to spend the remaining 293,711 bytes on 73,427 additional count-1 trigrams (E-035) improved dev macro WER by 0.06 pp but produced a tie on every product metric and was rejected.

The rare-term metric also needed a provenance correction. After including LibriSpeech train-clean-100, 35 terms across 37 T utterances—not 44 across 47—were genuinely absent from the 0.7.0 text, and all 35 were introduced by the term addenda that 0.8.1 trained on. The historical 47/81 readout is retained for comparability, but it is no longer evidence that the shipped model has never seen the vocabulary. This distinction does not change any measured value; it changes the sentence that the values support.

### 7.4 Noise robustness

Noise augmentation (E-024) is the intervention with the clearest practical effect. Figure 6 and Table 6 compare 0.6.0 and 0.7.0 on the same 100 S3 clips. On the shared pool, the gain is significant at 15, 10 and 5 dB: $-6.28$, $-11.54$ and $-9.68$ points. At 30 and 20 dB the differences are ties, and the clean condition is 1.70 points worse (CI includes zero). On a room recorded after training—and confirmed by the audio audit to be absent from the training noise pool—the relative gain is larger at every noisy condition ($-3.90$ to $-18.34$ points). The room is also harder in absolute terms: 36.50% WER at 15 dB against 27.33% on the shared pool. Both facts belong together; quoting only the larger gain would overstate absolute robustness.

The caveats are substantive. The shared-pool estimate reuses noise clips that were in training, so it may be optimistic. The held-out room is one 38 s take; its conditions and utterances are correlated, and it is not a sample of rooms. SNR is RMS-relative, not active-speech SNR or a measured acoustic condition. The ETA intervals all include zero. The noise test therefore supports a claim about this augmentation recipe on this protocol, not a general far-field robustness claim.





Figure 6: Noise curves for 0.6.0 (E-017 weights) and 0.7.0 (E-024 weights) on the first 100 S3 clips. (a) Shared noise pool, used in training. (b) Room recorded after training and absent from the training pool. Annotations show significant WER deltas in percentage points; "n.s." marks conditions whose paired CI includes zero. The new room is harsher in absolute terms: at 15 dB it is 36.50% WER for 0.7.0, against 27.33% on the shared pool.

### 7.5 Quantization and deployment

The shipped graph is dynamically quantized int8. E-037 measured what that costs by decoding the same checkpoint through the fp32 export and the int8 graph with the same A3 LM and decoder (Figure 7b). On the 3,939-clip dev set, macro WER rises from 22.8596% to 23.0170% (+0.1574 pp, CI $[+0.0539, +0.2664]$). On T-600 the point estimate is +0.4874 pp (CI $[-0.0290, +0.9963]$, a tie) with ETA $-0.8629$ pp; T-S3 is a tie at +0.4259 pp. FLEURS-EN is significantly worse (+0.4459 pp, CI $[+0.0087, +0.8652]$), while FLEURS-IT is slightly better ($-0.1559$ pp, tie). Rare-term hits are unchanged at 38/81, and the noise word count is slightly better under int8. The cost is real, small, and non-uniform. The fp32 package would be 54,164,659 bytes, so int8 is the only deployable format; the measurement documents the price of the ceiling rather than justifying a change.

The browser path adds a second, different cost. E-041 decoded T-600 through the shipped bundle in headless Chromium with ONNX Runtime Web: 24.7993% WER and 54.3624% ETA, against 24.0826% and 55.2253% from the Python runner. The WER difference is +0.7167 pp with CI $[0.0000, +1.4723]$ (touching zero), ETA $-0.8629$ pp (tie), and 151 of 600 hypotheses differ. The penalty is not uniform: S1 +0.26 pp WER, S2 +0.35 pp, S3 +1.53 pp and $-2.82$ pp ETA. The never-trained voice pays five to six times the WER cost of the trained voices.

This is a deployment property, not a model-quality claim. The browser uses a different log-mel implementation and different WASM kernels; the decoder itself is exact on identical logits, and the runtime acceptance suite passes 4/4 configurations (isolated 1/4 threads and non-isolated). Median RTFx was 42.3 in the first browser run (range 25.5–53.4) and 44.87 on the post-merge rerun that pinned the release (range 24.89–59.96), on a desktop with 10 hardware threads; the two runs produced identical hypotheses. The 0.8.1 acceptance fixture measured medians of 46.69, 46.23, 25.10 and 24.83 across four configurations. These are desktop measurements, not phone, Safari or end-user latency claims.

### 7.6 Speaker and seed variability

Figure 8 shows the per-voice result. Pooled T-600 is 24.08% WER and 55.23% ETA, but S1 is 20.98% / 63.28%, S2 is 26.32% / 51.56% and S3 is 24.96% / 51.27%. The voices span 5.34 pp WER and 12.02 pp ETA. The never-trained S3 is not the worst voice; S2 is. With three voices, between-speaker variance is not estimable and a speaker-cluster interval cannot be formed. The per-voice intervals overlap, so the ordering is descriptive. The correct sentence is: on the three available voices the model ranges from 20.98% to 26.32% WER and from 51.27% to 63.28% ETA; the pooled 24.08% / 55.23% is an average over voices.

Training-seed variability was measured only for the rejected E-036 recipe, not for the released 0.8.1 lineage. Four seeds of each of two conservative arms produced T-600 means of 24.0539% and 24.2116%, with within-arm ranges of 0.4587 pp and 0.1434 pp (Figure 9). The gap between the two arms (0.1577 pp) is smaller than the frozen arm's





Figure 7: (a) Composition of the shipped 0.8.1 package: 19.71 MB, with 293,711 bytes of headroom under the 20 MB ceiling. (b) Paired INT8−fp32 WER difference with the same E-028 checkpoint, A3 LM and decoder. Positive means INT8 is worse. Filled markers are intervals that exclude zero. The cost is small on dev, larger on T-600 and FLEURS-EN, and slightly negative on FLEURS-IT: it is not a uniform shift.

seed range, so the arm ordering carried no information. The same runs show that the rare-term shortfall reproduces (no replicate reaches 42/81) while the silence hallucination does not (four of eight replicates emit nothing on all 120 silence clips). The released model's single seed is therefore a limitation, not an estimated variance: 0.46 pp is the scale at which small acoustic differences should be treated as noise in this recipe family.

## 8 Negative Results

Table 7 lists the rejected interventions. Three clusters are worth reading in detail.

**Data and capacity.** Adding 200 h of English (E-012) improved English read speech but moved the model away from Italian and made T-600 5.16 points worse; the English-term accuracy did not move. A larger BPE vocabulary (E-013) shortened the English terms but did not teach the acoustic model to emit them, and Italian regressed. The first gold-term addendum (E-015) was too aggressive: rare terms rose from 8/47 to 11/47 with a CI including zero, natural terms fell from 439 to 423, FLEURS regressed, and dev jumped from 30.81% to 33.64%. These results are consistent with a capacity and mixture problem that a single lever cannot fix.

**Regularization, quantization and distillation.** Intermediate CTC (E-033) learned its auxiliary objective (loss 66.9 to 0.72 over 394,625 parameters) but produced no dev gain: +0.0249 pp with CI $[-0.0998, +0.1557]$. Quantization-aware training (E-029) closed the int8–fp32 dev gap in a short probe but failed the product gates on T-600, rare terms and natural terms. The conservative fine-tune (E-036) is the most instructive negative. It protected WER—dev and product WER were ties—but did not reach the rare-term target (39/81 and 41/81 against 42/81), and at seed 0 it emitted the token "x" on all 120 silence clips. A four-seed replication (E-040) then showed that the rare shortfall is a property of the recipe while the silence failure is a seed draw: four of eight replicates were clean. The lesson is not that the recipe was good; it is that a single-seed negative result would have supported the wrong generalization in both directions.

**Language model and decode-time bias.** A larger unpruned LM (E-023) was worth about 0.65 points on dev but produced a 26.63 MB package, over the ceiling. A 12 MB LM with more trigram coverage (E-034) was also worth about 0.6 points on dev and also did not fit. The budgeted variant (E-035) fit at 19,999,997 bytes and improved dev





Figure 8: Per-voice results for the shipped 0.8.1, with within-speaker 95% bootstrap intervals. Bars are the Python ONNX runner; diamonds are the browser path. S1 and S2 contributed acoustic training audio; S3 did not. The pooled number is an average over these three voices, not a speaker-independent estimate.





Figure 9: (a) T-600 WER of the rejected E-036 conservative fine-tune, four seeds per arm. The between-seed range of the frozen arm (0.4587 pp) is larger than the gap between arms (0.1577 pp). (b) Rare-term aligned hits for the same runs. No replicate reaches the pre-registered 42/81 target; the shortfall is a recipe property. The silence hallucination of E-036 did not reproduce (Section 8).

by 0.06 pp, but the product readout was a tie on all primary metrics; it was rejected rather than shipped because a tie does not justify spending the last 3 bytes of margin. Decode-time contextual bias with a 24-term glossary (E-027) left the rare terms exactly unchanged and was rejected. The successful LM change (E-031) was not "more LM": it was a different corpus treatment and term weighting inside the existing budget.

**What the pattern does and does not show.** The negative results are not a controlled comparison of architecture families. E-019 used a different model, data exposure and update budget; E-029 was a short probe; E-033 changed one regularization weight; E-036 changed several recipe details at once. The defensible pattern is narrower: in this project, at this scale and under this byte budget, small dev gains repeatedly failed to survive the product readout, and decode-side changes produced larger measured gains than the acoustic interventions that were tried. That is a statement about this development record, not a universal ranking of techniques.

Table 7: Rejected interventions. Each row has a written plan and a retained result; the outcome column reports the measured value that decided the rejection. These are not equal-budget controlled comparisons, and several are single-seed probes.

| ID | Intervention | Measured outcome | Decision |
|---|---|---|---|
| E-012 | $+200$ h LibriSpeech EN | FLEURS-EN $-5.4$ points, but T $+5.16$ worse and ETA flat | rejected |
| E-013 | BPE 4,096 | FLEURS-IT $+1.9$ worse, T flat, ETA unchanged, $+1.2$ M params | rejected |
| E-015 | first gold-term addendum | rare $8 \rightarrow 11/47$, CI includes zero; FLEURS worse; dev 33.64 | rejected |
| E-019 | Whistle LoRA probe | S3 $+2.30$ WER; FLEURS/CV significantly worse; 28 MB export | rejected |
| E-023 | full (unpruned) LM | dev $-0.65$ but 12.31 MB binary, 26.63 MB package | rejected |
| E-027 | decode-time contextual bias | rare ETA 22.22%→22.22%; T-600 +0.10 (tie) | rejected |
| E-029 | quantization-aware training | best probe T-600 25.34 vs 25.14 gate | rejected |
| E-032 | targeted S1 term addendum | rare up, but T-S3, FLEURS and natural terms down; 6 gates failed | rejected |
| E-033 | intermediate CTC (weight 0.3) | dev $+0.0249$ pp, CI $[-0.0998, +0.1557]$ | rejected |
| E-034 | larger n-gram LM | dev $-0.6$ pp, but 12.0–12.3 MB binary; package 26.4 MB | rejected |
| E-035 | budgeted count-1 trigrams | dev $-0.0645$ pp; product tie on all primary metrics | rejected |
| E-036 | conservative KD fine-tune | rare 39/81 and 41/81 vs 42 target; T-S3 ETA $-1.41$ | rejected |
| E-040 | four-seed replication | arm gap below seed noise; silence bimodal | no adoption |

## 9 Validity and Discussion

**What the evidence supports.** The evidence supports the following statements. A configured 11.58 M-parameter CTC model and a 19.71 MB package were built, trained, exported and run on CPU and in Chromium. On scripted mixed speech from three known voices, the released model reaches 24.08% WER and 55.23% ETA, with a per-voice range of 20.98–26.32% WER. It beats the measured Whisper-tiny and Whistle baselines on the mixed set and beats Whisper-tiny on FLEURS-IT, while remaining far behind Parakeet. Noise augmentation improved WER at 15, 10 and 5 dB on a paired protocol, including a room recorded after training. The int8 graph costs about 0.16 pp on dev and the browser path about 0.72 pp on T-600; both are measured, not assumed. The rare-term LM change raised aligned ETA from 28.4% to 46.9% at a cost of nine natural-term occurrences.

**Construct validity.** The core construct is "Italian speech with English words mixed in". T is scripted read speech, not spontaneous conversation. It was generated from a sentence pool, reviewed by hand and recorded in a quiet room. It contains controlled categories (single words, phrases, brands, acronyms, Italianized verbs, switches) but not the disfluencies, repairs, overlapped speech or topic drift of natural code-switching. ETA measures exact reproduction of annotated English-origin positions, not whether the term was understood. The 47-utterance rare subset is a diagnostic, not a representative sample of Italian technical vocabulary.

**Internal validity.** T and S3 have informed development repeatedly. T is not an untouched final test, and S3 is not an unseen speaker: it contributed no acoustic training audio but shares S1's microphone family and has been inspected across many experiments. The anchor A repeats 60 T sentences, so it cannot serve as independent dev. Checkpoint and decoder selection used dev and, for later arms, product readouts; the project pre-registered gates, but the sequence of experiments is adaptive. The released acoustic model has one training seed. The multi-seed evidence comes from a rejected recipe, not from the release lineage.

**External validity.** There are three voices, all recorded for this project, and no fourth voice exists in the repository. The per-voice range is descriptive and cannot be extrapolated to a speaker population. There is no spontaneous mixed-dev and no new-voice holdout; the owner decided not to record more data. The browser measurements are desktop

Chromium with WASM threads, not mobile browsers, Safari, live microphone capture or end-user latency. The noise evidence is one held-out room and synthetic RMS-relative SNR, not a corpus of real noisy environments.

**Statistical validity.** The bootstrap resamples utterances, not speakers, seeds or sessions. The intervals are therefore within-corpus intervals; they do not license inference to new speakers or new rooms. "Tie" means "the interval includes zero at this sample size", not equivalence. Multiple comparisons were not corrected; the paper reports the pre-registered primary readouts and labels exploratory ones. Several effects are small enough that seed variation of the order of 0.46 pp could matter. The 81 rare span tokens are correlated within 47 utterances, and the 47 utterances are not 47 independent terms.

**Upstream contamination.** Whisper-tiny, Whistle and Parakeet were pretrained on large, partly undisclosed corpora. FLEURS and Common Voice are public and may overlap with pretraining data. We can audit local audio and text leakage, and we did, but we cannot audit upstream pretraining. The FLEURS comparisons should be read with that uncertainty.

**Practical lessons.** Four lessons generalize beyond this model. (1) Calibrate the decoder before judging the acoustic model: a length-biased LM can hide several points of WER, and the fix costs no bytes. (2) Under a hard byte budget, LM corpus composition and weighting can be a better use of the last few hundred kilobytes than another acoustic block or a larger vocabulary. (3) A dev metric that is not the product metric can rank models backwards; report both and decide on the product readout. (4) Small gains need multiple seeds and per-voice reporting; a single-seed tie or win is weak evidence, and a single-seed hallucination can be a draw rather than a recipe property.

**Ethics, licenses and privacy.** The code is Apache-2.0; the initial encoder weights are MIT; the data licenses are recorded in the release NOTICE. Recorded speakers consented to the use of their audio for model development. The browser demo processes audio locally and does not upload it. The model is intended for dictation and note-taking, not for surveillance, speaker identification or medical/legal transcription. It has no diarization and no word timestamps, and it should not be used on speech from people who did not consent to being recorded.

## 10 Conclusion

Moth is a 19.71 MB Italian–English code-switching recognizer built from a pretrained Whisper-tiny encoder, two additional transformer blocks and a linear CTC head over a shared vocabulary. It reaches 24.08% WER and 55.23% English-term accuracy on a 600-utterance scripted mixed test set, 20.16% WER on filtered FLEURS-IT, and runs at a median $42\times$ real time in headless Chromium on a desktop. The paper documents the full path to that artifact: 41 experiments, twelve rejected interventions, two decoder recalibrations, a noise-augmentation recipe, an LM rebuild that closed the rare-term gap, and a measured account of what int8 and the browser cost.

The result is deliberately bounded. The code-switching evidence is scripted read speech from three known voices; the public FLEURS numbers are read speech from other speakers. There is no spontaneous code-switching test, no unseen speaker in the mixed test and no speaker-cluster interval. The released acoustic model has one seed. Those are not minor caveats to be buried in an appendix; they define what the headline numbers mean. Within that boundary, the system is a useful small model, and the development record is a concrete example of how much of the outcome was decided by measurement discipline—decoder calibration, LM data treatment, pre-registered gates and negative-result replication—rather than by adding parameters.

**Artifacts.** The released model and demo are available at `https://huggingface.co/semantique-team/moth-stt`. The repository retains the experiment ledgers, per-utterance hypotheses, comparison JSON, release records and the scripts that generate every figure in this paper. Checkpoints, raw audio and mel shards are not versioned; the paper and the retained artifacts distinguish what can be re-scored from what can be retrained.

## Acknowledgements

We thank the three speakers who recorded the T and R sets and consented to their use for model development, and the maintainers of Whisper, FLEURS, Common Voice, MLS, LibriSpeech, MUSAN, Silero VAD and ONNX Runtime. No external funding was used; all training ran on the author's laptop.

## References


Sunayana Sitaram, Khyathi Raghavi Chandu, Sai Krishna Rallabandi, and Alan W. Black. A survey of code-switched speech and language processing. *arXiv preprint arXiv:1904.00784*, 2019.

Dau-Cheng Lyu, Tien-Ping Tan, Eng-Siong Chng, and Haizhou Li. SEAME: A Mandarin-English code-switching speech corpus in south-east asia. In *Interspeech*, 2010.

Holy Lovenia, Samuel Cahyawijaya, Genta Winata, Peng Xu, Yan Xu, Zihan Liu, Rita Frieske, Tiezheng Yu, Wenliang Dai, Elham J. Barezi, Qifeng Chen, Xiaojuan Ma, Bertram Shi, and Pascale Fung. ASCEND: A spontaneous Chinese-English dataset for code-switching in multi-turn conversation. In *Language Resources and Evaluation Conference (LREC)*, 2022.

Gustavo Aguilar, Sudipta Kar, and Thamar Solorio. LinCE: A centralized benchmark for linguistic code-switching evaluation. In *Language Resources and Evaluation Conference (LREC)*, 2020.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision. In *International Conference on Machine Learning (ICML)*, pages 28492–28518, 2023.

Sanchit Gandhi, Patrick von Platen, and Alexander M. Rush. Distil-whisper: Robust knowledge distillation via large-scale pseudo labelling. *arXiv preprint arXiv:2311.00430*, 2023.

Nat Jeffries, Evan King, Ke Kim, et al. Moonshine: Speech recognition for live transcription and voice commands. *arXiv preprint arXiv:2410.15608*, 2024.

Cactus Compute. Whistle: On-device speech recognition. `https://github.com/cactus-compute/cactus`, 2024.

NVIDIA. NVIDIA NeMo framework. `https://github.com/NVIDIA/NeMo`, 2024.

Benoit Jacob, Skirmantas Kligys, Bo Chen, Menglong Zhu, Matthew Tang, Andrew Howard, Hartwig Adam, and Dmitry Kalenichenko. Quantization and training of neural networks for efficient integer-arithmetic-only inference. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

Alex Graves, Santiago Fernández, Faustino Gomez, and Jürgen Schmidhuber. Connectionist temporal classification: Labelling unsegmented sequence data with recurrent neural networks. In *International Conference on Machine Learning (ICML)*, pages 369–376, 2006.

Alex Graves. Sequence transduction with recurrent neural networks. *arXiv preprint arXiv:1211.3711*, 2012.

Awni Hannun, Carl Case, Jared Casper, Bryan Catanzaro, Greg Diamos, Erich Elsen, et al. Deep speech: Scaling up end-to-end speech recognition. *arXiv preprint arXiv:1412.5567*, 2014.

Jaesong Lee and Shinji Watanabe. Intermediate loss regularization for CTC-based speech recognition. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2021.

Taku Kudo and John Richardson. SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *EMNLP: System Demonstrations*, 2018.

Silero Team. Silero VAD: Pre-trained enterprise-grade voice activity detector. `https://github.com/snakers4/silero-vad`, 2021.

Rosana Ardila, Megan Branson, Kelly Davis, Michael Henretty, Michael Kohler, Josh Meyer, et al. Common voice: A massively-multilingual speech corpus. In *Language Resources and Evaluation Conference (LREC)*, 2020.

Vineel Pratap, Qiantong Xu, Anuroop Sriram, Gabriel Synnaeve, and Ronan Collobert. MLS: A large-scale multilingual dataset for speech research. In *Interspeech*, 2020.

Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. LibriSpeech: An ASR corpus based on public domain audio books. In *IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, 2015.

David Snyder, Guoguo Chen, and Daniel Povey. MUSAN: A music, speech, and noise corpus. *arXiv preprint arXiv:1510.08484*, 2015.

Daniel S. Park, William Chan, Yu Zhang, Chung-Cheng Chiu, Barret Zoph, Ekin D. Cubuk, and Quoc V. Le. SpecAugment: A simple data augmentation method for automatic speech recognition. In *Interspeech*, 2019.

Bradley Efron and Robert J. Tibshirani. *An Introduction to the Bootstrap*. Chapman & Hall/CRC, 1993.

George Kour. arxiv-style: A LaTeX style for arXiv preprints. `https://github.com/kourgeorge/arxiv-style`, 2024.

Table 8: The seven required files of Moth 0.8.1. The package sum is 19,706,289 bytes; the payload excluding `config.json` and `NOTICE` is 19,701,706 bytes. Full SHA-256 values are retained in `runs/E-031/release-0.8.1.json`; the two most important are shown in the text.

| File | Bytes | Role |
|---|---|---|
| `model.int8.onnx` | 11,910,677 | int8 acoustic graph |
| `lm_bpe3.bin` | 5,381,992 | trigram LM, sparse int16 CSR |
| `silero_vad.onnx` | 2,327,524 | Silero VAD v5 |
| `mel_filters.bin` | 64,320 | 80×201 float32 filterbank |
| `vocab.json` | 17,193 | exported CTC piece map |
| `config.json` | 1,323 | version, decoder and hashes |
| `NOTICE` | 3,260 | attributions |
| **Total** | **19,706,289** | 293,711 bytes of headroom |

# A Release Manifest

The int8 graph SHA-256 is `7bbfad7e288640538c5c0147f81738bfd63021727b8760b1f3cbbcc4f939764d`; the A3 LM SHA-256 is `3be1177b0ca9f18343efb8d00f0d96365226595c9de32d992720aa4e0b0f16f1`. The model was published on 12 November 2026 and verified live on Hugging Face; hashes pin content consistency, not publisher authenticity or an immutable external timestamp.

# B Experiment Index

Table 9: All executed experiment IDs, with the question or intervention and the outcome. E-018 was planned but never executed because it required a fourth speaker. "Closed" means the option was rejected or exhausted for this recipe; it does not mean the idea is false in general.

| ID | Question / intervention | Outcome |
|---|---|---|
| E-000 | Mac feasibility (MPS, bf16) | 394 ms/step synthetic; feasible |
| E-001 | Baseline matrix (Whisper, Whistle, Parakeet) | measured; FLEURS-IT bar corrected to 27.42 |
| E-002 | Corpus, manifests, mel cache | 509.8 h cached; splits hashed before training |
| E-003 | int8 export and browser smoke | 8.32 MB; 33–74× RTFx |
| E-004 | Frozen encoder probe | dev 75.77; padded and truncated equivalent |
| E-005 | Full fine-tune, 437.7 h | dev 33.77; FLEURS-IT gate failed by 5.3 |
| E-006 | +2 transformer blocks | dev 31.27; adopted |
| E-007 | CTC beam and hotwords | small WER gain; hotwords neutral |
| E-008 | Trigram LM in shallow fusion | dev 27.05; adopted; FLEURS-IT still behind Whisper |
| E-009 | Real-weight int8 export and browser RTFx | 54–66× (4 threads); adopted |
| E-010 | Browser beam and LM quality path | tie with Python; adopted |
| E-011 | Silence/noise/music robustness | beam+LM hallucinated on silence; VAD added later |
| E-012 | +200 h LibriSpeech EN | English better, Italian/T worse; rejected |
| E-013 | BPE 4,096 | FLEURS-IT worse, ETA flat; rejected |
| E-014 | Spliced IT+EN, 110 h | dev 30.86; adopted |
| E-015 | First gold-term addendum | rare CI includes zero, FLEURS worse; rejected |
| E-016 | S1 gold fine-tune | dev 30.90; adopted path to E-017 |
| E-017 | S1+S2 gold, S3 held out | T-600 32.77; 0.5.0 |
| E-018 | Gold scaling to S4 | never executed |
| E-019 | Whistle LoRA probe | S3 worse, FLEURS/CV worse; rejected |
| E-020 | End-to-end int8 WER cost | +0.17 T-600 tie; FLEURS-IT +0.32 |
| E-021 | fp32 export gap diagnosis | single-draw tail; seeded gate adopted |
| E-022 | Decoder recalibration | −6.85 T-600, −8.77 T-S3; 0.6.0 |
| E-023 | LM re-tune with calibrated decoder | optimum unchanged; larger LM over budget |
| E-024 | Noise augmentation, half CV-IT | −11.54 at 10 dB; 0.7.0 |

| ID | Question / intervention | Outcome |
|---|---|---|
| E-025 | Held-out room noise test | gain larger; absolute WER worse; no new weights |
| E-026 | Rare-term diagnostic | LM is the lever, not top-k; 41/47 reachable |
| E-027 | Contextual bias pilot | rare unchanged; rejected |
| E-028 | S2 term addendum + gentler fine-tune | rare 30.9%; six gates in fp32; 0.8.0 |
| E-029 | QAT probe | no publishable candidate; closed |
| E-030 | Decoder recalibration for int8 | 5/6 gates; published 0.8.0 |
| E-031 | Frozen-corpus LM rebuild | rare 46.9%, T-600 24.08; 0.8.1 |
| E-032 | S1 term addendum | rare up, six gates down; rejected |
| E-033 | Intermediate CTC | dev $+0.0249$ pp, tie; closed |
| E-034 | Larger n-gram LM | $-0.6$ dev, 26.4 MB package; rejected |
| E-035 | Budgeted count-1 trigrams | $-0.0645$ dev, product tie; rejected |
| E-036 | Conservative KD fine-tune | rare shortfall; rejected |
| E-037 | Paired fp32/INT8 cost | +0.1574 pp dev; INT8 remains |
| E-038 | Per-speaker T-600 | 5.34 pp WER, 12.02 pp ETA range |
| E-039 | Leakage and provenance audit | no literal leakage; 44→35 term correction |
| E-040 | Four-seed replication of E-036 | rare reproduces, silence does not |
| E-041 | Browser acoustic WER/ETA | +0.7167 pp tie; S3 pays the most |

## C Reproduction Notes

The repository separates what can be re-scored from what can be retrained. Per-utterance hypotheses, metrics, comparison JSON and release records are retained; checkpoints, raw audio, mel shards and the serialized tokenizer are not versioned. A clean clone can therefore reproduce the scoring and every figure in this paper from the retained JSON and logs, but it cannot retrain the model without the external data, the converted Whisper encoder, the gold recordings and the checkpoints.

Three provenance issues are recorded rather than smoothed over. First, the 0.7.0 release record labels the selected checkpoint step as 26,442, while the training log's minimum dev WER is at step 26,000; the checkpoint hash is not retained, so the discrepancy cannot be resolved from this checkout. Second, the 0.8.1 model is a decode-only update: the acoustic graph is byte-identical to 0.8.0 and only the LM and version string changed. Third, "never seen" in the rare-term literature means never seen by 0.7.0, not by 0.8.1; the corrected count is 35 terms across 37 utterances after including LibriSpeech.

Figure 2 is generated from `runs/*/train.log.jsonl`. The remaining figures are generated by `paper/figures/make_figures.py` from the retained JSON in `runs/E-024`, `E-031`, `E-037`, `E-038` and `E-040`, with values that have no machine-readable file transcribed from the named result reports. The paper is compiled with the arXiv-style LaTeX template [Kour, 2024] and `tectonic`.