Arduino Header



Standard Motorshield Assignments:
Channel A:

D12 – Direction
D3 – PWM (work duty)
D9 – Brake
A0 – current sensing.

Channel B:

D13 – Direction
D11 – PWM (work duty)
D8 – Brake
A1 – current sensing

DRV8874 control logic:

PH/EN Mode (PMODE Low)

nSleep	EN/PH	out1/2
0	X X	ZZ
1	0 X	00
1	1 0	01
1	1 1	10

nSleep = high / pwm
EN = not brake / pwm
PH = dir

PWM Mode (PMODE High)

nSleep	in1/2	out1/2
0	X X	ZZ
1	0 0	ZZ
1	0 1	01
1	1 0	10
1	1 1	00

nSleep = high
in1 = pwm and (dir or brake)
in2 = pwm and (not dir or brake)





DRV8874 Mode Select

Low: EN/PH
High: PWM
Z: Independent

Alternative pinout to allow stacking





DRV8874 Motor Driver





i2c headers



OLED Header



OpAmp as IORef Comparator



DRV8874 Current Sensing:

0.000455 A_prop per A

5V = 0.000455*(1500+780)*A => A=4,82
3,3V = 0.000455* 1500 *A => A=4,83

V_prop is limited to VRef inside DRV8874

FID101 Toolinghole_jlc
FID102 Toolinghole_jlc
FID103 Toolinghole_jlc
FID104 Fiducial
FID105 Fiducial
FID106 Fiducial

Power Sheet

Power

File: power.kicad_sch

Engineer: Erwin Peterlin
semify-eda.com

Sheet: /
File: motor-shield.kicad_sch

Title: Motor Shield (DCC-EX compatible)

Size: A3	Date: 2023-02-06	**Rev: Prototype A**
KiCad E.D.A. kicad (7.0.0)		Id: 1/2

Barrel Jack



VIN DCDC Buck Converter



Reverse Polarity Protection



Status LEDs



Bulk Caps









Engineer: Erwin Peterlin
semify-eda.com
Sheet: /Power/
File: power.kicad_sch

Title: Motor Shield (DCC-EX compatible)

Size: A4	Date: 2023-02-06	**Rev: Prototype A**
KiCad E.D.A. kicad (7.0.0)		Id: 2/2