

# Package ‘flowMagic’

May 28, 2026

**Type** Package

**Title** Automated gating of flow cytometry data

**Version** 0.99

**Description** tool to perform the automated gating of bivariate flow cytometry data.

**License** Apache License 2.0 | file LICENSE + file NOTICE

**Encoding** UTF-8

**LazyData** true

**Roxygen** list(markdown = TRUE)

**Imports** caret,  
ggplot2,  
stringr,  
parallel,  
randomForest,  
concaveman,  
sp,  
sf,  
stats,  
grDevices,  
doParallel,  
nnet,  
sm,  
pracma,  
patchwork,  
ggExtra,  
RColorBrewer,  
dplyr

**Suggests** flowCore,  
flowWorkspace,  
Biobase,  
data.tree,  
visNetwork,  
klaR(<= 0.6-12),  
remotes,

CytoML,  
 plotly,  
 magrittr,  
 geometry

**Config/roxygen2/version 8.0.0**

## Contents

|                                              |    |
|----------------------------------------------|----|
| add_labels_column . . . . .                  | 3  |
| assign_events_to_nearest_centroids . . . . . | 4  |
| check_polygons_intersection . . . . .        | 5  |
| compute_gates . . . . .                      | 5  |
| convert_to_integers_chr . . . . .            | 6  |
| csv_to_dens . . . . .                        | 6  |
| exports_plots . . . . .                      | 7  |
| export_raw_gs_plots . . . . .                | 8  |
| extract_polygon_gates . . . . .              | 9  |
| flowmagic_pred_to_gs . . . . .               | 10 |
| flowmagic_pred_to_poly_gates . . . . .       | 10 |
| format_channel_info . . . . .                | 11 |
| get_centroids . . . . .                      | 12 |
| get_classes_expr_df . . . . .                | 13 |
| get_density_features . . . . .               | 14 |
| get_density_scores . . . . .                 | 14 |
| get_distance_loc_vs_test . . . . .           | 15 |
| get_dist_template . . . . .                  | 15 |
| get_flowframe_from_gs . . . . .              | 16 |
| get_gate_channels . . . . .                  | 17 |
| get_hierarchy_all_pops . . . . .             | 18 |
| get_hull_all_gates . . . . .                 | 18 |
| get_indices_cross_val . . . . .              | 19 |
| get_list_df_gated_plots . . . . .            | 20 |
| get_local_train_sets . . . . .               | 20 |
| get_pops_hierarchy_list . . . . .            | 21 |
| get_pop_multiclass . . . . .                 | 22 |
| get_slot_hierarchy_list . . . . .            | 22 |
| get_test_sets . . . . .                      | 23 |
| get_train_data . . . . .                     | 23 |
| get_weights_density_features . . . . .       | 24 |
| import_gating_info . . . . .                 | 25 |
| import_reference_csv . . . . .               | 25 |
| import_test_set_csv . . . . .                | 26 |
| import_test_set_fcs . . . . .                | 26 |
| magicGating . . . . .                        | 27 |
| magicPlot . . . . .                          | 28 |
| magicplot_3D . . . . .                       | 29 |
| magicPlot_fs . . . . .                       | 30 |

|                                    |    |
|------------------------------------|----|
| magicPlot_gs_gates . . . . .       | 31 |
| magicPlot_gs_hierarchy . . . . .   | 32 |
| magicPlot_gs_node . . . . .        | 35 |
| magicPlot_template . . . . .       | 36 |
| magicPred . . . . .                | 37 |
| magicPred_all . . . . .            | 38 |
| magicPred_hierarchy . . . . .      | 39 |
| magicTrain . . . . .               | 40 |
| magicTrain_dt . . . . .            | 41 |
| magicTrain_hierarchy . . . . .     | 42 |
| magicTrain_knn . . . . .           | 43 |
| magicTrain_nb . . . . .            | 44 |
| magicTrain_nnet . . . . .          | 45 |
| magicTrain_rf . . . . .            | 46 |
| magic_label_poly . . . . .         | 47 |
| magic_label_rectangle . . . . .    | 47 |
| magic_manual_gating . . . . .      | 48 |
| magic_plot_wrap . . . . .          | 49 |
| magic_template_predict . . . . .   | 50 |
| magic_template_train . . . . .     | 52 |
| map_to_parent . . . . .            | 53 |
| map_to_root . . . . .              | 54 |
| merge_magicGating_labels . . . . . | 55 |
| name_pop_gating . . . . .          | 55 |
| post_process_gates . . . . .       | 56 |
| process_test_data . . . . .        | 57 |
| range01 . . . . .                  | 57 |
| smooth_hull . . . . .              | 58 |
| update_label_association . . . . . | 59 |

|              |           |
|--------------|-----------|
| <b>Index</b> | <b>60</b> |
|--------------|-----------|

---

|                   |                          |
|-------------------|--------------------------|
| add_labels_column | <i>add_labels_column</i> |
|-------------------|--------------------------|

---

## Description

function to add label association column.

## Usage

```
add_labels_column(df, labels_association)
```

## Arguments

df                      Dataframe.  
labels\_association      Vector of label association.

**Value**

Dataframe.

**Examples**

```
add_labels_column()
```

---

```
assign_events_to_nearest_centroids  
    assign_events_to_nearest_centroids
```

---

**Description**

function to assign events to class with nearest centroid.

**Usage**

```
assign_events_to_nearest_centroids(  
    gated_df,  
    n_cores = 1,  
    method_dist = "euclidean",  
    thr_dist = 0.15,  
    include_zero = F,  
    remove_centroids = T  
)
```

**Arguments**

|                               |                                                                            |
|-------------------------------|----------------------------------------------------------------------------|
| <code>gated_df</code>         | dataframe with labels (third column).                                      |
| <code>n_cores</code>          | Number of cores. Default to 1.                                             |
| <code>method_dist</code>      | Distance method calculation. Default to euclidean.                         |
| <code>thr_dist</code>         | Distance threshold for centroids calculation. Default to 0.15.             |
| <code>include_zero</code>     | Consider centroid of label 0. Default to False.                            |
| <code>remove_centroids</code> | Remove centroids too near each other based on <code>thr_dist</code> value. |

**Value**

Dataframe.

**Examples**

```
assign_events_to_nearest_centroids()
```

---

|                             |                              |
|-----------------------------|------------------------------|
| check_polygons_intersection |                              |
|                             | <i>extract_polygon_gates</i> |

---

**Description**

function to check polygons intersection.

**Usage**

```
check_polygons_intersection(list_df_hull)
```

**Arguments**

list\_df\_hull     List of polygons coordinates

**Value**

float

**Examples**

```
check_polygons_intersection()
```

---

|               |                      |
|---------------|----------------------|
| compute_gates | <i>compute_gates</i> |
|---------------|----------------------|

---

**Description**

function to assign events based on polygon gates.

**Usage**

```
compute_gates(gated_df, list_final_polygons_coors, no_classes = F)
```

**Arguments**

gated\_df            dataframe with labels (third column).  
list\_final\_polygons\_coors     List of dataframes containing polygon coordinates.  
no\_classes          Generate third column of labels. Default to False.

**Value**

Dataframe.

**Examples**

```
compute_gates()
```

---

```
convert_to_integers_chr
      convert_to_integers_chr
```

---

**Description**

function to text classes to integers-like classes if necessary.

**Usage**

```
convert_to_integers_chr(df)
```

**Arguments**

df                      Dataframe with classes (third column) to check and eventually modify

**Value**

Dataframe

**Examples**

```
convert_to_integers_chr()
```

---

```
csv_to_dens                      csv_to_dens
```

---

**Description**

function to get density of events (with classes associated if present).

**Usage**

```
csv_to_dens(df, with_classes = T, n_coord = "df", normalize_data = T)
```

**Arguments**

df                      Dataframe of marker expression values.  
with\_classes          Consider classes. Default to True.  
n\_coord                Grid size. Default to df.  
normalize\_data        If True, data is normalized to 0-1 range. Default to True.

**Value**

Dataframe.

**Examples**

```
csv_to_dens()
```

---

|               |                      |
|---------------|----------------------|
| exports_plots | <i>exports_plots</i> |
|---------------|----------------------|

---

**Description**

function to generate plots (no hierarchy) from list of labelled dataframes.

**Usage**

```
exports_plots(  
  list_gated_data,  
  path_output,  
  n_cores = 1,  
  type_plot = "dens",  
  show_legend = T,  
  x_lab = "x",  
  y_lab = "y",  
  size_title_x = 23,  
  size_title_y = 23,  
  aspect_ratio = NULL,  
  w_val = 16,  
  h_val = 10,  
  size_axis_text = 25,  
  export_csv = F,  
  side_by_side = F,  
  ...  
)
```

**Arguments**

|                 |                                                                                                      |
|-----------------|------------------------------------------------------------------------------------------------------|
| list_gated_data | list of dataframes. Each dataframe has 3 columns: marker 1 values, marker 2 values and label column. |
| path_output     | Path to the directory where to export the plots.                                                     |
| n_cores         | Number of cores to use. Default to 1.                                                                |
| type_plot       | the user can choose between density (="dens) or label assignment visualization (="ML")               |
| show_legend     | If True it shows the legend for the label assignment visualization. Default to True.                 |

|                             |                                                                                   |
|-----------------------------|-----------------------------------------------------------------------------------|
| <code>x_lab</code>          | x-axis label.                                                                     |
| <code>y_lab</code>          | y-axis label.                                                                     |
| <code>size_title_x</code>   | Size x axis label.                                                                |
| <code>size_title_y</code>   | Size y axis label.                                                                |
| <code>aspect_ratio</code>   | Set aspect ratio. Default to NULL> If = 1, y and x axis ticks have same distance. |
| <code>w_val</code>          | width value. Default to 16.                                                       |
| <code>h_val</code>          | height value. Default to 10.                                                      |
| <code>size_axis_text</code> | Size of ticks labels.                                                             |
| <code>export_csv</code>     | Export plot data as csv files. Default to False.                                  |
| <code>side_by_side</code>   | Arrange dens plot and ML plot side-by-side. Default to False.                     |

### Examples

```
exports_plots()
```

---

|                                  |                            |
|----------------------------------|----------------------------|
| <code>export_raw_gs_plots</code> | <i>export_raw_gs_plots</i> |
|----------------------------------|----------------------------|

---

### Description

function to generate ungated plots from selected gs node

### Usage

```
export_raw_gs_plots(
  gs,
  node_name,
  channel_x,
  channel_y,
  path_output,
  n_cores = 1,
  x_lab = NULL,
  y_lab = NULL,
  w_val = 7,
  h_val = 7,
  size_points = 1,
  return_data = F,
  ...
)
```



**Arguments**

|                          |                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------|
| <code>gs</code>          | GatingSet                                                                            |
| <code>path_output</code> | Path to the directory where to export the plots.                                     |
| <code>n_cores</code>     | Number of cores to use. Default to 1.                                                |
| <code>x_lab</code>       | x-axis label. Default to NULL (inherited from GatingSet metadata).                   |
| <code>y_lab</code>       | y-axis label. Default to NULL (inherited from GatingSet metadata).                   |
| <code>w_val</code>       | width value. Default to 7 inches.                                                    |
| <code>h_val</code>       | height value. Default to 7 inches.                                                   |
| <code>size_points</code> | Size points scatter plot.                                                            |
| <code>return_data</code> | If TRUE, return the list of dataframes used to generate the plots. Default to FALSE. |

**Examples**

```
export_raw_gs_plots()
```

---

```
extract_polygon_gates extract_polygon_gates
```

---

**Description**

function to extract the polygon gates objects based on the convex hull and classes.

**Usage**

```
extract_polygon_gates(gated_df, concavity_val = 1, ...)
```

**Arguments**

|                            |                                       |
|----------------------------|---------------------------------------|
| <code>gated_df</code>      | dataframe with labels (third column). |
| <code>concavity_val</code> | Concavity of polygons. Default to 1.  |

**Value**

List of dataframes.

**Examples**

```
extract_polygon_gates()
```

---

```
flowmagic_pred_to_gs  flowmagic_pred_to_gs
```

---

**Description**

function to add list of polygon objects generated by flowmagic\_pred\_to\_poly\_gates function to GatingSet object.

**Usage**

```
flowmagic_pred_to_gs(list_poly_gates, gs, parent_node)
```

**Arguments**

|                 |                                                                              |
|-----------------|------------------------------------------------------------------------------|
| list_poly_gates | List of polygonGate objects generated using the flowmagic_pred_to_poly_gates |
| gs              | GatingSet to update with the flowMagic polygons.                             |
| parent_node     | Parent population name of the new gate.                                      |

**Value**

GatingSet

**Examples**

```
flowmagic_pred_to_gs()
```

---

```
flowmagic_pred_to_poly_gates
flowmagic_pred_to_poly_gates
```

---

**Description**

function to label points of dataframe based on polygon coordinates

**Usage**

```
flowmagic_pred_to_poly_gates(
  list_df,
  pred_label,
  gate_label,
  n_cores = 1,
  concavity_val = 10
)
```

**Arguments**

|               |                                                                                                                      |
|---------------|----------------------------------------------------------------------------------------------------------------------|
| list_df       | List of dataframes with three columns: marker 1, marker 2, class. Can get input generated by the magicPred function. |
| pred_label    | Select prediction label to extract polygon.                                                                          |
| gate_label    | Label for the selected polygon within the GatingSet framework.                                                       |
| n_cores       | Number of cores to use. Default to 1.                                                                                |
| concavity_val | Concavity value for drawing polygon. Default to 10.                                                                  |

**Value**

list

**Examples**

```
flowmagic_pred_to_poly_gates()
```

---

|                     |                                        |
|---------------------|----------------------------------------|
| format_channel_info | <i>Format gate channel information</i> |
|---------------------|----------------------------------------|

---

**Description**

This helper function takes channel names used by a gate and matches them to the metadata stored in a flowFrame parameter table.

**Usage**

```
format_channel_info(channels, df_metadata)
```

**Arguments**

|             |                                                                                                                |
|-------------|----------------------------------------------------------------------------------------------------------------|
| channels    | Character vector. Channel names used by a gate. For example, c("BV480-A", "BV650-A").                          |
| df_metadata | Data frame. FlowFrame parameter metadata, usually from ff@parameters@data. Must contain columns name and desc. |

**Details**

The metadata table usually comes from:

```
ff@parameters@data
```

It should contain at least the columns name and desc.

For channels with a marker description, the function returns:

```
channel = marker
```

For channels without a marker description, such as scatter channels, the function returns only the channel name.

**Value**

A single character string containing formatted channel information, with one channel per line.

**Examples**

```
## Not run:
ff <- flowMagic::get_flowframe_from_gs(
  gs = gs,
  node_name = "root",
  sample_id = 1
)

df_metadata <- ff@parameters@data

format_channel_info(
  channels = c("BV480-A", "BV650-A"),
  df_metadata = df_metadata
)
# "BV480-A = CD19\nBV650-A = NK1.1"

## End(Not run)
```

---

get\_centroids

*get\_centroids*


---

**Description**

function to get centroids for each label

**Usage**

```
get_centroids(
  df,
  low_thr = 0.1,
  up_thr = 0.9,
  thr_dist = 0.15,
  include_zero = F,
  remove_centroids = T
)
```

**Arguments**

|          |                                                                |
|----------|----------------------------------------------------------------|
| df       | dataframe with labels (third column).                          |
| low_thr  | Lower threshold for quantile calculation.                      |
| up_thr   | Upper threshold for quantile calculation.                      |
| thr_dist | Distance threshold for centroids calculation. Default to 0.15. |

`include_zero`     Consider centroid of label 0. Default to False.  
`remove_centroids`     Remove centroids too near each other based on `thr_dist` value.

**Value**

Dataframe.

**Examples**

```
get_centroids()
```

---

|                                  |                                  |
|----------------------------------|----------------------------------|
| <code>get_classes_expr_df</code> | <code>get_classes_expr_df</code> |
|----------------------------------|----------------------------------|

---

**Description**

function to get classes of original expression df based on density df predictions.

**Usage**

```
get_classes_expr_df(dens_df, original_df)
```

**Arguments**

`dens_df`     Dataframe of density values.  
`original_df`     Original dataframe.

**Value**

Dataframe.

**Examples**

```
get_classes_expr_df()
```

---

|                      |                             |
|----------------------|-----------------------------|
| get_density_features | <i>get_density_features</i> |
|----------------------|-----------------------------|

---

**Description**

function to get density features only given a bivarite density csv.

**Usage**

```
get_density_features(df_dens, min_height = 0.06)
```

**Arguments**

|            |                                                  |
|------------|--------------------------------------------------|
| df_dens    | Dataframe of density estimates for both markers. |
| min_height | Minimum height of the peaks to consider.         |

**Value**

Vector of numbers.

**Examples**

```
get_density_features()
```

---

|                    |                           |
|--------------------|---------------------------|
| get_density_scores | <i>get_density_scores</i> |
|--------------------|---------------------------|

---

**Description**

function to get scores for distance template calculation.

**Usage**

```
get_density_scores(df_template, df_test, select_density_features = NULL)
```

**Arguments**

|                         |                                                  |
|-------------------------|--------------------------------------------------|
| df_template             | Dataframe of template markers expression values. |
| df_test                 | Dataframe of test markers expression values.     |
| select_density_features | Select features to use. Default to NULL.         |

**Value**

Matrix of numbers.

**Examples**

```
get_density_scores()
```

---

```
get_distance_loc_vs_test
    get_distance_loc_vs_test
```

---

**Description**

function to compare the similiraty between current test data and local training set.

**Usage**

```
get_distance_loc_vs_test(test_df, loc_df, show_plot = "none", nboot = 50)
```

**Arguments**

|           |                                             |
|-----------|---------------------------------------------|
| test_df   | Dataframe with bivariate marker expression. |
| loc_df    | Dataframe with bivariate marker expression. |
| show_plot | show density comparison. Default to none.   |
| nboot     | Number of permutations. Default to 50.      |

**Value**

List of p-values.

**Examples**

```
get_distance_loc_vs_test()
```

---

```
get_dist_template    get_dist_template
```

---

**Description**

function to get distance between template and test data.

**Usage**

```
get_dist_template(matrix_scores, dist_method = "euclidean")
```

**Arguments**

|               |                                                                      |
|---------------|----------------------------------------------------------------------|
| matrix_scores | Matrix of density features generated by get_density_scores function. |
| dist_method   | Type of distance method calculation.                                 |

**Value**

Number.

**Examples**

```
get_dist_template()
```

---

```
get_flowframe_from_gs  get_flowframe_from_gs
```

---

**Description**

Extract a population from a GatingSet or GatingHierarchy as a flowFrame.

**Usage**

```
get_flowframe_from_gs(gs, node_name, sample_id = NULL)
```

**Arguments**

|           |                                                                                                                                                                                              |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| gs        | A GatingSet or GatingHierarchy object. If a GatingSet is provided, sample_id must also be provided. If a GatingHierarchy is provided, sample_id is ignored.                                  |
| node_name | Character. Name of the population node to extract, such as "root", "Live_cells", "Singlets", or another node present in the gating hierarchy.                                                |
| sample_id | Character or NULL. Sample name to extract when gs is a GatingSet. The value must be present in sampleNames(gs). Default is NULL, which is allowed only when gs is already a GatingHierarchy. |

**Details**

This function extracts the events belonging to a selected population node from either a GatingSet or a GatingHierarchy. The extracted data are returned as a flowFrame, which can then be used by downstream flowMagic functions.

If gs is a GatingSet, the user must provide sample\_id because a GatingSet contains multiple samples. If gs is already a GatingHierarchy, sample\_id is not needed because a GatingHierarchy represents one sample.

The function uses inherits() to check whether the input object is a GatingSet or a GatingHierarchy. This is preferred over direct class() comparisons because Bioconductor/S4 objects may have multiple classes or inherit from other classes.

Internally, the selected population is first extracted using flowWorkspace::gh\_pop\_get\_data().

The resulting object is usually a cytoframe, which is then converted to a flowFrame using cytoframe\_to\_flowFrame().

**Value**

A flowFrame object containing the events from the selected population node.



### Examples

```
# Extract from a GatingSet
ff <- get_flowframe_from_gs(
  gs = gs,
  node_name = "Live_cells",
  sample_id = "sample_01.fcs"
)

# Extract from a GatingHierarchy
gh <- gs[["sample_01.fcs"]]

ff <- get_flowframe_from_gs(
  gs = gh,
  node_name = "Live_cells"
)
```

---

|                   |                                               |
|-------------------|-----------------------------------------------|
| get_gate_channels | <i>Extract gate channels for a population</i> |
|-------------------|-----------------------------------------------|

---

### Description

This helper function gets the gate used to define a population and extracts the flow cytometry channels used by that gate.

### Usage

```
get_gate_channels(gs, pop)
```

### Arguments

|     |                                         |
|-----|-----------------------------------------|
| gs  | A GatingSet or GatingHierarchy object.  |
| pop | Character. Name of the population/node. |

### Details

In some cases, `flowWorkspace::gs_pop_get_gate()` returns the gate directly. In other cases, it returns a list with one gate per sample. This function handles that by using the first gate in the list.

### Value

A character vector containing the channel names used by the gate. If the population is "root", if no gate is found, or if the channels cannot be extracted, an empty character vector is returned.

**Examples**

```
## Not run:
get_gate_channels(gs[[1]], "B_cells")
# [1] "BV480-A" "BV650-A"

## End(Not run)
```

---

```
get_hierarchy_all_pops
```

```
get_hierarchy_all_pops
```

---

**Description**

function to plot hierarchy of all nodes/cell populations from a GatingHierarchy object.

**Usage**

```
get_hierarchy_all_pops(gh, export_visnet = F, path.output = "None")
```

**Arguments**

`gh`                    GatingHierarchy.  
`export_visnet`    If true, it export visnetwork object.  
`path.output`       Path to save visnetwork object. Default to None.

**Value**

List of Dataframes.

**Examples**

```
get_hierarchy_all_pops()
```

---

```
get_hull_all_gates
```

```
get_hull_all_gates
```

---

**Description**

function to get the convex hull of all gates.

**Usage**

```
get_hull_all_gates(gated_df, concavity_val = 1, spar_val = 0.7, smoothing = F)
```

**Arguments**

|               |                                         |
|---------------|-----------------------------------------|
| gated_df      | dataframe with labels (third column).   |
| concavity_val | Values of concavity. Default to 1.      |
| spar_val      | Value of spar. Default to 0.7.          |
| smoothing     | Apply smoothing of lines? Default to F. |

**Value**

List of dataframes.

**Examples**

```
get_hull_all_gates()
```

---

```
get_indices_cross_val  get_indices_cross_val
```

---

**Description**

function to get indices for cross val.

**Usage**

```
get_indices_cross_val(
  df_train,
  n_cores = 1,
  train_inds = "plot_num",
  val_inds = "none",
  n_train_plots = 5,
  n_folds = 5,
  seed = 40,
  n_val_plots = 5
)
```

**Arguments**

|               |                                                                                            |
|---------------|--------------------------------------------------------------------------------------------|
| df_train      | Dataframe of training features generated by the get_train_data function.                   |
| n_cores       | Number of cores to use. Default to 1.                                                      |
| train_inds    | Type of method to extract training indices: plot_num,rand_set_num,rand_set_n_gates_info.   |
| val_inds      | Type of method to extract validation indices: plot_num,rand_set_num,rand_set_n_gates_info. |
| n_train_plots | Number of training plots to include in training data for each iteration.                   |
| n_folds       | Number of training iterations.                                                             |
| seed          | Seed to randomly extract data.                                                             |
| n_val_plots   | Number of training plots to include in validation data for each iteration.                 |

**Value**

List of integers.

**Examples**

```
get_indices_cross_val()
```

---

```
get_list_df_gated_plots
```

```
get_list_df_gated_plots
```

---

**Description**

function to get labelled dataframe based on selected node for each sample in gs.

**Usage**

```
get_list_df_gated_plots(gs, gate_name, label_pop = NULL)
```

**Arguments**

|           |                                                                       |
|-----------|-----------------------------------------------------------------------|
| gs        | GatingSet                                                             |
| gate_name | Name of the Gating tree node whose gating data needs to be extracted. |
| label_pop | Set label for selected gate.                                          |

**Value**

List.

**Examples**

```
get_list_df_gated_plots()
```

---

```
get_local_train_sets    get_local_train_sets
```

---

**Description**

Based on the hierarchy calculated using the get\_hierarchy function, we generate the local training sets gated by the biologists.

**Usage**

```
get_local_train_sets(gh, hierarchical_tree, info_hierarchy)
```

**Arguments**

`gh`                      GatingHierarchy.  
`hierarchical_tree`                      Dataframe of hierarchy information generated by the `get_hierarchy` function.  
`info_hierarchy`      List of hierarchy information generated by the `get_hierarchy` function.

**Value**

List of Dataframes.

**Examples**

```
get_local_train_sets()
```

---

```
get_pops_hierarchy_list  
                          get_pops_hierarchy_list
```

---

**Description**

function to get info from a list of hierarchical dataset (it reports all the pops for each level in a vector).

**Usage**

```
get_pops_hierarchy_list(hierarchical_list)
```

**Arguments**

`hierarchical_list`                      list of populations names for each level.

**Value**

Vector of characters.

**Examples**

```
get_pops_hierarchy_list()
```

---

|                    |                           |
|--------------------|---------------------------|
| get_pop_multiclass | <i>get_pop_multiclass</i> |
|--------------------|---------------------------|

---

**Description**

function to get the children of the selected population, useful for multiclass classification. The output is only the pops with same dimensions

**Usage**

```
get_pop_multiclass(gh, pop)
```

**Arguments**

|     |                                               |
|-----|-----------------------------------------------|
| gh  | GatingHierarchy.                              |
| pop | Name of population to get events assignments. |

**Value**

Vector of characters.

**Examples**

```
get_pop_multiclass()
```

---

|                         |                                |
|-------------------------|--------------------------------|
| get_slot_hierarchy_list | <i>get_slot_hierarchy_list</i> |
|-------------------------|--------------------------------|

---

**Description**

function to access a slot of results from the hierarchy list based on the pop selected.

**Usage**

```
get_slot_hierarchy_list(hierarchical_list, pop_selected)
```

**Arguments**

|                   |                                           |
|-------------------|-------------------------------------------|
| hierarchical_list | list of populations names for each level. |
| pop_selected      | Population name.                          |

**Value**

Element of a list.

**Examples**

```
get_slot_hierarchy_list()
```

---

|               |                      |
|---------------|----------------------|
| get_test_sets | <i>get_test_sets</i> |
|---------------|----------------------|

---

**Description**

Function to obtain the data ready to be gated (validation set or test set). It takes as input a flowSet and generates a list of dataframes with a ML structure for each ungated fcs file. Each dataframe is the expression matrix of the root.

**Usage**

```
get_test_sets(fs, gh)
```

**Arguments**

|    |                   |
|----|-------------------|
| fs | flowSet to gate.  |
| gh | Gating hierarchy. |

**Value**

List of dataframes.

**Examples**

```
get_test_sets()
```

---

|                |                       |
|----------------|-----------------------|
| get_train_data | <i>get_train_data</i> |
|----------------|-----------------------|

---

**Description**

function to import training data based on paths to files.

**Usage**

```
get_train_data(  
  paths_file = NULL,  
  df_paths = NULL,  
  n_cores = 1,  
  prop_down = NULL,  
  remove_class = NULL,  
  n_points_per_plot = NULL,  
  normalize_data = T,  
  vec_col = NULL  
)
```

**Arguments**

|                                |                                                                                                                                                                                                                                       |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>paths_file</code>        | Vector of paths. Each path points toward a single csv file containin training info (labels and bivariate expression). <code>paths_file</code> can be also directly the list of dataframes containing labels and bivariate expression. |
| <code>df_paths</code>          | Dataframe containing the paths of file to read. The paths to data must be in the first column. The associated paths to classes are in second column.                                                                                  |
| <code>n_cores</code>           | Number of cores. Default to 1.                                                                                                                                                                                                        |
| <code>prop_down</code>         | Proportion of events (downsampling). Default to NULL (downsampling using number of points).                                                                                                                                           |
| <code>remove_class</code>      | Vector of classes to ignore. Default to NULL.                                                                                                                                                                                         |
| <code>n_points_per_plot</code> | Number of points for downsampling.                                                                                                                                                                                                    |
| <code>normalize_data</code>    | If True, data is normalized to 0-1 range. Default to True.                                                                                                                                                                            |
| <code>vec_col</code>           | vector of columns names if the input dataframes have more than 3 columns. The third column name must always refer to the column with the gate label of each event. Default to NULL.                                                   |

**Value**

Dataframe.

**Examples**

```
get_train_data()
```

---

```
get_weights_density_features
      get_weights_density_features
```

---

**Description**

function to calculate final score based on density features.

**Usage**

```
get_weights_density_features(df_scores)
```

**Arguments**

|                        |                               |
|------------------------|-------------------------------|
| <code>df_scores</code> | Dataframe of distance scores. |
|------------------------|-------------------------------|

**Value**

Vector of numbers.

**Examples**

```
get_weights_density_features()
```



---

|                    |                            |
|--------------------|----------------------------|
| import_gating_info | <i>import_sample_gated</i> |
|--------------------|----------------------------|

---

**Description**

convert a flowWorkspace or a GatingML file of the train data folder into a gated gh (gh\_train)

**Usage**

```
import_gating_info(path, type = "gs", group_wsp = NULL)
```

**Arguments**

|           |                                |
|-----------|--------------------------------|
| path      | path to gs or GatingML object. |
| type      | type of object.                |
| group_wsp | Group of wsp to import.        |

**Value**

GatingSet object

**Examples**

```
import_sample_gated()
```

---

|                      |                             |
|----------------------|-----------------------------|
| import_reference_csv | <i>import_reference_csv</i> |
|----------------------|-----------------------------|

---

**Description**

function to import plain gold standards data (no hierarchy)

**Usage**

```
import_reference_csv(path_results, n_cores = 1)
```

**Arguments**

|              |                                                                                   |
|--------------|-----------------------------------------------------------------------------------|
| path_results | path to directory containing the csv files to read (with third column of labels). |
| n_cores      | Number of cores to use. Default to 1.                                             |

**Value**

list of dataframes

**Examples**

```
import_reference_csv()
```

---

```
import_test_set_csv    import_test_set_csv
```

---

**Description**

function to import test set in csv format.

**Usage**

```
import_test_set_csv(path_data, n_cores = 1, xy_col = T)
```

**Arguments**

|           |                                                                           |
|-----------|---------------------------------------------------------------------------|
| path_data | path to directory containing csv files to read (third column is ignored). |
| n_cores   | Number cores. Default to 1.                                               |
| xy_col    | Colnames equal to x and y. Default to True.                               |

**Value**

List of dataframes.

**Examples**

```
import_test_set_csv()
```

---

```
import_test_set_fcs    import_test_set
```

---

**Description**

Read the ungated fcs files into a flowSet.

**Usage**

```
import_test_set_fcs(
  path,
  n_samples = "All",
  ref_f_n = 1,
  pattern_filter = NULL
)
```

**Arguments**

|                |                                                                                |
|----------------|--------------------------------------------------------------------------------|
| path           | path of directory containig the fcs files.                                     |
| n_samples      | Number of samples. Default to All.                                             |
| ref_f_n        | Set reference flowFrame to match channel names. Default to 1(first flowFrame). |
| pattern_filter | Filter files to import based on string patterns. Default to NULL.              |

**Value**

flowSet.

**Examples**

```
import_test_set()
```

---

magicGating

*magicGating*

---

**Description**

function to manually gate samples in a flowSet.

**Usage**

```
magicGating(
  fs,
  sample_id = 1,
  channel_x,
  channel_y,
  gs_node = NULL,
  label_pol = "1",
  ...
)
```

**Arguments**

|           |                                                                                                                                                                 |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fs        | An object of class flowSet. Can be also an object of class cytoset (it will be converted to flowSet) or a GatingSet object (in this case, gs_node is mandatory) |
| sample_id | Names of the samples to gate. It can also be the numerical index of the sample. Default to sample 1.                                                            |
| channel_x | Name of the channel (x-axis).                                                                                                                                   |
| channel_y | Name of the channel (y-axis).                                                                                                                                   |
| gs_node   | Name of the node to extract data, if fs is a GatingSet object this a mandatory argument.                                                                        |
| label_pol | Label of the gate polygon. Default to "1".                                                                                                                      |

**Value**

List of two objects of class List. list\_poly\_gates: List of polygon coordinates. Each element refers to the coordinates of one sample. list\_gated\_data: List of gated data. Each element refers to the gated data of one sample.

**Examples**

```
magicGating()
```

---

magicPlot

*magicPlot*


---

## Description

function to generate the scatter plot with colored density of the events.

## Usage

```
magicPlot(
  df,
  type = "dens",
  polygons_coords_list = NULL,
  show_legend = T,
  size_axis_text = 18,
  size_title_x = 20,
  size_title_y = 20,
  treat_0_as_gate = F,
  x_lab = NULL,
  y_lab = NULL,
  gates_to_plot = NULL,
  apply_manual_scale = F,
  hull_only = F,
  size_points = 1,
  concavity_val = 20,
  aspect_ratio = NULL,
  x_lim1 = NULL,
  x_lim2 = NULL,
  y_lim1 = NULL,
  y_lim2 = NULL,
  add_labels = F,
  map_label_polygon = NULL,
  size_pol_name = 6,
  show_marginals = F,
  ...
)
```

## Arguments

|                                   |                                                                                                                                         |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| <code>df</code>                   | Dataframe of bivariate markers expression (with labels if gates to plot).                                                               |
| <code>type</code>                 | Type of plot to generated. "dens"= plot with bivariate density. "ML"= plot with color layer based on machine learning class assignments |
| <code>polygons_coords_list</code> | list of gates coordinates. Needed if labels not included in df. Default to NULL.                                                        |
| <code>show_legend</code>          | Show legend if type="ML". Default to True.                                                                                              |
| <code>size_axis_text</code>       | Size of axis ticks labels. Default to 18.                                                                                               |

|                    |                                                                                                         |
|--------------------|---------------------------------------------------------------------------------------------------------|
| size_title_x       | Size of x axis label title. Default to 20.                                                              |
| size_title_y       | Size of y axis label title. Default to 20.                                                              |
| treat_0_as_gate    | Treat 0 label as gate. Default to False (0 label is background)                                         |
| x_lab              | Label of x axis. Default to NULL (inherited from input dataframe by default).                           |
| y_lab              | Label of y axis. Default to NULL (inherited from input dataframe by default).                           |
| gates_to_plot      | Select labels to plot.                                                                                  |
| apply_manual_scale | Apply predefined scale of colors. Default to True.                                                      |
| size_points        | Size of points in scatter plot.                                                                         |
| concavity_val      | Concavity value. Default to 20. Higher value, less jagged boundaries                                    |
| aspect_ratio       | Aspect ratio value. If = 1, y and x axis have equal distance between the ticks labels. Default to NULL. |
| x_lim1             | Minimum limit x axis. Default to NULL.                                                                  |
| x_lim2             | Max limit x axis. Default to NULL.                                                                      |
| y_lim1             | Minimum limit y axis. Default to NULL.                                                                  |
| y_lim2             | Max limit y axis. Default to NULL.                                                                      |
| add_labels         | add polygon labels. Default to FALSE.                                                                   |
| map_label_polygon  | map of polygon labels (to assign custom labels). Default to NULL.                                       |
| size_pol_name      | size polygon labels. Default to 6.                                                                      |
| show_marginals     | show 1D density next to axis. Default to False.                                                         |

**Value**

Object of class ggplot

**Examples**

```
magicPlot()
```

---

magicplot\_3D

*magicplot\_3D*


---

**Description**

function to make a 3D plot of data.

**Usage**

```
magicplot_3D(  
  df,  
  class_col = F,  
  x_lab = "x",  
  y_lab = "y",  
  z_lab = "z",  
  type = "ML",  
  size_p = 1  
)
```

**Arguments**

|           |                                                                                                                                        |
|-----------|----------------------------------------------------------------------------------------------------------------------------------------|
| df        | input dataframe composed of at least three columns. Four columns if gate needs to be plot.                                             |
| class_col | Gate to plot? Default to False.                                                                                                        |
| x_lab     | label of the x axis                                                                                                                    |
| y_lab     | Label of the y axis                                                                                                                    |
| z_lab     | Label of the z axis                                                                                                                    |
| type      | Assuming class_col==T, If type==ML, Generate a plot colored based on the gate assignment. If type=="mesh", generate a 3d polygon gate. |
| size_p    | size of scatter plot points. Default to 1.                                                                                             |

**Value**

plotly plot

**Examples**

```
magicplot_3D()
```

---

|              |                     |
|--------------|---------------------|
| magicPlot_fs | <i>magicPlot_fs</i> |
|--------------|---------------------|

---

**Description**

function to plot FCM data directly from objects of class flowSet or flowFrame. The data is shown in a density scatter plot.

**Usage**

```
magicPlot_fs(fs, sample_id, channel_x, channel_y, ...)
```

**Arguments**

|                        |                                                                                                              |
|------------------------|--------------------------------------------------------------------------------------------------------------|
| <code>fs</code>        | object of class <code>flowSet</code> or <code>flowFrame</code> .                                             |
| <code>sample_id</code> | Name of the sample data to plot. No effect if <code>fs</code> is an object of class <code>flowFrame</code> . |
| <code>channel_x</code> | Name of the channel to plot (x-axis).                                                                        |
| <code>channel_y</code> | Name of the channel to plot (y-axis).                                                                        |

**Value**

Object of class `ggplot`

**Examples**

```
magicPlot_fs()
```

---

```
magicPlot_gs_gates    magicPlot_gs_gates
```

---

**Description**

Plot one sample from a `GatingSet` with one or more gated populations overlaid.

**Usage**

```
magicPlot_gs_gates(
  gs,
  sample_id,
  gate_names,
  size_points = 0.5,
  concavity_val = 50,
  ...
)
```

**Arguments**

|                            |                                                                                                                                                                                |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>gs</code>            | A <code>GatingSet</code> object.                                                                                                                                               |
| <code>sample_id</code>     | Character. Name of the sample to plot. Must be present in <code>sampleNames(gs)</code> .                                                                                       |
| <code>gate_names</code>    | Character vector. One or more <code>GatingSet</code> node names to extract and display.                                                                                        |
| <code>size_points</code>   | Numeric. Point size passed to <code>magicPlot()</code> . Default is 0.5.                                                                                                       |
| <code>concavity_val</code> | Numeric. Concavity parameter available for downstream polygon plotting. Default is 50.                                                                                         |
| <code>...</code>           | Additional arguments passed to <code>magicPlot()</code> , such as <code>type</code> , <code>size_axis_text</code> , <code>size_title_x</code> , or <code>size_title_y</code> . |

**Details**

This function extracts one or more gated populations from a single sample in a GatingSet and visualizes them using `magicPlot()`. If multiple gate names are supplied, the extracted gated data are merged so the selected populations are displayed together on the same bivariate plot. Each population is labeled using its node name.

**Value**

A ggplot object showing the selected sample and gated populations.

**Examples**

```
# Plot one gate
p1 <- magicPlot_gs_gates(
  gs = gs,
  sample_id = "sample_01.fcs",
  gate_names = "Live_cells",
  size_points = 0.5
)

# Plot multiple gates together
p2 <- magicPlot_gs_gates(
  gs = gs,
  sample_id = "sample_01.fcs",
  gate_names = c("Live_cells", "Dead_cells"),
  type = "ML",
  size_points = 0.5
)
```

---

magicPlot\_gs\_hierarchy  
*magicPlot\_gs\_hierarchy*

---

**Description**

Plot all gates from one GatingSet sample as a hierarchy-style figure.

**Usage**

```
magicPlot_gs_hierarchy(
  gs,
  sample_id,
  n_col_wrap = 4,
  size_points = 0.5,
  size_title = NULL,
  concavity_val = 50,
  add_labels = TRUE,
```



```

    size_pol_name = NULL,
    auto_size = TRUE,
    return_plot_list = FALSE,
    path_output = NULL,
    plot_width = 4,
    plot_height = 4,
    dpi = 300,
    ...
)

```

## Arguments

|                               |                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>gs</code>               | A GatingSet object.                                                                                                                                                                                                                                                                                                                                                                                   |
| <code>sample_id</code>        | Character. Name of the sample to plot. The value must be present in <code>sampleNames(gs)</code> .                                                                                                                                                                                                                                                                                                    |
| <code>n_col_wrap</code>       | Integer. Number of columns used to arrange the wrapped hierarchy figure. Default is 4.                                                                                                                                                                                                                                                                                                                |
| <code>size_points</code>      | Numeric. Point size passed to <code>magicPlot_gs_gates()</code> and ultimately to <code>magicPlot()</code> . Default is 0.5.                                                                                                                                                                                                                                                                          |
| <code>size_title</code>       | Numeric or NULL. Size of the title for each subplot. Each subplot title indicates the parent population, for example "Parent pop: CD45+". If NULL and <code>auto_size = TRUE</code> , the value is computed automatically from the grid size. If NULL and <code>auto_size = FALSE</code> , the default value is 10.                                                                                   |
| <code>concavity_val</code>    | Numeric. Concavity value used when polygon boundaries are estimated from gated events. This value is passed to <code>magicPlot_gs_gates()</code> and then to <code>magicPlot()</code> . Larger values generally produce smoother polygon boundaries. Default is 50.                                                                                                                                   |
| <code>add_labels</code>       | Logical. If TRUE, gate names are printed inside the polygon gates. This is passed to <code>magicPlot()</code> . Labels are only shown for plotting modes that support polygon labels, such as <code>type = "dens"</code> . Default is TRUE.                                                                                                                                                           |
| <code>size_pol_name</code>    | Numeric or NULL. Size of the gate labels printed inside polygon gates. If NULL and <code>auto_size = TRUE</code> , the value is computed automatically from the grid size. If NULL and <code>auto_size = FALSE</code> , the default value is 4.                                                                                                                                                       |
| <code>auto_size</code>        | Logical. If TRUE, automatically estimates text sizes for axis tick labels, axis titles, polygon labels, and subplot titles based on the number of rows and columns in the wrapped figure. User-supplied values passed through <code>...</code> , such as <code>size_axis_text</code> , <code>size_title_x</code> , or <code>size_title_y</code> , are respected and not overwritten. Default is TRUE. |
| <code>return_plot_list</code> | Logical. If FALSE, return only the wrapped plot. If TRUE, return a list containing the wrapped plot and intermediate objects used to build it. Default is FALSE.                                                                                                                                                                                                                                      |
| <code>path_output</code>      | Character or NULL. Full file path where the wrapped hierarchy plot should be saved. If NULL, no file is exported. The file format is inferred by <code>ggplot2::ggsave()</code> from the file extension, for example <code>.tiff</code> , <code>.png</code> , or <code>.pdf</code> . Default is NULL.                                                                                                 |
| <code>plot_width</code>       | Numeric. Width, in inches, assigned to each individual subplot when exporting the full wrapped figure. The final exported width is calculated as <code>plot_width * number_of_columns</code> . Default is 4.                                                                                                                                                                                          |

|             |                                                                                                                                                                                                                  |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| plot_height | Numeric. Height, in inches, assigned to each individual subplot when exporting the full wrapped figure. The final exported height is calculated as plot_height * number_of_rows. Default is 4.                   |
| dpi         | Numeric. Resolution used when exporting raster image formats such as .png or .tiff. Default is 300.                                                                                                              |
| ...         | Additional plotting arguments passed to magicPlot_gs_gates() and then to magicPlot(). Common examples include type, size_axis_text, size_title_x, size_title_y, show_legend, x_lim1, x_lim2, y_lim1, and y_lim2. |

## Details

This function generates a wrapped figure containing one bivariate plot for each gating step in a GatingSet hierarchy. For each subplot, the title indicates the parent population and the gate labels indicate the child population or populations shown on that plot.

Gates that share the same bivariate dimensions are automatically grouped into the same subplot. For example, if NK\_cells, B\_cells, and T\_cells are sibling gates drawn on the same two channels, they are displayed together in one plot. Gates that do not share dimensions with sibling gates are plotted individually.

The hierarchy order is determined from get\_hierarchy\_all\_pops(), and the final plots are combined using patchwork::wrap\_plots().

The function uses get\_hierarchy\_all\_pops() to obtain a hierarchy table. The table is walked row by row so that plots follow the gating hierarchy order. If a child population has an empty Dimensions value, it is plotted alone. If multiple child populations share the same Dimensions value, they are grouped into the same subplot and shown together.

The plotting itself is delegated to magicPlot\_gs\_gates(). This wrapper determines which gates should appear in each subplot, then calls magicPlot\_gs\_gates() repeatedly and combines the resulting plots.

## Value

If return\_plot\_list = FALSE, a wrapped patchwork plot object. If return\_plot\_list = TRUE, a list with the following elements:

**plot** The final wrapped hierarchy plot.

**plot\_list** A named list of individual ggplot objects before wrapping.

**plot\_groups** A named list describing which gate or gates were plotted in each subplot.

**plot\_titles** A named list containing the parent population title for each subplot.

**df\_tree** The hierarchy table returned by get\_hierarchy\_all\_pops() and used to build the figure.

## Examples

```
# Plot the full hierarchy for one sample
p <- magicPlot_gs_hierarchy(
  gs = gs,
  sample_id = "sample_01.fcs",
  n_col_wrap = 3,
  type = "dens"
```

```

)

# Plot and export the hierarchy figure as a TIFF file
p <- magicPlot_gs_hierarchy(
  gs = gs,
  sample_id = "sample_01.fcs",
  n_col_wrap = 3,
  type = "dens",
  path_output = "~/main/Results/sample_01_hierarchy.tiff",
  plot_width = 4,
  plot_height = 4,
  dpi = 300
)

# Manually control text sizes instead of using automatic sizing
p <- magicPlot_gs_hierarchy(
  gs = gs,
  sample_id = "sample_01.fcs",
  n_col_wrap = 3,
  auto_size = FALSE,
  size_title = 10,
  size_pol_name = 4,
  size_axis_text = 8,
  size_title_x = 10,
  size_title_y = 10,
  type = "dens"
)

```

---

magicPlot\_gs\_node

*magicPlot\_gs\_node*


---

## Description

Plot selected channels from one GatingSet node.

## Usage

```
magicPlot_gs_node(gs_input, node_name, sample_id, channel_x, channel_y, ...)
```

## Arguments

|           |                                                                                                                                                            |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| gs_input  | A GatingSet object.                                                                                                                                        |
| node_name | Character. Name of the population node to extract, such as "root", "Singlets", or "Live_cells".                                                            |
| sample_id | Sample identifier used to select one sample from the GatingSet. This can be a sample name or an index, depending on <code>get_flowframe_from_gs()</code> . |
| channel_x | Character. Name of the channel to plot on the x-axis.                                                                                                      |
| channel_y | Character. Name of the channel to plot on the y-axis.                                                                                                      |
| ...       | Additional arguments passed to <code>magicPlot_fs()</code> .                                                                                               |

**Details**

This function extracts one sample and one population node from a GatingSet as a flowFrame, then plots two selected channels using magicPlot\_fs(). Unlike magic\_plot\_gs\_gates(), this function does not overlay multiple gate labels. It simply plots the events contained in the selected node.

**Value**

A plot object returned by magicPlot\_fs().

**Examples**

```
magicPlot_gs_node(
  gs_input = gs,
  node_name = "Live_cells",
  sample_id = "sample_01.fcs",
  channel_x = "FSC-A",
  channel_y = "LIVE DEAD Blue-A"
)
```

---

|                    |                           |
|--------------------|---------------------------|
| magicPlot_template | <i>magicPlot_template</i> |
|--------------------|---------------------------|

---

**Description**

function to interactively generate a template based on bivariate ungated data.

**Usage**

```
magicPlot_template(df, size_points = 1)
```

**Arguments**

|             |                                                                                                                           |
|-------------|---------------------------------------------------------------------------------------------------------------------------|
| df          | input dataframe composed of two columns reporting markers expression (first column = marker 1, second column = marker 2). |
| size_points | Size of points in scatter plot. Default to 1.                                                                             |

**Value**

Dataframe

**Examples**

```
magicPlot_template()
```

magicPred

*magicPred***Description**

function to predict on plain test data (no hierarchy)

**Usage**

```
magicPred(
  test_data,
  magic_model = NULL,
  magic_model_n_gates = NULL,
  ref_model_info = NULL,
  n_cores = 1,
  ref_data_train = NULL,
  prop_down = NULL,
  thr_dist = 0.05,
  n_points_per_plot = NULL,
  normalize_data = T,
  include_zero_val = T,
  ...
)
```

**Arguments**

|                                  |                                                                                                                                                                                                                      |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>test_data</code>           | Dataframe of test data to gate. It has only the two columns of marker expression.                                                                                                                                    |
| <code>magic_model</code>         | Global trained model to predict gates. It can be a single model or list of named models (each model trained on selected number of gates).                                                                            |
| <code>magic_model_n_gates</code> | Global trained model to predict number of gates. If different from <code>NULL</code> , <code>magic_model</code> is expected to be a list of models to predict certain gates (e.g., 5 models for 2,3,4,5 or 6 gates). |
| <code>ref_model_info</code>      | Template model to predic gates.                                                                                                                                                                                      |
| <code>n_cores</code>             | Number of cores to use. Default to 1.                                                                                                                                                                                |
| <code>ref_data_train</code>      | Template data used to generate <code>ref_model_info</code> . Needed to calculate target-template distance.                                                                                                           |
| <code>prop_down</code>           | Proportion for downsampling. Default to <code>NULL</code> (automatic downsampling using <code>n_points_per_plot</code> ).                                                                                            |
| <code>n_points_per_plot</code>   | Number of points to consider for downsampling. Default to 500.                                                                                                                                                       |
| <code>normalize_data</code>      | If True, data is normalized to 0-1 range. Default to True.                                                                                                                                                           |
| <code>include_zero_val</code>    | considering events labeled as 0 as an additional gate when there is only one gate. Default to True.                                                                                                                  |

**Value**

List of Dataframes.

**Examples**

```
magicPred()
```

---

|                            |                      |
|----------------------------|----------------------|
| <code>magicPred_all</code> | <i>magicPred_all</i> |
|----------------------------|----------------------|

---

**Description**

function to predict on plain test data (no hierarchy)

**Usage**

```
magicPred_all(  
  list_test_data,  
  sample_id = NULL,  
  magic_model = NULL,  
  ref_model_info = NULL,  
  magic_model_n_gates = NULL,  
  ref_data_train = NULL,  
  prop_down = NULL,  
  n_points_per_plot = NULL,  
  n_gates_df = NULL,  
  thr_dist = 0.05,  
  n_cores = 1,  
  normalize_data = T,  
  include_zero_val = T,  
  n_cores_all = 1,  
  verbose = F,  
  ...  
)
```

**Arguments**

- `list_test_data` List of unlabeled dataframes. It has only the two columns of marker expression.
- `sample_id` Id of the samples to gate. Could be a vector containing the names or numerical indices (position) of the samples to gate. If NULL, all samples in `list_test_data` are gated. Default to NULL.
- `magic_model` Global trained model to predict gates. It can be a single model or list of named models (each model trained on selected number of gates).
- `ref_model_info` Template model to predic gates.

|                     |                                                                                                                                                                                           |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| magic_model_n_gates | Global trained model to predict number of gates. If different from NULL, magic_model is expected to be a list of models to predict certain gates (e.g., 5 models for 2,3,4,5 or 6 gates). |
| ref_data_train      | Template data used to generate ref_model_info. Needed to calculate target-template distance.                                                                                              |
| n_points_per_plot   | Number of points to consider for downsampling. Default to 500. Note: the gates in the downsampled data are projected back to the original data to get the actual populations.             |
| n_gates_df          | Dataframe pairing the sample name (first column) with the user-defined number of gates (second column). Default to NULL.                                                                  |
| thr_dist            | Distance threshold for centroids calculation during post processing. Default to 0.15.                                                                                                     |
| n_cores             | Number of cores to use to process one sample. Default to 1.                                                                                                                               |
| normalize_data      | If True, data is normalized to 0-1 range. Default to True.                                                                                                                                |
| include_zero_val    | considering events labeled as 0 as an additional gate when there is only one gate. Default to True.                                                                                       |
| n_cores_all         | Number of cores to use across all samples. Default to 1.                                                                                                                                  |
| verbose             | If True, print all message and disable tryCatch (any error will stop the execution). Default to False.                                                                                    |

**Value**

List of Dataframes.

**Examples**

```
magicPred_all()
```

---

|                     |                            |
|---------------------|----------------------------|
| magicPred_hierarchy | <i>magicPred_hierarchy</i> |
|---------------------|----------------------------|

---

**Description**

function to predict the gates on the ungated .fcs samples.

**Usage**

```
magicPred_hierarchy(list_test_sets, list_models_local, df_tree, n_cores = 1)
```

**Arguments**

`list_test_sets` contains the list of root dataframe for each ungated fcs file imported.

`list_models_local` contains the optimized local models pre-generated using the `magicTrain_local` function.

`df_tree` contains the info related to the populations hierarchy.

`n_cores` Number of cores to use. Default to 1.

**Value**

List of Dataframes.

**Examples**

```
magicPred_hierarchy()
```

---

magicTrain

*magicTrain*

---

**Description**

function to generate one training model based on a list of training sets (no hierarchy).

**Usage**

```
magicTrain(
  df_train,
  n_cores = 1,
  train_model = "rf",
  k_cv = 10,
  list_index_train = NULL,
  list_index_val = NULL,
  n_tree = 10,
  tune_lenght = 3,
  size_nnet_units = 100,
  decay_nnet = 0.1,
  method_control = "auto",
  type_y = "classes",
  seed_n = 40
)
```



**Arguments**

|                  |                                                                                                                           |
|------------------|---------------------------------------------------------------------------------------------------------------------------|
| df_train         | training dataframe generated by the get_train_data function.                                                              |
| n_cores          | Number of cores to use. Default to 1.                                                                                     |
| train_model      | Type of training model. Default to rf.                                                                                    |
| k_cv             | Number of k for cross-validation (if method control=cv)                                                                   |
| list_index_train | List of vector of indices to use in training for each fold.                                                               |
| list_index_val   | List of vector of indices to use as held out data for each fold.                                                          |
| n_tree           | Number of trees for random forest.                                                                                        |
| tune_lenght      | Number of parameters values trained during cross-validation.                                                              |
| size_nnet_units  | Number of units in hidden layer (if train_model=nnet).                                                                    |
| decay_nnet       | Decay parameter value for nnet model.                                                                                     |
| method_control   | Type of training control: oob or cv or auto. Default to auto.                                                             |
| type_y           | Type of response variable: classes (train to predict gates boundaries) or n_gates_info(train to predict number of gates). |
| seed_n           | Set seed. Default to 40.                                                                                                  |

**Value**

model object.

**Examples**

```
magicTrain()
```

---

magicTrain\_dt

*magicTrain\_dt*


---

**Description**

function to generate a random forest training model.

**Usage**

```
magicTrain_dt(
  Xtrain,
  Ytrain,
  k_cv = 10,
  list_index_train = NULL,
  list_index_val = NULL,
  tune_lenght = 5
)
```

**Arguments**

|                  |                                                                  |
|------------------|------------------------------------------------------------------|
| Xtrain           | Dataframe of training features.                                  |
| Ytrain           | Dataframe of labels (one column).                                |
| k_cv             | Number of k for cross-validation.                                |
| list_index_train | List of vector of indices to use in training for each fold.      |
| list_index_val   | List of vector of indices to use as held out data for each fold. |
| tune_lenght      | Number of hyper parameters to test. Default to 5.                |

**Value**

model object.

**Examples**

```
magicTrain_dt()
```

---

magicTrain\_hierarchy    *magicTrain\_local*

---

**Description**

function to generate the local training models using the list of hierarchical training set.

**Usage**

```
magicTrain_hierarchy(  
  list_train_sets,  
  n_tree = 10,  
  train_model = "rf",  
  method_control = "oob",  
  n_cores = 1  
)
```

**Arguments**

|                 |                                                                               |
|-----------------|-------------------------------------------------------------------------------|
| list_train_sets | List of labeled dataframe to train generated by the get_local_train function. |
| n_tree          | Number of tree for random forest model.                                       |
| train_model     | Type of training model. Default to random forest ("rf").                      |
| method_control  | Cross-validation method. Default to out-of-the-bag method (oob).              |
| n_cores         | Number of cores to use. Default to 1.                                         |

**Value**

List of models objects.

**Examples**

```
magicTrain_local()
```

---

|                |                       |
|----------------|-----------------------|
| magicTrain_knn | <i>magicTrain_knn</i> |
|----------------|-----------------------|

---

**Description**

function to generate a random forest training model.

**Usage**

```
magicTrain_knn(
  Xtrain,
  Ytrain,
  k_cv = 10,
  list_index_train = NULL,
  list_index_val = NULL,
  tune_lenght = 5
)
```

**Arguments**

|                  |                                                                  |
|------------------|------------------------------------------------------------------|
| Xtrain           | Dataframe of training features.                                  |
| Ytrain           | Dataframe of labels (one column).                                |
| k_cv             | Number of k for cross-validation.                                |
| list_index_train | List of vector of indices to use in training for each fold.      |
| list_index_val   | List of vector of indices to use as held out data for each fold. |
| tune_lenght      | Number of hyper parameters to test. Default to 5.                |

**Value**

model object.

**Examples**

```
magicTrain_knn()
```

---

|               |                      |
|---------------|----------------------|
| magicTrain_nb | <i>magicTrain_nb</i> |
|---------------|----------------------|

---

## Description

function to generate a random forest training model.

## Usage

```
magicTrain_nb(  
  Xtrain,  
  Ytrain,  
  k_cv = 10,  
  list_index_train = NULL,  
  list_index_val = NULL,  
  tune_lenght = 5  
)
```

## Arguments

|                  |                                                                  |
|------------------|------------------------------------------------------------------|
| Xtrain           | Dataframe of training features.                                  |
| Ytrain           | Dataframe of labels (one column).                                |
| k_cv             | Number of k for cross-validation.                                |
| list_index_train | List of vector of indices to use in training for each fold.      |
| list_index_val   | List of vector of indices to use as held out data for each fold. |
| tune_lenght      | Number of hyper parameters to test. Default to 5.                |

## Value

model object.

## Examples

```
magicTrain_nb()
```

---

|                 |                        |
|-----------------|------------------------|
| magicTrain_nnet | <i>magicTrain_nnet</i> |
|-----------------|------------------------|

---

## Description

function to generate a neural net training model.

## Usage

```
magicTrain_nnet(  
  Xtrain,  
  Ytrain,  
  k_cv = 10,  
  list_index_train = NULL,  
  list_index_val = NULL,  
  size = 100,  
  decay = 0.1,  
  tune_lenght = 5  
)
```

## Arguments

|                  |                                                                  |
|------------------|------------------------------------------------------------------|
| Xtrain           | Dataframe of training features.                                  |
| Ytrain           | Dataframe of labels (one column).                                |
| k_cv             | Number of k for cross-validation.                                |
| list_index_train | List of vector of indices to use in training for each fold.      |
| list_index_val   | List of vector of indices to use as held out data for each fold. |
| size             | Number of units in hidden layer (if train_model=nnet).           |
| decay            | Decay parameter value for nnet model.                            |

## Value

model object.

## Examples

```
magicTrain_nnet()
```

---

|               |                      |
|---------------|----------------------|
| magicTrain_rf | <i>magicTrain_rf</i> |
|---------------|----------------------|

---

## Description

function to generate a random forest training model.

## Usage

```
magicTrain_rf(  
  Xtrain,  
  Ytrain,  
  list_index_train = NULL,  
  list_index_val = NULL,  
  n_tree = 10,  
  method_control = "oob",  
  k_cv = 10  
)
```

## Arguments

|                  |                                                                  |
|------------------|------------------------------------------------------------------|
| Xtrain           | Dataframe of training features.                                  |
| Ytrain           | Dataframe of labels (one column).                                |
| list_index_train | List of vector of indices to use in training for each fold.      |
| list_index_val   | List of vector of indices to use as held out data for each fold. |
| n_tree           | Number of trees for random forest.                               |
| method_control   | Type of training control: oob or cv. Default to oob.             |
| k_cv             | Number of k for cross-validation (if method control=cv).         |

## Value

model object.

## Examples

```
magicTrain_rf()
```

---

|                               |                         |
|-------------------------------|-------------------------|
| <code>magic_label_poly</code> | <i>magic_label_poly</i> |
|-------------------------------|-------------------------|

---

**Description**

function to label points of dataframe based on polygon coordinates

**Usage**

```
magic_label_poly(df, polygon_df, label_pol = "1")
```

**Arguments**

- |                         |                                                                                                                                     |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <code>df</code>         | Dataframe composed of two columns for marker expression of first (x axis = first column) and second marker (y axis = second column) |
| <code>polygon_df</code> | Dataframe containing the x coordinates (first column) and y coordinates (second column) of the current polygon to label.            |
| <code>label_pol</code>  | Label for current polygon.                                                                                                          |

**Value**

Dataframe

**Examples**

```
magic_label_poly()
```

---

|                                    |                              |
|------------------------------------|------------------------------|
| <code>magic_label_rectangle</code> | <i>magic_label_rectangle</i> |
|------------------------------------|------------------------------|

---

**Description**

function to label points of dataframe based on rectangle coordinates

**Usage**

```
magic_label_rectangle(df, x_min, x_max, y_min, y_max, label_pol = "1")
```

**Arguments**

- |                        |                                                                                                                                     |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| <code>df</code>        | Dataframe composed of two columns for marker expression of first (x axis = first column) and second marker (y axis = second column) |
| <code>x_min</code>     | x coordinate minimum                                                                                                                |
| <code>x_max</code>     | x coordinate maximum                                                                                                                |
| <code>y_min</code>     | y coordinate minimum                                                                                                                |
| <code>y_max</code>     | y coordinate maximum                                                                                                                |
| <code>label_pol</code> | Label for current polygon.                                                                                                          |

**Value**

Dataframe

**Examples**

```
magic_label_rectangle()
```

---

```
magic_manual_gating    magic_manual_gating
```

---

**Description**

Perform interactive manual gating on selected samples and add or update the resulting polygon gate in a GatingSet.

**Usage**

```
magic_manual_gating(
  gs_input,
  parent_node,
  new_child_node,
  samples_id,
  channel_x,
  channel_y,
  size_points = 0.5,
  return_list_out = F,
  input_list_out = NULL,
  return_gs_only = T,
  ...
)
```

**Arguments**

|                              |                                                                                                                             |
|------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| <code>gs_input</code>        | A GatingSet object.                                                                                                         |
| <code>parent_node</code>     | Character. Name of the parent node where the new gate should be added or updated.                                           |
| <code>new_child_node</code>  | Character. Name of the child node to create or update.                                                                      |
| <code>samples_id</code>      | Character vector. Sample names to manually gate. These names must match <code>sampleNames(gs_input)</code> .                |
| <code>channel_x</code>       | Character. Name of the channel to plot on the x-axis.                                                                       |
| <code>channel_y</code>       | Character. Name of the channel to plot on the y-axis.                                                                       |
| <code>size_points</code>     | Numeric. Point size used in the interactive gating plot. Default is 0.5.                                                    |
| <code>return_list_out</code> | Logical. If TRUE, return only the output from <code>magicGating()</code> without modifying the GatingSet. Default is FALSE. |



- `input_list_out` Optional list. Existing output from `magicGating()` containing a `list_poly_gates` slot. If provided, interactive gating is skipped and these polygon gates are added or updated in the `GatingSet`.
- `return_gs_only` Logical. If `TRUE`, return only the modified `GatingSet`. If `FALSE`, return a list containing the modified `GatingSet` and the gating output. Default is `TRUE`.
- `...` Additional arguments passed to `magicGating()`.

**Details**

This function wraps `magicGating()` for one manual polygon gate and integrates the resulting `polygonGate` into a `GatingSet`. If the target child node does not already exist, it is created under `parent_node`. If the node already exists, the gate is updated only for the samples present in the gating output.

**Value**

If `return_gs_only = TRUE`, a modified `GatingSet`. Otherwise, a list with two elements: `gs`, the modified `GatingSet`, and `list_out`, the gating output used to add or update the gate.

**Examples**

```
gs <- magic_manual_gating(  
  gs_input = gs,  
  parent_node = "root",  
  new_child_node = "Live_cells",  
  samples_id = c("sample_01.fcs"),  
  channel_x = "FSC-A",  
  channel_y = "LIVE DEAD Blue-A"  
)
```

---

|                              |                        |
|------------------------------|------------------------|
| <code>magic_plot_wrap</code> | <i>magic_plot_wrap</i> |
|------------------------------|------------------------|

---

**Description**

function to wrap all plots in one plot

**Usage**

```
magic_plot_wrap(list_gated_data, n_col_wrap = 3, size_title = 10, ...)
```

**Arguments**

- `list_gated_data` List of dataframes composed by three columns (could be generated by the `get_list_df_gated_plots()` function)
- `n_col_wrap` number of columns in the wrapped plot. Default to 3.
- `size_title` size of title of each plot. Default to 10.

**Value**

wrapped plot

**Examples**

```
magic_plot_wrap()
```

---

|                               |
|-------------------------------|
| magic_template_predict        |
| <i>magic_template_predict</i> |

---

**Description**

Predict gated populations from a trained flowMagic template model and optionally add the predicted gates to a GatingSet.

**Usage**

```
magic_template_predict(  
  gs_input,  
  parent_node,  
  channel_x,  
  channel_y,  
  ref_train,  
  ref_model_info,  
  label_to_node,  
  n_cores = 1,  
  concavity_val = 50,  
  add_to_gs = TRUE,  
  return_gs_only = FALSE,  
  ...  
)
```

**Arguments**

|                |                                                                                                                                                                     |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| gs_input       | A GatingSet object.                                                                                                                                                 |
| parent_node    | Character. Name of the parent node from which raw data are exported and under which predicted gates are added.                                                      |
| channel_x      | Character. Name of the channel to use on the x-axis.                                                                                                                |
| channel_y      | Character. Name of the channel to use on the y-axis.                                                                                                                |
| ref_train      | Data frame. Training data generated by <code>get_train_data()</code> , typically <code>train_out\$ref_train</code> from <code>magic_template_train()</code> .       |
| ref_model_info | List. Trained model information returned by <code>magicTrain()</code> , typically <code>train_out\$ref_model_info</code> from <code>magic_template_train()</code> . |

|                |                                                                                                                                                                                 |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| label_to_node  | Named character vector. Names are predicted labels and values are the corresponding GatingSet node names. For example, <code>c("1" = "Live_cells", "2" = "Dead_cells")</code> . |
| n_cores        | Integer. Number of cores used for prediction and polygon extraction. Default is 1.                                                                                              |
| concavity_val  | Numeric. Concavity parameter passed to <code>flowmagic_pred_to_poly_gates()</code> . Higher values generally produce smoother polygon gates. Default is 50.                     |
| add_to_gs      | Logical. If TRUE, convert predicted labels to polygon gates and add or update them in the GatingSet. If FALSE, only prediction results are returned. Default is TRUE.           |
| return_gs_only | Logical. If TRUE, return only the modified GatingSet. Default is FALSE.                                                                                                         |
| ...            | Additional arguments passed to <code>export_raw_gs_plots()</code> .                                                                                                             |

## Details

This function exports bivariate expression data from a selected GatingSet node, predicts event labels using a previously trained flowMagic model, converts selected predicted labels into polygon gates, and optionally adds or updates these gates in the input GatingSet.

The `label_to_node` argument controls how predicted labels are mapped to GatingSet node names. For example, `c("1" = "Live_cells", "2" = "Dead_cells")` converts predicted label "1" into a node named "Live\_cells" and predicted label "2" into a node named "Dead\_cells".

## Value

If `return_gs_only = TRUE`, a modified GatingSet. Otherwise, a list with four elements: `gs`, the modified or original GatingSet; `list_test_data`, the exported test data; `list_dfs_pred`, the predicted labeled data frames; and `list_poly_gates`, the polygon gates generated for each requested node.

## Examples

```
pred_out <- magic_template_predict(
  gs_input = gs,
  parent_node = "root",
  channel_x = "FSC-A",
  channel_y = "LIVE DEAD Blue-A",
  ref_train = train_out$ref_train,
  ref_model_info = train_out$ref_model_info,
  label_to_node = c("1" = "Live_cells", "2" = "Dead_cells"),
  n_cores = 1,
  add_to_gs = TRUE
)

gs <- pred_out$gs
```

---

magic\_template\_train    *magic\_template\_train*

---

## Description

Build a template training set from manually gated samples and train a flowMagic classification model.

## Usage

```
magic_template_train(
  gs_input,
  parent_node,
  samples_id,
  channel_x,
  channel_y,
  size_points = 0.5,
  n_gates = 1,
  input_list_out_final = NULL,
  train_model = "rf",
  ...
)
```

## Arguments

|                      |                                                                                                                                                                                                                                             |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| gs_input             | A GatingSet object.                                                                                                                                                                                                                         |
| parent_node          | Character. Name of the parent node from which expression data are extracted for template gating.                                                                                                                                            |
| samples_id           | Character vector. Sample names to manually gate as template samples.                                                                                                                                                                        |
| channel_x            | Character. Name of the channel to plot on the x-axis.                                                                                                                                                                                       |
| channel_y            | Character. Name of the channel to plot on the y-axis.                                                                                                                                                                                       |
| size_points          | Numeric. Point size used in the interactive gating plot. Default is 0.5.                                                                                                                                                                    |
| n_gates              | Integer. Number of template gates to draw per selected sample. Each gate is assigned a label from 1 to n_gates. Default is 1.                                                                                                               |
| input_list_out_final | Optional list. Existing template data object, usually from a previous call to magic_template_train()\$list_out_final. If supplied, newly gated templates are added to this existing template set. Samples with matching names are replaced. |
| train_model          | Character. Model type passed to magicTrain(). Default is "rf".                                                                                                                                                                              |
| ...                  | Additional arguments passed to magicGating().                                                                                                                                                                                               |

## Details

This function performs one or more rounds of interactive manual gating on selected samples. Each gate is assigned a different label. If more than one gate is drawn, the labeled outputs are merged into a single template data object. The resulting templates are converted into training data using `get_train_data()` and used to train a model with `magicTrain()`.

Existing template data can be supplied through `input_list_out_final`, allowing users to add new manually gated templates without redrawing previous ones.

## Value

A list with five elements: `ref_model_info`, the trained model information returned by `magicTrain()`; `ref_train`, the training data returned by `get_train_data()`; `list_out_final`, the complete merged template set; `list_out_new`, the newly generated template data; and `all_list_out_obj`, the raw outputs from each call to `magicGating()`.

## Examples

```
train_out <- magic_template_train(
  gs_input = gs,
  parent_node = "root",
  samples_id = c("sample_01.fcs", "sample_02.fcs"),
  channel_x = "FSC-A",
  channel_y = "LIVE DEAD Blue-A",
  n_gates = 2,
  train_model = "rf"
)

# Add additional template samples later
train_out2 <- magic_template_train(
  gs_input = gs,
  parent_node = "root",
  samples_id = c("sample_03.fcs"),
  channel_x = "FSC-A",
  channel_y = "LIVE DEAD Blue-A",
  n_gates = 2,
  input_list_out_final = train_out$list_out_final
)
```

---

map\_to\_parent

map\_to\_parent

---

## Description

function to get binary dataset with gate assignation based on the mother population of the selected pop (instead of the root).

Usage

```
map_to_parent(gh, binary_df)
```

Arguments

- gh                    GatingHierarchy.
- binary\_df            Dataframe generated by the map\_to\_root function.

Value

Dataframe.

Examples

```
map_to_parent()
```

---

|             |                    |
|-------------|--------------------|
| map_to_root | <i>map_to_root</i> |
|-------------|--------------------|

---

Description

it generates a dataset indicating what cells belong to the selected pop (1) 0 otherwise. Old name: pre\_process\_manual\_binary() The dataset is always the dataset of the Root pop. gh and pop are mandatory arguments, dim and mode have a default value.

Usage

```
map_to_root(gh, pop)
```

Arguments

- gh                    GatingHierarchy.
- pop                   Name of the population to get events assignments.

Value

Dataframe.

Examples

```
map_to_root()
```

---

```
merge_magicGating_labels
      merge_magicGating_labels
```

---

**Description**

function to merge list of gated data when gating multiple gates.

**Usage**

```
merge_magicGating_labels(list_out_1, list_out_2, gated_data_only = F)
```

**Arguments**

`list_out_1`      List of Dataframes to update.  
`list_out_2`      List of Dataframes to merge with `list_out_1` dataframes.  
`gated_data_only`      Input contains only gated data,not polygons.Default to False.

**Value**

list of Dataframes

**Examples**

```
merge_magicGating_labels()
```

---

```
name_pop_gating      name_pop_gating
```

---

**Description**

function to get the name of all the pops of the gating hierarchy.

**Usage**

```
name_pop_gating(gh)
```

**Arguments**

`gh`      GatingHierarchy.

**Value**

Vector of characters.

**Examples**

```
name_pop_gating()
```

---

|                    |                           |
|--------------------|---------------------------|
| post_process_gates | <i>post_process_gates</i> |
|--------------------|---------------------------|

---

**Description**

function to post process the events after model prediction.

**Usage**

```
post_process_gates(
  gated_df,
  n_cores = 1,
  thr_dist = 0.15,
  include_zero = F,
  remove_centroids = T,
  type = "dist",
  concavity_val = 5,
  normalize_data = T,
  ...
)
```

**Arguments**

|                               |                                                                            |
|-------------------------------|----------------------------------------------------------------------------|
| <code>gated_df</code>         | dataframe with labels (third column).                                      |
| <code>n_cores</code>          | Number of cores. Default to 1.                                             |
| <code>thr_dist</code>         | Distance threshold for centroids calculation. Default to 0.15.             |
| <code>include_zero</code>     | Consider centroid of label 0. Default to False.                            |
| <code>remove_centroids</code> | Remove centroids too near each other based on <code>thr_dist</code> value. |
| <code>type</code>             | Type of post-processing.                                                   |
| <code>concavity_val</code>    | Concavity of polygons for the "polygon" type of post-processing            |

**Value**

Dataframe.

**Examples**

```
post_process_gates()
```



---

|                   |                          |
|-------------------|--------------------------|
| process_test_data | <i>process_test_data</i> |
|-------------------|--------------------------|

---

**Description**

function to get test data correctly formatted.

**Usage**

```
process_test_data(  
  test_data,  
  prop_down = NULL,  
  n_points_per_plot = 500,  
  normalize_data = T  
)
```

**Arguments**

- test\_data           Dataframe of bivariate markers expression.
- prop\_down           Proportion of events (downsampling). Default to NULL (downsampling using number of points).
- n\_points\_per\_plot   Number of points for downsampling.
- normalize\_data   If True, data is normalized to 0-1 range. Default to True.

**Value**

Dataframe.

**Examples**

```
process_test_data()
```

---

|         |                |
|---------|----------------|
| range01 | <i>range01</i> |
|---------|----------------|

---

**Description**

function to put data in range 0-1.

**Usage**

```
range01(x)
```

**Arguments**

x                      Vector of numbers to scale.

**Value**

Vector of numbers.

**Examples**

range01()

---

|             |                    |
|-------------|--------------------|
| smooth_hull | <i>smooth_hull</i> |
|-------------|--------------------|

---

**Description**

function to smooth concave polygons

**Usage**

smooth\_hull(hull\_df, spar = 0.7)

**Arguments**

|             |                                                                                     |
|-------------|-------------------------------------------------------------------------------------|
| hull_df     | Dataframe generate by concaveman functions inside get_huget_hull_all_gates function |
| spar        | Spar value to regulate smoothing process: higher value (max 1) higher smoothing.    |
| buffer_dist | Regulate buffer distance before smoothing. Default to 500.                          |

**Value**

Dataframe.

**Examples**

smooth\_hull()

---

```
update_label_association  
    update_label_association
```

---

**Description**

function to update label association.

**Usage**

```
update_label_association(df)
```

**Arguments**

df                      Dataframe.

**Value**

Vector.

**Examples**

```
update_label_association()
```

# Index

- \* **GatingHierarchy**
  - get\_flowframe\_from\_gs, 16
- \* **GatingSet**
  - get\_flowframe\_from\_gs, 16
  - magic\_template\_predict, 50
  - magicPlot\_gs\_gates, 31
  - magicPlot\_gs\_hierarchy, 32
  - magicPlot\_gs\_node, 35
- \* **automated**
  - magic\_template\_predict, 50
- \* **flowFrame**
  - get\_flowframe\_from\_gs, 16
- \* **flowMagic**
  - add\_labels\_column, 3
  - assign\_events\_to\_nearest\_centroids, 4
  - check\_polygons\_intersection, 5
  - compute\_gates, 5
  - convert\_to\_integers\_chr, 6
  - csv\_to\_dens, 6
  - export\_raw\_gs\_plots, 8
  - exports\_plots, 7
  - extract\_polygon\_gates, 9
  - flowmagic\_pred\_to\_gs, 10
  - flowmagic\_pred\_to\_poly\_gates, 10
  - get\_centroids, 12
  - get\_classes\_expr\_df, 13
  - get\_density\_features, 14
  - get\_density\_scores, 14
  - get\_dist\_template, 15
  - get\_distance\_loc\_vs\_test, 15
  - get\_flowframe\_from\_gs, 16
  - get\_hierarchy\_all\_pops, 18
  - get\_hull\_all\_gates, 18
  - get\_indices\_cross\_val, 19
  - get\_list\_df\_gated\_plots, 20
  - get\_local\_train\_sets, 20
  - get\_pop\_multiclass, 22
  - get\_pops\_hierarchy\_list, 21
  - get\_slot\_hierarchy\_list, 22
  - get\_test\_sets, 23
  - get\_train\_data, 23
  - get\_weights\_density\_features, 24
  - import\_gating\_info, 25
  - import\_reference\_csv, 25
  - import\_test\_set\_csv, 26
  - import\_test\_set\_fcs, 26
  - magic\_label\_poly, 47
  - magic\_label\_rectangle, 47
  - magic\_manual\_gating, 48
  - magic\_plot\_wrap, 49
  - magic\_template\_predict, 50
  - magic\_template\_train, 52
  - magicGating, 27
  - magicPlot, 28
  - magicplot\_3D, 29
  - magicPlot\_fs, 30
  - magicPlot\_gs\_gates, 31
  - magicPlot\_gs\_hierarchy, 32
  - magicPlot\_gs\_node, 35
  - magicPlot\_template, 36
  - magicPred, 37
  - magicPred\_all, 38
  - magicPred\_hierarchy, 39
  - magicTrain, 40
  - magicTrain\_dt, 41
  - magicTrain\_hierarchy, 42
  - magicTrain\_knn, 43
  - magicTrain\_nb, 44
  - magicTrain\_nnet, 45
  - magicTrain\_rf, 46
  - map\_to\_parent, 53
  - map\_to\_root, 54
  - merge\_magicGating\_labels, 55
  - name\_pop\_gating, 55
  - post\_process\_gates, 56
  - process\_test\_data, 57
  - range01, 57

- smooth\_hull, 58
- update\_label\_association, 59
- \* **gating**
  - magic\_template\_predict, 50
  - magic\_template\_train, 52
- \* **hierarchy**
  - magicPlot\_gs\_hierarchy, 32
- \* **machine-learning**
  - magic\_template\_train, 52
- \* **plotting**
  - magicPlot\_gs\_gates, 31
  - magicPlot\_gs\_hierarchy, 32
  - magicPlot\_gs\_node, 35
- \* **prediction**
  - magic\_template\_predict, 50
- \* **template**
  - magic\_template\_predict, 50
  - magic\_template\_train, 52
- \* **training**
  - magic\_template\_train, 52
- add\_labels\_column, 3
- assign\_events\_to\_nearest\_centroids, 4
- check\_polygons\_intersection, 5
- compute\_gates, 5
- convert\_to\_integers\_chr, 6
- csv\_to\_dens, 6
- export\_raw\_gs\_plots, 8
- exports\_plots, 7
- extract\_polygon\_gates, 9
- flowmagic\_pred\_to\_gs, 10
- flowmagic\_pred\_to\_poly\_gates, 10
- format\_channel\_info, 11
- get\_centroids, 12
- get\_classes\_expr\_df, 13
- get\_density\_features, 14
- get\_density\_scores, 14
- get\_dist\_template, 15
- get\_distance\_loc\_vs\_test, 15
- get\_flowframe\_from\_gs, 16
- get\_gate\_channels, 17
- get\_hierarchy\_all\_pops, 18
- get\_hull\_all\_gates, 18
- get\_indices\_cross\_val, 19
- get\_list\_df\_gated\_plots, 20
- get\_local\_train\_sets, 20
- get\_pop\_multiclass, 22
- get\_pops\_hierarchy\_list, 21
- get\_slot\_hierarchy\_list, 22
- get\_test\_sets, 23
- get\_train\_data, 23
- get\_weights\_density\_features, 24
- import\_gating\_info, 25
- import\_reference\_csv, 25
- import\_test\_set\_csv, 26
- import\_test\_set\_fcs, 26
- magic\_label\_poly, 47
- magic\_label\_rectangle, 47
- magic\_manual\_gating, 48
- magic\_plot\_wrap, 49
- magic\_template\_predict, 50
- magic\_template\_train, 52
- magicGating, 27
- magicPlot, 28
- magicplot\_3D, 29
- magicPlot\_fs, 30
- magicPlot\_gs\_gates, 31
- magicPlot\_gs\_hierarchy, 32
- magicPlot\_gs\_node, 35
- magicPlot\_template, 36
- magicPred, 37
- magicPred\_all, 38
- magicPred\_hierarchy, 39
- magicTrain, 40
- magicTrain\_dt, 41
- magicTrain\_hierarchy, 42
- magicTrain\_knn, 43
- magicTrain\_nb, 44
- magicTrain\_nnet, 45
- magicTrain\_rf, 46
- map\_to\_parent, 53
- map\_to\_root, 54
- merge\_magicGating\_labels, 55
- name\_pop\_gating, 55
- post\_process\_gates, 56
- process\_test\_data, 57
- range01, 57
- smooth\_hull, 58
- update\_label\_association, 59