### **BATTERY**

# SMILE-G3-BAT-10.1P



| Model                               | SMILE-G3-BAT-10.1P   | SMILE-G3-BAT-10.1P II | SMILE-G3-BAT-10.1PIII | SMILE-G3-BAT-10.1PIV | SMILE-G3-BAT-10.1PV | SMILE-G3-BAT-10.1PVI |  |
|-------------------------------------|--|-----------------------|-----------------------|----------------------|---------------------|----------------------|--|
| Physical                            |  |                       |                       |                      |                     |                      |  |
| Battery Type                        | ttery Type LFP (LiFePO4)   |                       |                       |                      |                     |                      |  |
| Weight                              | 90 kg  |                       |                       |                      |                     |                      |  |
| Dimension(W x D x H)                | 610 x 212 x 793 mm   |                       |                       |                      |                     |                      |  |
| IP Protection                       | IP65 (Outdoor)   |                       |                       |                      |                     |                      |  |
| Warranty                            | 10 Year Battery Product and Performance Warranty                             |                       |                       |                      |                     |                      |  |
| Electrical                          |  |                       |                       |                      |                     |                      |  |
| Depth of Discharge (DoD)            | 95%  |                       |                       |                      |                     |                      |  |
| Nominal Voltage                     | 96 V   |                       |                       |                      |                     |                      |  |
| Operating Voltage Range             | 90 ~ 108 V   |                       |                       |                      |                     |                      |  |
| Cycle Life                          | 10 000*  |                       |                       |                      |                     |                      |  |
| Operation                           |  |                       |                       |                      |                     |                      |  |
| Rated. Charging/DisCharging Current |  | 52.5 A                |                       |                      |                     |                      |  |
| Rated DC Power                      | 5.04 kW  |                       |                       |                      |                     |                      |  |
| Max. Charging/DisCharging Current   |  | 60 A                  |                       |                      |                     |                      |  |
| Operating Temperature Range         |  | -10 °C ~ 50 °C**      |                       |                      |                     |                      |  |
| Relative Humidity                   | 0 ~ 95% (No Condensation)  |                       |                       |                      |                     |                      |  |
| BMS                                 |  |                       |                       |                      |                     |                      |  |
| Modules Connection                  | 1 ~ 6 in Parallel  |                       |                       |                      |                     |                      |  |
| <b>Energy Capacity</b>              | 10.1kWh  | 20.2 kWh              | 30.2 kWh              | 40.3 kWh             | 50.4 kWh            | 60.5 kWh             |  |
| Usable Capacity                     | 9.6 kWh  | 19.2 kWh              | 28.7 kWh              | 38.3 kWh             | 47.9 kWh            | 57.5 kWh             |  |
| Monitoring Parameters               | System Voltage, Current, Cell Voltage,<br>Cell Temperature, PCBA Temperature |                       |                       |                      |                     |                      |  |
| Communication                       | CAN  |                       |                       |                      |                     |                      |  |
| Certification                       |  |                       |                       |                      |                     |                      |  |
| Transportation                      |  |                       | UN38.3                |                      |                     |                      |  |
| Safety                              | IEC 62619 , IEC 63056 , IEC 62040  |                       |                       |                      |                     |                      |  |
| Country of Manufacture              | China  |                       |                       |                      |                     |                      |  |

\*Under specific test conditions.



- \*\* +86 513 8060 6891 \*\* info@alpha-ess.com
- ← www.alphaess.com

   ☐ Jiuhua Road 888, Nantong High-Tech Industrial Development Zone, Nantong,
   Jiangsu Province, China

- ★ +86 512 6828 7609★ info@alpha-ess.com
- www.alphaess.com
  Building 10-A, Canal Town Industrial Park,
  99 Taihu E Rd, Wuzhong District, Suzhou,
  Jiangsu Province, China

- **1 +49 610 3459 1601**
- Hessen D-63225 Germany

- **a** +61 02 9000 7676

- **\*\*** +39 339 462 4288
- ⊯ www.alphaess.com
   Wia Don Minzoni, 17, Calenzano
   Firenze 50041 Italy

info@alpha-ess.com
 2F, 19-4, Nohyeong 11-gil,
 Jeju-si,Jeju-do, Republic of Korea

## 1 408 368 7828 2 usa@alpha-ess.com 4 Unit 5 2180 S Ivanhoe St,

<sup>\*\*</sup> Max. charge / discharge current derating may occur with changes in temperature and SOC.