

CONTACTS AND LOCATIONS

Contacts and Locations



Lesson objectives

By the end of this lesson, you will be able to:


- Describe contacts and contact roles
- Configure contact roles
- Describe and configure locations



Contacts and contact roles


Contacts

- A contact is a person or a company
- A contact may need to be contacted for policy information
- Contacts can be:
 - Created on account and reused on policy
 - Created on policy



Contacts and Contact Roles


- Account File Contacts page lists all contacts on an account
- Policy may have some or all of the Account contacts
- Some contact information is shared across PolicyPeriods and some is PolicyPeriod specific
- Contacts are identified by the role they fill
 - One contact can fill multiple roles on the account and policy



Configuring contact role

Contact roles for Accounts and Policies

Primary subtypes



Contact role behavior patterns in PolicyCenter


- Normal
 - Array of contacts connected to an entity (additionalNamedInsured)
- Singleton
 - One and only one contact connected to an entity (BillingContact)
- Simple Details
 - One contact with array of details (AdditionalInsured)
- Join Details
 - Details join contact to another entity (Driver)

Policy contact roles in default configuration

Policy Contact Role	Data Model Pattern	Attached to
Named Insured	Normal	Policy Period
Primary Named Insured	Singleton	Policy Period
Secondary Named Insured	Singleton	Policy Period
Location Named Insured	Join Details	Policy Period
Additional Insured	Simple Details	Policy Line
Billing Contact	Singleton	Policy Period
Driver	Join Details	PA Line
Additional Interest	Join Details	Policy Period
Owner Officer	Normal	WC Line
Labor Client	Simple Details	WC Line
Labor Contractor	Simple Details	WC Line

Example policy contact role pattern

Additional Insured contact follows a *Simple Details* pattern



The screenshot shows a web form titled "Additional Insureds". At the top, there are two buttons: "Add" (green) and "Remove" (grey). Below these is a table with two columns: "Name" and "Type". The "Name" column contains three entries, all of which are "EverReady Rentals". The "Type" column contains three entries: "Controlling Interest", "Townhouse Associations", and "Managers or Lessors of Premises". Each row has a small square checkbox to the left of the "Name" column.

<input type="checkbox"/>	Name	Type*
<input type="checkbox"/>	EverReady Rentals	Controlling Interest
<input type="checkbox"/>	EverReady Rentals	Townhouse Associations
<input type="checkbox"/>	EverReady Rentals	Managers or Lessors of Premises

Contact has multiple types of *AdditionalInsured* roles

Contact configuration plugin

- Implements `IContactConfigPlugin`
 - Example: **ContactConfigPlugin**, **WC7ContactConfigPlugin**
 - Registered in `config/plugin/registry/IContactConfigPlugin`
- Configures the Contact entity
 - Maps `PolicyContactRole` to `AccountContactRole`
 - Controls contact subtypes allowed for each role
 - Disables roles by setting first argument to false
- Syntax:
 - `new ContactConfig(enable, { contactType }, AccountContactRole , { PolicyContactRole1, PolicyContactRole2, ... })`

Extending the contact role data model


- Contact role entities that are extendable include:
 - PolicyContactRole and AccountContactRole
 - All other roles in the default configuration
- You can define roles for:
 - Person or
 - Company or
 - Both
- Roles can be disabled when not needed

Strategy to configure a new contact role

- For a contact role that does not exist in base application:
 - Add a new contact role and
 - Configure it to follow the implementation of an existing contact role
- Compare desired behavior of contact to roles in base application and find role with most similar behavior:
 - How many of them can be created?
 - How the match attaches to other roles or objects?

Adding new contact role


- New contact roles can be configured by defining new subtypes of PolicyContactRole and AccountContactRole
- Steps to extend these entities:
 1. Add extension file (*_Ext.eti) that defines the new subtype
 2. Modify the registered Contact Config Plugin file to map new subtypes to each other
 3. Add display keys as needed
 4. Create entity name for new contact role
 5. Reference display name as needed
 6. Modify PCFs and Gosu classes as needed
 7. Restart server to load new entities and entity names



Location overview

Locations

- A **location** is a physical location which may be referenced on a policy
- Locations can be:
 - Created on account and reused on policy
 - Created on policy



Location numbering

- System assigns each location a sequential number
 - AccountLocation and PolicyLocation are numbered separately
 - Stored in LocationNum field
- LocationNum can be configured based on how a carrier wants to number and renumber locations within policies

AccountLocation

LocationNum
1, 2, 3, 4, 5



PolicyLocation



01/01/18 Submission
with account
LocationNum 1, 3, 5

Locations renumbered
LocationNum 1, 2, 3




Configuring locations




LOB specific location types

- Subtypes of *PolicyLine* entity have associated location type
- LOB location types have foreign key *Location*, that points to *PolicyLocation*



Creating a new account location

To add a new AccountLocation to the account, call the **newLocation()** method on account



```
AccountBaseEnhancement.gsx x
176 static function createAccountForContact(contact : Contact) : Account {
177     var account = new Account(contact.Bundle)
178     account.changeAccountHolderTo(contact)
179     if (contact.PrimaryAddress != null) {
180         account.createPrimaryLocationFromMainContact()
181     } ...
209 function createPrimaryLocationFromMainContact() : AccountLocation {
210     if (this.PrimaryLocation != null) {
211         return this.PrimaryLocation
212     }
213
214     var accountLocation = this.newLocation()
215     copyPrimaryAddressInformationToAccountLocation(accountLocation)
216     this.PrimaryLocation = accountLocation
217     return accountLocation
218 }
```

Creating a new policy location


- Add a new PolicyLocation using newLocation method on PolicyPeriod

- **newLocation()** or

- **newLocation(acctLoc : AccountLocation)**

where:

acctLoc - existing AccountLocation to which the new policy location is associated with



```
96 var policyLoc = policyLocs.first()
97
98 // Create a new PolicyLocation if necessary
99 if (policyLoc == null && acctLoc != null) {
100     policyLoc = this.PolicyPeriod.newLocation(acctLoc)
101     for (var tc in policyLoc.TerritoryCodes)
102         tc.fillWithFirst()
103 }
```

Lesson objectives review

You are now able to:

- Describe contacts and contact roles
- Configure contact roles
- Describe and configure locations



This presentation contains information that may be privileged or confidential and is the property of the Capgemini Group.

Copyright © 2022 Capgemini. All rights reserved.

